

x-project: a document-oriented toolkit to design and implement Web Applications based on HTML5 Web Components

Andrea D'Amelio
Università Roma Tre
Dipartimento di Ingegneria
Università Roma Tre
Rome, Italy
damelio@ing.uniroma3.it

Tiziano Sperati
Università Roma Tre
Dipartimento di Ingegneria
Università Roma Tre
Rome, Italy
sperati@ing.uniroma3.it

Enrico Marino
Università Roma Tre
Dipartimento di Ingegneria
Università Roma Tre
Rome, Italy
marino@ing.uniroma3.it

Federico Spini
Università Roma Tre
Dipartimento di Ingegneria
Università Roma Tre
Rome, Italy
spini@ing.uniroma3.it

ABSTRACT

In this paper a software toolkit named **x-project** is introduced. It consists of a Web Component library which applied over a very powerful web framework, i.e. Loopback by Strongloop, realize an ibrid prototypal tool which bring together the customizability of a modern web framework with the ease of use of traditional CMSs.

Furthermore, the introduction of this tool implicitly defines a document-driven development process that extremize the concept of the reuse of code whose complessive readability, maintainability and extendibility result dramatically increased.

CCS Concepts

•Information systems → Web applications; •Applied computing → Cartography; Format and notation; •Computer systems organization → Client-server architectures; Real-time system architecture;

1. INTRODUCTION

Since the beginning of Internet, the ability to create and publish content on the web has made the success of Content Management Systems. Products like Joomla! or WordPress, born to handle simple website or blogs, are evolved to support web applications of any sort (e.g. personal portfolio, on-line newspaper, on-line shopping), running as of January 2015 more than 25% of the top ten million websites [13]. This evolution has been allowed by a plugin-based architec-

ture, where each plugin is responsible to handle a functional subset of the whole application, presenting the user whit a simple accessible configuration interface.

The large number of available plugins covers most of the common and frequently required customizations, thus avoiding to write ad-hoc code. Nevertheless, the implmentation of specific functional characteristics inevitably require to intervene at code level.

Where the effort required to add custom features to a CMS results too expensive, a web framework can be adopted instead. A web framework consists of a set of software facilities that aims to alleviate the overhead associate with common development activities. Web application coding effort, while eased by the web framework, is anyway rewarded by an increased level of extensibility and customizability of the produced application.

The most desirable features for a wab framework are: a) user management, b) session management, c) automatic generation of CRUD methods on data models exposed via HTTP RESTfull APIs, d) data access policies management. In order to effectively speed up web applications development, these facilities should be provided mostly reling on external configuration files and less on procedural code [3].

In this paper a software toolkit named **x-project** is introduced. It consists of a Web Component library which applied over a very powerful web framework, i.e. Loopback by Strongloop, realize an ibrid prototypal tool which bring together the customizability of a modern web framework with the ease of use of traditional CMSs.

Furthermore, the introduction of this tool implicitly defines a document-driven development process that extremize the concept of the reuse of code whose complessive readability, maintainability and extendibility result dramatically increased.

The remainder of this document is organized as follows. Section 3 is devoted to describe the architecture and the tecnology stack exposed by applications developed with the toolkit, while section 4 presents the toolkit itself. Section 5 reports about a case-study application: it is shown how to

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

DocEng2015 Sep 8–11, 2015, Lausanne, Switzerland

© 2015 ACM. ISBN 123-4567-24-567/08/06...\$15.00

DOI: 10.475/123_4

build a CMS by mean of the toolkit introduced in this paper. Finally section 2 outlines the development process implicitly defined by the introduction of the **x-project** toolkit.

2. ARCHITECTURE

Web applications developed exploiting **x-project** toolkit are full stack *JavaScript*.

On the server-side they rely on *Node.js*, exploiting the power of the *Loopback* framework by *Strongloop*. As mention above, the aim is to have a development process entirely document-driven, and those documents are the schemas of the models used by the application. These are JSON documents. Each document represents a model and presents the following fields: the **name** of the model, the set of **properties**, the list of **relations** to others models and the list of **ACL** (Access Control Layer) rules.

Loopback generates model's API from the models schemas, to let CRUD operations on models.

The API can be extended: the developer can add remote functions to models or add hooks to existing APIs to add behaviour before and/or after the API handler (to preprocess the request and/or postprocess the response).

The resulting API is RESTful, cookie free, signed by authentication token.

By default, applications have a built-in model that represent a user, with properties **username**, **email** and **password** for login and the property **role** used by the ACL module.

A very remarkable feature exposed by *Loopback* is that it abstracts from the particular DBMS utilized by the mean of an indirection layer, allowing to choose the preferred one, be it a noSQL or a graph-based one.

On the client-side, developed applications happen to be SPA (single page application) which exploit a variety of technologies, briefly described below.

Web Components are a collection of standards which are working their way through the W3C and landing in browsers at the moment. They allow to bundle markup and styles into custom HTML elements. *Custom Elements*[8], *HTML Imports*[9], *HTML Templates*[10], *Shadow DOM*[11]. Since these specifications are currently W3C Working Draft, they aren't fully supported across all major browsers, so As these technologies are implemented in browsers, the polyfills will shrink to gain the benefits of native implementations. [7]

Polymer library (<https://www.polymer-project.org/>) provides a thin layer of API on top of web components (native implementations and their polyfills) and several powerful features, such as custom events and delegation, mixins, accessors and component lifecycle functions, that makes it easier and faster to create Web Components. Similar to *Polymer* are *x-tag* and *Bosonic*. Web repositories <http://component.kitchen> and <http://customelements.io> already counts thousands of open source user-contributed custom elements.

3. X-PROJECT TOOLKIT

"Everything is an element", from an AJAX request to an entire web page. Every part of the website is encapsulated inside an element.

x-project provide a set of Polymer element for local routing, API requests, forms, lists, and style.

Elements can be customized through their attributes. We note that attributes could acts as inputs parameters (values that have effects to the element) or output parameters (values that are returned by the element); futhermore, the output parameter of an element could be an input parameter of another element.

The following elements performs local routing (for Single Page Application).

<x-router> implements local routing using *HTML5 Push State API*. It represent the core element of the app. It intercepts routes, create pages, and pass parameters to the page.

<x-route> represents a route-to-page mapping. Parameters presented in an URL are sent as attributes to the corresponding page.

```
<x-route route="{{route}}" page="{{page}}">
```

<x-link> is an extension of the anchor element **<a>** that prevents the default behavior when a click event occurs, blocking page request to the server and redirecting the request to the local router.

```
<a is="x-link" href="{{href}}">{{link}}</a>
```

The following elements handle HTTP RESTful API for the collections of the app.

<api-collection-get> gets a collection of models.

```
<api-collection-get name="{{name}}"
  where="{{where}}"
  page="{{page}}" perpage="{{perpage}}"
  items="{{items}}" schema="{{schema}}"
  count="{{count}}">
</api-collection-get>
```

Where **name** is the name of the collection to retrieve; **where** is object that specifies a set of logical conditions to match, similar to a **WHERE** clause in a SQL query; **page** and **perpage** are pagination parameters; **collection** is the retrieved collection; **schema** is the schema of the collection; **count** is the number of items in the collection (not the number of items retrieved, that corresponds to **perpage** value).

<api-collection-post> create a new model.

```
<api-collection-post name="{{name}}"
  model="{{model}}"></api-collection-post>
```

<api-model-get> retrieve a model.

```
<api-model-get name="{{name}}" model-id="{{id}}"
  model="{{model}}"></api-model-get>
```

Where **name** is the name of the collection of the model; **model-id** is the model id; **model** is the model retrieved (it acts as an output).

<api-model-put> update a model.

```
<api-model-put name="{{name}}" model-id="{{id}}"
  model="{{model}}"></api-model-put>
```

Where **model** is the model updated (it acts as an input).

<api-model-del> delete a model.

```
<api-model-del name="{{name}}" model-id="{{id}}">
</api-model-del>
```

<api-filter> generate dinamically (from a model schema) a form to create an API **where** clause filter.

```
<api-filter schema="{{schema}}"
  filter="{{filter}}"></api-filter>
```

The following elements are used to create forms.

`<x-input>` is an extension of the input element.

```
<x-input type="{{type}}" label="{{label}}"
value="{{value}}"></x-input>
```

Where `type` can be `string`, `number`, `date`, `email`, `url`, `location` (with autocompletion based on Google Place API) and `file`.

`<x-form>` generate dynamically (from a model schema) a form to create/update a model.

```
<x-form schema="{{schema}}"
model="{{model}}"></x-form>
```

The following elements are used to manage lists.

`<x-table>` generate dynamically (from a model schema) a table of models.

```
<x-table schema="{{schema}}" [editable]
items="{{items}}"></x-table>
```

Where `schema` is used to generate the columns of the table; `collection` is used to generate the rows (the values) of the table; `editable` is a optional attribute.

`<x-pager>` generate the list of links to handle pagination.

```
<x-pager count="{{count}}" perpage="{{perpage}}"
current="{{page}}"></x-pager>
```

Where `count` is the total number of item to paginate; `perpage` is the number of item per page; `current` is the current page clicked by the user.

By itself pagination doesn't paginate any list, but (as shown in the case study) it can be used in conjunction with `<api-collection-get>`, where the `current` output parameter of `<x-pager>` is the input `page` parameter of `<api-collection-get>`.

The style is based on `iron-flex-layout` [4], a CSS library of style mixins for cross-platform Flexible Box [12] layouts.

Even a page can be encapsulated in an element. `x-project` provides a set of pages for the admin part of the app, `<page-collection>` and `<page-model-edit>`, presented below.

4. CASE STUDY

In this section we discuss the design and the implementation of a blog platform.

For a blog platform the essential entities to model are: `Post` and `Tag`.

```
{
  "name": "Post",
  "properties": {
    "title": { "type": "string" },
    "posted": { "type": "date" },
    "content": { "type": "text" },
    "permalink": { "type": "string" }
  },
  "relations": [
    {
      "name": "tags",
      "type": "has_many",
      "model": "Tag"
    }
  ]
}
```

```
{
  "name": "Tag",
  "properties": {
    "name": { "type": "string" }
  }
}
```

These models results in the following HTTP RESTful API (automatically generated by Loopback server).

```
GET|POST /api/Posts
GET|PUT|DELETE /api/Posts/:post_id
GET|POST /api/Tags
GET|PUT|DELETE /api/Tags/:tag_id
```

Since a snippet is worth a thousand words, in the following we present the pages of the app. It's important to note how easily a page can be built without writing code but assembling elements.

`index.html` imports the pages and set the router. `<page-collection>` and `<page-model-edit>` are provided by the toolkit.

```
<x-router>
  <x-route route="/admin/:collection"
    page="page-collection"></x-route>
  <x-route route="/admin/:collection/:model_id"
    page="page-model-edit"></x-route>
  <x-route route="/"
    page="page-posts"></x-route>
  <x-route route="/posts/:id"
    page="page-post"></x-route>
</x-router>
```

`<page-collection>` shows models of a collection.

```
<template name="page-collection">
  <api-collection-get name="{{name}}"
    where="{{filter}}"
    page="{{page}}" perpage="{{perpage}}"
    items="{{items}}" schema="{{schema}}"
    count="{{count}}">
  </api-collection-get>
  <api-filter schema="{{schema}}"
    filter="{{filter}}"></api-filter>
  <x-table schema="schema" editable
    items="{{items}}"></x-table>
  <x-pager count="{{count}}" perpage="{{perpage}}"
    current="{{page}}"></x-pager>
</template>
```

`<page-model-edit>` shows the forms to update a model.

```
<template name="page-model-edit">
  <api-model-get name="{{collection}}"
    model-id="model_id"
    model="{{model}}" schema="{{schema}}">
  </api-model-get>
  <x-form schema="{{schema}}"
    model="{{model}}"></x-form>
  <api-model-put name="{{collection}}"
    model-id="{{model_id}}"></api-model-put>
</template>
```

`<page-posts>` show the list of posts.

```
<template name="page-posts">
  <api-collection-get name="Posts"
    page="{{page}}" perpage="10"
    collection="{{posts}}" count="{{count}}">
  </api-collection-get>
  <template is="dom-repeat" items="{{posts}}">
    <div>
      <h1>{{item.title}}</h1>
      <h3>{{item.posted}}</h3>
    </div>
  </template>
  <x-pager perpage="10" total="{{count}}"
    current="{{page}}"></x-pager>
</template>
```

`<page-post>` show a post. It is accessible via `/posts/:post_id` route. The `post_id` parameter is picked from the url by the router and passed to the page.

```
<template name="page-post">
```

```

<api-model-get name="Posts"
  model-id="{{post_id}}" model="{{post}}">
</api-model-get>
<div>
  <h1>{{post.title}}</h1>
  <h2>by <span>{{post.author}}</span></h2>
  <h3>on <span>{{post.date}}</span></h3>
</div>
<div>{{post.content}}</div>
</template>

```

5. A 4-STEP WEB DEVELOPMENT PROCESS

We model the web development process as a four-steps procedure that can be applied recursively to each page (or view) of a web application as well as to every single complex component (or widgets) of the page itself.

This modellization is based on the reasonable assumption that server side operation on data models are nowadays be sufficiently explored, and as proven by the *KeystoneJS* experience, at least one choice is available to automagically 1) generate server-side CRUD methods on models with ACL capabilities and 2) handle users and sessions, once a JSON description of data models and relations between them are provided to the system. This very JSON descriptor documents drive the whole process, actually composed by the following four steps.

1st step - JSON data model description. The JSON descriptors must be defined, specifying data type, relation, and user role read/write capabilities on particular portion of data.

2nd step - Model actions definion. Since CRUD operation coul not be enough to describe all the needed operation further actions on models can be defined and exposed as RESTful APIs via http verbs.

3rd step - UI component definition. Then individual UI component can be defined, relying exclusively on CRUD operations and actions available server-side on data models.

4th step - UI component assemblation. As last task, previously defined UI component have to be mounted to define application views. Assembly should be kept as simple as possible, in the case of x-project toolkit, it only consists of a juxtaposition of HTML5 tags.

6. REFERENCES

- [1] G. T. Heineman and W. T. Councill, editors. *Component-based Software Engineering: Putting the Pieces Together*. Addison-Wesley Longman Publishing Co., Inc., Boston, MA, USA, 2001.
- [2] M. Nath and A. Arora. Content management system : Comparative case study. In *Software Engineering and Service Sciences (ICSESS), 2010 IEEE International Conference on*, pages 624–627, July 2010.
- [3] V. Okanovic. Web application development with component frameworks. In *Information and Communication Technology, Electronics and Microelectronics (MIPRO), 2014 37th International Convention on*, pages 889–892, May 2014.
- [4] A. Osmani and E. Bidelman. iron-elements. Available at <https://github.com/PolymerElements/iron-elements>, 2015. [Online; accessed 15-May-2015].
- [5] S. Patel, V. Rathod, and S. Parikh. Joomla, drupal and wordpress - a statistical comparison of open source cms. In *Trendz in Information Sciences and Computing (TISC), 2011 3rd International Conference on*, pages 182–187, Dec 2011.
- [6] A. Repenning, A. Ioannidou, M. Payton, W. Ye, and J. Roschelle. Using components for rapid distributed software development. *Software, IEEE*, 18(2):38–45, Mar 2001.
- [7] Z. Rocha. Web components polyfills. Available at <http://webcomponents.org/polyfills/>, 2015. [Online; accessed 15-May-2015].
- [8] W3C. Custom elements. Available at <http://www.w3.org/TR/custom-elements/>, 2014. [Online; accessed 15-May-2015].
- [9] W3C. Html imports. Available at <http://www.w3.org/TR/html-imports/>, 2014. [Online; accessed 15-May-2015].
- [10] W3C. Html templates. Available at <http://www.w3.org/TR/html-templates/>, 2014. [Online; accessed 15-May-2015].
- [11] W3C. Shadow dom. Available at <http://www.w3.org/TR/shadow-dom/>, 2014. [Online; accessed 15-May-2015].
- [12] W3C. Css flexbox. Available at <http://www.w3.org/TR/css3-flexbox/>, 2015. [Online; accessed 15-May-2015].
- [13] W3Techs. Usage of content management systems for websites. Available at http://w3techs.com/technologies/overview/content_management/all/, 2015. [Online; accessed 15-May-2015].
- [14] L. Wu, R. De Matta, and T. Lowe. Updating a modular product: How to set time to market and component quality. *Engineering Management, IEEE Transactions on*, 56(2):298–311, May 2009.