

DESCRIPTION

Total Thickness	EN ISO24346	mm	3.60		
Thickness of the wearlayer	EN ISO24340	mm	0.40		
Weight	EN ISO 23997	g/m²	2675		
Size	EN ISO 24342	mm	245 x 1250	150 x 750	500 x 500
Number of planks /tiles and sqm per box	-	-	14 / 4.29 m²	38 / 4.28 m²	18 / 4.5 m²
M²					
Norm/Product Specification	-	-	EN ISO 11638		
European classification	EN ISO 10874	classe	32		
Fire rating	EN 13 501-1	classe	Bfl-s1		
Static Electrical Propensity	EN 1815	kV	< 2		
Slip Resistance Wet	DIN 51130	classe	R10		





PERFORMANCES

Wear Resistance	EN 660.2	mm³	≤ 2.0		
Wear Group	QB 30	groupe	T		
Impact Sound Insulation	EN ISO 717-2	dB	20		
Room Impact	NFS 31 074	dB	< 65		
Dimensional Stability (norm)	EN ISO 23999	%	≤ 0.25		
Dimensional Stability (average measure)	EN ISO 23999	%	≤ 0.05		
Residual Indentation (norm)	EN ISO 24343-1	mm	≤ 0.20		
Residual Indentation (average measure)	EN ISO 24343-1	mm	0.12		
Castor Chair : H Type	ISO 4918	-	OK		
Thermal Conductivity	EN ISO 10456	W/(m.K)	0.25		
Colour Fastness	EN 20 105 - B02	degré	≥ 6		
Chemical Products Resistance	EN ISO 26987	classe	OK		
Surface Treatment	-	-	ProtecShield™		

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/ m³	< 10		
--------------------	-------------	--------	------	--	--

MARQUAGE CE

	EN 14041	-	  
		-	