



Essential Guide for NLP

Construct a Neural Bag-of-Words
Framework for Evaluating Sentiments

DCA0305
ivanovitch.silva@ufrn.br






MLOps




Essential guide for NLP


Foundations	Data Preparation	Applications	ML Introduction
From Linguistics to NLP	Tokenization Bag of Words	Text Classification	Foundations of Attention
Standard Models	Word Embeddings	Image Captioning Machine Translation	From RNN to Transformer

Data leakage!!!







In theory, I can only
create the vocabulary
after here



Where is the
Exploratory
Data
Analysis
(EDA) ?

Vocabulary Creation only using Train Data



```
# load all docs in a directory
def process_docs(directory, vocab):
    # walk through all files in the folder
    for filename in listdir(directory):
        # skip any reviews in the test set
        if filename.startswith('cv9'):
            continue
        # create the full path of the file to open
        path = directory + '/' + filename
        # add doc to vocab
        add_doc_to_vocab(path, vocab)
```

Converting Reviews into Lines of Tokens

```
# load the vocabulary
vocab_filename = 'vocab.txt'
vocab = load_doc(vocab_filename)
vocab = vocab.split()
vocab = set(vocab)
# load all training reviews
docs, labels = load_clean_dataset(vocab)
# summarize what we have
print(len(docs), len(labels))
```

1800,1800

```
# load and clean a dataset
def load_clean_dataset(vocab):
    # load documents
    neg = process_docs('txt_sentoken/neg', vocab)
    pos = process_docs('txt_sentoken/pos', vocab)
    docs = neg + pos
    # prepare labels
    labels = [0 for _ in range(len(neg))] + [1 for _
in range(len(pos))]
    return docs, labels
```

Converting Reviews into Lines of Tokens

```
# load all docs in a directory
def process_docs(directory, vocab):
    lines = list()
    # walk through all files in the folder
    for filename in listdir(directory):
        # skip any reviews in the test set
        if filename.startswith('cv9'):
            continue
        # create the full path of the file to open
        path = directory + '/' + filename
        # load and clean the doc
        line = doc_to_line(path, vocab)
        # add to list
        lines.append(line)
    return lines
```


1 docs[0]

'caliber killer struck starring john leguizamo mira sorvino adrian brody jennifer esposito michael bebe neuwirth rated summer sam remembered waste spike lees abilities lee great filmmaker often exhibiting kinetic visual flair par brian depalma martin scorsese storytelling ability comparable steven spielberg gets bind latest effort case director pretending something say reality little substance absorb work summer unusual summer new york city hottest summer record boot new yorks first serial killer loose calling son sam david killed people new york area frightened whole city population understandable nyc hit blackout people went berserk causing billions dollars damage city movies focus group twentysomethings fateful summer vinny john leguizamo clubhopping hairdresser benevolent wife dionna mira sorvino looking young ritchie adrian brody punk becomes outcast well son sam suspect gang small time mobsters minor characters follow roller coaster lives thrown whack even recent killings vinny dionna marital problems vinny cheats dionna tries please make stay faithful ritchie gets shunned group friends started become eccentric point dancing gay night clubs making porno films girlfriend tensions build conflicts arise anniversary night son sams first murder looms night promises strike local gang much time hands makes list detailing people members think might suspects top list ritchie vinny unwilling part said group called upon set trap friend watch proceedings painfully graphic dreaded question springs mind way movie made id guessed spike lee trying tell us something searched deeper became clear little find lee touches much media punk scene details actual killings well characters personal dilemmas doesnt bring topics together form coherent theme make discernible statement lost movie turns hollow saving grace film enjoyable bad summer sam doesnt get help frankly bore redundant repetitive two hour twenty minute film doesnt entertain beyond first half hour suspense film refuses fully murders little involving drama film muddled focus vague leguizamos turn vinnie annoying whiny script makes clear supposed believe character flawed still good guy youd never guess performance adrian brody especially mira sorvino fare better so sorvino gives riveting touching performance banal movie im tempted think liked nearly everything else around inane character affecting emotions brody paints effective portrait young guy desperate attention gets little bargained summer sam superficial elements good film looks great notable performances suppose pretty well directed purely technical way also empty pretentious boring like last years thin red line movie director doesnt know wants say goes ahead says anyway eugene<'

Transforming Movie Reviews into Bag-of-Words Vectors

tip: the previous step is repeated here

```
1 x_train[0]  
array([0.          , 0.01278772, 0.          , ..., 0.          , 0.          ,  
       0.          ])
```

```
# fit a tokenizer  
def create_tokenizer(lines):  
    tokenizer = Tokenizer()  
    tokenizer.fit_on_texts(lines)  
    return tokenizer  
  
# load the vocabulary  
vocab_filename = 'vocab.txt'  
vocab = load_doc(vocab_filename)  
vocab = set(vocab.split())  
  
# load all reviews  
train_docs, y_train = load_clean_dataset(vocab, True)  
test_docs, y_test = load_clean_dataset(vocab, False)  
  
# create the tokenizer  
tokenizer = create_tokenizer(train_docs)  
  
# encode data  
x_train = tokenizer.texts_to_matrix(train_docs, mode='freq')  
x_test = tokenizer.texts_to_matrix(test_docs, mode='freq')  
print(x_train.shape, x_test.shape)
```

Sentiment Analysis Models

```
# define the model
def define_model(n_words):
    # define network
    model = Sequential()
    model.add(Dense(50, input_shape=(n_words), activation='relu'))
    model.add(Dense(1, activation='sigmoid'))
    # compile network
    model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])
    # summarize defined model
    model.summary()
    plot_model(model, to_file='model.png', show_shapes=True)
    return model
```

