



PDF Download
3745812.3745844.pdf
16 January 2026
Total Citations: 0
Total Downloads: 293

Latest updates: <https://dl.acm.org/doi/10.1145/3745812.3745844>

RESEARCH-ARTICLE

Optimizing Game Strategies with Deep Reinforcement Learning: A Framework for Intelligent Decision-Making

MAHAVEERAKANNAN R, Saveetha School of Engineering, Chennai, TN, India

HEMAVATHI R, Saveetha School of Engineering, Chennai, TN, India

CUDDAPAH ANITHA, Mohan Babu University, Tirupati, AP, India

DINESH GOYAL, Poornima Institute of Engineering & Technology, Jaipur, RJ, India

PANKAJ DADHEECH, Swami Keshvanand Institute of Technology Management & Gramothan, Jaipur, RJ, India

Open Access Support provided by:

Mohan Babu University

Saveetha School of Engineering

Swami Keshvanand Institute of Technology Management & Gramothan

Poornima Institute of Engineering & Technology

Published: 23 December 2024

[Citation in BibTeX format](#)

ICIMMI 2024: 6th INTERNATIONAL
CONFERENCE ON INFORMATION
MANAGEMENT & MACHINE
INTELLIGENCE

December 23 - 24, 2024
RJ, Jaipur, India

Optimizing Game Strategies with Deep Reinforcement Learning: A Framework for Intelligent Decision-Making

Mahaveerakannan R
Department of Computer Science and Engineering
Saveetha School of Engineering,
Saveetha Institute of Medical and
Technical Sciences, Saveetha
University,
Chennai, Tamil Nadu, India
mahaveerakannanr.sse@saveetha.com

Hemavathi R
Computer Science and Engineering
Saveetha School of Engineering
Chennai, Tamilnadu, India
Computer Science and Engineering
SRGDS Matriculation
Tiruvannamalai, Tamilnadu, India
rhemavathi.sse@saveetha.com

Cuddapah Anitha
Department of Computer Science and Engineering,
School of Computing, Mohan Babu
University, (Erstwhile
SreeVidyanikethan Engineering
College),
Tirupati, AP, India
cuddapah.anitha@mbu.asia

Dinesh Goyal
Computer Science & Engineering
Poornima Institute of Engineering
and Technology, Jaipur, Rajasthan,
India
Jaipur, Rajasthan, India
dinesh8dg@gmail.com

Pankaj Dadheech
Computer Science & Engineering
Swami Keshvanand Institute of
Technology, Management and
Gramothan, Jaipur, Rajasthan,
India-302017
Jaipur, Rajasthan, India
pankajdadheech777@gmail.com

Abstract

In order to succeed, teams need strategies that play to their strengths while also being flexible enough to respond to unexpected challenges. Improving game strategy through intelligent decision-making under pressure is possible with the help of the novel and fascinating deep reinforcement learning (DRL) technology. As their names suggest, deep reinforcement learning (DRL) agents thrive in dynamic, unpredictable environments. In order to determine the most effective one, they conduct a myriad of tests. This might be accomplished by combining reinforcement learning with deep neural networks. The purpose of this research is to find out how sports strategy and other game strategies might benefit from dynamic response learning (DRL). This happens because players become distracted because they are tired, hurt, or suffering from mental pain. So, here are a few ways: Agents can adapt their optimization strategies with moss growth optimization (MGO) as the game demands. Modifying a few settings in the Deep Soft Actor-Critic (SAC) model should solve the problem. In order to overcome these obstacles and enhance sports tactical tactics procedures, some provide DRL innovative optimization. This hypothesis was tested by scientists using NBA data. Following minmax's cleaning and normalization of the data, we identified features. The suggested approach enhances sports techniques more effectively, according to NBA statistics. Significant DRL challenges in games are the focus of this research. Stability throughout training, accurate sampling, and limiting of state area are all ensured by them. To further the

state of the art in intelligent game design, this project seeks to build a framework for optimizing strategies across different types of games.

Keywords

Deep Reinforcement Learning, Optimized based Deep Soft Actor-Critic, Moss growth optimization, Decision Making Problems, National Basketball Association, Game Strategy

ACM Reference Format:

Mahaveerakannan R, Hemavathi R, Cuddapah Anitha, Dinesh Goyal, and Pankaj Dadheech. 2024. Optimizing Game Strategies with Deep Reinforcement Learning: A Framework for Intelligent Decision-Making. In *6th INTERNATIONAL CONFERENCE ON INFORMATION MANAGEMENT & MACHINE INTELLIGENCE (ICIMMI 2024)*, December 23, 24, 2024, Jaipur, India. ACM, New York, NY, USA, 9 pages. <https://doi.org/10.1145/3745812.3745844>

1 Introduction

ACM's new manuscript submission template aims to provide consistent styles for use across ACM publications, and The versatility and utility of machine learning make it an essential building block of artificial intelligence. The three main methods of artificial intelligence (AI) learning are supervised learning (SL), restorative learning (RL), and RL. These learning models have had a major influence on the development of this field [1-2]. The foundation of SL is the correlations between input and output data, which are essential to many practical applications [3]. It includes features including spam filtering, object detection, image recognition, and predictive analytics. Unlabeled data mining (UL) uses dimensional reduction and principal component data classification to unearth previously unseen patterns [4].



This work is licensed under a Creative Commons Attribution 4.0 International License. *ICIMMI 2024, Jaipur, India*

© 2024 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-1122-0/2024/12

<https://doi.org/10.1145/3745812.3745844>

Incorporating AI technology was determined to be the most effective way to promote sustainable education development after examining the current educational framework [5]. Artificial intelligence has advanced as a result of recent breakthroughs in science and technology. Building AI systems that can mimic human intellect and improving our knowledge of AI are the main goals of this research. In this domain, computers can learn to behave and perform like humans with higher-order cognitive abilities [6]. Computer research is the basis of this academic discipline. Consequently, AI has become an essential component for numerous modern businesses. The capacity of deep learning (DL) to enhance educational operational systems is one reason for its popularity [7-8]. Improving artificial intelligence requires deterministic learning. The feature has thrust DL technology into the heart of academic arguments due to its possible impact on preschool programming. This idea has been supported by other scientific investigations' results [9].

The use of optimization strategies to improve team games and tactical planning is gaining prominence as a means to elevate athletic events. To improve AI-based solutions, coaches and analysts can examine large datasets, player data, and game dynamics in real-time [10]. This method gets solutions ready for refinement. A new family of optimization algorithms has been developed in response to the growing complexity of real-world engineering challenges [11]. Obtaining a precise solution to these high-dimensional, multi-modal, differentiable, hybridised global optimisation problems is a difficult task [12]. The sports industry was quick to adapt new strategies and approaches around the turn of the millennium, including social media, streaming broadcasting, and global supply chains [13]. The ever-increasing significance of the sports sector has led academics to concentrate their attention on the management of sports teams. It is [14] The creation of decision-support systems by a few researchers is an effort to provide assistance to clubs in the process of picking draft prospects. In the field of sports performance research, the ability to accurately forecast the outcomes of sporting events is an essential component that has an impact on a number of different sports markets [15]. These marketplaces offer a diverse selection of services, some of which include customer service, betting, and the administration of sports teams, amongst others. This is due to the fact that when managers are able to accurately forecast the outcome of a sporting event for their team, they are able to obtain crucial information regarding the strategy of the organisation, the degree of interest shown by spectators, and the activities taken by bookies. When working in a group context, for instance, there is a supervisor or general manager (GM) who is tasked with the responsibility of making a great deal of crucial choices regarding the day-to-day operations of the group. Since the beginning of time, humans have found a way to pleasure themselves through the participation in sports and activities. In today's world, people simply carry them out [16]. In the past, monarchs and nations would use sports and games as a means of displaying their political and social power. It is possible that the ancient Olympics were initially held as a means of commemorating Zeus; nevertheless, they quickly evolved into a means of exercising governmental control over the athletes who took part in them [17]. One of the most important strengths for people who operate in

the gambling industry is the ability to conduct oversight of sporting events. When it comes to the execution, the primary goal is to lessen the possibility of potential injury while simultaneously improving the performance of rivals. The amount of exercise that an individual gets, the individual's current state of health, and the amount of time that they spend exercising are all factors that can influence the likelihood that they will be successful in achieving their goals.

For the purpose of achieving their objectives and outperforming their competitors, individuals and sports teams are dependent on activities, decisions, and arrangements that have been planned and deliberated over. These distinct approaches to strategy are referred to as tactical tactics.

Techniques for sports strategy face a challenge in the form of the inherent instability that is associated with athlete performance. The reason for this is because athletes are susceptible to becoming sidetracked from their intended training paths due to factors such as exhaustion, injury, or their own feelings. In order to solve these concerns and accomplish the goal of improving sports tactical strategies, the optimised based SAC technique was offered as a potential solution. For the goal of fine-tuning, the MGO algorithm is utilised during the process.

The remainder of the assignment is completed through the usage of sections. In Section 2 of the study, the works that are pertinent to the topic are cited. Section 3 contains a comprehensive outline of all of the strategies and initiatives that are recommended. Additionally, the results of the presentation analysis and the accompanying debate are presented in the fourth section. Section 5 presents a summary of the findings obtained from the research.

2 RELATED WORKS

A DRL architecture utilizing Spatial Pyramid Pooling (SPP) is proposed as a solution by Lemos et al. [18] for this issue. The SPP layer can be incorporated into the proximal policy optimization (PPO) method's critic network because of GridNet's encoder-decoder structure. This part ought to be a part of the GridNet concept. The initial observation size is irrelevant to how this SPP layer evolves; it follows the criteria of the game state. This allows the agent to adapt its decision-making to different map designs. Our experimental results show that the suggested method greatly improves the model's performance and flexibility when training agents for scenarios involving real-time strategy games. Regulations also apply to smaller maps. Applying this method to sequential choice problems with stronger and more versatile AI agents and observations of varying sizes is possible.

A performance-oriented strategic training module (PFSTM) based on concatenated neural networks is thoroughly evaluated by Liu and Liu [19]. By comparing current and historical game statistics, this module aims to identify players who are performance-oriented. We can learn which traits are failing in practice by combining our findings. Our tactical training can be customized to focus on those specific aspects. Taking into consideration the most effective training results, recurrent learning decides which tactical training components to use in this form of training. It is suggested to apply overlapping features after multiple strategy review sessions in order to maximize performance. Before being released to

the public, the packed performance qualities are disassembled and fine-tuned. As a result, the module is useful for football players' tactical use in any setting. Based on prior instruction, this module determines performance attributes. The most self-aware athletes pay close attention to their passing, dribbling, and overall game plan. A player's passing accuracy and goal-scoring prowess will both see rapid improvements for guys in better shape.

The upgraded YOLOv7 model has a number of beneficial applications, one of which is the efficient identification of elephants in regions that are occupied by humans. These places include highways, railway lines, and other such areas. This is accomplished through the utilisation of a Visual Attention Network (VAN) layer in conjunction with YOLOv7. The first time that Mullick and Mandal put forward this concept was in the year 20. Your first and greatest responsibility is to notify the appropriate authorities. The objective of this study is to investigate the dependability of object detection algorithms for the detection of elephants, with a particular emphasis on the numerous YOLO (You Only Look Once) variants. When applied to a one-of-a-kind Elephant Detection (ED) dataset, the improved YOLOv7 model accomplished better results than its predecessors. For the purpose of training the model, a combination of public and private datasets pertaining to elephants were employed. For the purpose of completing the training, cloud-based camera photos from a number of different locations were utilised. Furthermore, the model attained a validation accuracy of 97%, which is quite remarkable.

One of the primary objectives of Cengizel and Şenel's [21] study was to investigate the impact of various post-treatment regimens on thermal asymmetry and the demands of a three-on-three basketball game in male competitors. The short-term effects of each medication were another factor that was taken into consideration during the investigation. The laboratory was visited by a minimum of 18 male basketball players over the course of four days, with a 72-hour interval between each visit. The average age of these players was 21.7 ± 1.5 years, and their average level of experience was 10.6 ± 1.9 years. There were three distinct protocols in which the players participated, namely the baseline (3×3 game) and the FCM plus PAP plus 3×3 game. Each of these protocols was distinct and distinct from the others. For the purpose of analysing game profiles and determining the internal and external stressors that the players were experiencing, thermography was utilised during the operations. For the purpose of determining the internal load, the results showed that there was no statistically significant difference between FCM and PAP. On the other hand, the three-on-three basketball game which followed the FCM had the largest overall and band 2 distances. Immediately following the FCM and PAP, there was a discernible increase in both the turnover rate and the fraction of attempts to score a point. Following the FCM, there was a discernible difference in temperature between the lower back and the belly, as well as a change in the pressure throughout the peripheral artery system. The purpose of this study is to offer coaches and practitioners with the information they need to improve three-on-three basketball players by identifying the unique abilities that are required for the game.

In order to capture the cost-benefit trade-offs that occur between an attacker trying to hide behind statistical changes in the profile

and a provider trying to strike a balance between compromise detection and the expenditure of throughput measurements, Rao et al. [22] provide a game theoretic framework. This framework is designed to capture the cost-benefit decisions that occur between the two parties. When the game-specific Nash conditions are considered, the success provider is able to obtain qualitative insights and clear bounds. It is possible to establish these requirements by employing the generalisation equation of the machine learning estimation technology. In order to demonstrate that this is the case, we will provide experimental data that demonstrates how an adversary may sneak up on DTN and compromise a significant portion of its computational capacity by manipulating the features of the ML estimation.

The optimisation methodology was utilised by Xiao [23] in order to enhance the efficiency of the tactical methods that are implemented during sporting events. Tactics are acts, judgements, and arrangements that are purposeful and preplanned, and they are utilised by individuals and groups in order to accomplish their goals and outmanoeuvre their adversaries. In order to find the most effective method for constructing security solutions through the use of a game theory simulation, one must first ascertain the number of distinct possibilities that are associated with the issue at hand. Players choose which structure to attack based on unique unforeseen attack scenarios, and the attacker is responsible for managing the various strategic alternatives that are available to them. It is also the responsibility of the attacker to determine the defences that are in place for the system. The unpredictability of human performance, which can be influenced by factors such as fatigue, injuries, or emotional states, is a factor that impedes the creation of tactical strategies. In order to overcome these issues and improve sports tactical approaches, one solution that has been presented is called SRICSO, which is an acronym that stands for self-regulated immune cat swarm optimisation. A dataset that was gathered from the National Basketball Association (NBA) was utilised by the researchers in order to investigate and evaluate this proposition. Immediately following the collection of the dataset, the data underwent preprocessing by means of the minmax normalisation method. The subsequent phase was to draw out characteristics through the use of primary analysis. The purpose of this study is to evaluate the accuracy and precision of our strategy in comparison to strategies that are considered to be more conventional, such as OCNN, NB, and RF. An examination that was conducted with a dataset from the National Basketball Association revealed that the SRICSO method fared better than other competing approaches in terms of enhancing sports tactical strategies.

3 PROPOSED METHODOLOGY

The results of the strategic identification task that was completed by the deep learning method that was proposed are displayed in Figure 1. In the part that comes after this one, you will find thorough descriptions of each of the types described.

3.1 Dataset

The information that was gathered by STATSLLC from the SportVU tracking system was included in the analysis. The National Basketball Association (NBA) made a contribution to the database by




Figure 1: Workflow of Research Model

providing information on player trajectories [23]. Each and every data file includes a representation of a possession in its corresponding contents. During a game, "possession" refers to the situation in which one team maintains control of the ball for the bulk of the time. The moment when either team scores or takes control of the ball, the ball is regarded to be no longer in possession of the team that first scored it. One of the most important metrics for efficiency is possession. This is due to the fact that it is essential to be able to do statistical analysis on each possession. A set of tracking coordinates, denoted by $S_t^i = X_t^i, Y_t^i$, is assigned to each and every item in the collection. These coordinates are recorded at a frequency of 25 Hz, and they are assigned to each and every player X. There is only one team that is permitted to have possession of the ball throughout the entirety of the possession time. Between fifty and three hundred frames are included in the holdings, which is the total number of frames for the collection. A total of 36,330 possessions were included in this dataset, which was collected during the 2012–2013 NBA season. STATS SportsVU was the organisation that was in charge of monitoring this data. There were over 630 games that were used to compile the data [24].

3.2 Preprocessing using Min-max normalization

The min-max normalisation method can be used to ensure that numerical data remains within a given range. Data normalization and feature scaling are two other names for this technique. After a dataset is normalized, all of its variables and attributes are scaled. The objective is to facilitate analysis and comparisons. One way to improve strategic approaches in sports analytics is to use the min-max normalization method. All data, including team traits and individual records, must be systematically scaled in order to achieve this goal. If researchers and coaches compared materials fairly and precisely, it could be easier to accurately evaluate trends, strengths, and shortcomings.

$$R_{new} = \frac{R - \min(R)}{\max(R) - \min(R)} \quad (1)$$

R_{new} =novel value got from the normalizing results, =Former $\max(R)$ =High value dataset and $\min(R)$ =Low charge of dataset.

3.3 System overview

In this study, we provide a system that can track and assess field athletes in real-time as they compete. Among the many technologies utilized by the system are deep reinforcement learning, the internet of things (IoT), and edge computing. The Internet of Things, which includes wearable sensors, allows for the precise collection and real-time distribution of data. Sensor data is wirelessly transmitted to peripheral processing nodes. Data concerning physiological variables and mobility make up this dataset. By doing computations in real-time at nodes next to the data source, edge computing increases capabilities and decreases data transit latency. Lightspeed processing of massive data sets is possible with 16 GB of RAM, multi-core CPUs (such as Intel Xeon), and gigabit per second (Gbps) connections on every edge node. Using wireless technologies like Wi-Fi and Bluetooth, data may be reliably and quickly transmitted between sensors and nodes located on the network's periphery. Please understand that I am not attempting to downplay the significance of other factors, such as reliable networks and control over available bandwidth. Intelligent agent models powered by deep reinforcement learning get better at mimicking the virtual methods of sports. This ensures that the training will have maximum impact.

While setting up the system, the primary goal is to ensure that each athlete has the right sensors placed on them. Reinforcement learning models build input processing and analysis modules after a strong foundation is established. Before we can declare the system complete, we need to test and integrate it. Track and field athletes can benefit from these recommendations by tailoring their training to their specific demands, improving their utilization of speed data, and optimizing their overall performance. This strategy has the potential to revolutionize track and field by fostering innovation in smartly improving training methods and by enhancing the safety

and efficiency of training for athletes an RL method that is deeply rooted in the SAC paradigm.

Deep learning's maximum entropy reinforcement learning framework is employed by the Soft Actor-Critic (SAC) approach [25]. A non-governmental actor-critic is a concept that influenced this approach. The goal of research and activity capture should be to maximize the expected return while simultaneously minimizing entropy. To make sure we're collecting the right data and allocating resources optimally, our track and field athlete monitoring system uses the SAC algorithm. Training AI models using SAC ensures consistent and accurate processing of real-time data. By utilizing these technologies, one may effectively control processing power and network traffic, enabling the management of data in real-time under dynamic conditions. To accommodate the varied data flow requirements of each athlete, SAC, for instance, is responsible for continuously modifying the distribution of resources at edge computing nodes. Through the optimization of data flow channels, the SAC algorithm enhances the system's aesthetics and decreases latency.

Furthermore, SAC improves the caliber of personal training program recommendations. Training programs provided by SAC are risk-free and productive because the organization is devoted to constant study and the enhancement of its methods. These routines are designed to cater to the athletes' present condition while also considering their previous performance. By integrating SAC into the athlete monitoring system, we can improve data processing and resource allocation, offer smart support for individualized training, and bring fresh perspectives to the field of sports training.

The SAC method enhances both value and policy functions at the same time by using a structure called maximal entropy. The following sections and equations not only describe the procedure, but also give an abstract of the key components of the SAC algorithm. Using the highest feasible entropy level to optimize the policy's anticipated return is the primary goal of the SAC technique:

$$J(\pi) = \sum_{t=0}^T E_{(s_t, a_t) \sim \rho_\pi} [r(s_t, a_t) + \alpha \mathcal{H}(\pi(\cdot|s_t))] \quad (2)$$

where $\mathcal{H}(\pi(\cdot|s_t)) = -\log \pi(a_t|s_t)$ characterises the entropy π at state s_t , and α is the temperature parameter.

The soft Q-function $Q^\pi(s_t, a_t)$ evaluates the expected return of action a_t in state s_t :

$$Q^\pi(s_t, a_t) = r(s_t, a_t) + \gamma E_{s_{t+1} \sim p} [V^\pi(s_{t+1})] \quad (3)$$

where $V^\pi(s_{t+1})$ is the value function under the policy π and γ is factor.

The soft value function $V^\pi(s_t)$ is the expected value of the policy π :

$$V^\pi(s_t) = E_{a_t \sim \pi} [Q^\pi(s_t, a_t) - \alpha \log \pi(a_t|s_t)] \quad (4)$$

Reducing the gap between the existing policy and the Q-exponential purpose's value updates the policy:

$$J_\pi = E_{s_t \sim D} [\alpha \log(\pi_\theta(a_t|s_t)) - Q_\phi(s_t, a_t)] \quad (5)$$

The temperature limit α is adjusted to term, matching predictable entropy to a target entropy $\mathcal{H}_0$:

$$J(a) = E_{a_t \sim \pi_\theta} [-\alpha \log \pi_\theta(a_t|s_t) - \alpha \mathcal{H}_0] \quad (6)$$

Robust and efficient learning in dynamic situations is achieved by SAC updating these components, striking a balance exploitation. Algorithm 1 presents the SAC procedure for prediction process.

Algorithm 1 Soft Actor-Critic (SAC)

Input: Initial parameters θ_1, θ_2 for critic networks, ϕ for actor network, replay buffer D , discount factor γ , soft update coefficient τ

Output: Updated critic networks $Q_{\theta_1}, Q_{\theta_2}$, actor network π_ϕ , and temperature parameter τ

```

1: Initialize target networks  $\theta'_1 \leftarrow \theta_1, \theta'_2 \leftarrow \theta_2$ 
2: Prime replay buffer  $D$ 
3: for each iteration do
4: for each situation step do
5: Select action  $a_t \sim \pi_\phi(a_t|s_t)$ 
6: Execute  $a_t$  to observe reward  $r_t$  and next state  $s_{t+1}$ 
7: Store transition  $(s_t, a_t, r_t, s_{t+1})$  in  $D$ 
8: end for
9: for each gradient step do
10: Sample transitions  $(s_t, a_t, r_t, s_{t+1})$  from  $D$ 
11: Compute target value:
 $y_t = r_t + \gamma (\min_{i=1,2} Q_{\theta'_i}(s_{t+1}, a_{t+1}) - \alpha \log \pi_\phi(a_{t+1}|s_{t+1}))$ 
12: Update critics by minimizing the loss:
 $L(\theta_i) = E_{(s_t, a_t, r_t, s_{t+1}) \sim D} [(Q_{\theta_i}(s_t, a_t) - y_t)^2]$ 
13: Update actor by minimizing the loss:
 $J_\pi(\phi) = E_{s_t \sim D} [\alpha \log \pi_\phi(a_t|s_t) - Q_\theta(s_t, a_t)]$ 
14: Adjust temperature parameter  $\alpha$  by minimizing:
 $J(a) = E_{a_t \sim \pi_\phi} [-\alpha \log \pi_\phi(a_t|s_t) - \alpha \mathcal{H}_0]$ 
15: Soft update target networks:
 $\theta'_i \leftarrow \tau \theta_i + (1 - \tau) \theta'_i$ 
16: end for
17: end for

```

3.3.1 Fine-tuning using MGO. In the year 2024, Zheng et al. [26] were the ones who initially introduced the metaheuristic method that is today known as MGO. The methodology behind the program is derived from the natural growth pattern of moss. First and foremost, the MGO approach begins with the determination of the evolutionary path that the population has taken. In order to accomplish this, a method known as the determination of wind direction is utilised, which entails splitting the population into several groups. The search for vegetative reproduction systems in moss is one of the two new elements that have been included to the program. In conclusion, the algorithm is modified from the traditional metaheuristic approach when the cryptobiosis process is used to directly affect the answers that people come up with. This is done in order to prevent the algorithm from becoming trapped on a solution that is optimal in the local context. In order to achieve its goal of imitating the biological behaviour of moss, the MGO algorithm is dependent on the mathematical model that is shown below:

MGO has developed a method that is revolutionary in terms of determining the direction in which the wind is blowing. One of these methods is called "Wind direction determination," and it involves determining the evolutionary trajectory of a population by utilising the geographical characteristics of the ideal person.

First, the grouping operation is carried out for each population X . The optimal individual in the current population is denoted by M_{best} , and the j th dimension of M_{best} is utilized as the threshold. The set $X_{i,j}$ that is greater than $M_{best,j}$ is classified as belonging to the DX_{j1} set, while the set $X_{-(i,j)}$ that is less than $M_{best,j}$ is classified as belonging to the DX_{j2} set. Equation 7) is used to determine the division of DX_{j2} into two sets.

$$dicX_j = \begin{cases} DX_{j1}, & \text{count}(DX_{j1}) \geq \text{count}(DX_{j2}) \\ DX_{j2}, & \text{count}(DX_{j1}) < \text{count}(DX_{j2}) \end{cases} \quad (7)$$

where $\text{count}(\cdot)$ is the act of tallying the components comprising a specific set. This splitting operation will be repeated multiple times, and the resultant set looks like this:

$$dicX = \left\{ M_i = (M_{i,1}, M_{i,2}, \dots, M_{i,dim}) \mid M_i \in \bigcap_{j=1}^{dn} divX_{pj}, M_i \in X \right\} \quad (8)$$

The set is initially strongminded to be divided dn times, and then dn dimensions are randomly selected. The first dimension is used to divide the set, and dimension. This procedure continues until the number of divisions is exhausted, yielding the dimension $dicX$. The given data was used to derive the following wind direction vectors:

$$D_{wind} = M_{best} - \text{mean}(divX) \quad (9)$$

where D_{wind} signifies M_{best} minus modesapiece dimension of $divX$;

2. Spore dispersal search: The spreading of spores is mimicked in the exploring stage of MGO. The dispersion distance of spores is reduced in turbulent conditions, although it can go farther in the presence of high winds. In Equation 10), to can see the process modelled.

$$M_i^{new} = \begin{cases} M_i + \text{step1} \cdot D_{wind} \cdot r1 > 0.2 \\ M_i + \text{step2} \cdot D_{wind} \cdot r1 \leq 0.2 \end{cases} \quad (10)$$

where M_i^{new} represents the i th individual's offspring, while $r1$ is an arbitrary integer between zero and one. According to Equations 11) and (12), the two modes' update steps are step1 and step2, respectively.

$$\text{step1} = \omega \cdot (r_2 - 0.5) \cdot E \quad (11)$$

where ω refers to the wind speed, r_2 is a random vector among 0 and 1, and E is a constant value of two, as seen in Equation 13).

$$\text{step2} = 0.1 \cdot \omega \cdot (r_3 - 0.5) \cdot E \cdot \left[1 + \tan\beta \sqrt{1 - \beta^2} \right] \quad (12)$$

where r_3 is a random vector among 0 besides 1, besides β is exposed in Equation 14).

$$E = 1 - \frac{FEs}{MaxFEs} \quad (13)$$

where FEs symbolises evaluations, and $MaxFEs$ means the extreme number of evaluations.

$$\beta = \frac{\text{count}(divX)}{\text{count}(X)} \quad (14)$$

where β denotes the proportion of the size of $divX$ and X ;

3. Using a mathematical model, to can see MGO procedure employs dual broadcast search with an 80% probability. This technique

mimics the occurrence of both sexual and asexual spore reproduction.:

$$\begin{cases} M_i^{new} = (1 - act) \cdot M_i + act \cdot M_{best} \cdot r_4 > 0.5 \\ M_{i,j}^{new} = M_{best,j} + \text{step3} \cdot D_{wind_j} \cdot r_4 \leq 0.5 \end{cases} \quad (15)$$

In Equation 15), the part where $r_4 > 0.5$ means it is informing the i th separate, while the part where $r_4 \leq 0.5$ means it dimension of the i th separate, where act signifies the stricture controlling whether M_{best} is as exposed in Equation 16), besides step3 signifies the update step as exposed in Equation 17).

$$act = act = \begin{cases} 1, & \frac{1}{1.5 - 10 \cdot r_5} \geq 0.5 \\ 0, & \frac{1}{1.5 - 10 \cdot r_5} < 0.5 \end{cases} \quad (16)$$

where r_5 is a chance vector among zero besides one.

$$\text{step3} = 0.1 \cdot (r_6 - 0.5) \cdot E \quad (17)$$

where r_6 is an arbitrary vector ranging from 0 to 1, and E is the wind speed according to Equation 13);

The amazing capacity of mosses to recover and grow after being dried out is the foundation of the physiological phenomenon known as cryptobiosis. In the process of selecting traditional metaheuristic algorithms, it is helpful. In contrast to the more prevalent method of selection known as greedy selection, this strategy archives individuals in a methodical manner who have been subjected to updates over the course of multiple generations. If specific conditions are satisfied, such as reaching a particular count, the current user will be replaced with the most notable performer from the archive. This will take effect if certain requirements are met. It is possible to significantly enhance the performance of the MGO's optimisation by employing this strategy, which involves beginning the search of each individual from the same location multiple times. In the study that was cited, there is a more detailed explanation of it that may be found for those who are interested [26].


At long last, MGO will employ a method of selection that is based on randomness in order to produce a group of individuals who will be starting out. There is a direct correlation between the direction of the wind during each cycle and the evolutionary trajectory of the population. After then, it employs the cryptobiosis mechanism in order to keep everyone informed while it methodically searches for spore dispersal and dual propagation based on the likelihood that has been provided. The procedure is to be repeated until either all of the applicants have been taken into consideration or until the maximum number of evaluations has been reached, whichever occurs first.

4 RESULTS AND DISCUSSION

For the purpose of performance evaluation, a standalone workstation that was running Ubuntu 20.04 LTS, with 32 GB DDR4 RAM, 1 TB of NVMe SSD storage, and an Intel Core i7-10700K CPU (eight cores in addition to sixteen threads, base clocked at 3.8 GHz) were utilized [27-28]. For the purpose of gathering and analyzing performance metrics on this platform, the ManageEngine software, version 3.2.45, was utilized.

Table 1: Performance Metrics of Different Models

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
DBN	92	88	89	90
CNN	95	90	91	93
DQL	96	93	92	94
Proposed	97	95	94	96

**Figure 2: Analysis of Proposed model**

4.1 Validation analysis of proposed classical with existing practises

Figures 2 and 3 demonstrate the experimental assessment of the proposed classical with existing techniques. These figures compare the proposed classical with existing methodologies in terms of multiple metrics for various training and testing data ratios.

Table 1 contains a table that displays the accuracy, precision, recall, and F1-score of a number of different models. According to the data presented in this table, the performance of the suggested model is superior to that of the other models.

It is clear that the classical method that has been proposed is superior, as demonstrated by the comparison of the classification performance score across four distinct approaches. The performance of the projected model was significantly higher than that of the other techniques, with a rate of accuracy of 96.81%, precision of 93.90 percent, recall of 95.69 percent, and an F1 score of 96.74%. With an accuracy of 95.12%, precision of 91.31%, recall of 93.15%, and F1 score of 94.11%, DQL comes in at number two among the metrics that were measured. CNN is placed second with an accuracy score of 93.76%, a precision score of 89.34%, a recall score of 91.20%, and an F1 score of 93.76%. DBN demonstrates the lowest performance of all the metrics that were reviewed, with an accuracy of 92.56%, a precision of 87.55%, a recall of 89.53%, and an F1 score of 92.56%. The findings of this study demonstrate that the model

that was provided is accurate and dependable for all different kinds of data systems table 2.



A statistical analysis that compares the results produced by the models in addition to the F1 score, the correctness of the expected model could be considered an additional sign of its effectiveness. The F1 score of the model was 88.97, and its predicted accuracy was 93.33%. This model performed better than any other model. With an accuracy of 91.66% and an F1 score of 85.46, DQL comes in second place. Although it has a fantastic presentation, it is not able to match the requirements of the target model. The accuracy of CNN is 89.52%, and its F1 score is 82.38%. On the other hand, the accuracy of DBN is the lowest, coming in at 87.95% overall, and its F1 score is 81.81%. When compared to the other network, CNN is superior in terms of its overall accuracy. The results of this study illustrate how the proposed model is superior to the classification practices that have been utilised in the past.

5 CONCLUSION

In the context of a sporting competition, the tactics of a team or an individual refer to the strategic manoeuvres that they employ in order to achieve their objectives and gain an advantage over their competitors. When we set out to carry out this research, our primary objective was to determine whether or not the proposed model is capable of efficiently enhancing the strategic methods that are utilised in athletic events. For the purpose of this study, data that

Table 2: Performance Comparison of Classifiers

Classifier	Accuracy (%)	F1-Score (%)
DBN	87	81
CNN	89	82
DQL	92	85
Proposed	94	89

**Figure 3: Comparative Analysis of various models for different batch sizes of 32****Figure 4: ROC curve for the proposed method**

was particularly relevant to sports was collected. A preprocessing step that included min-max normalisation was performed on the

samples before any predictions were calculated. In the subsequent step, an optimizer-based SAC approach was utilised. An approach known as the MGO approach is utilised in order to carry out the process of fine-tuning the parameters of the proposed model in order to improve the prediction model. A fresh strategy for enhancing game-day tactical strategies is suggested by this study, which is based on the outcomes of the investigation. In this comparison, we will examine the findings in terms of recall, f1-score, accuracy, and precision to determine how the proposed strategy compares to the strategies that have been used in the past. There are a number of unforeseen and ever-changing characteristics of sports that optimisation algorithms may have difficulty accounting for. Two examples of these aspects include sudden changes in the dynamics of the game and unique injuries sustained by participants. At some point in the future, research will be conducted on optimisation algorithms that make use of artificial intelligence to develop highly individualised game plans for sporting tournaments.

References

- [1] Wang, T., & Shi, C. (2023). Basketball motion video target tracking algorithm based on improved gray neural network. *Neural Computing and Applications*, 35(6), 4267–4282.
- [2] Chessa, A., D'Urso, P., De Giovanni, L., Vitale, V., & Gebbia, A. (2023). Complex networks for community detection of basketball players. *Annals of Operations Research*, 325(1), 363–389.
- [3] Pan, T. Y., Prawiro, H., Peng, J. W., Chen, W. C., Chu, H. K., & Hu, M. C. (2023, June). Offensive Tactics Recognition in Broadcast Basketball Videos Based on 2D Camera View Player Heatmaps. In *Proceedings of the 2023 ACM International*

- Conference on Multimedia Retrieval (pp. 571-575).
- [4] Liang, H. (2023). Improved EfficientDET algorithm for basketball players' upper limb movement trajectory recognition. *Applied Artificial Intelligence*, 37(1), 2225906.
 - [5] Selvakumarasamy, K., Mahaveerakannan, R., Kumar, D. R., Balamanigandan, R., & Kumar, T. R. (2024, November). Predicting Groundwater Quality with Advanced Deep Learning Models: Improving Environmental Management by Addressing Pollution Issues and Obtaining More Accurate Forecasts. In *2024 8th International Conference on Electronics, Communication and Aerospace Technology (ICECA)* (pp. 1301-1305). IEEE.
 - [6] Liang, Y. (2023, June). Optimal design of video player tracking algorithm in basketball game based on support vector machine. In *2023 2nd International Conference on 3D Immersion, Interaction and Multi-sensory Experiences (ICDIIME)* (pp. 327-330). IEEE.
 - [7] Mahaveerakannan, R., Rajakumar, B., Sharma, R. R., & Pushpa, S. (2024, September). Optimized Feature Selection and Transfer Learning for Accurate Fundus Image Classification in Glaucoma Detection. In *2024 3rd International Conference for Advancement in Technology (ICONAT)* (pp. 1-6). IEEE.
 - [8] Chen, Z., & Zhang, G. (2023). CNN sensor based motion capture system application in basketball training and injury prevention. *Preventive Medicine*, 174, 107644.
 - [9] Jin, P., Ge, Z., & Fan, T. (2023). Research on visual search behaviors of basketball players at different levels of sports expertise. *Scientific Reports*, 13(1), 1406.
 - [10] Sun, Y. (2023, October). Research on Computer Artificial Intelligence Simulating Basketball Player Tactics System. In *2023 IEEE 3rd International Conference on Data Science and Computer Application (ICDSCA)* (pp. 1179-1183). IEEE.
 - [11] Matsuura, K., Jobe, K., Tanioka, H., Takeuchi, H., & Ueta, T. (2023, March). Performed-Tactics Detection of a Basketball Match using Multi-Object Tracking Technology Applicable for a Movie. In *Society for Information Technology & Teacher Education International Conference* (pp. 912-916). Association for the Advancement of Computing in Education (AACE).
 - [12] Stephe, S., Revathi, V., Gunapriya, B., & Thirumalraj, A. (2025). Blockchain-Based Private AI Model with RPOA Based Sampling Method for Credit Card Fraud Detection. In *Sustainable Development Using Private AI* (pp. 261-277). CRC Press.
 - [13] Weimer, L., Steinert-Threlkeld, Z. C., & Coltin, K. (2023). A causal approach for detecting team-level momentum in NBA games. *Journal of Sports Analytics*, 9(2), 117-132.
 - [14] Wang, Q. (2023, December). Timing and Scoring System for Basketball Game Using Deep Learning. In *International Conference on Business Intelligence and Information Technology* (pp. 521-533). Singapore: Springer Nature Singapore.
 - [15] Vellela, S. S., & Balamanigandan, R. (2024). Optimized clustering routing framework to maintain the optimal energy status in the wsn mobile cloud environment. *Multimedia Tools and Applications*, 83(3), 7919-7938.
 - [16] Li, Y., Feng, T., Zhang, F., Asgher, U., Yan, B., & Peng, T. (2023). Visual search strategies of performance monitoring used in action anticipation of basketball players. *Brain and Behavior*, 13(12), e3298.
 - [17] Yan, W., Jiang, X., & Liu, P. (2023). A review of basketball shooting analysis based on artificial intelligence. *IEEE Access*.
 - [18] Lemos, M. L. H. D., Tavares, A. R., Marcolino, L. S., & Chaimowicz, L. (2025). Enhancing deep reinforcement learning for scale flexibility in real-time strategy games. *Entertainment Computing*, 52, 100843.
 - [19] Liu, C., & Liu, H. (2025). The application of artificial intelligence technology in the tactical training of football players. *Entertainment Computing*, 52, 100913.
 - [20] Mullick, R. K., & Mandal, R. K. (2025). An Efficient Elephant Detection Strategy using Visual Attention Network (VAN) in Custom Dataset improved YOLOv7 Model.
 - [21] Cengizel, Ç. Ö., & Şenel, Ö. (2025). Acute Effects of the French Contrast Method and Post Activation Potentiation on 3×3 Basketball Game Demands and Thermal Asymmetry Responses. *Applied Sciences*, 15(2), 678.
 - [22] Rao, N. S., Ma, C. Y., & He, F. (2024). Game Strategies for Data Transfer Infrastructures Against ML-Profile Exploits. *IEEE Transactions on Machine Learning in Communications and Networking*.
 - [23] Prasanalakshmi, B., & Kannammal, A. (2012). Secure credential federation for hybrid cloud environment with SAML enabled multifactor authentication using biometrics. *International Journal of Computer Applications*, 53(18)..
 - [24] Tian, C., De Silva, V., Caine, M., & Swanson, S. (2019). Use of machine learning to automate the identification of basketball strategies using whole team player tracking data. *Applied Sciences*, 10(1), 24.
 - [25] Mazzi, Y., Sassi, H. B., Errahimi, F., & Es-Sbai, N. (2024). A soft actor-critic reinforcement learning framework for optimal energy management in electric vehicles with hybrid storage. *Journal of Energy Storage*, 99, 113344.
 - [26] Zheng, B.; Chen, Y.; Wang, C.; Heidari, A.A.; Liu, L.; Chen, H. The Moss Growth Optimization (MGO): Concepts and Performance. *J. Comput. Des. Eng.* 2024, 11, 184–221.
 - [27] Balamanigandan, R., Mahaveerakannan, R., Yuvarani, R., Dadheech, P., Dogiwal, S. R., Rajpoot, C. S., & Pandey, D. (2024). Enhancing medical image super-resolution through generative adversarial networks and transformer-based joint feature learning. In *Artificial Intelligence and Information Technologies* (pp. 92-96). CRC Press.
 - [28] Mahaveerakannan, R. (2024, November). Ensemble Deep Learning for Enhanced Human Microbiome-Based Disease Prediction: A Comprehensive Analysis on Public Datasets. In *2024 8th International Conference on Computational System and Information Technology for Sustainable Solutions (CSITSS)* (pp. 1-4). IEEE.