

include_crawler – informal design document

```
/*
* usage: ./include_crawler [-Idir] ... file.c|file.l|file.y ...
*
* processes the c/yacc/lex source file arguments, outputting the dependencies
* between the corresponding .o file, the .c/l/y source file, and any included
* .h files
*
* each .h file is also processed to yield a dependency between it and any
* included .h files
*
* these dependencies are written to standard output in a form compatible with
* make; for example, assume that foo.c includes inc1.h, and inc1.h includes
* inc2.h and inc3.h; this results in
*
*         foo.o: foo.c inc1.h inc2.h inc3.h
*
* note that system includes (i.e. those in angle brackets) are NOT processed
*
* include_crawler uses the CPATH environment variable, which can contain a
* set of directories separated by ':' to find included files;
* if any additional directories are specified in the command line,
* these are prepended to those in CPATH, left to right
*
* for example, if CPATH is "/home/user/include:/usr/local/group/include",
* and if "-Ifoo/bar/include" is specified on the command line, then when
* processing
*         #include "x.h"
* x.h will be located by searching for the following files in this order
*
*         ./x.h
*         foo/bar/include/x.h
*         /home/user/include/x.h
*         /usr/local/group/include/x.h
*/

/*
* general design of main()
* =====
*
* 1. look up CPATH in environment
* 2. assemble directories list from ".", any -Idir flags, and fields in CPATH
*    (if it is defined)
* 3. create a master dictionary to map from file name to files upon which
*    it depends
* 4. create a workQ of files that need to be processed for #include lines
* 5. for each file argument (after -Idir flags)
*    a. insert mapping from file.o to file.ext (where ext is c, y, or l) into
*       dictionary
*    b. insert mapping from file.ext to empty list into dictionary
```

```

*   c. append file.ext on workQ
* 6. for each file on the workQ
*   a. create a linked list for names of files #include'd
*   b. invoke process(name, linkedlist, dictionary, workQ)
* 7. for each file argument (after -Idir flags)
*   a. create a set in which to track file names already printed
*   b. create a linked list to track dependencies yet to print
*   c. print "foo.o:", insert "foo.o" into set
*       and append "foo.o" to linked list
*   d. invoke print_dependencies(dictionary, printed, to_process)
*
* general design for process()
* =====
*
* 1. open the file
* 2. for each line of the file
*   a. skip leading whitespace
*   b. if match "^#include"
*       i. skip leading whitespace after "include"
*       ii. if next character is '"'
*           * collect remaining characters of file name (up to '"')
*           * append file name to dependency list for this open file
*           * if file name not already in the dictionary
*               - create empty linked list of dependencies
*               - insert mapping from file name to empty list in dictionary
*               - append file name to workQ
* 3. close file
*
* general design for print_dependencies()
* =====
*
* 1. while there is still a file in the to_process linked list
* 2. fetch next file from to_process
* 3. lookup up the file in the dictionary, yielding the linked list of deps
* 4. while there is a next element
*   a. if the filename is already in the printed hash table, continue
*   b. print the filename
*   c. insert into printed
*   d. append to to_process
*
* Additional helper functions
* =====
*
* parse_file() - breaks up filename into root and extension
* open_file() - attempts to open a filename using the search path defined
*                by the directories list.
*/

```