

Lecture 16:

Recurrent Neural Networks

Visual Question Answering



Q: What endangered animal is featured on the truck?

- A: A bald eagle.**
- A: A sparrow.
- A: A humming bird.
- A: A raven.



Q: Where will the driver go if turning right?

- A: Onto 24 3/4 Rd.**
- A: Onto 25 3/4 Rd.
- A: Onto 23 3/4 Rd.
- A: Onto Main Street.



Q: When was the picture taken?

- A: During a wedding.**
- A: During a bar mitzvah.
- A: During a funeral.
- A: During a Sunday church service





Q: Who is under the umbrella?


- A: Two women.**
- A: A child.
- A: An old man.
- A: A husband and a wife.

Agrawal et al, "VQA: Visual Question Answering", ICCV 2015
Zhu et al, "Visual 7W: Grounded Question Answering in Images", CVPR 2016
Figure from Zhu et al, copyright IEEE 2016. Reproduced for educational purposes.

Visual Question Answering: RNNs with Attention



What kind of animal is in the photo?
A **cat**.



Why is the person holding a knife?
To cut the **cake** with.

Zhu et al, "Visual 7W: Grounded Question Answering in Images", CVPR 2016
Figures from Zhu et al, copyright IEEE 2016. Reproduced for educational purposes.

Multilayer RNNs

$$h_t^l = \tanh W^l \begin{pmatrix} h_t^{l-1} \\ h_{t-1}^l \end{pmatrix}$$


$h \in \mathbb{R}^n$ $W^l [n \times 2n]$

LSTM:

$W^l [4n \times 2n]$


$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \text{sigm} \\ \text{sigm} \\ \text{sigm} \\ \text{tanh} \end{pmatrix} W^l \begin{pmatrix} h_t^{l-1} \\ h_{t-1}^l \end{pmatrix}$$
$$c_t^l = f \odot c_{t-1}^l + i \odot g$$
$$h_t^l = o \odot \tanh(c_t^l)$$

depth



Vanilla RNN Gradient Flow

Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013




$$\begin{aligned} h_t &= \tanh(W_{hh}h_{t-1} + W_{hx}x_t) \\ &= \tanh\left((W_{hh} \quad W_{hx}) \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}\right) \\ &= \tanh\left(W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}\right) \end{aligned}$$

Vanilla RNN Gradient Flow

Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013


Backpropagation from h_t
to h_{t-1} multiplies by W
(actually W_{hh}^T)



$$\begin{aligned} h_t &= \tanh(W_{hh}h_{t-1} + W_{hx}x_t) \\ &= \tanh\left((W_{hh} \quad W_{hx}) \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}\right) \\ &= \tanh\left(W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}\right) \end{aligned}$$


Vanilla RNN Gradient Flow

Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013



Computing gradient
of h_0 involves many
factors of W
(and repeated \tanh)


Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013



Largest singular value < 1 :
Vanishing gradients

Vanilla RNN Gradient Flow

Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013



Computing gradient of h_0 involves many factors of W (and repeated \tanh)

Largest singular value > 1 :
Exploding gradients


Largest singular value < 1 :
Vanishing gradients

Gradient clipping: Scale gradient if its norm is too big

```
grad_norm = np.sum(grad * grad)
if grad_norm > threshold:
    grad *= (threshold / grad_norm)
```

Vanilla RNN Gradient Flow

Bengio et al, "Learning long-term dependencies with gradient descent is difficult", IEEE Transactions on Neural Networks, 1994
Pascanu et al, "On the difficulty of training recurrent neural networks", ICML 2013



Computing gradient
of h_0 involves many
factors of W
(and repeated tanh)

Largest singular value > 1 :
Exploding gradients

Largest singular value < 1 :
Vanishing gradients

→ Change RNN architecture

Long Short Term Memory (LSTM)

Vanilla RNN

$$h_t = \tanh \left(W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix} \right)$$

LSTM

$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$
$$c_t = f \odot c_{t-1} + i \odot g$$
$$h_t = o \odot \tanh(c_t)$$

Hochreiter and Schmidhuber, "Long Short Term Memory", Neural Computation
1997


Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller

Long Short Term Memory (LSTM)

[Hochreiter et al., 1997]

- f: Forget gate, Whether to erase cell
- i: Input gate, whether to write to cell
- g: Gate gate (?), How much to write to cell
- o: Output gate, How much to reveal cell




$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$

$$c_t = f \odot c_{t-1} + i \odot g$$

$$h_t = o \odot \tanh(c_t)$$

Long Short Term Memory (LSTM)


[Hochreiter et al., 1997]



$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$
$$c_t = f \odot c_{t-1} + i \odot g$$
$$h_t = o \odot \tanh(c_t)$$

Long Short Term Memory (LSTM): Gradient Flow

[Hochreiter et al., 1997]




Backpropagation from c_t to c_{t-1} only elementwise multiplication by f , no matrix multiply by W

$$\begin{pmatrix} i \\ f \\ o \\ g \end{pmatrix} = \begin{pmatrix} \sigma \\ \sigma \\ \sigma \\ \tanh \end{pmatrix} W \begin{pmatrix} h_{t-1} \\ x_t \end{pmatrix}$$
$$c_t = f \odot c_{t-1} + i \odot g$$
$$h_t = o \odot \tanh(c_t)$$

Long Short Term Memory (LSTM): Gradient Flow

[Hochreiter et al., 1997]


Uninterrupted gradient flow!




Long Short Term Memory (LSTM): Gradient Flow

[Hochreiter et al., 1997]

Uninterrupted gradient flow!



Similar to ResNet!




Subhransu Maji, Chuang Gan and TAs

Some slides kindly provided by Fei-Fei Li, Jiajun Wu, Erik Learned-Miller


Long Short Term Memory (LSTM): Gradient Flow

[Hochreiter et al., 1997]

Uninterrupted gradient flow!



Similar to ResNet!



In between:
Highway Networks

$$g = T(x, W_T)$$

$$y = g \odot H(x, W_H) + (1 - g) \odot x$$

Srivastava et al, "Highway Networks",
ICML DL Workshop 2015

Other RNN Variants

GRU [*Learning phrase representations using rnn encoder-decoder for statistical machine translation*, Cho et al. 2014]

$$r_t = \sigma(W_{xr}x_t + W_{hr}h_{t-1} + b_r)$$

$$z_t = \sigma(W_{xz}x_t + W_{hz}h_{t-1} + b_z)$$

$$\tilde{h}_t = \tanh(W_{xh}x_t + W_{hh}(r_t \odot h_{t-1}) + b_h)$$

$$h_t = z_t \odot h_{t-1} + (1 - z_t) \odot \tilde{h}_t$$

[*LSTM: A Search Space Odyssey*, Greff et al., 2015]

[*An Empirical Exploration of Recurrent Network Architectures*, Jozefowicz et al., 2015]

MUT1:

$$z = \text{sigm}(W_{xz}x_t + b_z)$$

$$r = \text{sigm}(W_{xr}x_t + W_{hr}h_t + b_r)$$

$$h_{t+1} = \tanh(W_{hh}(r \odot h_t) + \tanh(x_t) + b_h) \odot z + h_t \odot (1 - z)$$

MUT2:

$$z = \text{sigm}(W_{xz}x_t + W_{hz}h_t + b_z)$$

$$r = \text{sigm}(x_t + W_{hr}h_t + b_r)$$

$$h_{t+1} = \tanh(W_{hh}(r \odot h_t) + W_{xh}x_t + b_h) \odot z + h_t \odot (1 - z)$$

MUT3:

$$z = \text{sigm}(W_{xz}x_t + W_{hz} \tanh(h_t) + b_z)$$

$$r = \text{sigm}(W_{xr}x_t + W_{hr}h_t + b_r)$$


$$h_{t+1} = \tanh(W_{hh}(r \odot h_t) + W_{xh}x_t + b_h) \odot z + h_t \odot (1 - z)$$

Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T

Encoder: $h_t = f_W(x_t, h_{t-1})$




Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T

Encoder: $h_t = f_W(x_t, h_{t-1})$ From final hidden state predict:
Initial decoder state s_0
Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Problem: Input sequence bottlenecked through fixed-sized vector. What if

Sequence to Sequence with RNNs

Input: Sequence x_1, \dots, x_T

Output: Sequence y_1, \dots, y_T


Decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c)$

Encoder: $h_t = f_W(x_t, h_{t-1})$

From final hidden state predict:

Initial decoder state s_0

Context vector c (often $c=h_T$)



Problem: Input sequence bottlenecked through fixed-sized vector. What if


Idea: use new context vector at each step of decoder!

Sequence to Sequence with RNNs and Attention

Input: Sequence x_1, \dots, x_T

Output: Sequence $y_1, \dots, y_{T'}$


Encoder: $h_t = f_W(x_t, h_{t-1})$ From final hidden state:
Initial decoder state s_0




Sequence to Sequence with RNNs and **Attention**

Compute (scalar) **alignment scores**

$$e_{t,i} = f_{\text{att}}(s_{t-1}, h_i) \quad (f_{\text{att}} \text{ is an MLP})$$



Sequence to Sequence with RNNs and Attention




Compute (scalar) **alignment scores**

$$e_{t,i} = f_{\text{att}}(s_{t-1}, h_i) \quad (f_{\text{att}} \text{ is an MLP})$$

Normalize alignment scores
to get **attention weights**

$$0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$$

Sequence to Sequence with RNNs and **Attention**




Compute (scalar) **alignment scores**
 $e_{t,i} = f_{\text{att}}(s_{t-1}, h_i)$ (f_{att} is an MLP)

Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$

Compute context vector as linear combination of hidden states
 $c_t = \sum_i a_{t,i} h_i$

[START]

Sequence to Sequence with RNNs and **Attention**



Compute (scalar) **alignment scores**
 $e_{t,i} = f_{att}(s_{t-1}, h_i)$ (f_{att} is an MLP)


Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$

Compute context vector as linear combination of hidden states

$$c_t = \sum_i a_{t,i} h_i$$

Use context vector in decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c_t)$

Sequence to Sequence with RNNs and Attention



Compute (scalar) **alignment scores**
 $e_{t,i} = f_{\text{att}}(s_{t-1}, h_i)$ (f_{att} is an MLP)

Normalize alignment scores to get **attention weights**
 $0 < a_{t,i} < 1 \quad \sum_i a_{t,i} = 1$

Compute context vector as linear combination of hidden states


$$c_t = \sum_i a_{t,i} h_i$$

Use context vector in decoder: $s_t = g_U(y_{t-1}, s_{t-1}, c_t)$


This is all differentiable! No supervision on attention weights – backprop through everything

Sequence to Sequence with RNNs and Attention


Repeat: Use s_1 to compute new context vector c_2



Sequence to Sequence with RNNs and Attention




Sequence to Sequence with RNNs and Attention



Sequence to Sequence with RNNs and Attention

Use a different context vector in each timestep of decoder

- Input sequence not bottlenecked through single vector
- At each timestep of decoder, context vector “looks at” different parts of the input sequence




Sequence to Sequence with RNNs and Attention

Example: English to French translation

Input: “The agreement on the European Economic Area was signed in August 1992.”

Output: “L'accord sur la zone économique européenne a été signé en août 1992.”

Visualize attention weights $a_{t,i}$



Sequence to Sequence with RNNs and Attention

Example: English to French translation


Input: “**The agreement on the** European Economic Area was signed **in August 1992.**”

Output: “**L'accord sur la** zone économique européenne a été signé **en août 1992.**”

Diagonal attention means words correspond in order

Diagonal attention means words correspond in order

Visualize attention weights $a_{t,i}$



Sequence to Sequence with RNNs and Attention

Example: English to French translation

Input: “The agreement on the European Economic Area was signed in August 1992.”


Output: “L’accord sur la zone économique européenne a été signé en août 1992.”

Diagonal attention means words correspond in order

Attention figures out different word orders

Diagonal attention means words correspond in order


Visualize attention weights $a_{t,i}$



Sequence to Sequence with RNNs and Attention

The decoder doesn't use the fact that h_i form an ordered sequence – it just treats them as an unordered set $\{h_i\}$

Can use similar architecture given any set of input hidden vectors $\{h_i\}$!



Summary

- RNNs allow a lot of flexibility in architecture design
- Vanilla RNNs are simple but don't work very well
- Common to use LSTM or GRU: their additive interactions improve gradient flow
- Backward flow of gradients in RNN can explode or vanish. Exploding is controlled with gradient clipping. Vanishing is controlled with additive interactions (LSTM)
- Better/simpler architectures are a hot topic of current research
- Better understanding (both theoretical and empirical) is needed.