

Masters Thesis on
**Benchmarking Somatic Variant
Callers**

By R. S. Chintalapati

29th April 2021

Declaration

I hereby declare, that I am the sole author and composer of my thesis and that no other sources or learning aids, other than those listed, have been used. Furthermore, I declare that I have acknowledged the work of others by providing detailed references of said work.

I hereby also declare, that my Thesis has not been prepared for another examination or assignment, either wholly or excerpts thereof.

Place, Date

Signature

Abstract

Variant calling pipelines consists of two main types, aimed at quantifying different types of variant namely Germline (inheritable variants) and Somatic (uninheritable variants). In terms of benchmarking, many Germline variant calling pipelines were compared and documented by the standards of the Genome in a Bottle (GIAB) Consortium [1]. For Somatic variant calling pipelines, only a few comparisons were achieved because the comparisons are more complex and less well-established. In the diploid human genome, a variant can be found either homozygously, heterozygously or not at all. Tumors, on the other hand, are inhomogeneous cells that might carry variants possibly with rare mutations not found in the others making the Somatic variant calling pipelines benchmarking challenging. Due to the diverse natures of these two types of analysis, the goal of this thesis is to benchmark a select few datasets, in order to establish a reliable variant caller for cancer research.

Contents

1	Introduction	5
2	Literature Study	9
2.1	Background Study	9
2.2	Galaxy	10
2.3	Tools	11
2.4	Research Papers	11
3	Background	13
3.1	Map Workflow	13
3.2	Filter Workflow	14
3.3	WES Analysis Workflow	15
4	Approach	18
4.1	Inputs	18
4.2	Execution	19
4.3	Columns in VCFs	20
4.4	Operations	21
5	Experiments	22
5.1	Positions, SNPs, & Indels	22
5.2	Allele Frequencies	23
5.3	Read Depths	24
5.4	Variant Combination Bias	24
5.5	Benchmarking	24
6	Results	25
6.1	Positions, SNPs & Indels	26

6.2	Variants	26
6.3	Allele Frequencies	28
6.4	Read Depth	29
7	Conclusions	41

Chapter 1

Introduction

A variant is a type of mutation that differs in some respect from a reference genome/transcriptome standard, where a variant in bioinformatics is an alteration in the most common DNA/RNA nucleotide sequence. It is defined based on the type of DNA/RNA error and can be used to describe an alteration that may be benign, pathogenic or of unknown significance.

Based on the way they occur, variants are of two types i.e. Germline variants and Somatic variants. Germline variants are a gene change in the egg or sperm that are incorporated into the DNA of every cell in the offspring from the parent. These hereditary variants are even referred to as Germline mutations. Somatic variants are alterations in the DNA that occur after conception and can occur in any cell of the body except the germ cells i.e. egg and sperm cells. Therefore, Somatic variants cannot be passed on to children.

The process to identify the variants is called Variant Calling and the variants are identified from the sequence data obtained through sequencing. Sequencing is the operation of determining the precise order of the four bases Adenine (A), Guanine (G), Cytosine (C) and Thymine (T) in a DNA strand.

In terms of sequencing, there is Whole Genome Sequencing (WGS) or Whole Exome Sequencing (WES). In WGS, also known as full genome sequencing, the DNA sequence of an entire organism's genome is determined at a single time. WES is also known as Exome Sequencing is a genomic technique for sequencing all of the protein-coding regions of genes in a genome also known as exomes.

Through one of the sequencing techniques, FASTQ files which are a text-based format for storing both a biological sequence and its corresponding quality scores are obtained. These FASTQ files are then aligned based on a reference genome thereby creating a BAM file which is a compressed binary version of a SAM file or the human-readable text file with biological sequences aligned to a reference sequence.

Using the BAM files, differences between the aligned reads and the reference genome can be written into a Variant Call Format (VCF) file. This process of identifying variants from the sequence data is called Variant Calling and this process is different for both Germline and Somatic variant calling.

In the Germline variant calling, the reference genome is standard for the species of interest and the genomes are diploid. So at any given locus, either all reads have the same base, indicating homozygosity or approximately half the reads have one base and the other half have another indicating heterozygosity with the only exception being the sex chromosomes in the male mammals. In Somatic variant calling, the reference is tissue from the same individual with mosaicism between the cells, where mosaicism is when a person has two or more genetically different sets of cells in their body.

The goal of this thesis is to benchmark Somatic variant callers based on their ability to identify cancer-causing variants. To perform the comparison, we require the Truth Data to which the variant calling outcomes or the VCF files are compared should know. Therefore, the artificial dataset pair for Somatic variant calling by the GIAB project available from the GIAB FTP site is considered the Truth Data and based on the comparisons, the effectiveness of the Somatic variant callers is determined.

There are several variant callers for both Germline and Somatic variant calling. Some commonly-used Germline variant callers are FreeBayes, Strelka2, VarScan, and Beagle. Similarly, some common Somatic variant callers are LoFreq, MuSE, MuTect2, SomaticSniper, Strelka, VarScan and VarDict. The choice of the variant callers that are benchmarked in this thesis is dependent on work done by Dr Wolfgang Maier and Dr Björn Grüning, with data from Use Case 3 of the German MIRACUM initiative [2].

The Medical Informatics in Research and Care in University Medicine (MIRACUM) initiative has three use cases and the referred third use case is “From Knowledge to Action - Support for Molecular Tumor Boards”. A tumor board is a group of doctors and health care providers with different specialities meeting regularly to discuss cancer cases and share knowledge¹. In contrast to traditional cancer tumor boards, molecular tumor boards are made up of cancer experts across specialities as well as researchers with expertise on a variety of cancer types, gene sequencing technologies and genomic data, who work together to make informed treatment decisions[3].

The MIRACUM consortium aims to support Molecular Tumor Boards with innovative IT solutions by improving the complex processes of quality assurance, data preparation, data analysis, data integration and information retrieval between genetic high-throughput analysis and medical therapy decisions. Additionally, clinicians will be offered decision support through efficient data visualization[2].

Using Galaxy an open web-based platform that provides accessibility, reproducibility, and transparency, Dr Wolfgang Maier built two workflows that are supported by the MIRACUM partners². A workflow is a series of tools and dataset actions that run in a sequence as a batch operation. The first workflow is the WES tumour/normal sample pair analysis and the second is gene panel data with only the tumor sample.

The major difference between the two workflows is the variant calling software used in them. For the first workflow or the WES tumor/normal sample pair analysis workflow, VarScan Somatic is used and for the second workflow or the gene panel data workflow, LoFreq Call is used.

For this thesis, the WES tumor/normal sample pair analysis workflow is used to obtain VCF files through VarScan Somatic variant caller. Aside from this, the Strelka variant caller is also added to the workflow using Galaxy and the outcomes from both the variant callers are compared to the artificial truth data considered from the GIAB FTP site to benchmark.

¹<https://cancer.net/blog/2017-07/what-tumor-board-expert-qa>

²<https://github.com/AG-Boerries/MIRACUM-Pipe-Galaxy>

This report comprises a total of six sections and is outlined as follows. The first section is ‘Introduction’ dealing with the basics needed to approach the thesis. The second section is ‘Literature Study’ encompassing articles, research papers, tools and websites that helped the thesis. The third section is ‘Background’ dealing with acquiring workflows, modifying tools, setting parameters to obtain the VCF files etc. The fourth section is ‘Approach’ dealing each step starting from writing ymal files, using Planemo, understanding the tools, reading VCF files etc.

The fifth section is ‘Experiments’ dealing with different comparisons, bias and benchmarking methods. The sixth section is ‘Results’ dealing with the outcomes of the experiments in terms of positions, SNPs, allele frequencies, read depths, variant combinations, and INDELs. The seventh section is ‘Conclusion’ dealing with the choice of the variant caller based on the results and scope for future work.

Chapter 2

Literature Study

Out of the numerous ways to approach the thesis, the first section ‘Background Study’ deals with comprehending the scope of the topic. In the second section, the platform needed to execute the goal i.e. Galaxy [4] and its concepts are dealt with. In the third section, tasks and tools used based on the information obtained from the Galaxy are mentioned and in the last section, research papers related to the thesis are presented.

2.1 Background Study

An introduction to variant calling can be learnt from “Introduction to Variant Calling¹” and the difference between the mutations in Germline and Somatic can be learnt from BioNinja². To upload and update the progress of the thesis, GitHub is used and the operations from GitHub are learnt from “Version Control with Git and GitHub [5]”.

To comprehend information about the third use case of which the thesis is a part, as well as to gain access to the workflows that are used for the variant calling based on MIRACUM [2], the MIRACUM Pipe Galaxy portal³ was used. The first of the two workflows i.e. WES tumor/normal sample pair

¹<https://training.galaxyproject.org/training-material/topics/variant-analysis/slides/introduction.html#1>

²<https://ib.bioninja.com.au/standard-level/topic-3-genetics/33-meiosis/somatic-vs-germline-mutatio.html>

³<https://github.com/AG-Boerries/MIRACUM-Pipe-Galaxy>

analysis workflow⁴ is selected for VarScan Somatic variant calling and Strelka variant calling. For information about the variant callers, refer VarScan Somatic [8] and Strelka Somatic [9].

For benchmarking, visit GIAB [6] and for the tools needed for benchmarking as per the GIAB standards, visit Germline Small Variant Benchmarking Tools and Standards⁵. For the forward reads, reverse reads, bed file, and truth vcf file, visit the GIAB FTP site⁶.

2.2 Galaxy

In Galaxy, the training materials can be accessed from Galaxy Training [7] and for an introduction to variant calling, the Variant Analysis subtopic was used. In the Variant Analysis training, for an introduction to the tools for “Exome Sequencing”, refer to the tutorial “Exome sequencing data analysis for diagnosing a genetic disease [10][11]” and for “Somatic Variant Calling”, visit the tutorial “Identification of Somatic and Germline Variants from Tumor and Normal Sample Pairs [12][13]”.

To execute the selected MIRACUM workflow, use Galaxy Workflow Executor⁷ or workflow2executable⁸. In the Galaxy Workflow Executor, the creation of the yaml file is mentioned briefly. For more detailed information about creating yaml files, visit Toolshed Yaml⁹. With the yaml creation, Planemo can be used to execute workflows through the command line. For information about Planemo, visit Planemo Quick Start¹⁰.

⁴<https://github.com/AG-Boerries/MIRACUM-Pipe-Galaxy/tree/master/workflows>

⁵<https://github.com/ga4gh/benchmarking-tools/>

⁶ftp://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/use_cases/mixtures/UMCUTRECHT_NA12878_NA24385_mixture_10052016/

⁷<https://github.com/ebi-gene-expression-group/galaxy-workflow-executor>

⁸<https://github.com/mvdbeek/workflow2executable>

⁹https://galaxy-iuc-standards.readthedocs.io/en/latest/best_practices/shed_yaml.html

¹⁰<https://planemo.readthedocs.io/en/latest/readme.html>

2.3 Tools

Except for the tools in the WES tumor/normal sample pair analysis workflow, for the comparison of the VCF files from the variant callers three tools are used. For power statistics for VCF files, we can use the vcfstats tool suite¹¹. For comparing files, summarising variants, merging files, filtering variants and converting to different file types, visit vcftools¹². For comparing SNPs and positions in VCF files, visit vcftoolz¹³.

For calculating allele frequency from VCF files, visit vcftools¹⁴ and for calculating allele frequency for Strelka VCF files, visit Strelka User Guide¹⁵. For plotting allele frequency based on VCF files in terms of regions or whole-genome, visit afplot¹⁶ and for plotting any outcome data, visit Matplotlib¹⁷. For operations on VCF files, visit Filtering and Handling VCFs¹⁸.

2.4 Research Papers

For reference, in terms of Germline variants comparison, Systematic comparison of germline variant calling pipelines cross multiple next-generation sequencers by Jiayun Chen, et al talk about variant calling performance of 12 combinations in WES datasets testing three variant calling pipelines HaplotypeCaller, Strelka2 and Samtools-VarScan2.

In terms of Somatic variant calling comparison, Systematic comparison of somatic variant calling performance among different sequencing depth and mutation frequency by Zixi Chen, et al talk about mutation frequency as a major problem and increasing sequencing depth as a method to improve the mutation calling performance. Using Strelka2 and Mutect2 tools, the performance of 30 combinations of sequencing depth and mutation frequency

¹¹<https://vcfstats.readthedocs.io/en/latest/>

¹²<http://vcftools.sourceforge.net/index.html>

¹³<https://vcftoolz.readthedocs.io/en/latest/readme.html>

¹⁴<https://vcftools.github.io/documentation.html#freq>

¹⁵<https://github.com/Illumina/strelka/blob/v2.9.x/docs/userGuide/README.md#somatic>

¹⁶<https://github.com/sndrtj/afplot>

¹⁷<https://matplotlib.org/>

¹⁸https://speciationgenomics.github.io/filtering_vcf/

is observed.

Chapter 3

Background

The VCF files that are to be benchmarked in comparison to the Truth Data are an outcome of the Map, Filter and WES analysis workflows. In these Galaxy workflows, the WES analysis workflow is supported by the MIRACUM partners and was built and parameterised by Dr Wolfgang Maier in MIRACUM Pipe Galaxy¹. The Map workflow is a sub-workflow of the WES analysis workflow and the Filter workflow was built by Dr Mehmet Tekman specifically for this thesis to reduce the input size.

3.1 Map Workflow

In the Map workflow, there are three sections. The first section is about the inputs i.e. the forward and reverse reads, the second section is about trimming the unneeded reads and the third section is about mapping the trimmed reads to the reference reads.

In the input section, for the Somatic variant calling, there are two types of samples i.e Normal and Tumor samples. Therefore, there are Normal forward reads, Normal reverse reads, Tumor forward reads and Tumor reverse reads. In the flowchart, the Forward Reads are represented by FR and the Reverse Reads for both Normal and Tumor samples are represented by RR.

In the second section, forward and reverse reads of both normal and tumor samples are trimmed based on the minimum quality per base, minimum

¹<https://github.com/AG-Boerries/MIRACUM-Pipe-Galaxy/tree/master/workflows>




Figure 3.1: Sequence of tools in Map workflow.

length of the reads and a few other conditions. Using the Trimmomatic tool in Galaxy, either the paired-end or the single-ended reads are trimmed. In the flowchart, Tr represents all the trimming operations.

In the third section, the trimmed forward and reverse reads of Normal and Tumor samples are mapped with the reference genome i.e. Human Feb. 2009 (GRCh37/hg19)(hg19). Using the 'Map with BWA-MEM tool' in Galaxy, Normal forward and reverse reads are mapped into 'Mapped reads of Normal' and Tumor forward and reverse reads are mapped into 'Mapped reads of Tumor'. In the flowchart, M represents the mapping operation.

3.2 Filter Workflow

In the Filter workflow, there are three sections. The first section is about the inputs i.e. the mapped reads, capture regions, forward and reverse reads. The second section is about filtering mapped reads based on the capture regions and the third section is about filtering forward and reverse reads of Normal and Tumor samples based on the filtered mapped reads.

In the first section, the considered inputs are the outcome of the Mapped workflow or the mapped Normal and Tumor samples for forward and reverse reads, capture regions represented in a BED file, Normal forward reads, Normal reverse reads, Tumor forward reads and Tumor reverse reads. In the flowchart, Mapped forward and reverse reads for both Normal and Tumor samples are represented by M, the Capture Regions file is represented by CR, the Forward Reads are represented by FR and the Reverse Reads are represented by RR for both Normal and Tumor samples.




Figure 3.2: Sequence of tools in Filter workflow.

In the second section, based on the capture regions, the mapped Normal and Tumor samples for forward and reverse reads are filtered using the Samtools view tool from Galaxy. This tool filters and subsamples alignments as per the user requirement and generates a bam file as the outcome.

In the third section, based on the bam file from the Samtools, the forward reads and reverse reads for both Normal and Tumor samples represented by FR and RR in the flowchart are mapped to create the Mapped Normal and Tumor samples for forward and reverse reads. Using the 'Filter Sequences by Mapping' tool in Galaxy, the selected reads in the bam file are mapped with forward and reverse reads for both Normal and Tumor samples. In the flowchart, these outcomes are represented by FFR for Filtered Forward Reads and FRR for Filtered Reverse Reads.

3.3 WES Analysis Workflow

In the WES Analysis workflow, there are five sections. The first section is about the inputs i.e. Normal filtered forward reads, Normal filtered reverse




Figure 3.3: Sequence of tools in WES Analysis workflow.

reads, Tumor filtered forward reads, and Tumor filtered reverse reads. The second section is about trimming filtering reads, the third section is about mapping the trimmed filtered reads, the fourth section is about postprocessing the mapped trimmed reads and the fifth section is about variant calling.

In the first section, the considered inputs are the outcome of the Filter workflow or the Filtered Normal and Tumor samples for forward and reverse reads, sample names, and purity estimates. In the flowchart, Filtered Normal and Tumor samples for forward and reverse reads are represented by FFR and FRR, sample names are represented by NM, and purity estimates are represented by PR.

In the second section, Filtered forward and reverse reads of both normal and tumor samples are trimmed based on the minimum quality per base, minimum length of the reads and a few other conditions. Using the Trimmomatic tool in Galaxy, either the paired-end or the single-ended reads are trimmed. In the flowchart, Tr represents all the trimming operations.

In the third section, the trimmed Filtered forward and reverse reads of Normal and Tumor samples are mapped with the reference genome i.e. Human Feb. 2009 (GRCh37/hg19)(hg19). Using the 'Map with BWA-MEM tool' in Galaxy, trimmed Filtered normal forward and reverse reads are mapped into 'Mapped reads of Normal' and Tumor forward and reverse reads

are mapped into 'Mapped reads of Tumor'. In the flowchart, M represents the mapping operation.

In the fourth section, the Mapped reads of Normal and Mapped reads of Tumors are processed to filter the paired-end reads of all samples to retain only those read pairs, for which both the forward and the reverse read have been mapped to the reference successfully and to deduplicate, reads[10][11]. The outcome of this process is a bam file and in the flowchart, P represents the Post-mapping operation.

In the fifth section, with the bam input from the Post-mapping operation, sample names and purity estimates for both the Normal and Tumor samples, the variant calling is performed. The choice of the variant caller in the WES workflow is VarScan Somatic with minimum base quality of 28, minimum mapping quality of 1, minimum coverage of 8 and minimum variant allele frequency 0.1. Along with VarScan somatic, Strelka somatic could also be implemented. The outcome of this process is vcf files and in the flowchart, VC represents Variant Callers.

Chapter 4

Approach

Starting from the Input data until performing experiments on the VCF files, there are four steps involved. The first step is obtaining the input data and the capture regions, the second step is executing the Map, Filter and WES Analysis workflows, the third step is selecting the necessary columns for operations and the fourth step is about performing operations like count, sum, comparisons and variant combinations on the VCF files.

4.1 Inputs

The list of inputs needed to obtain the VCF files is based on the Map, Filter and WES Analysis workflows. For the Map workflow, the needed files are Normal forward reads, Normal reverse reads, Tumor forward reads, and Tumor reverse reads. For the Filter workflow, the needed files are Normal forward reads, Normal reverse reads, Tumor forward reads, Tumor reverse reads, Capture Regions, mapped Normal reads, and mapped Tumor reads.

For the WES Analysis workflow, the needed files are Normal sample name, Tumor sample name, Normal purity estimate, Tumor purity estimate, mapped Normal forward reads, mapped Normal reverse reads, mapped Tumor forward reads, mapped Tumor reverse reads. Along with these inputs, Truth Data or the Truth VCF file is needed to compare the VCF outcomes.

The input for the Map workflow and the Truth Data can be downloaded

from GIAB FTP site¹ and the Capture Regions needed for the Filter workflow can be downloaded from MIRACUM Annotation Data². Except for these inputs, the rest of the inputs are created while executing the workflows.

From the user end, Normal sample name, Tumor sample name, Normal purity estimate, Tumor purity estimate are needed and purity estimates are always between 0.0 to 1.0. In this thesis, the Normal purity estimate is always 1.0 and the Tumor purity estimate which represents the percentage of cancer cells in a solid tumor sample are 0.3, 0.5 and 0.7 in every experiment.

4.2 Execution

The Map, Filter and WES Analysis workflows can be executed either through the command line or through Galaxy. When executing through the command line, choose the Galaxy domain, set up the workflow, create the yaml file and then use the planemo command to execute the workflow. Example YAML files for the three workflows can be accessed at Appendix A.

```
planemo run workflow.ga
params.yml
--galaxy_url https://usegalaxy.eu/
--galaxy_user_key APIKEY
--engine external_galaxy
--no_shed_install
```

If executing through Galaxy, import the workflow at usegalaxy.eu and run the workflow. In the three workflows, Map workflow should be executed first for the Mapped Normal and Tumor reads. Using the Map workflow outcomes, Filter workflow should be executed to obtain mapped forward and reverse reads for Normal and Tumor samples. Using the Filter workflow outcomes, the WES Analysis workflow should be executed.

By using Galaxy, the outcomes of one workflow can be dragged and dropped into the new workflow without any processing time. The need for

¹ftp://ftp-trace.ncbi.nlm.nih.gov/giab/ftp/use_cases/mixtures/UMCUTRECHT_NA12878_NA24385_mixture_10052016/

²<https://usegalaxy.eu/u/wolfgang-maier/h/miracum-annotation-data>

three workflows when the WES Analysis workflow alone could produce the VCF files is because using the other workflows, the input data size is reduced by selecting only the reads that map and belong to the capture regions.

4.3 Columns in VCFs

After executing the workflows, VCF outcomes using Strelka and VarScan variant callers with Tumor purity estimate of 0.3, 0.5 and 0.7 are obtained and the columns in all of the VCFs are CHROM, POS, ID, REF, ALT, QUAL, FILTER, INFO, FORMAT, NORMAL, TUMOR.

CHROM is typically a chromosome, POS is the position of a variation in a sequence, ID is the identifier of the variation, REF is the reference base or bases, ALT is the list of alternative alleles, QUAL is the quality score of the alleles, FILTER indicates if a given set of filters passed or not, INFO and FORMAT columns have sub-fields that vary as per the variant caller and SAMPLEs column has NORMAL and TUMOR samples.

Of these columns, ID, QUAL, FILTER and INFO aren't used either in comparison or benchmarking. Of the other columns, CHROM column value is sometimes just a number i.e. 12 and sometimes a string concatenated with a number i.e. chr12. To compare the VCF files, the CHROM values in both of the files should be consistent. To add chr, use the command

```
awk '{
if($0 !~ /^#/ )
print "chr"$0;
else if(match($0,/##contig=<ID>(.*)/,m))
print m[1]"chr"m[2];
else print $0
}' no_chr.vcf > with_chr.vcf
```

With the chr, CHROM column can be used to segregate reads based on chromosomes. To segregate, use the command and replace chrno to the specific chromosome. For example, chr12

```
grep -w '^#\|^chrno' old_file.vcf > new_file.vcf
```

4.4 Operations

With consistent VCF files, three operations are to be performed to determine the better variant caller for detecting cancer-causing variants. These three operations are comparisons, bias detection and benchmarking. To perform the operations, specific columns from the VCF files should be selected. The command to select the needed columns is

```
cut -f column_numbers old_file.vcf > new_file.vcf
```

Replace the column_numbers with integers based on the column occurrence in VCF files starting from 1 and separate the list with commas if there are couple of columns to be selected i.e 1-3,5.

When performing operations on the selected columns in the VCF files by considering them as csv or tabular files, the header information presented in the VCF files explaining the columns aren't needed. To delete the header information, use the command

```
sed '/^#/d' old_file.vcf > new_file.vcf
```

Chapter 5

Experiments

For the comparison, bias and benchmarking, there are five experiments performed. The first experiment is comparing the positions, SNPs and Indels between the VCF files and the truth data. The second experiment is comparing the allele frequencies between the VCF files. The third experiment is comparing the read depths between the VCF files in comparison to the truth data. The fourth experiment is comparing the sixteen variant combinations between the VCF files and truth data. The fifth experiment would be benchmarking the variant callers based on the True Positives, True Negatives, False Positives and False Negatives. Based on the conclusions of these experiments, the choice of the variant caller between Strelka and VarScan is determined for detecting cancer-causing variants.

5.1 Positions, SNPs, & Indels

A single-nucleotide polymorphism is a substitution of a single nucleotide at a specific position in the genome that is present in a sufficiently large fraction of the population and an Indel is a molecular biology term for an insertion or deletion of bases in the genome of an organism. In the first experiment, positions, SNPs and Indels are compared between the variant caller outcomes and actual data to observe how many variant positions, SNPs and Indels match between the variant calling outcomes and truth data.

This comparison can be done using the VCFToolz by using the command

```
vcftoolz compare file1.vcf file2.vcf file3.vcf > output.txt
```

This tool notes the differences in a text file alongside plotting venn diagrams showing the common and different positions and SNPs between the compared files. However, the number of SNPs aren't consistent with the number of position atleast for the input files considered for the thesis and the Indels aren't even compared by this tool.

So by using the specific code written for this thesis in Appendix D, positions, SNPs and Indels are compared. To execute the code in Appendix D, files with only SNPs and files with only Indels are needed. To obtain the file with only SNPs, use the command

```
vcftools --vcf input_file.vcf --remove-indels --recode  
--recode-INFO-all --out SNPs_only
```

To obtain the file with only Indels, use the command

```
vcftools --vcf input_file.vcf --keep-only-indels --recode  
--recode-INFO-all --out INDELS_only
```

Using these files, `len` and `merge` operations along with `matplotlib` package, the comparison of the positions, SNPs and Indels in terms of their `count` are listed in tables and represented in venn diagrams.

5.2 Allele Frequencies

Allele frequency, or gene frequency is defined as the relative frequency of an allele at a particular locus in a population, expressed as a fraction or percentage. In the second experiment, the number of positions within specific allele frequencies limits are tabulated and plotted as per the variant caller using the code in Appendix B.

The calculation of the allele frequency also varies for VarScan somatic and Strelka variant callers. For VarScan somatic, `vcftools` can be used to calculate the allele frequency for REF and ALT values by using the command

```
vcftools --vcf input.vcf --freq --out output
```

For Strelka, vcftools cannot be used and the code in Strelka Allele Frequency section of Appendix B should be used to calculate the allele frequencies for REF and ALT values. In terms of calculations, Strelka SNPs allele frequency varies from Strelka Indels allele frequency. The formula to calculate the Strelka SNPs allele frequency is

$$\text{SNPs allele frequency} = \text{AltCounts} / (\text{AltCounts} + \text{RefCounts})$$

5.3 Read Depths

The fourth experiment would be comparing the read depths between the variant callers using the code in Appendix E.

```
vcftools --vcf input_data.vcf --depth -c > depth_summary.txt
```

```
vcftools --vcf input_data.vcf --site-depth --max-missing 1.0 --out  
site_depth_summary
```

5.4 Variant Combination Bias

The second experiment would be comparing the occurrence of the sixteen combinations of variants between the different variant callers i.e. AA, AT, AG, AC, TA, ... using the code in Appendix F.

5.5 Benchmarking

The fifth experiment would be benchmarking the variant callers based on the True Positives, True Negatives, False Positives and False Negatives using the code in Appendix C.

Chapter 6

Results

To compare the Strelka, VarScan and Truth VCF files, the first step is calculating the number of positions, SNPs and Indels. This step helps in finding out the common positions, SNPs and Indels amongst the VCF files and even helps in normalising the variants in the second step.

In the second step, to know the bias of the variant callers, each variant type is counted and normalised. Through this step, information about a variant caller showing a specific bias in calling variant combinations quite often can be known in comparison to the truth data.

In the third step, to observe genetic diversity, allele frequencies between the truth data and the Strelka and VarScan VCF files are compared to learn which variant caller is comparably close to the truth data and which variant caller calls the reads with higher allele frequencies.

In the fourth step, to know the number of times a nucleotide has been read, the read depth of each VCF file is compared. This step reveals the coverage of a read in every variant caller while providing an idea as to which variant caller has the better coverage.

In the fifth and final step, ALT variants in each of the VCF files are compared for benchmarking. Through this step, the truth data is compared with the Strelka VCF file and VarScan VCF file individually to know the number of true positives, true negatives, false positives and false negatives.

6.1 Positions, SNPs & Indels

A single-nucleotide polymorphism is a substitution of a single nucleotide at a specific position in the genome that is present in a sufficiently large fraction of the population. Indel is a molecular biology term for an insertion or deletion of bases in the genome of an organism. In this section, Positions, SNPs and INDELs from different somatic variant callers are compared with the artificial truth data obtained from <https://ftp-trace.ncbi.nlm.nih.gov/>

Tumor Purity	Positions	SNPs	Indels
0.3	13,315	12,897	418
0.5	13,315	12,897	418
0.7	13,315	12,897	418

Table 6.1: Values from Strelka VCF files

Tumor Purity	Positions	SNPs	Indels
0.3	29,316	26,312	3,004
0.5	29,294	26,290	3,004
0.7	29,171	26,185	2,986

Table 6.2: Values from VarScan VCF files

Tumor Purity	Positions	SNPs	Indels
1.0	11,04,786	10,07,793	96,993

Table 6.3: Values from Truth Data VCF files

6.2 Variants

A variant is an alteration in the most common DNA sequence. In this section, variants from different somatic variant callers are compared with the artificial truth data obtained from <https://ftp-trace.ncbi.nlm.nih.gov/>

Type	Positions
Strelka	13,315
VarScan	29,316
Truth Data	11,04,786
Strelka & VarScan	3,104
VarScan & Truth Data	2,843
Strelka & Truth Data	3,791
Strelka, VarScan & Truth Data	1,052

Table 6.4: Positions comparison with Tumor Purity 0.3

Type	Positions
Strelka	13,315
VarScan	29,294
Truth Data	11,04,786
Strelka & VarScan	3,096
VarScan & Truth Data	2,843
Strelka & Truth Data	3,791
Strelka, VarScan & Truth Data	1,052

Table 6.5: Positions comparison with Tumor Purity 0.5

Type	Positions
Strelka	13,315
VarScan	29,171
Truth Data	11,04,786
Strelka & VarScan	3,051
VarScan & Truth Data	2,843
Strelka & Truth Data	3,791
Strelka, VarScan & Truth Data	1,052

Table 6.6: Positions comparison with Tumor Purity 0.7

Type	SNPs
Strelka	12,897
VarScan	26,312
Truth Data	10,07,793
Strelka & VarScan	2,778
VarScan & Truth Data	2,484
Strelka & Truth Data	3,150
Strelka, VarScan & Truth Data	875

Table 6.7: SNPs comparison with Tumor Purity 0.3

Type	SNPs
Strelka	12,897
VarScan	26,290
Truth Data	10,07,793
Strelka & VarScan	2,770
VarScan & Truth Data	2,484
Strelka & Truth Data	3,150
Strelka, VarScan & Truth Data	875

Table 6.8: SNPs comparison with Tumor Purity 0.5

Type	SNPs
Strelka	12,897
VarScan	26,185
Truth Data	10,07,793
Strelka & VarScan	2,729
VarScan & Truth Data	2,484
Strelka & Truth Data	3,150
Strelka, VarScan & Truth Data	875

Table 6.9: SNPs comparison with Tumor Purity 0.7

6.3 Allele Frequencies

Allele frequency, or gene frequency is defined as the relative frequency of an allele at a particular locus in a population, expressed as a fraction or

Type	Indels
Strelka	418
VarScan	3,004
Truth Data	96,993
Strelka & VarScan	110
VarScan & Truth Data	200
Strelka & Truth Data	127
Strelka, VarScan & Truth Data	29

Table 6.10: Indels comparison with Tumor Purity 0.3 & 0.5

Type	Indels
Strelka	418
VarScan	2,986
Truth Data	96,993
Strelka & VarScan	107
VarScan & Truth Data	200
Strelka & Truth Data	127
Strelka, VarScan & Truth Data	29

Table 6.11: Indels comparison with Tumor Purity 0.7

percentage. In this section, allele frequencies from different somatic variant callers are compared with the artificial truth data obtained from <https://ftp-trace.ncbi.nlm.nih.gov/>

Figure 6.1 shows Strelka Allele Frequency Counts.

Figure 6.2 shows VarScan Allele Frequency Counts.

Figure 6.3 shows Allele Frequencies with Tumor Purity of 0.3, 0.5 & 0.7.

6.4 Read Depth

Read Depth describes the number of times that a given nucleotide in the genome has been read in an experiment. In this section, read depths from different somatic variant callers are compared with the artificial truth data obtained from <https://ftp-trace.ncbi.nlm.nih.gov/>




Figure 6.1: Strelka Allele Frequency Counts




Figure 6.2: VarScan Allele Frequency Counts




Figure 6.3: Allele Frequencies with Tumor Purity of 0.3, 0.5 & 0.7

Combination	Tumor Purity 0.3	Tumor Purity 0.5	Tumor Purity 0.7
AA	0	0	0
AT	393	393	393
AG	1,196	1,196	1,196
AC	1,942	1,942	1,942
TT	0	0	0
TA	647	647	647
TG	1,491	1,491	1,491
TC	1,245	1,245	1,245
GG	0	0	0
GA	1,700	1,700	1,700
GT	882	882	882
GC	478	478	478
CC	0	0	0
CA	1,072	1,072	1,072
CT	1,441	1,441	1,441
CG	409	409	409

Table 6.12: Variant counts in Strelka variant caller

Combination	Tumor Purity 0.3	Tumor Purity 0.5	Tumor Purity 0.7
AA	0	0	0
AT	662	662	662
AG	4,354	4,354	4,350
AC	962	958	947
TT	0	0	0
TA	722	720	715
TG	990	989	976
TC	4,343	4,342	4,336
GG	0	0	0
GA	4,960	4,959	4,950
GT	969	966	949
GC	1,212	1,212	1,210
CC	0	0	0
CA	1,059	1,054	1,033
CT	4,843	4,840	4,829
CG	1,235	1,233	1,231

Table 6.13: Variant counts in VarScan variant caller

Combination	Tumor Purity 1.0
AA	0
AT	32,639
AG	1,52,935
AC	38,384
TT	0
TA	32,817
TG	37,707
TC	1,53,474
GG	0
GA	1,91,603
GT	44,538
GC	43,851
CC	0
CA	44,253
CT	1,91,442
CG	44,049

Table 6.14: Variant counts in Truth Data

Combination	Strelka	VarScan	Truth Data
AA	0	0	0
AT	3.04	2.51	3.23
AG	9.27	16.54	15.17
AC	15.05	3.65	3.80
TT	0	0	0
TA	5.01	2.74	3.25
TG	11.56	3.76	3.74
TC	9.65	16.50	15.22
GG	0	0	0
GA	13.18	18.85	19.01
GT	6.83	3.68	4.41
GC	3.70	4.60	4.35
CC	0	0	0
CA	8.31	4.02	4.39
CT	11.17	18.40	18.99
CG	3.17	4.69	4.37

Table 6.15: Normalised variant counts with Tumor Purity 0.3

Combination	Strelka	VarScan	Truth Data
AA	0	0	0
AT	3.04	2.51	3.23
AG	9.27	16.56	15.17
AC	15.05	3.64	3.80
TT	0	0	0
TA	5.01	2.73	3.25
TG	11.56	3.76	3.74
TC	9.65	16.51	15.22
GG	0	0	0
GA	13.18	18.86	19.01
GT	6.83	3.67	4.41
GC	3.70	4.61	4.35
CC	0	0	0
CA	8.31	4.00	4.39
CT	11.17	18.41	18.99
CG	3.17	4.69	4.37

Table 6.16: Normalised variant counts with Tumor Purity 0.5

Combination	Strelka	VarScan	Truth Data
AA	0	0	0
AT	3.04	2.51	3.23
AG	9.27	16.61	15.17
AC	15.05	3.61	3.80
TT	0	0	0
TA	5.01	2.73	3.25
TG	11.56	3.72	3.74
TC	9.65	16.55	15.22
GG	0	0	0
GA	13.18	18.90	19.01
GT	6.83	3.62	4.41
GC	3.70	4.62	4.35
CC	0	0	0
CA	8.31	3.94	4.39
CT	11.17	18.44	18.99
CG	3.17	4.70	4.37

Table 6.17: Normalised variant counts with Tumor Purity 0.7

Format	Purity	≤ 0.25	$0.25 < \& \leq 0.50$	$0.50 < \& \leq 0.75$	> 0.75
Normal	0.3	11,266	809	1,020	212
Tumor	0.3	10,095	1,185	177	1,845
Normal	0.5	11,266	809	1,020	212
Tumor	0.5	10,095	1,185	177	1,845
Normal	0.7	11,266	809	1,020	212
Tumor	0.7	10,095	1,185	177	1,845

Table 6.18: Allele Frequencies count from Strelka variant caller VCF files

Purity	≤ 0.25	$0.25 < \& \leq 0.50$	$0.50 < \& \leq 0.75$	> 0.75
0.3	9,893	14,732	4,546	0
0.5	9,893	14,732	4,546	0
0.7	9,893	14,732	4,546	0

Table 6.19: Allele Frequencies count from VarScan variant caller VCF files

≤ 0.25	$0.25 < \& \leq 0.50$	$0.50 < \& \leq 0.75$	> 0.75
11,266	809	1,020	212

Table 6.20: Allele Frequencies count from Truth Data VCF file

Type	≤ 0.25	$0.25 < \& \leq 0.50$	$0.50 < \& \leq 0.75$	> 0.75
Strelka Normal	469	561	2	0
Strelka Tumor	1,032	0	0	0
VarScan	0	0	1,032	0
Truth Data	0	1,032	0	0

Table 6.21: Allele Frequencies count with Tumor Purity of 0.3, 0.5 & 0.7

Format	Purity	Minimum	Maximum	Mean	Median	Mode
Normal	0.3	1	299	58.32	53	0 43
Normal	0.3	0	114	20.71	19	0 17
Normal	0.5	1	299	58.32	53	0 43
Tumor	0.5	0	114	20.71	19	0 17
Normal	0.7	1	299	58.32	53	0 43
Tumor	0.7	0	114	20.71	19	0 17

Table 6.22: Read Depth statistics from Strelka variant caller VCF files

Format	Purity	Minimum	Maximum	Mean	Median	Mode
Normal	0.3	10	99	∞	55	0 38
Normal	0.3	10	98	∞	19	0 17
Normal	0.5	10	99	∞	55	0 38
Tumor	0.5	10	98	∞	19	0 17
Normal	0.7	10	99	∞	55	0 38
Tumor	0.7	10	98	∞	19	0 17

Table 6.23: Read Depth statistics from VarScan variant caller VCF files

Minimum	Maximum	Mean	Median	Mode
100	999	∞	647	0 640

Table 6.24: Read Depth statistics from Truth Data VCF file

Type	Minimum	Maximum	Mean	Median	Mode
Strelka Normal	20	139	70.38	64	0 59
Strelka Tumor	14	61	26.61	25	0 19
VarScan Normal	16	117	55.11	50	0 41
VarScan Tumor	9	52	21.18	19	0 16
Truth Data	274	1,104	662.83	660	0 730

Table 6.25: Read Depth statistics from Tumor Purity 0.3, 0.5, & 0.7

Chapter 7

Conclusions

Bibliography

Bibliography

- [1] Adam Cornish, Chittibabu Guda, "A Comparison of Variant Calling Pipelines Using Genome in a Bottle as a Reference", *BioMed Research International*, vol. 2015, Article ID 456479, 11 pages, 2015. <https://doi.org/10.1155/2015/456479>
- [2] Prokosch HU, Acker T, Bernarding J, et al. MIRACUM: Medical Informatics in Research and Care in University Medicine. *Methods Inf Med*. 2018;57(S 01):e82-e91. doi:10.3414/ME17-02-0025
- [3] Schwaederle M, Parker BA, Schwab RB, et al. Molecular tumor board: the University of California-San Diego Moores Cancer Center experience. *Oncologist*. 2014;19(6):631-636. doi:10.1634/theoncologist.2013-0405
- [4] Enis Afgan, Dannon Baker, B  renice Batut, Marius van den Beek, Dave Bouvier, Martin   ech, John Chilton, Dave Clements, Nate Coraor, Bj  rn A Gr  ning, Aysam Guerler, Jennifer Hillman-Jackson, Saskia Hiltmann, Vahid Jalili, Helena Rasche, Nicola Soranzo, Jeremy Goecks, James Taylor, Anton Nekrutenko, Daniel Blankenberg, The Galaxy platform for accessible, reproducible and collaborative biomedical analyses: 2018 update, *Nucleic Acids Research*, Volume 46, Issue W1, 2 July 2018, Pages W537–W544, <https://doi.org/10.1093/nar/gky379>
- [5] Blischak JD, Davenport ER, Wilson G (2016) A Quick Introduction to Version Control with Git and GitHub. *PLoS Comput Biol* 12(1): e1004668. <https://doi.org/10.1371/journal.pcbi.1004668>
- [6] Xiao, C., Zook, J., Trask, S., & Sherry, S. 2014. Abstract 5328: GIAB: Genome reference material development resources for clinical sequencing. *Molecular and Cellular Biology*. Presented at the Proceedings: AACR An-

- nual Meeting 2014; April 5-9, 2014; San Diego, CA, American Association for Cancer Research. <https://doi.org/10.1158/1538-7445.am2014-5328>.
- [7] Clements D, Hiltemann S, Batut B, Rasche H, Heydarian M, Training Network TG. Using the Galaxy Training Network tutorial library for bioinformatics training programs. *J Biomol Tech.* 2020;31(Suppl):S2.
 - [8] Koboldt, D. C., Zhang, Q., Larson, D. E., Shen, D., McLellan, M. D., et al. 2012. VarScan 2: Somatic mutation and copy number alteration discovery in cancer by exome sequencing. *Genome Research*, 22(3): 568–576.
 - [9] Christopher T. Saunders, Wendy S. W. Wong, Sajani Swamy, Jennifer Becq, Lisa J. Murray, R. Keira Cheetham, Strelka: accurate somatic small-variant calling from sequenced tumor–normal sample pairs, *Bioinformatics*, Volume 28, Issue 14, 15 July 2012, Pages 1811–1817, <https://doi.org/10.1093/bioinformatics/bts271>
 - [10] Wolfgang Maier, Bérénice Batut, Torsten Houwaart, Anika Erxleben, Björn Grüning, Exome sequencing data analysis for diagnosing a genetic disease (Galaxy Training Materials). </archive/2019-12-01/topics/variant-analysis/tutorials/exome-seq/tutorial.html> Online; accessed Sat Apr 10 2021
 - [11] Batut et al., 2018 Community-Driven Data Analysis Training for Biology Cell Systems 10.1016/j.cels.2018.05.012
 - [12] Wolfgang Maier, 2021 Identification of somatic and germline variants from tumor and normal sample pairs (Galaxy Training Materials). </training-material/topics/variant-analysis/tutorials/somatic-variants/tutorial.html> Online; accessed Sat Apr 10 2021
 - [13] Batut et al., 2018 Community-Driven Data Analysis Training for Biology Cell Systems 10.1016/j.cels.2018.05.012

Appendix A

Map Workflow YAML

NORMAL forward reads:

`class: File`
`location: https://zenodo.org/record/....fastq.gz`

NORMAL reverse reads:

`class: File`
`location: https://zenodo.org/record/....fastq.gz`

TUMOR forward reads:

`class: File`
`location: https://zenodo.org/record/....fastq.gz`

TUMOR reverse reads:

`class: File`
`location: https://zenodo.org/record/....fastq.gz`

Appendix B

Strelka Allele Frequency

```
# Importing the needed packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import csv

matplotlib.rcParams['font.sans-serif'] = ['Computer Modern Roman',
    'sans-serif']

# The first step is to selected the neccessary columns.
# Step 1 - 'cut -f 1-2,4-5,9-11 Input.vcf > Output.vcf'

# Removing all the rows starting with a #
# Step 2 - 'sed '/^#/d' Output.vcf > Updated_Output.vcf'

# Consider the Updated_Output.vcf as input.
dff = pd.read_csv("Selected_Strelka_0.3_Indels.vcf", sep = '\t',
    index_col= False)
dff1 = pd.read_csv("Selected_Strelka_0.5_Indels.vcf", sep = '\t',
    index_col= False)
dff2 = pd.read_csv("Selected_Strelka_0.7_Indels.vcf", sep = '\t',
    index_col= False)
```

```

# Renaming the columns after importing the input.
dff.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']
dff1.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']
dff2.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
    dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising them.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]

# Creating new columns by splitting the "NORMAL" and "TUMOR"
columns by ':' and renaming the new columns based on the format
"DP:FDP:SDP:SBDP:AU:CU:GU:TU"
dff[['Normal_DP', 'Normal_DP2', 'Normal_TAR', 'Normal_TIR',
     'Normal_TOR', 'Normal_DP50', 'Normal_FDP50', 'Normal_SBDP50',
     'Normal_BCN50']] = dff['NORMAL'].str.split(':', expand=True)
dff[['Tumor_DP', 'Tumor_DP2', 'Tumor_TAR', 'Tumor_TIR',
     'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50', 'Tumor_SBDP50',

```



```

    'Tumor_BCN50']] = dff['TUMOR'].str.split(':',expand=True)

dff1[['Normal_DP', 'Normal_DP2', 'Normal_TAR', 'Normal_TIR',
      'Normal_TOR', 'Normal_DP50', 'Normal_FDP50', 'Normal_SUBDP50',
      'Normal_BCN50']] = dff1['NORMAL'].str.split(':',expand=True)
dff1[['Tumor_DP', 'Tumor_DP2', 'Tumor_TAR', 'Tumor_TIR',
      'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50', 'Tumor_SUBDP50',
      'Tumor_BCN50']] = dff1['TUMOR'].str.split(':',expand=True)

dff2[['Normal_DP', 'Normal_DP2', 'Normal_TAR', 'Normal_TIR',
      'Normal_TOR', 'Normal_DP50', 'Normal_FDP50', 'Normal_SUBDP50',
      'Normal_BCN50']] = dff2['NORMAL'].str.split(':',expand=True)
dff2[['Tumor_DP', 'Tumor_DP2', 'Tumor_TAR', 'Tumor_TIR',
      'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50', 'Tumor_SUBDP50',
      'Tumor_BCN50']] = dff2['TUMOR'].str.split(':',expand=True)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
               'Normal_DP2', 'Normal_TOR', 'Normal_DP50', 'Normal_FDP50',
               'Normal_SUBDP50', 'Normal_BCN50', 'Tumor_DP', 'Tumor_DP2',
               'Tumor_DP2', 'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50',
               'Tumor_SUBDP50', 'Tumor_BCN50'], axis=1)

dff1 = dff1.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
                 'Normal_DP2', 'Normal_TOR', 'Normal_DP50', 'Normal_FDP50',
                 'Normal_SUBDP50', 'Normal_BCN50', 'Tumor_DP', 'Tumor_DP2',
                 'Tumor_DP2', 'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50',
                 'Tumor_SUBDP50', 'Tumor_BCN50'], axis=1)

dff2 = dff2.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
                 'Normal_DP2', 'Normal_TOR', 'Normal_DP50', 'Normal_FDP50',
                 'Normal_SUBDP50', 'Normal_BCN50', 'Tumor_DP', 'Tumor_DP2',
                 'Tumor_DP2', 'Tumor_TOR', 'Tumor_DP50', 'Tumor_FDP50',
                 'Tumor_SUBDP50', 'Tumor_BCN50'], axis=1)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
# columns by ':' and renaming the new columns based on the format
# "DP:FDP:SDP:SBDP:AU:CU:GU:TU"
dff[['Normal_TAR_First', 'Normal_TAR_Second']] =
    dff['Normal_TAR'].str.split(',',expand=True)

```

```

dff[['Normal_TIR_First', 'Normal_TIR_Second']] =
    dff['Normal_TIR'].str.split(',', expand=True)
dff[['Tumor_TAR_First', 'Tumor_TAR_Second']] =
    dff['Tumor_TAR'].str.split(',', expand=True)
dff[['Tumor_TIR_First', 'Tumor_TIR_Second']] =
    dff['Tumor_TIR'].str.split(',', expand=True)

dff1[['Normal_TAR_First', 'Normal_TAR_Second']] =
    dff1['Normal_TAR'].str.split(',', expand=True)
dff1[['Normal_TIR_First', 'Normal_TIR_Second']] =
    dff1['Normal_TIR'].str.split(',', expand=True)
dff1[['Tumor_TAR_First', 'Tumor_TAR_Second']] =
    dff1['Tumor_TAR'].str.split(',', expand=True)
dff1[['Tumor_TIR_First', 'Tumor_TIR_Second']] =
    dff1['Tumor_TIR'].str.split(',', expand=True)

dff2[['Normal_TAR_First', 'Normal_TAR_Second']] =
    dff2['Normal_TAR'].str.split(',', expand=True)
dff2[['Normal_TIR_First', 'Normal_TIR_Second']] =
    dff2['Normal_TIR'].str.split(',', expand=True)
dff2[['Tumor_TAR_First', 'Tumor_TAR_Second']] =
    dff2['Tumor_TAR'].str.split(',', expand=True)
dff2[['Tumor_TIR_First', 'Tumor_TIR_Second']] =
    dff2['Tumor_TIR'].str.split(',', expand=True)

# Renaming the new table with column names.
dff.columns = ['CHROM_POS', 'REF', 'ALT', 'Normal_TAR',
               'Normal_TIR', 'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',
               'Normal_TAR_Second', 'Normal_TIR_First', 'Normal_TIR_Second',
               'Tumor_TAR_First', 'Tumor_TAR_Second', 'Tumor_TIR_First',
               'Tumor_TIR_Second']

dff1.columns = ['CHROM_POS', 'REF', 'ALT', 'Normal_TAR',
               'Normal_TIR', 'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',
               'Normal_TAR_Second', 'Normal_TIR_First', 'Normal_TIR_Second',
               'Tumor_TAR_First', 'Tumor_TAR_Second', 'Tumor_TIR_First',
               'Tumor_TIR_Second']

dff2.columns = ['CHROM_POS', 'REF', 'ALT', 'Normal_TAR',
               'Normal_TIR', 'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',

```

```

    'Normal_TAR_Second', 'Normal_TIR_First', 'Normal_TIR_Second',
    'Tumor_TAR_First', 'Tumor_TAR_Second', 'Tumor_TIR_First',
    'Tumor_TIR_Second']

# Dropping of the unnecessary columns and reorganising them.
dff = dff.drop(['Normal_TAR_Second', 'Normal_TIR_Second',
    'Tumor_TAR_Second', 'Tumor_TIR_Second'], axis=1)
print(dff)

dff1 = dff1.drop(['Normal_TAR_Second', 'Normal_TIR_Second',
    'Tumor_TAR_Second', 'Tumor_TIR_Second'], axis=1)
print(dff1)

dff2 = dff2.drop(['Normal_TAR_Second', 'Normal_TIR_Second',
    'Tumor_TAR_Second', 'Tumor_TIR_Second'], axis=1)
print(dff2)

# Converting string values columns to int for calculations.
dff['Normal_TAR_First'] = dff['Normal_TAR_First'].astype(int)
dff['Normal_TIR_First'] = dff['Normal_TIR_First'].astype(int)
dff['Tumor_TAR_First'] = dff['Tumor_TAR_First'].astype(int)
dff['Tumor_TIR_First'] = dff['Tumor_TIR_First'].astype(int)

dff1['Normal_TAR_First'] = dff1['Normal_TAR_First'].astype(int)
dff1['Normal_TIR_First'] = dff1['Normal_TIR_First'].astype(int)
dff1['Tumor_TAR_First'] = dff1['Tumor_TAR_First'].astype(int)
dff1['Tumor_TIR_First'] = dff1['Tumor_TIR_First'].astype(int)

dff2['Normal_TAR_First'] = dff2['Normal_TAR_First'].astype(int)
dff2['Normal_TIR_First'] = dff2['Normal_TIR_First'].astype(int)
dff2['Tumor_TAR_First'] = dff2['Tumor_TAR_First'].astype(int)
dff2['Tumor_TIR_First'] = dff2['Tumor_TIR_First'].astype(int)

# Adding the values for the formula.
dff['SUM'] = dff["Normal_TAR_First"] + dff["Normal_TIR_First"]
dff['COMMON'] = dff["Tumor_TAR_First"] + dff["Tumor_TIR_First"]
print(dff)

dff1['SUM'] = dff1["Normal_TAR_First"] + dff1["Normal_TIR_First"]
dff1['COMMON'] = dff1["Tumor_TAR_First"] + dff1["Tumor_TIR_First"]

```

```

print(dff1)

dff2['SUM'] = dff2["Normal_TAR_First"] + dff2["Normal_TIR_First"]
dff2['COMMON'] = dff2["Tumor_TAR_First"] + dff2["Tumor_TIR_First"]
print(dff2)

# Getting Allele Frequency
dff['Normal_Allele_Frequency'] = dff['Normal_TIR_First']/dff['SUM']
dff['Tumor_Allele_Frequency'] =
    dff['Tumor_TIR_First']/dff['COMMON']

dff1['Normal_Allele_Frequency'] =
    dff1['Normal_TIR_First']/dff1['SUM']
dff1['Tumor_Allele_Frequency'] =
    dff1['Tumor_TIR_First']/dff1['COMMON']

dff2['Normal_Allele_Frequency'] =
    dff2['Normal_TIR_First']/dff2['SUM']
dff2['Tumor_Allele_Frequency'] =
    dff2['Tumor_TIR_First']/dff2['COMMON']

# Converting string values columns to int.
dff['Normal_Allele_Frequency'] =
    dff['Normal_Allele_Frequency'].astype(float).round(2)
dff['Tumor_Allele_Frequency'] =
    dff['Tumor_Allele_Frequency'].astype(float).round(2)

dff1['Normal_Allele_Frequency'] =
    dff1['Normal_Allele_Frequency'].astype(float).round(2)
dff1['Tumor_Allele_Frequency'] =
    dff1['Tumor_Allele_Frequency'].astype(float).round(2)

dff2['Normal_Allele_Frequency'] =
    dff2['Normal_Allele_Frequency'].astype(float).round(2)
dff2['Tumor_Allele_Frequency'] =
    dff2['Tumor_Allele_Frequency'].astype(float).round(2)

# Concatinating the "CHROM" and "POS"
dff["Normal_Allele_Frequency"] = dff['REF'].astype(str) + ':' +
    dff['Normal_Allele_Frequency'].astype(str)

```

```

dff["Tumor_Allele_Frequency"] = dff['REF'].astype(str) + ':' +
    dff['Tumor_Allele_Frequency'].astype(str)

dff1["Normal_Allele_Frequency"] = dff1['REF'].astype(str) + ':' +
    dff1['Normal_Allele_Frequency'].astype(str)
dff1["Tumor_Allele_Frequency"] = dff1['REF'].astype(str) + ':' +
    dff1['Tumor_Allele_Frequency'].astype(str)

dff2["Normal_Allele_Frequency"] = dff2['REF'].astype(str) + ':' +
    dff2['Normal_Allele_Frequency'].astype(str)
dff2["Tumor_Allele_Frequency"] = dff2['REF'].astype(str) + ':' +
    dff2['Tumor_Allele_Frequency'].astype(str)

# Dropping of the unnecessary columns and reorganising them.
dff = dff.drop(['REF', 'ALT', 'Normal_TAR', 'Normal_TIR',
    'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',
    'Normal_TIR_First', 'Tumor_TAR_First', 'Tumor_TIR_First',
    'SUM', 'COMMON'], axis=1)
print(dff)

dff1 = dff1.drop(['REF', 'ALT', 'Normal_TAR', 'Normal_TIR',
    'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',
    'Normal_TIR_First', 'Tumor_TAR_First', 'Tumor_TIR_First',
    'SUM', 'COMMON'], axis=1)
print(dff1)

dff2 = dff2.drop(['REF', 'ALT', 'Normal_TAR', 'Normal_TIR',
    'Tumor_TAR', 'Tumor_TAR', 'Normal_TAR_First',
    'Normal_TIR_First', 'Tumor_TAR_First', 'Tumor_TIR_First',
    'SUM', 'COMMON'], axis=1)
print(dff2)

# Merging columns based on "CHROM-POS"
First = pd.merge(dff, dff1, on=['CHROM_POS'])
Second = pd.merge(First, dff2, on=['CHROM_POS'])

# Renaming Columns
Second.columns = ['CHROM_POS', 'Strelka_Normal_0.3',
    'Strelka_Tumor_0.3', 'Strelka_0.5_Normal', 'Strelka_0.5_Tumor',
    'Strelka_0.7_Normal', 'Strelka_0.7_Tumor']

```

```

print(Second)

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Selected_Strelka_0.3_SNP.vcf", sep = '\t',
                  index_col= False)
dff1 = pd.read_csv("Selected_Strelka_0.5_SNP.vcf", sep = '\t',
                  index_col= False)
dff2 = pd.read_csv("Selected_Strelka_0.7_SNP.vcf", sep = '\t',
                  index_col= False)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']
dff1.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']
dff2.columns = ['CHROM', 'POS', 'REF', 'ALT', 'FORMAT', 'NORMAL',
               'TUMOR']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
                  dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
                  dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
                  dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()

```

```

cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]

# Adding columns for single read depth value.
dff['REF_U'] = dff["REF"] + "U"
dff['ALT_U'] = dff["ALT"] + "U"

dff1['REF_U'] = dff1["REF"] + "U"
dff1['ALT_U'] = dff1["ALT"] + "U"

dff2['REF_U'] = dff2["REF"] + "U"
dff2['ALT_U'] = dff2["ALT"] + "U"

# Creating new columns by splitting the "NORMAL" and "TUMOR"
# columns by ':' and renaming the new columns based on the format
# "DP:FDP:SDP:SBDP:AU:CU:GU:TU"
dff[['Normal_DP', 'Normal_FDP', 'Normal_SDP', 'Normal_SBDP',
     'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU']] =
    dff['NORMAL'].str.split(':', expand=True)
dff[['Tumor_DP', 'Tumor_FDP', 'Tumor_SDP', 'Tumor_SBDP',
     'Tumor_AU', 'Tumor_CU', 'Tumor_GU', 'Tumor_TU']] =
    dff['TUMOR'].str.split(':', expand=True)

dff1[['Normal_DP', 'Normal_FDP', 'Normal_SDP', 'Normal_SBDP',
     'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU']] =
    dff1['NORMAL'].str.split(':', expand=True)
dff1[['Tumor_DP', 'Tumor_FDP', 'Tumor_SDP', 'Tumor_SBDP',
     'Tumor_AU', 'Tumor_CU', 'Tumor_GU', 'Tumor_TU']] =
    dff1['TUMOR'].str.split(':', expand=True)

dff2[['Normal_DP', 'Normal_FDP', 'Normal_SDP', 'Normal_SBDP',
     'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU']] =
    dff2['NORMAL'].str.split(':', expand=True)
dff2[['Tumor_DP', 'Tumor_FDP', 'Tumor_SDP', 'Tumor_SBDP',
     'Tumor_AU', 'Tumor_CU', 'Tumor_GU', 'Tumor_TU']] =
    dff2['TUMOR'].str.split(':', expand=True)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
               'Normal_FDP', 'Normal_SDP', 'Normal_SBDP', 'Tumor_DP',

```

```

        'Tumor_FDP', 'Tumor_SDP', 'Tumor_SUBDP'], axis=1)
dff1 = dff1.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
        'Normal_FDP', 'Normal_SDP', 'Normal_SUBDP', 'Tumor_DP',
        'Tumor_FDP', 'Tumor_SDP', 'Tumor_SUBDP'], axis=1)
dff2 = dff2.drop(['FORMAT', 'NORMAL', 'TUMOR', 'Normal_DP',
        'Normal_FDP', 'Normal_SDP', 'Normal_SUBDP', 'Tumor_DP',
        'Tumor_FDP', 'Tumor_SDP', 'Tumor_SUBDP'], axis=1)

for i in dff['CHROM_POS']:
    dff.loc[dff['REF_U'] == 'AU', 'REF_Normal'] = dff.Normal_AU
    dff.loc[dff['REF_U'] == 'CU', 'REF_Normal'] = dff.Normal_CU
    dff.loc[dff['REF_U'] == 'GU', 'REF_Normal'] = dff.Normal_GU
    dff.loc[dff['REF_U'] == 'TU', 'REF_Normal'] = dff.Normal_TU
    dff.loc[dff['ALT_U'] == 'AU', 'ALT_Normal'] = dff.Normal_AU
    dff.loc[dff['ALT_U'] == 'CU', 'ALT_Normal'] = dff.Normal_CU
    dff.loc[dff['ALT_U'] == 'GU', 'ALT_Normal'] = dff.Normal_GU
    dff.loc[dff['ALT_U'] == 'TU', 'ALT_Normal'] = dff.Normal_TU
    dff.loc[dff['REF_U'] == 'AU', 'REF_Tumor'] = dff.Tumor_AU
    dff.loc[dff['REF_U'] == 'CU', 'REF_Tumor'] = dff.Tumor_CU
    dff.loc[dff['REF_U'] == 'GU', 'REF_Tumor'] = dff.Tumor_GU
    dff.loc[dff['REF_U'] == 'TU', 'REF_Tumor'] = dff.Tumor_TU
    dff.loc[dff['ALT_U'] == 'AU', 'ALT_Tumor'] = dff.Tumor_AU
    dff.loc[dff['ALT_U'] == 'CU', 'ALT_Tumor'] = dff.Tumor_CU
    dff.loc[dff['ALT_U'] == 'GU', 'ALT_Tumor'] = dff.Tumor_GU
    dff.loc[dff['ALT_U'] == 'TU', 'ALT_Tumor'] = dff.Tumor_TU
print(dff)

for i in dff1['CHROM_POS']:
    dff1.loc[dff1['REF_U'] == 'AU', 'REF_Normal'] = dff1.Normal_AU
    dff1.loc[dff1['REF_U'] == 'CU', 'REF_Normal'] = dff1.Normal_CU
    dff1.loc[dff1['REF_U'] == 'GU', 'REF_Normal'] = dff1.Normal_GU
    dff1.loc[dff1['REF_U'] == 'TU', 'REF_Normal'] = dff1.Normal_TU
    dff1.loc[dff1['ALT_U'] == 'AU', 'ALT_Normal'] = dff1.Normal_AU
    dff1.loc[dff1['ALT_U'] == 'CU', 'ALT_Normal'] = dff1.Normal_CU
    dff1.loc[dff1['ALT_U'] == 'GU', 'ALT_Normal'] = dff1.Normal_GU
    dff1.loc[dff1['ALT_U'] == 'TU', 'ALT_Normal'] = dff1.Normal_TU
    dff1.loc[dff1['REF_U'] == 'AU', 'REF_Tumor'] = dff1.Tumor_AU
    dff1.loc[dff1['REF_U'] == 'CU', 'REF_Tumor'] = dff1.Tumor_CU
    dff1.loc[dff1['REF_U'] == 'GU', 'REF_Tumor'] = dff1.Tumor_GU
    dff1.loc[dff1['REF_U'] == 'TU', 'REF_Tumor'] = dff1.Tumor_TU

```



```

dff1.loc[dff1['ALT_U'] == 'AU', 'ALT_Tumor'] = dff1.Tumor_AU
dff1.loc[dff1['ALT_U'] == 'CU', 'ALT_Tumor'] = dff1.Tumor_CU
dff1.loc[dff1['ALT_U'] == 'GU', 'ALT_Tumor'] = dff1.Tumor_GU
dff1.loc[dff1['ALT_U'] == 'TU', 'ALT_Tumor'] = dff1.Tumor_TU
print(dff1)

for i in dff2['CHROM_POS']:
    dff2.loc[dff2['REF_U'] == 'AU', 'REF_Normal'] = dff2.Normal_AU
    dff2.loc[dff2['REF_U'] == 'CU', 'REF_Normal'] = dff2.Normal_CU
    dff2.loc[dff2['REF_U'] == 'GU', 'REF_Normal'] = dff2.Normal_GU
    dff2.loc[dff2['REF_U'] == 'TU', 'REF_Normal'] = dff2.Normal_TU
    dff2.loc[dff2['ALT_U'] == 'AU', 'ALT_Normal'] = dff2.Normal_AU
    dff2.loc[dff2['ALT_U'] == 'CU', 'ALT_Normal'] = dff2.Normal_CU
    dff2.loc[dff2['ALT_U'] == 'GU', 'ALT_Normal'] = dff2.Normal_GU
    dff2.loc[dff2['ALT_U'] == 'TU', 'ALT_Normal'] = dff2.Normal_TU
    dff2.loc[dff2['REF_U'] == 'AU', 'REF_Tumor'] = dff2.Tumor_AU
    dff2.loc[dff2['REF_U'] == 'CU', 'REF_Tumor'] = dff2.Tumor_CU
    dff2.loc[dff2['REF_U'] == 'GU', 'REF_Tumor'] = dff2.Tumor_GU
    dff2.loc[dff2['REF_U'] == 'TU', 'REF_Tumor'] = dff2.Tumor_TU
    dff2.loc[dff2['ALT_U'] == 'AU', 'ALT_Tumor'] = dff2.Tumor_AU
    dff2.loc[dff2['ALT_U'] == 'CU', 'ALT_Tumor'] = dff2.Tumor_CU
    dff2.loc[dff2['ALT_U'] == 'GU', 'ALT_Tumor'] = dff2.Tumor_GU
    dff2.loc[dff2['ALT_U'] == 'TU', 'ALT_Tumor'] = dff2.Tumor_TU
print(dff2)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
# columns by ':' and renaming the new columns based on the format
# "DP:FDP:SDP:SUBDP:AU:CU:GU:TU"
dff[['REF_Normal_First', 'REF_Normal_Second']] =
    dff['REF_Normal'].str.split(':', expand=True)
dff[['ALT_Normal_First', 'ALT_Normal_Second']] =
    dff['ALT_Normal'].str.split(':', expand=True)
dff[['REF_Tumor_First', 'REF_Tumor_Second']] =
    dff['REF_Tumor'].str.split(':', expand=True)
dff[['ALT_Tumor_First', 'ALT_Tumor_Second']] =
    dff['ALT_Tumor'].str.split(':', expand=True)
print(dff)

dff1[['REF_Normal_First', 'REF_Normal_Second']] =
    dff1['REF_Normal'].str.split(':', expand=True)

```

```

dff1[['ALT_Normal_First', 'ALT_Normal_Second']] =
    dff1['ALT_Normal'].str.split(',', expand=True)
dff1[['REF_Tumor_First', 'REF_Tumor_Second']] =
    dff1['REF_Tumor'].str.split(',', expand=True)
dff1[['ALT_Tumor_First', 'ALT_Tumor_Second']] =
    dff1['ALT_Tumor'].str.split(',', expand=True)
print(dff1)

dff2[['REF_Normal_First', 'REF_Normal_Second']] =
    dff2['REF_Normal'].str.split(',', expand=True)
dff2[['ALT_Normal_First', 'ALT_Normal_Second']] =
    dff2['ALT_Normal'].str.split(',', expand=True)
dff2[['REF_Tumor_First', 'REF_Tumor_Second']] =
    dff2['REF_Tumor'].str.split(',', expand=True)
dff2[['ALT_Tumor_First', 'ALT_Tumor_Second']] =
    dff2['ALT_Tumor'].str.split(',', expand=True)
print(dff2)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['REF_U', 'ALT_U', 'Normal_AU', 'Normal_CU',
    'Normal_GU', 'Normal_TU', 'Tumor_AU', 'Tumor_CU', 'Tumor_GU',
    'Tumor_TU', 'REF_Normal_Second', 'ALT_Normal_Second',
    'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU', 'Tumor_AU',
    'Tumor_CU', 'Tumor_GU', 'Tumor_TU', 'REF_Tumor_Second',
    'ALT_Tumor_Second'], axis=1)
print(dff)

dff1 = dff1.drop(['REF_U', 'ALT_U', 'Normal_AU', 'Normal_CU',
    'Normal_GU', 'Normal_TU', 'Tumor_AU', 'Tumor_CU', 'Tumor_GU',
    'Tumor_TU', 'REF_Normal_Second', 'ALT_Normal_Second',
    'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU', 'Tumor_AU',
    'Tumor_CU', 'Tumor_GU', 'Tumor_TU', 'REF_Tumor_Second',
    'ALT_Tumor_Second'], axis=1)
print(dff1)

dff2 = dff2.drop(['REF_U', 'ALT_U', 'Normal_AU', 'Normal_CU',
    'Normal_GU', 'Normal_TU', 'Tumor_AU', 'Tumor_CU', 'Tumor_GU',
    'Tumor_TU', 'REF_Normal_Second', 'ALT_Normal_Second',
    'Normal_AU', 'Normal_CU', 'Normal_GU', 'Normal_TU', 'Tumor_AU',
    'Tumor_CU', 'Tumor_GU', 'Tumor_TU', 'REF_Tumor_Second',

```

```

    'ALT_Tumor_Second'], axis=1)
print(dff2)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM_POS', 'REF', 'ALT', 'REF_Normal',
               'ALT_Normal', 'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
               'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First']
print(dff)

dff1.columns = ['CHROM_POS', 'REF', 'ALT', 'REF_Normal',
               'ALT_Normal', 'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
               'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First']
print(dff1)

dff2.columns = ['CHROM_POS', 'REF', 'ALT', 'REF_Normal',
               'ALT_Normal', 'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
               'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First']
print(dff2)

# Converting string values columns to int.
dff['REF_Normal_First'] = dff['REF_Normal_First'].astype(int)
dff['ALT_Normal_First'] = dff['ALT_Normal_First'].astype(int)
dff['REF_Tumor_First'] = dff['REF_Tumor_First'].astype(int)
dff['ALT_Tumor_First'] = dff['ALT_Tumor_First'].astype(int)
print(dff)

dff1['REF_Normal_First'] = dff1['REF_Normal_First'].astype(int)
dff1['ALT_Normal_First'] = dff1['ALT_Normal_First'].astype(int)
dff1['REF_Tumor_First'] = dff1['REF_Tumor_First'].astype(int)
dff1['ALT_Tumor_First'] = dff1['ALT_Tumor_First'].astype(int)
print(dff1)

dff2['REF_Normal_First'] = dff2['REF_Normal_First'].astype(int)
dff2['ALT_Normal_First'] = dff2['ALT_Normal_First'].astype(int)
dff2['REF_Tumor_First'] = dff2['REF_Tumor_First'].astype(int)
dff2['ALT_Tumor_First'] = dff2['ALT_Tumor_First'].astype(int)
print(dff2)

# Adding the values for formula.
dff['SUM'] = dff["REF_Normal_First"] + dff["ALT_Normal_First"]

```

```

dff['COMMON'] = dff["REF_Tumor_First"] + dff["ALT_Tumor_First"]
print(dff)

dff1['SUM'] = dff1["REF_Normal_First"] + dff1["ALT_Normal_First"]
dff1['COMMON'] = dff1["REF_Tumor_First"] + dff1["ALT_Tumor_First"]
print(dff1)

dff2['SUM'] = dff2["REF_Normal_First"] + dff2["ALT_Normal_First"]
dff2['COMMON'] = dff2["REF_Tumor_First"] + dff2["ALT_Tumor_First"]
print(dff2)

# Getting Allele Frequency
dff['Normal'] = dff['ALT_Normal_First']/dff['SUM']
dff['Tumor'] = dff['ALT_Tumor_First']/dff['COMMON']
print(dff)

dff1['Normal'] = dff1['ALT_Normal_First']/dff1['SUM']
dff1['Tumor'] = dff1['ALT_Tumor_First']/dff1['COMMON']
print(dff1)

dff2['Normal'] = dff2['ALT_Normal_First']/dff2['SUM']
dff2['Tumor'] = dff2['ALT_Tumor_First']/dff2['COMMON']
print(dff2)

# Converting string values columns to int.
dff['Normal'] = dff['Normal'].astype(float).round(2)
dff['Tumor'] = dff['Tumor'].astype(float).round(2)
print(dff)

dff1['Normal'] = dff1['Normal'].astype(float).round(2)
dff1['Tumor'] = dff1['Tumor'].astype(float).round(2)
print(dff1)

dff2['Normal'] = dff2['Normal'].astype(float).round(2)
dff2['Tumor'] = dff2['Tumor'].astype(float).round(2)
print(dff2)

# Concatinating the "CHROM" and "POS"
dff["Normal"] = dff['REF'].astype(str) + ':' +
    dff['Normal'].astype(str)

```

```

dff["Tumor"] = dff['REF'].astype(str) + ':' +
    dff['Tumor'].astype(str)
print(dff)

dff1["Normal"] = dff1['REF'].astype(str) + ':' +
    dff1['Normal'].astype(str)
dff1["Tumor"] = dff1['REF'].astype(str) + ':' +
    dff1['Tumor'].astype(str)
print(dff1)

dff2["Normal"] = dff2['REF'].astype(str) + ':' +
    dff2['Normal'].astype(str)
dff2["Tumor"] = dff2['REF'].astype(str) + ':' +
    dff2['Tumor'].astype(str)
print(dff2)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['REF', 'ALT', 'REF_Normal', 'ALT_Normal',
    'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
    'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First',
    'SUM', 'COMMON'], axis=1)
print(dff)

dff1 = dff1.drop(['REF', 'ALT', 'REF_Normal', 'ALT_Normal',
    'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
    'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First',
    'SUM', 'COMMON'], axis=1)
print(dff1)

dff2 = dff2.drop(['REF', 'ALT', 'REF_Normal', 'ALT_Normal',
    'REF_Tumor', 'ALT_Tumor', 'REF_Normal_First',
    'ALT_Normal_First', 'REF_Tumor_First', 'ALT_Tumor_First',
    'SUM', 'COMMON'], axis=1)
print(dff2)

# Merging columns based on "CHROM-POS"
First = pd.merge(dff, dff1, on=['CHROM_POS'])
Third = pd.merge(First, dff2, on=['CHROM_POS'])

# Renaming Columns

```

```

Third.columns = ['CHROM_POS', 'Strelka_Normal_0.3',
                 'Strelka_Tumor_0.3', 'Strelka_0.5_Normal', 'Strelka_0.5_Tumor',
                 'Strelka_0.7_Normal', 'Strelka_0.7_Tumor']
print(Third)

# Assigning column names.
Second.columns = ['CHROM_POS', 'Indel_Normal_0.3',
                 'Indel_Tumor_0.3', 'Indel_Normal_0.5', 'Indel_Tumor_0.5',
                 'Indel_Normal_0.7', 'Indel_Tumor_0.7']
Third.columns = ['CHROM_POS', 'SNP_Normal_0.3', 'SNP_Tumor_0.3',
                 'SNP_Normal_0.5', 'SNP_Tumor_0.5', 'SNP_Normal_0.7',
                 'SNP_Tumor_0.7']
print(Second)
print(Third)

# Using merge function by setting how='inner'
df = pd.merge(Second, Third, on='CHROM_POS', how='outer')
df['Normal_0.3_AF'] =
    df['Indel_Normal_0.3'].combine_first(df['SNP_Normal_0.3'])
df['Tumor_0.3_AF'] =
    df['Indel_Tumor_0.3'].combine_first(df['SNP_Tumor_0.3'])
df['Normal_0.5_AF'] =
    df['Indel_Normal_0.5'].combine_first(df['SNP_Normal_0.5'])
df['Tumor_0.5_AF'] =
    df['Indel_Tumor_0.5'].combine_first(df['SNP_Tumor_0.5'])
df['Normal_0.7_AF'] =
    df['Indel_Normal_0.7'].combine_first(df['SNP_Normal_0.7'])
df['Tumor_0.7_AF'] =
    df['Indel_Tumor_0.7'].combine_first(df['SNP_Tumor_0.7'])
print(df)

# Dropping unneeded columns.
df = df.drop(['Indel_Normal_0.3', 'Indel_Tumor_0.3',
             'Indel_Normal_0.5', 'Indel_Tumor_0.5', 'Indel_Normal_0.7',
             'Indel_Tumor_0.7', 'SNP_Normal_0.3', 'SNP_Tumor_0.3',
             'SNP_Normal_0.5', 'SNP_Tumor_0.5', 'SNP_Normal_0.7',
             'SNP_Tumor_0.7'], axis=1)
print(df)

# Saving the result into a csv file for plotting.

```

```

df.to_csv('Strelka_Allele_Frequency.csv', sep=',', index = False)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
# columns by ':' and renaming the new columns based on the format
# "GT:GQ:DP:AD:ADF:ADR".
df[['Normal_0.3_Allele', 'Normal_0.3_Value']] =
    df['Normal_0.3_AF'].str.split(':', expand=True)
df[['Tumor_0.3_Allele', 'Tumor_0.3_Value']] =
    df['Tumor_0.3_AF'].str.split(':', expand=True)
df[['Normal_0.5_Allele', 'Normal_0.5_Value']] =
    df['Normal_0.5_AF'].str.split(':', expand=True)
df[['Tumor_0.5_Allele', 'Tumor_0.5_Value']] =
    df['Tumor_0.5_AF'].str.split(':', expand=True)
df[['Normal_0.7_Allele', 'Normal_0.7_Value']] =
    df['Normal_0.7_AF'].str.split(':', expand=True)
df[['Tumor_0.7_Allele', 'Tumor_0.7_Value']] =
    df['Tumor_0.7_AF'].str.split(':', expand=True)
print(df)

# Dropping of the unnecessary columns and only choosing the
# "NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
# "TUMOR-DP"
dff = df.drop(['CHROM_POS', 'Normal_0.3_AF', 'Tumor_0.3_AF',
               'Normal_0.5_AF', 'Tumor_0.5_AF', 'Normal_0.7_AF',
               'Tumor_0.7_AF', 'Normal_0.3_Allele', 'Tumor_0.3_Allele',
               'Normal_0.5_Allele', 'Tumor_0.5_Allele', 'Normal_0.7_Allele',
               'Tumor_0.7_Allele'], axis=1)

# Renaming the columns.
dff.columns = ['Normal_0.3', 'Tumor_0.3', 'Normal_0.5',
               'Tumor_0.5', 'Normal_0.7', 'Tumor_0.7']
print(dff)

# Converting string values columns to float.
dff['Normal_0.3'] = dff['Normal_0.3'].astype(float)
dff['Tumor_0.3'] = dff['Tumor_0.3'].astype(float)
dff['Normal_0.5'] = dff['Normal_0.5'].astype(float)
dff['Tumor_0.5'] = dff['Tumor_0.5'].astype(float)
dff['Normal_0.7'] = dff['Normal_0.7'].astype(float)
dff['Tumor_0.7'] = dff['Tumor_0.7'].astype(float)

```

```

print(dff)

# Getting a count based on allele frequency values.
dff1 = dff[dff < 0.26].count()
dff2 = dff[dff < 0.51].count()
dff3 = dff[dff < 0.76].count()
dff4 = dff[dff < 1.01].count()

# Getting the final values
dff5 = (dff1 - dff2).abs()
dff6 = (dff2 - dff3).abs()
dff7 = (dff3 - dff4).abs()
print(dff1)
print(dff5)
print(dff6)
print(dff7)

# Converting into list.
First_Column = dff1.tolist()
Second_Column = dff5.tolist()
Third_Column = dff6.tolist()
Fourth_Column = dff7.tolist()
Fifth_Column = ['Normal_0.3', 'Tumor_0.3', 'Normal_0.5',
                'Tumor_0.5', 'Normal_0.7', 'Tumor_0.7']
print(First_Column)
print(Second_Column)
print(Third_Column)
print(Fourth_Column)

# Declaring new columns.
dff8 = pd.DataFrame(Fifth_Column, columns = ['Type'])
dff8['Less than 0.25'] = First_Column
dff8['Between 0.25 & 0.50'] = Second_Column
dff8['Between 0.50 & 0.75'] = Third_Column
dff8['Between 0.75 & 1.00'] = Fourth_Column
print(dff8)

# Saving the results in csv.
dff8.to_csv('Strelka_Allele_Frequency_Counts.csv', sep=',', index
            = None)

```



```

dff9 = dff8.drop(['Type'], axis=1)
print(dff9)

# Converting the values to a list
List = dff9.values.tolist()
a1, a2, a3, a4, a5, a6 = List
print(a1)
print(a2)
print(a3)
print(a4)
print(a5)

# set width of bar
width = 0.10

# Columns from the file
# a1 = First_Column
# a2 = Second_Column
# a3 = Third_Column
# a4 = Fourth_Column

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]
r4 = [x + width for x in r3]
r5 = [x + width for x in r4]
r6 = [x + width for x in r5]

# Make the plot
plt.bar(r1, a1, color='#ff0000', width=width, edgecolor='white',
        label='Normal_0.3')
plt.bar(r2, a2, color='#ffa07a', width=width, edgecolor='white',
        label='Tumor_0.3')
plt.bar(r3, a3, color='#f08080', width=width, edgecolor='white',
        label='Normal_0.5')
plt.bar(r4, a4, color='#fa8072', width=width, edgecolor='white',
        label='Tumor_0.5')

```

```

plt.bar(r5, a5, color='#b22222', width=width, edgecolor='white',
        label='Normal_0.7')
plt.bar(r6, a6, color='#800000', width=width, edgecolor='white',
        label='Tumor_0.7')

csfont = {'fontname':'Comic Sans MS'}
hfont = {'fontname':'Helvetica'}

# Add xticks on the middle of the group bars
plt.xlabel('Strelka_Allele_Frequencies')
plt.xticks([r + width for r in range(len(a1))], ['<= 0.25', '<= 0.50', '<= 0.75', '<= 1.00'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('Strelka_Allele_Frequency_Plot.pdf')
plt.savefig('Strelka_Allele_Frequency_Plot.png', dpi = 300)

```

Truth Data Allele Frequency

```

# Importing packages.
import numpy as np
import pandas as pd
import matplotlib
import matplotlib.pyplot as plt
import csv

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("Somatic_Truth.frq", sep = '\t', index_col=
    False, error_bad_lines=False)
dff.columns = ['CHROM', 'POS', 'N_ALLELES', 'N_CHR', 'ALLELE:FREQ']
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)

# Reorganising columns.
dff = dff.drop(['N_ALLELES', 'N_CHR', 'CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()

```

```

cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

# Saving the results in csv.
dff.to_csv('Truth_Data.csv', sep=',', index = False)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
  columns by ':' and renaming the new columns based on the format
  "GT:GQ:DP:AD:ADF:ADR".
dff[['Allele', 'Freq']] =
  dff['ALLELE:FREQ'].str.split(':', expand=True)
print(dff)

# Dropping of the unnecessary columns and only choosing the
  "NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
  "TUMOR-DP"
dff = dff.drop(['CHROM_POS', 'ALLELE:FREQ', 'Allele'], axis=1)
print(dff)

# Renaming the columns.
dff.columns = ['Freq']
print(dff)

# Converting string values columns to float.
dff['Freq'] = dff['Freq'].astype(float)
print(dff)

# Getting a count based on allele frequency values.
dff1 = dff[dff < 0.26].count()
dff2 = dff[dff < 0.51].count()
dff3 = dff[dff < 0.76].count()
dff4 = dff[dff < 1.01].count()

# Getting the final values
dff5 = (dff1 - dff2).abs()
dff6 = (dff2 - dff3).abs()
dff7 = (dff3 - dff4).abs()
print(dff1)
print(dff5)

```

```

print(dff6)
print(dff7)

# Converting into list.
First_Column = dff1.tolist()
Second_Column = dff5.tolist()
Third_Column = dff6.tolist()
Fourth_Column = dff7.tolist()
Fifth_Column = ['Truth_Data']
print(First_Column)
print(Second_Column)
print(Third_Column)
print(Fourth_Column)

# Declaring new columns.
dff8 = pd.DataFrame(Fifth_Column, columns = ['Type'])
dff8['Less than 0.25'] = First_Column
dff8['Between 0.25 & 0.50'] = Second_Column
dff8['Between 0.50 & 0.75'] = Third_Column
dff8['Between 0.75 & 1.00'] = Fourth_Column
print(dff8)

# Saving the results in csv.
dff8.to_csv('Truth_Data_Allele_Frequency_Counts.csv', sep=',',
            index = None)

```

VarScan Allele Frequency

```

# Importing packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import csv

```

```

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("VarScan_0.3.frq", sep = '\t', index_col= False)
dff.columns = ['CHROM', 'POS', 'N_ALLELES', 'N_CHR', 'ALLELE:FREQ']
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)

dff2 = pd.read_csv("VarScan_0.5.frq", sep = '\t', index_col= False)
dff2.columns = ['CHROM', 'POS', 'N_ALLELES', 'N_CHR',
    'ALLELE:FREQ']
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

dff3 = pd.read_csv("VarScan_0.7.frq", sep = '\t', index_col= False)
dff3.columns = ['CHROM', 'POS', 'N_ALLELES', 'N_CHR',
    'ALLELE:FREQ']
dff3["CHROM_POS"] = dff3['CHROM'].astype(str) + '-' +
    dff3['POS'].astype(str)

# Reorganising columns.
dff = dff.drop(['N_ALLELES', 'N_CHR', 'CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

dff2 = dff2.drop(['N_ALLELES', 'N_CHR', 'CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

dff3 = dff3.drop(['N_ALLELES', 'N_CHR', 'CHROM', 'POS'], axis=1)
cols = dff3.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff3 = dff3[cols]
print(dff3)

# Merging columns based on "CHROM_POS"
Result = pd.merge(dff, dff2, on="CHROM_POS")
Merge = pd.merge(Result, dff3, on="CHROM_POS")

```

```

Merge.columns = ['CHROM_POS', 'VarScan_0.3_AF', 'VarScan_0.5_AF',
                 'VarScan_0.7_AF']

# Saving the results in csv.
Merge.to_csv('VarScan_Allele_Frequencies.csv', sep=',', index =
            False)

# Creating new columns by splitting the "Allele" and "Value" by
':'.
Merge[['VarScan_0.3_Allele', 'VarScan_0.3_Value']] =
    Merge['VarScan_0.3_AF'].str.split(':', expand=True)
Merge[['VarScan_0.5_Allele', 'VarScan_0.5_Value']] =
    Merge['VarScan_0.5_AF'].str.split(':', expand=True)
Merge[['VarScan_0.7_Allele', 'VarScan_0.7_Value']] =
    Merge['VarScan_0.7_AF'].str.split(':', expand=True)
print(Merge)

# Dropping of the unnecessary columns and only choosing the
"NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
"TUMOR-DP"
dff4 = Merge.drop(['CHROM_POS', 'VarScan_0.3_AF',
                  'VarScan_0.5_AF', 'VarScan_0.7_AF', 'VarScan_0.3_Allele',
                  'VarScan_0.5_Allele', 'VarScan_0.7_Allele'], axis=1)

# Renaming the columns.
dff4.columns = ['VarScan_0.3', 'VarScan_0.5', 'VarScan_0.7']
print(dff4)

# Converting string values columns to float.
dff4['VarScan_0.3'] = dff4['VarScan_0.3'].astype(float)
dff4['VarScan_0.5'] = dff4['VarScan_0.5'].astype(float)
dff4['VarScan_0.7'] = dff4['VarScan_0.7'].astype(float)
print(dff4)

# Getting a count based on allele frequency values.
dff5 = dff4[dff4 < 0.26].count()
dff6 = dff4[dff4 < 0.51].count()
dff7 = dff4[dff4 < 0.76].count()
dff8 = dff4[dff4 < 1.01].count()

```

```

# Getting the final values
dff9 = (dff5 - dff6).abs()
dff10 = (dff6 - dff7).abs()
dff11 = (dff7 - dff8).abs()
print(dff5)
print(dff9)
print(dff10)
print(dff11)

# Converting into list.
First_Column = dff5.tolist()
Second_Column = dff9.tolist()
Third_Column = dff10.tolist()
Fourth_Column = dff11.tolist()
Fifth_Column = ['VarScan_0.3', 'VarScan_0.5', 'VarScan_0.7']
print(First_Column)
print(Second_Column)
print(Third_Column)
print(Fourth_Column)

# Declaring new columns.
dff8 = pd.DataFrame(Fifth_Column, columns = ['Type'])
dff8['Less than 0.25'] = First_Column
dff8['Between 0.25 & 0.50'] = Second_Column
dff8['Between 0.50 & 0.75'] = Third_Column
dff8['Between 0.75 & 1.00'] = Fourth_Column
print(dff8)

# Saving the results in csv.
dff8.to_csv('VarScan_Allele_Frequency_Counts.csv', sep=',', index
           = None)

dff9 = dff8.drop(['Type'], axis=1)
print(dff9)

# Converting the values to a list
List = dff9.values.tolist()
a1, a2, a3 = List
print(a1)
print(a2)

```

```

print(a3)

# set width of bar
width = 0.15

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]

# Make the plot
plt.bar(r1, a1, color='#ff0000', width=width, edgecolor='white',
        label='VarScan_0.3')
plt.bar(r2, a2, color='#ffa07a', width=width, edgecolor='white',
        label='VarScan_0.5')
plt.bar(r3, a3, color='#f08080', width=width, edgecolor='white',
        label='VarScan_0.7')

# Add xticks on the middle of the group bars
plt.xlabel('VarScan_Allele_Frequencies')
plt.xticks([r + width for r in range(len(a1))], ['<= 0.25', '<= 0.50', '<= 0.75', '<= 1.00'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('VarScan_Allele_Frequency_Plot.pdf')
plt.savefig('VarScan_Allele_Frequency_Plot.png', dpi = 300)

```

Allele Frequency Comparison

```

# Importing packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'

```



```

import matplotlib.pyplot as plt
import csv

# Reading csv files and concatenating "CHROM" and "POS"
df = pd.read_csv("Strelka_0.3.csv", sep = '\t', index_col= False)
df1 = pd.read_csv("VarScan_0.3.csv", sep = '\t', index_col= False)
df2 = pd.read_csv("Somatic_Truth.csv", sep = '\t', index_col=
    False)

# Merging columns based on "CHROM-POS"
First = pd.merge(df, df1, on=['CHROM_POS'])
Second = pd.merge(First, df2, on=['CHROM_POS'])

# Renaming Columns
Second.columns = ['CHROM_POS', 'Strelka_Normal', 'Strelka_Tumor',
    'VarScan', 'Truth_Data']
print(Second)

# Saving the results in csv.
Second.to_csv('Tumor_Purity_0.3.csv', sep=',', index = None)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
columns by ':' and renaming the new columns based on the format
"GT:GQ:DP:AD:ADF:ADR".
Second[['Strelka_Normal_Allele', 'Strelka_Normal_Value']] =
    Second['Strelka_Normal'].str.split(':',expand=True)
Second[['Strelka_Tumor_Allele', 'Strelka_Tumor_Value']] =
    Second['Strelka_Tumor'].str.split(':',expand=True)
Second[['VarScan_Normal_Allele', 'VarScan_Normal_Value']] =
    Second['VarScan'].str.split(':',expand=True)
Second[['Truth_Data_Allele', 'Truth_Data_Value']] =
    Second['Truth_Data'].str.split(':',expand=True)
print(Second)

# Dropping of the unnecessary columns and only choosing the
"NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
"TUMOR-DP"
dff = Second.drop(['CHROM_POS', 'Strelka_Normal', 'Strelka_Tumor',
    'VarScan', 'Truth_Data', 'Strelka_Normal_Allele',
    'Strelka_Tumor_Allele', 'VarScan_Normal_Allele',

```

```

    'Truth_Data_Allele'], axis=1)
print(dff)

# Renaming the columns.
dff.columns = ['Strelka_Normal', 'Strelka_Tumor', 'VarScan',
               'Truth_Data']
print(dff)

# Converting string values columns to float.
dff['Strelka_Normal'] = dff['Strelka_Normal'].astype(float)
dff['Strelka_Tumor'] = dff['Strelka_Tumor'].astype(float)
dff['VarScan'] = dff['VarScan'].astype(float)
dff['Truth_Data'] = dff['Truth_Data'].astype(float)
print(dff)

# Getting a count based on allele frequency values.
dff1 = dff[dff < 0.26].count()
dff2 = dff[dff < 0.51].count()
dff3 = dff[dff < 0.76].count()
dff4 = dff[dff < 1.01].count()

# Getting the final values
dff5 = (dff1 - dff2).abs()
dff6 = (dff2 - dff3).abs()
dff7 = (dff3 - dff4).abs()
print(dff1)
print(dff5)
print(dff6)
print(dff7)

# Converting into list.
First_Column = dff1.tolist()
Second_Column = dff5.tolist()
Third_Column = dff6.tolist()
Fourth_Column = dff7.tolist()
Fifth_Column = ['Strelka_Normal', 'Strelka_Tumor', 'VarScan',
                'Truth_Data']
print(First_Column)
print(Second_Column)
print(Third_Column)

```

```

print(Fourth_Columnn)

# Declaring new columns.
dff8 = pd.DataFrame(Fifth_Columnn, columns = ['Type'])
dff8['Less than 0.25'] = First_Columnn
dff8['Between 0.25 & 0.50'] = Second_Columnn
dff8['Between 0.50 & 0.75'] = Third_Columnn
dff8['Between 0.75 & 1.00'] = Fourth_Columnn
print(dff8)

# Saving the results in csv.
dff8.to_csv('Tumor_Purity_0.3_AF_Counts.csv', sep=',', index =
            None)

# set width of bar
width = 0.25

# Columns from the file
a1 = First_Columnn
a2 = Second_Columnn
a3 = Third_Columnn
a4 = Fourth_Columnn

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]
r4 = [x + width for x in r3]

# Make the plot
plt.bar(r1, a1, color='#FFD700', width=width, edgecolor='white',
        label='Strelka_Normal')
plt.bar(r2, a2, color='#FFAA1C', width=width, edgecolor='white',
        label='Strelka_Tumor')
plt.bar(r3, a3, color='#FF8C01', width=width, edgecolor='white',
        label='VarScan')
plt.bar(r4, a4, color='#FF0000', width=width, edgecolor='white',
        label='Truth_Data')

# Add xticks on the middle of the group bars

```

```
plt.xlabel('Tumor_0.3_Allele_Frequencies')
plt.xticks([r + width for r in range(len(a1))], ['<= 0.25', '<= 0.50', '<= 0.75', '<= 1.00'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('Tumor_Purity_0.3_AF_Plot.pdf')
plt.savefig('Tumor_Purity_0.3_AF_Plot.png', dpi = 300)
```

Appendix C

Appendix D

Strelka Positions, SNPs, Indels

```
# Importing packages.
import numpy as np
import pandas as pd

# Inputing vcf files for positions.
df = pd.read_csv("Updated_Strelka_0.3.vcf", sep = '\t', index_col=
False)
df1 = pd.read_csv("Updated_Strelka_0.5.vcf", sep = '\t',
index_col= False)
df2 = pd.read_csv("Updated_Strelka_0.7.vcf", sep = '\t',
index_col= False)

# Inputing vcf files for SNPs.
df3 = pd.read_csv("Updated_Strelka_0.3_SNPs.vcf", sep = '\t',
index_col= False)
df4 = pd.read_csv("Updated_Strelka_0.5_SNPs.vcf", sep = '\t',
index_col= False)
df5 = pd.read_csv("Updated_Strelka_0.7_SNPs.vcf", sep = '\t',
index_col= False)

# Inputing vcf files for Indels.
df6 = pd.read_csv("Updated_Strelka_0.3_Indels.vcf", sep = '\t',
index_col= False)
df7 = pd.read_csv("Updated_Strelka_0.5_Indels.vcf", sep = '\t',
index_col= False)
df8 = pd.read_csv("Updated_Strelka_0.7_Indels.vcf", sep = '\t',
index_col= False)
```

```

# Outcome for positions.
Strelka3_Positions = len(df)
Strelka5_Positions = len(df1)
Strelka7_Positions = len(df2)

print("Number of positions in Strelka 0.3:")
print(Strelka3_Positions)
print("Number of positions in Strelka 0.5:")
print(Strelka5_Positions)
print("Number of positions in Strelka 0.7:")
print(Strelka7_Positions)

# Outcome for SNPs.
Strelka3_SNPs = len(df3)
Strelka5_SNPs = len(df4)
Strelka7_SNPs = len(df5)

print("Number of SNPs in Strelka 0.3:")
print(Strelka3_SNPs)
print("Number of SNPs in Strelka 0.5:")
print(Strelka5_SNPs)
print("Number of SNPs in Strelka 0.7:")
print(Strelka7_SNPs)

# Outcome for SNPs.
Strelka3_Indels = len(df6)
Strelka5_Indels = len(df7)
Strelka7_Indels = len(df8)

print("Number of Indels in Strelka 0.3:")
print(Strelka3_Indels)
print("Number of Indels in Strelka 0.5:")
print(Strelka5_Indels)
print("Number of Indels in Strelka 0.7:")
print(Strelka7_Indels)

# Declaring a new dataframe.
df = []

```

```

# Taking all combinations as a list.
data = {'Type': ['Strelka_Tumor_Purity_0.3',
                'Strelka_Tumor_Purity_0.5', 'Strelka_Tumor_Purity_0.7'],
        'Strelka_Positions': [Strelka3_Positions, Strelka5_Positions,
                               Strelka7_Positions], 'Strelka_SNPs': [Strelka3_SNPs,
                               Strelka5_SNPs, Strelka7_SNPs], 'Strelka_INDELS':
        [Strelka3_Indels, Strelka5_Indels, Strelka7_Indels]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
print(df)

# Saving the results in csv.
df.to_csv('Strelka_Counts.csv', sep=',', index = None)

```

Truth Data Positions, SNPs, Indels

```

# Importing packages.
import numpy as np
import pandas as pd

# Inputting vcf files for positions.
df1 = pd.read_csv("Updated_Somatic_Truth.vcf", sep = '\t',
                  index_col= False)

# Inputting vcf files for SNPs.
df2 = pd.read_csv("Updated_Somatic_Truth_SNPs.vcf", sep = '\t',
                  index_col= False)

# Inputting vcf files for Indels.
df3 = pd.read_csv("Updated_Somatic_Truth_Indels.vcf", sep = '\t',
                  index_col= False)

# Outcome for positions.
Truth_Positions = len(df1)

print("Number of positions in Somatic Truth:")
print(Truth_Positions)

```



```

# Outcome for SNPs.
Truth_SNPs = len(df2)

print("Number of SNPs in Somatic Truth:")
print(Truth_SNPs)

# Outcome for SNPs.
Truth_Indels = len(df3)

print("Number of Indels in Somatic Truth:")
print(Truth_Indels)

# Declaring a new dataframe.
df = []

# Taking all combinations as a list.
data = {'Type': ['Somatic_Truth'], 'Truth_Positions':
        [Truth_Positions], 'Truth_SNPs': [Truth_SNPs], 'Truth_INDELS':
        [Truth_Indels]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
print(df)

# Saving the results in csv.
df.to_csv('Truth_Counts.csv', sep=',', index = None)

```

VarScan Positions, SNPs, Indels

```

# Importing packages.
import numpy as np
import pandas as pd

# Inputting vcf files for positions.
df = pd.read_csv("Updated_VarScan_0.3.vcf", sep = '\t', index_col=
False)

```

```

df1 = pd.read_csv("Updated_VarScan_0.5.vcf", sep = '\t',
    index_col= False)
df2 = pd.read_csv("Updated_VarScan_0.7.vcf", sep = '\t',
    index_col= False)

# Inputing vcf files for SNPs.
df3 = pd.read_csv("Updated_VarScan_0.3_SNPs.vcf", sep = '\t',
    index_col= False)
df4 = pd.read_csv("Updated_VarScan_0.5_SNPs.vcf", sep = '\t',
    index_col= False)
df5 = pd.read_csv("Updated_VarScan_0.7_SNPs.vcf", sep = '\t',
    index_col= False)

# Inputing vcf files for Indels.
df6 = pd.read_csv("Updated_VarScan_0.3_Indels.vcf", sep = '\t',
    index_col= False)
df7 = pd.read_csv("Updated_VarScan_0.5_Indels.vcf", sep = '\t',
    index_col= False)
df8 = pd.read_csv("Updated_VarScan_0.7_Indels.vcf", sep = '\t',
    index_col= False)

# Outcome for positions.
VarScan3_Positions = len(df)
VarScan5_Positions = len(df1)
VarScan7_Positions = len(df2)

print("Number of positions in VarScan 0.3:")
print(VarScan3_Positions)
print("Number of positions in VarScan 0.5:")
print(VarScan5_Positions)
print("Number of positions in VarScan 0.7:")
print(VarScan7_Positions)

# Outcome for SNPs.
VarScan3_SNPs = len(df3)
VarScan5_SNPs = len(df4)
VarScan7_SNPs = len(df5)

print("Number of SNPs in VarScan 0.3:")
print(VarScan3_SNPs)

```

```

print("Number of SNPs in VarScan 0.5:")
print(VarScan5_SNPs)
print("Number of SNPs in VarScan 0.7:")
print(VarScan7_SNPs)

# Outcome for SNPs.
VarScan3_Indels = len(df6)
VarScan5_Indels = len(df7)
VarScan7_Indels = len(df8)

print("Number of Indels in VarScan 0.3:")
print(VarScan3_Indels)
print("Number of Indels in VarScan 0.5:")
print(VarScan5_Indels)
print("Number of Indels in VarScan 0.7:")
print(VarScan7_Indels)

# Declaring a new dataframe.
df = []

# Taking all combinations as a list.
data = {'Type': ['VarScan_Tumor_Purity_0.3',
                'VarScan_Tumor_Purity_0.5', 'VarScan_Tumor_Purity_0.7'],
        'VarScan_Positions': [VarScan3_Positions, VarScan5_Positions,
                               VarScan7_Positions], 'VarScan_SNPs': [VarScan3_SNPs,
                               VarScan5_SNPs, VarScan7_SNPs], 'VarScan_INDELS':
        [VarScan3_Indels, VarScan5_Indels, VarScan7_Indels]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
print(df)

# Saving the results in csv.
df.to_csv('VarScan_Counts.csv', sep=',', index = None)

```

Positions Comparison

```
# Importing packages.
```

```

import numpy as np
import pandas as pd
import matplotlib
from matplotlib import pyplot as plt
from matplotlib_venn import venn3_circles, venn3_unweighted
from matplotlib_venn import _common, _venn3
from matplotlib.patches import Circle
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'

# Reading csv files and concatenating "CHROM" and "POS"
df = pd.read_csv("Updated_Strelka_0.3.vcf", sep = '\t', index_col=
    False)
df1 = pd.read_csv("Updated_VarScan_0.3.vcf", sep = '\t',
    index_col= False)
df2 = pd.read_csv("Updated_Somatic_Truth.vcf", sep = '\t',
    index_col= False)

# Merging columns based on "POS"
First = pd.merge(df, df1, on=['POS'])
Second = pd.merge(df1, df2, on=['POS'])
Third = pd.merge(df, df2, on=['POS'])
Fourth = pd.merge(First, df2, on=['POS'])

# Position outcomes.
print("Number of Strelka Positions:")
Strelka_Positions = len(df)
print(Strelka_Positions)

print("Number of VarScan Positions:")
VarScan_Positions = len(df1)
print(VarScan_Positions)

print("Number of Truth Data Positions:")
Truth_Positions = len(df2)
print(Truth_Positions)

print("Number of Positions in Strelka and VarScan:")
Strelka_VarScan_Positions = len(First)

```

```

print(Strelka_VarScan_Positions)

print("Number of Positions in VarScan and Truth Data:")
VarScan_Truth_Positions = len(Second)
print(VarScan_Truth_Positions)

print("Number of Positions in Truth Data and Strelka:")
Strelka_Truth_Positions = len(Third)
print(Strelka_Truth_Positions)

print("Number of Positions in Strelka, VarScan & Truth Data:")
Strelka_VarScan_Truth_Positions = len(Fourth)
print(Strelka_VarScan_Truth_Positions)

# Declaring a new dataframe.
df3 = []

# Taking all combinations as a list.
data = {'Type': ['Strelka', 'VarScan', 'Truth_Data',
                'Strelka_and_VarScan', 'VarScan_and_Truth_Data',
                'Truth_Data_and_Strelka',
                'Strelka_and_VarScan_and_Truth_Data'], 'Positions':
        [Strelka_Positions, VarScan_Positions, Truth_Positions,
         Strelka_VarScan_Positions, VarScan_Truth_Positions,
         Strelka_Truth_Positions, Strelka_VarScan_Truth_Positions]}

# Collecting it into a dataframe.
df3 = pd.DataFrame(data)
print(df3)

# Saving the results in csv.
df3.to_csv('Positions_Count.csv', sep=',', index = None)

# Formulas
Strelka_Exclude = Strelka_Positions - (Strelka_VarScan_Positions +
    Strelka_Truth_Positions + Strelka_VarScan_Truth_Positions)
VarScan_Exclude = VarScan_Positions - (Strelka_VarScan_Positions +
    VarScan_Truth_Positions + Strelka_VarScan_Truth_Positions)
Truth_Exclude = Truth_Positions - (VarScan_Truth_Positions +
    Strelka_Truth_Positions + Strelka_VarScan_Truth_Positions)

```

```

# Set of values.
subsets = (Strelka_Exclude, VarScan_Exclude,
            Strelka_VarScan_Positions, Truth_Exclude,
            Strelka_Truth_Positions, VarScan_Truth_Positions,
            Strelka_VarScan_Truth_Positions)

# Adding venn diagram.
v = venn3_unweighted(subsets, set_labels = ('Strelka_0.3',
      'VarScan_0.3', 'Truth_Data'), set_colors=('red', 'orange',
      'skyblue'))
areas = (1, 1, 1, 1, 1, 1, 1)
centers, radii = _venn3.solve_venn3_circles(areas)

# Saving the values.
plt.title("Positions [SNPs + Indels]")
plt.show()
plt.savefig('Tumor_Purity_0.3_Positions_Plot.pdf')
plt.savefig('Tumor_Purity_0.3_Positions_Plot.png', dpi = 300)

```

SNPs Comparison

```

# Importing packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
from matplotlib import pyplot as plt
from matplotlib_venn import venn3_circles, venn3_unweighted
from matplotlib_venn import _common, _venn3
from matplotlib.patches import Circle

# Reading csv files and concatenating "CHROM" and "POS"
df = pd.read_csv("Updated_Strelka_0.3_SNPs.vcf", sep = '\t',
                index_col= False)

```

```

df1 = pd.read_csv("Updated_VarScan_0.3_SNPs.vcf", sep = '\t',
                  index_col= False)
df2 = pd.read_csv("Updated_Somatic_Truth_SNVs.vcf", sep = '\t',
                  index_col= False)
print("Length of Strelka SNPs:")
Strelka_SNPs = len(df)
print(Strelka_SNPs)
print("Length of VarScan SNPs:")
VarScan_SNPs = len(df1)
print(VarScan_SNPs)
print("Length of Truth SNPs:")
Truth_SNPs = len(df2)
print(Truth_SNPs)

# Adding REF and ALT
df["REF_ALT"] = df["REF"] + df["ALT"]
df1["REF_ALT"] = df1["REF"] + df1["ALT"]
df2["REF_ALT"] = df2["REF"] + df2["ALT"]

# Merging columns based on "POS"
First = pd.merge(df, df1, on=['POS'])
Second = pd.merge(df1, df2, on=['POS'])
Third = pd.merge(df, df2, on=['POS'])
Fourth = pd.merge(First, df2, on=['POS'])

# Dropping of the unnecessary columns.
First = First.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Second = Second.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Third = Third.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Fourth = Fourth.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y', 'REF',
                     'ALT'], axis=1)
print(First)
print(Second)
print(Third)
print(Fourth)

# Conditional replacement.
First['Result'] = np.where(First["REF_ALT_x"] ==
                          First["REF_ALT_y"], 0, 1)
First = First[First["Result"] == 0]

```

```

print(First)

Second['Result'] = np.where(Second["REF_ALT_x"] ==
    Second["REF_ALT_y"], 0, 1)
Second = Second[Second["Result"] == 0]
print(Second)

Third['Result'] = np.where(Third["REF_ALT_x"] ==
    Third["REF_ALT_y"], 0, 1)
Third = Third[Third["Result"] == 0]
print(Third)

Fourth['Result'] = np.where(((Fourth["REF_ALT_x"] ==
    Fourth["REF_ALT_y"]) & (Fourth["REF_ALT_x"] ==
    Fourth["REF_ALT"])) & (Fourth["REF_ALT_y"] ==
    Fourth["REF_ALT"])), 0, 1)
Fourth = Fourth[Fourth["Result"] == 0]
print(Fourth)

# Position outcomes.
print("Number of SNPs in Strelka and VarScan:")
Strelka_VarScan_SNPs = len(First)
print(Strelka_VarScan_SNPs)

print("Number of SNPs in VarScan and Truth Data:")
VarScan_Truth_SNPs = len(Second)
print(VarScan_Truth_SNPs)

print("Number of SNPs in Truth Data and Strelka:")
Strelka_Truth_SNPs = len(Third)
print(Strelka_Truth_SNPs)

print("Number of SNPs in Strelka, VarScan & Truth Data:")
Strelka_VarScan_Truth_SNPs = len(Fourth)
print(Strelka_VarScan_Truth_SNPs)

# Declaring a new dataframe.
df3 = []

# Taking all combinations as a list.

```



```

data = {'Type': ['Strelka', 'VarScan', 'Truth_Data',
                'Strelka_and_VarScan', 'VarScan_and_Truth_Data',
                'Truth_Data_and_Strelka',
                'Strelka_and_VarScan_and_Truth_Data'], 'SNPs': [Strelka_SNPs,
                VarScan_SNPs, Truth_SNPs, Strelka_VarScan_SNPs,
                VarScan_Truth_SNPs, Strelka_Truth_SNPs,
                Strelka_VarScan_Truth_SNPs]}

# Collecting it into a dataframe.
df3 = pd.DataFrame(data)
print(df3)

# Saving the results in csv.
df3.to_csv('SNPs_Count.csv', sep=',', index = None)

# Formulas
Strelka_Exclude = Strelka_SNPs - Strelka_VarScan_SNPs -
    Strelka_Truth_SNPs - Strelka_VarScan_Truth_SNPs
VarScan_Exclude = VarScan_SNPs - Strelka_VarScan_SNPs -
    VarScan_Truth_SNPs - Strelka_VarScan_Truth_SNPs
Truth_Exclude = Truth_SNPs - VarScan_Truth_SNPs -
    Strelka_Truth_SNPs - Strelka_VarScan_Truth_SNPs

# Set of values.
subsets = (Strelka_Exclude, VarScan_Exclude, Strelka_VarScan_SNPs,
            Truth_Exclude, Strelka_Truth_SNPs, VarScan_Truth_SNPs,
            Strelka_VarScan_Truth_SNPs)

# Adding venn diagram.
v = venn3_unweighted(subsets, set_labels = ('Strelka_0.3',
            'VarScan_0.3', 'Truth_Data'), set_colors=('red', 'orange',
            'skyblue'))
areas = (1, 1, 1, 1, 1, 1, 1)
centers, radii = _venn3.solve_venn3_circles(areas)

# Saving the values.
plt.title("SNPs")
plt.show()
plt.savefig('Tumor_Purity_0.3_SNPs_Plot.pdf')
plt.savefig('Tumor_Purity_0.3_SNPs_Plot.png', dpi = 300)

```

Indels Comparison

```
# Importing packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
from matplotlib import pyplot as plt
from matplotlib_venn import venn3_circles, venn3_unweighted
from matplotlib_venn import _common, _venn3
from matplotlib.patches import Circle

# Reading csv files and concatenating "CHROM" and "POS"
df = pd.read_csv("Updated_Strelka_0.3_Indels.vcf", sep = '\t',
    index_col= False)
df1 = pd.read_csv("Updated_VarScan_0.3_Indels.vcf", sep = '\t',
    index_col= False)
df2 = pd.read_csv("Updated_Somatic_Truth_Indels.vcf", sep = '\t',
    index_col= False)
print("Length of Strelka Indels:")
Strelka_Indels = len(df)
print(Strelka_Indels)
print("Length of VarScan Indels:")
VarScan_Indels = len(df1)
print(VarScan_Indels)
print("Length of Truth Indels:")
Truth_Indels = len(df2)
print(Truth_Indels)

# Adding REF and ALT
df["REF_ALT"] = df["REF"] + df["ALT"]
df1["REF_ALT"] = df1["REF"] + df1["ALT"]
df2["REF_ALT"] = df2["REF"] + df2["ALT"]

# Merging columns based on "POS"
First = pd.merge(df, df1, on=['POS'])
Second = pd.merge(df1, df2, on=['POS'])
```

```

Third = pd.merge(df, df2, on=['POS'])
Fourth = pd.merge(First, df2, on=['POS'])

# Dropping of the unnecessary columns.
First = First.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Second = Second.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Third = Third.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y'], axis=1)
Fourth = Fourth.drop(['REF_x', 'ALT_x', 'REF_y', 'ALT_y', 'REF',
                      'ALT'], axis=1)
print(First)
print(Second)
print(Third)
print(Fourth)

# Conditional replacement.
First['Result'] = np.where(First["REF_ALT_x"] ==
                          First["REF_ALT_y"], 0, 1)
First = First[First["Result"] == 0]
print(First)

Second['Result'] = np.where(Second["REF_ALT_x"] ==
                          Second["REF_ALT_y"], 0, 1)
Second = Second[Second["Result"] == 0]
print(Second)

Third['Result'] = np.where(Third["REF_ALT_x"] ==
                          Third["REF_ALT_y"], 0, 1)
Third = Third[Third["Result"] == 0]
print(Third)

Fourth['Result'] = np.where(((Fourth["REF_ALT_x"] ==
                          Fourth["REF_ALT_y"]) & (Fourth["REF_ALT_x"] ==
                          Fourth["REF_ALT"])) & (Fourth["REF_ALT_y"] ==
                          Fourth["REF_ALT"])), 0, 1)
Fourth = Fourth[Fourth["Result"] == 0]
print(Fourth)

# Position outcomes.
print("Number of Indels in Strelka and VarScan:")
Strelka_VarScan_Indels = len(First)

```

```

print(Strelka_VarScan_Indels)

print("Number of Indels in VarScan and Truth Data:")
VarScan_Truth_Indels = len(Second)
print(VarScan_Truth_Indels)

print("Number of SNPs in Truth Data and Strelka:")
Strelka_Truth_Indels = len(Third)
print(Strelka_Truth_Indels)

print("Number of SNPs in Strelka, VarScan & Truth Data:")
Strelka_VarScan_Truth_Indels = len(Fourth)
print(Strelka_VarScan_Truth_Indels)

# Declaring a new dataframe.
df3 = []

# Taking all combinations as a list.
data = {'Type': ['Strelka', 'VarScan', 'Truth_Data',
                'Strelka_and_VarScan', 'VarScan_and_Truth_Data',
                'Truth_Data_and_Strelka',
                'Strelka_and_VarScan_and_Truth_Data'], 'INDELS':
        [Strelka_Indels, VarScan_Indels, Truth_Indels,
         Strelka_VarScan_Indels, VarScan_Truth_Indels,
         Strelka_Truth_Indels, Strelka_VarScan_Truth_Indels]}

# Collecting it into a dataframe.
df3 = pd.DataFrame(data)
print(df3)

# Saving the results in csv.
df3.to_csv('Indels_Count.csv', sep=',', index = None)

# Formulas
Strelka_Exclude = Strelka_Indels - Strelka_VarScan_Indels -
                  Strelka_Truth_Indels - Strelka_VarScan_Truth_Indels
VarScan_Exclude = VarScan_Indels - Strelka_VarScan_Indels -
                  VarScan_Truth_Indels - Strelka_VarScan_Truth_Indels
Truth_Exclude = Truth_Indels - VarScan_Truth_Indels -
                Strelka_Truth_Indels - Strelka_VarScan_Truth_Indels

```

```

# Set of values.
subsets = (Strelka_Exclude, VarScan_Exclude,
           Strelka_VarScan_Indels, Truth_Exclude, Strelka_Truth_Indels,
           VarScan_Truth_Indels, Strelka_VarScan_Truth_Indels)

# Adding venn diagram.
v = venn3_unweighted(subsets, set_labels = ('Strelka_0.3',
      'VarScan_0.3', 'Truth_Data'), set_colors=('red', 'orange',
      'skyblue'))
areas = (1, 1, 1, 1, 1, 1, 1)
centers, radii = _venn3.solve_venn3_circles(areas)

# Saving the values.
plt.title("Indels")
plt.show()
plt.savefig('Tumor_Purity_0.3_Indels_Plot.pdf')
plt.savefig('Tumor_Purity_0.3_Indels_Plot.png', dpi = 300)

```

Appendix E

Strelka Read Depth

```
# Importing the needed packages.
import numpy as np
import pandas as pd

# Reading the csv input file that is obtained after performing the
# following operations on the vcf file.
# Step 1 - 'cut -f 1-2, 9-11 Input-VCF-File > Output-VCF-File'
# Step 2 - 'sed '/^#/d' Output-VCF-File > Updated_Output-VCF-File'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_Strelka_0.3.vcf", sep = '\t',
                  index_col= False)
dff1 = pd.read_csv("Updated_Strelka_0.5.vcf", sep = '\t',
                  index_col= False)
dff2 = pd.read_csv("Updated_Strelka_0.7.vcf", sep = '\t',
                  index_col= False)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'NORMAL', 'TUMOR', '2:NORMAL',
               '2:TUMOR']
dff1.columns = ['CHROM', 'POS', 'NORMAL', 'TUMOR', '2:NORMAL',
                '2:TUMOR']
dff2.columns = ['CHROM', 'POS', 'NORMAL', 'TUMOR', '2:NORMAL',
                '2:TUMOR']

# Concatinating the "CHROM" and "POS"
```

```

dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff2["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]
print(dff1)

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
columns by ':' and renaming the new columns based on the format
"DP:FDP:SDP:SBDP:AU:CU:GU:TU"
dff[['Normal_Read_Depth', 'NORMAL-FDP', 'NORMAL-SDP',
    'NORMAL-SBDP', 'NORMAL-AU', 'NORMAL-CU', 'NORMAL-GU',
    'NORMAL-TU', 'NORMAL-Last']] =
    dff['NORMAL'].str.split(':', expand=True)
dff[['Tumor_Read_Depth', 'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SBDP',
    'TUMOR-AU', 'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last']]
    = dff['TUMOR'].str.split(':', expand=True)
dff[['2:Normal_Read_Depth', 'NORMAL1-FDP', 'NORMAL1-SDP',
    'NORMAL1-SBDP', 'NORMAL1-AU', 'NORMAL1-CU', 'NORMAL1-GU',
    'NORMAL1-TU', 'NORMAL1-Last']] =
    dff['2:NORMAL'].str.split(':', expand=True)

```

```

dff[['2:Tumor_Read_Depth', 'TUMOR1-FDP', 'TUMOR1-SDP',
    'TUMOR1-SUBDP', 'TUMOR1-AU', 'TUMOR1-CU', 'TUMOR1-GU',
    'TUMOR1-TU', 'TUMOR1-Last']] =
dff['2:TUMOR'].str.split(':',expand=True)

dff1[['Normal_Read_Depth', 'NORMAL-FDP', 'NORMAL-SDP',
    'NORMAL-SUBDP', 'NORMAL-AU', 'NORMAL-CU', 'NORMAL-GU',
    'NORMAL-TU', 'NORMAL-Last']] =
dff1['NORMAL'].str.split(':',expand=True)
dff1[['Tumor_Read_Depth', 'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SUBDP',
    'TUMOR-AU', 'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last']]
    = dff1['TUMOR'].str.split(':',expand=True)
dff1[['2:Normal_Read_Depth', 'NORMAL1-FDP', 'NORMAL1-SDP',
    'NORMAL1-SUBDP', 'NORMAL1-AU', 'NORMAL1-CU', 'NORMAL1-GU',
    'NORMAL1-TU', 'NORMAL1-Last']] =
dff1['2:NORMAL'].str.split(':',expand=True)
dff1[['2:Tumor_Read_Depth', 'TUMOR1-FDP', 'TUMOR1-SDP',
    'TUMOR1-SUBDP', 'TUMOR1-AU', 'TUMOR1-CU', 'TUMOR1-GU',
    'TUMOR1-TU', 'TUMOR1-Last']] =
dff1['2:TUMOR'].str.split(':',expand=True)

dff2[['Normal_Read_Depth', 'NORMAL-FDP', 'NORMAL-SDP',
    'NORMAL-SUBDP', 'NORMAL-AU', 'NORMAL-CU', 'NORMAL-GU',
    'NORMAL-TU', 'NORMAL-Last']] =
dff2['NORMAL'].str.split(':',expand=True)
dff2[['Tumor_Read_Depth', 'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SUBDP',
    'TUMOR-AU', 'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last']]
    = dff2['TUMOR'].str.split(':',expand=True)
dff2[['2:Normal_Read_Depth', 'NORMAL1-FDP', 'NORMAL1-SDP',
    'NORMAL1-SUBDP', 'NORMAL1-AU', 'NORMAL1-CU', 'NORMAL1-GU',
    'NORMAL1-TU', 'NORMAL1-Last']] =
dff2['2:NORMAL'].str.split(':',expand=True)
dff2[['2:Tumor_Read_Depth', 'TUMOR1-FDP', 'TUMOR1-SDP',
    'TUMOR1-SUBDP', 'TUMOR1-AU', 'TUMOR1-CU', 'TUMOR1-GU',
    'TUMOR1-TU', 'TUMOR1-Last']] =
dff2['2:TUMOR'].str.split(':',expand=True)

# Dropping of the unnecessary columns and only choosing the
  "NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
  "TUMOR-DP"

```



```

dff = dff.drop(['NORMAL', 'TUMOR', '2:NORMAL', '2:TUMOR',
               'NORMAL-FDP', 'NORMAL-SDP', 'NORMAL-SUBDP', 'NORMAL-AU',
               'NORMAL-CU', 'NORMAL-GU', 'NORMAL-TU', 'NORMAL-Last',
               'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SUBDP', 'TUMOR-AU',
               'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last',
               'NORMAL1-FDP', 'NORMAL1-SDP', 'NORMAL1-SUBDP', 'NORMAL1-AU',
               'NORMAL1-CU', 'NORMAL1-GU', 'NORMAL1-TU', 'NORMAL1-Last',
               'TUMOR1-FDP', 'TUMOR1-SDP', 'TUMOR1-SUBDP', 'TUMOR1-AU',
               'TUMOR1-CU', 'TUMOR1-GU', 'TUMOR1-TU', 'TUMOR1-Last'], axis=1)

dff1 = dff1.drop(['NORMAL', 'TUMOR', '2:NORMAL', '2:TUMOR',
                 'NORMAL-FDP', 'NORMAL-SDP', 'NORMAL-SUBDP', 'NORMAL-AU',
                 'NORMAL-CU', 'NORMAL-GU', 'NORMAL-TU', 'NORMAL-Last',
                 'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SUBDP', 'TUMOR-AU',
                 'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last',
                 'NORMAL1-FDP', 'NORMAL1-SDP', 'NORMAL1-SUBDP', 'NORMAL1-AU',
                 'NORMAL1-CU', 'NORMAL1-GU', 'NORMAL1-TU', 'NORMAL1-Last',
                 'TUMOR1-FDP', 'TUMOR1-SDP', 'TUMOR1-SUBDP', 'TUMOR1-AU',
                 'TUMOR1-CU', 'TUMOR1-GU', 'TUMOR1-TU', 'TUMOR1-Last'], axis=1)

dff2 = dff2.drop(['NORMAL', 'TUMOR', '2:NORMAL', '2:TUMOR',
                 'NORMAL-FDP', 'NORMAL-SDP', 'NORMAL-SUBDP', 'NORMAL-AU',
                 'NORMAL-CU', 'NORMAL-GU', 'NORMAL-TU', 'NORMAL-Last',
                 'TUMOR-FDP', 'TUMOR-SDP', 'TUMOR-SUBDP', 'TUMOR-AU',
                 'TUMOR-CU', 'TUMOR-GU', 'TUMOR-TU', 'TUMOR-Last',
                 'NORMAL1-FDP', 'NORMAL1-SDP', 'NORMAL1-SUBDP', 'NORMAL1-AU',
                 'NORMAL1-CU', 'NORMAL1-GU', 'NORMAL1-TU', 'NORMAL1-Last',
                 'TUMOR1-FDP', 'TUMOR1-SDP', 'TUMOR1-SUBDP', 'TUMOR1-AU',
                 'TUMOR1-CU', 'TUMOR1-GU', 'TUMOR1-TU', 'TUMOR1-Last'], axis=1)

# Replacing '.' values with '0'
dff.replace('.', '0', inplace=True)
dff1.replace('.', '0', inplace=True)
dff2.replace('.', '0', inplace=True)

# Converting string values columns to int.
dff['Normal_Read_Depth'] = dff['Normal_Read_Depth'].astype(int)
dff['2:Normal_Read_Depth'] = dff['2:Normal_Read_Depth'].astype(int)
dff['Tumor_Read_Depth'] = dff['Tumor_Read_Depth'].astype(int)
dff['2:Tumor_Read_Depth'] = dff['2:Tumor_Read_Depth'].astype(int)

```

```

dff1['Normal_Read_Depth'] = dff1['Normal_Read_Depth'].astype(int)
dff1['2:Normal_Read_Depth'] =
    dff1['2:Normal_Read_Depth'].astype(int)
dff1['Tumor_Read_Depth'] = dff1['Tumor_Read_Depth'].astype(int)
dff1['2:Tumor_Read_Depth'] = dff1['2:Tumor_Read_Depth'].astype(int)

dff2['Normal_Read_Depth'] = dff2['Normal_Read_Depth'].astype(int)
dff2['2:Normal_Read_Depth'] =
    dff2['2:Normal_Read_Depth'].astype(int)
dff2['Tumor_Read_Depth'] = dff2['Tumor_Read_Depth'].astype(int)
dff2['2:Tumor_Read_Depth'] = dff2['2:Tumor_Read_Depth'].astype(int)

# Adding columns for single read depth value.
dff['Normal_RD'] = dff["Normal_Read_Depth"] +
    dff["2:Normal_Read_Depth"]
dff['Tumor_RD'] = dff["Tumor_Read_Depth"] +
    dff["2:Tumor_Read_Depth"]

dff1['Normal_RD'] = dff1["Normal_Read_Depth"] +
    dff1["2:Normal_Read_Depth"]
dff1['Tumor_RD'] = dff1["Tumor_Read_Depth"] +
    dff1["2:Tumor_Read_Depth"]

dff2['Normal_RD'] = dff2["Normal_Read_Depth"] +
    dff2["2:Normal_Read_Depth"]
dff2['Tumor_RD'] = dff2["Tumor_Read_Depth"] +
    dff2["2:Tumor_Read_Depth"]

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['Normal_Read_Depth', 'Tumor_Read_Depth',
    '2:Normal_Read_Depth', '2:Tumor_Read_Depth'], axis=1)
dff.columns = ['CHROM_POS', 'Normal_Read_Depth',
    'Tumor_Read_Depth']
print(dff)

dff1 = dff1.drop(['Normal_Read_Depth', 'Tumor_Read_Depth',
    '2:Normal_Read_Depth', '2:Tumor_Read_Depth'], axis=1)
dff1.columns = ['CHROM_POS', 'Normal_Read_Depth',
    'Tumor_Read_Depth']

```

```

print(dff1)

dff2 = dff2.drop(['Normal_Read_Depth', 'Tumor_Read_Depth',
                 '2:Normal_Read_Depth', '2:Tumor_Read_Depth'], axis=1)
dff2.columns = ['CHROM_POS', 'Normal_Read_Depth',
                'Tumor_Read_Depth']
print(dff2)

# Merging columns based on "CHROM-POS"
First = pd.merge(dff, dff1, on=['CHROM_POS'])
Second = pd.merge(First, dff2, on=['CHROM_POS'])

# Renaming Columns
Second.columns = ['CHROM_POS', 'Strelka_Normal_0.3',
                  'Strelka_Tumor_0.3', 'Strelka_Normal_0.5', 'Strelka_Tumor_0.5',
                  'Strelka_Normal_0.7', 'Strelka_Tumor_0.7']
print(Second)

# Saving the results in csv.
Second.to_csv('Strelka_Read_Depth.csv', sep=',', index = None)

# Finding the minimum values
min1 = Second['Strelka_Normal_0.3'].min()
min2 = Second['Strelka_Tumor_0.3'].min()
min3 = Second['Strelka_Normal_0.5'].min()
min4 = Second['Strelka_Tumor_0.5'].min()
min5 = Second['Strelka_Normal_0.7'].min()
min6 = Second['Strelka_Tumor_0.7'].min()

# Finding the maximum values
max1 = Second['Strelka_Normal_0.3'].max()
max2 = Second['Strelka_Tumor_0.3'].max()
max3 = Second['Strelka_Normal_0.5'].max()
max4 = Second['Strelka_Tumor_0.5'].max()
max5 = Second['Strelka_Normal_0.7'].max()
max6 = Second['Strelka_Tumor_0.7'].max()

# Finding the mean values
mean1 = Second['Strelka_Normal_0.3'].mean()
mean2 = Second['Strelka_Tumor_0.3'].mean()

```

```

mean3 = Second['Strelka_Normal_0.5'].mean()
mean4 = Second['Strelka_Tumor_0.5'].mean()
mean5 = Second['Strelka_Normal_0.7'].mean()
mean6 = Second['Strelka_Tumor_0.7'].mean()

# Finding the minimum values
median1 = Second['Strelka_Normal_0.3'].median()
median2 = Second['Strelka_Tumor_0.3'].median()
median3 = Second['Strelka_Normal_0.5'].median()
median4 = Second['Strelka_Tumor_0.5'].median()
median5 = Second['Strelka_Normal_0.7'].median()
median6 = Second['Strelka_Tumor_0.7'].median()
print(median6)

# Finding the minimum values
mode1 = Second['Strelka_Normal_0.3'].mode()
mode2 = Second['Strelka_Tumor_0.3'].mode()
mode3 = Second['Strelka_Normal_0.5'].mode()
mode4 = Second['Strelka_Tumor_0.5'].mode()
mode5 = Second['Strelka_Normal_0.7'].mode()
mode6 = Second['Strelka_Tumor_0.7'].mode()
print(mode6)

# Declaring a new dataframe.
df = pd.DataFrame()

# Taking all combinations as a list.
Type = ['Strelka_Normal_0.3', 'Strelka_Tumor_0.3',
        'Strelka_Normal_0.5', 'Strelka_Tumor_0.5',
        'Strelka_Normal_0.7', 'Strelka_Tumor_0.7']
Minimum_Value = [min1, min2, min3, min4, min5, min6]
Maximum_Value = [max1, max2, max3, max4, max5, max6]
Mean_Value = [mean1, mean2, mean3, mean4, mean5, mean6]
Median_Value = [median1, median2, median3, median4, median5,
                median6]
Mode_Value = [mode1, mode2, mode3, mode4, mode5, mode6]

# Adding columns
df['Type'] = Type
df['Minimum_Value'] = Minimum_Value

```

```

df['Maximum_Value'] = Maximum_Value
df['Mean_Value'] = Mean_Value
df['Median_Value'] = Median_Value
df['Mode_Value'] = Mode_Value
# Collecting it into a dataframe.
print(df)

# Saving the results in csv.
df.to_csv('Strelka_Read_Depth_Statistics.csv', sep=',', index =
         False)

```

Truth Data Read Depth

```

# Importing the needed packages.
import numpy as np
import pandas as pd

# Reading the csv input file that is obtained after performing the
    following operations on the vcf file.
# Step 1 - 'cut -f 1-2,9-10 Input.vcf > Output.vcf'
# Step 2 - 'sed '/^#/d' Output.vcf > Updated.vcf'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_Somatic_Truth.vcf", sep = '\t',
                 index_col= False)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'FORMAT', 'VALUE']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
                 dff['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS', 'FORMAT'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]

```

```

dff = dff[cols]
print(dff)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
# columns by ':' and renaming the new columns based on the format
# "GT:PS:DP:GQ".
dff[['VALUE-GT', 'VALUE-PS', 'Read_Depth', 'VALUE-GQ']] =
    dff['VALUE'].str.split(':', expand=True)

# Dropping of the unnecessary columns and only choosing the
# "NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
# "TUMOR-DP"
dff = dff.drop(['VALUE', 'VALUE-GT', 'VALUE-PS', 'VALUE-GQ'],
    axis=1)
print(dff)

# Saving the result into a csv file for plotting.
dff.to_csv('Truth_Data_Read_Depth.csv', sep=',', index = None)

# Finding the minimum values
min1 = dff['Read_Depth'].min()

# Finding the maximum values
max1 = dff['Read_Depth'].max()

# Finding the mean values
mean1 = dff['Read_Depth'].mean()

# Finding the minimum values
median1 = dff['Read_Depth'].median()

# Finding the minimum values
mode1 = dff['Read_Depth'].mode()

# Declaring a new dataframe.
df = pd.DataFrame()

# Taking all combinations as a list.
Type = ['Truth_Data']
Minimum_Value = [min1]

```

```

Maximum_Value = [max1]
Mean_Value = [mean1]
Median_Value = [median1]
Mode_Value = [mode1]

# Adding columns
df['Type'] = Type
df['Minimum_Value'] = Minimum_Value
df['Maximum_Value'] = Maximum_Value
df['Mean_Value'] = Mean_Value
df['Median_Value'] = Median_Value
df['Mode_Value'] = Mode_Value
# Collecting it into a dataframe.
print(df)

# Saving the results in csv.
df.to_csv('Truth_Data_Read_Depth_Statistics.csv', sep=',', index =
         False)

```

VarScan Read Depth

```

# Importing the needed packages.
import numpy as np
import pandas as pd

# Reading the csv input file that is obtained after performing the
    following operations on the vcf file.
# Step 1 - 'cut -f 1-2,9-11 Input-VCF-File > Output-VCF-File'
# Step 2 - 'sed '/^#/d' Output-VCF-File > Updated_Output-VCF-File'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_VarScan_0.3.vcf", sep = '\t',
                  index_col= False)
dff1 = pd.read_csv("Updated_VarScan_0.5.vcf", sep = '\t',
                  index_col= False)
dff2 = pd.read_csv("Updated_VarScan_0.7.vcf", sep = '\t',
                  index_col= False)

```

```

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'FORMAT', 'NORMAL', 'TUMOR']
dff1.columns = ['CHROM', 'POS', 'FORMAT', 'NORMAL', 'TUMOR']
dff2.columns = ['CHROM', 'POS', 'FORMAT', 'NORMAL', 'TUMOR']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
    dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS', 'FORMAT'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

dff1 = dff1.drop(['CHROM', 'POS', 'FORMAT'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]
print(dff1)

dff2 = dff2.drop(['CHROM', 'POS', 'FORMAT'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

# Creating new columns by splitting the "NORMAL" and "TUMOR"
columns by ':' and renaming the new columns based on the format
"GT:GQ:DP:AD:ADF:ADR".
dff[['NORMAL-GT', 'NORMAL-GQ', 'Normal_Read_Depth',
    'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR']] =
    dff['NORMAL'].str.split(':', expand=True)

```



```

dff[['TUMOR-GT', 'TUMOR-GQ', 'Tumor_Read_Depth',
      'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR']] =
dff['TUMOR'].str.split(':', expand=True)

dff1[['NORMAL-GT', 'NORMAL-GQ', 'Normal_Read_Depth',
      'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR']] =
dff1['NORMAL'].str.split(':', expand=True)
dff1[['TUMOR-GT', 'TUMOR-GQ', 'Tumor_Read_Depth',
      'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR']] =
dff1['TUMOR'].str.split(':', expand=True)

dff2[['NORMAL-GT', 'NORMAL-GQ', 'Normal_Read_Depth',
      'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR']] =
dff2['NORMAL'].str.split(':', expand=True)
dff2[['TUMOR-GT', 'TUMOR-GQ', 'Tumor_Read_Depth',
      'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR']] =
dff2['TUMOR'].str.split(':', expand=True)

# Dropping of the unnecessary columns and only choosing the
# "NORMAL Depth" i.e. "NORMAL-DP" and "TUMOR Depth" i.e.
# "TUMOR-DP"
dff = dff.drop(['NORMAL', 'TUMOR', 'NORMAL-GT', 'NORMAL-GQ',
               'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR', 'TUMOR-GT',
               'TUMOR-GQ', 'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR'], axis=1)
print(dff)

dff1 = dff1.drop(['NORMAL', 'TUMOR', 'NORMAL-GT', 'NORMAL-GQ',
                 'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR', 'TUMOR-GT',
                 'TUMOR-GQ', 'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR'], axis=1)
print(dff1)

dff2 = dff2.drop(['NORMAL', 'TUMOR', 'NORMAL-GT', 'NORMAL-GQ',
                 'NORMAL-AD', 'NORMAL-ADF', 'NORMAL-ADR', 'TUMOR-GT',
                 'TUMOR-GQ', 'TUMOR-AD', 'TUMOR-ADF', 'TUMOR-ADR'], axis=1)
print(dff2)

# Merging columns based on "CHROM-POS"
First = pd.merge(dff, dff1, on=['CHROM_POS'])
Second = pd.merge(First, dff2, on=['CHROM_POS'])

```

```

# Renaming Columns
Second.columns = ['CHROM_POS', 'VarScan_Normal_0.3',
                  'VarScan_Tumor_0.3', 'VarScan_Normal_0.5', 'VarScan_Tumor_0.5',
                  'VarScan_Normal_0.7', 'VarScan_Tumor_0.7']
print(Second)

# Saving the results in csv.
Second.to_csv('VarScan_Read_Depth_Counts.csv', sep=',', index =
              None)

# Finding the minimum values
min1 = Second['VarScan_Normal_0.3'].min()
min2 = Second['VarScan_Tumor_0.3'].min()
min3 = Second['VarScan_Normal_0.5'].min()
min4 = Second['VarScan_Tumor_0.5'].min()
min5 = Second['VarScan_Normal_0.7'].min()
min6 = Second['VarScan_Tumor_0.7'].min()

# Finding the maximum values
max1 = Second['VarScan_Normal_0.3'].max()
max2 = Second['VarScan_Tumor_0.3'].max()
max3 = Second['VarScan_Normal_0.5'].max()
max4 = Second['VarScan_Tumor_0.5'].max()
max5 = Second['VarScan_Normal_0.7'].max()
max6 = Second['VarScan_Tumor_0.7'].max()

# Finding the mean values
mean1 = Second['VarScan_Normal_0.3'].mean()
mean2 = Second['VarScan_Tumor_0.3'].mean()
mean3 = Second['VarScan_Normal_0.5'].mean()
mean4 = Second['VarScan_Tumor_0.5'].mean()
mean5 = Second['VarScan_Normal_0.7'].mean()
mean6 = Second['VarScan_Tumor_0.7'].mean()

# Finding the minimum values
median1 = Second['VarScan_Normal_0.3'].median()
median2 = Second['VarScan_Tumor_0.3'].median()
median3 = Second['VarScan_Normal_0.5'].median()
median4 = Second['VarScan_Tumor_0.5'].median()
median5 = Second['VarScan_Normal_0.7'].median()

```

```

median6 = Second['VarScan_Tumor_0.7'].median()

# Finding the minimum values
mode1 = Second['VarScan_Normal_0.3'].mode()
mode2 = Second['VarScan_Tumor_0.3'].mode()
mode3 = Second['VarScan_Normal_0.5'].mode()
mode4 = Second['VarScan_Tumor_0.5'].mode()
mode5 = Second['VarScan_Normal_0.7'].mode()
mode6 = Second['VarScan_Tumor_0.7'].mode()

# Declaring a new dataframe.
df = pd.DataFrame()

# Taking all combinations as a list.
Type = ['VarScan_Normal_0.3', 'VarScan_Tumor_0.3',
        'VarScan_Normal_0.5', 'VarScan_Tumor_0.5',
        'VarScan_Normal_0.7', 'VarScan_Tumor_0.7']
Minimum_Value = [min1, min2, min3, min4, min5, min6]
Maximum_Value = [max1, max2, max3, max4, max5, max6]
Mean_Value = [mean1, mean2, mean3, mean4, mean5, mean6]
Median_Value = [median1, median2, median3, median4, median5,
                median6]
Mode_Value = [mode1, mode2, mode3, mode4, mode5, mode6]

# Adding columns
df['Type'] = Type
df['Minimum_Value'] = Minimum_Value
df['Maximum_Value'] = Maximum_Value
df['Mean_Value'] = Mean_Value
df['Median_Value'] = Median_Value
df['Mode_Value'] = Mode_Value
# Collecting it into a dataframe.
print(df)

# Saving the results in csv.
df.to_csv('VarScan_Read_Depth_Statistics.csv', sep=',', index =
          False)

```

Read Depth Comparison

```
# Importing packages.
import numpy as np
import pandas as pd

# Reading csv files and concatenating "CHROM" and "POS"
df = pd.read_csv("Strelka_Read_Depth_Counts.csv", sep = ',',
                 index_col= False)
df1 = pd.read_csv("VarScan_Read_Depth_Counts.csv", sep = ',',
                  index_col= False)
df2 = pd.read_csv("Truth_Data_Read_Depth_Counts.csv", sep = ',',
                  index_col= False)

# Merging columns based on "CHROM-POS"
First = pd.merge(df, df1, on=['CHROM_POS'])
Second = pd.merge(First, df2, on=['CHROM_POS'])

# Assigning column names.
Second.columns = ['CHROM_POS', 'Strelka_Normal_0.3_Read_Depth',
                  'Strelka_Tumor_0.3_Read_Depth',
                  'Strelka_Normal_0.5_Read_Depth',
                  'Strelka_Tumor_0.5_Read_Depth',
                  'Strelka_Normal_0.7_Read_Depth',
                  'Strelka_Tumor_0.7_Read_Depth',
                  'VarScan_Normal_0.3_Read_Depth',
                  'VarScan_Tumor_0.3_Read_Depth',
                  'VarScan_Normal_0.5_Read_Depth',
                  'VarScan_Tumor_0.5_Read_Depth',
                  'VarScan_Normal_0.7_Read_Depth',
                  'VarScan_Tumor_0.7_Read_Depth', 'Somatic_Truth_Read_Depth']

# Deleting the unneeded columns.
Second = Second.drop(['Strelka_Normal_0.5_Read_Depth',
                      'Strelka_Tumor_0.5_Read_Depth',
                      'Strelka_Normal_0.7_Read_Depth',
                      'Strelka_Tumor_0.7_Read_Depth',
                      'VarScan_Normal_0.5_Read_Depth',
                      'VarScan_Tumor_0.5_Read_Depth',
```

```

        'VarScan_Normal_0.7_Read_Depth',
        'VarScan_Tumor_0.7_Read_Depth'], axis=1)
print(Second)

# Saving the results in csv.
Second.to_csv('Tumor_Purity_0.3_Read_Depths.csv', sep=',',
              index=False)

Second.columns = ['CHROM_POS', 'Strelka_Normal', 'Strelka_Tumor',
                  'VarScan_Normal', 'VarScan_Tumor', 'Truth_Data']
print(Second)

# Finding the minimum values
min1 = Second['Strelka_Normal'].min()
min2 = Second['Strelka_Tumor'].min()
min3 = Second['VarScan_Normal'].min()
min4 = Second['VarScan_Tumor'].min()
min5 = Second['Truth_Data'].min()

# Finding the maximum values
max1 = Second['Strelka_Normal'].max()
max2 = Second['Strelka_Tumor'].max()
max3 = Second['VarScan_Normal'].max()
max4 = Second['VarScan_Tumor'].max()
max5 = Second['Truth_Data'].max()

# Finding the mean values
mean1 = Second['Strelka_Normal'].mean()
mean2 = Second['Strelka_Tumor'].mean()
mean3 = Second['VarScan_Normal'].mean()
mean4 = Second['VarScan_Tumor'].mean()
mean5 = Second['Truth_Data'].mean()

# Finding the minimum values
median1 = Second['Strelka_Normal'].median()
median2 = Second['Strelka_Tumor'].median()
median3 = Second['VarScan_Normal'].median()
median4 = Second['VarScan_Tumor'].median()
median5 = Second['Truth_Data'].median()

```

```

# Finding the minimum values
mode1 = Second['Strelka_Normal'].mode()
mode2 = Second['Strelka_Tumor'].mode()
mode3 = Second['VarScan_Normal'].mode()
mode4 = Second['VarScan_Tumor'].mode()
mode5 = Second['Truth_Data'].mode()

# Declaring a new dataframe.
df = pd.DataFrame()

# Taking all combinations as a list.
Type = ['Strelka_Normal_0.3', 'Strelka_Tumor_0.3',
        'VarScan_Normal_0.3', 'VarScan_Tumor_0.3', 'Truth_Data']
Minimum_Value = [min1, min2, min3, min4, min5]
Maximum_Value = [max1, max2, max3, max4, max5]
Mean_Value = [mean1, mean2, mean3, mean4, mean5]
Median_Value = [median1, median2, median3, median4, median5]
Mode_Value = [mode1, mode2, mode3, mode4, mode5]

# Adding columns
df['Type'] = Type
df['Minimum_Value'] = Minimum_Value
df['Maximum_Value'] = Maximum_Value
df['Mean_Value'] = Mean_Value
df['Median_Value'] = Median_Value
df['Mode_Value'] = Mode_Value
# Collecting it into a dataframe.
print(df)

# Saving the results in csv.
df.to_csv('Tumor_Purity_0.3_Read_Depth_Statistics.csv', sep=',',
          index = False)

```

Appendix F

Strelka Variants

```
# Importing the needed packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import pandas as pd
import csv
import numpy as np

# Reading the csv input file that is obtained after performing the
# following operations on the vcf file.
# Step 1 - 'cut -f 1-2,4-5 Input.vcf > Output.vcf'
# Step 2 - 'sed '/^#/d' Output.vcf > Updated.vcf'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_Strelka_0.3_SNV.vcf", sep = '\t',
    index_col= False)
dff1 = pd.read_csv("Updated_Strelka_0.5_SNV.vcf", sep = '\t',
    index_col= False)
dff2 = pd.read_csv("Updated_Strelka_0.7_SNV.vcf", sep = '\t',
    index_col= False)

# Naming the columns after importing the csv file.
```

```

dff.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff1.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff2.columns = ['CHROM', 'POS', 'REF', 'ALT']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
    dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]
print(dff1)

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

# Mentioning the column names and inputing the csv file.
dff.columns = ['CHROM_POS', 'REF', 'ALT']
dff1.columns = ['CHROM_POS', 'REF', 'ALT']
dff2.columns = ['CHROM_POS', 'REF', 'ALT']

# Printing the list.
dff4 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'A')]
dff5 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'A')]
dff6 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'A')]

```



```

AA1 = len(dff4.index)
AA2 = len(dff5.index)
AA3 = len(dff6.index)

dff7 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'T')]
dff8 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'T')]
dff9 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'T')]
AT1 = len(dff7.index)
AT2 = len(dff8.index)
AT3 = len(dff9.index)

dff10 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'G')]
dff11 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'G')]
dff12 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'G')]
AG1 = len(dff10.index)
AG2 = len(dff11.index)
AG3 = len(dff12.index)

dff13 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'C')]
dff14 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'C')]
dff15 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'C')]
AC1 = len(dff13.index)
AC2 = len(dff14.index)
AC3 = len(dff15.index)

dff16 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'T')]
dff17 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'T')]
dff18 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'T')]
TT1 = len(dff16.index)
TT2 = len(dff17.index)
TT3 = len(dff18.index)

dff19 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'A')]
dff20 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'A')]
dff21 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'A')]
TA1 = len(dff19.index)
TA2 = len(dff20.index)
TA3 = len(dff21.index)

dff22 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'G')]

```

```

dff23 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'G')]
dff24 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'G')]
TG1 = len(dff22.index)
TG2 = len(dff23.index)
TG3 = len(dff24.index)

dff25 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'C')]
dff26 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'C')]
dff27 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'C')]
TC1 = len(dff25.index)
TC2 = len(dff26.index)
TC3 = len(dff27.index)

dff28 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'G')]
dff29 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'G')]
dff30 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'G')]
GG1 = len(dff28.index)
GG2 = len(dff29.index)
GG3 = len(dff30.index)

dff31 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'A')]
dff32 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'A')]
dff33 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'A')]
GA1 = len(dff31.index)
GA2 = len(dff32.index)
GA3 = len(dff33.index)

dff34 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'T')]
dff35 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'T')]
dff36 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'T')]
GT1 = len(dff34.index)
GT2 = len(dff35.index)
GT3 = len(dff36.index)

dff37 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'C')]
dff38 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'C')]
dff39 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'C')]
GC1 = len(dff37.index)
GC2 = len(dff38.index)
GC3 = len(dff39.index)

```

```

dff40 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'C')]
dff41 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'C')]
dff42 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'C')]
CC1 = len(dff40.index)
CC2 = len(dff41.index)
CC3 = len(dff42.index)

dff43 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'A')]
dff44 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'A')]
dff45 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'A')]
CA1 = len(dff43.index)
CA2 = len(dff44.index)
CA3 = len(dff45.index)

dff46 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'T')]
dff47 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'T')]
dff48 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'T')]
CT1 = len(dff46.index)
CT2 = len(dff47.index)
CT3 = len(dff48.index)

dff49 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'G')]
dff50 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'G')]
dff51 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'G')]
CG1 = len(dff49.index)
CG2 = len(dff50.index)
CG3 = len(dff51.index)

# Declaring a new dataframe.
df = []
df1 = []
df2 = []

# Taking all combinations as a list.
data = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
               'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
               'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'Strelka_0.3': [AA1, AT1, AG1, AC1, TT1, TA1, TG1, TC1, GG1,
                          GA1, GT1, GC1, CC1, CA1, CT1, CG1]}

```

```

data1 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
          'Strelka_0.5': [AA2, AT2, AG2, AC2, TT2, TA2, TG2, TC2, GG2,
                          GA2, GT2, GC2, CC2, CA2, CT2, CG2]}
data2 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
          'Strelka_0.7': [AA3, AT3, AG3, AC3, TT3, TA3, TG3, TC3, GG3,
                          GA3, GT3, GC3, CC3, CA3, CT3, CG3]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
df1 = pd.DataFrame(data1)
df2 = pd.DataFrame(data2)

# Merging columns based on "CHROM-POS"
First = pd.merge(df, df1, on=['ALT', 'REF'])
Second = pd.merge(First, df2, on=['ALT', 'REF'])

# Mentioning the column names and inputing the csv file.
Second.columns = ['REF', 'ALT', 'Strelka_0.3', 'Strelka_0.5',
                  'Strelka_0.7']
print(Second)

# Saving the results in csv.
Second.to_csv('Strelka_Counts.csv', sep=',', index = None)

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("Strelka_Counts.csv", sep = ',', index_col=
                  False, error_bad_lines=False)
dff.columns = ['REF', 'ALT', 'Strelka_One', 'Strelka_Two',
               'Strelka_Three']

# set width of bar
width = 0.25

# Columns from the file
a1 = dff.Strelka_One.to_list()
a2 = dff.Strelka_Two.to_list()

```

```

a3 = dff.Strelka_Three.to_list()

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]

# Make the plot
plt.bar(r1, a1, color='#FFD700', width=width, edgecolor='white',
        label='Strelka_0.3')
plt.bar(r2, a2, color='#FFA500', width=width, edgecolor='white',
        label='Strelka_0.5')
plt.bar(r3, a3, color='#DC143C', width=width, edgecolor='white',
        label='Strelka_0.7')

# Add xticks on the middle of the group bars
plt.xlabel('Combinations')
plt.xticks([r + width for r in range(len(a1))], ['AA', 'AT', 'AG',
        'AC', 'TT', 'TA', 'TG', 'TC', 'GG', 'GA', 'GT', 'GC', 'CC',
        'CA', 'CT', 'CG'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('Strelka_Counts_Plot.pdf')
plt.savefig('Strelka_Counts_Plot.png', dpi = 300)

```

Truth Data Variants

```

# Importing the needed packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import pandas as pd

```

```

import csv
import numpy as np

# Importing the csv file.
dff = pd.read_csv("Updated_Somatic_Truth_SNP.vcf", sep = '\t',
                  index_col= False)

# Mentioning the column names and inputing the csv file.
dff.columns = ['CHROM', 'POS', 'REF', 'ALT']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
                  dff['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

# Mentioning the column names and inputing the csv file.
dff.columns = ['CHROM_POS', 'REF', 'ALT']

# Printing the list.
dff1 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'A')]
AA = len(dff1.index)
print('The number of REF as A and ALT as A is')
print(AA)

dff2 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'T')]
AT = len(dff2.index)
print('The number of REF as A and ALT as T is')
print(AT)

dff3 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'G')]
AG = len(dff3.index)
print('The number of REF as A and ALT as G is')
print(AG)

```

```

dff4 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'C')]
AC = len(dff4.index)
print('The number of REF as A and ALT as C is')
print(AC)

dff5 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'T')]
TT = len(dff5.index)
print('The number of REF as T and ALT as T is')
print(TT)

dff6 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'A')]
TA = len(dff6.index)
print('The number of REF as T and ALT as A is')
print(TA)

dff7 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'G')]
TG = len(dff7.index)
print('The number of REF as T and ALT as G is')
print(TG)

dff8 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'C')]
TC = len(dff8.index)
print('The number of REF as T and ALT as C is')
print(TC)

dff9 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'G')]
GG = len(dff9.index)
print('The number of REF as G and ALT as G is')
print(GG)

dff10 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'A')]
GA = len(dff10.index)
print('The number of REF as G and ALT as A is')
print(GA)

dff11 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'T')]
GT = len(dff11.index)
print('The number of REF as G and ALT as T is')
print(GT)

```

```

dff12 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'C')]
GC = len(dff12.index)
print('The number of REF as G and ALT as C is')
print(GC)

dff13 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'C')]
CC = len(dff13.index)
print('The number of REF as C and ALT as C is')
print(CC)

dff14 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'A')]
CA = len(dff14.index)
print('The number of REF as C and ALT as A is')
print(CA)

dff15 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'T')]
CT = len(dff15.index)
print('The number of REF as C and ALT as T is')
print(CT)

dff16 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'G')]
CG = len(dff16.index)
print('The number of REF as C and ALT as G is')
print(CG)

# Delcaring a new dataframe.
df = []

# Taking all combinations as a list.
data = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
               'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
               'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'Truth_Data': [AA, AT, AG, AC, TT, TA, TG, TC, GG, GA, GT, GC,
                        CC, CA, CT, CG]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
print(df)

# Exporting the outcome into CSV.

```



```

df.to_csv('Truth_Data_Counts.csv', sep=',', index = None)

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("Truth_Data_Counts.csv", sep = ',', index_col=
    False, error_bad_lines=False)
dff.columns = ['REF', 'ALT', 'Truth_Data']

# set width of bar
width = 0.35

# Columns from the file
a1 = dff.Truth_Data.to_list()

# Set position of bar on X axis
r1 = np.arange(len(a1))

# Make the plot
plt.bar(r1, a1, color='#FFD700', width=width, edgecolor='white',
    label='Truth_Data')

# Add xticks on the middle of the group bars
plt.xlabel('Combinations')
plt.xticks([r + width for r in range(len(a1))], ['AA', 'AT', 'AG',
    'AC', 'TT', 'TA', 'TG', 'TC', 'GG', 'GA', 'GT', 'GC', 'CC',
    'CA', 'CT', 'CG'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('Truth_Data_Counts_Plot.pdf')
plt.savefig('Truth_Data_Counts_Plot.png', dpi = 300)

```

VarScan Variants

```

# Importing the needed packages.
import numpy as np
import pandas as pd
import matplotlib

```

```

from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import pandas as pd
import csv
import numpy as np

# Reading the csv input file that is obtained after performing the
    following operations on the vcf file.
# Step 1 - 'cut -f 1-2,4-5 Input.vcf > Output.vcf'
# Step 2 - 'sed '/^#/d' Output.vcf > Updated.vcf'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_VarScan_0.3_SNP.vcf", sep = '\t',
    index_col= False)
dff1 = pd.read_csv("Updated_VarScan_0.5_SNP.vcf", sep = '\t',
    index_col= False)
dff2 = pd.read_csv("Updated_VarScan_0.7_SNP.vcf", sep = '\t',
    index_col= False)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff1.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff2.columns = ['CHROM', 'POS', 'REF', 'ALT']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
    dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]

```

```

print(dff)

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]
print(dff1)

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

# Mentioning the column names and inputing the csv file.
dff.columns = ['CHROM_POS', 'REF', 'ALT']
dff1.columns = ['CHROM_POS', 'REF', 'ALT']
dff2.columns = ['CHROM_POS', 'REF', 'ALT']

# Printing the list.
dff4 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'A')]
dff5 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'A')]
dff6 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'A')]
AA1 = len(dff4.index)
AA2 = len(dff5.index)
AA3 = len(dff6.index)

dff7 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'T')]
dff8 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'T')]
dff9 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'T')]
AT1 = len(dff7.index)
AT2 = len(dff8.index)
AT3 = len(dff9.index)

dff10 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'G')]
dff11 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'G')]
dff12 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'G')]
AG1 = len(dff10.index)
AG2 = len(dff11.index)
AG3 = len(dff12.index)

```

```

dff13 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'C')]
dff14 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'C')]
dff15 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'C')]
AC1 = len(dff13.index)
AC2 = len(dff14.index)
AC3 = len(dff15.index)

dff16 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'T')]
dff17 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'T')]
dff18 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'T')]
TT1 = len(dff16.index)
TT2 = len(dff17.index)
TT3 = len(dff18.index)

dff19 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'A')]
dff20 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'A')]
dff21 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'A')]
TA1 = len(dff19.index)
TA2 = len(dff20.index)
TA3 = len(dff21.index)

dff22 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'G')]
dff23 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'G')]
dff24 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'G')]
TG1 = len(dff22.index)
TG2 = len(dff23.index)
TG3 = len(dff24.index)

dff25 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'C')]
dff26 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'C')]
dff27 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'C')]
TC1 = len(dff25.index)
TC2 = len(dff26.index)
TC3 = len(dff27.index)

dff28 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'G')]
dff29 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'G')]
dff30 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'G')]
GG1 = len(dff28.index)

```

```

GG2 = len(dff29.index)
GG3 = len(dff30.index)

dff31 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'A')]
dff32 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'A')]
dff33 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'A')]
GA1 = len(dff31.index)
GA2 = len(dff32.index)
GA3 = len(dff33.index)

dff34 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'T')]
dff35 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'T')]
dff36 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'T')]
GT1 = len(dff34.index)
GT2 = len(dff35.index)
GT3 = len(dff36.index)

dff37 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'C')]
dff38 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'C')]
dff39 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'C')]
GC1 = len(dff37.index)
GC2 = len(dff38.index)
GC3 = len(dff39.index)

dff40 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'C')]
dff41 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'C')]
dff42 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'C')]
CC1 = len(dff40.index)
CC2 = len(dff41.index)
CC3 = len(dff42.index)

dff43 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'A')]
dff44 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'A')]
dff45 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'A')]
CA1 = len(dff43.index)
CA2 = len(dff44.index)
CA3 = len(dff45.index)

dff46 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'T')]
dff47 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'T')]

```

```

dff48 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'T')]
CT1 = len(dff46.index)
CT2 = len(dff47.index)
CT3 = len(dff48.index)

dff49 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'G')]
dff50 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'G')]
dff51 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'G')]
CG1 = len(dff49.index)
CG2 = len(dff50.index)
CG3 = len(dff51.index)

# Declaring a new dataframe.
df = []
df1 = []
df2 = []

# Taking all combinations as a list.
data = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
               'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
               'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'VarScan_0.3': [AA1, AT1, AG1, AC1, TT1, TA1, TG1, TC1, GG1,
                        GA1, GT1, GC1, CC1, CA1, CT1, CG1]}
data1 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'VarScan_0.5': [AA2, AT2, AG2, AC2, TT2, TA2, TG2, TC2, GG2,
                        GA2, GT2, GC2, CC2, CA2, CT2, CG2]}
data2 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'VarScan_0.7': [AA3, AT3, AG3, AC3, TT3, TA3, TG3, TC3, GG3,
                        GA3, GT3, GC3, CC3, CA3, CT3, CG3]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
df1 = pd.DataFrame(data1)
df2 = pd.DataFrame(data2)

# Merging columns based on "CHROM-POS"

```

```

First = pd.merge(df, df1, on=['ALT', 'REF'])
Second = pd.merge(First, df2, on=['ALT', 'REF'])

# Mentioning the column names and inputing the csv file.
Second.columns = ['REF', 'ALT', 'VarScan_0.3', 'VarScan_0.5',
                  'VarScan_0.7']
print(Second)

# Saving the results in csv.
Second.to_csv('VarScan_Counts.csv', sep=',', index = None)

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("VarScan_Counts.csv", sep = ',', index_col=
                  False, error_bad_lines=False)
dff.columns = ['REF', 'ALT', 'VarScan_One', 'VarScan_Two',
               'VarScan_Three']

# set width of bar
width = 0.25

# Columns from the file
a1 = dff.VarScan_One.to_list()
a2 = dff.VarScan_Two.to_list()
a3 = dff.VarScan_Three.to_list()

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]

# Make the plot
plt.bar(r1, a1, color='#FFD700', width=width, edgecolor='white',
        label='VarScan_0.3')
plt.bar(r2, a2, color='#FFA500', width=width, edgecolor='white',
        label='VarScan_0.5')
plt.bar(r3, a3, color='#DC143C', width=width, edgecolor='white',
        label='VarScan_0.7')

# Add xticks on the middle of the group bars
plt.xlabel('Combinations')

```

```

plt.xticks([r + width for r in range(len(a1))], ['AA', 'AT', 'AG',
    'AC', 'TT', 'TA', 'TG', 'TC', 'GG', 'GA', 'GT', 'GC', 'CC',
    'CA', 'CT', 'CG'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('VarScan_Counts_Plot.pdf')
plt.savefig('VarScan_Counts_Plot.png', dpi = 300)

```

Variants Comparison

```

# Importing the needed packages.
import numpy as np
import pandas as pd
import matplotlib
from matplotlib import rc
matplotlib.rcParams['mathtext.fontset'] = 'cm'
matplotlib.rcParams['font.family'] = 'serif'
import matplotlib.pyplot as plt
import pandas as pd
import csv
import numpy as np

# Reading the csv input file that is obtained after performing the
    following operations on the vcf file.
# Step 1 - 'cut -f 1-2,4-5 Input.vcf > Output.vcf'
# Step 2 - 'sed '/^#/d' Output.vcf > Updated.vcf'

# The first step is to selected the needed columns in the vcf file.
# The second step if to eliminate all lines that start with a '#'
dff = pd.read_csv("Updated_Strelka_0.3_SNV.vcf", sep = '\t',
    index_col= False)
dff1 = pd.read_csv("Updated_VarScan_0.3_SNP.vcf", sep = '\t',
    index_col= False)
dff2 = pd.read_csv("Updated_Somatic_Truth_SNP.vcf", sep = '\t',
    index_col= False)

```



```

# SNP Counts
SSC = len(dff)
VSC = len(dff1)
TSC = len(dff2)

# Naming the columns after importing the csv file.
dff.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff1.columns = ['CHROM', 'POS', 'REF', 'ALT']
dff2.columns = ['CHROM', 'POS', 'REF', 'ALT']

# Concatinating the "CHROM" and "POS"
dff["CHROM_POS"] = dff['CHROM'].astype(str) + '-' +
    dff['POS'].astype(str)
dff1["CHROM_POS"] = dff1['CHROM'].astype(str) + '-' +
    dff1['POS'].astype(str)
dff2["CHROM_POS"] = dff2['CHROM'].astype(str) + '-' +
    dff2['POS'].astype(str)

# Dropping of the unnecessary columns and reorganising the columns.
dff = dff.drop(['CHROM', 'POS'], axis=1)
cols = dff.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff = dff[cols]
print(dff)

dff1 = dff1.drop(['CHROM', 'POS'], axis=1)
cols = dff1.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff1 = dff1[cols]
print(dff1)

dff2 = dff2.drop(['CHROM', 'POS'], axis=1)
cols = dff2.columns.tolist()
cols = cols[-1:] + cols[:-1]
dff2 = dff2[cols]
print(dff2)

# Mentioning the column names and inputing the csv file.
dff.columns = ['CHROM_POS', 'REF', 'ALT']
dff1.columns = ['CHROM_POS', 'REF', 'ALT']

```

```

dff2.columns = ['CHROM_POS', 'REF', 'ALT']

# Printing the list.
dff4 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'A')]
dff5 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'A')]
dff6 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'A')]
AA1 = len(dff4.index)
AA2 = len(dff5.index)
AA3 = len(dff6.index)

dff7 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'T')]
dff8 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'T')]
dff9 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'T')]
AT1 = (len(dff7.index)/SSC) * 100
AT2 = (len(dff8.index)/VSC) * 100
AT3 = (len(dff9.index)/TSC) * 100

dff10 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'G')]
dff11 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'G')]
dff12 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'G')]
AG1 = (len(dff10.index)/SSC) * 100
AG2 = (len(dff11.index)/VSC) * 100
AG3 = (len(dff12.index)/TSC) * 100

dff13 = dff[(dff['REF'] == 'A') & (dff['ALT'] == 'C')]
dff14 = dff1[(dff1['REF'] == 'A') & (dff1['ALT'] == 'C')]
dff15 = dff2[(dff2['REF'] == 'A') & (dff2['ALT'] == 'C')]
AC1 = (len(dff13.index)/SSC) * 100
AC2 = (len(dff14.index)/VSC) * 100
AC3 = (len(dff15.index)/TSC) * 100

dff16 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'T')]
dff17 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'T')]
dff18 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'T')]
TT1 = len(dff16.index)
TT2 = len(dff17.index)
TT3 = len(dff18.index)

dff19 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'A')]
dff20 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'A')]

```

```

dff21 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'A')]
TA1 = (len(dff19.index)/SSC) * 100
TA2 = (len(dff20.index)/VSC) * 100
TA3 = (len(dff21.index)/TSC) * 100

dff22 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'G')]
dff23 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'G')]
dff24 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'G')]
TG1 = (len(dff22.index)/SSC) * 100
TG2 = (len(dff23.index)/VSC) * 100
TG3 = (len(dff24.index)/TSC) * 100

dff25 = dff[(dff['REF'] == 'T') & (dff['ALT'] == 'C')]
dff26 = dff1[(dff1['REF'] == 'T') & (dff1['ALT'] == 'C')]
dff27 = dff2[(dff2['REF'] == 'T') & (dff2['ALT'] == 'C')]
TC1 = (len(dff25.index)/SSC) * 100
TC2 = (len(dff26.index)/VSC) * 100
TC3 = (len(dff27.index)/TSC) * 100

dff28 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'G')]
dff29 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'G')]
dff30 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'G')]
GG1 = len(dff28.index)
GG2 = len(dff29.index)
GG3 = len(dff30.index)

dff31 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'A')]
dff32 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'A')]
dff33 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'A')]
GA1 = (len(dff31.index)/SSC) * 100
GA2 = (len(dff32.index)/VSC) * 100
GA3 = (len(dff33.index)/TSC) * 100

dff34 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'T')]
dff35 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'T')]
dff36 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'T')]
GT1 = (len(dff34.index)/SSC) * 100
GT2 = (len(dff35.index)/VSC) * 100
GT3 = (len(dff36.index)/TSC) * 100

```

```

dff37 = dff[(dff['REF'] == 'G') & (dff['ALT'] == 'C')]
dff38 = dff1[(dff1['REF'] == 'G') & (dff1['ALT'] == 'C')]
dff39 = dff2[(dff2['REF'] == 'G') & (dff2['ALT'] == 'C')]
GC1 = (len(dff37.index)/SSC) * 100
GC2 = (len(dff38.index)/VSC) * 100
GC3 = (len(dff39.index)/TSC) * 100

dff40 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'C')]
dff41 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'C')]
dff42 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'C')]
CC1 = len(dff40.index)
CC2 = len(dff41.index)
CC3 = len(dff42.index)

dff43 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'A')]
dff44 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'A')]
dff45 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'A')]
CA1 = (len(dff43.index)/SSC) * 100
CA2 = (len(dff44.index)/VSC) * 100
CA3 = (len(dff45.index)/TSC) * 100

dff46 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'T')]
dff47 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'T')]
dff48 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'T')]
CT1 = (len(dff46.index)/SSC) * 100
CT2 = (len(dff47.index)/VSC) * 100
CT3 = (len(dff48.index)/TSC) * 100

dff49 = dff[(dff['REF'] == 'C') & (dff['ALT'] == 'G')]
dff50 = dff1[(dff1['REF'] == 'C') & (dff1['ALT'] == 'G')]
dff51 = dff2[(dff2['REF'] == 'C') & (dff2['ALT'] == 'G')]
CG1 = (len(dff49.index)/SSC) * 100
CG2 = (len(dff50.index)/VSC) * 100
CG3 = (len(dff51.index)/TSC) * 100

# Declaring a new dataframe.
df = []
df1 = []
df2 = []

```

```

# Taking all combinations as a list.
data = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
               'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
               'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'Strelka_0.3': [AA1, AT1, AG1, AC1, TT1, TA1, TG1, TC1, GG1,
                        GA1, GT1, GC1, CC1, CA1, CT1, CG1]}
data1 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'VarScan_0.3': [AA2, AT2, AG2, AC2, TT2, TA2, TG2, TC2, GG2,
                        GA2, GT2, GC2, CC2, CA2, CT2, CG2]}
data2 = {'REF': ['A', 'A', 'A', 'A', 'T', 'T', 'T', 'T', 'G', 'G',
                'G', 'G', 'C', 'C', 'C', 'C'], 'ALT': ['A', 'T', 'G', 'C', 'T',
                'A', 'G', 'C', 'G', 'A', 'T', 'C', 'C', 'A', 'T', 'G'],
        'Truth_Data': [AA3, AT3, AG3, AC3, TT3, TA3, TG3, TC3, GG3,
                        GA3, GT3, GC3, CC3, CA3, CT3, CG3]}

# Collecting it into a dataframe.
df = pd.DataFrame(data)
df1 = pd.DataFrame(data1)
df2 = pd.DataFrame(data2)

# Merging columns based on "CHROM-POS"
First = pd.merge(df, df1, on=['ALT', 'REF'])
Second = pd.merge(First, df2, on=['ALT', 'REF'])

# Mentioning the column names and inputting the csv file.
Second.columns = ['REF', 'ALT', 'Strelka_0.3', 'VarScan_0.3',
                  'Truth_Data']
print(Second)

# Saving the results in csv.
Second.to_csv('Tumor_Purity_0.3_Counts.csv', sep=',', index = None)

# Reading csv files and concatenating "CHROM" and "POS"
dff = pd.read_csv("Tumor_Purity_0.3_Counts.csv", sep = ',',
                  index_col= False, error_bad_lines=False)
dff.columns = ['REF', 'ALT', 'Strelka', 'VarScan', 'Truth']

# set width of bar

```

```

width = 0.25

# Columns from the file
a1 = dff.Strelka.to_list()
a2 = dff.VarScan.to_list()
a3 = dff.Truth.to_list()

# Set position of bar on X axis
r1 = np.arange(len(a1))
r2 = [x + width for x in r1]
r3 = [x + width for x in r2]

# Make the plot
plt.bar(r1, a1, color='#FFD700', width=width, edgecolor='white',
        label='Strelka_0.3')
plt.bar(r2, a2, color='#FFA500', width=width, edgecolor='white',
        label='VarScan_0.3')
plt.bar(r3, a3, color='#DC143C', width=width, edgecolor='white',
        label='Truth_Data')

# Add xticks on the middle of the group bars
plt.xlabel('SNP Combinations')
plt.xticks([r + width for r in range(len(a1))], ['AA', 'AT', 'AG',
        'AC', 'TT', 'TA', 'TG', 'TC', 'GG', 'GA', 'GT', 'GC', 'CC',
        'CA', 'CT', 'CG'])

# Create legend & Show graphic
plt.legend()
plt.show()
plt.savefig('Tumor_Purity_0.3_Plot.pdf')
plt.savefig('Tumor_Purity_0.3_Plot.png', dpi = 300)

```
