

LESLIE'S

WATER ANALYSIS

Powered By **AccuBlue**

CURRENT TIER:



PERKS ELITE

CUSTOMER:
George Watts



S05700018706976 George Watts

POOL DETAILS:

Pool & Spa
10500 Gal

Chlorine
Pebble

Store #238 • 4615 E RAY RD STE E-1 • (480)961-4465

WEEKLY MAINTENANCE ROUTINE

1 Sanitize

Maintain 1-4 ppm of Free Chlorine using Leslie's Tabs.

2 Shock

Add 12 oz of any Leslie's Shock weekly.

3 Prevent

Add 6 Fl oz of Leslie's Perfect Weekly every week.

Pro Tip: For problem pools with heavy use, swimming animals, or significant debris, add 4 Fl oz of Leslie's Algae Control weekly.

PROBLEMS REPORTED: N/A

WATER TEST QUALITY SCORE



DOWNLOAD OUR APP NOW!
TO TRACK WATER TESTS AND PERK REWARDS
LEARN MORE AT LESLIESPOOL.COM/APP

This treatment plan applies exclusively to Leslie's chemicals and is based on the residential pool details provided above.
Always operate the pump on high speed when adding chemicals to your pool or spa.

TEST	IDEAL RANGE	RESULT
Free Chlorine	1 - 4 ppm	2.65
Total Chlorine	Within 0.2 of FAC	2.65
pH	7.2 - 7.8	7.4
Total Alkalinity	80 - 120 ppm	4*
Calcium Hardness	200 - 400 ppm	660
Cyanuric Acid	30 - 100 ppm	209
Iron	0 - 0.2 ppm	0
Copper	0 - 0.2 ppm	0
Phosphates	0 - 100 ppb	55
TDS	0 - 2500 ppm	5000

* Total Alkalinity has been adjusted due to the effect of CyA on tested Total Alkalinity

TEST COMPLETED 08/08/26 04:42 PM BY Michael R. (Store Spin)

YOUR NEXT RECOMMENDED TEST DATE 08/15/26



For more expert pool care tips, speak with one of our helpful store associates or check out the links below!

lesliespool.com/blog
youtube.com/@LesliesPoolCare

A CLEAN POOL STARTS WITH A CLEAN FILTER!



Check out this article to learn more about how to clean your filter.

The information contained in this water test analysis is provided solely as a courtesy by Leslie's to its customers and is intended to exclusively apply to residential (i.e., Private) pools and specifically does not apply to commercial (i.e., Public class A-F pools), as defined by the American National Standards Institute ("ANSI"). Leslie's makes every effort to provide accurate recommendations based upon current ANSI/APSP ICC-11 standards 2019, but codes and regulations change, and Leslie's assumes no liability for any omissions or errors in this analysis or the outcome of any project. Customers must always exercise reasonable caution, carefully read the label on all products, follow all product directions, follow all current codes and regulations that may apply, and consult with a licensed professional if in doubt about any procedures. Leslie's assumes no legal responsibility for customer's reliance or interpretation of the data contained herein and makes no representations or warranties of any kind concerning the quality, safety, or suitability of the information, whether express or implied, including, without limitation, any implied warranties of merchantability or fitness of particular purpose.

CUSTOMIZED TREATMENT PLAN

Product	Problem / Solution
	Step #1 Very High Calcium Hardness - A high Calcium Hardness level can cause scale formation, cloudy water, clogged filters & heaters and swimmer discomfort. Solutions: We recommend partially or completely draining your pool and refilling with fresh water. If you decide to do this, please ensure that you read the following cautions and contact your builder with any questions. ⚠ 1. Do not fully drain a vinyl-liner or fiberglass pool as irreversible damage will occur. Drain a maximum of one foot and add one foot of fresh water. Repeat until the desired Calcium Hardness level is achieved. 2. Draining during summer months is not recommended when air temperature exceeds 80 °F. (Pebble-surfaced pools are exempt.) 3. Do not drain if water table is high as your pool can float on the water underneath. 4. If you choose to drain, promptly refill and disregard the remaining prescription recommendations unless you have algae, which must be treated first. 💡 Pro Tip: After refilling with fresh water, circulate the water throughout the system. Promptly return to the store so we can assist you with balancing your water.
	Step #2 High TDS - A high TDS level can cause poor chlorine effectiveness, cause the water to look old and dull, and can promote algae growth. Solutions: We recommend partially or completely draining your pool and refilling with fresh water. If you decide to do this, please ensure that you read the following cautions and contact your builder with any questions. ⚠ 1. Do not fully drain a vinyl-liner or fiberglass pool as irreversible damage will occur. Drain a maximum of one foot and add one foot of fresh water. Repeat until the desired TDS level is achieved. 2. Draining during summer months is not recommended when air temperature exceeds 80 °F. (Pebble-surfaced pools are exempt.) 3. Do not drain if water table is high as your pool can float on the water underneath. 4. If you choose to drain, promptly refill and disregard the remaining prescription recommendations unless you have algae, which must be treated first. 💡 Pro Tip: After refilling with fresh water, circulate the water throughout the system. Promptly return to the store so we can assist you with balancing your water.
 Leslie's Clearaway CYA	Step #3 Very High CyA - A high Cyanuric Acid (CyA) level impacts the effectiveness of sanitizers. Solutions: 1. We recommend adding a Leslie's ClearAway CYA Cyanuric Acid Remover to your skimmer. Follow the product label directions. 2. For more severe cases where a Cyanuric Acid remover does not help, you will need to dilute your pool water by draining and refilling one foot of water at a time, testing the Cyanuric Acid level with every refill. Repeat this process as needed until the Cyanuric Acid level is within range. Exercise extreme caution when draining your pool partially or fully. Doing so incorrectly can cause significant damage to the structure. If you would like more information about how to drain your pool safely, you can read our Resource Center article, Pool Draining 101. When in doubt contact your pool builder with any questions. ⚠ 1. Do not fully drain a vinyl-liner or fiberglass pool as irreversible damage will occur. Drain a maximum of one foot and add one foot of fresh water. Repeat until the desired Cyanuric Acid level is achieved. 2. Draining during summer months is not recommended when air temperature exceeds 80 °F. (Pebble-surfaced pools are exempt.) 3. Do not drain if water table is high as your pool can float on the water underneath. 4. If you choose to drain, promptly refill and disregard the remaining prescription recommendations unless you have algae, which must be treated first. 💡 Pro Tip: Cyanuric Acid Remover: Ensure the pouch is fully submerged and there is adequate water flow. Draining Option: After refilling with fresh water, circulate the water throughout the system. Promptly return to the store so we can assist you with balancing your water.
 Leslie's Alkalinity Up	Step #4 Low Total Alkalinity - Low Total Alkalinity causes pH issues, corrosion of metal parts, surface damage and swimmer discomfort. Solutions: 1. Your pool needs a Total Amount of 14 lbs 2 oz of Leslie's Alkalinity Up. The <u>Maximum Dose</u> you should add at any one time is 10 lbs 8 oz. 2. Broadcast the Alkalinity Up into your pool water with the pump running. 3. Wait 4 hours and add additional product (never exceeding the Maximum Dose) until the Total Amount has been added. (We recommend retesting after half of the Total Amount has been added.) Additional adjustments may be needed when complete. 4. After the last dose has been added, wait 4 hours, then proceed to next step. ⚠ Do not add Leslie's Alkalinity Up the same day as Leslie's Hardness Plus. 💡 Pro Tip: Adjusting the Total Alkalinity affects the pH. Retest both as additional balancing may be required.