

Terra Firma Partners — Project Instructions

V4 Rebuild Progress

- **Steps 1-11:** Complete and deployed
- **Step 8 (Stand Icon Polish):**  Complete — checkpointed as “V4 Step 8 stand icon polish”
- **Step 9 (Stand Explainability):**  Complete — checkpointed as “V4 Step 9 stand explainability”
- **Step 11b (Map Choreography):**  Complete — checkpointed as “V4 Step 11b map choreography polish”
- **Step 12 (Debug Cleanup):**  Complete — checkpointed as “TFP V4 Step 12 debug cleanup”

Step 9 Decisions & Changes

`lib/scoring/stand-explainability.ts` — Enhanced engine:

1. New `KeyIndicator` type with 3 prominent signals: Intercept (Strong/Moderate/Weak), Pressure (Low/Moderate/High), Resilience (High/Moderate/Low)
2. New `getCorridorChip` — “Primary Corridor” / “Near Corridor” / “Corridor Access” / “Off Corridor” based on `distToCorridorMeters`
3. Wind chip renamed: “Clean Wind” → “Leeward Advantage” for strong wind positioning
4. Interior chip renamed: “Deep Interior” → “Interior Access” for clarity
5. `buildRankRationale` rewritten — natural conversational sentences (“Strong intercept quality and low pressure, sits on a primary corridor with strong resilience.”)
6. New `buildSelectionExplanation` — full paragraph answering “Why does this stand rank where it does?” with strengths, weaknesses, terrain context
7. New `renderKeyIndicatorsHTML` — 3-column indicator badges for map popups
8. Pressure indicator is inverted (high pressure = bad = red, low pressure = good = green)

`components/intel/StandAlignmentPanel.tsx` — Richer UI:

1. New `IndicatorBadge` component with smart color logic (pressure inverted)
2. Key indicators row (3 badges) added between name and chips for each stand
3. “★ TODAY” badge on #1 stand
4. Expanded view now shows full `selectionExplanation` in a styled panel before quality bars
5. Removed duplicate resilience chip (now in indicators row)

`app/intel/page.tsx` — Popup & tooltip improvements:

1. Map popup now shows full `selectionExplanation` instead of short rationale
2. Key indicators row added to popup (between explanation and chips)
3. Removed redundant “To Corridor” and “To Bedding” distance boxes (info now in chips/indicators)
4. Approach risk label changed from “LOW risk” to “LOW risk approach”
5. Hover tooltip automatically gets improved chips + rationale from engine changes

Step 11b Decisions & Changes

`lib/map-animation.ts` — Enhanced animation toolkit:

1. Added `easeOutQuart`, `easeInQuart`, `easeOutExpo` easing curves
2. `staggeredFadeToggle` — cascading layer reveals/hides with per-layer delay
3. `gracefulClear` — fade-out all visible layers before wiping data sources (prevents “pop” on parcel)

switch)

4. `orchestratedReveal` — timed sequence for cinematic layer intros
5. Improved defaults: `fadeIn` uses `easeOutQuart` (400ms), `fadeOut` uses `easeInQuart` (300ms)

`app/intel/page.tsx` — Choreography improvements:

1. **Stand selection flyTo**: 1200ms duration, preserves current zoom (min 15.5), padding for top bar, popup shows after 400ms delay
2. **Corridor dim on stand select**: 600ms (was 400ms) with delayed highlight reveal (200ms gap)
3. **Layer toggles**: Corridors + ridges use `staggeredFadeToggle` (50ms/45ms stagger) for cascading effect
4. **Stand toggle**: HTML markers fade with per-marker CSS stagger (80ms), scale from 0.85→1
5. **Parcel clear**: Uses `gracefulClear` to fade all layers out (220ms) before wiping sources
6. **Marker rebuild** (wind/season): Old markers fade out (200ms) with scale shrink, new markers fade in with 80ms stagger
7. **Heatmap crossfade**: Slower reveal (550ms) for smoother pressure view transitions
8. **Re-center flyTo**: 1400ms duration (was instant)

Step 8 Decisions & Changes

All changes in `app/intel/page.tsx`:

1. **Rebuilt `buildStandSVG`** — fixed 100×100 viewBox for pixel-perfect crispness at all zoom levels
2. **Tapered tree-stand pole** replaces old broomstick rect — polygon with narrowing profile + platform crossbar + ground tick
3. **Consistent glow for all tiers** — top stand gets stronger glow (opacity 0.55), secondary/tertiary get subtle ambient glow (opacity 0.25)
4. **Inner shadow gradient** on disc for depth/dimension
5. **Crosshair ticks outside reticle ring** with center dot — cleaner scope aesthetic
6. **Removed tertiary opacity:0.7 hack** — all tiers now full opacity, differentiated by color/size only
7. **Unified color pipeline** — stroke and glow colors use `LAYER_COLORS` constants consistently (no more random hex values inline)
8. **standEmphasisGlow changed** from teal (`#2dd4bf`) to warm orange (`#f09048`) to match icon family
9. **Hover emphasis standardized** — all tiers get identical `scale(1.12)` + warm `fillColor`-tinted drop-shadow
10. **Tooltip colors standardized** — use tier-specific `LAYER_COLORS` instead of arbitrary hex

Step 12 Decisions & Changes

All changes in `app/intel/page.tsx`:

1. Removed `BUILD_STAMP` (fuchsia version badge at bottom-left)
2. Replaced “USGS 10m DEM” badge → “Verified Terrain” / “Preview” (customer-friendly)
3. Gated Explore/Debug buttons behind `?debug=true` URL param
4. Replaced `DEMModeBadge` component with clean “Data Quality” indicator
5. Replaced technical stats with plain-language “Primary Routes”, “Secondary Routes”, “Pinch Points”
6. Customer-friendly global error panel and `ErrorBoundary` (`AlertTriangle`, warm messaging)
7. Production console silencer — suppresses `[TFP]`, `[INTEL]`, `[MAP]`, `[EDGE]`, `[Backbone]`, `[TerrainFlow]`, `[EXPLORE]`, `[StandResilience]`, `[OVERLAY]` prefixed logs
8. Renamed “Export” → “Screenshot”

v4-fix14: Parcel-Only Camera Framing (replaces v4-fix10b)

- **Initial fit** (parcelPolygon available): Parcel-only bounds, padding 80px all sides, maxZoom 17, min zoom enforced at 14.5 after animation
- **Post-analysis refit**: REMOVED. v4-fix10b's stand-aware expansion (15% rule) caused progressive zoom-out on repeated Re-Align clicks when off-parcel stands pulled the camera outward. Camera is now ALWAYS parcel-only.
- **Re-center button**: Now uses `fitBounds` on parcel polygon (was `flyTo` zoom:14 which zoomed OUT from the 14.5 initial fit)
- **Refs**: `hasFitToParcel` (initial, one-shot), `hasPostAnalysisFit` (retained but unused — no consuming useEffect)
- **TARGET_MIN_ZOOM**: 14.5

v4-fix11: Camera-Synced Stand Markers

- **Two-phase scaling**: During camera motion → CSS `transform: scale()` on outer `el` (GPU-accelerated, no SVG rebuild). On camera settle → rebuild SVGs at final zoom for crispness.
- **rAF throttling**: Only one `requestAnimationFrame` in flight at a time during `move` events
- **Entry transition cleanup**: CSS transitions from staggered fade-in are removed 50ms after completion to prevent interference with zoom scaling
- **SVG rebuild threshold**: Only rebuilds if zoom delta > 0.3 from last rebuild (avoids unnecessary work on small pans)
- **will-change: transform** added during motion, removed on settle
- **Direction indicators** (tapered pole) are part of SVG, inherently synced with marker
- **Diagnostics**: `[STAND-DIAG] CAMERA MOVING`, `[STAND-DIAG] MARKER SYNC UPDATE`, `[STAND-DIAG] CAMERA SETTLED`, `[STAND-DIAG] MARKER SETTLED`
- **Refs**: `lastSVGRebuildZoom` tracks zoom at which SVGs were last built; `el.dataset.refScale` stores per-marker reference scale

vNext: GeoJSON Stand System (LOCKED BASELINE — 2026-04-02)

- **Status**: Stable baseline for demo and user testing. Do NOT modify stand rendering, transforms, or visual behavior unless a clear regression or user-facing issue appears.
- **Architecture**: Stands rendered as map-native Mapbox GeoJSON layers (zero HTML markers).
- Single `tfp-stands` GeoJSON source with point features for top 3 stands.
- 6 layers (highest z-index): `tfp-stands-glow`, `tfp-stands-disc`, `tfp-stands-reticle`, `tfp-stands-center`, `tfp-stands-label`, `tfp-stands-rank`.
- `STAND_LAYER_IDS` constant defined near the stand useEffect in `app/intel/page.tsx`.
- **Properties per feature**: `rank`, `label`, `rankLabel`, `color`, `strokeColor`, `score`, `standIdx`.
- **Click/hover**: `map.on('click'/'mouseenter'/'mouseleave', 'tfp-stands-disc', ...)` — calls `showStandPopup()` on click.
- **Visibility**: `setLayoutProperty(id, 'visibility', ...)` for show/hide. `setFilter(id, ...)` for solo mode.
- **Cleanup**: `(map.getSource('tfp-stands') as GeoJSONSource).setData(EMPTY_FC)` — no DOM elements to remove.

- **Removed machinery (~380 lines):** `markersRef`, `buildStandSVG`, `addStandMarkers`, `revealStandMarkers`, `scheduleStandReveal`, `standRevealTimerRef`, `cameraMovingRef`, camera tracker `useEffect`.
- **Zero-drift guarantee:** Mapbox handles all positioning internally. No CSS transforms, no DOM competition.
- **Preserved unchanged:** `tfp-hunt-pockets`, `tfp-stand-direction`, `tfp-stand-emphasis`, `showStandPopup()`, all stand selection/scoring logic (v4-fix17).

Parcel Pick Mode (Live Demo Feature)

- **Purpose:** One-click parcel selection for live demos — click any location on the map to look up the parcel, zoom to it, and auto-analyze.
- **Not debug-gated:** Available to all users (separate from the debug-only Exploration Mode).
- **UI:** “Pick Parcel” button in top bar (amber highlight when active). Floating instruction banner + loading spinner. Crosshair cursor when active.
- **Flow:** Click → `/api/parcels/lookup` → build GeoJSON Feature from lookup → `setParcelPolygon()` immediately (gold boundary) → `fitBounds` → sync `activeLatRef/activeLngRef/activeAcreageRef` → set active state → `setTimeout(runAnalysis, 100)`.
- **Stale-Closure Fix:** `runAnalysis` reads coordinates from `activeLatRef` / `activeLngRef` / `activeAcreageRef` (NOT from closure-captured `lat` / `lng`). All callers that update coords via `setActiveLat` / `setActiveLng` must also synchronously update these refs before scheduling `runAnalysis`. This applies to: `handleParcelPick`, `handleQaParcelAnalyze`, `handleQaParcelClear`, and the demo fallback path.
- **State:** `parcelPickMode`, `parcelPickLoading`. Exits pick mode after successful selection.
- **Esc key:** Exits pick mode.
- **Cleanup:** Clears all previous overlays, stand markers, huntability data, and analysis state before starting new parcel analysis.
- **Preserved:** All parcel-safe rules (stand pins inside parcel only), camera behavior, marker architecture.

v4-fix17: Parcel-Safe Stand Enforcement (replaces v4-fix16)

- **Rule:** All Top-3 stands must be strictly inside the parcel with a 15m interior safety buffer (`PARCEL_INSET_METERS`).
- **Three-tier enforcement in `computeAlignmentScores()`:**
 1. **Inside with buffer** (distance to edge $\geq 15\text{m}$) → accept as-is
 2. **Near boundary** (inside but $<15\text{m}$ from edge, or outside but within `MAX_SNAP_DISTANCE_METERS`) → snap inward via `snapToParcelInterior()`. Moves point to nearest valid interior position with buffer.
 3. **Too far outside** ($>80\text{m}$ from parcel) → discard, promote next-best candidate
- **Snap logic** (`snapToParcelInterior`):
 - Primary: move closest boundary point toward polygon centroid by `insetMeters + 2`
 - Fallback: iteratively move the candidate point toward centroid until buffered
 - Last resort: use polygon centroid if all else fails
 - Returns null if unable to snap → candidate discarded

- **Helpers added:** `signedDistanceToParcel()`, `getParcelRings()`, `movePointToward()`, `snapToParcelInterior()`
- **Diagnostics:** `[STAND-DIAG] snapped stand id=<id>`,
`[STAND-DIAG] rejecting ... reason=too far outside`,
`[STAND-DIAG] final stand count in parcel = <n> (snapped <n>, rejected <n>)`
- **Visual stability:** Marker `setLngLat(coords)` uses the snapped coordinate, so markers are anchored at the constrained position — no visual drift during zoom/pan.
- **Off-parcel terrain:** Still used for analysis context (corridors, pressure, movement) — only final stand PINS are constrained.
- **Fallback:** If no `parcelPolygon` geometry is available, all candidates pass through (graceful degradation).

v4-fix15: Settle-Gated Stand Reveal

- **Problem:** Stands 2–5 appeared to “fly in from outside the parcel” because markers were added and faded in while the camera was still moving (from `fitBounds`). Mapbox’s `translate()` repositioned their screen coordinates during camera motion, creating dramatic slide-in for off-center stands. Stand 1 looked fine because it was near the camera center.
- **Fix:** Decoupled marker creation from marker reveal:
 1. Markers created at opacity 0 / scale(0.85) with `dataset.revealed = '0'`
 2. `scheduleStandReveal()` checks if camera is moving → if idle, reveals after 80ms; if moving, delegates to settle handler
 3. `settleMarkers()` (camera settle callback) now calls `revealStandMarkers()` for any unrevealed markers
 4. `revealStandMarkers()` uses uniform 300ms fade-in with tight 40ms stagger — all stands appear together
 5. Phase 1 (camera move scaling) skips unrevealed markers
 6. Stand toggle skips unrevealed markers
- **Result:** All 5 stands appear at their final screen positions simultaneously — no fly-in, no speed differential

v4-fix13: Parcel Boundary Stability

- **Problem:** `gracefulClear` faded ALL tfp-* layers including parcel boundary, causing intermittent disappearance between analyzer clicks.
- **Fix:** (1) Removed `tfp-parcel` from `ALL_TFP_SOURCES` clear list. (2) Added `preserveLayerPrefixes` parameter to `gracefulClear()` — layers matching `'tfp-parcel-'` prefix skip the fade-out. Parcel boundary stays visible during re-analysis of the same parcel.

Key Architecture Notes

- **debugMode:** `const debugMode = searchParams.get('debug') === 'true'` at line ~1363 in `intel/page.tsx`. Admin features accessible via `?debug=true`.
- **Two mode variables in intel/page.tsx:**
- Outer scope: `TerrainMode ( 'real' | 'preview' )` — used in top bar
- Inner scope (line ~8125): `FlowMode ( 'real_dem' | 'terrain_driven' | 'synthetic' | 'error' )` — used in right panel terrain stats

- **QA panels** (Scorecard/Session/Analytics) only show in `explorationMode`, which requires `debug-Mode` — automatically hidden from customers.

Deployment

- **Primary hostname:** `terrafirmapartners.abacusai.app`
- **Custom domain:** `terrafirma.partners`
- **Always deploy after changes** — user preference

Demo Polish & Conversion (Latest)

- **Hero Parcels:** 4 curated demo parcels accessible via `?parcel=<slug>` URL param or `?demo=true`. Slugs: `pineville`, `pomme-de-terre`, `cedar-creek`, `mark-twain`. Defined in `HERO_PARCELS` constant in `app/intel/page.tsx`.
- Hero parcel selector grid (2×2) appears at top of left panel when in demo/hero mode.
- Active parcel highlighted with amber ring. Clicking another parcel clears state and triggers full re-analysis.
- `loadHeroParcel()` function handles clearing, coord update, camera fly, and analysis trigger.
- Pick Parcel de-emphasized (lower opacity) in demo mode but still functional.
- `activeHeroSlug` state tracks which hero is selected; cleared when entering Pick Parcel mode.
- **Onboarding banner:** Dismissible welcome card below hero selector when `demoMode` is true and no specific hero slug. Updated text references “Switch between demo parcels above.”
- **Section descriptions:** One-line plain-English subtitles under “Terrain Flow” (“How terrain shapes where deer travel”), “Deer Flow” (“Predicted movement patterns and pressure zones”), and “Stand Selection” (“Best treestand locations ranked by terrain advantage”) in the right panel.
- **“What We Found” card:** Green-tinted summary card in Chapter 3 (Intelligence Readout) that generates a natural-English sentence from `alignedStands.length`, `topStandScore`, `totalBeddingAcres`, `funnelCount`. Only shows when `summary` exists and `!isLoading`.
- **CTA card:** Red-tinted conversion card at bottom of left panel (after Re-Align button). Links to `/map?product=hunt_report` (“Analyze My Property”) and `/pricing`. Only shows when `summary` exists and `!isLoading`.

Mapping Stack (April 2026)

- **Mapbox GL JS** (`mapbox-gl@1.13.3`): Used for ALL maps — interactive map (`components/map/interactive-map.tsx`), territory share page, and PDF static images (Mapbox Static Images API). Google Maps fully removed.
- **Mapbox Token:** `NEXT_PUBLIC_MAPBOX_TOKEN` (client + server). No Google Maps API keys remain.
- **Style mapping:** `satellite`→ `satellite-v9`, `terrain`→ `outdoors-v12`, `hybrid`→ `satellite-streets-v12`, `roadmap`→ `streets-v12`
- **PDF routes** use `fetchMapboxStaticImage()` + `buildGeoJsonOverlay()` for static map images in generated PDFs.

Product Info

- Two-tier pricing: Hunt Report (\$149), Land Report (\$49)
- Target audience: Hunters (Facebook ad demos), rural land brokers
- Demo-friendly, broker-ready UI is critical

v2.0 Deer Flow & Stand Diversity (April 2026)

Deer Flow: v2.2 Parcel-Aware Expression (April 2026)

- **Design:** Stands = primary output; Deer Flow = secondary “why this works” layer, stronger on irregular parcels
- **Influence radii / falloff / soft-cap / smoothing:** unchanged from v2.0 (tight anti-blob core)
- **HARD_PRESSURE_FLOOR:** 0.62 (v2.0=0.68) — more mid-range terrain signal
- **Mapbox heatmap-radius:** 7/11/16 at zoom 10/15/18 (v2.0=6/10/15) — +1px
- **Weight dead zone:** 0.22 (v2.0=0.30); **Intensity:** 0.63/1.05; **Opacity:** 0.76; **Ridge overlap:** 0.54
- **Parcel complexity** (`computeParcelComplexity()` in `intel/page.tsx`): isoperimetric + vertex count + density → 0-1
- **getFocusPaintParams(focus, complexity)** in `terrain-heatmap.ts`: higher complexity → +2px radius, +0.08 intensity, +0.06 opacity

Stand Diversity Selection

- **Diversity pass** in `computeAlignmentScores()` — greedy selection with penalties:
- 150m hard minimum separation between any two selected stands
- Proximity penalty: smooth decay within 250m radius (35% factor)
- Terrain similarity penalty: 12% when dominant context matches (ridge/draw/bench/bedding_edge)
- Classification by TPI: >1.5=ridge, <-1.5=draw, bedding<80m=bedding_edge, else=bench
- **Raster stand spacing:** `MIN_SEPARATION_CELLS` raised to 10 (was 4) = ~150m separation
- Applied BEFORE parcel-safe enforcement so diversity is maintained even after snapping

v2.1: EDGE_STAND Field-Edge Hunting (April 2026)

Detection (`terrain-raster.ts` → `detectFieldEdge()`)

- Radial scan of cover scores (ridge0.6 + bench0.3 + sidehill*0.1) in 8 compass directions, 4-cell radius (~60m)
- Edge detected when: center has cover (≥ 0.20), steepest direction drop ≥ 0.12 , AND opposite direction retains cover (confirms edge, not open field)
- Excluded: saddle >0.4, full timber (ridge>0.5 && bench>0.3), draw, open — only ‘edge’ and partial ‘timber’ qualify
- Output: `isEdgeStand`, `fieldBearing` (bearing toward open field), `edgeConfidence` (0-1)
- Propagated: `PrimeStandSite` → `primeStandSitesToGeoJSON` → `StandPointProperties` (`types/terrain.ts`)

Position Bias (`intel/page.tsx` → `computeAlignmentScores`)

- After parcel-safe enforcement, edge stands nudged 10m toward `fieldBearing`
- Only applied if nudged position is safely inside parcel (no snap needed)
- Logged: `[STAND-DIAG] EDGE_STAND nudge`

Hunt Pocket (`buildHuntPocketFeatures`)

- **Terrain stands:** unchanged teardrop (FWD 2.8 / BWD 0.35 / LAT 0.45, upstream shift 30%)
- **Edge stands:** forward-biased fan:
- FWD_STRETCH 2.4 / BWD_STRETCH 0.55 (70/30 forward bias)
- Asymmetric laterals: field-side 0.70 (wide fan) / timber-side 0.30 (tight)

- Pocket center shifted 35% toward field (vs 30% upstream for terrain)
- corridorBias 0.75 (vs 0.85 for terrain) — fan shape, not corridor lane
- `isEdgeStand` flag included in pocket feature properties

Kill Zone Wedge v2.3 (`buildStandDirectionFeatures`)

- **Output:** Filled Polygon wedge fans (was LineString broomstick lines)
- **Facing:** Composite 70% movement vector + 30% wind-adjusted (downwind) bearing via circular weighted average
- **Terrain stands:** 50m length, $\pm 12^\circ$ half-angle (narrow)
- **Edge stands:** 65m length, $\pm 25^\circ$ half-angle (wide), points into field via `fieldBearing`
- **Layers:** `tfp-stand-direction-main` = `fill` type (fill-opacity 0.14/0.18), `tfp-stand-direction-flank` = `line` type (outline stroke, line-opacity 0.25/0.35)
- **Semantic labels:** `watchLabel` property on each polygon: “Watching: Field Edge” / “Watching: Saddle Funnel” / “Watching: Creek Crossing” / “Watching: Corridor” / “Watching: Ridge Line”
- **Wind param:** `windDirectionRef.current` passed at call site
- **layer-visibility.ts:** `tfp-stand-direction-main` → `fill-opacity` 0.16

What NOT to Touch

- Terrain-driven stands (saddle, ridge, draw) are completely unaffected
- vNext GeoJSON stand layer system remains locked
- Existing scoring, diversity selection, and parcel-safe enforcement unchanged

v2.1-fix1: Direction Layer Opacity + Stand Cap (April 2026)

- **Bug:** Direction wedge layers (`tfp-stand-direction-main` , `tfp-stand-direction-flank`) are `line` type but `opacityProp` was set to `fill-opacity` in two places:
- `lib/layer-visibility.ts` reconcile table
- `app/intel/page.tsx` `staggeredFadeToggle` call
- After `gracefulClear` correctly faded them out via `line-opacity` , restore paths used `fill-opacity` (no-op on line layers) → layers stayed invisible
- **Fix:** Changed all `fill-opacity` refs to `line-opacity` for both direction layers. Added explicit visibility + opacity restoration in the stand `useEffect` (alongside `STAND_LAYER_IDS` restore).
- **Bug:** `alignedStands` could contain >3 stands because `allScoredDiverse` includes diversity picks + remaining pool, and parcel-safe enforcement accepts all that pass.
- **Fix:** Added `aligned = aligned.slice(0, 3)` as single enforcement point before `setAlignedStands()` . Eliminates stale/extra cards from compare dropdowns and any other `.map()` consumers.

Stand & Pocket Visual Refinement (April 2026)

- **Stand marker layers** (all 6 `tfp-stands-*` layers in intel page):
- Glow ring: radii 14/12/10 (was 18/15/13), opacity 0.18/0.12/0.08 (was 0.25/0.18/0.12)
- Main disc: radii 9/7.5/6 (was 10/8.5/7), stroke-width 1.8/1.5 (was 2.5/2), stroke-opacity 0.7 (was 0.9)
- Reticle: radii 4.5/3.8/3 (was 5.5/4.5/3.5), stroke-width 0.7 (was 1), opacity 0.3 (was 0.4)
- Center dot: radius 1.2 (was 1.5), opacity 0.5 (was 0.6)

- Labels: `DIN Pro Medium` (was Bold), sizes 11/10/9.5 (was 12/11/10), halo-width 1.2 (was 2), halo-blur 0.5 (was 1), letter-spacing 0.02em
- Rank numbers: `DIN Pro Medium` (was Bold), sizes 12/10.5/9.5 (was 14/12/11), halo-width 0.6 (was 1)
- **Hunt pocket fill:** Muted to warm tan `#c49872` / `#c4a67a` (was saturated orange `#e2712a` / `#e8943a` matching stand markers — caused visual competition/busyness)

Deterministic PRNG (April 2026)

- All `Math.random()` in `terrain-flow.ts` and `terrain-flow-v3.ts` replaced with seeded PRNG (`sRand()` from `lib/seeded-rng.ts`).
- PRNG seeded from parcel centroid via `seedRng()` — same parcel always produces identical flow lines, convergence zones, and scores.
- Sort tie-breaking added: `terrain-raster.ts` candidates by row/col, intel page alignment scores by original rank.
- Flow IDs use deterministic counter (`nextFlowId()`) instead of `Date.now()`.
- `seedRng` and `sRand` exported from both `seeded-rng.ts` and re-exported from `terrain-flow.ts`.

v2.3 PRNG Race Condition Fix (April 2026)

- **Root cause:** `_seededRng` was a module-level singleton. Rapid Re-Analyze clicks could trigger overlapping `runAnalysis` calls, each calling `seedRng()` which reset the shared RNG mid-generation, corrupting both runs' stand candidate sequences.
- **Fix 1 — Guard ref:** `analysisInFlightRef` at top of `runAnalysis` returns early if an analysis is already running. Cleared in `finally` block. Prevents overlapping runs entirely.
- **Fix 2 — Factory-based RNG:** `lib/seeded-rng.ts` rewritten with:
 - `createSeededRng(centroid)` → returns isolated `SeededRng` instance with `.random()` and `.nextFlowId()`
 - `setActiveRng(rng)` → sets the instance that `sRand()` / `nextFlowId()` delegate to (backward compat for `terrain-flow-v3` call sites)
 - `seedRng(centroid)` retained as legacy wrapper (creates + activates in one call)
 - `terrain-flow.ts` updated at both call sites (`generateTerrainDrivenFlow` line ~377, `generateLegacySyntheticFlow` line ~981) to use `createSeededRng()` + `setActiveRng()`

Territory Mode (April 2026)

- **Three-tier model:** Free = 1 parcel analysis. Pro = \$99/yr or \$12/mo, 5-parcel Territory Mode. Pro Max = \$199/yr or \$24/mo, 10-parcel Territory Mode.
- **Parcel cap:** Tier-based — `TERRITORY_PARCEL_CAP` computed from `isProMax ? 10 : isPro ? 5 : 1`.
- `isPro` = `subStatus === 'pro' || subStatus === 'promax'` (gates save/share/territory access)
- `isProMax` = `subStatus === 'promax'` (gates 10-parcel cap)
- **Stripe price IDs:** Pro Annual `price_1TM7iXCj0K9CKFruXstxLL2e`, Pro Monthly `price_1TM7LRCj0K9CKFruUtcZBuZA`. Pro Max Annual `price_1TMuhSCj0K9CKFruz6PR8tvR`, Pro Max Monthly `price_1TMukZCj0K9CKFruSNqFzG8r` (live in Stripe; env vars `STRIPE_PROMAX_ANNUAL_PRICE_ID` / `STRIPE_PROMAX_MONTHLY_PRICE_ID` with alt aliases `STRIPE_PRO_MAX_YEARLY_PRICE_ID` / `STRIPE_PRO_MAX_MONTHLY_PRICE_ID`).
- **Webhook tier detection:** `getTierFromPriceId()` checks price against ProMax env vars → returns 'promax' or 'pro'.

- **Brett Wilson** (`bwilson@restoredental.com`): Manually set to `promax` in DB.
- **Stripe session polling**: Loop + “Already subscribed? Click to activate” escape hatch.
- **Grey film overlay**: `tfp-adjacent-parcels-fill` hidden during territory mode.
- **Territory parcels vanishing fix**: 4 forced `visibility: 'none'` calls gated — territory layers only hide if `territoryParcels` array is explicitly empty.

Pricing Page Pro Max Wiring (April 2026)

- `app/pricing/page.tsx` Pro and Pro Max cards are now wired directly to Stripe checkout via `handleUpgrade(tier)` function.
- `handleUpgrade` posts `{plan, tier}` to `/api/stripe/checkout` (`tier = 'pro' | 'promax'`, `plan = 'annual' | 'monthly'` from billing toggle).
- Unauthenticated users redirect to `/login?callbackUrl=%2Fpricing` (NOTE: actual auth route is `/login`, NOT `/signin` — intel page has the same bug with `/signin` references that should be corrected when touched).
- Pro card: emerald-600 styling, “Go Pro” CTA.
- Pro Max card: **solid bronze/dark-gold palette** — border `#8b6b1f`, header background `#8b6b1f` (solid, no gradient), price text `#8b6b1f`, feature checkmarks `#8b6b1f`, “BEST VALUE” badge `#6b4f14`, CTA `#8b6b1f` with hover `#6b4f14`, text on bronze `#f5e6b8`. “Go Pro Max” CTA. Retains “⚡ PRO MAX” header, \$199/year or \$24/month pricing, 10-parcel Territory Mode + Priority processing features.
- Free tier still uses `<Link href="/intel">` — “Get Started Free” button (unchanged).
- Billing toggle state drives both price display and which price ID gets used (annual vs monthly) by the backend.

Territory ErrorBoundary Guard + MultiPolygon Fix (April 2026)

- **Root cause**: “Analyzer Paused” full-screen modal fired on second territory parcel pick. The `Intel-ErrorBoundary` (class component) caught render-time or cascading errors and showed the modal with no territory awareness.
- **Fix 1 — ErrorBoundary territory master guard**: Module-level `_territoryModeGlobal` ref synced from `useEffect([territoryMode])`. `getDerivedStateFromError` returns `hasError: false` when territory mode is active. `componentDidCatch` auto-recovers. `render()` has belt-and-suspenders check.
- **Fix 2 — Stall watchdog territory guard**: `setInterval` callback returns early when `territory-ModeRef.current` is true. Prevents demo fallback from firing during territory building.
- **Fix 3 — Empty result guard territory guard**: `useEffect` returns early when `territory-ModeRef.current` is true. Prevents demo fallback from firing when territory mode has no analysis results.
- **Fix 4 — Demo fallback catch territory guard**: Added `!territoryModeRef.current` to the demo fallback condition in `runAnalysis` catch block (alongside existing `!isTerritoryRun`).
- **Fix 5 — Territory pick MultiPolygon handling**: `handleParcelPick` territory path now reads `parcel.geometryType` from the lookup API. MultiPolygon parcels create `GeoJSON.Feature<GeoJSON.MultiPolygon>` instead of wrapping coordinates as Polygon.
- **Fix 6 — mergeParcelPolygons MultiPolygon**: Now iterates all sub-polygons from MultiPolygon parcels instead of only taking `coordinates[0]`.

- **Fix 7 — `getTerritoryBounds` `MultiPolygon`:** Iterates all outer rings from all sub-polygons instead of only `coordinates[0][0]`.
- **Fix 8 — Territory map source try-catch:** `useEffect([territoryParcels])` wrapped in try-catch to prevent Mapbox `source.setData()` errors from propagating.
- **Diagnostic logging:** `[TRIGGER-DIAG]` prefix on `runAnalysis` entry, `[ERROR-BOUNDARY]` prefix on `ErrorBoundary` methods.

Territory Builder Firewall (April 2026)

- **Problem:** Single-parcel terrain analyzer and territory builder shared state — clicking Territory then adding adjacent parcels blanked the Territory Builder sidebar, lost yellow primary boundary, and caused 502 errors on Re-Align.
- **Solution:** “TERRITORY FIREWALL” guards across all single-parcel code paths that could corrupt territory state.
- **Guarded functions** (all return early when `territoryModeRef.current` is true):
 - `handleQaParcelLookup` — prevents single-parcel lookups from overwriting territory
 - `handleQaParcelAnalyze` — prevents single-parcel analyze from replacing territory analysis
 - `handleQaParcelClear` — prevents clearing territory parcels/overlays
 - `loadHeroParcel` — prevents hero parcel loading from replacing territory
- Adjacent parcel click handler — prevents adjacent parcel overlay from running in territory mode
- **`runAnalysis` territory firewall** (top of function): When `territoryModeRef.current` is true AND no `prefetchedParcelRef.current` AND `territoryParcelsRef.current.length <= 1`, returns early. Blocks stale mount calls, `setTimeout` leftovers, and demo fallbacks from firing single-parcel analysis during territory mode.
- **`runAnalysis` catch block:** When `territoryModeRef.current` is true, errors are logged but `setError` and `setProgressStep('Failed')` are suppressed.
- **Error suppression in territory mode:**
 - `useEffect([territoryMode, error])` auto-clears error/isLoading/backgroundAnalysis when both are truthy
 - Error toast guarded with `!territoryMode` — never renders during territory building
 - `globalError` panel: when `globalError && territoryMode`, schedules `setTimeout(0)` to clear error state and shows gentle toast “Parcel added — hit Analyze Territory to run the full report”
- **Territory auto-seed:** Entering territory mode auto-seeds primary parcel (instead of starting empty)
- **Re-Align fix:** When `isTerritoryRun && !prefetchedParcel`, `runAnalysis` calls `mergeParcelPolygons(territoryParcelsRef.current)` to re-create the merged `MultiPolygon` instead of fetching a wrong single parcel from `Regrid`
- **`clearAllOverlaySources` skip:** Skipped for territory re-aligns to preserve territory boundaries
- **Server timeout:** Increased from 25s to 55s in `app/api/terrain-analysis/route.ts`
- **Client timeout:** Territory analysis uses 90s timeout with 1200m buffer
- **`gracefulClear` preserves** `tfp-territory-` prefix layers — territory boundaries survive overlay clears
- **`ALL_TFP_SOURCES`** does NOT include `tfp-territory-parcels` — territory layer data is never wiped by source clears

Deer Flow Stitching (Territory Mode, April 2026)

- Flow lines now cross parcel boundaries and unify territory movement picture across all 5 parcels.
- Three files fixed: `lib/terrain-analysis.ts`, `lib/terrain-flow.ts`, `lib/terrain-flow-v3.ts`.
- Union geometry replaces largest-polygon-only extraction across entire pipeline.
- `extractMultiPolygonData`, `pointInAnyRing` helpers added.
- `createBufferedParcel` buffers all sub-polygons for full territory DEM coverage.
- `clipFlowLinesToParcel` is multi-ring aware; overlap threshold lowered from 0.40 to 0.20 for territories.
- Convergence and opportunity zone generation supports multiple polygon rings.

Modal Backend Integration

- Cold start fix: timeouts extended, `fetchWithRetry()` helper, `flowMode: 'synthetic'` flag.
- Pick Parcel 502 fix: HTTP status check + toast + auto-retry on both pick paths.

Key Contacts

- Grant Martin — Douglas County KS, 40 acres, onX power user
- Brett Wilson — Oklahoma, 4-5 parcels + in-laws 4,000 spread acres, Pro subscriber
- Cheryl Schmidt — Kansas landowner

Region Gate: 8-State Supported Coverage (April 2026)

- **Root cause of OK silent failures (historical):** `/api/parcels/lookup/route.ts` had a hardcoded 2-state bounds gate (KS + MO only) that rejected ALL out-of-region clicks before Regrid was ever called.
- **Now fixed — gate expanded to 8 supported regions** via named variables:
 - `inKS` (36.99–40.00 lat, -102.05 to -94.59 lng)
 - `inMO` (35.99–40.61 lat, -95.77 to -89.10 lng)
 - `inOK` (33.62–37.00 lat, -103.00 to -94.43 lng)
 - `inAR` (33.00–36.50 lat, -94.62 to -89.64 lng)
 - `inNE` (39.99–43.00 lat, -104.06 to -95.30 lng)
 - `inIA` (40.37–43.51 lat, -96.64 to -90.14 lng)
 - `inTXPanhandle` (34.30–36.51 lat, -103.05 to -99.99 lng)
 - `inCOEast` (plains only, 37.00–41.01 lat, -105.80 to -102.04 lng — intentionally excludes Front Range/mountains)
- **Combined via** `inSupportedRegion = inKS || inMO || inOK || inAR || inNE || inIA || inTXPanhandle || inCOEast`
- **Rejection response** returns `likelyState` which now classifies edge-of-region as `OK_EDGE` | `AR_EDGE` | `NE_EDGE` | `IA_EDGE` | `TX_PANHANDLE_EDGE` | `CO_EAST_EDGE` | `OUT_OF_REGION` for server-log correlation.
- **Error message text:** “Location outside current coverage area. Supported states: KS, MO, OK, AR, NE, IA, TX panhandle, eastern CO.”
- **Regrid coverage confirmed via docs:** All 8 regions are covered by Regrid Parcel API tier we already pay for. OK alone has 335K+ parcels across all 77 counties.

- **Territory Mode diagnostics retained** (client-side `attemptTerritoryLookup` in `app/intel/page.tsx` ~8107-8175):
- `[TERRITORY-REGRID-DIAG]` console.error logs for non-JSON / HTTP error / no-parcel failures with `attempt`, `clickLat/Lng`, `httpStatus`, `errorCode`, `fullResponseBody`, `debugInfo`
- 3-branch toast.error: outside-coverage (“Supported states: KS, MO, OK, AR, NE, IA, Texas pan-handle, and eastern CO”), rate-limit, generic coverage-gap (“No parcel boundary found here — Regrid coverage may be limited in this county”).
- **Server-side:** `[PARCEL_LOOKUP]` prefix logs on region-gate rejection + Regrid response failures (non-JSON, HTTP error, status=error, 0-results). Response includes `regrid` field with upstream body on failures.
- **Scope:** Only Territory Mode click path in `handleParcelPick` has the enhanced toast/logging. Single-parcel path (~line 8203) and QA path (~line 7784) still use original silent-return pattern.
- **To add another state:** Define `inXX` const with bounding-box lat/Lng, add to `inSupportedRegion` OR chain, add `XX_EDGE` clause to `likelyState` classifier, add to rejection log payload. All three changes in same file (~lines 110-155).

Territory Shareable URLs (April 2026)

- **File:** `app/intel/page.tsx` — three parts work together.
- **URL format:** `https://terrafirma.partners/intel?territory=true&name=<name>&p1lat=..&p1lng=..&p2lat=..&p2lng=..&p3lat=..&p3lng=..&p4lat=..&p4lng=..&p5lat=..&p5lng=..` (supports up to 5 parcels, matches `TERRITORY_PARCEL_CAP` for Pro). Only lat/Lng pairs that are non-zero are loaded.
- **URL param block** (~line 1879): parses `urlTerritory`, `urlP1Lat/Lng` through `urlP5Lat/Lng`, and `urlTerritoryName`.
- **Auto-load useEffect** (~line 4685, runs once on mount when `mapReady` + `urlTerritory` are true, guarded by `territoryUrlLoadedRef`):
 1. Sets `territoryMode=true` and `territoryName=urlTerritoryName`.
 2. For each non-zero (lat, lng) pair: calls `/api/parcels/lookup?lat=..&lng=..`, builds a GeoJSON Polygon / MultiPolygon Feature (mirrors Territory Mode click handler logic — handles `geometry-Type: 'MultiPolygon'` and closes Polygon rings), then `addParcelToTerritory(...)`.
 3. 150ms delay between adds so React state settles.
 4. After loop, 2000ms delay for React to flush, then merges polygons, sets `parcelPolygon` + `activeLat/Lng/Acreage/Address` + refs + `prefetchedParcelRef.current = merged` + `territoryFadeInPending.current = true` + `runAnalysis()` (200ms further delay for camera fit).
 5. Keeps `territoryMode=true` so Builder panel stays visible during analysis (matches the Analyze Territory button behavior).
 6. Does NOT force `setTerritoryMode(false)` — `isTerritoryRun` is determined by `territoryParcelsRef.current.length > 1` in `runAnalysis`, independent of `territoryMode` state.
- **copyTerritoryLink function** (~line 3177, useCallback deps: `[territoryParcels, territoryName]`): builds the URL using `URLSearchParams`, writes to clipboard via `navigator.clipboard.writeText`, shows sonner `toast.success`. Falls back to `window.prompt` if clipboard fails (insecure context / older browsers). Only operates when `territoryParcels.length >= 2`.
- **Copy Territory Link button** (~line 9782, Territory Builder panel, just below Analyze Territory button): green-on-dark-green styling (bg `#1a3a2a`, text `#52b788`, border `#2d6a4f`), only renders when `territoryParcels.length >= 2`.
- **Diagnostics:** `[TERRITORY-URL]` prefix for all console logs (load, failures, auto-analyze trigger).

Hunt Report PDF Page 1 Density (April 2026)

- **File:** `app/api/parcel-hunt-file/route.ts` (~662 lines) — NOT `generate-pdf/route.ts`.
- **Problem:** Page 1 slightly overflowed onto a blank last page — too much vertical padding and margins.
- **Solution — .page-1 scoped CSS overrides** (in the `<style>` block, below `.disclaimer`):
 - `.page-1 .header { margin-bottom: 20px }`
 - `.page-1 .gold-bar { margin-bottom: 14px }`
 - `.page-1 .score-hero { padding: 20px; margin-bottom: 14px }` (was 32/24)
 - `.page-1 .big-score { font-size: 60px }` (was 72px)
 - `.page-1 .score-sub { margin-top: 4px }`
 - `.page-1 .grid-3 { margin-bottom: 14px }`
 - `.page-1 .stat-box { padding: 10px }` (was 16px)
 - `.page-1 .stat-value { font-size: 22px }` (was 28px — targets the “11.3 / 0 / 6” Bedding/Corridors/Funnels row)
 - `.page-1 .stat-label { margin-top: 2px }`
 - `.page-1 .section-title { margin-bottom: 10px; padding: 8px 16px }`
 - `.page-1 .season-grid { margin-bottom: 14px }`
 - `.page-1 .season-cell { padding: 14px }` (was 20px)
- **Scoping matters:** `.score-hero`, `.stat-box`, `.stat-value`, `.grid-3`, `.section-title`, `.season-grid`, `.season-cell`, `.gold-bar` are ALL used on other pages. Use `.page-1` scope — never edit base CSS.
- **Page 1 wrapper:** `<div class="page page-1 border">` (add `page-1` class alongside existing `page border`).
- **Inline tightenings:** Title div `margin-bottom:24→14px`, `28→26px`; Terrain Character padding `16/20→12/16`, margin `24→14`, line-height `1.8→1.55`; bottom 4-col grid `gap:16px;margin-bottom:24px → gap:12px;margin-bottom:10px`.
- **leaseIntelHTML / dualAudienceHTML** are page-1-only variables (used only once, at line ~343 & ~358 in the page 1 wrapper) — tightened directly (`12/14` padding, `1.45-1.5` line-heights, `10px` inner padding, `20px` stat font).
- **When adding new page-1 content:** prefer `.page-1 .your-class` overrides over inline styles to keep the density pattern consistent.

Free-Tier Download Wall (April 2026)

- **PDF watermark:** `parcel-hunt-file/route.ts` derives tier server-side from `session.user.subscriptionStatus`. When `serverTier === 'free'`, adds `preview-watermark` class to all `.page` divs. CSS `::after` pseudo-element renders diagonal “PREVIEW” text (`120px`, `rgba 0.06` opacity, `-35deg` rotation) across each page.
- **Soft auth:** `/api/parcel-hunt-file` uses soft auth — no session → free tier (PREVIEW watermark). Logged-in users get tier from `session.user.subscriptionStatus`. No 401 rejection. Tier is NEVER passed from client.
- **PDF layout fix:** `.page` uses `padding-bottom: 60px` (no min-height). `.footer` is static flow with `margin-top: 24px` (was absolute positioned with `min-height: 1056px` causing half-page white space).
- **Download button gating** (intel page): `isPro` → normal download. Free → locked button with  icon, triggers `showDownloadWall` modal.

- **Download wall modal:** “Share Your Territory Score” title, copy about A+ score / lease value / intercept points. “Go Pro — \$99/yr” CTA → `handleUpgrade('annual', 'pro')`. “Maybe Later” dismiss.
- **Share link gating:** Territory “Copy Territory Link” locked for free (🔒 prefix, triggers download wall). “Share Territory Score” button shown in muted style for free with 🔒, triggers download wall.
- **Single-parcel Save/Share:** Already gated by existing `isPro` checks — no changes needed.
- **Report preview modal** (`showReportPreview`): Free users see “📄 View Hunt Report Preview” button (gold outline on dark). Opens inline JSX modal rendering report content directly from component state (`alignedStands`, `summary`, `terrainStory`, `tieredCorridorData`) — no API fetch. Has PREVIEW watermark, stand cards, hunt certificate, bottom CTA bar with Close + “🔒 Upgrade to Download” buttons. Upgrade button chains to `showUpgradeModal`.
- **Pro users:** See gold “↓ Download Hunt Report” button that triggers direct `handleDownloadParcel-HuntFile` download.
- **States:** Only `showReportPreview` boolean. Button onClick is simply `setShowReportPreview(true)` — no fetch, no loading state needed.
- **What NOT changed:** Zero terrain analysis, stand logic, map layer, or scoring changes.

Stuck Dim Overlay Fix (April 2026)

- **Root cause:** `dimOverlayLayers(0.4)` called during Re-Align sets `reAlignFadeInPending.current = true`. Restore only happened in data-painting `useEffect` (triggers on `layers` state change). On analysis failure, `layers` never updates → `useEffect` never fires → `dim` stays permanently at 0.4.
- **Fix:** Added `dimOverlayLayers(1.0)` restore in TWO places in `runAnalysis`:
 1. `catch` block: if `reAlignFadeInPending.current` is still true, restore immediately
 2. `finally` block: belt-and-suspenders safety net for demo fallback path (which `returns` before `finally`)

Stand Paywall & Stability System (April 2026)

Phase 1 — Stand Pin Hiding (Free Users)

- Stand GeoJSON `useEffect` gated with `parcelUnlockedRef + isProRef`
- When locked: all stand-related sources cleared (`EMPTY_FC`), all layers hidden
- Sources: `tfp-stands`, `tfp-stand-emphasis`, `tfp-hunt-pockets`, `tfp-stand-direction`, `tfp-stand-tertiary`
- Visibility toggle + map click handler also gated
- Blur overlay shows “📍 N Stand Locations Identified” teaser
- Floating CTA shows stand count when available

Phase 2 — Stand Stability

- `previousStandsRef` remembers last top-3 stands
- `STABILITY_REPLACEMENT_THRESHOLD = 5` points; `STABILITY_NEIGHBORHOOD_M = 50m`
- Diagnostic logging: `[STAND-STABILITY]` prefix (`REPLACED`, `SNAPPED`, `RETAINED`, `NEW_STAND`, `INITIAL`)
- Resets on parcel change

Visual Stability Polish (April 2026)

Bedding Area Stability

- `previousBeddingRef` remembers bedding polygons across re-analyses
- `BEDDING_NEIGHBORHOOD_M` = 80m — snap to previous geometry if centroid within 80m
- Diagnostic logging: `[BEDDING-STABILITY]` prefix (SNAPPED, NEW)
- Resets on parcel change

Stand Toggle Fix

- Visibility toggle refactored with `applyVisibility()` + `style.load` retry
- Added `mapReady`, `parcelUnlocked`, `isPro` to deps for deterministic sync

Hunt Pocket Translucency Stability

- Hunt pocket layers use layout `visibility` toggle (not opacity animation)
- Data-driven `fill-opacity` expression re-applied after `gracefulClear`
- Prevents scalar overwrite of expression-based paint properties

\$19 Per-Parcel Monetization Layer (April 2026)

- **ParcelPurchase model** added to Prisma schema: `userId + parcelLat + parcelLng` unique constraint, links to User
- **Stripe Price ID:** `price_1T0eUsCj0K9CKFru97ub9E2o` (\$19 one-time, env var `STRIPE_HUNT_PLAN_PRICE_ID`)
- **API routes added:**
 - `GET /api/parcels/check-access?lat=XX&lng=YY` — returns `{ hasAccess, isPro, isLoggedIn }`
 - `POST /api/parcels/purchase` — creates Stripe checkout for \$19 parcel unlock
 - `DELETE /api/properties/delete?id=XX` — removes saved property
- **Webhook update** (`/api/stripe-webhook`): handles `purchaseType: 'hunt_plan'` in checkout metadata → upserts `ParcelPurchase`
- **Save API** (`/api/properties/save`): Pro gate REMOVED — any logged-in user can save parcels
- **Access logic:** `isPro` (pro/promax subscription) bypasses per-parcel paywall. Free users need \$19 purchase per parcel.
- **Intel page changes:**
 - `parcelUnlocked` state checked after analysis via `/api/parcels/check-access`
 - `handlePurchaseParcel()` function → Stripe checkout for \$19
 - `StandAlignmentPanel` wrapped with blur overlay when locked
 - Paywall modal with \$19 unlock + Pro upsell
 - Save prompt (logged-in) / sign-up prompt (anonymous) in left panel
 - Beta banner (“⚡ Beta Access — Intro Pricing \$19”) top of viewport for free users
 - Floating CTA button (“🎯 Get My Hunt Plan — \$19”) bottom center
 - “My Parcels” link in top bar for logged-in users
 - `parcel_unlocked=true` URL param handled on return from Stripe
 - `parcelUnlocked` + `lastSavedPropertyId` reset on new parcel selection
- **Properties page** (`/properties`): “Terrain Intelligence Library” — shows saved parcels with grade, stats, unlock status, delete, click-to-reopen. Pro upsell for free users.

- **Coexistence:** Pro/ProMax subscribers see everything unlocked everywhere. The \$19 per-parcel flow is for free-tier users only.

Key Files

- `app/intel/page.tsx` — Main terrain intelligence page (~12,100 lines)
- `app/api/parcel-hunt-file/route.ts` — Hunt Report PDF generator (~662 lines, `.page-1` scoped density)
- `lib/map-animation.ts` — Animation utility (Step 11)
- `lib/scoring/stand-explainability.ts` — Stand scoring (Step 9)
- `components/intel/StandAlignmentPanel.tsx` — Stand alignment UI (Step 9)
- `components/intel/WindCompass.tsx` — Wind compass (Step 5)
- `lib/terrain-analysis.ts` — Territory flow stitching
- `lib/terrain-flow.ts` — Flow line generation (multi-polygon aware)
- `lib/terrain-flow-v3.ts` — V3 flow generation (multi-polygon aware)