

# **SOURCEBOOK**

## **DEVISE**

### **DATA ANALYSIS**

**Abstract:** This chapter provides step-by-step instructions on how to obtain basic statistical output using DEVISE via written instructions. Simple examples for most undergraduate-level between-subjects and within-subjects research designs are provided.

**Keywords:** DEVISE, directions for use

**Original:** March 2021

**Updated:** January 2025

This document is part of an online statistics sourcebook.

A browser-friendly viewing platform for the sourcebook is available:

<https://cwendorf.github.io/Sourcebook>

All data, syntax, and output files are available:

<https://github.com/cwendorf/Sourcebook>

## TABLE OF CONTENTS FOR THIS CHAPTER

Frequencies .....	3
Descriptives .....	4
Transformations and Standardized Scores .....	5
Correlations .....	6
Confidence Intervals .....	7
One Sample t Test.....	8
Paired Samples t Test.....	9
Independent Samples t Test .....	10
OneWay ANOVA.....	11
Post Hoc Comparisons .....	12
Repeated Measures ANOVA .....	13
Factorial ANOVA.....	14

# Frequencies

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Frequencies

Get the frequency distribution for the variable.

```
(Outcome) |> describeFrequencies()
```

## Obtaining Summary Statistics

Get the percentiles for the variable.

```
(Outcome) |> describePercentiles()
```

# Descriptives

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Frequencies

Get the frequency distribution for the variable.

```
(Outcome) |> describeFrequencies()
```

## Obtaining Descriptive Statistics

Get the mean and standard deviation for the variable.

```
(Outcome) |> describeMoments()
```

# Transformations and Standardized Scores

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Computing Transformations

Use a formula to calculate a new vector with the transformed scores.

```
trOutcome <- Outcome + 1
```

Create and display a the data set in a frame.

```
construct(Outcome, trOutcome)
```

## Computing Standardized Scores

Create a new variable vector containing the standardized scores.

```
zOutcome <- scale(Outcome)
```

Create and display the data set in a frame.

```
construct(Outcome, trOutcome, zOutcome)
```

# Correlations

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the means and standard deviations for the variables.

```
(CorrelationData) |> describeMoments()
```

Get the covariance matrix for the variables.

```
(CorrelationData) |> describeCovariances()
```

Get the correlation matrix for the variables.

```
(CorrelationData) |> describeCorrelations()
```

## Obtaining Inferential Statistics

Get the correlation and its confidence interval.

```
(CorrelationData) |> estimateCorrelations()
```

Test the correlation for statistical significance.

```
(CorrelationData) |> testCorrelations()
```

# Confidence Intervals

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation for the variable.

```
(Outcome) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the mean and its confidence interval.

```
(Outcome) |> estimateMeans()
```

# One Sample t Test

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation for the variable.

```
(Outcome) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the mean difference and its confidence interval.

```
(Outcome) |> estimateMeans(mu = 7)
```

Test the mean difference for statistical significance.

```
(Outcome) |> testMeans(mu = 7)
```

Get the standardized effect size for the mean difference.

```
(Outcome) |> standardizeMeans(mu = 7)
```



# Paired Samples t Test

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the means and standard deviations for the variables.

```
(PairedData) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the mean difference and its confidence interval.

```
(PairedData) |> estimateDifference()
```

Test the mean difference for statistical significance.

```
(PairedData) |> testDifference()
```

Get the standardized effect size for the mean difference.

```
(PairedData) |> standardizeDifference()
```

# Independent Samples t Test

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation of the dependent variable for each of the levels.

```
(Outcome~Factor) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the mean difference and its confidence interval.

```
(Outcome~Factor) |> estimateDifference()
```

Test the mean difference for statistical significance.

```
(Outcome~Factor) |> testDifference()
```

Get the standardized effect size for the mean difference.

```
(Outcome~Factor) |> standardizeDifference()
```

# OneWay ANOVA

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation of the dependent variable for each of the levels.

```
(Outcome~Factor) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the analysis of variance source table.

```
(Outcome~Factor) |> describeEffect()
```

Test the main effect for statistical significance.

```
(Outcome~Factor) |> testEffect()
```

Get the proportion of variance accounted for by the main effect.

```
(Outcome~Factor) |> estimateEffect()
```

# Post Hoc Comparisons

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation for the dependent variable for each of the levels.

```
(Outcome~Factor) |> describeMoments()
```

## Obtaining Inferential Statistics

Get all pairwise mean difference and their confidence intervals while adjusting them for multiple comparisons.

```
(Outcome~Factor) |> estimatePosthoc()
```

Test all pairwise mean differences for statistical significance while adjusting them for multiple comparisons.

```
(Outcome~Factor) |> testPosthoc()
```

Get standardized mean differences for all pairwise comparisons.

```
(Outcome~Factor) |> standardizePosthoc()
```

# Repeated Measures ANOVA

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the means and standard deviations for the variables.

```
(RepeatedData) |> describeMoments()
```

## Obtaining Inferential Statistics

Get the analysis of variance source table.

```
(RepeatedData) |> describeEffect()
```

Test the main effect for statistical significance.

```
(RepeatedData) |> testEffect()
```

Get the proportion of variance accounted for by the main effect.

```
(RepeatedData) |> estimateEffect()
```

# Factorial ANOVA

Prior to the steps below, enter the data as appropriate for the analyses (described elsewhere). As always, the following commands should be typed directly in the R console window.

## Obtaining Descriptive Statistics

Get the mean and standard deviation of the dependent variable for each of the levels. The “by” option tells DEVISE how to split the data.

```
(Outcome~FactorA) |> describeMoments(by = FactorB)
```

## Obtaining Inferential Statistics

Get the analysis of variance source table.

```
(Outcome~FactorA) |> describeFactorial(by = FactorB)
```

Test the main effects for statistical significance.

```
(Outcome~FactorA) |> testFactorial(by = FactorB)
```

Get the proportion of variance accounted for by the main effects.

```
(Outcome~FactorA) |> estimateFactorial(by = FactorB)
```