

Module 3

Regression

Spring 2026

What is regression?

- We observe data: $(x_n, t_n), \quad n = 1, \dots, N$
- Assume a model: $t_n = y(x_n, \mathbf{w}) + \epsilon_n$
- Where: $\epsilon_n \sim \mathcal{N}(0, \sigma^2)$
- Goal: infer parameters \mathbf{w}

Not “draw a curve”

→ infer a *model that explains noisy measurements*

From model to probability

□ Noise assumption gives a likelihood: $p(t_n \mid \mathbf{w}) = \mathcal{N}(t_n \mid y(x_n, \mathbf{w}), \sigma^2)$

From model to probability

□ Noise assumption gives a likelihood: $p(t_n \mid \mathbf{w}) = \mathcal{N}(t_n \mid y(x_n, \mathbf{w}), \sigma^2)$

□ For independent datapoints:

$$p(\mathbf{t} \mid \mathbf{w}) = \prod_{n=1}^N \mathcal{N}(t_n \mid y(x_n, \mathbf{w}), \sigma^2)$$

From model to probability

❑ Noise assumption gives a likelihood: $p(t_n \mid \mathbf{w}) = \mathcal{N}(t_n \mid y(x_n, \mathbf{w}), \sigma^2)$

❑ For independent datapoints:

$$p(\mathbf{t} \mid \mathbf{w}) = \prod_{n=1}^N \mathcal{N}(t_n \mid y(x_n, \mathbf{w}), \sigma^2)$$

❑ Take log:

$$\log p(\mathbf{t} \mid \mathbf{w}) = -\frac{1}{2\sigma^2} \sum_n (t_n - y(x_n, \mathbf{w}))^2 + \text{const}$$

Least squares emerges

□ Maximize likelihood \Leftrightarrow minimize:

$$\chi^2(\mathbf{w}) = \sum_n (t_n - y(x_n, \mathbf{w}))^2$$



Remember from last module!

□ Least squares = MLE for Gaussian noise

□ Important: fitting depends on noise assumptions

Linear-in-parameters model


□ 'Linear Regression model' -> model parameters are linear

$$y(x, \mathbf{w}) = \sum_{j=0}^M w_j \phi_j(x)$$

Linear-in-parameters model

□ 'Linear Regression model' -> model parameters are linear

$$y(x, \mathbf{w}) = \sum_{j=0}^M w_j \phi_j(x)$$




Basis functions are not necessarily linear – e.g. polynomial, Fourier

Linear-in-parameters model

□ 'Linear Regression model' -> model parameters are linear

$$y(x, \mathbf{w}) = \sum_{j=0}^M w_j \phi_j(x)$$



Basis functions are not necessarily linear – e.g. polynomial, Fourier

□ Define design matrix

$$\Phi_{nj} = \phi_j(x_n)$$

Linear-in-parameters model

□ 'Linear Regression model' -> model parameters are linear

$$y(x, \mathbf{w}) = \sum_{j=0}^M w_j \phi_j(x)$$

Basis functions are not necessarily linear – e.g. polynomial, Fourier

□ Define design matrix

$$\Phi_{nj} = \phi_j(x_n)$$

□ Model becomes:

$$t_n = y(x_n, \mathbf{w}) + \epsilon_n \quad \longrightarrow \quad \mathbf{t} = \Phi \mathbf{w} + \epsilon$$

Deriving the normal equations

□ Goal - Minimize: $E(\mathbf{w}) = ||\mathbf{t} - \Phi\mathbf{w}||^2$

Deriving the normal equations

□ Goal - Minimize: $E(\mathbf{w}) = ||\mathbf{t} - \Phi\mathbf{w}||^2$

□ Differentiate and solve $\frac{\partial E}{\partial \mathbf{w}} = -2\Phi^T(\mathbf{t} - \Phi\mathbf{w}) = 0$

Deriving the normal equations

□ Goal - Minimize: $E(\mathbf{w}) = ||\mathbf{t} - \Phi\mathbf{w}||^2$

□ Differentiate and solve $\frac{\partial E}{\partial \mathbf{w}} = -2\Phi^T(\mathbf{t} - \Phi\mathbf{w}) = 0$


$$\Phi^T \Phi \mathbf{w} = \Phi^T \mathbf{t}$$

$$\mathbf{w}_{ML} = (\Phi^T \Phi)^{-1} \Phi^T \mathbf{t}$$

Note: use linear solver for last step – inverting the matrix will get computationally expensive


Geometric meaning

- ☐ Measurements of data do not lie in perfect plane due to noise



Geometric meaning

- ❑ Measurements of data do not lie in perfect plane due to noise
- ❑ Hyperplane represents best prediction of output given our input data



Geometric meaning

- ❑ Measurements of data do not lie in perfect plane due to noise
- ❑ Hyperplane represents best prediction of output given our input data
- ❑ Does this by minimizing distance of projections onto hyperplane

