

MSc assignment: Projectional Editing support for Textual Languages

Mauricio Verano Merino


14th of February 2019

Context

Language Workbenches



Language



User Interface
Debuggers
Processors
Type Checkers
Code Generators
...

Rascal

<http://www.rascal-mpl.org>




- Meta-programming language for **source code analysis** and **transformation**.
- **Language workbench** for DSL development.
- Successfully used in various domains (e.g., finance, digital forensics)
- Command line Read-Eval-Print Loop (**REPL**) + Eclipse **IDE**.

Bacatá

A **language parametric** Jupyter notebook generator for DSLs written using Rascal language workbench, **which reuses** language components.

Objectives:

- Open up the **interactive notebook metaphor** for DSLs
- Extend current set of **generated IDE services** of language workbenches
- Generate DSL notebooks with **minimum effort**



jupyter Tax form Last Checkpoint: a few seconds ago (autosaved) Logout

File Edit View Insert Cell Kernel Help Trusted | QL O

In [1]:

```
1 form taxOfficeExample {
2   "Did you buy a house in 2010?"
3   hasBoughtHouse: boolean
4
5   "Did you enter a loan?"
6   hasMaintLoan: boolean
7
8   "Did you sell a house in 2010?"
9   hasSoldHouse: boolean
10
11   if (hasSoldHouse) {
12     "What was the selling price?"
13     sellingPrice: money
14     "Private debts for the sold house:"
15     privateDebt: money
16     "Value residue:"
17     valueResidue: money = sellingPrice - privateDebt
18   }
19 }
```

Out[1]:

Form: taxOfficeExample
Did you buy a house in 2010? ☐ true ☒ false
Did you enter a loan? ☐ true ☒ false
Did you sell a house in 2010? ☐ true ☒ false
What was the selling price?
Private debts for the sold house:
Value residue:

In []: 1

Language Workbench Support for Block-based Environments

Tool for **deriving** block-based environments from **context-free grammars**.

```
start syntax Machine
= machine: "machine" Id State*;


syntax State
= state: "state" Id "{" Trans* "}";

syntax Trans
= transitions: "on" Id "to" Id;

lexical Id
= [a-zA-Z]+;



lexical State
= [a-zA-Z]+;
```

Context-free
grammars




Projectional Editing support for Textual Languages

Textual Languages
(Rascal)



Projectional Editors
(MPS)





Language A

Abstract
Syntax

Parser

Type
checker


Concrete
Syntax

Interpreter

Program A

Textual

Projectional



Editor

Constraints

Transformations

Structure

Type system

Model A

Language A'

Projectional Editing support for Textual Languages

➡Goal

- Explore a way to enable **interoperability** between textual and projectional language workbenches.

➡Exploratory research

- **Characterize** constructs of projectional editors
- Define a possible **mapping** between textual and projectional language artefacts.
- Manipulate MPS models somehow **API-wise** outside MPS

➡Case study (Océ)

- Small configuration DSL