

Search Q

Sian in

Public API



GET statuses/show/:id

Returns a single Tweet, specified by the id parameter. The Tweet's author will also be embedded within the tweet.

See GET statuses / lookup for getting Tweets in bulk (up to 100 per call). See also Embeddable Timelines, Embeddable Tweets, and GET statuses/oembed for tools to render Tweets according to Display Requirements.

About Geo

If there is no geotag for a status, then there will be an empty <geo/> or "geo" : {}. This can only be populated if the user has used the Geotagging API to send a statuses/update.

The JSON response mostly uses conventions laid out in GeoJSON. Unfortunately, the coordinates that Twitter renders are reversed from the GeoJSON specification (GeoJSON specifies a longitude then a latitude, whereas we are currently representing it as a latitude then a longitude). Our JSON renders as:

```
"geo": { "type": Point", "coordinates": [37.78029, -122.39697] }
```

Contributors

If there are no contributors for a Tweet, then there will be an empty or "contributors": {}. This field will only be populated if the user has contributors enabled on his or her account — this is a beta feature that is not yet generally available to all.

This object contains an array of user IDs for users who have contributed to this status (an example of a status that has been contributed to is this one). In practice, there is usually only one ID in this array. The JSON renders as such "contributors": [8285392].

Resource URL

https://api.twitter.com/1.1/statuses/show.json

Resource Information

Response formats	JSON
Requires authentication?	Yes
Rate limited?	Yes
Requests / 15-min window (user auth)	180
Requests / 15-min window (app auth)	180

Parameters

id required	The numerical ID of the desired Tweet. Example Values: 123		
trim_user optional	When set to either true, t or 1, each tweet returned in a timeline will include a user object including only the status authors numerical ID. Omit this parameter to receive the complete user object. Example Values: true		
include_my_retweet optional	When set to either true, t or 1, any Tweets returned that have been retweeted by the authenticating user will include an additional current_user_retweet node, containing the ID of the source status for the retweet. Example Values: true		
include_entities	The entities node will be disincluded when set to false.		

Example Values: false

optional

OAuth Signature Generator

Sign in to see a list of your registered applications.

Example Request

GET

https://api.twitter.com/1.1/statuses/show.json?id=210462857140252672

Example Result

```
"coordinates": null,
"favorited": false,
"truncated": false,
"created_at": "Wed Jun 06 20:07:10 +0000 2012",
"id_str": "210462857140252672",
"entities": {
 "urls": [
   "expanded_url": "https://dev.twitter.com/terms/display-guidelines",
   "url": "https://t.co/Ed4omjYs",
   "indices": [
   76,
   97
  ],
   "display_url": "dev.twitter.com/terms/display-\u2026"
 1,
 "hashtags": [
   "text": "Twitterbird",
  "indices": [
   19,
   31
 "user_mentions": [
```

```
},
 "in reply to user id str": null,
 "contributors": [
 14927800
 ],
 "text": "Along with our new #Twitterbird, we've also updated our Display
Guidelines: https://t.co/Ed4omjYs ^JC",
 "retweet count": 66,
 "in_reply_to_status_id_str": null,
 "id": 210462857140252672,
 "geo": null,
 "retweeted": true,
 "possibly sensitive": false,
 "in reply to user id": null,
 "place": null,
 "user": {
  "profile_sidebar_fill_color": "DDEEF6",
  "profile sidebar border color": "CODEED",
  "profile background tile": false,
  "name": "Twitter API",
  "profile_image_url":
"http://a0.twimg.com/profile_images/2284174872/7df3h38zabcvjylnyfe3_normal.pn
g",
  "created_at": "Wed May 23 06:01:13 +0000 2007",
  "location": "San Francisco, CA",
  "follow_request_sent": false,
  "profile link color": "0084B4",
  "is translator": false,
  "id str": "6253282",
  "entities": {
   "url": {
    "urls": [
      "expanded url": null,
      "url": "http://dev.twitter.com",
      "indices": [
      0,
      22
```

```
},
   "description": {
    "urls": [
    1
  }
  },
  "default profile": true,
  "contributors enabled": true,
  "favourites count": 24,
  "url": "http://dev.twitter.com",
  "profile image url https":
"https://si0.twimg.com/profile images/2284174872/7df3h38zabcvjylnyfe3 normal.
png",
  "utc_offset": -28800,
  "id": 6253282,
  "profile use background image": true,
  "listed count": 10774,
  "profile text color": "333333",
  "lang": "en",
  "followers_count": 1212963,
  "protected": false,
  "notifications": null,
  "profile_background_image_url_https":
"https://si0.twimg.com/images/themes/theme1/bg.png",
  "profile_background_color": "C0DEED",
  "verified": true,
  "geo enabled": true,
  "time zone": "Pacific Time (US & Canada)",
  "description": "The Real Twitter API. I tweet about API changes, service
issues and happily answer questions about Twitter and our API. Don't get an
answer? It's on my website.",
  "default profile image": false,
  "profile_background_image_url":
"http://a0.twimg.com/images/themes/theme1/bg.png",
  "statuses_count": 3333,
  "friends_count": 31,
  "following": true,
  "show all inline media": false,
```

```
"screen_name": "twitterapi"
},
"in_reply_to_screen_name": null,
"source": "web",
"in_reply_to_status_id": null
}
```

This request could also be obtained with: GET

https://api.twitter.com/1.1/statuses/show/210462857140252672.json

	FABRIC	DATA & WEB	RESOURCES	PROGRAMS	TOOLS
	Digits	Gnip	Documentation	Certified Partner	API Status
	Sign in with Twitter	REST APIs	Forums	Events	API Console
	Twitter Social	Streaming APIs	Blog	Flight 2014	Manage Your Apps
	Crashlytics	Twitter for Websites	Case Studies		Cards Validator
Answers by Crashlytics		API Terms			
	Beta by Crashlytics				
	MoPub				

Subscribe to Our Newsletter

▼ Terms Of Service Copyright © 2014 Twitter Inc All Rights Reserved

About Blog Help Status Jobs Terms Privacy Cookies Adsinfo Brand Advertise

Businesses Media Developers Directory

© 2015 Twitter, Inc.