

Chapter 4

Automata

Mathematical Modeling

(Materials drawn from this chapter in:

- Peter Linz. *An Introduction to Formal Languages and Automata*, (5th Ed.), Jones & Bartlett Learning, 2011.
- John E. Hopcroft, Rajeev Motwani and Jeffrey D. Ullamn. *Introduction to Automata Theory, Languages, and Computation* (3rd Ed.), Prentice Hall, 2006.
- Antal Iványi *Algorithms of Informatics*, Kempelen Farkas Hallgatói Információs Központ, 2011.)

TVHoai, HTNguyen, NAKhuong, LHTrang
Faculty of Computer Science and Engineering
University of Technology, VNU-HCM



Contents

- 1 Motivation
- 2 Alphabets, words and languages
- 3 Regular expression or rationnal expression
- 4 Non-deterministic finite automata
- 5 Deterministic finite automata
- 6 Recognized languages
- 7 Determinisation
- 8 Minimization
- 9 DFAs combination
- 10 Some applications



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rationnal expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications



Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications


Course learning outcomes

L.O.1	Understanding of predicate logic
	L.O.1.1 – Give an example of predicate logic
	L.O.1.2 – Explain logic expression for some real problems
	L.O.1.3 – Describe logic expression for some real problems
L.O.2	Understanding of deterministic modeling using some discrete structures
	L.O.2.1 – Explain a linear programming (mathematical statement)
	L.O.2.2 – State some well-known discrete structures
	L.O.2.3 – Give a counter-example for a given model
	L.O.2.4 – Construct discrete model for a simple problem
L.O.3	Be able to compute solutions, parameters of models based on data
	L.O.3.1 – Compute/Determine optimal/feasible solutions of integer linear programming models, possibly utilizing adequate libraries
	L.O.3.2 – Compute/ optimize solution models based on automata, ..., possibly utilizing adequate libraries

Introduction

Standard states of a process in operating system

- **O** with label: states
- \rightarrow : transitions



Why study automata theory?

A useful model

for many important kinds of software and hardware

- ① designing and checking the behaviour of digital circuits
- ② lexical analyser of a typical compiler: a compiler component that breaks the input text into logical units
- ③ scanning large bodies of text, such as collections of Web pages, to find occurrences of words, phrases or other patterns
- ④ verifying practical systems of all types that have a finite number of distinct states, such as communications protocols and other protocols for securely information exchange, etc.



Definition

Alphabet Σ (*bảng chữ cái*) is a finite and non-empty set of symbols (or characters).

For example:

- $\Sigma = \{a, b\}$
- The binary alphabet: $\Sigma = \{0, 1\}$
- The set of all lower-case letters: $\Sigma = \{a, b, \dots, z\}$
- The set of all ASCII characters.

Remark

Σ is almost always all available characters (lowercase letters, capital letters, numbers, symbols and special characters such as space or newline).

But nothing prevents to imagine other sets.



Strings (words)



Definition

- A **string/word** u (*chuỗi/từ*) over Σ is a finite **sequence** (possibly empty) of **symbols** (or characters) in Σ .
- A **empty string** is denoted by ε .
- The length of the string u , denoted by $|u|$, is the number of characters.
- All the strings over Σ is denoted by Σ^* .
- A **language** L over Σ is a sub-set of Σ^* .

Remark

The purpose aims to analyze a string of Σ^* in order to know whether it belongs or not to L .

Example

Let $\Sigma = \{0, 1\}$

- ε is a string with length of 0.
- 0 and 1 are the strings with length of 1.
- 00, 01, 10 and 11 are the strings with length of 2.
- \emptyset is a language over Σ . It's called the **empty language**.



Example

Let $\Sigma = \{0, 1\}$

- ε is a string with length of 0.
- 0 and 1 are the strings with length of 1.
- 00, 01, 10 and 11 are the strings with length of 2.
- \emptyset is a language over Σ . It's called the **empty language**.
- Σ^* is a language over Σ . It's called the **universal language**.
- $\{\varepsilon\}$ is a language over Σ .
- $\{0, 00, 001\}$ is also a language over Σ .
- The set of strings which contain an odd number of 0 is a language over Σ .
- The set of strings that contain as many of 1 as 0 is a language over Σ .



String concatenation

Intuitively, the concatenation of two strings **01** and **10** is **0110**.
Concatenating the empty string ε and the string **110** is the string **110**.

Definition

String concatenation is an application of $\Sigma^* \times \Sigma^*$ to Σ^* .
Concatenation of two strings u and v in Σ is the string $u.v$.



Specifying languages

A language can be specified in several ways:





Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Specifying languages

A language can be specified in several ways:

- a enumeration of its words, for example:
- $L_1 = \{\varepsilon, 0, 1\},$
 - $L_2 = \{a, aa, aaa, ab, ba\},$
 - $L_3 = \{\varepsilon, ab, aabb, aaabbb, aaaabbbb, \dots\},$



Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Specifying languages

A language can be specified in several ways:

a enumeration of its words, for example:

- $L_1 = \{\varepsilon, 0, 1\},$
- $L_2 = \{a, aa, aaa, ab, ba\},$
- $L_3 = \{\varepsilon, ab, aabb, aaabbb, aaaabbbb, \dots\},$

b a property, such that all words of the language have this property but other words have not, for example:

- $L_4 = \{a^n b^n \mid n = 0, 1, 2, \dots\},$
- $L_5 = \{uu^{-1} \mid u \in \Sigma^*\} \text{ with } \Sigma = \{a, b\},$
- $L_6 = \{u \in \{a, b\}^* \mid n_a(u) = n_b(u)\} \text{ where } n_a(u) \text{ denotes the number of letter 'a' in word } u.$



Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Specifying languages

A language can be specified in several ways:

a enumeration of its words, for example:

- $L_1 = \{\varepsilon, 0, 1\}$,
- $L_2 = \{a, aa, aaa, ab, ba\}$,
- $L_3 = \{\varepsilon, ab, aabb, aaabbb, aaaabbbb, \dots\}$,

b a property, such that all words of the language have this property but other words have not, for example:

- $L_4 = \{a^n b^n \mid n = 0, 1, 2, \dots\}$,
- $L_5 = \{uu^{-1} \mid u \in \Sigma^*\}$ with $\Sigma = \{a, b\}$,
- $L_6 = \{u \in \{a, b\}^* \mid n_a(u) = n_b(u)\}$ where $n_a(u)$ denotes the number of letter 'a' in word u .

c its grammar, for example:

- Let $G = (N, T, P, S)$ where
 $N = \{S\}$, $T = \{a, b\}$, $P = \{S \rightarrow aSb, S \rightarrow ab\}$
i.e. $L(G) = \{a^n b^n \mid n \geq 1\}$ since
 $S \Rightarrow aSb \Rightarrow a^2 Sb^2 \Rightarrow \dots \Rightarrow a^n Sb^n$

Operations on languages

L, L_1, L_2 are languages over Σ

- *union*

$$L_1 \cup L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ or } u \in L_2\},$$

- *intersection*

$$L_1 \cap L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ and } u \in L_2\},$$

- *difference*

$$L_1 \setminus L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ and } u \notin L_2\},$$

- *complement*

$$\overline{L} = \Sigma^* \setminus L,$$

- *multiplication*

$$L_1 L_2 = \{uv \mid u \in L_1, v \in L_2\},$$



Operations on languages

L, L_1, L_2 are languages over Σ

- *union*

$$L_1 \cup L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ or } u \in L_2\},$$

- *intersection*

$$L_1 \cap L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ and } u \in L_2\},$$

- *difference*

$$L_1 \setminus L_2 = \{u \in \Sigma^* \mid u \in L_1 \text{ and } u \notin L_2\},$$

- *complement*

$$\overline{L} = \Sigma^* \setminus L,$$

- *multiplication*

$$L_1 L_2 = \{uv \mid u \in L_1, v \in L_2\},$$

- *power*

$$L^0 = \{\varepsilon\}, \quad L^n = L^{n-1} L, \text{ if } n \geq 1,$$

- *iteration or star operation*

$$L^* = \bigcup_{i=0}^{\infty} L^i = L^0 \cup L \cup L^2 \cup \dots \cup L^i \cup \dots,$$

We will use also the notation L^+

$$L^+ = \bigcup_{i=1}^{\infty} L^i = L \cup L^2 \cup \dots \cup L^i \cup \dots.$$

The union, product and iteration are called **regular operations**.



Example

Let $\Sigma = \{a, b, c\}$, $L_1 = \{ab, aa, b\}$, $L_2 = \{b, ca, bac\}$

- a $L_1 \cup L_2 = ?$,
- b $L_1 \cap L_2 = ?$,
- c $L_1 \setminus L_2 = ?$,
- d $L_1 L_2 = ?$,
- e $L_2 L_1 = ?$.



Example

Let $\Sigma = \{a, b, c\}$, $L_1 = \{ab, aa, b\}$, $L_2 = \{b, ca, bac\}$

- a $L_1 \cup L_2 = \{ab, aa, b, ca, bac\}$,
- b $L_1 \cap L_2 = \{b\}$,
- c $L_1 \setminus L_2 = \{ab, aa\}$,
- d $L_1 L_2 = \{abb, aab, bb, abca, aaca, bca, abbac, aabac, bbac\}$,
- e $L_2 L_1 = \{bab, baa, bb, caab, caaa, cab, bacab, bacaa, bacb\}$.



Example

Let $\Sigma = \{a, b, c\}$, $L_1 = \{ab, aa, b\}$, $L_2 = \{b, ca, bac\}$

- a $L_1 \cup L_2 = \{ab, aa, b, ca, bac\}$,
- b $L_1 \cap L_2 = \{b\}$,
- c $L_1 \setminus L_2 = \{ab, aa\}$,
- d $L_1 L_2 = \{abb, aab, bb, abca, aaca, bca, abbac, aabac, bbac\}$,
- e $L_2 L_1 = \{bab, baa, bb, caab, caaa, cab, bacab, bacaa, bacb\}$.

Let $\Sigma = \{a, b, c\}$ and $L = \{ab, aa, b, ca, bac\}$

$L^2 = ?$



Example

Let $\Sigma = \{a, b, c\}$, $L_1 = \{ab, aa, b\}$, $L_2 = \{b, ca, bac\}$

- a $L_1 \cup L_2 = \{ab, aa, b, ca, bac\}$,
- b $L_1 \cap L_2 = \{b\}$,
- c $L_1 \setminus L_2 = \{ab, aa\}$,
- d $L_1 L_2 = \{abb, aab, bb, abca, aaca, bca, abbac, aabac, bbac\}$,
- e $L_2 L_1 = \{bab, baa, bb, caab, caaa, cab, bacab, bacaa, bacb\}$.

Let $\Sigma = \{a, b, c\}$ and $L = \{ab, aa, b, ca, bac\}$

$L^2 = u.v$, with $u, v \in L$ including the following strings:

- $abab, abaa, abb, abca, abbac,$
- $aaab, aaaa, aab, aaca, aabac,$
- $bab, baa, bb, bca, bbac,$
- $caab, caaa, cab, caca, cabac,$
- $bacab, bacaa, bacb, bacca, bacbac.$



Let $\Sigma = \{a, b, c\}$

Give at least 5 strings for each of the following languages

- 1 all strings with exactly one '*a*'.
- 2 all strings of even length.
- 3 all strings which the number of appearances of '*b*' is divisible by 3.
- 4 all strings ending with '*a*'.
- 5 all non-empty strings not ending with '*a*'.
- 6 all strings with at least one '*a*'.
- 7 all strings with at most one '*a*'.
- 8 all strings without any '*a*'.
- 9 all strings including at least one '*a*' and whose the first appearance of '*a*' is not followed by '*c*'.



Exercise

Let $\Sigma = \{a, b, c\}$ and $L = \{ab, aa, b, ca, bac\}$

Which of the following strings are in L^* ?

Ⓐ $aaa = a^3$,

Ⓑ $abaabaaabaa = aba^2ba^3ba^2$,

Ⓒ bbb ,

Ⓓ aab ,

Ⓔ cc ,

Ⓕ $aaaabaaaa = a^4ba^4$,

Ⓖ $cabbbbbaaaaaaaaaab = cab^4a^9b$,

Ⓗ $baaaaabaaaab = ba^5ba^4b$,

Ⓙ $baaaaabaac = ba^5ba^2c$,

⓫ $baca$.



Regular expressions

Regular expressions (biểu thức chính quy)

Permit to specify a language with strings consist of letters and ε , parentheses $()$, operating symbols $+$, $.$, $*$. This string can be empty, denoted \emptyset .

Regular operations on the languages

- **union** \cup or $+$
- **product of concatenation**
- **transitive closure** $*$



Regular expressions

Regular expressions (biểu thức chính quy)

Permit to specify a language with strings consist of letters and ε , parentheses $()$, operating symbols $+$, $.$, $*$. This string can be empty, denoted \emptyset .

Regular operations on the languages

- **union** \cup or $+$
- **product of concatenation**
- **transitive closure** $*$

Example on the alphabet set $\Sigma = \{a, b\}$

- $(a + b)^*$ represent all the strings
- $a^*(ba^*)^*$ represent the same language
- $(a + b)^*aab$ represent all strings ending with aab .



Regular expressions

- \emptyset is a regular expression representing the empty language.
- ε is a regular expression representing language $\{\varepsilon\}$.
- If $a \in \Sigma$, then a is a regular expression representing language $\{a\}$.
- If x, y are regular expressions representing languages X and Y respectively, then $(x + y)$, (xy) , x^* are regular expression representing languages $X \cup Y$, XY and X^* respectively.



Regular expressions

- \emptyset is a regular expression representing the empty language.
- ε is a regular expression representing language $\{\varepsilon\}$.
- If $a \in \Sigma$, then a is a regular expression representing language $\{a\}$.
- If x, y are regular expressions representing languages X and Y respectively, then $(x + y)$, (xy) , x^* are regular expression representing languages $X \cup Y$, XY and X^* respectively.

$$x + y \equiv y + x$$

$$(x + y) + z \equiv x + (y + z)$$

$$(xy)z \equiv x(yz)$$

$$(x + y)z \equiv xz + yz$$

$$x(y + z) \equiv xy + xz$$

$$(x + y)^* \equiv (x^* + y)^* \equiv (x + y^*)^* \equiv (x^* + y^*)^*$$

$$(x + y)^* \equiv (x^* y^*)^*$$

$$(x^*)^* \equiv x^*$$

$$x^* x \equiv x x^*$$

$$x x^* + \varepsilon \equiv x^*$$





Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Kleene's theorem

Language $L \subseteq \Sigma^*$ is regular if and only if there exists a regular expression over Σ representing language L .

Exercise

Let $\Sigma = \{a, b, c\}$

Give at least 3 words for each language represented by the following regular expressions

- ① $E_1 = a^* + b^*$,
- ② $E_2 = a^*b + b^*a$,
- ③ $E_3 = b(ca + ac)(aa)^* + a^*(a + b)$,
- ④ $E_4 = (a^*b + b^*a)^*$.

Example

$$a^*b = \{b, ab, a^2b, a^3b, \dots, aaa \dots ab\},$$



Exercise

Let $\Sigma = \{a, b, c\}$

Determine regular expression presenting for each of the following languages.

- 1 all strings with exactly one '*a*'.
- 2 all strings of even length.
- 3 all strings which the number of appearances of '*b*' is divisible by 3.
- 4 all strings ending with '*a*'.
- 5 all non-empty strings not ending with '*a*'.
- 6 all strings with at least one '*a*'.
- 7 all strings with at most one '*a*'.
- 8 all strings without any '*a*'.
- 9 all strings including at least one '*a*' and whose the first appearance of '*a*' is not followed by a '*c*'.



[Contents](#)[Motivation](#)[Alphabets, words and
languages](#)[Regular expression or
rational expression](#)[Non-deterministic
finite automata](#)[Deterministic finite
automata](#)[Recognized languages](#)[Determinisation](#)[Minimization](#)[DFAs combination](#)[Some applications](#)

Let $\Sigma = \{a, b, c\}$ and $L = \{ab, aa, b, ca, bac\}$

Which languages represented by the following regular expressions are in L^* ?

- ① $E_1 = a^* + ba,$
- ② $E_2 = b^* + a^* aba^*,$
- ③ $E_3 = aab + cab^* ac,$
- ④ $E_4 = b(ca + ac)(aa)^* + a^*(a + b),$
- ⑤ $E_5 = (a^4 ba^3)^{2*} c,$
- ⑥ $E_6 = b^+ ac \ (b^+ = bb^*),$
- ⑦ $E_7 = (b + c)ab + ba(c + ab)^*,$
- ⑧ $E_8 = (b + c)^* ab + a(c + a)^*.$

Exercise

Let $\Sigma = \{a, b, c\}$ and $L = \{ab, aa, b, ca, bac\}$

Which languages represented by the following regular expressions are in L^* ?

- ① $E_1 = a^* + ba,$
- ② $E_2 = b^* + a^* aba^*,$
- ③ $E_3 = aab + cab^* ac,$
- ④ $E_4 = b(ca + ac)(aa)^* + a^*(a + b),$
- ⑤ $E_5 = (a^4 ba^3)^{2*} c,$
- ⑥ $E_6 = b^+ ac \ (b^+ = bb^*),$
- ⑦ $E_7 = (b + c)ab + ba(c + ab)^*,$
- ⑧ $E_8 = (b + c)^* ab + a(c + a)^*.$

Define a (simple) regular expression representing the language L^* .





Simplify each of the following regular expressions

- ① $E_1 = b + ab^* + aa^*b + aa^*ab^*$,
- ② $E_2 = a^*(b + ab^*)$,
- ③ $E_3 = \varepsilon + ab + abab(ab)^*$,
- ④ $E_4 = (ba)^* + a(ba)^* + (ba)^*b + a(ba)^*b$,
- ⑤ $E_5 = aa(b^* + a) + a(ab^* + aa)$,
- ⑥ $E_6 = (a^*(ba)^*)^*(b + \varepsilon)$,
- ⑦ $E_7 = a(a + b)^* + aa(a + b)^* + aaa(a + b)^*$.

Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Finite automata (Automat hữu hạn)

- The aim is representation of a process system.
- It consists of states (including an **initial state** and one or several (or one) **final/accepting states**) and **transitions** (events).
- The number of states must be finite.



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization


DFAs combination

Some applications

Finite automata

Finite automata (Automat hữu hạn)

- The aim is representation of a process system.
- It consists of states (including an **initial state** and one or several (or one) **final/accepting states**) and **transitions** (events).
- The number of states must be finite.



Regular expression

$$b^*(a + b)$$




Exercise

Let $\Sigma = \{a, b\}$

Which of the strings

- ① a^3b ,
- ② aba^2b ,
- ③ $a^4b^2ab^3a$,
- ④ a^4ba^4 ,
- ⑤ ab^4a^9b ,
- ⑥ ba^5ba^4b ,
- ⑦ ba^5b^2 ,
- ⑧ bab^2a

are accepted by the following finite automata?





Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications


Let $\Sigma = \{a, b, c\}$

Propose FA presenting each of the following languages

- ① all strings with exactly one '*a*'.
- ② all strings of even length.
- ③ all strings which the number of appearances of '*b*' is divisible by 3.
- ④ all strings ending with '*a*'.
- ⑤ all non-empty strings not ending with '*a*'.
- ⑥ all strings with at least one '*a*'.
- ⑦ all strings with at most one '*a*'.
- ⑧ all strings without any '*a*'.
- ⑨ all strings including at least one '*a*' and whose the first appearance of '*a*' is not followed by a '*c*'.


Exercise

Give regular expression for the following finite automata.




Exercise

Give regular expression for the following finite automata.




Exercise

Give regular expression for the following finite automata.



and this one.



Nondeterministic finite automata

Definition

A **nondeterministic finite automata** (**NFA**, *Automat hữu hạn phi đơn định*) is mathematically represented by a 5-tuples $(Q, \Sigma, q_0, \delta, F)$ where

- Q a finite set of states.
- Σ is the alphabet of the automata.
- $q_0 \in Q$ is the initial state.
- $\delta : Q \times \Sigma \rightarrow Q$ is a transition function.
- $F \subseteq Q$ is the set of final/accepting states.

Remark


According to an event, a state may go to one or more states.



NFA with empty symbol ε

Other definition of NFA

Finite automaton with transitions defined by character x (in Σ) or empty character ε .



Exercise

Consider the set of strings on $\{a, b\}$ in which every aa is followed immediately by b .

For example aab , $aaba$, $aabaabbaab$ are in the language, but $aaab$ and $aabaa$ are not.

Construct an accepting NFA.





Let $\Sigma = \{a, b, c\}$

Propose NFA presenting each of the following languages

- ① all strings with exactly one '*a*'.
- ② all strings of even number of appearances of '*b*'.
- ③ all strings which the number of appearances of '*b*' is divisible by 3.

Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

**Non-deterministic
finite automata**

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications



Let $\Sigma = \{a, b, c\}$

Construct an accepting finite automata for languages represented by the following regular expressions.


- $E_1 = a^*c + b^*a,$
- $E_2 = b^*ab + a^*aba^*,$
- $E_3 = aab + cab^*ac,$
- $E_4 = b(ca + ac)(aa)^* + a^*(a + b),$
- $E_5 = (ab)^{2*}c + bac,$
- $E_6 = bb^*ac + b^*a,$
- $E_7 = (b + c)ab + ba(c + ab)^*,$
- $E_8 = (b + c)^*ba + a(c + a)^*,$
- $E_9 = [a(b + c)^* + bc^*]^*,$
- $E_{10} = b^*ac + bb^*a.$

[Contents](#)[Motivation](#)[Alphabets, words and languages](#)[Regular expression or rational expression](#)[Non-deterministic finite automata](#)[Deterministic finite automata](#)[Recognized languages](#)[Determinisation](#)[Minimization](#)[DFAs combination](#)[Some applications](#)

Exercise

Let $\Sigma = \{a, b\}$


Give 3 valid strings & 5 invalid strings in language L^2 , with L represented by the following finite automata.



Exercise

Let $\Sigma = \{a, b\}$

Give 3 valid strings & 5 invalid strings in language L^2 , with L represented by the following finite automata.



[Contents](#)[Motivation](#)[Alphabets, words and languages](#)[Regular expression or rational expression](#)[Non-deterministic finite automata](#)[Deterministic finite automata](#)[Recognized languages](#)[Determinisation](#)[Minimization](#)[DFAs combination](#)[Some applications](#)

Definition

A **deterministic finite automata** (**DFA**, *Automat hữu hạn đơn định*) is given by a 5-tuplet $(Q, \Sigma, q_0, \delta, F)$ with

- Q a finite set of states.
- Σ is the input alphabet of the automata.
- $q_0 \in Q$ is the initial state.
- $\delta : Q \times \Sigma \rightarrow Q$ is a transition function.
- $F \subseteq Q$ is the set of final/accepting states.


Condition

Transition function δ is an **application**.

Example

Let $\Sigma = \{a, b\}$

Hereinafter, a deterministic and complete automata that recognizes the set of strings which contain an odd number of a .



- $Q = \{q_0, q_1\}$,
- $\delta(q_0, a) = q_1, \delta(q_0, b) = q_0, \delta(q_1, a) = q_0, \delta(q_1, b) = q_1$,
- $F = \{q_1\}$.



Configurations and executions

Let $A = (Q, \Sigma, q_0, \delta, F)$

A **configuration** (*cấu hình*) of automata A is a couple (q, u) where $q \in Q$ and $u \in \Sigma^*$.

We define the relation \rightarrow of **derivation** between configurations :
 $(q, a.u) \rightarrow (q', u)$ iff $\delta(q, a) = q'$

An execution (*thực thi*) of automata A is a sequence of configurations

$(q_0, u_0) \dots (q_n, u_n)$ such that
 $(q_i, u_i) \rightarrow (q_{i+1}, u_{i+1})$, for $i = 0, 1, \dots, n - 1$.



Exercise

Let $\Sigma = \{0, 1\}$

- Give a DFA that accepts all words that contain a number of 0 multiple of 3.
- Give an execution of this automata on 1101010.



Exercise

Let $\Sigma = \{0, 1\}$

- Give a DFA that accepts all words that contain a number of 0 multiple of 3.
- Give an execution of this automata on 1101010.

Let $\Sigma = \{a, b\}$

- Give a DFA that accepts all strings containing 2 characters a .
- Give an execution of this automata on $aabb$, $ababb$ and $bbaa$.



Recognized languages

Definition

A language L over an alphabet Σ , defined as a sub-set of Σ^* , is recognized if there exists a finite automata accepting all strings of L .

Proposition

If L_1 and L_2 are two recognized languages, then

- $L_1 \cup L_2$ and $L_1 \cap L_2$ are also recognized;
- $L_1.L_2$ and L_1^* are also recognized.



Example

Sub-string ab

Construct a DFA that recognizes the language over the alphabet $\{a, b\}$ containing the sub-string ab .

Regular expression

$$(a + b)^* ab (a + b)^*$$



Example

Sub-string ab

Construct a DFA that recognizes the language over the alphabet $\{a, b\}$ containing the sub-string ab .


Regular expression

$$(a + b)^* ab(a + b)^*$$

Transition table

	a	b
$\rightarrow q_0$	q_1	q_0
q_1	q_1	q_2
q_2^*	q_2	q_2

Automata



Exercise

Let $\Sigma = \{a, b, c\}$

Propose DFA presenting each of the following languages

- ① all strings which the number of appearances of ' aa ' and the one of ' b ' are the same.
- ② all strings which the number of appearances of ' a ' is equal to the one of ' b ' plus the one of ' c '.
- ③ all strings including at least one ' a ' and whose the first appearance of ' a ' is not followed by a ' c '.
- ④ all strings which the difference between number of appearances of ' a ' and the one of ' c ' is less than 1.
- ⑤ all strings which there is at least ' b ' or ' cb ' after ' a ' or ' aa '.



Example

Let $\Sigma = \{a, b, c\}$


Construct DFAs that recognize the languages represented by the following regular expressions.

- $E_1 = a^* + b^*a$,
- $E_2 = b^* + a^*aba^*$,
- $E_3 = aab + cab^*ac$,
- $E_4 = bb^*ac + b^*a$,
- $E_5 = b^*ac + bb^*a$.



From NFA to DFA

Given a NFA



Transition table

	a	b
0		
1		
2		



From NFA to DFA



Contents

Motivation

Alphabets, words and languages

Regular expression or rational expression

Non-deterministic finite automata

Deterministic finite automata

Recognized languages


Determinisation

Minimization

DFA's combination

Some applications

Given a NFA




Transition table

	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0\}$

From NFA to DFA

Given a NFA




Transition table

	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0\}$
$\{1\}$	$\{0, 2\}$	$\{1\}$



From NFA to DFA

Given a NFA




Transition table

	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0\}$
$\{1\}$	$\{0, 2\}$	$\{1\}$
$\{0, 2\}^*$	$\{1\}$	$\{0\}$



From NFA to DFA


Given a NFA



Transition table


	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0\}$
$\{1\}$	$\{0, 2\}$	$\{1\}$
$\{0, 2\}^*$	$\{1\}$	$\{0\}$

Corresponding DFA



Other example of determinisation

Given a NFA



Transition table


	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0, 1\}$
$\{1\}^*$	$\{0\}$	$\{1\}$
$\{0, 1\}^*$	$\{0, 1\}$	$\{0, 1\}$




Other example of determinisation



Given a NFA



Corresponding DFA




Transition table

	a	b
$\rightarrow \{0\}$	$\{1\}$	$\{0, 1\}$
$\{1\}^*$	$\{0\}$	$\{1\}$
$\{0, 1\}^*$	$\{0, 1\}$	$\{0, 1\}$

Exercise

Let $\Sigma = \{a, b, c\}$

Determine DFAs which corresponds to the following NFAs:



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization


DFAs combination

Some applications

Exercise

Let $\Sigma = \{a, b, c\}$

Determine DFAs which corresponds to the following NFAs:



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization


DFAs combination

Some applications

Exercise

Let $\Sigma = \{a, b, c\}$


Determine DFAs which corresponds to the following NFAs:



Exercise

Let $\Sigma = \{a, b, c\}$

Determine DFAs which corresponds to the following NFAs:





Let $\Sigma = \{a, b, c\}$

Determine finite automata, not necessarily deterministic, recognizing the following languages:

- $L_1 = \{a, ab, ca, cab, acc\}$,
- $L_2 = \{ \text{set of words of even number of } a \}$,
- $L_3 = \{ \text{set of words containing } ab \text{ and ending with } b \}$.

Then, determine the corresponding complete DFAs.

Contents

Motivation

Alphabets, words and languages

Regular expression or rational expression

Non-deterministic finite automata

Deterministic finite automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications



Contents

Motivation

Alphabets, words and
languagesRegular expression or
rational expressionNon-deterministic
finite automataDeterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Let $\Sigma = \{a, b, c\}$

Construct DFAs for languages represented by following expressions.

- $E_1 = a^* + b^*a,$
- $E_2 = b^* + a^*aba^*,$
- $E_3 = (aab + ab^*)^*,$
- $E_4 = b(ca + ac)(aa)^* + a^*(a + b),$
- $E_5 = ba^*b + baa + baba,$
- $E_6 = (ba^*b + baa + baaba)^*,$
- $E_7 = ba^*b + baa + aba(a + b)^*,$
- $E_9 = [a(b + c)^* + bc^*]^*,$
- $E_{10} = bb^*ac + ba^*b.$
- $E_{11} = bb^*ac + b^*a,$
- $E_{12} = (b + c)ab + ba(c + ab)^*,$
- $E_{13} = (b + c)^*ba + a(c + a)^*,$

Example


Determine a DFA that recognizes the language over the alphabet $\{a, b\}$ with an even number of a and an even number b .



Example

Determine a DFA that recognizes the language over the alphabet $\{a, b\}$ with an even number of a and an even number b .


Automata



Example

Determine a DFA that recognizes the language over the alphabet $\{a, b\}$ with an even number of a and an even number b .

Automata



Transition table


	a	b
$\rightarrow q_0^*$	q_2	q_1
q_1	q_3	q_0
q_2	q_0	q_3
q_3	q_1	q_2

\rightarrow : start state

$*$: final state(s)



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$						



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	1		1		1	1



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$						
$cl(s.b)$						



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II					
$cl(s.b)$	II					



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I				
$cl(s.b)$	II	I				



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I			
$cl(s.b)$	II	I	I			



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I		
$cl(s.b)$	II	I	I	I		



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	
$cl(s.b)$	II	I	I	I	I	



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I

0	1	2	3	4	5
I	II		II		



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I

0	1	2	3	4	5
I	II	III	II		



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I

0	1	2	3	4	5
I	II	III	II	IV	



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I

0	1	2	3	4	5
I	II	III	II	IV	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I
$cl(s.a)$	II	I	I	I	II	I
$cl(s.b)$	II	I	I	I	I	I

	0	1	2	3	4	5
	I	II	III	II	IV	III
	II	IV	III	IV	II	III
	II	III	III	I	III	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I	I	II	III	II	IV	III
$cl(s.a)$	II	I	I	I	II	I	II	IV	III	IV	II	III
$cl(s.b)$	II	I	I	I	I	I	II	III	III	I	III	III

s	0	1	2	3	4	5
$cl(s)$	I	II	III		IV	III
$cl(s.a)$	II	IV	III		II	III
$cl(s.b)$		III	III		III	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I	I	II	III	II	IV	III
$cl(s.a)$	II	I	I	I	II	I	II	IV	III	IV	II	III
$cl(s.b)$	II	I	I	I	I	I	II	III	III	I	III	III

s	0	1	2	3	4	5
$cl(s)$	I	II	III	V	IV	III
$cl(s.a)$	II	IV	III		II	III
$cl(s.b)$		III	III		III	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I	I	II	III	II	IV	III
$cl(s.a)$	II	I	I	I	II	I	II	IV	III	IV	II	III
$cl(s.b)$	II	I	I	I	I	I	II	III	III	I	III	III

s	0	1	2	3	4	5
$cl(s)$	I	II	III	V	IV	III
$cl(s.a)$	II	IV	III		II	III
$cl(s.b)$	V	III	III		III	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5	0	1	2	3	4	5
$cl(s)$	I	II	I	II	I	I	I	II	III	II	IV	III
$cl(s.a)$	II	I	I	I	II	I	II	IV	III	IV	II	III
$cl(s.b)$	II	I	I	I	I	I	II	III	III	I	III	III

s	0	1	2	3	4	5
$cl(s)$	I	II	III	V	IV	III
$cl(s.a)$	II	IV	III	IV	II	III
$cl(s.b)$	V	III	III	I	III	III



From a DFA to a smaller DFA




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	II	III	V	IV	III
$cl(s.a)$	II	IV	III	IV	II	III
$cl(s.b)$	V	III	III	I	III	III



Another example of minimization




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	I	II	I	I	I
$cl(s.a)$	I	I	I	I	I	I
$cl(s.b)$	I	II	II	I	I	II



Another example of minimization




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	I	II	I	I	I
$cl(s.a)$	I	I	I	I	I	I
$cl(s.b)$	I	II	II	I	I	II


	0	1	2	3	4	5
	I	III	II	I	I	III
	III	I	I	III	I	I
	I	II	II	I	I	II



Another example of minimization



Another example of minimization




equivalence relationships

s	0	1	2	3	4	5
$cl(s)$	I	III	II	I	I	III
$cl(s.a)$	III	I	I	III	I	I
$cl(s.b)$	I	II	II	I	I	II



Another example of minimization




equivalence relationships

s	0	1	2	3	4	5	0	1	2	3	4	5
$cl(s)$	I	III	II	I	I	III	I	III	II	I	IV	III
$cl(s.a)$	III	I	I	III	I	I	III	IV	I	III	IV	IV
$cl(s.b)$	I	II	II	I	I	II	IV	II	II	IV	I	II



Another example of minimization



equivalence relationships


s	0	1	2	3	4	5
$cl(s)$	I	III	II	I	IV	III
$cl(s.a)$	III	IV	I	III	IV	IV
$cl(s.b)$	IV	II	II	IV	I	II




Exercise

Let $\Sigma = \{a, b\}$

Determine minimal DFA which corresponds to the following DFA:



Exercise



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages


Determinisation

Minimization

DFAs combination

Some applications

Exercise



Hint

Two-steps approach: (NFA \rightarrow DFA); min (DFA).



Exercise

$$\sigma = \{a, b\}$$

Determine minimal DFA recognized the languages represented by the following regular expressions:

$$\textcircled{1} E_1 = (a + b)^* b (a + b)^*$$



Exercise

$$\sigma = \{a, b\}$$

Determine minimal DFA recognized the languages represented by the following regular expressions:

$$\textcircled{1} E_1 = (a + b)^* b (a + b)^*$$

$$\textcircled{2} E_2 = ((a + b)^2)^* + ((a + b)^3)^*$$



Exercise

$$\sigma = \{a, b\}$$

Determine minimal DFA recognized the languages represented by the following regular expressions:

$$\textcircled{1} E_1 = (a + b)^* b (a + b)^*$$

$$\textcircled{2} E_2 = ((a + b)^2)^* + ((a + b)^3)^*$$

$$\textcircled{3} E_3 = ((a + b)^2)^+ + ((a + b)^3)^+$$



Exercise

$$\sigma = \{a, b\}$$

Determine minimal DFA recognized the languages represented by the following regular expressions:

- ① $E_1 = (a + b)^* b (a + b)^*$
- ② $E_2 = ((a + b)^2)^* + ((a + b)^3)^*$
- ③ $E_3 = ((a + b)^2)^+ + ((a + b)^3)^+$
- ④ $E_4 = baa^* + ab + (a + b)ab^*$.



Exercise

$$\sigma = \{a, b, c, d\}$$

Determine minimal complete DFA recognized the languages consisting of all strings where all 'a' is followed by a 'b' and all 'c' is followed by a 'b'.

Then, deduce the corresponding regular expressions.



Exercise

$$\sigma = \{a, b, c, d\}$$

Determine minimal complete DFA recognized the languages consisting of all strings where all 'a' is followed by a 'b' and all 'c' is followed by a 'b'.

Then, deduce the corresponding regular expressions.

$$\sigma = \{a, b\}$$

Give a NFA (as simple as possible) for the language defined by the regular expression $ab^* + a(ba)^*$. Then determine the equivalent DFA.



Exercise

Let $\Sigma = \{a, b, c\}$



Determine minimal DFA recognized the languages represented by the following regular expressions:

- ① $a^* + b^*$,
- ② $a^*b + b^*a$,
- ③ $b(ca + ac)(aa)^* + a^*(a + b)$,
- ④ $(a^*b + b^*a)^*$.
- ⑤ $a^*bc + bca^*$,
- ⑥ $b(c + c)(aa)^* + (a + c)a^*$,
- ⑦ $aab + cab^*ac$,
- ⑧ $b(ca + ac)(a)^* + a(a + b)^*$,
- ⑨ $ab(b + c)ab + ba(c + b)^* + (b + c)ab(b + c)$.





Equivalent automata

Two following automatas are equivalent?



Equivalent automata

Two following DFAs are equivalent?



Combination of two automata

$$\Sigma = \{a, b\}$$

- a) Given two languages L_a, L_b defined by regular expressions
 $E_a = a(a + b)^*$ and $E_b = a^*(ba)^*$
- b) Give a DFA for the language L_a, L_b .
- c) Then, determine a (minimized) DFA for the following languages.
 - ① $L_1 = L_a \circ L_b$
 - ② $L_2 = L_a \cap L_b$
 - ③ $L_3 = L_a \cup L_b$
 - ④ $L_4 = L_a \setminus L_b$



Combination of two automata

$$\Sigma = \{a, b\}$$

- a) Given two languages L_a, L_b defined by regular expressions $E_a = (a^*b + b^*a)^+$ and $E_b = (a + b)^*b(a + b)^*a$
- b) Give a DFA for the language L_a, L_b .
- c) Then, determine a (minimized) DFA for the following languages.

- ① $L_1 = L_a \circ L_b$
- ② $L_2 = L_a \cap L_b$
- ③ $L_3 = L_a \cup L_b$
- ④ $L_4 = L_a \setminus L_b$



Combination of two automata



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

$$\Sigma = \{a, b\}$$

- a) Given two languages L_a, L_b defined by regular expressions
 $E_a = ab^* + a(ba)^*$ and $E_b = baa^* + ab + (a + b)ab^*$
- b) Give a DFA for the language L_a, L_b .
- c) Then, determine a (minimized) DFA for the following languages.

① $L_1 = L_a \circ L_b$

② $L_2 = L_a \cap L_b$

③ $L_3 = L_a \cup L_b$

④ $L_4 = L_a \setminus L_b$

Odd Parity Detector

Describe DFA for Odd Parity Detector

Automata

TVHoai, HTNguyen,
NAKhuong, LHTrang



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

TCP/IP protocol

Describe DFA for a demonstration of TCP/IP protocol

Automata

TVHoi, HTNguyen,
NAKhuong, LHTrang



Contents

Motivation

Alphabets, words and
languages

Regular expression or
rational expression

Non-deterministic
finite automata

Deterministic finite
automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications

Propose an automata to describe a vehicular multi-information display system with a given number of buttons.

For example, digital speedo meter of Honda Lead motor with only one button can display information about: petroleum level, speed, trip, date, time, engine oil life.

(Hint: we distinguish two different actions: quickly press the button; press the button and hold-down over two seconds.)



Contents

Motivation

Alphabets, words and languages

Regular expression or rational expression

Non-deterministic finite automata

Deterministic finite automata

Recognized languages

Determinisation

Minimization

DFAs combination

Some applications