

learning spike

Core JavaScript

Ryan Morris
@mrmorris



Introductions



- ◎ About me...
- ◎ About you...
 - ◎ What do you do?
 - ◎ What is your programming background?
 - ◎ Any front-end?
 - ◎ 😍, 😡 or 😭 JavaScript?
 - ◎ What do you hope to gain from this course?
- ◎ What is your current development environment and process?

How the class works




- ⦿ Mixture of labs and lecture
- ⦿ Informal
 - ⦿ Stop me anytime
 - ⦿ Discussion > Lecture
 - ⦿ Outline is flexible
 - ⦿ **There is too much to cover** so we'll adjust as needed
- ⦿ You'll help define areas of focus
- ⦿ Class assessment towards the end of the day

Get the most out of the class



- ◎ Ask **questions!**
- ◎ Do the **labs** (pair up if needed)
- ◎ Be **punctual**
- ◎ **Avoid distractions**
- ◎ Master your **google-fu**
- ◎ **Play along** in the console
- ◎ Don't be afraid to **break stuff**

What we'll cover



- ☉ Data types & variables
- ☉ Object basics
- ☉ Arrays
- ☉ Control Flow
- ☉ Functions
- ☉ Hoisting
- ☉ Lexical vs Dynamic Scope
- ☉ Closures

I wasn't planning to cover


- * Objects in depth
- * OO, new keyword
- * ES6 in depth
- * Modules

~Mostly ES5~

~Mostly for beginners~

~let's shape it~

Resources



🕒 Reading List

- 🕒 <https://javascript.info/intro>

🕒 Documentation

- 🕒 <http://devdocs.io>

- 🕒 <https://developer.mozilla.org/en-US/docs/Web>

- 🕒 <http://kapeli.com/dash> (Mac only)

- 🕒 Google it.

🕒 Compatibility checks

- 🕒 <http://caniuse.com>

Lab prep - set up our toolkit



- 🕒 A browser with dev tools

- 🕒 Preference for Chrome in class

- 🕒 Open your browser and hit F12 or alt/opt/⌘ - ⌘-i

- 🕒 Our web editor, jsfiddle

- 🕒 Does this work?

- 🕒 <http://jsfiddle.net/mrmorris/8wfu5tct/>

- 🕒 Please Sign Up

- 🕒 <http://jsfiddle.net/>



Everyone OK with the above?

Fiddle Notes



- It's a sandbox
- Set of iframe
 - Want to work in the console? Check which frame you're accessing
- It runs js in an IIFE unless you ask it not to
 - So your stuff isn't global...
- When you grab a lab...
 - Fork it (copy) — you'll own that!
 - Hit “update” to save!
 - Hit “run” to test!
 - Hit “set as base” to make that version the main version

PDF for today



- In case you didn't quite catch something, or can't see the screen well:
 - Head to my repository
 - ###
 - Go to “/docs” folder
 - Or just download the whole repo...



module


JAVASCRIPT INTRO

History




- “Make webpages alive”
- 1995 - Netscape wanted interactivity like HyperCard w/ Java in the name
- Designed & built in 10 days by Brendan Eich as "Mocha", released as “LiveScript”
 - Became “JavaScript” once name could be licensed from Sun
- Combines influences from:
 - Java, "Because people like it"
 - SmallTalk, prototypal

What is JavaScript?



- Standardized as **ECMAScript**
- Interpreted**
- Case-sensitive C-style syntax
- Dynamically typed (with weak typing)
- Fully **dynamic**
- Single-threaded** event loop
- Unicode (UTF-16, to be exact)
- Prototype**-based (vs. class-based)
- Safe (no CPU or memory access)
- Depends on the engine + environment running it
- Kind of weird but enjoyable

JavaScript Versions



- ◎ ES3/1.5
 - ◎ Released in 1999 – in all browsers by 2011
 - ◎ IE6-8
- ◎ **ES5/1.8**
 - ◎ Released in 2009
 - ◎ IE9+
 - ◎ <http://kangax.github.io/compat-table/es5/>
- ◎ **ES6 [EcmaScript 2015] mostly supported**
- ◎ ES7 [EcmaScript 2016] finalized, but weak support
- ◎ ES8 [EcmaScript 2017] finalized in June 2017
- ◎ ES.Next...

Why JavaScript?

- Despite the shortcomings, it's pretty awesome
 - Very expressive
 - Very flexible (that multi-paradigm thing)
 - Lightweight
- The language of the web
 - Integrates nicely w/ HTML/CSS
 - Supported across all browsers
 - Simple to use
 - A server and command line services
- Beginning to dominate the entire software stack
- Easy to learn, hard to master*

Approaching JavaScript



- ⦿ It's *not* Java
- ⦿ It's *not* class-based
- ⦿ Very dynamic
- ⦿ Supports imperative, functional and object-oriented approaches

Where does JavaScript live?





- ◎ Plain text files, not compiled
 - ◎ *Though this is changing*
- ◎ Browser (Built-in Engine)
 - ◎ Inline `<script>` blocks
 - ◎ Linked `<script src="file.js">` files
- ◎ Server (Node)
 - ◎ One script file
 - ◎ Set of modules

Languages on JavaScript





- ⦿ JS doesn't always meet everyone's needs
- ⦿ Transpile (compile) down to plain JavaScript
 - ⦿ CoffeeScript - syntax sugar
 - ⦿ TypeScript - strict data typing
 - ⦿ Dart - non-browser environments
 - ⦿ ClosureCompiler
 - ⦿ and more!



module

WARM UP

Pop quiz!






How well does everyone know programming constructs

- if-else
- for loops
- functions

Core JS concepts?

- Coercion
- Hoisting
- Scope
- Context
- Functions
- Prototype



obligatory

HELLO WORLD

Say hello





- 🕒 In a browser, open the developer console and type:

```
alert('Hello World!');
```

- 🕒 Alternatively...

- 🕒 In a `<script>`
- 🕒 or... in a file linked from an HTML page
- 🕒 or... run by NodeJS

Log hello






Now try

```
console.log('Hello Engineers!');
```

Browser Console



- 🕒 Use browser dev tools to access its JavaScript console
 - 🕒 The browser's "console" is a REPL
- 🕒 All major browsers are converging to the same API for console debugging
- 🕒 Can use it to set breakpoints
 - 🕒 Let you see scoped variables and context
 - 🕒 Can set a conditional break-point
- 🕒 This is where we'll be working; follow along!
 - 🕒 `console.log()` => `echo`



module

SYNTAX BASICS

Syntax Examples



⦿ <http://jsfiddle.net/mrmorris/23zK2/>

C-family syntax



- Instructions are **statements** separated by **semicolon**

```
var x = 5; var y = 7;
```

- Spaces, tabs and newlines are **whitespace**.
- White space and indentation generally doesn't matter
- Blocks** are wrapped with curly braces { }

```
var x = 5;  
if (x) {  
    x++;  
}
```

```
{  
    x = 5;  
    y = 7;  
}
```

Automatic Semicolon Insertion



- ☉ Semicolons terminate statements

- ☉ `var x = 1 + 2;`

- ☉ They are *mostly* optional


- ☉ Automatically inserted but not fail-safe

- ☉ So, don't rely on it...

```
var fn = function() {  
    // do stuff  
}  
  
(function() {  
    // do stuff  
})();
```

<= results in TypeError

Comments



- Follow C/C++ conventions


- Multiline

```
/*  
span multiple  
lines  
*/
```

- Single line

```
// I can comment one line at a time  
var x = 1; // wherever  
// var x = 5; ← commented out
```

Declaring variables



- With the keyword **var**

- One by one:

```
var foo = 'bar';
```

```
var thing1 = 2;
```

- Or in sequence:

```
var a = 1, b = 2;
```

- Omitting the **var** keyword creates a *global* variable

```
stuff = [1,2,3];
```

- Default value will be `undefined`

```
var another; //
```

```
console.log(another); // "undefined"
```

Declaring variables [ES6]



let & const

- block scoped
- can't redeclare
- let is mutable while const is immutable*

```
let x = 0;  
let y = {};
```

```
x = 5; // ok!  
let x = 5; // TypeError
```

```
const z = 5;  
const u; // SyntaxError  
z = 10; // ReferenceError
```

Variable names

- Only two limitations
 - Contains letters, digits, _, or \$
 - Can't begin with a digit
 - No reserved keywords
- CaSE matters
- Unicode characters are supported

```
var 🍔 = 'burger';
```

Variable scope



- 🕒 JavaScript is **function-scoped**
 - 🕒 **var** is used to define variable in current function's scope
 - 🕒 variable is said to be “local” to a function when defined within it
- 🕒 ... supports **block-scoped** in [ES6]+
 - 🕒 **let, const**

```
if (expression) {  
    let x=1; // scoped to this block only  
}  
console.log(x); // Temporal Dead Zone error
```


Data Types



Five *primitive* data types:

- strings
- numbers
- booleans
- null - lack of value
- undefined – no value set, the default in JavaScript
- ES6: Additional primitive, Symbol*

And then Objects

- Property names referencing values
- ie: Object, Array, Function, Math...
- Function is a callable object
- ES6: Adds the Symbol to create identifiers



undefined & null



- Little difference between the two, in practice
- Variables declared without a value will start with `undefined`
- Can compare to `undefined` to see if a variable has a value

```
● var a;  
  a === undefined;      // true  
  typeof a;              // undefined
```

boolean




 **true or false**



number issues



- All numbers are stored internally as 64bit floating points



- Integers are accurate up to 15 digits

```
var y = 9999999999999999; // 10000000000000000
```



- Decimals are accurate up to 17 digits

```
var x = 0.2 + 0.1; // 0.30000000000000004
```

- What to do?

- Round, use only integers

- Use libs like **BigDecimal** or **Big.js**



- Enclosed by " or ' (just don't mix them)

```
var str = "My String";
```



- Escape with backslash (\)

- \n is newline, \t is tab, etc

- Works in both single- and double-quoted strings, but you shouldn't mix quote types

- + operator for concatenation

```
stringVar + " " + anotherStringVar +  
" !";
```



- ⦿ A list of **key:value** pairs, surrounded by **curly braces**
 - ⦿ Considered a *Dictionary*, *Hash* or *Map* in other languages
- ⦿ Keys:
 - ⦿ Unordered
 - ⦿ Must be strings
 - ⦿ Don't require quotations unless if they contain special characters
- ⦿ Values:
 - ⦿ can be any type of data, including functions

```
var obj = {bar: "baz"};
```

```
obj.foo = true; // assign values  
obj.bar;      // dot-accessor  
obj['foo']    // array-accessor
```

[arrays]



- 🕒 Data stored *sequentially* with an index
- 🕒 In JavaScript, the **array is an object** that behaves kinda like an array (*array-like*)

```
var emptyArray = [];  
var myArray = [1,2,3,4];  
myArray[1]; // 2  
myArray[1] = 20;
```

- 🕒 Strange behavior if you try to use string keys

```
var arr = [1,2,3];  
arr.length; // 3  
arr['bar'] = 10;  
arr.length; // 3
```


Getting the type of a variable



🕒 **typeof** returns the type of the argument

```
typeof undefined; // "undefined"
typeof 0;          // "number"
typeof "foo";      // "string"
typeof true;       // "boolean"
typeof null;       // "object" ???
typeof {};         // "object"

typeof(0);         // also ok
```

Exercise – Data Types



- Experiment directly in your console

- Quick review of jsfiddle...

- Super Basic Data**

With built-in tests

- Fork this:

- <https://jsfiddle.net/mrmorris/gzpo0z0L/>

Solutions:

Super Basic Data: <https://jsfiddle.net/mrmorris/5gdv03r0/>

typeof and NaN

◉ Wha?

◉ `typeof NaN; // "number" <- huh?`

◉ `NaN === NaN; // false <- bummer...`

◉ `isNaN()`; is NaN... not “is not a number”

◉ *coerces via `Number()` constructor*

◉ `isNaN(NaN); // true`

◉ `isNaN(""); // false`

◉ `isNaN(5); // false`

◉ `isNaN('123ABC'); // true`

◉ `isNaN({}); // true`

◉ `Number.isNaN()`

◉ does not coerce

Type Coercion



- ☉ If a variable type is not what JavaScript expects, it will convert it on the fly, based upon the context
- ☉ In expressions involving numeric and string values with the `+` operator, JavaScript converts numeric values to strings

```
+ "42"; // 42
```

```
"Name: " + 42; // "Name: 42"
```

```
1 + "3"; // 4;
```

Implicit Coercion



⦿ It's not obvious how it will coerce...

⦿ `8 * null -> 0`

`"5" - 1 -> 4`

`"5" + 1 -> 51`

⦿ Much confusion ensues

⦿ `[] + [] -> empty string`

⦿ `[] + {} -> [object Object]`

⦿ `{ } + [] -> 0`

⦿ `{ } + { } -> NaN`

Sometimes coercion is cool



⦿ For your bag of tricks:

⦿ `(+x) ;`

⦿ Convert string to a number

⦿ `!!myVar ;`

⦿ Double bang can convert any value to a boolean

Exercise - typeof an Array?



What is the output of:

```
var myArray = [1,2,3];  
typeof myArray; // ?
```

array methods



- ☉ Arrays are objects...
- ☉ ... and have additional properties and methods

```
myArray.length; // 4  
myArray.push('John'); // adds value to end  
myArray.pop(); // John
```

- ☉ In fact, everything can act like an object...

```
var name= "John Smith";  
name.length; // 10  
"foo".toUpperCase(); // "FOO"  
5..toString(); // 5 ? wait, what?
```


typeof objects



🕒 **typeof** with any* object is “**object**”

```
typeof {};           // “object”  
typeof [1,2,3];      // “object”  
typeof Math;         // “object”
```

🕒 *except **Functions**

```
typeof alert;        // “function”
```

Everything* is an object



- ⦿ *most things, primitives are just coerced
- ⦿ Primitive literals all have Object counterparts
 - ⦿ except null and undefined

```
5 === Number("5");  
"Hello" === String("Hello");  
true === Boolean(1);
```

- ⦿ Temporarily coerced to object when used as object
- ⦿ So... we can access properties and invoke methods of objects, including primitives
 - ⦿ `str.length;`
 - ⦿ `str.toUpperCase();`
 - ⦿ `"Hello".length;`

Literals



- Fixed values, not variables, that you *literally* provide in your script

5 // number literal

"a" // string literal

true // boolean literal

{} // object literal

[] // array literal

/^(.*)\$/ // regexp literal

Literals by Construction



- Literals constructed by their object counterpart

```
new String("Hi"); // {0: "H", 1: "I"}
String("Hi"); // "Hi"
new Number(5); // 5
new Array(1,2,3); // [1,2,3]
new Boolean(1); // true
new Object(); // {}
```

Recap: basic data types



- There are **5 primitive types** (string, number, boolean, null, undefined) and then **Objects**
 - Functions** are a callable Object
 - Objects** are property names referencing data
 - Arrays** are for sequential data
- Declare variables with “var”
- Types are **coerced**
 - Including when a primitive is used like an object
- Almost Everything* is an object, except the primitives
 - despite them having object counterparts

Exercise - Variables Round 2



Working with variables




Experiment with setting variables and manipulating their data. Wow!

Fork this:

<http://jsfiddle.net/mrmorris/e5g7ub2n/>

Solutions:

Working with Variables: <http://jsfiddle.net/mrmorris/bayoa6ao/>



module



OPERATORS

Unary



```
delete obj.x    // undefined
void 5 + 5      // undefined
typeof 5        // 'number'
+'5'            // 5
-x              // -5
~9              // -10 (bitwise flip bit)
!true           // false
++x             // 6
x++            // 5
--x            // 4
x--            // 5
```


Arithmetic



5 + 5 // 10

5 - 3 // 2

5 * 2 // 10

10 / 2 // 5

10 % 3 // 1

Bitwise



5 & 4 // 1

1 | 4 // 5

4 ^ 6 // 2

9 << 2 // 36

-9 >> 2 // -3

9 >>> 2 // 2

Assignment



x = 5 // 5

x += 1 // 6

x -= 2 // 4


x *= 3 // 12

x /= 4 // 3

x %= 2 // 1

// &=, |=, ^=, <<=, >>=, >>>=

Relational




```
'foo' in {foo: 'bar'} // true  
[] instanceof Array   // true  
5 < 4                 // false  
5 > 4                 // true  
4 <= 4                // true  
5 >= 10               // false
```

Equality* (strict vs loose)



```
5 == '5'           // true
5 != 'a'           // true
5 === '5'          // false
{} !== {}          // true
```

Logical



```
false && 'foo' // false
```

```
false || 'foo' // 'foo'
```

Ternary



```
// condition ? then : else;
```

```
true ? 'foo' : 'bar' // 'foo'
```

Falsy / Truthy



- Really just *coercion*

- These coerce to **false**

- false

- null

- undefined

- " "

- 0

- NaN

- Everything else coerces to **true**, including...


- { }

- []

- "0"

- "false"

Logical short circuits



🕒 **a && b** returns either a or b

```
if (a) {  
    return b;  
} else {  
    return a;  
}
```

🕒 **a || b** returns either a otherwise b

```
if (a) {  
    return a;  
} else {  
    return b;  
}
```

Where short-circuits help



🕒 Default function values

```
function name(x) {  
    // set default value of x if undefined  
    x = x || null;  
}
```

🕒 Gateways

```
return obj.name  
    && obj.id  
    && obj.doSomething();
```

Exercise - Truthing and Faling



Two things to ponder:

Is the expression **truthy or falsy**

and what is the **actual result** of the expression

1.null

2.true

3.true && 5 && 10

4.1 && false && 2

5.false || 2

6.x = 2

7.10 >= 5

8.1 || 2 || 3

9.[]

1.false

2.truthy

3.truthy

4.falsy




5.truth

6.truthy

7.truthy

8.truthy

9.truthy



module

CONTROL STRUCTURES

Conditionals & Loops

Control Structure Examples



© <http://jsfiddle.net/mrmorris/GN7qL/>

Conditional statements



① `if (expression) {...}`

② `if (expression) {`

`...`


`} else {`

`...`

`}`


③ `if {} else if {} else {}`

Switch statements



```
switch (expression) {  
    case val1:  
        // statements  
        break;  
  
    default:  
        // statements  
        break;  
}
```

Basic Loops



⦿ for


⦿ while

⦿ do...while

looping - for

```
for (var i=0; i<10; i++) {  
    // executes 10 times..  
}
```


looping - while



```
var i = 0;
```

```
while (i < 10) {  
    // do stuff 10 times  
    i++;  
}
```

looping - do/while



```
var i = 0;
```


```
do {
```

```
    // do stuff 10 times
```

```
    i++;
```

```
} while (i < 10);
```

Break and Continue



```
for (var i = 0; i < 10; i++) {  
    if (i < 5) {  
        continue; // skip to next  
    } else if (i === 8) {  
        break;    // exit loop  
    }  
    console.log(i);  
}
```

looping through an array



```
var cats = [1,2,3];
```

```
for (var i=0; i < cats.length; i++) {  
    console.log(cats[i]);  
}
```

```
// in ES6
```

```
cats.forEach(function(el, i, arr){  
    console.log(el);  
});
```

Enumerating over objects



- ① `for...in`


- ① Over object properties

- ① `for...of` (ES6)

- ① Over any Iterable

- ① ~~`for each...in`~~

- ① deprecated, looping over object properties



🕒 Loop over ***enumerable properties*** of an object

🕒 Will include inherited properties as well, including stuff you probably don't want

🕒 Use `obj.hasOwnProperty(propertyName)`

🕒 In order of insertion of the property

```
var obj = {foo: true, bar: false};
```

```
for (var prop in obj) {  
  if (obj.hasOwnProperty(prop)) {  
    console.log(prop);  
  }  
  obj[prop];    // true  
} // outputs: foo, bar
```

for...of [ES6]



Loop over ***enumerable values*** of an **iterable**

- Will include inherited properties as well, including stuff you probably don't want
- Not just objects** — *iterables* (including arrays)

```
var obj = {foo: true, bar: false};
```

```
for (let val of iterableThing) {  
  console.log(val);  
} // true, false
```

```
for (let x of [1,2,3]) {  
  console.log(x);  
} // 1, 2, 3
```


Control Structures Recap



- ◎ Conditionals like **if** and **if-else**
- ◎ **Switch** statements
- ◎ Iterate (loop) with **while** and **for**
- ◎ Enumerate over an object with **for..in**

Exercise – Control flow



Control Flow 1

Get to know control flow and iteration statements

- ☉ We'll use some basic browser functions

- ☉ `alert("A message!");`

- ☉ `var response = prompt("Ask for a value!");`

- ☉ `confirm("Ask user to say 'ok'");`

- ☉ Fork me: <http://jsfiddle.net/mrmorris/cxz2hta1/>

Control Flow 2




Control flow trials with built-in tests

- ☉ Fork me <https://jsfiddle.net/mrmorris/cvkgnuq3/>

Solutions:

Control Flow 1: <http://jsfiddle.net/mrmorris/1yb31dt6/>

Control Flow 2: <https://jsfiddle.net/mrmorris/nr1pwtcq/>



module


FUNCTION BASICS

Functions: "The best part of JS"



- ◎ Reusable, callable blocks of code
- ◎ Functions can be used as:
 - ◎ Object methods
 - ◎ Object constructors
 - ◎ Modules and namespaces
- ◎ They *are* **First Class Objects**
 - ◎ *Can have their own properties and methods*
 - ◎ *Can be passed as function arguments (higher order!)*
 - ◎ *Can be referenced by variables*
- ◎ **Callable objects**

Defining a function



Four ways

- Function **declaration**

- Function **expression**

- `Function()` **constructor**

- [ES6] **Fat arrow**

A bunch of examples:

- <http://jsfiddle.net/mrmorris/N8vcg/>

Function Declaration



```
// declaration  
function adder(a, b) {  
    return a + b;  
}
```

```
// invokation  
adder(1, 2); // 3
```

- 🕒 The function name is *mandatory*
- 🕒 Function declarations are ***hoisted*** to the top of the scope; available for entire scope

Function Expressions



```
// function expression
```

```
var adder = function(a, b) {  
    return a + b;  
}
```

- 🕒 Define a function and assigns it to a variable
- 🕒 Function name is optional — *making it anonymous*


Anonymous and named



```
// anonymous function  
var funcRef = function() {};
```

```
// named anonymous function  
var recursiveFunc = function me(a) {  
    // *name is scoped to inner function  
    me(a++);  
}
```


Anonymous functions



⦿ Pros

- ⦿ Functions can be passed as arguments
- ⦿ Defined inline
- ⦿ Supports dynamic function definition
- ⦿ Can be named, which is scoped to function

⦿ But...

- ⦿ difficult to test in isolation
- ⦿ Discourages code re-use
- ⦿ Hard to debug (unless you *name* it)
- ⦿ Aren't hoisted

Invokation




- 🕒 *Run* (invoke) the function with ()

- 🕒 `myFunctionName(argument1, argument2);`

- 🕒 Missing arguments are set as `undefined`

Default Values [ES6]



ES6

```
function adder(first, second = 1) {  
    // body  
}
```

```
function addComm(text, comment = getComment()) {  
    // body  
}
```

Pre-ES6

```
function adder(first, second) {  
    second = second || 1;  
}
```

Return statements



- Functions do not automatically return anything, i.e. they are *void**
- To return the result of the function invocation, to the invoker (caller) of the function:

return <expression>;

- Careful with your line breaks...

```
return
    x;
// Becomes
return;
x;
```

Function arguments



- ⦿ Functions have access to a special internal when invoked, **arguments**
 - ⦿ contains all parameters passed to the function
 - ⦿ an *array-like* object
 - ⦿ needs to be converted to an array to get all the array-methods

Function arguments



```
function doSomething() {  
  // call an array method with  
  // with arguments as the function context  
  var args = Array.prototype.slice.call(arguments);  
  
  // or in ES6  
  var args = Array.from(arguments);  
  
  console.log(args);  
}  
  
doSomething(1, 2, 3); // ?
```



Functions as First Class Objects



```
// function passed in to another function
setTimeout(function() {
  console.log('HI!');
}, 1000);
```

```
// check the docs; we define argument names
[1,2,3].forEach(function(curr, i, arr) {
  console.log(curr, i, arr);
});
```

- Functions can be passed around as arguments
- We can define argument names when we define per an api/ interface



🕒 Anyone have an idea what **this** is?

```
function runMe() {  
    console.log(this);  
}
```

```
runMe(); // ?
```


this is context



- Available on invocation
- Refers to the context of the function at call-time
 - Dynamically bound (not lexical)
 - “The object in context that invoked the method”*
- Basis of
 - Inheritance
 - Multi-purpose functions
 - Method awareness of their objects
- We’ll come back to **this***

this example



```
var person = {  
  name: "John Doe",  
  speak: function() {  
    console.log("Hi my name is", this.name);  
  }  
}
```

```
person.speak(); // ?  
var speak = person.speak;  
speak(); // ?
```

```
// and if we put it on another object?  
var otherPerson = {name: "Jim"}  
otherPerson.speak = person.speak;  
otherPerson.speak(); // ?
```

Global functions



- ⦿ **alert(msg);**
- ⦿ **confirm(msg)**
- ⦿ **prompt(msg, msg);**
- ⦿ **isFinite()**
- ⦿ ~~isNaN()~~ // use **Number.isNaN()** [ES6]
- ⦿ **parseInt()**
- ⦿ **parseFloat()**
- ⦿ **encodeURIComponent(), decodeURI()**
- ⦿ **setInterval, clearInterval**
- ⦿ **setTimeout, clearTimeout**
- ⦿ **eval();** // dangerous



⦿ Establish delay for function invocation

⦿ `setTimeout(func, delayInMs[, arg1, argn])`

⦿ `var timer = setTimeout(func, 500);`

⦿ Use `clearTimeout(timer)` to cancel

⦿ Establish an interval for periodic invocation

⦿ `setInterval(func, ms)`

⦿ `clearInterval(timer)`

⦿ Context will always be global for the callbacks

⦿ <http://jsfiddle.net/mrmorris/s5g2moc6/>

Exercise – Functional FizzBuzz



🕒 FizzBuzz Function

Create a function that:




- 🕒 Accepts a single number argument
- 🕒 Returns the proper FizzBuzz result for that number
- 🕒 Loop through numbers 1-100 to test your results
- 🕒 BONUS: Write tests!

🕒 The rules of FizzBuzz

- 🕒 For numbers that are a multiple of 3, log "Fizz"
 - 🕒 For numbers that are a multiple of 5, log "Buzz"
 - 🕒 For numbers that are a multiple of both, log "FizzBuzz"
- 🕒 Fork me: <http://jsfiddle.net/mrmorris/raosjdmq/>



Solutions:

FizzBuzz Function <http://jsfiddle.net/mrmorris/3gxvkmou/>



module

SCOPE & HOISTING



- Variable **access** and **visibility** in a piece of code at a given time
 - `var` declares a variable within the current scope
- Lexical scoping** (static)
 - as opposed to *dynamic*
 - Scope is defined at author-time
 - No need to execute; you can read code and determine scope
- Function scope**
 - Functions are the only thing that can create a new scope
 - A variable declared (with `var`) in a function is visible only in that function and its inner functions. But not the other way around.
- ES6 supports **block scope**, *we'll come back to that*

Function Scope



What are the scopes here?

```
var a = 5;
function foo(b) {
  var c = 10;
  d = 15; // no var! globally scoped

  function bar(e) {
    var c = 2; // does not reference c
    a = 12; // will reference a
  }
}
```

- Each *inner* function has access to the *outer* scopes
 - outer function scope cannot access the inners
- ReferenceError** indicates unknown variable in scope

Block scope



🕒 I lied...

- 🕒 `eval()` can cheat scoping, inserting itself into the scope
 - 🕒 But... in *strict mode* `eval()` creates its own scope
- 🕒 An exception's “catch” block has its own scope

🕒 And in an ES6 world..

- 🕒 **let** & **const** define variables within any block's scope
- 🕒 but same visibility rules apply

```
let x = 5;
```

```
if (x > 1) {  
  let x = 10; // OK, shadows outer x  
  let y = 20;  
}
```

```
console.log(x); // 5  
console.log(y); // ReferenceError - not defined
```

The Global Scope



- Variables defined w/out “var” are defined in the global scope

```
alert() === window.alert(); // true  
var user_id = 5;  
window.user_id; // 5
```

- “use strict” will prevent you from creating a global var
- let & const do not define variables in the global object

```
let user_id = 5;  
window.user_id; // undefined
```

- Craft your scope
 - Don't pollute global
 - Use functions and closures to define scopes and conceal vars

Exercise: Hoisting (pt 1 of 3)



What will the output be?

```
function foo() {  
  x = 42;  
  var x;  
  
  console.log(x); // ?  
  return x;  
}  
foo();
```

Exercise: Hoisting (pt 1 of 3)



This...

```
function foo() {  
  x = 42;  
  var x;  
  
  console.log(x);  
  return x;  
}  
foo();
```

Becomes...

```
function foo() {  
  var x;  
  x = 42;  
  
  console.log(x);  
  return x;  
}  
foo();
```

Exercise: Hoisting (pt 2 of 3)



☉ And this?

```
function foo() {  
  console.log(x); // ?  
  var x = 42;  
  return x;  
}  
foo();
```

Exercise: Hoisting (pt 2 of 3)



This...

```
function foo() {  
  console.log(x);  
  var x = 42;  
  return x;  
}
```

Becomes...

```
function foo() {  
  var x;  
  console.log(x);  
  x = 42;  
  return x;  
}
```

Exercise: Hoisting (pt 3 of 3)



🕒 And finally

```
foo(); // ?
```

```
bar(); // ?
```

```
function foo() {  
  console.log("Foo!");  
}
```

```
var bar = function(){  
  console.log("Bar!");  
}
```

Exercise: Hoisting (pt 3 of 3)



This...

```
foo();  
bar();  
  
function foo() {  
  console.log("Foo!");  
}  
  
var bar = function(){  
  console.log("Bar!");  
}
```

Becomes...

```
var x;  
function foo() {  
  console.log("Foo!");  
}  
  
foo();  
bar();  
  
bar = function(){  
  console.log("Bar!");  
}
```


Hoisting



- ⦿ When a variable declaration is **lifted** to the top of its scope
 - ⦿ ... only the declaration, not the assignment
 - ⦿ JS breaks a variable declaration into two statements
- ⦿ **Best practice**
 - ⦿ declare variables at the top of your scope

This...

```
var myVar = 0;  
var myOtherVar;
```

Becomes...

```
var myVar = undefined  
var myOtherVar = undefined;  
myVar=0;
```

Function hoisting



🕒 Function *statements* are hoisted, too

```
hoo(); // 'hoo'  
bat(); // TypeError, function not defined
```

```
function hoo() {  
    console.log('hoo');  
}
```

```
var bat = function() {  
    console.log('bat');  
}
```

Exercise – Function Scope



☉ Scope Sharing




Write two functions that share a *global* and *non-global variable*

☉ Fork me

☉ <http://jsfiddle.net/mrmorris/nv348zo4/>

Solutions:

Scope Sharing: <http://jsfiddle.net/mrmorris/ksy6js0e/>



module

OBJECTS

Why Objects



- Objects are structured data
- Objects as
 - a collection
 - a map
 - a utility library
- Objects to represent things in our world or system (OOP)
 - They have attributes (properties)
 - And behavior (methods)
 - And can relate to other objects

Objects



- Remember that everything is an object except **null** and **undefined**
- Even primitive literals have object wrappers
 - They remain primitive until used as objects, for performance reasons
- An object is a dynamic collection of properties
 - Properties can be any type, including functions and objects
- this** is a special keyword; inside an object method it refers to the object it resides in

Creating an object literal




- Create an object literal with {}:

```
var myObjLiteral = {  
    name: "Mr Object",  
    age: 99,  
    toString = function() {  
        return this.name;  
    }  
};
```

- <http://jsfiddle.net/mrmorris/4dsLonat/>

Object properties



- Dot Syntax

- `myObj.key;`


- Square bracket Syntax

- `myObj["key"];`

- Can delete a property with `delete`

- `delete myObj.key;`

Properties descriptors




- Object properties have descriptors that affect its behavior
 - enumerable
 - configurable
- ```
Object.defineProperty(obj, "key", {
 .. descriptors ..
})
```

# Object reflection



- ◎ Objects actually “inherit” properties from their prototype
  - ◎ ex: Array inherits from Object
  - ◎ “Own” means the property exists on the object itself, not from up the prototype chain
- ◎ `in` operator
  - ◎ `“propertyName” in object`
  - ◎ Goes all the way up the chain, not just “own”
- ◎ `hasOwnProperty`
  - ◎ `myObj.hasOwnProperty( “propertyName” )`

# Object enumerating



## ⦿ for...in

```
⦿ for (var propName in objectName) {
 objectName[propName];
}
```

⦿ Enumerates over enumerable properties

⦿ And all *inherited* properties

⦿ Arbitrary order (not for arrays)

# Object enumeration, continued




## Object.keys(obj)

- Returns array of all “own”, enumerable properties

## Object.getOwnPropertyNames(obj)

- Returns array of all own property names, including non-enumerable

# Exercise - Mutations



🕒 What will the result of this be:

```
var rabbit = {name: 'Tim'};
var hp = 100;
```

```
function attack(obj, hp) {
 obj.fight = true;
 hp = 10;
}
```

```
mutator(rabbit);
console.log(hp, rabbit); // ???
```

# Mutability



- 🕒 All primitives in JavaScript are immutable
  - 🕒 Using an assignment operator just creates a new instance of the primitive
  - 🕒 Pass-by-value
  - 🕒 Unless you used an object constructor for a primitive...
- 🕒 Objects are mutable (and pass-by-reference)
  - 🕒 Their values (properties) can change

# Exercise: Copy Object



## Object Copy




Create a function that can clone an object's own properties

Fork me:

<http://jsfiddle.net/mrmorris/mLccst8c/>

## Solutions:

Copy Object <http://jsfiddle.net/mrmorris/qwcLhf69/>



module

# BUILT-IN OBJECTS



# Lot's of Built-in Objects



- String
- Number
- Boolean
- Function
- Array
- Date
- Math
- RegExp
- Error
- <http://jsfiddle.net/mrmorris/rrb67ev0/>



# String

## Instance properties

```
new String('foo').length // 3
```

## Instance method examples

```
var str = new String('hello
world!');
str.charAt(0); // 'h'
str.concat('!'); // 'hello world!!'
str.indexOf('w'); // 6
str.slice(0, 5); // 'hello'
str.substr(6, 5); // 'world'
str.toUpperCase(); // 'HELLO WORLD!'
```



## Generics

`Number.MIN_VALUE`

`Number.MAX_VALUE`

`Number.NaN`

`Number.POSITIVE_INFINITY`

`Number.NEGATIVE_INFINITY`




## Instance method examples

```
var num = new Number(3.1415);
```

```
num.toExponential(); // "3.1415e+0"
```

```
num.toFixed(); // 3
```

```
num.toPrecision(3); // 3.14
```




☉ Singleton-ish

☉ Methods

☉ `abs, log, max, min, pow, sqrt, sin, floor, ceil, random...`

☉ Properties

☉ `E, LN2, LOG2E, PI, SQRT2...`



```
arr.pop(); // 3
arr.push(3); // 3
arr.reverse(); // [3, 2, 1]
arr.shift(); // 3
arr.sort(); // [1, 2]
arr.splice(1, 0, 1.5); // [1, 1.5, 2]
arr.unshift(0); // [0, 1, 1.5, 2]
arr.concat([2, 4]); // [1, 1, 2, 4]
arr.join('-'); // "1-1"
arr.slice(1, 1); // [1]
```



- Represents a single moment in time based on the number of milliseconds since 1 January, 1970 UTC

- Generics

```
Date.now()
```

```
Date.parse('2015-01-01')
```

```
Date.UTC(2015, 0, 1)
```



- Instance method examples

```
var d = new Date();
```

```
d.getFullYear(); // 2015
```

```
d.getMonth(); // 7
```

```
d.getDate(); // 15
```



- ⦿ Creates a regular expression object for matching text with a pattern

```
var re = new RegExp("\\w+", "g");
var re = /\w+/g;
```

- ⦿ Instance methods

- ⦿ **re.exec**(*str*)

- ⦿ **re.test**(*str*)

- ⦿ String methods that accept RegExp params

- ⦿ **str.match**(*regex*); // array of matches

- ⦿ **str.replace**(*regex*, *replacement*); // string with replacement

- ⦿ **str.search**(*regex*); // returns 1 at first match

- ⦿ **str.split**(*regex*, *limit*); // returns array

# Exercise – Core objects



## 🕒 Data Grids

Display an array of objects as a table in the console

🕒 <http://jsfiddle.net/mrmorris/0kptbv7p/>

## 🕒 Arrays

Filtering and mutating arrays

🕒 <https://jsfiddle.net/mrmorris/ce7s09j0/>

## 🕒 Strings

Replacing a word in a string

🕒 <https://jsfiddle.net/mrmorris/owrtzequ/>




### Solutions:

Data Grid <http://jsfiddle.net/mrmorris/5kfLhn8a/>

Arrays <https://jsfiddle.net/mrmorris/bptg1mkw/>

Strings <https://jsfiddle.net/mrmorris/oc2ba3jj/>





module

# CONTEXT

# Scope & Context




- ◉ We already discussed *Scope*
  - ◉ Determines visibility of variables
  - ◉ Lexical scope (write-time)
- ◉ There is also *Context*
  - ◉ Context refers to the location a function/method was invoked from
  - ◉ Sort of dynamic scope; defined at run-time
  - ◉ Context is referenced by “this”

# “this” is the context



- ◎ `this` keyword is a reference to the “object of invocation”
  - ◎ Bound at invocation
  - ◎ Depends on the call-site of the function
- ◎ It...
  - ◎ allows a method to know what object it is concerned with
  - ◎ allows a single function object instance to service many functions/usages
  - ◎ is key to inheritance
  - ◎ gives methods access to their objects

# this example (again)



```
var person = {
 name: "John Doe",
 speak: function() {
 console.log("Hi my name is", this.name);
 }
}
```

```
person.speak(); // ?
var speak = person.speak;
speak(); // ?
```

```
// and if we put it on another object?
var otherPerson = {name: "Jim"}
otherPerson.speak = person.speak;
otherPerson.speak(); // ?
```

# “this” is determined by call-site



- ⦿ this is *bound* at call-time to an object
- ⦿ 1) Default binding
  - ⦿ Global
- ⦿ 2) Implicit binding
  - ⦿ Object method
    - ⦿ Warning: Inside an inner function of an object method it refers to the global object
- ⦿ 3) Explicit binding
  - ⦿ Set with `.call()` or `.apply()`
- ⦿ 4) Hard binding
  - ⦿ Defined by `.bind()`
- ⦿ 5) “new” binding
  - ⦿ When *constructing* a new object
- ⦿ <http://jsfiddle.net/mrmorris/RUNS5/>

# “this” and global



- It's possible to “leak” and access the global object when invoking functions that reference this from outside objects

```
var setName = function(name) {
 this.name = name;
}
setName('Tim');
name; // "Tim"
window.name === name; // true! oops.
```

- “use strict” prevents leaks like that by keeping global “this” undefined in this case

# More explicit binding



- Context can be changed, which affects the value of `this`, via Function's `call`, `apply` and `bind` methods
  - `obj.foo(); // obj context`  
`obj.foo.call(window); // window context`
- “`bind`” doesn't execute, it returns a copy of the function with the context re-defined. The resulting function is a “bound function”
  - `var getX = module.getX;`  
`boundGetX = getX.bind(module);`
- <http://jsfiddle.net/mrmorris/or7y5orn/>

# Example: Explicit binding



```
var speak = person.speak;
```

```
// invoke speak in the context of person
speak.call(person);
speak.apply(person);
```

```
// invoke speak in the context of otherPerson
person.speak.call(otherPerson);
```



# Example: Binding context



```
// permanently bound to person object
var speak = person.speak.bind(person);
speak();
```

```
// and if we put it on another object?
var otherPerson = {name: "Jim"};
```

```
otherPerson.jimSpeak = person.speak.bind(person);
otherPerson.jimSpeak(); // ?
```

# Arrow Functions [ES6]



- Fat Arrow functions
  - Support super-short syntax in a few ways
  - No **arguments** of its own
    - it's the arguments of the outer function
  - No **this** (context) of its own
    - Lexically bound; wherever the function was defined

```
var add = function (x) {
 return x + 1;
}
```

```
// becomes
var add = x => x + 1;
```

# Arrow functions continued



```
var add = function (x, y) {
 return x + y;
}
```

// becomes

```
var add = (x, y) => x + y;
```


// which is also

```
var add = (x, y) => {
 return x + y; // what is this here?
}
```

// Gotcha...

```
me = {
 name: 'Tim',
 talk: (x) => {
 console.log(this.name, x);
 }
}
```

# Exercise - Objects





## Objectify Yourself

Fork: <https://jsfiddle.net/mrmorris/rt5z9mo0/>



## Solutions:

Objectify Yourself - <https://jsfiddle.net/mrmorris/d2847z01/>



module

**IFFE**



⦿ Immediately Invoked Function Expression

⦿ A function that is defined within a parenthesis, and immediately executed

```
(function() {
 var x = 1;
 return x;
}) ();
```

# IIFE Uses



- Define namespaces/modules/packages
  - Typically singletons or “static” objects
- Creates a scope for private variables/functions
- Extremely common in JS

# Privacy and modules with IFEs



```
var helper = (function() {
 var x = 1; // effectively private
 return {
 getX: function() {
 return x;
 },
 increment: function() {
 return x = x + 1;
 }
 }
})();
```




```
helper.getX();
helper.increment();
```



# Privacy and modules with IFEs



```
var helper = (function($) {
 var $el = $('button');
 return {
 getElement: function() {
 return $el;
 },
 clearElement: function() {
 $el.html('');
 }
 }
})(jQuery); // pass in globals
```



module

# CLOSURES

# Closures




- ⦿ A **closure** is created when an inner function has access to an outer (enclosing) function's variables
- ⦿ A function that maintains state (it's outer scope) after returning
- ⦿ It has access three scopes:
  - ⦿ Own – variables defined in its body
  - ⦿ Outer – parameters and variables in the outer function
  - ⦿ Global
- ⦿ Pragmatically, *every* function in JavaScript is a closure!

# Closures



- One of the most important features of JavaScript
- And often one of the most misunderstood & feared features
- But... they are *all around you* in JavaScript
- They happen when you write code that relies on lexical scope

# Consider scope:




```
var a = 1; // global
```

```
function accessA() {
 console.log(a); // ok
};
```

```
a = 5;
accessA(); // 5 !
```

# Close over scope



```
function closingOver() {
 var a = 1; // local

 return function accessA() {
 console.log(a);
 };
}

accessA = closingOver();
a = 5;
accessA(); // ?
```

# Closure Module Example




```
var helper = (function() {
 var secret = "I am special";

 return {
 secret: secret,
 tellYourSecret: function() {
 console.log(secret);
 }
 }
})();
```

```
helper.tellYourSecret(); // ?
helper.secret = "New secret";
helper.tellYourSecret(); // ?
```

# Closures for Privacy



```
var controller = function() {
 var privateVar = 42;

 var getter = function() {
 return privateVar;
 }

 return {
 getPrivateVar: getter
 }
}

var x = Controller();
```



# Exercise: Closures



## 🕒 Month Names

Using a closure to track month names in a function

🕒 <http://jsfiddle.net/mrmorris/y37qch2g/>

## 🕒 Objectify Me - Private Trophies

🕒 In your Objectify Me lab, go back and make “trophies” a private variable with a getTrophy(i) accessor.

## 🕒 Counter Object

🕒 Make a function that stores a “count” which can be increased or decreased.


<https://jsfiddle.net/mrmorris/yn7yww7q/>

## Solutions:

Month Names - <http://jsfiddle.net/mrmorris/507kocdn/>

Objectify Yourself private - <https://jsfiddle.net/mrmorris/wocw3b1v/>

Counter Object - <https://jsfiddle.net/mrmorris/8r9n4yp1/>



module

# FUNCTION PATTERNS

# Function Chaining



- Fluent style of writing a series of function calls on the same object
  - By returning context (**this**)

```
"this_is_a_long_string"
 .substr(8)
 .replace('_', ' ')
 .toUpperCase(); // A LONG STRING
```

# Support function chaining



```
var Cat = {
 color: null,
 hair: null,
 setColor: function(color) {
 this.color = color;
 return this;
 },
 setHair: function(hair) {
 this.hair = hair;
 return this;
 }
};

Cat.setColor('grey').setHair('short');
```

# Function callbacks



- When a function is provided as an argument as something to be invoked inline, or under specific circumstances (like an event)
- ```
function runCallback(callback) {  
    // does things  
    return callback();  
}
```

Callbacks and closures



⦿ Careful with function expressions in loops

⦿ Can have scope issues

```
⦿ for (var i=0; i<3; i++) {  
    setTimeout(function(){  
        console.log(i);  
    }, 1000*i);  
} // what will this output?
```

⦿ Instead, create an additional scope to maintain state for the inner function (expression)

⦿ Closures save the day

⦿ <http://jsfiddle.net/mrmorris/e8n62r3w/>

Functions Recap



- Are **Objects** with their own methods and properties
- Can be **anonymous**
- Can be bound to a particular **context**, or particular **arguments**
- Can be **chained** together, provided the return of each function has methods
- **Closures** can be used to maintain access to calling context's variables
- **IIFEs** can be used to maintain internal state
 - Both closures and IIFEs can be used to simulate "private" or hidden variables

Strict vs Sloppy



- `"use strict";`
- It kills deprecated and unsafe features
- It changes "silent errors" into thrown exceptions
- It disables features that are confusing or poorly thought out
 - Ensures "eval" has its own scope
 - Does not auto-declare variables at the global level during a scope-chain lookup
- Can be set globally or within function block
 - Careful when concatenating scripts
- <http://jsfiddle.net/mrmorris/d2f6hohb/>

Final Exercise



Track Temperatures

Build a mini module to store and track temp values

<https://jsfiddle.net/mrmorris/3s0sgk9e/>

Smart Stub




Write a function that keeps track of how many times it has been called, as well as the arguments it was called with in sequence

<https://jsfiddle.net/mrmorris/zyqd0cou/>

Solutions:

Track Temps - <https://jsfiddle.net/mrmorris/uz2bh5jr/>

Smart Stub - <https://jsfiddle.net/mrmorris/jeevsryx/>



the end is near

WRAPPING UP

Going beyond





- 🕒 Inheritance (Prototype)
- 🕒 Advanced Modules
- 🕒 Promises and asynchronous JS
- 🕒 AJAX
- 🕒 Observables
- 🕒 JS in the Browser
 - 🕒 The DOM
 - 🕒 Events
- 🕒 JS in the server
 - 🕒 NodeJS

Best Practices so far...



- ⦿ “use strict”
- ⦿ Don’t pollute global
- ⦿ Take care of scope; define variables up top
- ⦿ Determine a nice code standard and stick to it
- ⦿ Use semi-colons (or... don’t)
- ⦿ Take care with coercion; use strict comparison
- ⦿ Avoid primitive constructors (ex: Number() and String())
- ⦿ Use ES6 standards if you’re able... or babel to transpile
 - ⦿ let/const
 - ⦿ fat arrow only when it’s useful

Stay sharp



- ☉ Solve small challenges for kata

- ☉ <http://www.codewars.com/>

- ☉ Code interactively

- ☉ <http://www.codecademy.com/>

- ☉ Share your code and get feedback

- ☉ <http://jsfiddle.net>


- ☉ Free e-book

- ☉ <http://eloquentjavascript.net/>

- ☉ Re-introduction to JavaScript

- ☉ https://developer.mozilla.org/en-US/docs/Web/JavaScript/A_re-introduction_to_JavaScript

Go now and code well



☉ That's a wrap!

- ☉ What did you enjoy learning about the most?
- ☉ What is your key takeaway?
- ☉ What do you wish we did differently?
- ☉ Any other comments, questions, suggestions?
- ☉ Feel free to contact me at mr.morris@gmail.com or my eerily silent twitter **@mrmorris**