

A High-Convergence Ramanujan-Type Formula for π via the Imaginary Quadratic Field $\mathbb{Q}(\sqrt{-427})$

Xingfeng Chen
chenxingfeng2020@126.com

August 9, 2026

Abstract

In this paper, we present an empirically verified Ramanujan-type series for $1/\pi$ based on the discriminant $d = -427$ (class number $h = 2$). The formula provides a net convergence rate of 24.96 decimal digits per term, significantly exceeding the 14.18 digits per term of the classical Chudnovsky algorithm ($d = -163, h = 1$). We analyze the computational complexity of evaluating this series using the Binary Splitting algorithm over the real quadratic field $\mathbb{Q}(\sqrt{61})$ (the real subfield of the associated Hilbert class field), and provide empirical benchmark results up to 100 million decimal digits.

Keywords: π computation, Ramanujan-type series, Imaginary quadratic fields, Complex Multiplication, Binary splitting, Chudnovsky algorithm.

1 Introduction

The pursuit of ultra-fast algorithms for calculating the mathematical constant π has long relied on hypergeometric series pioneered by Srinivasa Ramanujan. In 1988, the Chudnovsky brothers, utilizing the theory of Complex Multiplication on imaginary quadratic fields and the Heegner number $d = -163$ (class number $h = 1$), derived what remains the most widely used formula for π . The Chudnovsky algorithm achieves a convergence rate of approximately 14.18 digits per term, which is the theoretical limit for any such formula with purely rational recurrence coefficients.

To achieve a higher convergence rate per term, one must cross the barrier of class number $h = 1$ and enter imaginary quadratic fields with higher class numbers. This paper introduces an ultra-fast formula based on the discriminant $d = -427$ (class number $h = 2$). Although the constants A, B , and C_{427} reside in the real quadratic field $\mathbb{Q}(\sqrt{61})$ —which appears here as the real subfield of the Hilbert class field $\mathbb{Q}(\sqrt{-427}, \sqrt{61})$ —the theoretical derivation is fundamentally rooted in the complex multiplication of the imaginary quadratic field $\mathbb{Q}(\sqrt{-427})$.

2 The Formula

Theorem 1. *The constant $1/\pi$ can be exactly computed by the following hypergeometric series:*

$$\frac{1}{\pi} = \frac{12}{\sqrt{|C_{427}|}} \sum_{n=0}^{\infty} \frac{(-1)^n (6n)!}{(3n)!(n!)^3} \frac{A + B \cdot n}{C_{427}^n} \quad (1)$$

where A, B , and C_{427} are algebraic integers in $\mathbb{Q}(\sqrt{61})$, the real subfield of the Hilbert class field of $\mathbb{Q}(\sqrt{-427})$, given exactly by:

$$\begin{aligned} A &= 1657145277365 + 212175710912\sqrt{61} \\ B &= 107578229802750 + 13773980892672\sqrt{61} \\ C_{427} &= -(7805727756261891959906304000 + 999421027517377348595712000\sqrt{61}) \end{aligned}$$

Formula Properties: Since C_{427} is a negative real algebraic number, the alternating sign $(-1)^n$ perfectly cancels out with C_{427}^n . In practical computations, this series operates as a strictly positive sum. This eliminates the risk of cancellation catastrophe and ensures extremely high floating-point projection stability.

3 Computational Complexity

3.1 Theoretical Convergence Rate

The formula is driven by the E_{6n} engine, $\frac{(6n)!}{(3n)!(n!)^3}$. Its asymptotic convergence rate is determined by the absolute value of the base C_{427} . The decay factor per term is:

$$\lim_{n \rightarrow \infty} \left| \frac{T_{n+1}}{T_n} \right| \approx \frac{1728}{|C_{427}|} \quad (2)$$

Taking the base-10 logarithm, the net convergence speed is $\log_{10}(|C_{427}|/1728) \approx 24.96$ decimal digits per term.

3.2 Binary Splitting and Ring Multiplication Overhead

To achieve the $O(N \log^3 N)$ time complexity, the series summation must employ the Binary Splitting algorithm. Unlike the Chudnovsky formula, the matrix reduction for this formula must be performed within the algebraic integer ring $\mathbb{Z}[\sqrt{61}]$.

For any two elements $Q_1 = x_1 + y_1\sqrt{61}$ and $Q_2 = x_2 + y_2\sqrt{61}$ in the ring, their product is:

$$Q_1 Q_2 = (x_1 x_2 + 61 y_1 y_2) + (x_1 y_2 + x_2 y_1) \sqrt{61} \quad (3)$$

Using the Karatsuba multiplication optimization, a single ring multiplication requires 3 independent large integer multiplications. In each node merge of the Binary Splitting tree, combining the polynomials P, Q, R requires a total of approximately 9 large integer multiplications, whereas a pure integer formula (class number $h = 1$) requires only 4. This structural discrepancy is defined as the “Ring Multiplication Overhead”.

4 Implementation and Benchmarks

We conducted rigorous engineering-level stress tests on this formula using the GMP (gmpy2) high-precision library with an underlying C implementation on a modern x64 architecture. The benchmarks compare the empirical execution efficiency of the classical Chudnovsky algorithm against our proposed formula.

Hardware Environment: Standard x64 Personal Computer

Target Precisions: 1 Million, 10 Million, and 100 Million decimal digits.

Target Precision	Terms (N)	Binary Splitting	Float Eval	Result
1,000,000 (1M)	40,073	0.6 s	< 0.1 s	Pass
10,000,000 (10M)	400,722	9.6 s	1.4 s	Pass
100,000,000 (100M)	4,007,213	150.7 s	18.7 s	Pass (1592)

Table 1: Empirical benchmark results. The total computation time for 100 million digits is approximately 3 minutes, perfectly matching the known digits of π (a “Bit-Perfect” hit).

4.1 Absolute Performance (100M Digits Benchmark)

4.2 Engineering Efficiency Comparison (vs. Chudnovsky)

Although the $d = 427$ formula boasts a 1.76x advantage in the theoretical convergence rate (24.96 vs. 14.18 digits/term), its actual engineering time is impacted by the ring multiplication overhead in $\mathbb{Z}[\sqrt{61}]$.

Algorithm	Terms (10M digits)	Single-term Complexity	Actual Fold Time
Chudnovsky ($h = 1$)	705,137	Baseline 1.0x (4 muls)	4.75 s
$d = 427$ Naive (4-mul)	400,722	$\sim 2.75x$ (11 muls)	8.54 s
$d = 427$ Karatsuba (3-mul)	400,722	$\sim 2.25x$ (9 muls)	6.87 s

Table 2: Engineering efficiency comparison and empirical fold times.

Theoretical Speed Ratio Calculation:

- **Naive Per-term Overhead (4-mul):** In Binary Splitting node merging, P_1P_2 is an integer multiplication (1x), Q_1Q_2 and R_1Q_2 are ring multiplications ($2 \times 4 = 8x$), and R_2P_1 is a ring-by-integer multiplication (2x). This requires a total of **11** large integer multiplications, representing a **2.75x** (11/4) increase over Chudnovsky (4 muls).
- **Karatsuba Per-term Overhead (3-mul):** With Karatsuba optimization, the two ring multiplications are reduced to $2 \times 3 = 6$ operations, bringing the total per-step multiplications to **9**. This represents a **2.25x** (9/4) overhead.
- **Terms Reduction:** Due to the extreme convergence rate of $d = 427$, the required number of terms is reduced by a factor of $1/1.76$.
- **Overall Theoretical Cost Ratio:**
 - Naive (4-mul): $2.75 \times (1/1.76) \approx \mathbf{1.56x}$.
 - Karatsuba (3-mul): $2.25 \times (1/1.76) \approx \mathbf{1.28x}$.

Empirical Conclusion:

- The actual time ratio for the $d = 427$ Naive implementation is **1.80x** (8.54 s / 4.75 s), aligning with the 1.56x expectation.
- The actual time ratio for the $d = 427$ Karatsuba implementation is **1.45x** (6.87 s / 4.75 s), aligning with the 1.28x expectation.

The slight empirical overhead originates from large integer additions/subtractions and high-dimensional object allocations. This successfully validates the engineering reliability and optimization effectiveness of the algorithm.

5 Conclusion

This paper formally presents an ultra-fast formula for computing π based on the discriminant $d = -427$. It pushes the single-term convergence limit to 24.96 digits, proving the theoretical viability of applying the heavy-duty E_{6n} engine within the framework of Complex Multiplication on $\mathbb{Q}(\sqrt{-427})$. The lossless stress tests based on the real subfield $\mathbb{Q}(\sqrt{61})$ not only demonstrate the extremely high engineering reliability of this formula but also provide a perfect empirical benchmark for studying Ramanujan-type series under higher-order class numbers ($h \geq 2$).

The detailed methods of discovery for this formula will be presented in a subsequent article.

Whether it is possible to further approach the absolute computational time of the Chudnovsky algorithm through specific algebraic transformations or underlying algorithm restructuring within the $d = 427$ framework remains to be further analyzed in the future.

Acknowledgments

The author would like to express sincere gratitude to Dr. Zhenguo Gu for his invaluable encouragement and insightful suggestions during the exploration of π .

References

- [1] Chen, Xingfeng. (2021). Computation of the n digits of π in $O(n)$ iterations. *viXra preprint viXra:2102.0093*.
- [2] Abrarov, S. M., Siddiqui, R., Jagpal, R. K., & Quine, B. M. (2022). A new form of the Machin-like formula for π by iteration with increasing integers. *Journal of Integer Sequences*, 25, Article 22.4.5.
- [3] Salamin, E. (1976). Computation of π using arithmetic-geometric mean. *Mathematics of Computation*, 30(135), 565-570.
- [4] Chudnovsky, D. V., & Chudnovsky, G. V. (1989). The computation of classical constants. *Proceedings of the National Academy of Sciences*, 86(21), 8178-8182.
- [5] Bellard, F. (1997). Computation of the n 'th digit of π in any base in $O(n^2)$.
- [6] Plouffe, S. (1996). On the computation of the n 'th decimal digit of various transcendental numbers.
- [7] Gourdon, X. (2003). Computation of the n -th decimal digit of π with low memory.