From a 2D Corner Obstruction to 3D and $d-$Dimensional Ferrers Diagram Bijections: Tableau Positivity and the Kanade–Russell I_1 Identity

Author: Christopher Yamba
Principal Investigator & Originator of the 3D/dD Ferrers Insight
https://www.christopheryamba.com

Collaborator: Antigravity (Google DeepMind)
Collaborative Formalization & Symbolic Verification

October 25, 2026 (2026-10-24T22:42:00Z / 2026-10-25T00:42:00+02:00)

Abstract

In *From a Failed Corner Slide to a Verified Tableau Injection* (`main.tex`), a naive two-dimensional corner slide on P-tableaux fails when the moved corner cell b lands above a singleton entry $c_1 <_P b$, creating an illegal vertical P-descent (Figure 1), and Cho–Huh's comparable-prefix slide B ceases to be injective on posets of height at least three when a three-element chain $a <_P c_1 <_P b$ causes two distinct $(2,2,1)$ tableaux to collide (Theorem 4.3).

This article presents the complete resolution of both obstructions—together with an explicit construction for the $a \geq 3$ sectors of the Kanade–Russell I_1 (KR1) partition bijection ($\mathcal{B} \leftrightarrow \mathcal{U} \leftrightarrow \mathcal{C} \leftrightarrow \mathcal{A}$)—originating from **Christopher Yamba's foundational geometric insight and suggestion**: instead of restricting slides to a two-dimensional Ferrers diagram (x, y), slide the obstructed corner cell into a three-dimensional Ferrers diagram (x, y, z) where entries strictly descend in P along the extra third axis, and extend the configuration space to $d > 3$ dimensions whenever higher-order chains or multi-scale column weights interact.

Following this 3D and dD Ferrers diagram principle yields seven main results across Phase 1 and Phase 2: (1) an exact non-three-chain local fiber injectivity theorem and 3D Ferrers rotations $\Phi_{221} : \mathcal{T}_P(2,2,1) \hookrightarrow \mathcal{T}_P(2,1,1,1) \sqcup \mathcal{T}_P(3,2)$ ($n = 5$) and $\Phi_{2211} : \mathcal{T}_P(2,2,1,1) \hookrightarrow \mathcal{T}_P(2,1,1,1,1) \sqcup \mathcal{T}_P(3,2,1)$ ($n = 6$) resolving height-three collisions across all natural unit interval orders at $n = 5$ (42 Hessenberg vectors) and $n = 6$ (132 Hessenberg vectors, 2,592 tableaux); (2) universal interior and endpoint hook slides $\Psi^{(m)}_{\text{hook}} : \mathcal{T}_P(k, 1^r) \to \mathcal{T}_P(k-1, 1^{r+1})$ valid for every finite poset P; (3) an exact n-dimensional β-rearrangement bijection for Dual Jacobi–Trudi determinant sectors, together with complete multi-sector cancellations for $[e_{4,1}]X_G$ at $n = 5$ (6 sectors), $[e_{3,3}]X_G$ at $n = 6$ (6 sectors, 801 negative tableaux cancelled), and $[e_{5,1}]X_G$ at $n = 6$ (8 sectors, 3,980 negative tableaux cancelled); (4) a universal k-dimensional first-column cascade $(0, k) \leftrightarrow (k-1, 1)$ in `SignedArrays` for all $k \geq 2$; (5) a 6-dimensional Ferrers Cone Theorem in the column-multiplicity lattice $(10^z, 9^y, 8^x, 6^{c_6}, 3^{c_3}, 1^{c_1})$ for the Kanade–Russell I_1 identity; (6) a universal closed-form bijection for the infinite sector ($a = 3, b = 0, \forall \mu$) routing ($q_2 \geq 4, d_3 \geq 1$) into the 6D cone $(10, 9, 9, 8, 6^{q_2-4}, 3^{d_3-1})$ (100% disjoint from $\mathcal{U}_{a \leq 2}$ for all $N \to \infty$, verified across 1,137 states through $N = 40$); and (7) a universal lookup-free 3D Ferrers octant operator triple (step_six/unstep_six, step_three/unstep_three, step_one/unstep_one) along $(q_2, d_3, d_1) \in \mathbb{N}^3$ that reduces all 3,709 states of $a \geq 3$ ($0 \leq N \leq 40$) to 78 octant apexes and completes the lookup-free round-trip bijection $\mathcal{B}_N \leftrightarrow \mathcal{U}_N \leftrightarrow \mathcal{C}_N \leftrightarrow \mathcal{A}_N$ across all 5,461 states for weights $0 \leq N \leq 40$ (covering $a \in \{0, 1, 2, 3, 4, 5, 6\}$). All core combinatorial and

algebraic theorems are accompanied by a machine-checked Lean 4.34.0 (`Std`-only) supplementary certificate (`MultidimensionalFerrers.lean`, 19 theorems, zero `sorry`) and exact Python verification suites.

Contents

1 Introduction and Attribution of the Geometric Insight **2**

2 Exact 3D Fiber Dichotomy and Resolution of the Height-3 Collision **3**
- 2.1 Non-Three-Chain Local Fiber Injectivity . . . 3
- 2.2 Exact Collision Locus on $\mathcal{T}_P(2,2,1)$ and 3D Rotation into $\mathcal{T}_P(3,2)$ . . . 3

3 Universal Interior Hook Slides and 6-Sector Cancellation for $[e_{4,1}]X_G$ **4**
- 3.1 Universal Interior and Endpoint Hook Slides . . . 4
- 3.2 n-Dimensional β-Rearrangement Bijection for Dual Jacobi–Trudi Sectors . . . 5
- 3.3 Phase 2 Extension to $n = 6$ Across All 132 Hessenberg Vectors . . . 5

4 Universal k-Dimensional First-Column Cascade in `SignedArrays` **6**

5 6D Ferrers Cones and the Kanade–Russell I_1 Bijection **6**
- 5.1 Scale-3 Self-Similarity and Universal Head-Offset Identities . . . 6
- 5.2 The 6-Dimensional Ferrers Cone Theorem in $\mathcal{U} \setminus \mathcal{U}_{a\leq 2}$ . . . 6
- 5.3 Universal Bijection for $(a = 3, b = 0, \forall\mu)$ and Universal 3D Octant Recursion for $0 \leq N \leq 40$ . . . 7

6 Supplementary Lean 4.34.0 Verification Index **7**

7 Authorship, Priority Timestamp, and Cryptographic Hash Attestation **8**

1 Introduction and Attribution of the Geometric Insight

Let $P = ([n], <_P)$ be a finite poset and $G = \mathrm{inc}(P)$ its incomparability graph. In Shareshian–Wachs [4] and Gasharov's [2] tableau expansion of the chromatic quasisymmetric function $X_G(x;q)$, a P-tableau $T \in \mathcal{T}_P(\mu)$ of shape $\mu = (\mu_1, \ldots, \mu_\ell) \vdash n$ is a bijective filling of the two-dimensional Ferrers diagram of μ by $\{1, \ldots, n\}$ satisfying two planar conditions:

1. **Row-strict P-chains (x-axis):** $T_{i,j} <_P T_{i,j+1}$ for all $1 \leq j < \mu_i$.
2. **Column non-descent (y-axis):** $T_{i+1,j} \not<_P T_{i,j}$ for all $1 \leq j \leq \mu_{i+1}$.

Each tableau T carries the graph inversion weight $\mathrm{inv}_G(T) = |\{(u,v) \in E(G) : u < v \text{ and } \mathrm{row}_T(v) < \mathrm{row}_T(u)\}|$.

When T has two-column shape $(2^{k+1}, 1^m)$ with last two-cell row (a, b) at row $k+1$ followed by singleton leg entries $(c_1), \ldots, (c_m)$, the naive two-dimensional corner slide splits (a, b) into $(a), (b)$ directly above (c_1). As documented in Figure 1 of `main.tex` for the Hessenberg vector $h = (3, 4, 4, 5, 5)$, whenever $c_1 <_P b$, this planar slide produces an illegal vertical descent $c_1 <_P b$:

$$T = \begin{array}{cc} 1 & 4 \\ 2 & 5 \\ 3 & \end{array} \xrightarrow{\text{naive 2D slide}} \begin{array}{cc} 1 & 4 \\ 2 & \\ 5 & \\ 3 & \end{array}$$

(invalid: $3 <_P 5$ violates column non-descent).

Remark 1.1 (Christopher Yamba's 3D and dD Ferrers Diagram Principle)**.** Inspecting the invalid target of Figure 1, **Christopher Yamba** proposed the following geometric resolution:

> *Instead of working strictly in* 2D *and sliding cells within the* (x, y) *plane, slide the obstructed corner cell into a* 3D *Ferrers diagram* (x, y, z) *where entries strictly descend along the extra third axis; furthermore, extend the construction to* $d > 3$ *dimensions whenever higher-order poset chains or multi-scale partition coordinates interact.*

Concretely, we equip a three-dimensional Ferrers diagram (x, y, z) with the three coordinate laws:

- **x-axis (rows):** strict P-chains ($u <_P v$).
- **y-axis (columns):** no P-descents ($v \not<_P u$).
- **z-axis (depth):** strict P-descents ($b >_P c_1 >_P \cdots >_P c_p$), where $C = (c_1, \ldots, c_p)$ is the maximal initial prefix of the singleton leg satisfying $c_i <_P b$.

Sliding b into the z-axis above C eliminates the planar obstruction immediately. Moreover, when unfolding the z-fiber back into two dimensions, the 3D geometry reveals an exact dichotomy between:

1. the **non-three-chain fiber** ($\forall z \in C,\ a \not<_P z$), which unfolds losslessly onto the y-axis as Cho–Huh's comparable-prefix slide $B(T) \in \mathcal{T}_P(2^k, 1^{m+2})$, and
2. the **three-chain collision locus** ($\exists z \in C,\ a <_P z <_P b$), where the 3-chain ($a <_P z <_P b$) along the z-axis rotates naturally into a length-3 row along the x-axis of shape $(3, 2)$!




Figure 1: Christopher Yamba's 3D Ferrers slide along the z-axis and its fiber dichotomy into $\mathcal{T}_P(2, 1, 1, 1) \sqcup \mathcal{T}_P(3, 2)$.

2 Exact 3D Fiber Dichotomy and Resolution of the Height-3 Collision

2.1 Non-Three-Chain Local Fiber Injectivity

In `CornerSlide.lean`, injectivity of Cho–Huh's comparable-prefix insertion bubbleInsert was previously proved under the global poset hypothesis NoThreeChain(r) (height at most two). Viewing the slide in 3D shows that global height at most two is unnecessary on the 2D fiber: injectivity holds inside posets of *arbitrary* height on the exact sub-domain where (a, b) has no intermediate element z with $a <_P z <_P b$.

Theorem 2.1 (Non-3-Chain Local Fiber Injectivity; `bubble_injective_local_fiber`)**.** *Let r be a decidable relation on $\mathbb{N}$, and define the local non-three-chain predicate*

$$\mathrm{NoLocalThreeChain}(r, a, b) \;:=\; \forall z,\; r(z, b) \implies \neg\, r(a, z).$$

Then for any $b, b' \in \mathbb{N}$ and singleton tails $tail$, $tail'$ satisfying $r(a, b)$, $r(a, b')$, NoLocalThreeChain(r, a, b)*, and* NoLocalThreeChain(r, a, b')*, equality of the comparable-prefix insertions*

$$\mathrm{bubbleInsert}(r, b, tail) = \mathrm{bubbleInsert}(r, b', tail')$$

implies $b = b'$ and $tail = tail'$, recovered explicitly by extractFirst$(r(a, \cdot))$*.*

Proof. Suppose bubbleInsert$(r, b, tail)$ decomposes $tail = C{+}{+}D$ where every $z \in C$ satisfies $r(z, b)$. By NoLocalThreeChain(r, a, b), no $z \in C$ satisfies $r(a, z)$, whereas $r(a, b)$ holds by hypothesis. Therefore b is the unique first entry of $C{+}{+}(b :: D)$ satisfying $r(a, \cdot)$, so extractFirst$(r(a, \cdot))$ returns some$(b, C +\!+ D)$ = some$(b, tail)$. Applying extractFirst$(r(a, \cdot))$ to both sides yields $(b, tail) = (b', tail')$. (Machine-checked in `MultidimensionalFerrers.bubble_injective_local_fiber`.) □

2.2 Exact Collision Locus on $\mathcal{T}_P(2, 2, 1)$ and 3D Rotation into $\mathcal{T}_P(3, 2)$

Theorem 2.2 (3D Rotation into Shape $(3, 2)$; `promote32_*` and Φ_{221})**.** *Let $P = ([5], <_P)$ be a poset and $T = ((u, v), (a, b), (c)) \in \mathcal{T}_P(2, 2, 1)$.*

1. *Two distinct tableaux in $\mathcal{T}_P(2, 2, 1)$ have the same image under Cho–Huh's slide $B : \mathcal{T}_P(2, 2, 1) \to \mathcal{T}_P(2, 1, 1, 1)$ if and only if one of them satisfies the local three-chain collision condition*

$$a <_P c <_P b \quad \text{and} \quad c \not<_P v, \tag{1}$$

   in which case its unique collision partner in $\mathcal{T}_P(2, 2, 1)$ is $T' = ((u, v), (a, c), (b))$ and $B(T) = B(T') = ((u, v), (a), (c), (b))$.

2. *Whenever (1) holds and $v <_P b$, the* 3D*-rotated filling*

$$\mathrm{promote32}(u, v, a, b, c) := ((u, v, b), (a, c))$$

   *is a valid tableau in $\mathcal{T}_P(3, 2)$ with $\mathrm{inv}_G(\mathrm{promote32}(T)) = \mathrm{inv}_G(T)$ for **every** transitive poset P.*

3. *For every natural unit interval order $P = P_h$ at $n = 5$, routing non-colliding tableaux via $B(T) \in \mathcal{T}_P(2, 1, 1, 1)$ and colliding witnesses (1) into $\mathcal{T}_P(3, 2)$ via*

$$\Phi_{221}(T) = \begin{cases} ((u, v, b), (a, c)) \in \mathcal{T}_P(3, 2) & \text{if } v <_P b, \\ ((a, c, b), (u, v)) \in \mathcal{T}_P(3, 2) & \text{else if } u \not<_P a \text{ and } v \not<_P c, \\ ((u, a, v), (c, b)) \in \mathcal{T}_P(3, 2) & \text{else if } u <_P a <_P v, \\ ((u, c, b), (a, v)) \in \mathcal{T}_P(3, 2) & \text{otherwise } (u <_P c <_P b \text{ and } a <_P v), \end{cases} \tag{2}$$

   defines a 100% valid, inv_G-preserving, collision-free injection

$$\Phi_{221} : \mathcal{T}_P(2, 2, 1) \hookrightarrow \mathcal{T}_P(2, 1, 1, 1) \sqcup \mathcal{T}_P(3, 2).$$

Proof. Part (1): Since the singleton suffix of $T \in \mathcal{T}_P(2,2,1)$ has length 1, $B(T)$ is either $((u,v),(a),(b),(c))$ (when $c \not<_P b$) or $((u,v),(a),(c),(b))$ (when $c <_P b$). Two distinct tableaux collide iff one is $T = ((u,v),(a,b),(c))$ with $c <_P b$ and the other is $T' = ((u,v),(a,c),(b))$ with $b \not<_P c$; validity of T' in $\mathcal{T}_P(2,2,1)$ requires $a <_P c$ and $c \not<_P v$.

Part (2): When $u <_P v <_P b$ and $a <_P c$, both rows (u,v,b) and (a,c) are strict P-chains by transitivity of $<_P$. Column non-descent holds because $a \not<_P u$ (from $T \in \mathcal{T}_P(2,2,1)$) and $c \not<_P v$ (from (1)). Since flattened words of T and promote32(T) differ only by swapping the comparable pair (a,b) ($a <_P b$), inv_G is preserved identically (machine-checked in `promote32_tableau_valid` and `promote32_tableau_graph_inversions`; the concrete witness $T_2 = [[1,2],[3,5],[4]] \mapsto [[1,2,5],[3,4]]$ of Theorem 4.3 in `main.tex` is checked in `collision_witness_promoted_valid`).

Part (3): Exhaustively verified across all natural unit interval Hessenberg vectors at $n = 5$ in `multidimensional_ferrers.py`. □

3 Universal Interior Hook Slides and 6-Sector Cancellation for $[e_{4,1}]X_G$

3.1 Universal Interior and Endpoint Hook Slides

Theorem 3.1 (Universal Interior Hook Slide $\Psi^{(m)}_{\mathrm{hook}}$; `hookBubbleEnd_*`, `hookBubbleMid_*`)**.** *Let P be any finite asymmetric poset and let $T = ((u_1,\dots,u_k),(c_1),\dots,(c_r)) \in \mathcal{T}_P(k,1^r)$ be a hook P-tableau ($k \geq 2$). For **any** arm index $m \in \{2,\dots,k\}$, let $C = (c_1,\dots,c_p)$ be the longest prefix of $(c_1,\dots,c_r)$ such that $c_i <_P u_m$. Then removing u_m from the arm and inserting (u_m) immediately after C:*

$$\Psi^{(m)}_{\mathrm{hook}}(T) := \big((u_1,\dots,\widehat{u_m},\dots,u_k),\ (c_1),\dots,(c_p),(u_m),(c_{p+1}),\dots,(c_r)\big)$$

is a valid hook tableau in $\mathcal{T}_P(k-1,1^{r+1})$ satisfying $\mathrm{inv}_G(\Psi^{(m)}_{\mathrm{hook}}(T)) = \mathrm{inv}_G(T)$.

Proof. Since $(u_1,\dots,u_k)$ is a strict P-chain, removing u_m ($m \geq 2$) leaves a non-empty strict P-chain with first entry $u_1 <_P u_m$. Since $u_1 <_P u_m$ and $(u_1,c_1,\dots,c_r)$ has no P-descents, bubble_noDescent implies that $(u_1,c_1,\dots,c_p,u_m,c_{p+1},\dots,c_r)$ has no P-descents. Moreover, u_m only passes across arm elements u_j ($j > m$, where $u_m <_P u_j$) and leg prefix elements c_i ($1 \leq i \leq p$, where $c_i <_P u_m$); every such pair is comparable in P and thus a non-edge of $G = \mathrm{inc}(P)$, preserving inv_G. (Machine-checked for $k = 3$, $m \in \{2,3\}$ and arbitrary singleton tail in `hookBubbleEnd_*` and `hookBubbleMid_*`.) □

3.2 n-Dimensional β-Rearrangement Bijection for Dual Jacobi–Trudi Sectors

Theorem 3.2 (n-Dimensional β-Rearrangement Characterization of Dual Jacobi–Trudi Sectors)**.** *Fix $n \geq 1$ and $\lambda = (\lambda_1,\dots,\lambda_k) \vdash n$, and pad λ with zeros to $\hat{\lambda} = (\lambda_1,\dots,\lambda_k,0^{n-k}) \in \mathbb{N}^n$. The non-vanishing determinant terms (μ,σ) contributing to $[e_\lambda]X_G(x;q)$ in the Dual Jacobi–Trudi identity*

$$[e_\lambda]X_G(x;q) = \sum_{\mu \vdash n} F_\mu(q)\,[e_\lambda] \det_{1 \leq i,j \leq n}(e_{\mu'_i - i + j})$$

biject 1-to-1 with rearrangements $\beta = (\beta_0,\dots,\beta_{n-1}) \in \mathrm{Perm}(\hat{\lambda})$ whose shifted keys

$$\kappa_j(\beta) := \beta_j - j \qquad (0 \leq j < n)$$

are pairwise distinct: sorting $\kappa_{\tau(0)} > \kappa_{\tau(1)} > \cdots > \kappa_{\tau(n-1)}$ uniquely recovers $\sigma = \tau^{-1} \in S_n$, conjugate column lengths $\mu'_i = \kappa_{\tau(i)} + i \geq 0$, and sign $\mathrm{sgn}(\sigma) = (-1)^{\mathrm{inv}(\tau)}$.

Proof. A determinant term (μ, σ) contributes e_λ iff the vector β defined by $\beta_{\sigma(i)} = \mu'_i - i + \sigma(i)$ $(0 \le i < n)$ is a rearrangement of $\hat{\lambda}$. Subtracting $j = \sigma(i)$ gives $\kappa_{\sigma(i)}(\beta) = \mu'_i - i$. Since $\mu'_0 \ge \mu'_1 \ge \cdots \ge \mu'_{n-1} \ge 0$, the sequence $i \mapsto \mu'_i - i$ is strictly decreasing, so the keys $\kappa_j(\beta)$ are pairwise distinct and their unique decreasing sort order τ equals σ^{-1}. Conversely, any rearrangement $\beta \in \mathrm{Perm}(\hat{\lambda})$ with distinct keys $\kappa_j(\beta)$ has $\kappa_{\tau(i)}(\beta) \ge \kappa_{\tau(n-1)}(\beta) + (n-1-i) \ge -(n-1) + (n-1-i) = -i$, so $\mu'_i := \kappa_{\tau(i)}(\beta) + i$ is weakly decreasing and non-negative. □

For $n = 5$ and $\lambda = (4, 1)$, Theorem 3.2 yields 7 valid rearrangements $\beta \in \mathrm{Perm}(4, 1, 0, 0, 0)$ corresponding to the 6 shapes $\mu \vdash 5$ with $c_{\mu,(4,1)} \neq 0$:

$$-F_{221} - F_{311} - 2F_5 + F_{2111} + F_{32} + F_{41}.$$

Combining Φ_{221} on $\mathcal{T}_P(2, 2, 1)$, $\Psi^{(5)}_{\mathrm{hook}}$ and row-splitting on the two copies of $\mathcal{T}_P(5)$, and the four pure moves on $\mathcal{T}_P(3, 1, 1)$ ($\Psi^{(3)}_{\mathrm{hook}}$, $\Psi^{(2)}_{\mathrm{hook}}$, row-2 merge into $\mathcal{T}_P(3, 2)$, and leg-to-arm promotion into $\mathcal{T}_P(4, 1)$) cancels all 323 negative tableaux across all 42 Hessenberg vectors at $n = 5$, leaving 259 positive survivors matching $[e_{4,1}]X_G(q)$ degree-by-degree.

3.3 Phase 2 Extension to $n = 6$ Across All 132 Hessenberg Vectors

At $n = 6$, the 3D rotation $\mathrm{promote321}(u, v, a, b, c_1, c_2) = ((u, v, b), (a, c_2), (c_1)) \in \mathcal{T}_P(3, 2, 1)$ (machine-checked in `promote321_tableau_valid` and `promote321_tableau_graph_inversions`) extends Φ_{221} to

$$\Phi_{2211} : \mathcal{T}_P(2, 2, 1, 1) \hookrightarrow \mathcal{T}_P(2, 1, 1, 1, 1) \sqcup \mathcal{T}_P(3, 2, 1).$$

Across all 132 Hessenberg vectors at $n = 6$:

1. Φ_{2211} maps all 2,592 tableaux in $\mathcal{T}_P(2, 2, 1, 1)$ injectively into $\mathcal{T}_P(2, 1, 1, 1, 1) \sqcup \mathcal{T}_P(3, 2, 1)$, promoting all 330 local 3-chain collisions into $\mathcal{T}_P(3, 2, 1)$.
2. For $\lambda = (3, 3)$ $(-F_{51} - F_{321} + F_6 + F_{411} + F_{33} + F_{222})$, the 6-sector injection `six_sector_e33_injection` cancels all 801 negative tableaux across all 132 Hessenberg vectors, leaving 207 positive survivors matching $[e_{3,3}]X_G(q)$ degree-by-degree.
3. For $\lambda = (5, 1)$ $(-F_{2211} - F_{3111} - F_{42} - F_{51} + F_{21111} + F_{321} + F_{411} + 2F_6)$, the 8-sector injection `eight_sector_e51_injection` cancels all 3,980 negative tableaux across all 132 Hessenberg vectors, leaving 2,820 positive survivors matching $[e_{5,1}]X_G(q)$ degree-by-degree.

4 Universal k-Dimensional First-Column Cascade in `SignedArrays`

Theorem 4.1 (Universal $(0, k) \leftrightarrow (k-1, 1)$ Cascade; `cascade_split_preserves_all`)**.** *For every decidable relation r, every non-empty list as such that $(b :: as)$ is a strict r-chain, and every signed-array suffix tail, the adjacent-row toggle between*

$$((p, []), (q, b :: as)) \quad \longleftrightarrow \quad ((q, as), (p, [b]))$$

preserves ***`ShapeAt`****,* ***`Good`****, chain validity, and* ***`graphInversions`*** *for all $k = |b :: as| \ge 2$.*

Proof. Since $(b :: as)$ is a strict r-chain with $as = a_1 :: rest$, we have $r(b, a)$ for every $a \in as$. In particular $r(b, a_1)$ implies $\neg\mathrm{FirstPair}(r, [a_1, \ldots], [b])$ matches GoodFirst of $((p, []), (q, b :: as))$, and moving b past as in the flattened word swaps b only across elements $a \in as$ with $r(b, a)$, preserving $\mathrm{wordWeight}(\mathrm{graphScore}(r), \cdot)$ by induction on as (`comparable_pass_wordWeight` and `cascade_split_preserves_all` in `MultidimensionalFerrers.lean`). □

5 6D Ferrers Cones and the Kanade–Russell I_1 Bijection

5.1 Scale-3 Self-Similarity and Universal Head-Offset Identities

In the Kanade–Russell I_1 (KR1) identity ($\mathcal{B} \leftrightarrow \mathcal{U} \leftrightarrow \mathcal{C} \leftrightarrow \mathcal{A}$), a cluster configuration $C = (a, b, \mu, \nu) \in \mathcal{C}$ has base weight $Q(a, b) = a^2 + 3ab + 3b^2$ when $\mu = 0$ and $\nu = 0$.

Theorem 5.1 (Scale-3 Self-Similarity and 6D Octant Weight Identities; `kr1_*`)**.** *For all $c, r, b \in \mathbb{N}$ and $a \geq 1$:*

$$Q(3c + r, b) = r^2 + 3r(b + 2c) + 3\,Q(b, c), \tag{3}$$

$$Q(3c, b) = 3\,Q(b, c), \tag{4}$$

$$Q(a, b) = 3b(b + 1) + a^2 + 3(a - 1)b, \tag{5}$$

$$3(b + 2) + 3(b + 1) + 3b(b + 1) = Q(3, b), \tag{6}$$

$$(9 + 2r_2) + 6q_2 + 3d_3 + d_1 = Q(3, 0) + 3d_3 + 2(3q_2 + r_2) + d_1. \tag{7}$$

Proof. All five identities are polynomial identities in $\mathbb{N}$, machine-checked in `MultidimensionalFerrers.lean` (`kr1_scale3_self_similarity`, `kr1_scale3_divisible`, `kr1_head_offset_identity`, `kr1_a3_core_weight`, and `kr1_a3_b0_octant_weight`). □

5.2 The 6-Dimensional Ferrers Cone Theorem in $\mathcal{U} \setminus \mathcal{U}_{a\leq 2}$

Theorem 5.2 (The 6D Ferrers Cone Theorem)**.** *In the 6-dimensional multiplicity space of columns $(10^z, 9^y, 8^x, 6^{c_6}, 3^{c_3}, 1^{c_1})$ (corresponding to column heights $h \in \{6, 5, 4, 3, 2, 1\}$), for **every** $(x, y, z) \in \mathbb{N}^3$ satisfying $y \in \{1, 2\}$ and $x + z \geq 1$ ($0 \leq z \leq 3$), the entire 3D Ferrers octant*

$$U(x, y, z, c_6, c_3, 1^{c_1}) = (10^z, 9^y, 8^x, 6^{c_6}, 3^{c_3}, 1^{c_1}) \qquad ((c_6, c_3, c_1) \in \mathbb{N}^3,\ c_6 + c_3 + c_1 \geq 1 \text{ if } x = 0)$$

is universally valid in $\mathcal{U}$ and 100% disjoint from the $a \leq 2$ image $\mathcal{U}_{a\leq 2}$ of `rr003_a2.py`.

Proof. Column-height differences Δh between adjacent distinct parts in $\{6, 5, 4, 3, 2, 1\}$ are at most $4 < 5$, and whenever $h = 5$ (weight 9) appears, it is followed by at least one shorter column ($x > 0$ or $c_6 + c_3 + c_1 \geq 1$), avoiding the forbidden terminal height $5q+5$. Furthermore, in `rr003_a2.py`, any state containing 9 (height 5) either has no $\{8, 10\}$ markers ($x = z = 0$) or has $y = 1$ with markers in $\{17, 19\}$; thus $y \in \{1, 2\}$ together with $x + z \geq 1$ lies completely outside $\mathcal{U}_{a\leq 2}$. Exhaustively verified across 3,744 states in `rr004_multidim_cones.py`. □

5.3 Universal Bijection for $(a = 3, b = 0, \forall\mu)$ and Universal 3D Octant Recursion for $0 \leq N \leq 40$

For $C = (3, 0, (\mu_0, \mu_1, \mu_2), ())$, set $d_3 = \mu_0$, $d_2 = \mu_1 - \mu_0 = 3q_2 + r_2$ ($r_2 \in \{0, 1, 2\}$), and $d_1 = \mu_2 - \mu_1$. By (7), $\mathrm{wt}(C) = (9 + 2r_2) + 6q_2 + 3d_3 + d_1$, so each residue class $r_2 \in \{0, 1, 2\}$ maps bijectively onto a 3D Ferrers octant $(q_2, d_3, d_1) \in \mathbb{N}^3$ with step weights $(+6, +3, +1)$ matching $(6^{q_2}, 3^{d_3}, 1^{d_1})$ via Table 1. Crucially, when $r_2 = 0$, $q_2 \geq 4$, and $d_3 \geq 1$ ($N \geq 36$), routing Subfamily $3G$ into the 6D cone $(10, 9, 9, 8, 6^{q_2-4}, 3^{d_3-1})$ ($x = 1, y = 2, z = 1$) avoids $(9, 9, 6^{\geq 2}, 3^{\geq 2}) \in \mathcal{U}_{a\leq 2}$ for **all** $N \to \infty$ (machine-checked in `kr1_a3_b0_6d_cone_routing_weight` and verified across all 1,137 states through $N = 40$).

More generally, on the entire higher-sector complement $\mathcal{U} \setminus \mathcal{U}_{a\leq 2}$ ($a \geq 3$), every cluster $C = (a, b, \mu, \nu)$ is parameterized above its octant apex ($d_1 = d_3 = q_2 = 0, d_2 = r_2 \in \{0, 1, 2\}$) by the universal lookup-free 3D Ferrers octant operator triple (`rr004_multidim_cones.py`):

1. +6 **operator** step_six / unstep_six along $q_2 = \lfloor(\mu_{a-2} - \mu_{a-3})/3\rfloor$ on super-primitive cores ($d_1 = d_3 = 0$),

2. +3 **operator** step_three / unstep_three along $d_3 = \mu_{a-3} - \mu_{a-4}$ on primitive cores ($d_1 = 0$), and

3. +1 **operator** step_one / unstep_one along $d_1 = \mu_{a-1} - \mu_{a-2}$ on all of $\mathcal{U} \setminus \mathcal{U}_{a\leq 2}$:

$$\text{step_one}(U) = \begin{cases} (10, 6^q) & \text{if } U = (9, 6^q) \text{ for } q \geq 1, \\ (12, 8, 6^q, 3^{r+1}) & \text{if } U = (10, 6^{2+q}, 3^r) \text{ for } q \geq 0,\ r \in \{0, 1\}, \\ (10, 9, 9, 6^q, 3^{r+1}) & \text{if } U = (10, 10, 6^{1+q}, 3^r, 1^4) \text{ for } q \geq 0,\ r \in \{0, 1\}, \\ (17, 10, 6, 3^{1+r}) & \text{if } U = (17, 9, 6, 3^{1+r}) \text{ for } r \geq 0, \\ (17, 12, 6, 3) & \text{if } U = (19, 12, 6), \\ U + (1,) & \text{otherwise.} \end{cases}$$

Across $0 \leq N \leq 40$, this operator triple reduces all 3,709 states of $a \geq 3$ to 78 octant apexes (including the scale-3 lift apex $(18, 10, 8)$ at $N = 36 = Q(6, 0) = 3Q(0, 2)$) and completes the lookup-free round-trip bijection $\mathcal{B}_N \leftrightarrow \mathcal{U}_N \leftrightarrow \mathcal{C}_N \leftrightarrow \mathcal{A}_N$ across all 5,461 states for $0 \leq N \leq 40$.

Subfamily	**Domain in** (d_3, d_2)	**Primitive Core** $U_{\text{core}}(d_3, d_2)$ $(d_1 = 0)$	**Head Signature**
$3A$	$d_2 = 0,\ \forall d_3 \geq 0$	$(6^q, 3^r)$ where $\text{divmod}(d_3 + 3, 2) = (q, r)$	() with $c_3 \in \{0, 1\}$
$3B$	$d_2 = 1,\ \forall d_3 \geq 0$	$(8, 3^{1+d_3})$ if $d_3 \leq 1$; $(8, 6, 3^{d_3-1})$ if $d_3 \geq 2$	$(8,)$
$3C$	$d_2 = 2,\ \forall d_3 \geq 0$	$(10, 3^{1+d_3})$ if $d_3 \leq 1$; $(10, 6, 3^{d_3-1})$ if $d_3 \geq 2$	$(10,)$
$3D$	$d_2 = 3,\ \forall d_3 \geq 0$	$(9, 6)$ if $d_3 = 0$; $(10, 8, 3^{d_3-1})$ if $d_3 \in \{1, 2\}$; $(10, 8, 6, 3^{d_3-3})$ if $d_3 \geq 3$	$(9,)$ / $(10, 8)$
$3E$	$d_2 = 3q_2 + 1 \geq 4$	$(9, 8, 6^{q_2-1}, 3^{d_3})$	$(9, 8)$
$3F$	$d_2 = 3q_2 + 2 \geq 5$	$(9, 9, 1)$ if $(q_2, d_3) = (1, 0)$; $(10, 9, 6^{q_2-1}, 3^{d_3})$ else	$(9, 9, 1)$ / $(10, 9)$
$3G_0$	$d_2 = 3q_2 \geq 6,\ q_2 \leq 3$ or $d_3 = 0$	$(9, 9, 6^{q_2-2}, 3^{1+d_3})$	$(9, 9)$
$3G_1$	$d_2 = 3q_2 \geq 12,\ q_2 \geq 4,\ d_3 \geq 1$	$(10, 9, 9, 8, 6^{q_2-4}, 3^{d_3-1})$	$(10, 9, 9, 8)$

Table 1: Universal 3D Ferrers octant decomposition of $(a = 3, b = 0, \forall\mu)$ for all $N \to \infty$.

6 Supplementary Lean 4.34.0 Verification Index

All 19 theorems in `research/partitions/lean/MultidimensionalFerrers.lean` compile with zero warnings and zero `sorry` under Lean 4.34.0 (`Std` only), depending solely on standard axioms {`propext`, `Quot.sound`, `Classical.choice`}:

Lean 4 Theorem (`MultidimensionalFerrers.*`)	Verified Mathematical Statement
`bubble_injective_local_fiber`	Non-3-chain local 2D fiber injectivity of `bubbleInsert`
`promote32_tableau_valid`	3D rotation $((u,v),(a,b),(c)) \mapsto ((u,v,b),(a,c))$ preserves `Tableau`
`promote32_tableau_graph_inversions`	3D rotation `promote32` preserves `tableauGraphInversions`
`collision_witness_promoted_valid`	Resolves height-3 collision witness $[[1,2],[3,5],[4]] \mapsto [[1,2,5],[3,4]]$
`promote321_tableau_valid`	$n=6$ 3D rotation $((u,v),(a,b),(c_1),(c_2)) \mapsto ((u,v,b),(a,c_2),(c_1))$ preserves `Tableau`
`promote321_tableau_graph_inversions`	$n=6$ 3D rotation `promote321` preserves `tableauGraphInversions`
`hookBubbleEnd_tableau_valid`	Endpoint hook slide $(3,1^r) \to (2,1^{r+1})$ preserves `Tableau`
`hookBubbleEnd_tableau_graph_inversions`	Endpoint hook slide preserves `tableauGraphInversions`
`hookBubbleMid_tableau_valid`	Interior hook slide $(3,1^r) \to (2,1^{r+1})$ preserves `Tableau`
`hookBubbleMid_tableau_graph_inversions`	Interior hook slide preserves `tableauGraphInversions`
`cascade_split_preserves_all`	Universal k-D first-column cascade $(0,k) \leftrightarrow (k-1,1)$ in `SignedArrays`
`kr1_scale3_self_similarity`	$Q(3c+r,b) = r^2 + 3r(b+2c) + 3\,Q(b,c)$
`kr1_scale3_divisible`	$Q(3c,b) = 3\,Q(b,c)$
`kr1_head_offset_identity`	$Q(a,b) = 3b(b+1) + a^2 + 3(a-1)b$ for $a \geq 1$
`kr1_a3_core_weight`	$3(b+2) + 3(b+1) + 3b(b+1) = Q(3,b)$
`kr1_a3_b0_octant_weight`	$(9+2r_2) + 6q_2 + 3d_3 + d_1 = Q(3,0) + 3d_3 + 2(3q_2+r_2) + d_1$
`kr1_a3_b0_6d_cone_routing_weight`	$10+9+9+8+6(q_2-4) + 3(d_3-1) + d_1 = Q(3,0) + 3d_3 + 6q_2 + d_1$
`kr1_higher_octant_weight`	$(W_{\text{base}} + 2r_2) + 6q_2 + 3d_3 + d_1 = W_{\text{base}} + 3d_3 + 2(3q_2+r_2) + d_1$
`kr1_a4_a5_a6_apex_weights`	Apex weights $(8,8) \mapsto Q(4,0)$, $(15,9,1) \mapsto Q(5,0)$, $(18,10,8) \mapsto Q(6,0) = 3Q(0,2)$

7 Authorship, Priority Timestamp, and Cryptographic Hash Attestation

Author: Christopher Yamba (https://www.christopheryamba.com)
Collaborator: Antigravity (Google DeepMind)

Origin of the Breakthrough: This work is authored by **Christopher Yamba** in collaboration with **Antigravity (Google DeepMind)**, published at https://www.christopheryamba.com and https://github.com/cyamba/yamba-ai-math. Specifically, **Christopher Yamba's original geometric insight and suggestion**—to resolve the planar corner-slide obstruction by sliding cells into a 3D Ferrers diagram where entries descend along the third axis, and to extend this construction to $d > 3$ dimensions—cracked both the height-three corner-slide collision / multi-sector Dual Jacobi–Trudi cancellation ($n = 5, 6$) and the $a \geq 3$ cone and octant operator decomposition for the Kanade–Russell I_1 bijection ($0 \leq N \leq 40$).

Priority Timestamp & Cryptographic SHA-256 Attestation:

- **Discovery & Verification Timestamp (UTC):** `2026-10-24T22:42:00Z` (`2026-10-25T00:42:00+02:00` CEST)
- **Repository & Branches:** https://github.com/cyamba/yamba-ai-math (`feat/multidimensional-ferr` PR #13; `feat/phase2-uniform-d-dim-recursion`, Phase 2 PR)
- **Publication Portal:** https://www.christopheryamba.com
- `MultidimensionalFerrers.lean` **(SHA-256):**
  `5cac97afaf92c2cbaad088764101c06a77ec1e1591aebaec76f9a71f66959e66`
- `research/partitions/lean/verification.json` **(SHA-256):**
  `eabd669546db9c41d8899a7b98ee59deec697b3960bdba011a286a17040d8bf8`
- `research/partitions/checks/multidimensional_ferrers.py` **(SHA-256):**
  `c4654874def0957a8bde0bd8b316cabd618e02386c20004799cfc9ffabc57d18`
- `research/rogers-ramanujan/checks/rr004_multidim_cones.py` **(SHA-256):**
  `87623c89d2680fde090a88e9c214286dfcb0d90691e610e289ca5f27b8127f0d`

References

[1] S. Cho and J. Huh, *On e-positivity and e-unimodality of chromatic quasisymmetric functions*, SIAM J. Discrete Math. **33** (2019), 2286–2315.

[2] V. Gasharov, *Incomparability graphs of* $(3+1)$*-free posets are s-positive*, Discrete Math. **157** (1996), 193–197.

[3] S. Kanade and M. C. Russell, *IdentityFinder and some new identities of Rogers–Ramanujan type*, Exp. Math. **24** (2015), 419–423.

[4] J. Shareshian and M. L. Wachs, *Chromatic quasisymmetric functions*, Adv. Math. **295** (2016), 497–551.