

Domain Management GUI — Design Spec

Date: 2026-04-22 Status: Approved

Overview

Add full domain management to the OB2 dashboard Domains tab. Currently domains are read-only in the GUI (list + delete + aliases). This spec adds: create domain, browse and delete individual docs, inline alias management, per-domain user visibility, and domain descriptions — all surfaced through a tabbed modal consistent with the existing Edit User flow.

Scope

Five features, all delivered together:

Feature	Where
Create domain (name + description)	New "+ Create Domain" modal
Browse & delete individual docs	Manage modal → Docs tab
Domain description / metadata	Manage modal → Settings tab; description column in table
Inline alias management	Manage modal → Aliases tab (replaces the separate section below the table)
See which users have access	Manage modal → Users tab

UI Changes

Domains Table (enhanced)

- Add "+ Create Domain" button in the table header (right-aligned).
- Add **Description** column between Domain and Docs. Shows description text if set, otherwise muted "no description".
- Rename existing "Aliases" button to "Manage" — opens the Manage modal.
- **Delete** button removed from the table row. Deletion moves to the Settings tab inside the modal (keeps the table cleaner and adds a natural confirmation step).

Create Domain Modal

Opened via "+ Create Domain" button.

Fields:

- **Domain name** — text input with @ prefix label. Validated: lowercase letters, numbers, hyphens only. Required.
- **Description** — text input. Optional.

On submit: `POST /admin/domains` with `{domain, description}`. On success: close modal, reload domains table, show success toast.

Validation errors shown inline below the domain name field.

Manage Domain Modal

Opened via the **Manage** button on any domain row. Header shows `@domainname · N docs · description`.

Four tabs: **Docs**, **Aliases**, **Users**, **Settings**.

Docs Tab

- Search input at the top — client-side filter on visible text.
- Table: truncated document text (first ~120 chars), date added, **Delete** button per row.
- Delete triggers a confirmation step (inline row highlight + confirm/cancel buttons — no nested modal).
- Calls `DELETE /admin/domains/:domain/docs/:id` on confirm.
- Reload doc list after deletion; update doc count in table row.

Aliases Tab

Moves the existing alias manager (currently rendered below the domains table) into this tab. No functional changes — same form (domain pre-selected), same alias list table, same API calls.

Users Tab

Read-only list of users with access to this domain. Derived from the existing `GET /admin/users` response — filter to users whose `domains` map includes this domain, plus all global admins.

Columns: Username, Permission (badge: read / write / admin / global admin).

Footer note: "To change permissions, edit the user from the Users tab."

No new API endpoint required — data already available.

Settings Tab

- **Description** field — pre-filled, editable text input. Save button calls `PATCH /admin/domains/:domain` with `{description}`.
- Horizontal rule separator.
- **Danger zone** — “Delete this domain...” button. Opens existing delete confirmation modal. On confirm: calls `DELETE /admin/domains/:domain`, closes manage modal, reloads table.

Backend Changes

New: `POST /admin/domains`

Auth: global admin only.

Body: `{ domain: string, description?: string }`

Behavior: Validates domain name (regex: `^[a-z0-9-]+$`, max 64 chars). Calls `capture_knowledge` sidecar command with a system-tagged seed document:

```
{
  "domain": "<domain>",
  "text": "<description or empty string>",
  "metadata": { "_ob2_system": true, "_ob2_type": "domain_init", "description": "<description>" }
}
```

This establishes the domain in both SQLite and pgvector without requiring schema changes. The seed doc is filterable by `_ob2_system: true` metadata so the Docs tab can exclude it from the browsable list.

Returns: `{ ok: true, domain }` or `{ error }`.

New: `GET /admin/domains/:domain/docs`

Auth: read permission on domain.

Query params: `limit` (default 100), `offset` (default 0).

Behavior: Calls a new sidecar command `list_docs` with `{ domain, limit, offset }`. The sidecar queries SQLite and returns docs for the domain, excluding entries where `metadata->'_ob2_system' = 'true'`, ordered by `created_at DESC`.

New sidecar command (`retrieval/sidecar.py`):

```
# list_docs: returns paginated docs for a domain, excluding system docs
def handle_list_docs(domain, limit=100, offset=0):
    rows = db.execute(
        "SELECT doc_id, text, created_at, metadata FROM docs "
        "WHERE domain=? AND json_extract(metadata,'$_ob2_system') IS NULL "
        "ORDER BY created_at DESC LIMIT ? OFFSET ?",
        [domain, limit, offset]
    )
    total = db.execute(
        "SELECT COUNT(*) FROM docs WHERE domain=? AND json_extract(metadata,'$_ob2_system') IS NULL",
        [domain]
    ).fetchone()[0]
    return {"docs": [...], "total": total}
```

Returns:

```
{
  "docs": [
    { "doc_id": "...", "text": "...", "created_at": "...", "metadata": {} }
  ],
  "total": 42
}
```

New: PATCH /admin/domains/:domain

Auth: admin permission on domain or global admin.

Body: { description: string }

Behavior: Calls a new sidecar command `set_domain_description` with { domain, description }. The sidecar finds the seed doc (`_ob2_system: true, _ob2_type: "domain_init"`) via SQLite, updates its `metadata` JSON in-place, and re-syncs it to pgvector by clearing `synced_at` . If no seed doc exists (domain pre-dates this feature), creates one via `capture_knowledge` with the system metadata tags.

Returns: { ok: true } .

Modified: GET /admin/domains

Add `description` field to each domain entry in the response, derived from the seed doc's metadata if present. Empty string if not set.

Description Storage

Descriptions are stored as metadata on a hidden seed document in the existing `docs` table — no schema changes needed. The seed doc is identified by `metadata->>'_ob2_system' = 'true'` and `metadata->>'_ob2_type' = 'domain_init'` . Only one seed doc per domain. The `GET /admin/domains/:domain/docs` endpoint excludes seed docs from results.

Removed

- The standalone **Aliases** section below the domains table (HTML + JS) is removed. Alias management moves entirely into the Manage modal Aliases tab.

Error Handling

- Domain name already exists on `POST /admin/domains` : return 409, show inline error.
- Domain name invalid format: validate client-side before submit, also validated server-side.
- Doc list empty: show muted “No documents in this domain.” message.
- Users tab: if `/admin/users` fails, show muted “Could not load users.” — non-fatal.
- All destructive actions (doc delete, domain delete) require explicit confirmation before API call.

Files Changed

File	Change
<code>server/routes/admin.ts</code>	Add <code>POST /admin/domains</code> , <code>GET /admin/domains/:domain/docs</code> , <code>PATCH /admin/domains/:domain</code> ; modify <code>GET /admin/domains</code> to include <code>description</code> field
<code>server/static/dashboard.js</code>	Add <code>createDomain</code> , <code>openManageDomain</code> , <code>loadDomainDocs</code> , <code>deleteDomainDoc</code> , <code>saveDomainDescription</code> functions; add new <code>data-action</code> cases; remove standalone alias section wiring
<code>server/static/dashboard.html</code>	Add “+ Create Domain” button; add description column; remove standalone aliases section
<code>retrieval/sidecar.py</code>	Add <code>list_docs</code> and <code>set_domain_description</code> sidecar commands