

DEFEND WORKSHOP

Izdihar



PRACTICAL NMAP FOR ASSET DISCOVERY

Basic network discovery scan

```
nmap -sn 192.168.0.0/24
```

Detailed service detection scan

```
nmap -sV 192.168.0.0/24
```

Output to file for documentation

```
nmap -sV 192.168.0.0/24 -oN scan_results.txt
```





PRACTICAL NMAP FOR ASSET DISCOVERY

Practical Tips:

- Look for unexpected open ports (22, 80, 443, 3389)
- Check for unauthorized services
- Compare against your inventory document





VULNERABILITY SCANNING WITH NUCLEI

What is Nuclei?

- Open-source vulnerability scanner
- Template-based detection approach
- Faster and more customizable than many commercial tools
- Perfect for SMEs and blue teams with limited resources





VULNERABILITY SCANNING WITH NUCLEI

Basic scan of a target

```
nuclei -u http://example.com -o results.txt
```

Scan multiple targets

```
nuclei -l hosts.txt -o results.txt
```

Scan with specific severity levels

```
nuclei -u http://example.com -severity critical,high
```

Scan specific vulnerability types

```
nuclei -u http://example.com -tags cve,rce,oast
```





VULNERABILITY SCANNING WITH NUCLEI

Interpreting Results:

- Focus on critical and high severity findings first
- Validate findings to eliminate false positives
- Prioritize internet-facing vulnerabilities
- Document and track remediation status





SECURITY CONFIGURATION ANALYSIS

File Locations to Check:

- Linux: /etc/ssh/sshd_config, /etc/passwd, crontabs
- Windows: Registry, scheduled tasks, startup items

Common Misconfigurations:

- Default credentials
- Password authentication enabled
- Excessive permissions
- Plaintext secrets in config files





SECURITY CONFIGURATION ANALYSIS

Find files containing password strings

```
grep -r "password" --include="*.conf" /etc/
```

```
grep -r "key" --include="*.json" /home/
```

Check SSH configuration

```
cat /etc/ssh/sshd_config | grep "PasswordAuthentication"
```





LOG ANALYSIS TECHNIQUES

Common Log Patterns to Look For:

- Failed login attempts in sequence (brute force)
- Suspicious IP addresses or geolocations
- Unusual access times
- Sensitive file access
- Command execution patterns





LOG ANALYSIS TECHNIQUES

Count occurrences of IPs in logs

```
cat auth.log | grep "Failed password" | awk '{print $11}' | sort |  
uniq -c | sort -nr
```

Find events within a timeframe

```
cat auth.log | grep "Apr 22" | grep "authentication failure"
```

Detect unusual admin actions

```
cat auth.log | grep "sudo" | grep -v "user=root"
```





MALWARE IDENTIFICATION

Quick File Analysis:

Check file type

```
file suspicious_file
```

See strings inside a file

```
strings suspicious_file | less
```

Calculate file hash for VirusTotal

```
sha256sum suspicious_file
```





MALWARE IDENTIFICATION

Red Flags:

- Executable files in unexpected locations
- Files with multiple extensions (.doc.exe)
- Base64-encoded scripts
- Obfuscated code





INCIDENT RESPONSE BASICS

Initial Response Steps:

- Document what's happening
- Contain the issue (isolate affected systems)
- Collect evidence before changes
- Determine impact and scope
- Remediate and recover





INCIDENT RESPONSE BASICS

Documentation Focus:

- Timestamps of all actions
- Systems affected
- Actions taken
- Evidence collected





CTF PREVIEW AND TOOL SUMMARY

Key Tools Covered:

- Nmap: Network discovery and service detection
- Text editors & grep: Configuration analysis
- Log analysis tools: Pattern recognition in logs
- File analysis: Malware identification




An abstract graphic design on a black background. A large white circle is centered, with a thick green line tracing its right side. To the left of the circle, there are two horizontal wavy lines. Below the circle, on the left, is a small orange circle. To the right of the circle, there is a small orange circle with a white outline. In the bottom right corner, there is a square grid of small white dots.

TEMPLATES



SahurCTF



- <https://btctf.cyber673.com>
- Register
- Defend (or try to)!
- Winner gets... something!

cyber673