

CSE 201: Data Structures and Algorithms

Lecture 5:Queues

Dr. Vidhya Balasubramanian


Queues

- It is a first-in-first-out abstract data type
- Applications in Real World
 - Transportation
 - Operations Research
 - Acts as buffer in many applications



Queues: An Overview

- Element that is inserted first is removed first
 - Insertions at the rear of the queue and deletions at the front of the queue



[http://upload.wikimedia.org/wikipedia/commons/thumb/5/52/Data_Queue.svg/300px-](http://upload.wikimedia.org/wikipedia/commons/thumb/5/52/Data_Queue.svg/300px-Data_Queue.svg.png)

[Data_Queue.svg.png](http://upload.wikimedia.org/wikipedia/commons/thumb/5/52/Data_Queue.svg/300px-Data_Queue.svg.png)

Queue ADT: Main Operations

- enqueue(o)
 - Inserts an object o at the end of the queue
 - Input: object; Output: None
- dequeue()
 - Removes and returns the first element in the queue
 - Input: none; Output: object
 - Error occurs if queue is empty

Other Queue Operations

- `size()`
 - Returns the number of objects in the queue
- `isEmpty()`
 - Returns a Boolean indicating if the queue is empty
- `front()`
 - Return first element of the queue without removing it. Error occurs if queue is empty
 - Input: None; Output: Object

Queue Exceptions

- Some operations may cause an error causing an exceptions
- Exceptions in the Queue ADT
 - QueueEmptyException
 - dequeue() and front() cannot be performed if the queue is empty
 - QueueFullException
 - Occurs when the queue has a maximum size limit ie implemented with an array
 - enqueue(o) cannot occur when the queue is full

Queue Example

Operation	Output	Queue Contents
enqueue(5)	-	(5)
enqueue(3)	-	(5,3)
enqueue(7)	-	(5,3,7)
dequeue()	5	(3,7)
size()	2	(3,7)
enqueue(4)	-	(3,7,4)
dequeue()	3	(7,4)
dequeue()	7	(4)
size()	1	(4)
dequeue()	4	()
dequeue()	"error"	()

Queue Interface (Java)

```
public interface Queue<E>
```

```
    int size(): //returns number of objects in the queue
```

```
    boolean isEmpty() //returns true if queue is empty, false otherwise
```

```
    E front();
```

```
        //returns front object in queue, throws exception if queue empty
```

```
    void enqueue(E element): //inserts object at rear of queue
```

```
    E dequeue();
```

```
        //throws (Queue EmptyException)
```

```
}
```


Exercise


- Describe the output of the following series of queue operations
 - enqueue(5), enqueue(3), dequeue(), enqueue(2), enqueue(8), dequeue(), dequeue(), isEmpty(), enqueue(9), enqueue(1), size(), dequeue(), enqueue(7), enqueue(6), front(), dequeue(), dequeue(), enqueue(4), dequeue(), dequeue()
- Show how to implement a queue using two stacks. Analyze the running time of the queue operations.

Array based implementation of a Queue

- A Queue may be implemented by using a simple array
 - An N-element array
 - Queue is limited by the size of the array
 - Two variable to keep track of front and rear
 - Integer f denotes the index of the front element
 - Integer r denotes the position immediately past the rear element
- Strategy
 - Elements are added left to right

Circular Array Implementation

- After repeated enqueue and dequeue operations the rear part may reach end of queue
 - There may be place at the beginning of array
- Circular Queue
 - Allow f and r to wrap around to end of queue



src: Goodrich notes

Queue ADT Functions


- **Algorithm** size()
return $(N - f + r) \bmod N$ *#may use a variable `__len__` to keep track of size*
- **Algorithm** isEmpty()
return $(size() == 0)$ *# return $(f=r)$ and $(|r - f| = N - 1)$ indicates queue is full*
- **Algorithm** front()
if isEmpty() **then**
 throw a QueueEmptyException
return $Q[f]$

Queue ADT Functions


- **Algorithm** enqueue(o)
 - if** size() = $N-1$ **then**
 - throw** a QueueFullException
 - $Q[r] \leftarrow o$
 - $r \leftarrow (r+1) \bmod N$
- **Algorithm** dequeue()
 - if** isEmpty() **then**
 - throw** a QueueEmptyException
 - $o \leftarrow Q[f]$
 - $f \leftarrow (f+1) \bmod N$
 - return** o

Circular Array

- Size Function
 - size(): return the number $(N - f + r) \bmod N$
 - If $r \geq f$, then $r - f \geq 0$
 - $N + (r - f) \geq N$
 - $(N - f + r) \bmod N = -f + r = r - f$
 - If $r < f$, then $f - r > 0$
 - $N - f + r = N - (f - r) < N$
 - $(N - f + r) \bmod N = N - f + r$



Circular Queue: Example



- enqueue(24)
 - $r \leftarrow (r+1) \bmod N$
 - $= (4+1) \bmod 5 = 0$
- dequeue() (fig 11)
 - $f \leftarrow (f+1) \bmod N$
 - $= (4+1) \bmod 5 = 0$

Complexity Analysis

- Time Complexity
 - size – $O(1)$
 - isEmpty – $O(1)$
 - front – $O(1)$
 - enqueue – $O(1)$
 - dequeue – $O(1)$
- Space Complexity
 - $O(N)$


Growable Array-based Queue

- In an enqueue operation, when the array is full, instead of throwing an exception, we can replace the array with a larger one
- Similar to what we did for an array-based stack
- The enqueue operation has amortized running time
 - $O(n)$ with the incremental strategy
 - $O(1)$ with the doubling strategy

Exercises


- Reverse the order of elements in a stack S using one additional queue
- Using additional non-array variables, order all elements on a queue using
 - Two additional queues
 - One additional queue
- Is it possible to keep 2 stacks in a single array, if one grows from position one of the array, and the other grows from the last position. Write a procedure $PUSH(x,s)$ that pushes element x onto stack S , where S is one or the other of these two stacks. Include all necessary error checks.

Double-Ended Queue



Double-Ended Queues

- It is a queue like data structure that supports insertion and deletion at both ends
 - Front and rear of the queue
- Also known as deque



<http://www.brpreiss.com/books/opus4/html/img751.gif>

Deque Abstract Data Type

- insertFirst(o)
 - Insert a new object *o* at the beginning of D
 - Input: Object; Output: None
- insertLast(o)
 - Insert a new object *o* at the end of D
 - Input: Object; Output: None
- RemoveFirst()
 - Remove the first object of D. Error occurs if D is empty
 - Input: None; Output: None
- RemoveLast()
 - Remove the last object of D. Error occurs if D is empty
 - Input: None; Output: None

Additional Deque functions

- `first()`
 - Return first object of D; error occurs if D is empty
 - Input: None; Output: Object
- `last()`
 - Return last object of D; error occurs if D is empty
 - Input: None; Output: Object
- `size()`
 - Returns the number of objects in D
- `isEmpty()`
 - Returns a Boolean indicating if D is empty

Implementation

- Can use a dynamic array
 - uses a variant of a dynamic array that can grow from both ends, sometimes called array deques
 - Can also use circular arrays
- Dynamic Arrays
 - Works like regular arrays
 - No limit on size
 - array is discarded and replaced by a bigger array whenever necessary
 - Can use either linear or doubling strategy