

Technical Analysis of a Fighter -Configured Spyder Downloader

A later build matching the Spyder lineage publicly attributed to Patchwork

WRITTEN BY

Noam Rotem

Cyber Cyber Labs
cybercyberlabs.com

Sample period

July 2024

Evidence cutoff

26 July 2026, 09:20 UTC

Classification

Windows downloader / loader

Technical lineage

Spyder - Fighter branch

Technical Analysis of a Fighter-Configured Spyder Downloader

Technical Analysis of a Fighter-Configured Spyder Downloader

Executive Summary

1. Provenance, Scope, and Sample Overview
2. Packaging, Masquerade, and Signing
3. Execution, Persistence, and Defense Evasion
4. Host Profiling and Command-and-Control
5. Payload Delivery
6. Defensive Reacquisition of the C2 Domain
7. Comparison with QiAnXin's 2024 Spyder Research
8. Attribution Assessment
9. Conclusion

Appendices

Appendix A - Indicators

Appendix B - ATT&CK Mapping

Appendix C - Key Functions

Appendix D - Evidence Index

References

Technical Analysis of a **Fighter**-Configured Spyder Downloader

Version 1.0 | Published 26 July 2026

Sample period: July 2024

Evidence cutoff: 2026-07-26 09:20 UTC

Primary classification: Windows downloader / loader

Technical lineage: Spyder, **Fighter** configuration branch

Public actor attribution: Patchwork; QiAnXin tracking designation APT-Q-36

Executive Summary

The original encrypted archive analyzed in this report was forwarded by a staff member from the office of a high-ranking Indian political figure and preserved unchanged. The political figure and source office are known to the author but are not named because doing so would not add to the technical findings.

The archive contained a signed 32-bit Windows downloader disguised as Logitech G HUB software. Its apparent size was 902,087,680 bytes, but only 2,077,184 bytes contained the functional PE image. The executable was expanded with exactly **900,000,000 zero bytes** before the Authenticode certificate was appended. Matching embedded and calculated digests establish that the padding was part of the signed packaging workflow rather than later corruption. [E1-E2]

The malware restores clean executable sections in ten loaded Windows system DLLs, creates five one-time scheduled tasks, and copies the entire padded file to %LOCALAPPDATA%\Screen_.exe. It collects a stable machine identifier, hostname, username, Windows version, and installed antivirus products. It is configured to communicate over unencrypted HTTP with `systembackupsvault[.]com`, placing modified-Base64 JSON in a custom `boop` request header. The server can instruct it to download a password-protected ZIP archive, extract each entry into the Windows Internet Cache, and attempt to launch the extracted files. [E3-E7]

The sample matches with high confidence the **Fighter**-configured Spyder downloader lineage described by QiAnXin in August 2024. The match includes the same profile value, registration schema, custom header, encoding, C2 paths, task schedule, encrypted-ZIP delivery model, DLL-restoration routine, and signing subject. QiAnXin attributes that lineage to Patchwork. This investigation independently establishes the technical lineage; the Patchwork association relies partly on QiAnXin's public actor attribution. [R1-R2]

During the analysis, the embedded C2 domain was found to have expired and become available. It was acquired defensively and redirected to a controlled sinkhole at **2026-07-16 10:25:46 UTC**. By **2026-07-26 09:20 UTC**, the sinkhole had received **11,534 requests from 748 unique IP addresses**. None matched the malware's distinctive `/soup/pencil.php` and `boop` protocol. The traffic was overwhelmingly generic Internet scanning. This produced no evidence of surviving callbacks to this domain during almost ten days of observation, but it does not prove that no infected systems or related infrastructure remain elsewhere. [E9]

The evidence supports high-confidence attribution to the Spyder family and **Fighter** lineage. It does not identify the human operator, the certificate-abuse mechanism, a contractor, a named government agency, or the sponsor of this specific operation. The confirmed targeting of a high-ranking Indian political office is noteworthy because public reporting commonly describes Patchwork as Indian or pro-Indian; the available evidence does not determine whether this reflects domestic collection, a separate operational customer, shared tooling, or limitations in existing cluster attribution.

Confidence terminology

Term	Meaning in this report
Certain	Directly observed and reproducible in the supplied sample or sinkhole records.
High confidence	Supported by several distinctive, mutually consistent observations.
Moderate	More likely than alternatives, but important evidence is missing.
Plausible	Compatible with the evidence but not established.
Unsupported	No affirmative evidence in this investigation.

1. Provenance, Scope, and Sample Overview

The encrypted delivery archive was forwarded by a staff member from the targeted political office. The archive was retained unchanged and analyzed without executing the malware. This report addresses the artifact, its technical lineage, and the infrastructure exposed by the binary. It does not attempt to reconstruct incident-response facts that were documented elsewhere.

Analysis included archive inspection, cryptographic hashing, PE and resource analysis, Authenticode extraction, import mapping, address-level disassembly, runtime-string decoding, Task Scheduler and WMI COM reconstruction, C2 protocol reconstruction, library identification, static cross-reference analysis, and defensive monitoring of the expired C2 domain.


Property	Value
Delivery filename	[Politically themed filename referencing the targeted office].exe
Archive protection	AES-256 encrypted ZIP
Full-file size	902,087,680 bytes
Full-file SHA-256	bfeee28529c186b266ad8bec29f7a866d9ff7bbfaf32959a37e4de1006bcad08
Functional PE size	2,077,184 bytes
PE-core SHA-256	1bdb5bf22d74756a4c9da7dea447a851cf15bb83f4072469ed9cc374a46070cd

Property	Value
Architecture	32-bit Intel Windows GUI executable
PE timestamp	2024-07-15 17:24:07 UTC (0x66955B37)
Linker	Microsoft linker version 14.0

The file contains no Rich header, debug directory, PDB path, or recoverable source-build path. This is consistent with metadata removal or a build workflow that did not retain those artifacts, but the sample does not distinguish between those explanations. [E1]

2. Packaging, Masquerade, and Signing

2.1 Exact signed-padding layout



Total: 902,087,680 bytes. Matching Authenticode digests show that the padding was present when the file was signed.

Signed file layout

The functional PE ends at file offset `0x001FB200` ; the certificate table begins at `0x35C49B00` and is 10,496 bytes long. The exact 900,000,000-byte gap is all-zero padding. Because Authenticode excludes the certificate table but covers the preceding file content, the matching digest proves that the padded structure was present when the executable was signed. [E1-E2]

This design provides a compact delivery artifact when compressed while producing a very large extracted executable. It can frustrate pipelines with file-size, upload, storage, or analysis-time limits. It also imposes costs on the malware: the 32-bit process attempts to allocate and copy roughly 902 MB into LocalAppData, which can fail on systems with constrained address space, memory, or disk capacity.

2.2 Logitech masquerade

The version resources claim Logitech G HUB identity, including Logitech, Inc., G HUB, Logitech G HUB System Tray, and logi_system_tray.app. The resource section includes Logitech-themed visual assets and a large WinUI manifest. The file is not signed by Logitech and its behavior is unrelated to G HUB. [E1]

Other camouflage is less coherent: the persistence copy is named `Screen_.exe` , the tasks use the `Screen_int` prefix, and the Task Scheduler author is ASUS . The mixture suggests reusable packaging and persistence templates rather than a single carefully consistent vendor imitation.

2.3 Code-signing identity

Property	Value
Subject	Xi'an Qinxuntao Network Technology Co., Ltd.
Corporate identifier	91610113MA6X13GR4H
Issuer	Certum Extended Validation Code Signing 2021 CA
Serial	7E62CF95CF6830668D5433052DC63A62
SHA-256 certificate fingerprint	58486F3B9B6F693C0685C6F3026D1C8A6621DBC72965F505B4A904A30934601D
Validity	2024-05-08 to 2025-05-08
Embedded countersignature time	2024-07-17 14:14:40 UTC

The `osslsigncode` verification run reported certificate expiry, while the embedded and calculated file digests matched. The historical validity of the countersignature chain was not independently established. [E2]

The certificate holder is an attribution pivot, not proof of Chinese operation. Plausible explanations include certificate or token compromise, fraudulent issuance, a shell entity, an insider, a signing service, or knowing participation. The sample does not distinguish among them.

3. Execution, Persistence, and Defense Evasion



Execution and C2 lifecycle

3.1 Restoration of system-DLL code

The malware maps clean System32 images and overwrites the loaded `.text` sections of ten DLLs:

`kernel32.dll`, `ntdll.dll`, `ADVAPI32.dll`, `SHELL32.dll`, `ole32.dll`, `OLEAUT32.dll`, `CRYPT32.dll`, `WS2_32.dll`, `WININET.dll`, and `bcrypt.dll`.

The routine uses `GetModuleHandleW`, maps the disk image with `SEC_IMAGE`, locates `.text`, changes the loaded section protection with `VirtualProtect`, copies the clean bytes, and restores the original protection. This can remove inline user-mode hooks installed by security products, sandboxes, or instrumentation. No claim is made that a particular commercial product was successfully bypassed. [E4]

The code incorrectly calls `FreeLibrary` on module handles obtained through `GetModuleHandleW`. This API-lifecycle mistake, together with other defects below, is useful as a source-lineage fingerprint.

3.2 Persistence copy and scheduled tasks

The malware constructs `%LOCALAPPDATA%\Screen_.exe`. It first attempts to delete and re-register five tasks that point to this path, then reads its own full padded executable and writes it to the destination. [E5]

Task	One-time boundary
Screen_int A	14:00
Screen_int B	15:00
Screen_int C	16:00
Screen_int D	17:00
Screen_int E	18:00

The tasks use `TASK_TRIGGER_TIME`, `TASK_CREATE_OR_UPDATE`, and `TASK_LOGON_INTERACTIVE_TOKEN`. The code calls `ITaskSettings::put_StartWhenAvailable(TRUE)`. Microsoft documents that this setting applies only to time-based tasks with an end boundary or tasks that repeat indefinitely; neither condition was established here, so its practical effect is uncertain. The code writes `PT5M` through `IdleSettings::put_WaitTimeout`, which is an idle-condition wait value rather than a repetition interval. `RestartOnIdle` is set, but Microsoft documents that it is used only when `StopOnIdleEnd` is true, which was not established. [R3-R6]

The five staggered boundaries are best interpreted as fallback execution opportunities. An earlier successful launch recreates the task set for a new date before later boundaries normally occur. This interpretation is based on the observed control flow rather than a documented operator statement.

3.3 Task-date defects

The malware obtains UTC time with `GetSystemTime` and constructs the boundary as:

```
<year>-<month>-<day + 1>T<hard-coded time>
```

It performs no calendar normalization. At month-end it may generate invalid dates such as `2024-07-32T14:00:00`. It also omits a UTC marker or offset. Microsoft documents that a `StartBoundary` without an offset uses the local computer's timezone and daylight-saving configuration. The malware therefore combines a UTC-derived date with local-time interpretation. [E5, R3]

3.4 Defective mutex

The implant creates the named mutex:

```
T9zDZZVxfMECyLHBw9dmMNzgZ24RwXL2p
```

It checks only whether `CreateMutexW` returned `NULL` and never tests `ERROR_ALREADY_EXISTS`. The mutex does not correctly enforce single-instance execution. [E5]

4. Host Profiling and Command-and-Control

4.1 Configuration

Field	Value
Version	0.0.0.1
Protocol	HTTP
Host	systembackupsvault[.]com
Base path	/soup/
Registration/poll endpoint	pencil.php
Payload endpoint	download.php?mname=
Poll delay	4,000 ms
Profile	Fighter

`Fighter` is build-time configuration sent to the server under `jupiter.profile`. It is not victim-derived. The value may represent a project, branch, campaign family, customer, operator channel, or backend-routing profile; the sample cannot determine which. [E3, E6]

4.2 Registration and profiling

The implant initially sends a base JSON object containing:


```
{
  "xidid": "<encoded MachineGuid>",
  "about": "<encoded 0.0.0.1>"
}
```

If the server responds with `1`, the malware gathers and temporarily adds:

```
{
  "jupiter": {
    "address": "<encoded fully qualified hostname>",
    "page_id": "<encoded username>",
    "weather": "<encoded Windows ProductName>",
    "profile": "<encoded Fighter>",
    "news": "<encoded antivirus-product data>"
  }
}
```

Antivirus information is obtained through WMI by connecting to `root\SecurityCenter2`, executing `SELECT * FROM AntiVirusProduct`, and reading each `displayName`. After the detailed registration is sent, `jupiter` is removed and the base object is reused for polling. [E6]

4.3 Wire protocol



C2 encoding and response handling

The verified C2 channel uses WinINet and an empty request body. JSON is Base64-encoded and then transformed:

```
+ -> .  
/ -> _  
= -> -
```

The result is carried in:

```
boop: <encoded JSON>
```

The hard-coded user agent impersonates Chrome 104 on macOS. A response of `0`, or any response no longer than five bytes, leads to a four-second sleep and another poll. A longer response is decoded as a task. [E3]

5. Payload Delivery

A decoded task contains `first`, `middle`, and `last` fields. The sample uses them as follows:

Field	Use in this build
<code>first</code>	Parsed numerically and acknowledged as <code>thread_id</code>
<code>middle</code>	Archive name and <code>mname</code> parameter
<code>last</code>	ZIP extraction password

The malware constructs:

```
hxxp://systembackupsvault[.]com/soup/download.php?mname=<middle>
```


It retrieves the archive with `URLOpenBlockingStreamW`, stores it as `%LOCALAPPDATA%\<middle>.zip`, and processes it with minizip-compatible routines and zlib code containing 1.3.1 version strings. Each archive entry is written to the Windows Internet Cache and passed to `CreateProcessW`. The code **attempts** to launch every entry; static analysis cannot establish that process creation succeeds. [E7]

The archive is deleted after processing, while extracted files remain. The malware then sends `thread_id`, removes it from the persistent JSON object, and resumes polling. The acknowledgement indicates completion of the downloader's extraction and launch attempts, not successful completion of a child payload.

The stage-one sample does not itself implement screenshot capture, file theft, credential theft, keylogging, ransomware, or an interactive shell. It is a modular delivery and profiling component; follow-on capabilities depend on server-selected payloads.

6. Defensive Reacquisition of the C2 Domain

Static analysis identified `systembackupsvault[.]com` as the configured C2 domain. Infrastructure checks showed that the registration had expired and the domain was available. It was acquired defensively and redirected to a controlled sinkhole beginning at **2026-07-16 10:25:46 UTC**. Current DNS and hosting data after that time describe the research sinkhole, not attacker infrastructure. [E9]



At the evidence cutoff, **2026-07-26 09:20 UTC**, the sinkhole had operated for 9 days, 22 hours, 54 minutes, and 14 seconds.

Metric	Result
Total requests	11,534
Unique source IPs	748
GET	11,450
HEAD	60
POST	24
Previous 24 hours	1,034 requests from 72 IPs
Requests matching the malware protocol	0

None of the requests matched the expected Spyder protocol: no confirmed implant request combined the relevant `/soup/` behavior, `boop` header, user agent, and encoded-message structure. The traffic was consistent with generic automated scanning. Country counts must not be interpreted as victim locations; several countries' totals were dominated by a small number of high-volume sources.

The sinkhole did not issue tasks or host payloads, and no matching callback or victim identifier was received. The result provides no evidence of active callbacks to this domain during the observation window. It cannot establish that no infected hosts remain, that no host uses cached historical infrastructure, or that other Spyder domains are inactive.

7. Comparison with QiAnXin's 2024 Spyder Research

QiAnXin published an August 2024 analysis of a Spyder downloader compiled on June 4, 2024 and attributed the activity to Patchwork / APT-Q-36. The present sample was compiled approximately 41 days later. Direct binary diffing was not possible, so the comparison is limited to behavior and artifacts documented in the public report. [R1]

Stable lineage features	Sample-specific or deployment changes
Fighter profile and 0.0.0.1 version	C2 changed from <code>onlinecsstutorials[.]com</code> to <code>systembackupsvault[.]com</code>
<code>xidid</code> , <code>about</code> , and <code>jupiter</code> schema	Mutex changed
<code>address</code> , <code>page_id</code> , <code>weather</code> , <code>profile</code> , <code>news</code>	Copy name changed from <code>zlib1.exe</code> to <code>Screen_.exe</code>
<code>boop</code> header and modified Base64	Task prefix changed from <code>zlib data compression</code> to <code>Screen_int</code>
<code>/soup/pencil.php</code> and <code>download.php?mname=</code>	Logitech resources and ASUS task author

Stable lineage features	Sample-specific or deployment changes
Five one-time task times, 14:00-18:00	Political lure and encrypted delivery archive
Password-protected ZIP delivery and Internet Cache staging	Exact 900,000,000-byte signed padding documented in this sample
Ten-DLL .text restoration	Published decoy URLs present but no static references recovered
Same signing subject	<code>first</code> observed as acknowledgement <code>thread_id</code>

The stability of the protocol, task template, profile value, and source-level quirks establishes a common technical lineage. The changed domain, mutex, persistence names, task metadata, and masquerade are consistent with campaign or build configuration.

QiAnXin reported active decoy requests to GitHub and Google endpoints. The same literal URLs are present in this binary, but Ghidra cross-reference analysis and direct disassembly searches recovered no static references. They are therefore assessed with high confidence as inactive data in this build, while acknowledging that static analysis cannot absolutely exclude a computed or indirect reference. Their persistence is consistent with source-tree or linked-library residue. [E8, R1]

QiAnXin also observed screenshot and file-information collection components delivered by Spyder. Those findings establish capabilities used in the broader lineage, not payloads delivered by this particular C2. No follow-on component from `systembackupsvault[.]com` was recovered.

8. Attribution Assessment

8.1 Technical lineage

The sample belongs to Spyder and the `Fighter` configuration lineage with high confidence. The conclusion rests on an unusually specific protocol and implementation fingerprint rather than generic techniques.

8.2 Patchwork association

The sample matches with high confidence the Spyder lineage that QiAnXin attributes to Patchwork. The resulting Patchwork association is strong but partly inherited from that public actor attribution; this investigation independently proves the technical match, not the identity of the operators. MITRE describes Patchwork as a cyber-espionage group whose attribution is not definitive, while noting circumstantial evidence of an Indian or pro-Indian nexus. [R1-R2]

8.3 Confirmed Indian political targeting

The archive's provenance establishes that a high-ranking Indian political office was targeted. This is analytically important because public reporting commonly presents Patchwork as Indian or pro-Indian. Possible explanations include domestic political collection, use of Spyder by a separate customer or team, shared development or infrastructure suppliers, or limitations in existing actor-cluster attribution. The sample does not distinguish among them.

8.4 Signer and developer implications

The Chinese certificate subject is not evidence of Chinese sponsorship. Exact certificate pivots and the corporate identifier may reveal a compromised subscriber, fraudulent issuance, broker, shell company, or supplier, but this investigation does not resolve the relationship.

A distinctive developer or builder fingerprint emerges from the combination of:

- positional TLS-backed XOR string initialization;
- the custom Base64 alphabet and `boop` protocol;
- the `jupiter` schema and `Fighter` profile;
- ten-DLL `.text` restoration;
- `FreeLibrary(GetModuleHandleW(...))` misuse;
- defective mutex handling;
- five one-time tasks with naive `day + 1` construction;
- UTC/local boundary mismatch;
- manual whole-file self-copy;
- encrypted multi-entry ZIP execution;
- dead CPR/libcurl-related URL data;
- and exact 900,000,000-byte signed padding.

These features can support future sample clustering. They do not identify a named person or organization.

8.5 Attribution conclusion

Layer	Assessment
Malicious downloader behavior	Certain
Spyder family	High confidence
<code>Fighter</code> lineage	High confidence
Match to QiAnXin's documented variant	High confidence
Patchwork association	Strong; conditional in part on QiAnXin's attribution
Indian/pro-Indian nexus	Contextual, not independently proven by this sample
Same individual developer	Unresolved
Certificate holder's role	Unresolved

Layer	Assessment
Named agency or government sponsor	Unsupported

9. Conclusion

The analyzed artifact is a signed, deliberately oversized Windows downloader from the `Fighter`-configured `Spyder` lineage. It was supplied from a confirmed high-ranking Indian political target, combines a political lure with Logitech masquerade, establishes scheduled-task persistence, profiles the host and its security products, and uses a distinctive custom HTTP protocol to obtain encrypted follow-on payloads.

The strongest attribution finding is technical: the sample matches the `Spyder` lineage documented by QiAnXin with high confidence. Its association with Patchwork is strong but depends partly on QiAnXin's actor attribution. The confirmed Indian political victimology introduces an important tension with the usual Indian/pro-Indian characterization of Patchwork and may indicate domestic collection, shared tooling, multiple customers, or an incomplete public cluster model.

The defensive reacquisition of the expired C2 domain added a rare operational observation. Nearly ten days of sinkhole monitoring produced 11,534 requests but no traffic matching the malware protocol. That result narrows the current activity assessment for this specific domain without supporting broader claims that the campaign or all infections are inactive.

The sample does not reveal the human operator, sponsor, certificate-abuse mechanism, or payloads assigned to this target. Those questions require external delivery, certificate, provider, infrastructure, or law-enforcement evidence rather than further interpretation of this binary alone.

Appendices

Appendix A - Indicators

Files and certificate

Type	Value
Full-file SHA-256	bfeee28529c186b266ad8bec29f7a866d9ff7bbfaf32959a37e4de1006bcad08
PE-core SHA-256	1bdb5bf22d74756a4c9da7dea447a851cf15bb83f4072469ed9cc374a46070cd
PE-core SHA-1	f1ec0f60df9b5f63bc7f2fd18f3247e8d0341702
PE-core MD5	b0838f6aa79f5b7554d76d097cfb80b3
Persistence file	%LOCALAPPDATA%\Screen_.exe
Exact padding	900,000,000 zero bytes
Certificate serial	7E62CF95CF6830668D5433052DC63A62
Certificate SHA-256	58486F3B9B6F693C0685C6F3026D1C8A6621DBC72965F505B4A904A30934601D

Network and host

Type	Value
C2 domain	systembackupsvault[.]com
Registration/poll path	/soup/pencil.php
Payload path	/soup/download.php?mname=
Header	boop
Poll interval	4 seconds
Mutex	T9zDZZVxfMECyLHBrw9dmMNzgz24RWxL2p
Tasks	Screen_int A through Screen_int E
Task author	ASUS
WMI namespace	root\SecurityCenter2
WMI query	SELECT * FROM AntiVirusProduct

Appendix B - ATT&CK Mapping

Technique	ID	Evidence
User Execution: Malicious File	T1204.002	Encrypted archive and deceptive executable filename
Masquerading	T1036	Logitech identity and utility-themed task names
Code Signing	T1553.002	Signed malicious executable
Binary Padding	T1027.001	Exact 900,000,000-byte padding
Obfuscated Files or Information	T1027	Encoded strings and modified Base64
Scheduled Task/Job: Scheduled Task	T1053.005	Five COM-created time triggers
Query Registry	T1012	MachineGuid and ProductName
System Owner/User Discovery	T1033	GetUserNameW
System Information Discovery	T1082	Hostname and Windows product information
Security Software Discovery	T1518.001	WMI antivirus enumeration
Application Layer Protocol: Web Protocols	T1071.001	HTTP C2
Data Encoding	T1132.001	Base64 with custom substitutions
Ingress Tool Transfer	T1105	Remote encrypted-ZIP retrieval
Deobfuscate/Decode Files	T1140	Password-protected ZIP extraction
Impair Defenses	T1562.001	Replacement of loaded DLL .text sections
File Deletion	T1070.004	Downloaded archive deletion

Appendix C - Key Functions

Address	Analytical label	Role
0x401000	Encoder	Base64 and custom substitutions
0x4015B0	DLL restorer	Replaces loaded .text sections
0x401800	WinINet POST	Registration, polling, acknowledgement
0x401950	URLMon downloader	Retrieves payload archive
0x401A40	Registry reader	MachineGuid and ProductName

Address	Analytical label	Role
0x401AE0	Task builder	Creates one-time scheduled tasks
0x402700	Configuration initializer	C2 and profile structure
0x402B30	WMI collector	Antivirus-product enumeration
0x402F30	Payload handler	Write, extract, launch, cleanup
0x403260	Main orchestration	Startup, persistence, C2, polling

Appendix D - Evidence Index

ID	Finding group	Primary basis
E1	Sample identity, PE metadata, resources, padding	Original archive, full file, PE-core extraction, PE parsing
E2	Signature and certificate	Authenticode extraction and osslsigncode output
E3	Configuration and C2	Function 0x402700; WinINet routine 0x401800; decoded constants
E4	DLL restoration	Function 0x4015B0; API mapping and section-name confirmation
E5	Persistence and task semantics	Function 0x401AE0; five call sites; COM vtable mapping
E6	Registration and profiling	Main control flow; WMI function 0x402B30; decoded JSON keys
E7	Payload delivery	URLMon routine 0x401950; payload function 0x402F30
E8	Inactive URL assessment	Ghidra XREF output and direct disassembly-reference search
E9	Sinkhole	Controlled-domain HTTP logs through 2026-07-26 09:20 UTC
E10	Provenance	Original unchanged archive forwarded by staff from targeted office

References

- **R1.** [QiAnXin Threat Intelligence Center - Analysis of New Variants and Subsequent Components of Patchwork Spyder Downloader](#), 23 August 2024.
- **R2.** [MITRE ATT&CK - Patchwork, G0040](#).
- **R3.** [Microsoft - ITrigger::put_StartBoundary](#).

- **R4.** [Microsoft - ITaskSettings::put_StartWhenAvailable.](#)
- **R5.** [Microsoft - IIdleSettings::put_RestartOnIdle.](#)
- **R6.** [Microsoft - IIdleSettings::put_WaitTimeout.](#)
- **R7.** [MITRE ATT&CK - User Execution: Malicious File, T1204.002.](#)