archive-index: private hybrid and multimodal search over personal research archives in Ukrainian and Russian, with the UA-PAR benchmark

Oleksandr Pylypenko
ORCID: 0009-0004-9610-9242
op1@cyberunit.tech, limblucifer666@gmail.com

Research draft — 22 October 2026

Abstract

We study local search over a heterogeneous research archive in Ukrainian and Russian, combining SQLite BM25 with lemma expansion, dense text retrieval and multimodal embeddings. UA-PAR provides 7 070 public-source files, 200 model-written queries and 5 572 pooled query–document pairs assessed by multiple language models. On the 170 answerable queries, mean nDCG@10 under the primary reviewed Gemini labels is 0.674 for multilingual-E5, 0.633 for EmbeddingGemma 2, 0.629 for adaptive fusion, 0.482 for lemmatized BM25 and 0.450 for plain BM25. Adaptive fusion exceeds BM25 after Holm correction, but has no demonstrated advantage over dense EG2 or reciprocal-rank fusion. The evidence for the lemma gain depends on the relevance judge. A control on identical text candidates changes EG2's score by less than 0.002. A separate 50-record extension targets documents, tables and repository files; with initial Gemini labels, EG2 and adaptive fusion score 0.759 and 0.756, versus 0.721 for E5. Separate image and speech tasks use source-dataset labels; costs are measured on one laptop, and a private-archive study exports operational aggregates only. All original answerable-query targets are notes, relevance is model-assessed, and no completed human relevance audit is claimed. These conditions bound the conclusions about retrieval effectiveness.

Keywords: information retrieval; hybrid search; BM25; dense retrieval; morphology; Ukrainian; Russian; multimodal retrieval; personal information management; benchmark; LLM relevance judgements.

AI involvement. The original 200 benchmark queries were written by GPT-6-Luna (OpenAI, through the Codex CLI) under the rules of Section 4; the separate 50-record extension was written by Qwen3.8 27B through local Ollama; Gemini 3.8 Flash is the primary relevance judge, Gemma 4 12B provides a sensitivity assessment, and Gemma 4 E4B provides an ancillary assessment. A separate Gemini pass reviews disagreements with Gemma 4 12B; this is a within-model review, not independent adjudication. GPT grades are reported only for comparison and do not enter the relevance labels; the code was written by the author together with Claude and Codex. The author approved the study design and is responsible for every claim. No completed human relevance audit is claimed. The primary judge was selected after inspection of judge diagnostics and before calculation of retrieval rankings; Gemini and Gemma share a provider. No AI system is an author.

1 Introduction

1.1 Motivation

A researcher's archive is not a document collection in the usual sense. It mixes notes, rendered papers, spreadsheets, source code, Git history, logs of experiments, conversations with coding agents, photographs and recordings; it is written in more than one language; and it is private, so it cannot be sent to a hosted search service. In Ukraine, notes and documents are routinely written in Ukrainian and Russian side by side, both highly inflected, so a search for a word form often misses the document that uses another form of the same word. People also look for documents they remember only vaguely: by a topic, by what a figure showed, by a sentence somebody said in a recording.

archive-index is a local search engine built for this setting (Section 3). It combines SQLite FTS5/BM25 over words and their Ukrainian and Russian lemmas with EmbeddingGemma 2 vectors for text, pictures and sound, and it chooses between an exact-phrase regime and a meaning-first regime per query. This paper asks how well such a system retrieves, which of its parts matter, what it costs, and how far its evaluation can be trusted when no human relevance judgements are available.

1.2 What is evaluated

Evidence is kept at four levels and the levels are never mixed: (L1) implementation behaviour, established by unit and integration tests; (L2) retrieval effectiveness on UA-PAR, a public benchmark built for this paper, with relevance labels from language-model judges (Sections 4–6); (L3) behaviour on the author's private archive, reported only as aggregates (Section 7); (L4) measurements of latency, memory and CPU/GPU use on one laptop (Section 6). Text-to-image and text-to-speech retrieval are measured separately on the human-labelled Crossmodal-3600 and FLEURS data.

1.3 Out of scope

The paper does not train or fine-tune any model, does not propose a new embedding method, and does not claim that model-made relevance labels equal human ones. The public benchmark evaluates about 10^5 chunks on one hardware configuration; the separate field study reports operational checks on one larger private archive. Systematic scaling beyond the public collection uses synthetic vectors. Languages other than Ukrainian and Russian (and the English found in code) are not evaluated. The privacy measures of Section 3 are described, not certified.

1.4 Contributions

(a) *A system.* archive-index: incremental local indexing of twelve collections of sources into one SQLite database, Ukrainian/Russian lemmas, identifier phrases, and one embedding space for text, pictures and sound. *Not claimed:* novelty of any single component.

(b) *A benchmark.* UA-PAR: 7 070 openly licensed files (notes, rendered documents, tables, code, pictures, speech), 200 queries in five categories, and graded labels for all 5 572 pairs of the depth-10 pool of ten systems, from four model judges with call logs. *Not claimed:* human gold labels; every query target is a note.

(c) *A measured comparison.* Ten systems and their ablations, with query-level bootstrap intervals and Holm-corrected paired tests, under several label variants, plus controls for the candidate universe and for a coverage defect. *Not claimed:* an advantage of the adaptive fusion; the measurements do not show one.

(d) *Morphology.* A defect in cross-language lemma guessing, its correction, and the measured effect of lemmas on BM25. *Not claimed:* an effect independent of the relevance judge.

(e) *A judging procedure.* Several judges from different providers, the query-writing model kept out of the labels, a separate within-model review of disagreements, known-answer checks, and the sensitivity of system rankings to the judge. *Not claimed:* a substitute for the human audit, which is prepared but reported only when done.

(f) *Costs.* Query latency on GPU and CPU with per-core and per-thread CPU use, indexing throughput, the retrieval quality of quantized GGUF builds, and the point where exact dense search becomes expensive. *Not claimed:* results for other hardware.

1.5 History of revisions and withdrawals

The study found defects in our own tools. Each was fixed with a test that reproduced it; none is hidden in the results.

1. *Lemmas invented by the other language's analyzer.* Words without Ukrainian-only letters went through both analyzers, and the one that did not know the word invented a lemma (*навчанню*→*навчанність*). In the first target-document diagnostic, lemmatized BM25 found the target in the top 10 for 45.3% of the answerable queries against 49.4% without lemmas; after the fix it found 50.0%. All reported runs use the fixed analyzer.

2. *Rebuilt terms differed from indexed terms* for pictures and sound, so an ablation index made by rebuilding terms was not identical to one built from scratch. Fixed before the runs used here.

3. *A relative corpus path* stored documents twice in an ablation index. Caught and fixed before any run was evaluated.

4. *Heading-only judge snippets.* In the first judging sheet, 393 of 5 572 pairs showed the judge under 200 characters, mostly a title and a source line. The snippet was changed to the beginning of the document before any judging was used.

5. *Query authorship.* The first query file named Claude as the author of queries that GPT-6-Luna wrote; it was corrected before judging, and GPT grades were then kept out of the labels.

6. *Substring coverage in the adaptive rule.* The test for an exact phrase counted substrings (`36` inside `1366`). It was found after the runs were frozen; the frozen runs are reported and the corrected rule is reported beside them (it changes the top 10 for one query of 200).

7. *Change of relevance protocol.* The plan named Claude as the primary judge. After the judge diagnostics and before any system ranking was computed, the author chose Gemini as the primary judge. A later partial Claude pass is deferred at the author's request and is excluded from all reported analyses. This is a post hoc decision and is reported as one.

2 Related work

Lexical, dense and hybrid retrieval. BM25, derived from the probabilistic relevance framework, remains the standard lexical ranking function [19]; archive-index uses the BM25 ranking built into SQLite FTS5 [2]. Dense retrieval encodes queries and documents with neural encoders and ranks by vector similarity [11, 18]. The BEIR benchmark found BM25 to be a robust zero-shot baseline across heterogeneous tasks and reported that dense models often underperformed

other approaches out of domain [23]. Hybrid systems combine the two kinds of ranking; reciprocal rank fusion is a simple, training-free way to merge ranked lists [5]. The adaptive rule studied here differs from score or rank fusion: it chooses between an exact-phrase regime and a meaning-first regime from the coverage of the best lexical match (Section 3).

Embedding models. EmbeddingGemma is an open text embedding model of about 300M parameters built from Gemma 3 and evaluated on MTEB [21]; this paper uses its successor, EmbeddingGemma 2, as released on Hugging Face with prompts and precision guidance in its model card [9]. Matryoshka representation learning trains embeddings whose prefixes remain usable at lower dimension [14], which motivates the 256-dimensional variant. Multilingual E5 is a family of open multilingual text embedding models trained by contrastive pre-training on about one billion multilingual text pairs followed by supervised fine-tuning [26]; its large model is the second dense baseline. Joint text–image embedding spaces were popularized by CLIP [17]; here text, pictures and speech share the EmbeddingGemma 2 space.

Ukrainian and Russian. Ukrainian and Russian are highly inflected; matching surface forms alone can miss documents that use other forms of a query term. pymorphy2 provides dictionary-based morphological analysis for both languages [13]; archive-index uses its maintained fork pymorphy3 [1]. Public multilingual retrieval benchmarks such as MIRACL cover many languages with human relevance judgements [27], whereas UA-PAR combines mixed document formats, repository files, Ukrainian and Russian, and queries describing a remembered document. This is a deliberately constructed archive setting, not a representative sample of personal archives. UA-PAR is built for that setting (Section 4).

Multimodal evaluation data. Crossmodal-3600 provides 3 600 geographically diverse images with human captions in 36 languages, written without translation [24]; FLEURS provides n-way parallel speech in 102 languages, built on the FLoRes-101 sentences [4]. We use their Ukrainian and Russian parts as human-labelled ground truth for text-to-image and text-to-speech retrieval.

Evaluation with incomplete and model-made judgements. nDCG with graded gains follows Järvelin and Kekäläinen [10]; we compute it with ir-measures [15]. Depth-k pooling leaves documents outside the pool unjudged; condensed-list evaluation, which drops unjudged documents from a run, is one standard way to check how much that matters [20]. For significance we use paired randomization and bootstrap procedures of the kind compared by Smucker et al. [22], and linear-weighted kappa for agreement on an ordinal scale [3]. Large language models have been studied as relevance assessors, with reports that they can predict searcher preferences well [25] and with discussion of the risks of replacing human assessors [8]. This paper uses several model judges from different providers, keeps the query-writing model out of the labels, and reports how system rankings change with the judge.

Personal information management. Desktop search over a person's own files was studied in Stuff I've Seen, which unified access to previously seen e-mail, files and web pages [7]. archive-index shares that goal but adds research-specific sources (code, agent sessions, run logs), multimodal content, two inflected languages, and a measured comparison of ranking strategies. Approximate nearest-neighbour indexes such as HNSW [16] and the Faiss library [6] provide approximate vector search; archive-index searches exactly, and Section 6 measures where that choice stops being cheap.

3 The archive-index system

3.1 Architecture and data flow

archive-index keeps one SQLite database per archive. A `documents` table records each source file (collection, path, size, modification time, SHA-256, title, project); a `chunks` table holds the text fragments with their locator (page, slide, time window, frame), the embedding vector as a binary blob, and a hash of the text that produced the vector. An FTS5 virtual table indexes three columns of each chunk: the word terms described below, the body and the heading, with the `unicode61` tokenizer and diacritics kept. The database runs in write-ahead-log mode, so the terminal interface, the scheduled indexing jobs and ad hoc searches can read while the indexer writes.

Sources are grouped into collections: Markdown notes (`wiki`); office documents and PDF (`docs`, with `.doc`, `.rtf`, `.odt`, `.ppt` and `.odp` converted through LibreOffice); spreadsheets and CSV (`tables`); Git history; Claude and Codex agent sessions; run logs; pictures; sound; and video. Source code, configuration and log files are opt-in collections searched only when named. Markdown is split at headings and packed paragraph by paragraph into chunks of at most 1 200 characters; a longer paragraph is split hard at that length.

3.2 Lexical layer

Words are runs of Unicode letters and digits that may be joined by a hyphen or an apostrophe, at least two characters long, lower-cased. The four apostrophe characters used in Ukrainian text (U+2019, U+02BC, U+2018 and the backtick) are mapped to the ASCII apostrophe before tokenization, so that *м'ята* and *м'ята* are one word. The FTS `terms` column stores every word followed by its normal forms from the pymorphy3 Ukrainian and Russian analyzers. A word containing a letter that exists only in Ukrainian (і, ї, є, ґ) goes through the Ukrainian analyzer only; other words go through both. When a dictionary knows the word, only dictionary normal forms are kept; the analyzers' guesses are used only for words that neither dictionary knows (Section 1.5 describes the defect that this rule corrects).

Identifiers such as `36.101`, `19.6.0` or `RVZ0014A-2` (letter and digit runs joined by dots or slashes, or a hyphen followed by a digit) are matched as exact phrases, so a query for `36.109` never matches a document that contains only `36`. A query becomes an FTS5 expression in which each word is a disjunction of its surface and normal forms, the words are joined by OR, and an identifier clause, if present, is joined to the words by AND. Lexical ranking is FTS5 BM25.

3.3 Dense layer

The dense layer uses EmbeddingGemma 2 through SentenceTransformers, in bfloat16 on a GPU (the model card warns that float16 degrades the embeddings) and in float32 on a CPU. Documents are embedded as `title: <title> | text: <chunk>`; queries carry the model's retrieval prompt `task: search result | query:`, or `task: code retrieval | query:` when the code collection is searched. Vectors are L2-normalized; the 256-dimensional variant truncates them (Matryoshka truncation) and normalizes again. Pictures, PDF pages without a text layer and video frames (one every 5 s, at most 120 per video) are embedded as images in the same space. Sound is resampled to 16 kHz and embedded in 20 s windows with a 15 s step; when a transcript file accompanies a recording, the transcript lines that overlap a window become that window's text. A llama.cpp server running a GGUF build of the model is an optional text-only backend. Semantic search is exact: all vectors are held in memory and scored with one NumPy matrix–vector product, with no approximate nearest-neighbour index.




Figure 1: Indexing and search data flow with the default local backend. Text redaction applies known patterns; images and audio are not content-redacted. Numeric-only chunks remain available to lexical search without vectors. Document collapse belongs to the benchmark, outside the query timer.

3.4 Fusion

Three ranking modes are available: lexical only, semantic only and hybrid. The default hybrid strategy (adaptive) looks at the best lexical chunk. If it contains at least 90% of the query words as whole words, the query is treated as a search for an exact phrase: only lexical results are returned, in BM25 order, except that chunks in which the query words occur in order within a slack of three words are moved to the front. Otherwise the semantic ranking comes first and the lexical results that it does not already contain follow; with no lexical match the result is purely semantic. Reciprocal-rank fusion with $k = 60$ (rrf) is the alternative hybrid strategy. In the interface, at most three chunks per document are shown, with a count of the remaining ones; benchmark runs collapse chunks to documents (Section 5).

3.5 Incremental indexing

A file is skipped when its size and modification time are unchanged, and also when its SHA-256 is unchanged; only then is it parsed again. Vectors are reused for chunks whose text hash is already stored, so editing a note re-embeds only the edited chunks. Files that disappeared are removed from their collection. Fragments of notes and documents with fewer than 20 letters (page numbers, punctuation) are dropped unless every fragment of the file is that short; pictures and sound are never dropped. Each run writes a report of indexed, skipped and failed files; a failure in one file does not stop the run.

3.6 Privacy

The default embedding backend processes document content locally. The optional llama.cpp client defaults to a loopback server; configuring an external `ARCHIVE_LLAMA_URL` sends text to that endpoint. Local processing therefore depends on the backend configuration. Directories `.ssh`, `.gnupg`, `.aws`, `.kube`, `.password-store`, `.docker` and key rings, and files whose names match key, certificate, password-store, environment and credential patterns (for example `*.pem`, `*.kdbx`, `id_rsa*`, `.env`, `*secret*`, `*token*`) never enter the index. Inside indexed text, PEM private-key blocks, access keys in the formats of several common services (OpenAI, AWS, GitHub, Slack, bearer tokens) and explicit credential assignments such as `password=...` are replaced by a redaction marker before storage. The patterns cover known formats only; they are a safety net, not a guarantee. The redaction report counts kinds and never stores values.

4 The UA-PAR benchmark

4.1 Sources and corpus

UA-PAR imitates a researcher's archive with openly licensed material in Ukrainian and Russian (licences in Section 10). The corpus has 7 070 files in six parts. *Notes*: 2 945 Wikipedia articles (1 960 Ukrainian, 985 Russian) on 25 topics, many of them technical, among them antennas, radio, LTE, software-defined radio, signal processing, microcontrollers, cryptography, machine learning, physics, history and literature; each article is stored as a Markdown note with its source line. *Documents*: 400 further articles (260 Ukrainian, 140 Russian) rendered to 133 PDF, 134 DOCX and 133 PPTX files, so the archive has office formats. *Tables*: 150 data.gov.ua datasets, 100 kept as CSV and 50 converted to XLSX. *Code*: 1 775 files from 30 Ukrainian-topic GitHub repositories, indexed as a code collection. *Pictures*: 1 000 Crossmodal-3600 images. *Speech*: 800 FLEURS recordings, 400 Ukrainian and 400 Russian. The articles were collected by topic search with a page-and-resume collector; the SDR topic did not have enough long articles, so the notes are 55 short of the planned 3 000 rather than padded with weakly related articles.

Not every collected file is indexable: archive-index skips generated and vendored files in repositories, so the full EG2 index holds 6 054 documents (759 from the code part) and 96 908

chunks. The text-only E5 index holds the 4 137 text documents of the same corpus and no pictures or speech; Section 6 shows that restricting EG2 to the same 4 137 documents changes its nDCG@10 by −0.0015.

4.2 Queries

There are 200 queries in five categories with fixed quotas: 40 *known-item* queries describing a specific document without quoting its title; 60 *topical* queries that several documents may answer; 40 *technical* queries containing identifiers, model numbers or standards as people write them; 30 *cross-lingual* queries in Russian for a Ukrainian target or the reverse; and 30 *no-answer* queries, plausible questions about things the corpus does not contain, often with invented model numbers. 126 queries are in Ukrainian and 74 in Russian. The 170 answerable queries were each written for one target note, which is recorded but is not the only relevant document. A validator checks the quotas and language shares, that every target exists, that no topical or cross-lingual query shares a run of more than five consecutive tokens with its target (no copying), and that every no-answer query has zero lexical matches in the index. All 200 queries pass.

The queries were written by GPT-6-Luna through the Codex CLI under these rules. Because the query writer must not grade its own queries, GPT grades never enter the relevance labels; they are used only to compare grading behaviour, which does not separate self-preference from general leniency (Section 6). The no-answer queries have no lexical match by construction, so BM25 returns nothing for them; the comparison of systems on these queries is therefore a check of whether a dense system ever abstains, not a fair contest between lexical and dense retrieval.

4.3 Relevance assessments

The assessment pool is the union of the first ten documents returned by each of the ten systems: 5 572 query–document pairs for 200 queries. Separate shuffled sheets hide the retrieval system identities. Each judge sees the query, document title and beginning, limited to 1 200 characters; speech records include the source transcript. Grades are 0 (unrelated), 1 (partly relevant) and 2 (directly answers the query). These labels describe the visible snippet rather than an inspection of the complete document.

The initial primary judge is Gemini 3.8 Flash, invoked through `agy` in batches of 50. Gemma 4 12B through Ollama provides the main sensitivity assessment, and Gemma 4 E4B provides an ancillary open-weights assessment. GPT-6-Luna authored the queries; its grades are reported only for comparison and never enter the primary or sensitivity relevance labels. All initial sheets are preserved. Gemini and Gemma share a provider, so separate grading does not establish independence of training data or errors.

Initial Gemini and Gemma 4 12B disagree on 1 091 pairs. For the reviewed variant, a separate Gemini pass reassesses those pairs with both initial grades visible under neutral A/B labels, balanced in presentation order. Agreed grades are retained. This is a within-model review, not independent third-judge adjudication. Retrieval results are compared across initial Gemini, initial Gemma 4 12B and reviewed Gemini. The choice of the primary judge followed inspection of agreement and target/no-answer diagnostics and preceded calculation of retrieval rankings; it was not preregistered. No completed human relevance audit is claimed.

All 170 answerable query targets are notes, and 134 targets occur in the depth-10 pool. Consequently, target-grade diagnostics use a denominator of 134 and do not measure accuracy on the complete target set. The 30 designated no-answer queries are analysed separately.

4.4 Multimodal subsets

Text-to-image and text-to-speech retrieval are evaluated outside the pooled benchmark, with human labels from the source datasets. For pictures, the query is the first Ukrainian or Russian

Crossmodal-3600 caption of an image, and the gold item is that image among all 1 000. For speech, the query is the FLEURS transcript of a sentence and the gold items are the recordings of that sentence; FLEURS is n-way parallel, so a Russian transcript can query Ukrainian recordings of the same sentence and the reverse. Each condition is scored three ways: against the audio vector of a recording, against its transcript embedded as text, and against the better of the two. When the query is the transcript of the recording itself, the text and combined scores are an upper bound, not a retrieval result; the audio-only and cross-lingual conditions carry the claims.

5 Evaluation methodology

5.1 Systems and units

All systems use the same archive-index search implementation with explicit configuration switches. The comparison includes plain and lemmatized BM25, full-dimensional EmbeddingGemma 2, a 256-dimensional EG2 variant, multilingual-E5, reciprocal-rank fusion, the adaptive system and three ablations removing phrase reranking, identifier handling or short-fragment filtering. Runs are document-level: the first retrieved chunk determines each document's rank, and subsequent chunks of that document are collapsed. Up to 100 documents are retained per query. The E5 index is text-only, unlike the full EG2 indexes; the differing candidate universes are reported as a limitation.

5.2 Query population and metrics

Retrieval means use the same 170 answerable queries for every system and judge variant, with each query weighted equally. The 30 designated no-answer queries are retained in the relevance files but excluded from those means; empty retrieval and positive-labelled results on them are reported separately. An answerable query with no positive pooled judgement remains in the average with score zero.

The primary metric is nDCG@10, using linear relevance gains 0, 1 and 2, discounted by $\log_2(i+1)$ at rank i and normalized by the ideal ranking of the judged documents. Secondary metrics are reciprocal rank at 10, success at 1 and 5, and recall at 100. Binary metrics treat grades 1 and 2 as relevant. Every system's retrieved top-10 documents are judged, but judgements outside the depth-10 union are incomplete. Recall at 100 is therefore relative to the known relevant pool, not exhaustive corpus recall. Results are also grouped by query category and language.

5.3 Uncertainty and comparisons

Confidence intervals for query means and paired mean differences use a percentile bootstrap over queries with 10 000 resamples and seed 2026. Two-sided paired sign-flip randomization tests use 10 000 resamples and the add-one correction $(b+1)/(10\,000+1)$. Each metric and judge variant has a family of nine comparisons against the full adaptive system; p-values receive Holm adjustment within that family, with threshold 0.05. The original morphology research question is additionally assessed by a separately labelled paired lemma-versus-plain BM25 contrast on nDCG@10; its unadjusted p-value is not part of the adaptive comparison family. Neither separate confidence-interval overlap nor failure to reject a difference is interpreted as equivalence.

The initial inter-judge agreement report uses linear-weighted Cohen's kappa with a 95% interval from 2 000 query-level bootstrap resamples. Resampling queries, rather than individual judgement pairs, preserves within-query clustering. These agreement intervals are separate from the 10 000-resample retrieval intervals. Rankings and pairwise ordering changes are reported for each relevance variant; numerically equal means within 10^{-12} share a rank.

5.4 Reproducibility and evidence

Initial judgement sheets, query definitions, corpus manifest, retrieval runs and available call logs are frozen before retrieval rankings are computed. A SHA-256 manifest validates those inputs; a separate prepared-review record binds the review to its original disagreements and presentation order. Structured call responses are logged with model, conversation and usage metadata when available. Canonical labels replace only disagreement grades after complete review, preserving every agreed grade. Report tables and figures are generated from the resulting JSON artifacts rather than maintained as independent numerical copies.

Unit and integration checks establish implementation behaviour; the public benchmark provides model-labelled retrieval evidence; the separate multimodal experiments use source-dataset labels. These evidence types do not substitute for a human relevance audit or deployment measurements.

5.5 Resource measurements

Query latency is the wall time of query embedding and chunk search in the evaluation harness, including lexical and semantic retrieval and fusion with a candidate limit of 400 chunks. The timer stops before document collapse and path resolution; these measurements are not end-to-end interface latency. Each system answers all 200 queries once as a warm-up and then once more under measurement, in one process, first with the GPU visible and then with `CUDA_VISIBLE_DEVICES` empty (the embedding models then run on the CPU in float32). During each measured pass the harness records per-core CPU use from `/proc/stat`, CPU seconds per thread of the process from `/proc/self/task`, the change in interrupt counts per core from `/proc/interrupts`, the peak resident set size, and GPU memory sampled every 0.2 s with `nvidia-smi`. The machine was an ordinary desktop session; the one-minute load average before each step is written to the measurement log.

Indexing cost is measured on a fixed random sample of the corpus (seed 2026: 300 notes, 40 documents, 15 tables, 60 pictures and 60 recordings) indexed by the `archive` command into an empty database with the GPU. The CPU run uses a fifth-sized sample: 60 notes, 8 documents, 3 tables, 12 pictures and 12 recordings. The two samples differ in size and composition, so their wall times do not estimate a paired CPU/GPU speedup. The sizes of the four full benchmark indexes are reported as built.

For quantization, the text chunks of the full index (84 788 vectorized rows in text collections) are embedded again by GGUF builds of EmbeddingGemma 2 (f16, Q8_0, Q4_K_M) served by llama.cpp with mean pooling, with the same `title: … | text: …` prefixes; queries use the same retrieval prompt. Dense retrieval with each build runs on the 4 137 text documents and is compared with the SentenceTransformers bfloat16 model on the same documents (`dense_eg2_text`) under the same labels. Documents that a quantized run brings into its top 10 but that no judge saw are counted as non-relevant, and their share is reported. The text collections include 21 PDF-page rows embedded as images by the full model. GGUF instead encodes their stored text (485 characters in total); 84 767 rows are text inputs. Thus identical document candidates do not mean identical input modality for every chunk, and the comparison does not isolate quantization alone.

Scaling of exact dense search is measured outside archive-index with collections grown from the 86 726 real EG2 vectors to 10^5, $3{\cdot}10^5$, 10^6 and $2{\cdot}10^6$ vectors; the added vectors are noisy copies of real ones (Gaussian noise, $\sigma = 0.05$, renormalized), so the collections are synthetic. Each of the 200 UA-PAR query vectors is searched one at a time with an optimized exact NumPy top-10 selection (matrix product and `argpartition`), an exact Faiss index and an HNSW index ($M = 32$, construction depth 200, search depth 64 and 256). A sequential follow-up calls the actual archive-index vector-ranking method on the same matrices: candidate gathering, full `argsort` and construction of 400 result tuples, excluding the SQLite cache-version poll. This

distinguishes the optimized reference from the deployed algorithm. HNSW recall@10 counts matching vector IDs against the NumPy reference; ties and floating-point differences are not credited as equivalent IDs. Agreement between the exact Faiss and NumPy rankings is audited separately, together with the fraction of Faiss results at or above the reference tenth score within 10^{-6}.

5.6 Software and hardware

All measurements ran on one laptop: Intel Core i9-14900HX (32 logical CPUs), 31 GiB RAM, NVIDIA GeForce RTX 4060 Laptop GPU with 8 GB, Linux 7.0. Software: Python 3.13.14, PyTorch 2.14.1, Transformers 5.19.0, SentenceTransformers 6.1.0, NumPy 2.5.4, SQLite 3.53.1, pymorphy3 2.0.6, ir-measures 0.4.3, llama.cpp commit `8bb3cf0`, and Faiss 1.15.1 in a separate environment for the scaling experiment. The full list is stored in `efficiency.json`.

6 Results

6.1 Retrieval and judge sensitivity

Table 1 reports all ten systems on the same answerable-query population. Confidence intervals describe query-level variation under the reported labels; they do not capture uncertainty in the labels themselves. Table 2 and Figure 2 preserve the initial and reviewed variants. Gemini review is within-model, and Gemini and Gemma share a provider.

E5 has the highest mean nDCG@10 under all three principal relevance variants. Its lead over adaptive does not reach the 0.05 threshold after Holm correction in any variant; this does not establish equivalence. Adaptive outperforms both BM25 baselines on the primary endpoint after correction, but shows no statistically detectable advantage over EG2 alone or RRF. Removing phrase reranking leaves the evaluated scores unchanged; the other adaptive ablation differences in nDCG@10 are small and not statistically detectable on this query set. These findings do not support a general claim that adaptive fusion improves over dense retrieval.

Lemmatization improves mean BM25 nDCG@10 under all three variants. The separately reported paired morphology contrast supports the difference under initial and reviewed Gemini labels, while its interval crosses zero under Gemma 4 12B labels. Thus the strength of the morphology finding depends on relevance assessment. The within-model review changes 334 of the 5 572 initial Gemini labels; all 4 481 initially agreed pairs remain unchanged.

6.2 Controls

Candidate universe. E5 searches 4 137 text documents; the full EG2 index holds 6 054 documents, including media. Restricting EG2 to the same 4 137 text documents (dense_eg2_text) changes its nDCG@10 by −0.0015 under reviewed Gemini labels (0.633 to 0.631); 0.29% of its top-10 documents were not in the judged pool. The paired difference EG2_{text} − E5 is −0.042 nDCG@10 (95% CI −0.078 to −0.006, unadjusted $p = 0.018$) with reviewed Gemini labels and −0.019 (−0.052 to 0.014, $p = 0.26$) with Gemma 4 12B labels (Table 3). Thus the candidate restriction has a small point effect in this control, while statistical support for the encoder difference depends on the labels. These exploratory comparisons use unadjusted p-values and an incomplete judgement pool.

Whole-word coverage. The adaptive rule's exact-phrase test counted substrings (Section 1.5). With the corrected rule, the top 10 changes for one query of 200 in each adaptive variant, and adaptive nDCG@10 moves from 0.629 to 0.627 (reviewed Gemini), 0.639 to 0.637 (initial Gemini) and stays at 0.675 (Gemma 4 12B). The frozen primary results are retained; the corrected point score does not create an adaptive advantage over dense EG2.

Table 1: Document retrieval on 170 answerable queries. Means and 95% query-bootstrap intervals use Gemini labels after the within-model disagreement review. The two panels preserve all five metrics. A dagger marks a paired difference from adaptive at Holm-adjusted $p < 0.05$, not necessarily an improvement. R@100 is pool-relative. E5 uses a smaller text-only candidate universe.

System	nDCG@10	R@100^{pool}	RR@10
bm25_plain	0.450† [0.413, 0.487]	0.648† [0.611, 0.685]	0.738† [0.682, 0.790]
bm25_lemma	0.482† [0.446, 0.518]	0.724† [0.693, 0.755]	0.753† [0.701, 0.802]
dense_eg2	0.633 [0.601, 0.664]	0.911 [0.890, 0.930]	0.872 [0.832, 0.910]
dense_e5	0.674 [0.647, 0.700]	0.880 [0.853, 0.906]	0.927 [0.894, 0.956]
rrf	0.630 [0.601, 0.660]	0.960† [0.946, 0.972]	0.873 [0.835, 0.910]
adaptive	0.629 [0.596, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
adaptive-phrase	0.629 [0.596, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
adaptive-ident	0.629 [0.597, 0.661]	0.912 [0.892, 0.931]	0.866 [0.826, 0.905]
adaptive-short	0.629 [0.597, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
dense_eg2_256	0.611 [0.577, 0.643]	0.888† [0.863, 0.911]	0.873 [0.830, 0.913]

System	Success@1	Success@5
bm25_plain	0.635† [0.559, 0.706]	0.876† [0.824, 0.924]
bm25_lemma	0.624† [0.547, 0.694]	0.929 [0.888, 0.965]
dense_eg2	0.794 [0.729, 0.853]	0.971 [0.941, 0.994]
dense_e5	0.876 [0.824, 0.924]	0.988 [0.971, 1.000]
rrf	0.788 [0.724, 0.847]	0.976 [0.953, 0.994]
adaptive	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-phrase	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-ident	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-short	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
dense_eg2_256	0.818 [0.759, 0.871]	0.953 [0.918, 0.982]

†: $p_{\text{Holm}} < 0.05$, adaptive; R@100: pool-relative.

Table 2: Sensitivity of nDCG@10 to relevance assessment. Initial Gemini and Gemma 4 12B grades are retained; the reviewed variant changes only their disagreements. The same frozen runs and 170 queries are used throughout. GPT grades do not enter this comparison.

System	Gemini initial	Gemma12 initial	Gemini reviewed
bm25_plain	0.453 [0.416, 0.491]	0.500 [0.462, 0.536]	0.450 [0.413, 0.487]
bm25_lemma	0.489 [0.453, 0.526]	0.519 [0.482, 0.554]	0.482 [0.446, 0.518]
dense_eg2	0.644 [0.613, 0.674]	0.681 [0.652, 0.709]	0.633 [0.601, 0.664]
dense_e5	0.685 [0.657, 0.711]	0.698 [0.671, 0.725]	0.674 [0.647, 0.700]
rrf	0.641 [0.612, 0.669]	0.665 [0.636, 0.694]	0.630 [0.601, 0.660]
adaptive	0.639 [0.608, 0.669]	0.675 [0.647, 0.703]	0.629 [0.596, 0.660]
adaptive-phrase	0.639 [0.608, 0.669]	0.675 [0.647, 0.703]	0.629 [0.596, 0.660]
adaptive-ident	0.639 [0.608, 0.669]	0.676 [0.648, 0.704]	0.629 [0.597, 0.661]
adaptive-short	0.639 [0.608, 0.669]	0.675 [0.647, 0.703]	0.629 [0.597, 0.660]
dense_eg2_256	0.622 [0.589, 0.654]	0.665 [0.633, 0.696]	0.611 [0.577, 0.643]

Table 3: E5 against EG2 on the same 4 137 text documents. Δ is the paired difference from E5 with a 95% query-bootstrap interval and an unadjusted sign-flip p; unjudged documents count as non-relevant, and their share is shown.

Gemini reviewed

System	nDCG@10	Δ [95% CI] vs E5	p	Unjudged@10
dense_e5	0.674	–	–	0.000
dense_eg2	0.633	-0.041 [-0.077, -0.005]	0.023	0.000
dense_eg2_text	0.631	-0.042 [-0.078, -0.006]	0.018	0.003

Gemini initial

System	nDCG@10	Δ [95% CI] vs E5	p	Unjudged@10
dense_e5	0.685	–	–	0.000
dense_eg2	0.644	-0.041 [-0.075, -0.007]	0.020	0.000
dense_eg2_text	0.642	-0.042 [-0.077, -0.009]	0.014	0.003

Gemma 12B initial

System	nDCG@10	Δ [95% CI] vs E5	p	Unjudged@10
dense_e5	0.698	–	–	0.000
dense_eg2	0.681	-0.018 [-0.050, +0.015]	0.285	0.000
dense_eg2_text	0.680	-0.019 [-0.052, +0.014]	0.258	0.003




Figure 2: System scores and 95% query-bootstrap intervals across relevance variants. Differences between separate intervals do not replace paired statistical comparisons.

6.3 Judges

Table 4 reports each judge's grades on the whole pool and on the two kinds of pairs whose answer is known in advance; Table 5 reports pairwise agreement. Gemini, the two Gemma models and GPT-6-Luna agree with linear-weighted κ between 0.535 and 0.652. Gemini gives the target document of a known-item or other answerable query grade 2 in 85.8% of the 134 pooled targets, Gemma 4 12B in 67.2%: the larger Gemma model agrees best with Gemini overall but rarely gives full marks. On the 708 pooled pairs of no-answer queries, Gemini, Gemma 4 12B and Gemma 4 E4B give grade 0 in 90.4%, 91.2% and 93.5% of pairs.

GPT-6-Luna, which wrote the queries, is the most lenient judge: its mean grade is 0.633 against 0.421–0.447 for the other judges, and it gives a positive grade to 24.3% of the no-answer pairs, against 6.5–9.6% for the others. Its grades are higher than every other judge's on average by 0.19–0.21. This is consistent with self-preference by the query author, but general leniency would produce the same pattern. The present comparison cannot distinguish those explanations. GPT grades are not used in any relevance label.

6.4 Images and speech

Table 6 reports separate image-caption and speech-transcript retrieval tasks. These point estimates have no computed confidence intervals. The monolingual text-only speech condition uses the same transcript as query and indexed text, so it is a ceiling condition rather than a realistic paraphrased-query evaluation. Cross-language queries are parallel source transcripts and also do not represent arbitrary conversational audio search.

6.5 Latency and indexing cost

Table 7 reports warm per-query latency on the same 200 queries. These are evaluation-harness timings on one laptop, not interactive response-time guarantees. The models remain loaded between systems: the device-wide GPU-memory increase from each baseline is not an isolated footprint for that system.

Table 8 reports the GPU sample of 475 files and CPU sample of 95 files. Their compositions differ; chunks per second are descriptive throughput figures, and the ratio of wall times is not a paired hardware speedup.

6.6 Quantized retrieval

Table 9 reports retrieval quality, embedding throughput and local-server query latency. The separate cosine-reference experiment in the appendix does not substitute for these retrieval comparisons. The f16 and Q8 point differences from the bf16 reference are small, but intervals containing zero do not establish equivalence. For Q4, treating unjudged results as non-relevant gives a difference of -0.018 (95% CI $[-0.030, -0.006]$); 9.9% of its top-ten results are unjudged, compared with 0.3% for the reference. On condensed runs the Q4 difference is $+0.004$ with an interval spanning zero. Removing unjudged results changes the evaluated ranking; it does not establish their relevance. Thus the frozen pool does not identify an intrinsic Q4 quality loss. These comparisons also change backend and numerical precision, not only quantization.

6.7 Synthetic scaling

Table 10 separates exact vector-search cost from HNSW approximation. It excludes query embedding, lexical search and document collapse, and does not measure retrieval relevance on a real million-document archive.




Figure 3: nDCG@10 by query category for four principal systems under the primary relevance variant. Each category uses its own query-bootstrap interval. No-answer queries are excluded.

Table 4: Judges on the 5 572 pooled pairs: mean grade, grade counts, and known-answer checks (share of pooled answerable-query targets graded 2; share of pooled no-answer pairs graded 0).

Judge	Pairs	Mean grade	0 / 1 / 2	Target = 2, %	No-answer = 0, %
Gemini 3.8 Flash	5 572	0.421	3 522 / 1 756 / 294	85.8 (n=134)	90.4 (n=708)
Gemma 4 12B	5 572	0.447	3 316 / 2 024 / 232	67.2 (n=134)	91.2 (n=708)
Gemma 4 E4B	5 572	0.438	3 519 / 1 665 / 388	74.6 (n=134)	93.5 (n=708)
GPT-6-Luna	5 572	0.633	2 554 / 2 510 / 508	91.8 (n=134)	75.7 (n=708)

Table 5: Pairwise agreement between judges on the same 5 572 pairs: linear-weighted Cohen's κ with a 95% interval from 2 000 query-level bootstrap resamples, exact agreement, and the mean grade difference.

Judges	Pairs	Weighted κ [95% CI]	Exact agreement	Mean A−B
Gemini 3.8 Flash – Gemma 4 12B	5 572	0.652 [0.625, 0.677]	0.804	-0.026
Gemini 3.8 Flash – Gemma 4 E4B	5 572	0.591 [0.559, 0.622]	0.768	-0.017
Gemini 3.8 Flash – GPT-6-Luna	5 572	0.621 [0.595, 0.644]	0.759	-0.212
Gemma 4 12B – Gemma 4 E4B	5 572	0.650 [0.625, 0.674]	0.799	+0.008
Gemma 4 12B – GPT-6-Luna	5 572	0.586 [0.559, 0.612]	0.741	-0.186
Gemma 4 E4B – GPT-6-Luna	5 572	0.535 [0.506, 0.564]	0.700	-0.195




Figure 4: Query latency after a full warm-up. Markers show p50 and open endpoints p95, not confidence limits; the horizontal axis is logarithmic. Both passes include all 200 queries.

Table 6: Separate source-labelled multimodal tasks: query and candidate counts, followed by point estimates. No confidence intervals are fabricated. Speech text mode indexes the transcript; both mode combines transcript and audio.

Mode	Queries	Items
Image / ru	1000	1000
Image / uk	1000	1000
Speech / ru->ru / audio	265	400
Speech / ru->ru / both	265	400
Speech / ru->ru / text	265	400
Speech / ru->uk / audio	194	400
Speech / ru->uk / both	194	400
Speech / ru->uk / text	194	400
Speech / uk->ru / audio	194	400
Speech / uk->ru / both	194	400
Speech / uk->ru / text	194	400
Speech / uk->uk / audio	262	400
Speech / uk->uk / both	262	400
Speech / uk->uk / text	262	400

Mode	recall@1	recall@5	recall@10	mrr
Image / ru	0.889	0.983	0.994	0.932
Image / uk	0.857	0.977	0.986	0.909
Speech / ru->ru / audio	0.996	1.000	1.000	0.997
Speech / ru->ru / both	1.000	1.000	1.000	1.000
Speech / ru->ru / text	1.000	1.000	1.000	1.000
Speech / ru->uk / audio	0.985	1.000	1.000	0.991
Speech / ru->uk / both	1.000	1.000	1.000	1.000
Speech / ru->uk / text	1.000	1.000	1.000	1.000
Speech / uk->ru / audio	0.985	1.000	1.000	0.990
Speech / uk->ru / both	1.000	1.000	1.000	1.000
Speech / uk->ru / text	1.000	1.000	1.000	1.000
Speech / uk->uk / audio	0.996	1.000	1.000	0.997
Speech / uk->uk / both	1.000	1.000	1.000	1.000
Speech / uk->uk / text	1.000	1.000	1.000	1.000

Table 7: Warm query latency in milliseconds: p50 and p95 on GPU and CPU. VRAM is the device-wide increase above the stage baseline; previously loaded models remain resident.

System	GPU p50	GPU p95	CPU p50	CPU p95	VRAM +MiB
bm25_plain	12.3	41.6	13.8	48.0	0
bm25_lemma	19.9	64.1	19.9	62.4	0
dense_eg2	137.9	189.4	218.3	261.5	1592
dense_eg2_256	67.2	79.5	185.8	212.9	0
dense_e5	93.1	117.1	217.2	254.5	2130
rrf	132.5	177.4	266.8	362.1	2
adaptive	134.7	186.7	230.4	286.3	0




Figure 5: Frozen original-run quality against current warm GPU query cost. Quality intervals use 170 answerable queries and reviewed Gemini labels; latency uses all 200 queries after the whole-word coverage correction. The two axes describe different code revisions, as disclosed in the control analysis, and do not form a paired hardware experiment. Document collapse is excluded from the timer.

Table 8: Indexing into an empty database on two differently sized fixed samples. Counts refer to the files selected and chunks produced; RSS is the child-process peak. Sample disk includes database sidecars; full-index sizes count the main database files.

Device	Files	Chunks	Seconds	Chunks/s	DB MiB	RSS MiB	VRAM +MiB
GPU	475	5 155	106.1	48.58	59.9	2591	6816
CPU	95	1 187	1395.1	0.85	13.6	2979	0

Full index	Main database MiB
e5.sqlite3	1096.4
full.sqlite3	1120.7
noshort.sqlite3	1208.5
plain.sqlite3	1094.7

Table 9: GGUF EG2 builds on the same text candidates as the bfloat16 reference. Query latency follows a full 200-query warm-up. Differences use reviewed Gemini labels and exploratory unadjusted paired tests; unjudged results are counted as non-relevant. File sizes are MiB.

Build	File MiB	Chunks/s	Query p50
bf16 (SentenceTransformers)	–	–	–
f16	532	46	76.7
Q8_0	296	48	86.0
Q4_K_M	173	46	83.6

Build	nDCG@10	Δ [95% CI]	p	Unjudged@10
bf16 (SentenceTransformers)	0.631	–	–	0.003
f16	0.631	-0.001 [-0.005, +0.003]	0.734	0.016
Q8_0	0.630	-0.002 [-0.006, +0.003]	0.504	0.018
Q4_K_M	0.613	-0.018 [-0.030, -0.006]	0.002	0.099

Build	Condensed nDCG@10	Δ [95% CI]	p
bf16 (SentenceTransformers)	0.632	–	–
f16	0.634	+0.002 [-0.002, +0.006]	0.297
Q8_0	0.633	+0.000 [-0.004, +0.005]	0.869
Q4_K_M	0.636	+0.004 [-0.007, +0.015]	0.454




Figure 6: Paired nDCG@10 differences from bf16 EG2 versus GGUF file size on identical text candidates. The upper panel treats unjudged documents as non-relevant; the lower panel removes them. Error bars are 95% query-bootstrap intervals. The dependence on judgement coverage prevents interpreting the upper Q4 difference as an isolated quantization effect.




Figure 7: Vector-search latency and HNSW recall on synthetic enlarged collections. The latency axis is logarithmic, and no uncertainty intervals are estimated.

6.8 Additional target types

The separate extension uses 50 Qwen-written queries targeting 20 documents, 15 tables and 15 repository files, evaluated with the corrected coverage rule. Initial Gemini labels and initial Gemma 4 12B labels are reported separately in Table 11. The 50 records contain 49 distinct query wordings; one wording targets two files. They are not mixed into the original 200 or its primary relevance labels. GPT is comparison-only. Differences between the two query populations cannot identify self-preference because authorship, target type and difficulty also differ.

With initial Gemini labels, EG2 scores 0.759, adaptive fusion 0.756 and E5 0.721, compared with 0.523 for lemmatized BM25. With initial Gemma 4 12B labels the corresponding scores are 0.769, 0.765, 0.730 and 0.540. Adaptive exceeds both lexical baselines after Holm correction in both label variants; neither EG2 nor E5 is separated from adaptive by those tests. The changed point order of the dense encoders is cohort-specific evidence, not a comparison of overall difficulty with the original benchmark. GPT remains the most lenient judge on Qwen-written queries as well (mean grade 0.550 versus 0.379 for Gemini and 0.437 for Gemma), reinforcing that the initial GPT pattern does not identify query-author self-preference.

Keeping the lowest query ID per normalized wording removes q249, without selecting by retrieval score. Table 12 reports this exploratory sensitivity. The 50-record intervals treat records as resampling units despite their shared wording; the separate sensitivity avoids that duplicate but does not make the sample representative.

7 Field study on the author's archive

The private study runs the implemented adaptive search on the author's existing archive with three query sets written during system development. Their names (main, holdout7 and holdout11) are development labels, not evidence of an independently sampled or prospectively held-out user study. The sets contain 80, 86 and 214 queries respectively. No documents, query texts, paths, snippets or per-query outcomes are exported.

There are three operational checks. For an exact-item query, success means a returned chunk contains the expected phrase after whitespace and case normalization; ranks and reciprocal ranks are chunk-level. For a described-item query, success means the top five chunks include the expected project. For an absent-item query, success means lexical mode returns no result; this does not test abstention of dense search. The checks are weaker than independent document-relevance judgements. Each set and kind is summarized separately with query-bootstrap 95% intervals; the sets are not pooled into a general performance estimate.

Table 13 describes this deployment and these development queries. All-success samples produce degenerate percentile-bootstrap intervals of [1,1]; these are not population guarantees. Its intervals describe resampling within a set; they do not account for tuning on the archive, query selection or variation between people.

8 Discussion

Morphology (RQ1). The corrected lemma expansion increases BM25 nDCG@10 by 0.031 under the primary labels, with a paired 95% interval from 0.013 to 0.051. This supports its use for this query set under those labels. The weaker evidence under Gemma 4 12B limits a judge-independent claim. The earlier decrease before the analyzer fix also shows why linguistic expansion must be checked as implemented: adding a guessed lemma in the wrong language can change retrieval in the opposite direction.

Fusion and technical queries (RQ2–RQ3). The adaptive system exceeds BM25 on the primary endpoint but has no detected advantage over EG2 or RRF. E5 has the highest mean

Table 10: Exact and approximate search on synthetic collections derived from the real vectors. Latencies are p50 milliseconds for a single query. HNSW cells show latency / recall@10 against exact search; construction time is seconds. This experiment measures chunk-vector search only.

Vectors	NumPy top-k	Faiss flat	HNSW build s	HNSW ef64	HNSW ef256
100 000	6.16	10.65	9	0.19 / 0.914	0.57 / 0.984
300 000	17.85	26.52	33	0.27 / 0.940	0.69 / 0.990
1 000 000	51.78	75.83	187	0.29 / 0.904	0.97 / 0.991
2 000 000	106.63	139.95	676	0.39 / 0.893	1.28 / 0.983

Vectors	Archive path p50 ms	Flat ID agreement	Flat score threshold
100 000	60.84	1.000	1.000
300 000	166.80	1.000	1.000
1 000 000	497.64	1.000	1.000
2 000 000	2441.83	1.000	1.000

At 2 000 000 vectors, observed p50 is 106.6 ms for optimized NumPy top-k and 2441.8 ms for the archive vector path. HNSW ef256 is 1.28 ms at strict-ID recall@10 0.9825. These are sequential desktop-session measurements of different algorithms and output pools (10 versus 400), not paired hardware speedups or end-to-end interface latency.

Table 11: nDCG@10 and 95% query-bootstrap intervals on the separate 50-query extension. Both label variants are initial assessments; neither is the original benchmark's reviewed primary variant.

System	Gemini initial	Gemma 12B initial
bm25_plain	0.496 [0.404, 0.590]	0.507 [0.409, 0.604]
bm25_lemma	0.523 [0.431, 0.617]	0.540 [0.443, 0.639]
dense_eg2	0.759 [0.697, 0.817]	0.769 [0.701, 0.832]
dense_e5	0.721 [0.654, 0.785]	0.730 [0.666, 0.790]
rrf	0.684 [0.619, 0.749]	0.696 [0.623, 0.766]
adaptive	0.756 [0.694, 0.814]	0.765 [0.697, 0.827]
adaptive-phrase	0.756 [0.694, 0.814]	0.765 [0.697, 0.827]
adaptive-ident	0.756 [0.694, 0.814]	0.765 [0.697, 0.827]
adaptive-short	0.756 [0.694, 0.814]	0.765 [0.697, 0.827]
dense_eg2_256	0.713 [0.639, 0.782]	0.732 [0.662, 0.797]

Table 12: Five principal systems on the unique-wording subset of the extension. Initial labels and query-bootstrap intervals; remaining systems and paired statistics are preserved in the result JSON.

Unique-wording sensitivity: 49 queries.

System	Gemini initial	Gemma 12B initial
bm25_plain	0.503 [0.407, 0.597]	0.513 [0.414, 0.611]
bm25_lemma	0.530 [0.439, 0.624]	0.546 [0.448, 0.646]
dense_e5	0.717 [0.649, 0.782]	0.724 [0.659, 0.786]
dense_eg2	0.757 [0.695, 0.813]	0.765 [0.698, 0.826]
adaptive	0.754 [0.692, 0.810]	0.760 [0.694, 0.821]

Table 13: Operational checks on the private archive: counts, means and 95% query-bootstrap intervals. Exact-item metrics use chunk ranks; described-item success checks the project; absent-item success checks lexical abstention. Only aggregates are exported.

Archive: 11 394 documents, 902 739 chunks.

Set	Kind	Queries	Metric	Mean [95% CI]
holdout11	exact	192	hit@1	0.672 [0.604, 0.740]
holdout11	exact	192	hit@5	0.708 [0.641, 0.771]
holdout11	exact	192	mrr@10	0.691 [0.627, 0.754]
holdout11	absent	10	pass	1.000 [1.000, 1.000]
holdout11	described	12	hit@5	1.000 [1.000, 1.000]
holdout7	exact	64	hit@1	0.641 [0.516, 0.750]
holdout7	exact	64	hit@5	0.703 [0.594, 0.812]
holdout7	exact	64	mrr@10	0.668 [0.557, 0.777]
holdout7	absent	10	pass	1.000 [1.000, 1.000]
holdout7	described	12	hit@5	1.000 [1.000, 1.000]
main	exact	66	hit@1	0.697 [0.576, 0.803]
main	exact	66	hit@5	0.727 [0.621, 0.833]
main	exact	66	mrr@10	0.709 [0.598, 0.813]
main	absent	8	pass	1.000 [1.000, 1.000]
main	described	6	hit@5	1.000 [1.000, 1.000]

nDCG@10, including in the control with the same text candidates. The absence of a Holm-significant E5–adaptive contrast does not show equal effectiveness. The phrase-reranking ablation is numerically identical to the full system on the frozen runs; the identifier and short-fragment ablations also do not supply evidence of an improvement on this sample. These rules may address particular failure cases, but that possibility is not an empirical finding of this benchmark. The limited target coverage and query authorship call for evaluation on independently written queries and non-note targets before a general recommendation about the fusion rule.

Multimodal retrieval (RQ4). The image-caption and speech-transcript tasks test whether the embedding space connects the modalities in two languages. They use source-dataset labels, so they provide evidence distinct from the model-judged text benchmark. Image recall at one is 0.857 for Ukrainian captions and 0.889 for Russian captions on 1 000 images. The transcript-as-query text condition for speech is a ceiling test. High performance on parallel transcripts or dataset captions cannot be assumed to hold for a person's paraphrase, a long recording, or an arbitrary collection of photographs.

Assessment and scope. Agreement between model judges and checks of target documents reveal useful differences in grading, but do not establish human validity. The Gemini review changes the primary labels only on disagreements; its dependence on the original judges and visible grades remains. Judge sensitivity should therefore accompany the point estimates. A blind author audit would add a human reference for the sampled pairs, while still being an audit by one person and, because of grade-balanced sampling, not an unweighted estimate of whole-pool agreement. The cost experiments (RQ5) and private-archive aggregates are separate evidence streams and should be interpreted within their hardware and sampling conditions.

9 Limitations and threats to validity

9.1 Corpus and queries

UA-PAR imitates a personal archive with public material: Wikipedia articles stand in for notes and rendered articles for office documents, so the text is more uniform and better edited than real notes, and nothing in it is truly personal. The 200 queries were written by one model under written rules, not by people looking for their own documents, and every answerable target is a note. The separate 50-query extension targets documents, tables and repository files (Section 6.8), but is again model-written. It contains 49 distinct wordings, so the 50 records are not fully independent; a deterministic unique-wording sensitivity is reported separately. The no-answer queries have no lexical match by construction, which decides the lexical systems' result on them in advance. Topics follow the author's interests; a different archive could favour different systems.

9.2 Model-generated relevance labels

Text relevance labels are generated by language models rather than an independent human panel. Agreement, target-document checks and deliberately unanswerable queries provide diagnostic evidence but are not a complete gold standard. Gemini and Gemma may share errors because they share a provider. Reviewing disagreements with Gemini cannot remove this dependence; it also exposes the reviewer to the initial grades. We therefore preserve the original labels and report the sensitivity of retrieval metrics and system ordering to the judge and to the review. The primary judge was selected after examining judge diagnostics, a post hoc methodological choice. No completed human sample audit is claimed.

9.3 Query and candidate coverage

Although the corpus is heterogeneous, all authored answerable targets in the original 200-query set are notes. The separate extension adds a small sample of documents, tables and repository files. Neither set establishes general quality for arbitrary target formats, images or recordings. The E5 baseline searches a smaller text-only document universe, whereas the EG2 indexes include media. The control on identical candidates (Table 3) changes EG2's nDCG@10 by -0.0015, a small point effect in this control. This does not remove all candidate-coverage uncertainty: the control runs were not pooled, and 0.29% of their top-10 documents are unjudged.

Only the union of system top-10 results is fully judged. Relevant documents outside that pool may exist. Recall at 100 is therefore relative to the known relevant pool; treating unjudged documents as nonrelevant can favour pooled systems and does not estimate exhaustive corpus recall. A failure to reject a performance difference does not establish equivalence.

9.4 Single-author field study

The field study (Section 7) uses one person's archive and query sets that the author wrote during development of the system, partly to test it; they are not a random sample of real information needs, and the system was tuned on the same archive. Its numbers show behaviour in deployment, not generalizable effectiveness.

9.5 Measurements

All costs come from one laptop in an ordinary desktop session, with other programs running; the load before each step is logged but not controlled. The query timer includes embedding and chunk search but excludes document collapse, path resolution and interface rendering. Process-level resource counters span the whole measured pass, including collapse, so their scope differs from the per-query timer. CPU indexing was measured on a fifth of the GPU sample. The scaling experiment uses synthetic vectors derived from the real ones, and HNSW recall on them need not equal recall on a real collection of that size.

9.6 Construct validity

Judges see the title and the first 1 200 characters of a document, not the whole document, so a document relevant only further down can be graded too low; the same snippet is shown for every system, so the bias does not favour one system directly but favours documents whose relevance shows early. Grades 0/1/2 compress a judgement that people make differently: a model's "partly relevant" is not a person's. The primary metric, nDCG@10 over pooled labels, rewards systems for ranking judged-relevant documents high; it does not measure whether a person finds what they remember faster, which is what an archive search is for.

10 Data and code availability

Release. The code, the UA-PAR queries, relevance sheets with every judge's grades, call logs, retrieval runs, result files and the scripts that rebuild the corpus from its sources will be released together. [PENDING: public repository URL, release tag, software DOI and preprint DOI; the repository is private until the author approves publication]. The generated-table manifest binds its source result files by SHA-256; the frozen judging inputs are listed in `paper/results/judging_inputs_initial.json`.

Corpus licences. The corpus is rebuilt from its public sources by `paper/corpus`; each file in the manifest carries its source URL, licence and SHA-256. By part: 2 945 notes and 400 rendered

documents from Ukrainian and Russian Wikipedia (CC BY-SA 4.0); 150 tables from data.gov.ua datasets published under CC BY; 1 775 files from Ukrainian-topic GitHub repositories under the MIT licence (only MIT and Apache-2.0 repositories were taken; each repository's licence file is kept); 1 000 Crossmodal-3600 images (CC BY 2.0, authors listed in the dataset's attribution file) with captions (CC BY 4.0); and 800 FLEURS recordings with transcripts (CC BY 4.0).

Private data. The field study (Section 7) uses the author's own archive. Only aggregate numbers are released; its documents, queries and file names are not. A release check (`paper/release/check.py`) scans every released file for the private query texts, the author's home path and project names before publication.

Models and software. EmbeddingGemma 2 (Hugging Face `google/embeddinggemma-2`, revision `914f7f8`), multilingual-e5-large (`intfloat/multilingual-e5-large`), GGUF builds of EmbeddingGemma 2 made with llama.cpp, and the judges' model identifiers are listed in the result files. Python package versions are recorded with the efficiency results.

Writing aids. The Scientific Agent Skills writing workflow [12] was used while drafting; its rules (no invented citations or numbers, evidence bound to sources) are those followed here.

11 Conclusion

archive-index provides local lexical, dense and multimodal search over a heterogeneous archive. UA-PAR makes its text retrieval inspectable through a public-source corpus, frozen queries and runs, multiple model assessments and generated reports. On the 170 answerable queries under the primary reviewed Gemini labels, E5 obtains mean nDCG@10 of 0.674, EG2 0.633, adaptive fusion 0.629, lemmatized BM25 0.482 and plain BM25 0.450. Adaptive fusion exceeds BM25 after correction but has no demonstrated advantage over EG2 or RRF; the evidence for the morphology gain depends on the relevance judge. Separate image and speech tasks establish dataset-specific cross-modal retrieval behaviour. These results support a measured account of the implemented system and its limitations; they do not establish human relevance validity, a general advantage of adaptive fusion, or effectiveness for every kind of personal-archive query.

References

[1] pymorphy3, version 2.0.6, with pymorphy3-dicts-uk 2.4.1.1.1663094765 and pymorphy3-dicts-ru 2.4.417150.4580142. `https://github.com/no-plagiarism/pymorphy3`. Maintained fork of pymorphy2.

[2] SQLite FTS5 extension. `https://www.sqlite.org/fts5.html`. SQLite 3.53.1 as linked into the Python used for the measurements.

[3] Jacob Cohen. Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, 70(4):213–220, 1968. doi: 10.1037/h0026256.

[4] Alexis Conneau, Min Ma, Simran Khanuja, Yu Zhang, Vera Axelrod, Siddharth Dalmia, et al. FLEURS: Few-shot learning evaluation of universal representations of speech. In *2022 IEEE Spoken Language Technology Workshop (SLT)*, pages 798–805, 2023. doi: 10.1109/SLT54892.2023.10023141.

[5] Gordon V. Cormack, Charles L. A. Clarke, and Stefan Buettcher. Reciprocal rank fusion outperforms Condorcet and individual rank learning methods. In *Proceedings of the 32nd*

International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 758–759, 2009. doi: 10.1145/1571941.1572114.

[6] Matthijs Douze, Alexandr Guzhva, Chengqi Deng, Jeff Johnson, Gergely Szilvasy, Pierre-Emmanuel Mazaré, et al. The Faiss library, 2024.

[7] Susan Dumais, Edward Cutrell, J. J. Cadiz, Gavin Jancke, Raman Sarin, and Daniel C. Robbins. Stuff I've seen: A system for personal information retrieval and re-use. In *Proceedings of the 26th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 72–79, 2003. doi: 10.1145/860435.860451.

[8] Guglielmo Faggioli, Laura Dietz, Charles L. A. Clarke, Gianluca Demartini, Matthias Hagen, Claudia Hauff, et al. Perspectives on large language models for relevance judgment. In *Proceedings of the 2023 ACM SIGIR International Conference on Theory of Information Retrieval (ICTIR)*, pages 39–50, 2023. doi: 10.1145/3578337.3605136.

[9] Google DeepMind. EmbeddingGemma 2 model card. Hugging Face, `https://huggingface.co/google/embeddinggemma-2`, revision 914f7f89142e33e77833254d9c9b90c3cef7303b, 2026. Apache-2.0; prompts, float16 warning and Matryoshka dimensions as stated in the card.

[10] Kalervo Järvelin and Jaana Kekäläinen. Cumulated gain-based evaluation of IR techniques. *ACM Transactions on Information Systems*, 20(4):422–446, 2002. doi: 10.1145/582415.582418.

[11] Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, 2020. doi: 10.18653/v1/2020.emnlp-main.550.

[12] Timothy Kassis, Vinayak Agarwal, Yuhuan He, Darshil Patel, and Aubrey M. Brueckner. Scientific agent skills: A library of procedural knowledge for research agents, 2026. Writing-workflow skill used while drafting this manuscript.

[13] Mikhail Korobov. Morphological analyzer and generator for Russian and Ukrainian languages. In *Analysis of Images, Social Networks and Texts (AIST 2015)*, Communications in Computer and Information Science, pages 320–332. Springer International Publishing, 2015. doi: 10.1007/978-3-319-26123-2_31.

[14] Aditya Kusupati, Gantavya Bhatt, Aniket Rege, Matthew Wallingford, Aditya Sinha, Vivek Ramanujan, et al. Matryoshka representation learning, 2022.

[15] Sean MacAvaney, Craig Macdonald, and Iadh Ounis. Streamlining evaluation with ir-measures. In *Advances in Information Retrieval (ECIR 2022)*, Lecture Notes in Computer Science, pages 305–310, 2022. doi: 10.1007/978-3-030-99739-7_38.

[16] Yu. A. Malkov and D. A. Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42(4):824–836, 2020. doi: 10.1109/TPAMI.2018.2889473.

[17] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, et al. Learning transferable visual models from natural language supervision, 2021.

[18] Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, 2019. doi: 10.18653/v1/D19-1410.

[19] Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389, 2009. doi: 10.1561/1500000019.

[20] Tetsuya Sakai. Alternatives to bpref. In *Proceedings of the 30th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 71–78, 2007. doi: 10.1145/1277741.1277756.

[21] Henrique Schechter Vera, Sahil Dua, Biao Zhang, Daniel Salz, Ryan Mullins, Sindhu Raghuram Panyam, et al. EmbeddingGemma: Powerful and lightweight text representations, 2025.

[22] Mark D. Smucker, James Allan, and Ben Carterette. A comparison of statistical significance tests for information retrieval evaluation. In *Proceedings of the Sixteenth ACM Conference on Information and Knowledge Management (CIKM)*, pages 623–632, 2007. doi: 10.1145/1321440.1321528.

[23] Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. BEIR: A heterogenous benchmark for zero-shot evaluation of information retrieval models, 2021.

[24] Ashish V. Thapliyal, Jordi Pont-Tuset, Xi Chen, and Radu Soricut. Crossmodal-3600: A massively multilingual multimodal evaluation dataset, 2022.

[25] Paul Thomas, Seth Spielman, Nick Craswell, and Bhaskar Mitra. Large language models can accurately predict searcher preferences. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1930–1940, 2024. doi: 10.1145/3626772.3657707.

[26] Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. Multilingual E5 text embeddings: A technical report, 2024.

[27] Xinyu Zhang, Nandan Thakur, Odunayo Ogundepo, Ehsan Kamalloo, David Alfonso-Hermelo, Xiaoguang Li, et al. MIRACL: A multilingual retrieval dataset covering 18 diverse languages. *Transactions of the Association for Computational Linguistics*, 11:1114–1131, 2023. doi: 10.1162/tacl_a_00595.

A Detailed measured results

The following fragments are generated from the same result files as the main tables. Their source hashes and current primary relevance variant are recorded in `generated/manifest.json`.

A.1 Assessment status and scope

Judging: Gemini within-model reviewed. Metrics: 170 answerable queries; no-answer queries: 30.
R@100 is pool-relative; judgments are incomplete, not full gold. Gemini and Gemma12 share a provider family. Gemini review is within-model. GPT is excluded from principal tables and figures.
gemini: 5572 graded pairs.
gemma4-12b: 5572 graded pairs.
Initial disagreements: 1091/5572; linear-weighted Cohen kappa: 0.652.
Targets: total=170, in pool=134, outside pool=36. Target-grade denominator=134.
The manifest describes collected files, not all of them are indexable by archive-index.
The E5 baseline uses text-only input; its document universe differs from the multimodal EG2 indexes.
All 170 authored answerable query targets are notes; findings do not establish retrieval quality for targets in every archive format.
Raw chunks include lexical-only rows. Text-collection vector counts restrict collections to wiki, docs, tables and code; they include image-rendered PDF pages. Text-vector counts exclude image/audio input hashes.

A.2 Collected and indexed populations

Population	Count
Manifest files	7070
Queries (all)	200
e5 index documents	4137
full index documents	6054
noshort index documents	6054
plain index documents	6054
e5: raw chunks	94970
e5: vectors	84767
e5: text-collection vectors	84767
full: raw chunks	96908
full: vectors	86726
full: text-collection vectors	84788
noshort: raw chunks	97652
noshort: vectors	87441
noshort: text-collection vectors	85503
plain: raw chunks	96908
plain: vectors	86726
plain: text-collection vectors	84788

A.3 Ablations

System	nDCG@10	R@100^{pool}	RR@10
adaptive	0.629 [0.596, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
adaptive-phrase	0.629 [0.596, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
adaptive-ident	0.629 [0.597, 0.661]	0.912 [0.892, 0.931]	0.866 [0.826, 0.905]
adaptive-short	0.629 [0.597, 0.660]	0.908 [0.887, 0.928]	0.866 [0.826, 0.905]
dense_eg2_256	0.611 [0.577, 0.643]	0.888† [0.863, 0.911]	0.873 [0.830, 0.913]

System	Success@1	Success@5
adaptive	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-phrase	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-ident	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
adaptive-short	0.782 [0.718, 0.841]	0.971 [0.941, 0.994]
dense_eg2_256	0.818 [0.759, 0.871]	0.953 [0.918, 0.982]

†: $p_{\text{Holm}}<0.05$, adaptive; R@100: pool-relative.

A.4 Query categories

System	Known item	Topical
bm25_plain	0.475 [0.397, 0.552]	0.351 [0.296, 0.407]
bm25_lemma	0.524 [0.451, 0.594]	0.388 [0.338, 0.438]
dense_eg2	0.617 [0.549, 0.683]	0.568 [0.513, 0.619]
dense_e5	0.729 [0.682, 0.773]	0.662 [0.617, 0.706]
rrf	0.639 [0.584, 0.690]	0.564 [0.517, 0.609]
adaptive	0.612 [0.542, 0.680]	0.568 [0.513, 0.619]
adaptive-phrase	0.612 [0.542, 0.680]	0.568 [0.513, 0.619]
adaptive-ident	0.612 [0.542, 0.680]	0.568 [0.513, 0.619]
adaptive-short	0.612 [0.543, 0.681]	0.569 [0.514, 0.620]
dense_eg2_256	0.596 [0.527, 0.664]	0.539 [0.479, 0.598]

System	Technical	Cross-lingual
bm25_plain	0.649 [0.597, 0.702]	0.351 [0.273, 0.427]
bm25_lemma	0.651 [0.595, 0.706]	0.388 [0.302, 0.472]
dense_eg2	0.785 [0.746, 0.823]	0.582 [0.512, 0.650]
dense_e5	0.663 [0.606, 0.716]	0.639 [0.563, 0.709]
rrf	0.779 [0.734, 0.824]	0.554 [0.486, 0.619]
adaptive	0.772 [0.732, 0.810]	0.582 [0.512, 0.650]
adaptive-phrase	0.772 [0.732, 0.810]	0.582 [0.512, 0.650]
adaptive-ident	0.775 [0.736, 0.813]	0.582 [0.512, 0.650]
adaptive-short	0.772 [0.732, 0.810]	0.580 [0.510, 0.648]
dense_eg2_256	0.757 [0.716, 0.796]	0.579 [0.508, 0.648]

A.5 Query languages

System	Russian	Ukrainian
bm25_plain	0.421 [0.368, 0.474]	0.466 [0.417, 0.515]
bm25_lemma	0.480 [0.428, 0.531]	0.483 [0.436, 0.530]
dense_eg2	0.633 [0.582, 0.683]	0.633 [0.592, 0.672]
dense_e5	0.664 [0.612, 0.712]	0.679 [0.647, 0.710]
rrf	0.624 [0.579, 0.668]	0.634 [0.596, 0.671]
adaptive	0.623 [0.572, 0.674]	0.631 [0.591, 0.670]
adaptive-phrase	0.623 [0.572, 0.674]	0.631 [0.591, 0.670]
adaptive-ident	0.625 [0.574, 0.676]	0.631 [0.591, 0.670]
adaptive-short	0.623 [0.572, 0.674]	0.632 [0.591, 0.670]
dense_eg2_256	0.637 [0.584, 0.689]	0.597 [0.553, 0.640]

A.6 Quantization reference

The reference measures cosine agreement of embeddings on 20 texts and CPU seconds per text. It does not measure retrieval-quality loss or establish production latency.

GGUF	Mean cosine	Worst cosine	MB	CPU s/text
f16	0.99995	0.99994	532.1	0.061
Q8_0	0.99972	0.99892	295.5	0.069
Q4_K_M	0.99043	0.98503	173.3	0.053