

ADVANCED ENGINEERING WORKSHOP · TRACK A

Distributed Systems & Event Architecture

Building Resilient Microservices with Synapse Engine & Apex Bus

Lead Instructor:

Dr. Elena Rostova

Location:

Nexus Hall, Room 402


Duration: 4.0 Hours

Key Learning Objectives

- ✓ Master the fundamentals of event-driven asynchronous messaging using the **Synapse Pipeline**.
- ✓ Analyze consensus algorithms (Raft, Paxos) and evaluate system availability under network partitions (**CAP Theorem**).
- ✓ Design self-healing circuit breaker patterns and distributed sagas for cross-service transactions in **Apex Engine**.
- ✓ Calculate latency bounds, throughput ceilings, and resource utilization across distributed node clusters.

1 Core Architectural Concepts

Modern distributed architectures decouple services through event streams, ensuring high throughput and isolated fault domains. Below is the reference topology for the **Meridian Enterprise System** utilized throughout today's exercises.



1.1 Theoretical Foundations & Mathematical Models

When designing fault-tolerant clusters, overall system availability A_{sys} across n independent series components is bounded by:

$$A_{\text{sys}} = \prod_{i=1}^n A_i = A_1 \times A_2 \times \dots \times A_n \quad (1)$$

For parallel redundant nodes running active-active failover, availability improves according to:

$$A_{\text{parallel}} = 1 - \prod_{i=1}^m (1 - A_i) \quad (2)$$

Architectural Golden Rule

Never sacrifice consistency for availability in financial state engines. Utilize **Strong Eventual Consistency (SEC)** with Conflict-Free Replicated Data Types (CRDTs) when full ACID compliance introduces unacceptable tail latencies ($p_{99} > 150\text{ms}$).