



Nexa Connect API

Integration Guide for Server-Side SDKs

Version 2.4.0 | Revised March 2026 | api.nexa.dev

Overview

Nexa Connect is the unified API for payments, identity verification, and ledger reconciliation used by finance teams building on the Nexa platform. This guide covers authentication, the core REST endpoints, official SDKs for Python and Node.js, webhook signature verification, and error-handling conventions. It is written for backend engineers integrating Nexa Connect into an existing service — prior familiarity with REST and JSON is assumed. All requests are made over HTTPS to the single base URL <https://api.nexa.dev/v2>; there is no per-feature subdomain. Responses are JSON, timestamps are ISO 8601 in UTC, and monetary amounts are always integer minor units (e.g. cents) to avoid floating-point rounding errors.

Median Latency

118 ms

p50, create-payment

Auth Model

HMAC + Key

signed webhooks

Rate Limit

600 / min

per API key

1 Authentication

Every request must carry a bearer API key issued from the Nexa Dashboard under **Settings** → **API Keys**. Keys are environment-scoped: a `test_` key never touches production data, and a `live_` key cannot be used against the sandbox host.

Authenticated request

```
curl https://api.nexa.dev/v2/payments \
-H "Authorization: Bearer live_9k2Lp7XwQrT4vB1nZcHf" \
-H "Content-Type: application/json"
```

Caution

Do not embed `live_` keys in client-side or mobile code. Keys are shown once at creation time; a lost key must be revoked and reissued, since Nexa does not store the plaintext value after generation.

1.1 Key rotation

🔄 Rotate keys at least every 180 days; old and new keys overlap for 24 hours.

🔄 Revoking a key invalidates it within 30 seconds across all edge regions.

2 Endpoint Reference

The table below covers the core resources exposed under `/v2`. Full parameter schemas for each endpoint are listed in the OpenAPI document linked from the developer dashboard.

Method	Path	Description	Auth
GET	<code>/payments</code>	List payments, filterable by status and date range.	🔒
POST	<code>/payments</code>	Create a payment intent for a customer or card token.	🔒
GET	<code>/payments/{id}</code>	Retrieve a single payment by its identifier.	🔒
PUT	<code>/payments/{id}</code>	Update metadata or capture an authorized payment.	🔒
DELETE	<code>/payments/{id}</code>	Cancel a payment that has not yet settled.	🔒
GET	<code>/customers</code>	List customers with pagination cursors.	🔒