

CHAIN SLINGS CHART

CHAIN SLINGS CHART

- The range consists of chain sizes from 6mm through to 32mm offering lifting capacities of up to 67 tons.
- A wide range of terminal lifting are available in all sizes including clevis self-locking hooks, clevis sling hooks, grab hooks, shortening clutches etc.
- Each chain sling is fitted with an identification tag that display the WLL of the sling and an individual serial number.
- All slings are supplied with the certificate of conformity.
- Chains slings meets the standard of EN818-4.

CHAIN SLING SPECIFICATIONS

Factor of Safety		Single Leg Chains		2 Leg Chains				3 and 4 Leg Chains		Endless Chains	Basket Chains	
4												
Working Angles		-	-	0° - 45°	45° - 60°	0° - 45°	45° - 60°	0 - 45°	45° - 60°	-	0° - 45°	0° - 45°
Load Factor		1	0.8	1.4	1	1.12	0.8	2.1	1.5	1.6	1.4	2.1
Grade	Dia	Working Load Limits (Tonnes)										
8	6mm	1.12	0.90	1.60	1.12	1.25	0.90	2.36	1.70	1.80	1.60	2.36
8	7mm	1.50	1.20	2.12	1.50	1.70	1.20	3.15	2.24	2.50	2.12	3.15
8	8mm	2.00	1.60	2.80	2.00	2.24	1.60	4.25	3.00	3.15	2.80	4.25
8	10mm	3.15	2.50	4.25	3.15	3.55	2.50	6.70	4.75	5.00	4.25	6.70
8	13mm	5.30	4.25	7.50	5.30	5.90	4.25	11.20	8.00	8.50	7.50	11.20
8	16mm	8.00	6.30	11.20	8.00	9.00	6.30	17.00	11.80	12.50	11.20	17.00
8	20mm	12.50	10.00	17.00	12.50	14.00	10.0	21.20	19.00	20.00	17.00	21.20
8	22mm	15.00	12.00	21.20	15.00	17.00	12.0	30.00	22.40	23.60	21.20	30.00
8	26mm	21.20	16.95	30.00	21.20	23.70	16.95	45.00	31.50	33.50	30.00	45.00
8	32mm	31.50	25.20	45.00	31.50	35.20	25.20	67.00	47.50	50.00	45.00	67.00