



Cyberscope

Audit Report

BinoFi

March 2025

Network ETH

Address 0x2fABa2b7DE630A426F252431Ffad0b28c5A65FE2

Audited by © cyberscope

Analysis

● Critical ● Medium ● Minor / Informative ● Pass

Severity	Code	Description	Status
●	ST	Stops Transactions	Unresolved
●	OTUT	Transfers User's Tokens	Passed
●	ELFM	Exceeds Fees Limit	Passed
●	MT	Mints Tokens	Passed
●	BT	Burns Tokens	Passed
●	BC	Blacklists Addresses	Passed

Diagnostics

● Critical ● Medium ● Minor / Informative

Severity	Code	Description	Status
●	MEE	Missing Events Emission	Unresolved
●	RID	Redundant Interface Declaration	Unresolved
●	RSML	Redundant SafeMath Library	Unresolved
●	RSRS	Redundant SafeMath Require Statement	Unresolved
●	L02	State Variables could be Declared Constant	Unresolved
●	L04	Conformance to Solidity Naming Conventions	Unresolved
●	L16	Validate Variable Setters	Unresolved
●	L20	Succeeded Transfer Check	Unresolved

Table of Contents

Analysis	1
Diagnostics	2
Table of Contents	3
Risk Classification	5
Review	6
Audit Updates	6
Source Files	6
Findings Breakdown	7
ST - Stops Transactions	8
Description	8
Recommendation	8
MEE - Missing Events Emission	9
Description	9
Recommendation	9
RID - Redundant Interface Declaration	10
Description	10
Recommendation	10
RSML - Redundant SafeMath Library	11
Description	11
Recommendation	11
RSRS - Redundant SafeMath Require Statement	12
Description	12
Recommendation	12
L02 - State Variables could be Declared Constant	13
Description	13
Recommendation	13
L04 - Conformance to Solidity Naming Conventions	14
Description	14
Recommendation	15
L16 - Validate Variable Setters	16
Description	16
Recommendation	16
L20 - Succeeded Transfer Check	17
Description	17
Recommendation	17
Functions Analysis	18
Inheritance Graph	20
Flow Graph	21
Summary	22

Disclaimer**23****About Cyberscope****24**

Risk Classification

The criticality of findings in Cyberscope's smart contract audits is determined by evaluating multiple variables. The two primary variables are:

1. **Likelihood of Exploitation:** This considers how easily an attack can be executed, including the economic feasibility for an attacker.
2. **Impact of Exploitation:** This assesses the potential consequences of an attack, particularly in terms of the loss of funds or disruption to the contract's functionality.

Based on these variables, findings are categorized into the following severity levels:

1. **Critical:** Indicates a vulnerability that is both highly likely to be exploited and can result in significant fund loss or severe disruption. Immediate action is required to address these issues.
2. **Medium:** Refers to vulnerabilities that are either less likely to be exploited or would have a moderate impact if exploited. These issues should be addressed in due course to ensure overall contract security.
3. **Minor:** Involves vulnerabilities that are unlikely to be exploited and would have a minor impact. These findings should still be considered for resolution to maintain best practices in security.
4. **Informative:** Points out potential improvements or informational notes that do not pose an immediate risk. Addressing these can enhance the overall quality and robustness of the contract.

Severity	Likelihood / Impact of Exploitation
● Critical	Highly Likely / High Impact
● Medium	Less Likely / High Impact or Highly Likely/ Lower Impact
● Minor / Informative	Unlikely / Low to no Impact

Review

Contract Name	Binofi
Compiler Version	v0.8.28+commit.7893614a
Optimization	200 runs
Explorer	https://etherscan.io/address/0x2faba2b7de630a426f252431ffad0b28c5a65fe2
Address	0x2faba2b7de630a426f252431ffad0b28c5a65fe2
Network	ETH
Symbol	BINO
Decimals	18
Total Supply	2,000,000,000
Badge Eligibility	Yes

Audit Updates

Initial Audit	12 Mar 2025
---------------	-------------

Source Files

Filename	SHA256
Binofi.sol	e5c723392e78b7c78b9ed2ca35e62cfa81c58151c303c443818295df6a6aa0bd

Findings Breakdown



Critical	1
Medium	0
Minor / Informative	8

Severity	Unresolved	Acknowledged	Resolved	Other
Critical	1	0	0	0
Medium	0	0	0	0
Minor / Informative	8	0	0	0

ST - Stops Transactions

Criticality	Critical
Location	Binofi.sol#L261
Status	Unresolved

Description

The transactions are initially disabled for all users excluding the authorized addresses. The owner can enable the transactions for all users. Once the transactions are enable the owner will not be able to disable them again.

```
if (!whitelist[from] && !whitelist[to]) {  
    // trading disable till launch  
    require(trading, "BinoFi: Trading is disable");  
}
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

MEE - Missing Events Emission

Criticality	Minor / Informative
Location	Binofi.sol#L239,243
Status	Unresolved

Description

The contract performs actions and state mutations from external methods that do not result in the emission of events. Emitting events for significant actions is important as it allows external parties, such as wallets or dApps, to track and monitor the activity on the contract. Without these events, it may be difficult for external parties to accurately determine the current state of the contract.

```
trading = true;  
whitelist[_user] = _exmpt;
```

Recommendation

It is recommended to include events in the code that are triggered each time a significant action is taking place within the contract. These events should include relevant details such as the user's address and the nature of the action taken. By doing so, the contract will be more transparent and easily auditable by external parties. It will also help prevent potential issues or disputes that may arise in the future.

RID - Redundant Interface Declaration

Criticality	Minor / Informative
Location	Binofi.sol#L37,44
Status	Unresolved

Description

There are code segments that could be optimized. A segment may be optimized so that it becomes a smaller size, consumes less memory, executes more rapidly, or performs fewer operations.

The contract declares certain interfaces that are used in a meaningful way by the contract. As a result, these interfaces are redundant.

```
interface IDexFactory { ... }  
interface IDexRouter { ... }
```

Recommendation

The team is advised to take these segments into consideration and rewrite them so the runtime will be more performant. That way it will improve the efficiency and performance of the source code and reduce the cost of executing it.

RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Location	Binofi.sol
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert to underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, overhead and increases gas consumption unnecessarily in cases where the explanatory error message is not used.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library in cases where the revert error message is not used. Since the version of the contract is greater than `0.8.0` then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the `unchecked { ... }` statement.

Read more about the breaking change on

<https://docs.soliditylang.org/en/stable/080-breaking-changes.html#solidity-v0-8-0-breaking-changes>.

RSRS - Redundant SafeMath Require Statement

Criticality	Minor / Informative
Location	Binofi.sol#L276
Status	Unresolved

Description

The contract utilizes a `require` statement within the `add` function aiming to prevent overflow errors. This function is designed based on the SafeMath library's principles. In Solidity version 0.8.0 and later, arithmetic operations revert on overflow and underflow, making the overflow check within the function redundant. This redundancy could lead to extra gas costs and increased complexity without providing additional security.

```
function add(uint256 a, uint256 b) internal pure returns (uint256) {  
    uint256 c = a + b;  
    require(c >= a, "SafeMath: addition overflow");  
  
    return c;  
}
```

Recommendation

It is recommended to remove the `require` statement from the `add` function since the contract is using a Solidity pragma version equal to or greater than 0.8.0. By doing so, the contract will leverage the built-in overflow and underflow checks provided by the Solidity language itself, simplifying the code and reducing gas consumption. This change will uphold the contract's integrity in handling arithmetic operations while optimizing for efficiency and cost-effectiveness.

L02 - State Variables could be Declared Constant

Criticality	Minor / Informative
Location	Binofi.sol#L125,126,127,128
Status	Unresolved

Description

State variables can be declared as constant using the constant keyword. This means that the value of the state variable cannot be changed after it has been set. Additionally, the constant variables decrease gas consumption of the corresponding transaction.

```
string private _name = "BinoFi"  
string private _symbol = "BINO"  
uint8 private _decimals = 18  
uint256 private _totalSupply = 2_000_000_000 * 1e18
```

Recommendation

Constant state variables can be useful when the contract wants to ensure that the value of a state variable cannot be changed by any function in the contract. This can be useful for storing values that are important to the contract's behavior, such as the contract's address or the maximum number of times a certain function can be called. The team is advised to add the constant keyword to state variables that never change.

L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	Binofi.sol#L47,229,233,242
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```
function WETH() external pure returns (address);
address _receiver
address _token
uint256 _amount
bool _exmpt
address _user
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

<https://docs.soliditylang.org/en/stable/style-guide.html#naming-conventions>.

L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	Binofi.sol#L230
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```
payable(_receiver).transfer(address(this).balance)
```

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.

L20 - Succeeded Transfer Check

Criticality	Minor / Informative
Location	Binofi.sol#L234
Status	Unresolved

Description

According to the ERC20 specification, the transfer methods should be checked if the result is successful. Otherwise, the contract may wrongly assume that the transfer has been established.

```
IERC20(_token).transfer(_receiver, _amount)
```

Recommendation


The contract should check if the result of the transfer methods is successful. The team is advised to check the SafeERC20 library from the [Openzeppelin library](#).

Functions Analysis


Contract	Type	Bases		
	Function Name	Visibility	Mutability	Modifiers
Binofi	Implementation	Context, IERC20, Ownable		
		Public	✓	-
		External	Payable	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	✓	-
	allowance	Public		-
	approve	Public	✓	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	✓	-
	decreaseAllowance	Public	✓	-
	removeStuckEth	Public	✓	onlyOwner
	removeStuckToken	Public	✓	onlyOwner
	enableTrading	External	✓	onlyOwner
	setWhitelist	External	✓	onlyOwner
	_approve	Private	✓	

	_transfer	Private	✓	
--	-----------	---------	---	--

Inheritance Graph



Flow Graph



Summary

BinoFi contract implements a token mechanism. This audit investigates security issues, business logic concerns, and potential improvements. BinoFi is an interesting project that has a friendly and growing community. The Smart Contract analysis reported no compiler errors or critical issues. The contract Owner can access some admin functions that can not be used in a malicious way to disturb the users' transactions.

Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security. Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

cyberscope.io