



Cyberscope

Audit Report

Niza

October 2023

Network ETH

Address 0xb58E26ac9cc14c0422C2b419b0CA555Ee4DcB7CB

Audited by © cyberscope

Analysis

● Critical ● Medium ● Minor / Informative ● Pass

Severity	Code	Description	Status
●	ST	Stops Transactions	Passed
●	OTUT	Transfers User's Tokens	Passed
●	ELFM	Exceeds Fees Limit	Passed
●	MT	Mints Tokens	Passed
●	BT	Burns Tokens	Passed
●	BC	Blacklists Addresses	Passed

Diagnostics

● Critical ● Medium ● Minor / Informative

Severity	Code	Description	Status
●	RSW	Redundant Storage Writes	Unresolved
●	MEE	Missing Events Emission	Unresolved
●	RVD	Redundant Variable Declaration	Unresolved
●	RRS	Redundant Require Statement	Unresolved
●	RSML	Redundant SafeMath Library	Unresolved
●	IDI	Immutable Declaration Improvement	Unresolved
●	L02	State Variables could be Declared Constant	Unresolved
●	L04	Conformance to Solidity Naming Conventions	Unresolved
●	L07	Missing Events Arithmetic	Unresolved
●	L09	Dead Code Elimination	Unresolved
●	L16	Validate Variable Setters	Unresolved
●	L17	Usage of Solidity Assembly	Unresolved
●	L19	Stable Compiler Version	Unresolved

Table of Contents

Analysis	1
Diagnostics	2
Table of Contents	3
Review	5
Audit Updates	5
Source Files	5
Findings Breakdown	6
RSW - Redundant Storage Writes	7
Description	7
Recommendation	7
MEE - Missing Events Emission	8
Description	8
Recommendation	8
RVD - Redundant Variable Declaration	9
Description	9
Recommendation	9
RRS - Redundant Require Statement	10
Description	10
Recommendation	10
RSML - Redundant SafeMath Library	11
Description	11
Recommendation	11
IDI - Immutable Declaration Improvement	12
Description	12
Recommendation	12
L02 - State Variables could be Declared Constant	13
Description	13
Recommendation	13
L04 - Conformance to Solidity Naming Conventions	14
Description	14
Recommendation	15
L07 - Missing Events Arithmetic	16
Description	16
Recommendation	16
L09 - Dead Code Elimination	17
Description	17
Recommendation	18
L16 - Validate Variable Setters	19
Description	19

Recommendation	19
L17 - Usage of Solidity Assembly	20
Description	20
Recommendation	20
L19 - Stable Compiler Version	21
Description	21
Recommendation	21
Functions Analysis	22
Inheritance Graph	26
Flow Graph	27
Summary	28
Disclaimer	29
About Cyberscope	30

Review

Contract Name	Niza
Compiler Version	v0.8.17+commit.8df45f5f
Optimization	200 runs
Explorer	https://etherscan.io/address/0xb58e26ac9cc14c0422c2b419b0ca555ee4dcb7cb
Address	0xb58e26ac9cc14c0422c2b419b0ca555ee4dcb7cb
Network	ETH
Symbol	Niza
Decimals	9
Total Supply	10,000,000,000


Audit Updates

Initial Audit	18 Oct 2023
---------------	-------------

Source Files

Filename	SHA256
Niza.sol	a42d9ba12c944a97c1245a7322281c6dd779c4b1a0ec7efdc7080f7a3afbc3aa

Findings Breakdown



● Critical	0
● Medium	0
● Minor / Informative	13

Severity	Unresolved	Acknowledged	Resolved	Other
● Critical	0	0	0	0
● Medium	0	0	0	0
● Minor / Informative	13	0	0	0

RSW - Redundant Storage Writes

Criticality	Minor / Informative
Location	Niza.sol#L520,525
Status	Unresolved

Description

The contract modifies the state of the following variables without checking if their current value matches the provided argument. As a result, the contract performs redundant storage writes, when the provided parameter matches the current state of the variables, leading to unnecessary gas consumption and inefficiencies in contract execution.

```
_isEnemy[account] = value;  
Pause = value;
```

Recommendation

The team is advised to implement additional checks within to prevent redundant storage writes when the provided argument matches the current state of the variables. By incorporating statements to compare the new values with the existing values before proceeding with any state modification, the contract can avoid unnecessary storage operations, thereby optimizing gas usage.

MEE - Missing Events Emission

Criticality	Minor / Informative
Location	Niza.sol#L520,525,634
Status	Unresolved

Description

The contract performs actions and state mutations from external methods that do not result in the emission of events. Emitting events for significant actions is important as it allows external parties, such as wallets or dApps, to track and monitor the activity on the contract. Without these events, it may be difficult for external parties to accurately determine the current state of the contract.

```
_isEnemy[account] = value;  
Pause = value;  
FeeAddress = account;
```

Recommendation

It is recommended to include events in the code that are triggered each time a significant action is taking place within the contract. These events should include relevant details such as the user's address and the nature of the action taken. By doing so, the contract will be more transparent and easily auditable by external parties. It will also help prevent potential issues or disputes that may arise in the future.

RVD - Redundant Variable Declaration

Criticality	Minor / Informative
Location	Niza.sol#L462
Status	Unresolved

Description

There are code segments that could be optimized. A segment may be optimized so that it becomes a smaller size, consumes less memory, executes more rapidly, or performs fewer operations.

The contract declares certain variables that are not used in a meaningful way by the contract. As a result, these variables are redundant.

```
uint256 public Optimization = 30125312006352599514018880656650049718;
```

Recommendation

The team is advised to take these segments into consideration and rewrite them so the runtime will be more performant. That way it will improve the efficiency and performance of the source code and reduce the cost of executing it.

RRS - Redundant Require Statement

Criticality	Minor / Informative
Location	Niza.sol#L117
Status	Unresolved

Description

The contract utilizes a `require` statement within the `add` function aiming to prevent overflow errors. This function is designed based on the SafeMath library's principles. In Solidity version 0.8.0 and later, arithmetic operations revert on overflow and underflow, making the overflow check within the function redundant. This redundancy could lead to extra gas costs and increased complexity without providing additional security.

```
function add(uint256 a, uint256 b) internal pure returns (uint256) {  
    uint256 c = a + b;  
    require(c >= a, "SafeMath: addition overflow");  
    return c;  
}
```

Recommendation

It is recommended to remove the `require` statement from the `add` function since the contract is using a Solidity pragma version equal to or greater than 0.8.0. By doing so, the contract will leverage the built-in overflow and underflow checks provided by the Solidity language itself, simplifying the code and reducing gas consumption. This change will uphold the contract's integrity in handling arithmetic operations while optimizing for efficiency and cost-effectiveness.

RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Location	Niza.sol
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert to underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, overhead and increases gas consumption unnecessarily.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library. Since the version of the contract is greater than `0.8.0` then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the `unchecked { ... }` statement.

Read more about the breaking change on

<https://docs.soliditylang.org/en/v0.8.16/080-breaking-changes.html#solidity-v0-8-0-breaking-changes>.

IDI - Immutable Declaration Improvement

Criticality	Minor / Informative
Location	Niza.sol#L488,489
Status	Unresolved

Description

The contract declares state variables that their value is initialized once in the constructor and are not modified afterwards. The `immutable` is a special declaration for this kind of state variables that saves gas when it is defined.

```
_DECIMALS  
_DECIMALFACTOR
```

Recommendation

By declaring a variable as immutable, the Solidity compiler is able to make certain optimizations. This can reduce the amount of storage and computation required by the contract, and make it more gas-efficient.

L02 - State Variables could be Declared Constant

Criticality	Minor / Informative
Location	Niza.sol#L459,461,462
Status	Unresolved

Description

State variables can be declared as constant using the constant keyword. This means that the value of the state variable cannot be changed after it has been set. Additionally, the constant variables decrease gas consumption of the corresponding transaction.

```
uint256 private _MAX = ~uint256(0)
uint256 private _GRANULARITY = 100
uint256 public Optimization = 30125312006352599514018880656650049718
```

Recommendation

Constant state variables can be useful when the contract wants to ensure that the value of a state variable cannot be changed by any function in the contract. This can be useful for storing values that are important to the contract's behavior, such as the contract's address or the maximum number of times a certain function can be called. The team is advised to add the constant keyword to state variables that never change.

L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	Niza.sol#L400,454,455,456,457,459,460,461,462,470,471,472,475,478,481,482,483,519,638
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```
address public _owner
string private _NAME
string private _SYMBOL
uint256 private _DECIMALS
address public FeeAddress
uint256 private _MAX = ~uint256(0)
uint256 private _DECIMALFACTOR
uint256 private _GRANULARITY = 100
uint256 public Optimization = 30125312006352599514018880656650049718
uint256 public _TAX_FEE
uint256 public _BURN_FEE
uint256 public _CHARITY_FEE
mapping(address => bool) public _isEnemy
bool public Pause = false

...
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

<https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention>.

L07 - Missing Events Arithmetic

Criticality	Minor / Informative
Location	Niza.sol#L640
Status	Unresolved

Description

Events are a way to record and log information about changes or actions that occur within a contract. They are often used to notify external parties or clients about events that have occurred within the contract, such as the transfer of tokens or the completion of a task.

It's important to carefully design and implement the events in a contract, and to ensure that all required events are included. It's also a good idea to test the contract to ensure that all events are being properly triggered and logged.

```
_TAX_FEE = _txFee* 100
```

Recommendation

By including all required events in the contract and thoroughly testing the contract's functionality, the contract ensures that it performs as intended and does not have any missing events that could cause issues with its arithmetic.

L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	Niza.sol#L270,297,323,333,348,358,363,846
Status	Unresolved

Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
function isContract(address account) internal view returns (bool) {
    // According to EIP-1052, 0x0 is the value returned for not-yet
    created accounts
    // and
    0xc5d2460186f7233c927e7db2dcc703c0e500b653ca82273b7bfad8045d85a470 is
    returned
    // for accounts without code, i.e. 'keccak256(')
    bytes32 codehash;
    bytes32 accountHash =
    0xc5d2460186f7233c927e7db2dcc703c0e500b653ca82273b7bfad8045d85a470;
    // solhint-disable-next-line no-inline-assembly
    assembly { codehash := extcodehash(account) }
    return (codehash != accountHash && codehash != 0x0);
}

...
```

Recommendation

To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.

L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	Niza.sol#L498,499,501,634
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```
FeeAddress = _FeeAddress
_owner = tokenOwner
payable(service).transfer(msg.value)
FeeAddress = account
```

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.

L17 - Usage of Solidity Assembly

Criticality	Minor / Informative
Location	Niza.sol#L277,376
Status	Unresolved

Description

Using assembly can be useful for optimizing code, but it can also be error-prone. It's important to carefully test and debug assembly code to ensure that it is correct and does not contain any errors.

Some common types of errors that can occur when using assembly in Solidity include Syntax, Type, Out-of-bounds, Stack, and Revert.

```
assembly { codehash := extcodehash(account) }

assembly {
    let returndata_size := mload(returndata)
    revert(add(32, returndata), returndata_size)
}
```

Recommendation

It is recommended to use assembly sparingly and only when necessary, as it can be difficult to read and understand compared to Solidity code.

L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	Niza.sol#L5
Status	Unresolved

Description

The `^` symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
pragma solidity ^0.8.2;
```

Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.

Functions Analysis


Contract	Type	Bases		
	Function Name	Visibility	Mutability	Modifiers
Context	Implementation			
	_msgSender	Internal		
	_msgData	Internal		
IBEP20	Interface			
	totalSupply	External		-
	balanceOf	External		-
	transfer	External	✓	-
	allowance	External		-
	approve	External	✓	-
	transferFrom	External	✓	-
SafeMath	Library			
	add	Internal		
	sub	Internal		
	sub	Internal		
	mul	Internal		
	div	Internal		

	div	Internal		
	mod	Internal		
	mod	Internal		
Address	Library			
	isContract	Internal		
	sendValue	Internal	✓	
	functionCall	Internal	✓	
	functionCall	Internal	✓	
	functionCallWithValue	Internal	✓	
	functionCallWithValue	Internal	✓	
	_functionCallWithValue	Private	✓	
Ownable	Implementation	Context		
	owner	Public		-
	renounceOwnership	Public	✓	onlyOwner
	transferOwnership	Public	✓	onlyOwner
Niza	Implementation	Context, IBEP20, Ownable		
		Public	Payable	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-


	EnemyAddress	External	✓	onlyOwner
	setPause	External	✓	onlyOwner
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	✓	-
	allowance	Public		-
	approve	Public	✓	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	✓	-
	decreaseAllowance	Public	✓	-
	isExcluded	Public		-
	totalFees	Public		-
	totalBurn	Public		-
	totalCharity	Public		-
	deliver	Public	✓	-
	reflectionFromToken	Public		-
	tokenFromReflection	Public		-
	excludeAccount	External	✓	onlyOwner
	includeAccount	External	✓	onlyOwner
	setAsCharityAccount	External	✓	onlyOwner
	updateFee	Public	✓	onlyOwner
	_approve	Private	✓	
	_transfer	Private	✓	

	_transferStandard	Private	✓	
	_standardTransferContent	Private	✓	
	_transferToExcluded	Private	✓	
	_excludedFromTransferContent	Private	✓	
	_transferFromExcluded	Private	✓	
	_excludedToTransferContent	Private	✓	
	_transferBothExcluded	Private	✓	
	_bothTransferContent	Private	✓	
	_reflectFee	Private	✓	
	_getValues	Private		
	_getTBasics	Private		
	getTTransferAmount	Private		
	_getRBasics	Private		
	_getRTransferAmount	Private		
	_getRate	Private		
	_getCurrentSupply	Private		
	_sendToCharity	Private	✓	
	removeAllFee	Private	✓	
	restoreAllFee	Private	✓	
	_getTaxFee	Private		

Inheritance Graph



Flow Graph



Summary

Niza contract implements a token mechanism. This audit investigates security issues, business logic concerns and potential improvements. niza is an interesting project that has a friendly and growing community. The Smart Contract analysis reported no compiler error or critical issues. The contract's ownership has been renounced. The information regarding the transaction can be accessed through the following link:

<https://etherscan.io/tx/0x535a6eddf1a5b2c4ae8a3c4973f87655cc545646c27bb1a03baf3c6c899b3e4d>. The fees are locked at 0% for all transactions.

Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security. Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

<https://www.cyberscope.io>