



Cyberscope

Audit Report

Pry.Finance

January 2024

Network ETH

Address 0x6378baA17Dc84999770bB553F98bc06d744A28c9

Audited by © cyberscope

Analysis

● Critical ● Medium ● Minor / Informative ● Pass

Severity	Code	Description	Status
●	ST	Stops Transactions	Unresolved
●	OTUT	Transfers User's Tokens	Passed
●	ELFM	Exceeds Fees Limit	Passed
●	MT	Mints Tokens	Passed
●	BT	Burns Tokens	Passed
●	BC	Blacklists Addresses	Passed

Diagnostics

● Critical ● Medium ● Minor / Informative

Severity	Code	Description	Status
●	DDP	Decimal Division Precision	Unresolved
●	IDI	Immutable Declaration Improvement	Unresolved
●	MEE	Missing Events Emission	Unresolved
●	RED	Redundant Event Declaration	Unresolved
●	RSML	Redundant SafeMath Library	Unresolved
●	RSW	Redundant Storage Writes	Unresolved
●	L04	Conformance to Solidity Naming Conventions	Unresolved
●	L09	Dead Code Elimination	Unresolved
●	L13	Divide before Multiply Operation	Unresolved
●	L15	Local Scope Variable Shadowing	Unresolved

Table of Contents

Analysis	1
Diagnostics	2
Table of Contents	3
Review	5
Audit Updates	5
Source Files	6
Findings Breakdown	7
ST - Stops Transactions	8
Description	8
Recommendation	8
DDP - Decimal Division Precision	9
Description	9
Recommendation	9
IDI - Immutable Declaration Improvement	10
Description	10
Recommendation	10
MEE - Missing Events Emission	11
Description	11
Recommendation	11
RED - Redundant Event Declaration	12
Description	12
Recommendation	12
RSML - Redundant SafeMath Library	13
Description	13
Recommendation	13
RSW - Redundant Storage Writes	14
Description	14
Recommendation	14
L04 - Conformance to Solidity Naming Conventions	15
Description	15
Recommendation	16
L09 - Dead Code Elimination	17
Description	17
Recommendation	18
L13 - Divide before Multiply Operation	19
Description	19
Recommendation	19
L15 - Local Scope Variable Shadowing	20
Description	20

Recommendation	20
Functions Analysis	21
Inheritance Graph	27
Flow Graph	28
Summary	29
Disclaimer	30
About Cyberscope	31

Review

Contract Name	Pry
Compiler Version	v0.8.20+commit.a1b79de6
Optimization	200 runs
Explorer	https://etherscan.io/address/0x6378baa17dc84999770bb553f98bc06d744a28c9
Address	0x6378baa17dc84999770bb553f98bc06d744a28c9
Network	ETH
Symbol	Pry
Decimals	18
Total Supply	10,000,000
Badge Eligibility	Yes

Audit Updates

Initial Audit	14 Jan 2024
Corrected Phase 2	16 Jan 2024

Source Files

Filename	SHA256
Pry.sol	e95ad6f98d3774460c846f3e4f1589e9c7a55b144da8ce400e76b91a546 efa69

Findings Breakdown



Critical	1
Medium	0
Minor / Informative	10

Severity	Unresolved	Acknowledged	Resolved	Other
Critical	1	0	0	0
Medium	0	0	0	0
Minor / Informative	10	0	0	0

ST - Stops Transactions

Criticality	Critical
Location	contracts/Pry.sol#L1209
Status	Unresolved

Description

The transactions are initially disabled for all users excluding the authorized addresses. The owner can enable the transactions for all users. Once the transactions are enabled the owner will not be able to disable them again.

```
if (!tradingActive) {  
    require(  
        _isExcludedFromFees[from] || _isExcludedFromFees[to],  
        "Trading is not active."  
    );  
}
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

DDP - Decimal Division Precision

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1275,1276,1280,1281
Status	Unresolved

Description

Division of decimal (fixed point) numbers can result in rounding errors due to the way that division is implemented in Solidity. Thus, it may produce issues with precise calculations with decimal numbers.

Solidity represents decimal numbers as integers, with the decimal point implied by the number of decimal places specified in the type (e.g. decimal with 18 decimal places). When a division is performed with decimal numbers, the result is also represented as an integer, with the decimal point implied by the number of decimal places in the type. This can lead to rounding errors, as the result may not be able to be accurately represented as an integer with the specified number of decimal places.

Hence, the splitted shares will not have the exact precision and some funds may not be calculated as expected.

```
tokensForLiquidity += (fees * sellLiquidityFee) / sellTotalFees;  
tokensForDistro += (fees * sellDistroFee) / sellTotalFees;  
  
tokensForLiquidity += (fees * buyLiquidityFee) / buyTotalFees;  
tokensForDistro += (fees * buyDistroFee) / buyTotalFees;
```

Recommendation

The team is advised to take into consideration the rounding results that are produced from the solidity calculations. The contract could calculate the subtraction of the divided funds in the last calculation in order to avoid the division rounding issue.

IDI - Immutable Declaration Improvement

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1117,1118,1121,1122,1123,1125,1126,1127
Status	Unresolved

Description

The contract declares state variables that their value is initialized once in the constructor and are not modified afterwards. The `immutable` is a special declaration for this kind of state variables that saves gas when it is defined.

```
maxTransactionAmount
maxWallet
buyDistroFee
buyLiquidityFee
buyTotalFees
sellDistroFee
sellLiquidityFee
sellTotalFees
```

Recommendation

By declaring a variable as immutable, the Solidity compiler is able to make certain optimizations. This can reduce the amount of storage and computation required by the contract, and make it more gas-efficient.

MEE - Missing Events Emission

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1149,1158
Status	Unresolved

Description

The contract performs actions and state mutations from external methods that do not result in the emission of events. Emitting events for significant actions is important as it allows external parties, such as wallets or dApps, to track and monitor the activity on the contract. Without these events, it may be difficult for external parties to accurately determine the current state of the contract.

```
tradingActive = true;  
_isExcludedMaxTransactionAmount[updAds] = isEx;
```

Recommendation

It is recommended to include events in the code that are triggered each time a significant action is taking place within the contract. These events should include relevant details such as the user's address and the nature of the action taken. By doing so, the contract will be more transparent and easily auditable by external parties. It will also help prevent potential issues or disputes that may arise in the future.

RED - Redundant Event Declaration

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1081
Status	Unresolved

Description

There are code segments that could be optimized. A segment may be optimized so that it becomes a smaller size, consumes less memory, executes more rapidly, or performs fewer operations.

The contract declares certain events in its code. However, these events are not emitted within the contract's functions. As a result, these declared events are redundant and serve no purpose within the contract's current implementation.

```
event UpdateUniswapV2Router(  
    address indexed newAddress,  
    address indexed oldAddress  
);
```

Recommendation

The team is advised to take these segments into consideration and rewrite them so the runtime will be more performant. That way it will improve the efficiency and performance of the source code and reduce the cost of executing it.

RSML - Redundant SafeMath Library

Criticality	Minor / Informative
Location	contracts/Pry.sol
Status	Unresolved

Description

SafeMath is a popular Solidity library that provides a set of functions for performing common arithmetic operations in a way that is resistant to integer overflows and underflows.

Starting with Solidity versions that are greater than or equal to 0.8.0, the arithmetic operations revert to underflow and overflow. As a result, the native functionality of the Solidity operations replaces the SafeMath library. Hence, the usage of the SafeMath library adds complexity, overhead and increases gas consumption unnecessarily.

```
library SafeMath {...}
```

Recommendation

The team is advised to remove the SafeMath library. Since the version of the contract is greater than `0.8.0` then the pure Solidity arithmetic operations produce the same result.

If the previous functionality is required, then the contract could exploit the `unchecked { ... }` statement.

Read more about the breaking change on

<https://docs.soliditylang.org/en/v0.8.16/080-breaking-changes.html#solidity-v0-8-0-breaking-changes>.

RSW - Redundant Storage Writes

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1149,1158,1163,1180
Status	Unresolved

Description

The contract modifies the state of the following variables without checking if their current value is the same as the one given as an argument. As a result, the contract performs redundant storage writes, when the provided parameter matches the current state of the variables, leading to unnecessary gas consumption and inefficiencies in contract execution.

```
tradingActive = true;  
_isExcludedMaxTransactionAmount[updAds] = isEx;  
_isExcludedFromFees[account] = excluded;  
automatedMarketMakerPairs[pair] = value;
```

Recommendation

The team is advised to implement additional checks within to prevent redundant storage writes when the provided argument matches the current state of the variables. By incorporating statements to compare the new values with the existing values before proceeding with any state modification, the contract can avoid unnecessary storage operations, thereby optimizing gas usage.

L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	contracts/Pry.sol#L927,929,960,1002,1077
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```
function DOMAIN_SEPARATOR() external view returns (bytes32);
function PERMIT_TYPEHASH() external pure returns (bytes32);
function MINIMUM_LIQUIDITY() external pure returns (uint256);
function WETH() external pure returns (address);
mapping(address => bool) public _isExcludedMaxTransactionAmount
```


Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

<https://docs.soliditylang.org/en/v0.8.17/style-guide.html#naming-convention>.

L09 - Dead Code Elimination

Criticality	Minor / Informative
Location	contracts/Pry.sol#L542
Status	Unresolved

Description

In Solidity, dead code is code that is written in the contract, but is never executed or reached during normal contract execution. Dead code can occur for a variety of reasons, such as:

- Conditional statements that are always false.
- Functions that are never called.
- Unreachable code (e.g., code that follows a return statement).

Dead code can make a contract more difficult to understand and maintain, and can also increase the size of the contract and the cost of deploying and interacting with it.

```
function _burn(address account, uint256 amount) internal virtual {
    require(account != address(0), "ERC20: burn from the zero address");

    _beforeTokenTransfer(account, address(0), amount);

    uint256 accountBalance = _balances[account];
    ...
}
_totalSupply -= amount;

emit Transfer(account, address(0), amount);

_afterTokenTransfer(account, address(0), amount);
}
```

Recommendation

To avoid creating dead code, it's important to carefully consider the logic and flow of the contract and to remove any code that is not needed or that is never executed. This can help improve the clarity and efficiency of the contract.

L13 - Divide before Multiply Operation

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1274,1275,1276,1279,1280,1281
Status	Unresolved

Description

It is important to be aware of the order of operations when performing arithmetic calculations. This is especially important when working with large numbers, as the order of operations can affect the final result of the calculation. Performing divisions before multiplications may cause loss of precision.

```
fees = (amount * sellTotalFees) / 100
tokensForLiquidity += (fees * sellLiquidityFee) / sellTotalFees
```

Recommendation

To avoid this issue, it is recommended to carefully consider the order of operations when performing arithmetic calculations in Solidity. It's generally a good idea to use parentheses to specify the order of operations. The basic rule is that the multiplications should be prior to the divisions.

L15 - Local Scope Variable Shadowing

Criticality	Minor / Informative
Location	contracts/Pry.sol#L1115
Status	Unresolved

Description

Local scope variable shadowing occurs when a local variable with the same name as a variable in an outer scope is declared within a function or code block. When this happens, the local variable "shadows" the outer variable, meaning that it takes precedence over the outer variable within the scope in which it is declared.

```
uint256 totalSupply = 10_000_000 * 1e18
```

Recommendation

It's important to be aware of shadowing when working with local variables, as it can lead to confusion and unintended consequences if not used correctly. It's generally a good idea to choose unique names for local variables to avoid shadowing outer variables and causing confusion.

Functions Analysis

Contract	Type	Bases		
	Function Name	Visibility	Mutability	Modifiers
Context	Implementation			
	_msgSender	Internal		
	_msgData	Internal		
Ownable	Implementation	Context		
		Public	✓	-
	owner	Public		-
	renounceOwnership	Public	✓	onlyOwner
	transferOwnership	Public	✓	onlyOwner
	_transferOwnership	Internal	✓	
IERC20	Interface			
	totalSupply	External		-
	balanceOf	External		-
	transfer	External	✓	-
	allowance	External		-
	approve	External	✓	-
	transferFrom	External	✓	-

IERC20Metadata	Interface	IERC20		
	name	External		-
	symbol	External		-
	decimals	External		-
ERC20	Implementation	Context, IERC20, IERC20Meta data		
		Public	✓	-
	name	Public		-
	symbol	Public		-
	decimals	Public		-
	totalSupply	Public		-
	balanceOf	Public		-
	transfer	Public	✓	-
	allowance	Public		-
	approve	Public	✓	-
	transferFrom	Public	✓	-
	increaseAllowance	Public	✓	-
	decreaseAllowance	Public	✓	-
	_transfer	Internal	✓	
	_mint	Internal	✓	
	_burn	Internal	✓	


	_approve	Internal	✓	
	_beforeTokenTransfer	Internal	✓	
	_afterTokenTransfer	Internal	✓	
SafeMath	Library			
	tryAdd	Internal		
	trySub	Internal		
	tryMul	Internal		
	tryDiv	Internal		
	tryMod	Internal		
	add	Internal		
	sub	Internal		
	mul	Internal		
	div	Internal		
	mod	Internal		
	sub	Internal		
	div	Internal		
	mod	Internal		
IUniswapV2Factory	Interface			
	feeTo	External		-
	feeToSetter	External		-
	getPair	External		-

	allPairs	External		-
	allPairsLength	External		-
	createPair	External	✓	-
	setFeeTo	External	✓	-
	setFeeToSetter	External	✓	-
IUniswapV2Pair	Interface			
	name	External		-
	symbol	External		-
	decimals	External		-
	totalSupply	External		-
	balanceOf	External		-
	allowance	External		-
	approve	External	✓	-
	transfer	External	✓	-
	transferFrom	External	✓	-
	DOMAIN_SEPARATOR	External		-
	PERMIT_TYPEHASH	External		-
	nonces	External		-
	permit	External	✓	-
	MINIMUM_LIQUIDITY	External		-
	factory	External		-
	token0	External		-


	token1	External		-
	getReserves	External		-
	price0CumulativeLast	External		-
	price1CumulativeLast	External		-
	kLast	External		-
	mint	External	✓	-
	burn	External	✓	-
	swap	External	✓	-
	skim	External	✓	-
	sync	External	✓	-
	initialize	External	✓	-
IUniswapV2Router02	Interface			
	factory	External		-
	WETH	External		-
	addLiquidity	External	✓	-
	addLiquidityETH	External	Payable	-
	swapExactTokensForTokensSupportingFeeOnTransferTokens	External	✓	-
	swapExactETHForTokensSupportingFeeOnTransferTokens	External	Payable	-
	swapExactTokensForETHSupportingFeeOnTransferTokens	External	✓	-
Pry	Implementation	ERC20, Ownable		

		Public	✓	ERC20
		External	Payable	-
	enableTrading	External	✓	onlyOwner
	excludeFromMaxTransaction	Public	✓	onlyOwner
	excludeFromFees	Public	✓	onlyOwner
	setAutomatedMarketMakerPair	Public	✓	onlyOwner
	_setAutomatedMarketMakerPair	Private	✓	
	isExcludedFromFees	Public		-
	_transfer	Internal	✓	
	swapTokensForEth	Private	✓	
	addLiquidity	Private	✓	
	swapBack	Private	✓	

Inheritance Graph



Flow Graph



Summary

Pry.Finance contract implements a token mechanism. This audit investigates security issues, business logic concerns, and potential improvements. There are some functions that can be abused by the owner like stopping transactions. A multi-wallet signing pattern will provide security against potential hacks. Temporarily locking the contract or renouncing ownership will eliminate all the contract threats. The fees are locked at 4% on both buy and sell transactions.

Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security. Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

<https://www.cyberscope.io>