

Audit Report Pocketcoin Staking

March 2025

SHA256

b12a15ee11f9ee2f1fd10ed7dca6517163f2448a27df437804d17607579063e0

Audited by © cyberscope



Table of Contents

Table of Contents	1
Risk Classification	2
Review	3
Audit Updates	3
Source Files	3
Findings Breakdown	4
Diagnostics	5
CCR - Contract Centralization Risk	5
Description	6
Recommendation	6
CRP - Coupled Rewards Pool	7
Description	7
Recommendation	7
PTAI - Potential Transfer Amount Inconsistency	8
Description	8
Recommendation	9
L04 - Conformance to Solidity Naming Conventions	10
Description	10
Recommendation	10
L19 - Stable Compiler Version	11
Description	11
Recommendation	11
Functions Analysis	12
Inheritance Graph	13
Flow Graph	14
Summary	15
Disclaimer	16
About Cyberscope	17



Risk Classification

The criticality of findings in Cyberscope's smart contract audits is determined by evaluating multiple variables. The two primary variables are:

- 1. **Likelihood of Exploitation**: This considers how easily an attack can be executed, including the economic feasibility for an attacker.
- 2. **Impact of Exploitation**: This assesses the potential consequences of an attack, particularly in terms of the loss of funds or disruption to the contract's functionality.

Based on these variables, findings are categorized into the following severity levels:

- Critical: Indicates a vulnerability that is both highly likely to be exploited and can result in significant fund loss or severe disruption. Immediate action is required to address these issues.
- Medium: Refers to vulnerabilities that are either less likely to be exploited or would have a moderate impact if exploited. These issues should be addressed in due course to ensure overall contract security.
- Minor: Involves vulnerabilities that are unlikely to be exploited and would have a
 minor impact. These findings should still be considered for resolution to maintain
 best practices in security.
- 4. **Informative**: Points out potential improvements or informational notes that do not pose an immediate risk. Addressing these can enhance the overall quality and robustness of the contract.

Severity	Likelihood / Impact of Exploitation
 Critical 	Highly Likely / High Impact
Medium	Less Likely / High Impact or Highly Likely/ Lower Impact
Minor / Informative	Unlikely / Low to no Impact



Review

Audit Updates

Initial Audit	5 Mar 2025
Test Deploy	https://sepolia.etherscan.io/address/0xfE31f2C55Bf01FB7daF9 30213BCC6b5324c6df64

Source Files

Filename	SHA256
StakingContract_(2).sol	b12a15ee11f9ee2f1fd10ed7dca6517163f2448a27df437804d17607579 063e0



Findings Breakdown



Sev	verity	Unresolved	Acknowledged	Resolved	Other
•	Critical	0	0	0	0
	Medium	0	0	0	0
	Minor / Informative	5	0	0	0



Diagnostics

CriticalMediumMinor / Informative

Severity	Code	Description	Status
•	CCR	Contract Centralization Risk	Unresolved
•	CRP	Coupled Rewards Pool	Unresolved
•	PTAI	Potential Transfer Amount Inconsistency	Unresolved
•	L04	Conformance to Solidity Naming Conventions	Unresolved
•	L19	Stable Compiler Version	Unresolved



CCR - Contract Centralization Risk

Criticality	Minor / Informative
Location	StakingContract_(2).sol#L218,234,250
Status	Unresolved

Description

The contract's functionality and behavior are heavily dependent on external parameters or configurations. While external configuration can offer flexibility, it also poses several centralization risks that warrant attention. Centralization risks arising from the dependence on external configuration include Single Point of Control, Vulnerability to Attacks, Operational Delays, Trust Dependencies, and Decentralization Erosion.

```
function withdrawRemainingRewards() external nonReentrant onlyOwner {...}
function proposeMultiplierUpdate(uint256 lockDuration, uint256
newMultiplier) external onlyOwner {...}
function executeMultiplierUpdate(uint256 lockDuration) external onlyOwner
{...}
```

Recommendation

To address this finding and mitigate centralization risks, it is recommended to evaluate the feasibility of migrating critical configurations and functionality into the contract's codebase itself. This approach would reduce external dependencies and enhance the contract's self-sufficiency. It is essential to carefully weigh the trade-offs between external configuration flexibility and the risks associated with centralization.



CRP - Coupled Rewards Pool

Criticality	Minor / Informative
Location	StakingContract_(2).sol#L125
Status	Unresolved

Description

The contract maintains a balance of staked tokens and tokens aimed for rewards, where the staked tokens and reward tokens are the same token. The contract accepts a new stake by comparing its current balance to the staked amounts and the incoming deposit and rewards. The deposited balance of previous stakes is used to determine the eligibility of future stakes. Coupling user deposits with the expected rewards and the contract's balance is prone to errors and could yield inconsistencies.

```
uint256 contractBalance = token.balanceOf(address(this));
require(
contractBalance >= (totalStaked + totalPlannedRewards + amount +
plannedReward),
"Insufficient rewards in contract"
);
```

Recommendation

It is advisable to ensure consistency by maintaining a strict association between the available reward pool and the expected rewards. Decoupling the staked balance from the reward pool will ensure overall consistency.



PTAI - Potential Transfer Amount Inconsistency

Criticality	Minor / Informative
Location	StakingContract_(2).sol#L147
Status	Unresolved

Description

The transfer() and transferFrom() functions are used to transfer a specified amount of tokens to an address. The fee or tax is an amount that is charged to the sender of an ERC20 token when tokens are transferred to another address. According to the specification, the transferred amount could potentially be less than the expected amount. This may produce inconsistency between the expected and the actual behavior.

The following example depicts the diversion between the expected and actual amount.

Тах	Amount	Expected	Actual
No Tax	100	100	100
10% Tax	100	100	90

```
// Record the stake
stakes[msg.sender].push(Stake({
    amount: amount,
    startTime: block.timestamp,
    lockDuration: lockDuration,
    multiplier: multiplier,
    withdrawn: false
}));

// Transfer tokens from user to contract
token.safeTransferFrom(msg.sender, address(this), amount);
```



Recommendation

The team is advised to take into consideration the actual amount that has been transferred instead of the expected.

It is important to note that an ERC20 transfer tax is not a standard feature of the ERC20 specification, and it is not universally implemented by all ERC20 contracts. Therefore, the contract could produce the actual amount by calculating the difference between the transfer call.

Actual Transferred Amount = Balance After Transfer - Balance Before Transfer



L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	StakingContract_(2).sol#L89
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

- 1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
- 2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
- 3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
- 4. Use indentation to improve readability and structure.
- 5. Use spaces between operators and after commas.
- 6. Use comments to explain the purpose and behavior of the code.
- 7. Keep lines short (around 120 characters) to improve readability.

```
/// @param _tokenAddress The address of the ER
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation

https://docs.soliditylang.org/en/stable/style-guide.html#naming-conventions.



L19 - Stable Compiler Version

Criticality	Minor / Informative
Location	StakingContract_(2).sol#L2,4
Status	Unresolved

Description

The ^ symbol indicates that any version of Solidity that is compatible with the specified version (i.e., any version that is a higher minor or patch version) can be used to compile the contract. The version lock is a mechanism that allows the author to specify a minimum version of the Solidity compiler that must be used to compile the contract code. This is useful because it ensures that the contract will be compiled using a version of the compiler that is known to be compatible with the code.

```
pragma solidity ^0.8.19;
```

Recommendation

The team is advised to lock the pragma to ensure the stability of the codebase. The locked pragma version ensures that the contract will not be deployed with an unexpected version. An unexpected version may produce vulnerabilities and undiscovered bugs. The compiler should be configured to the lowest version that provides all the required functionality for the codebase. As a result, the project will be compiled in a well-tested LTS (Long Term Support) environment.




Functions Analysis

Contract	Туре	Bases		
	Function Name	Visibility	Mutability	Modifiers
StakingContrac t	Implementation	ReentrancyG uard		
		Public	✓	-
	stakeTokens	External	✓	nonReentrant
	withdrawTokens	External	✓	nonReentrant validStakeIndex
	emergencyWithdraw	External	✓	nonReentrant validStakeIndex
	withdrawRemainingRewards	External	✓	nonReentrant onlyOwner
	proposeMultiplierUpdate	External	✓	onlyOwner
	executeMultiplierUpdate	External	✓	onlyOwner
	getContractBalance	External		-
	getTotalPlannedRewards	External		-
	getStakesLocked	External		-
	getRewardMultipliers	External		-
	getUserStakes	External		-
	calculateReward	External		validStakeIndex
	getAllowedDurations	External		-




Inheritance Graph





Flow Graph





Summary

Pocketcoin contract implements a staking mechanism. This audit investigates security issues, business logic concerns and potential improvements. The Smart Contract analysis reported no compiler error or critical issues.



Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.



The Cyberscope team

cyberscope.io