Cyberscope

A TAC Security Company

Audit Report

Zypto

February 2026

Network BASE

Address 0x0a469c7dafc2bf715c49293c6af0c8cd2b0b14e2

Audited by © cyberscope

Analysis

Critical Medium Minor / Informative Pass

Severity	Code	Description	Status
Critical	ST	Stops Transactions	Unresolved
Pass	OTUT	Transfers User's Tokens	Passed
Pass	ELFM	Exceeds Fees Limit	Passed
Critical	MT	Mints Tokens	Unresolved
Critical	BT	Burns Tokens	Unresolved
Pass	BC	Blacklists Addresses	Passed

Diagnostics

Critical Medium Minor / Informative

Severity	Code	Description	Status
Critical	BUIBS	Balance Update Initiated Before Swap	Unresolved
Minor / Informative	CCR	Contract Centralization Risk	Unresolved
Minor / Informative	MAC	Missing Access Control	Unresolved
Minor / Informative	PZAS	Possible Zero Amount Swap	Unresolved
Minor / Informative	PLPI	Potential Liquidity Provision Inadequacy	Unresolved
Minor / Informative	PTRP	Potential Transfer Revert Propagation	Unresolved
Minor / Informative	PISV	Potentially Inconsistent State Variable	Unresolved
Minor / Informative	PVC	Price Volatility Concern	Unresolved
Minor / Informative	L04	Conformance to Solidity Naming Conventions	Unresolved
Minor / Informative	L16	Validate Variable Setters	Unresolved

Table of Contents

Analysis **1**
Diagnostics **2**
Table of Contents **3**
Risk Classification **5**
Review **6**
Audit Updates 6
Source Files 6
Findings Breakdown **8**
ST - Stops Transactions 9
Description 9
Recommendation 9
MT - Mints Tokens 10
Description 10
Recommendation 10
BT - Burns Tokens 12
Description 12
Recommendation 12
BUIBS - Balance Update Initiated Before Swap 14
Description 14
Recommendation 14
CCR - Contract Centralization Risk 15
Description 15
Recommendation 16
MAC - Missing Access Control 17
Description 17
Recommendation 17
PZAS - Possible Zero Amount Swap 18
Description 18
Recommendation 19
PLPI - Potential Liquidity Provision Inadequacy 20
Description 20
Recommendation 22
PTRP - Potential Transfer Revert Propagation 23
Description 23
Recommendation 24
PISV - Potentially Inconsistent State Variable 25
Description 25
Recommendation 26
PVC - Price Volatility Concern 27

Description 27
Recommendation 28
L04 - Conformance to Solidity Naming Conventions 29
Description 29
Recommendation 30
L16 - Validate Variable Setters 31
Description 31
Recommendation 31
Functions Analysis 32
Inheritance Graph 34
Flow Graph 35
Summary 36
Disclaimer 37
About Cyberscope 38

Risk Classification

The criticality of findings in Cyberscope's smart contract audits is determined by evaluating multiple variables. The two primary variables are:

1. **Likelihood of Exploitation**: This considers how easily an attack can be executed, including the economic feasibility for an attacker.
2. **Impact of Exploitation**: This assesses the potential consequences of an attack, particularly in terms of the loss of funds or disruption to the contract's functionality.

Based on these variables, findings are categorized into the following severity levels:

1. **Critical**: Indicates a vulnerability that is both highly likely to be exploited and can result in significant fund loss or severe disruption. Immediate action is required to address these issues.
2. **Medium**: Refers to vulnerabilities that are either less likely to be exploited or would have a moderate impact if exploited. These issues should be addressed in due course to ensure overall contract security.
3. **Minor**: Involves vulnerabilities that are unlikely to be exploited and would have a minor impact. These findings should still be considered for resolution to maintain best practices in security.
4. **Informative**: Points out potential improvements or informational notes that do not pose an immediate risk. Addressing these can enhance the overall quality and robustness of the contract.

Severity	Likelihood / Impact of Exploitation
● Critical	Highly Likely / High Impact
● Medium	Less Likely / High Impact or Highly Likely/ Lower Impact
● Minor / Informative	Unlikely / Low to no Impact

Review

Contract Name	ZyptoToken
Compiler Version	v0.8.24+commit.e11b9ed9
Optimization	200 runs
Explorer	https://basescan.org/address/0x0a469c7dafc2bf715c49293c6af0c8cd2b0b14e2
Address	0x0a469c7dafc2bf715c49293c6af0c8cd2b0b14e2
Network	BASE
Symbol	ZYPTO
Decimals	18

Audit Updates

Initial Audit	20 Feb 2026 https://github.com/cyberscope-io/audits/blob/main/1-zypto/v1/audit.pdf
Corrected Phase 2	23 Feb 2026 https://github.com/cyberscope-io/audits/blob/main/1-zypto/v2/audit.pdf
Corrected Phase 3	25 Feb 2026

Source Files

Filename	SHA256

ZyptoToken.sol	08bdedfb6cb7d3bbe092c430ad792af64c06b144660645beb8d7d9cab7215984

Findings Breakdown



Critical	4
Medium	0
Minor / Informative	9

Severity	Unresolved	Acknowledged	Resolved	Other
Critical	4	0	0	0
Medium	0	0	0	0
Minor / Informative	9	0	0	0

ST - Stops Transactions

Criticality	Critical
Location	Zypto.sol#L130
Status	Unresolved

Description

The transactions are initially disabled for all users excluding the authorized addresses. The owner can enable the transactions for all users. Once the transactions are enable the owner will not be able to disable them again. Furthermore, transactions can be stoped as described by the findings `BUIBS` , `PLPI` , `PTRP` & `PZAS` .

```
Shell
function openTrade() external onlyOwner {
_isOpenForTrading = true;

}
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions. Some suggestions are:

- Introduce a multi-sign wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

MT - Mints Tokens

Criticality	Critical
Location	Zypto.sol#L118
Status	Unresolved

Description

The contract owner and the `tokenPool` address have the authority to mint tokens. Both entities can achieve that by calling the `mint` function. As a result, the contract tokens will be highly inflated. Furthermore, the owner can set `tokenPool` to an arbitrary address using the `setTokenPool` method.

```shell
function mint(address account, uint256 amount) external {
        require(msg.sender == tokenPool || msg.sender ==
owner(), "Not authorized");
        _mint(account, amount);

    }
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions.

Temporary Solutions:

These measurements do not decrease the severity of the finding

- Introduce a time-locker mechanism with a reasonable delay.

- Introduce a multi-signature wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

Permanent Solution:

- Renouncing the ownership, which will eliminate the threats but it is non-reversible.
- Setting the `tokenPool` to an immutable value once defined.

BT - Burns Tokens

Criticality	Critical
Location	Zypto.sol#L123
Status	Unresolved

Description

The contract owner and the tokenPool address have the authority to burn tokens from a specific address. Both entities can achieve that by calling the `burn` function. As a result, the targeted address will lose the corresponding tokens. Furthermore, the owner can set tokenPool to an arbitrary address using the setTokenPool method.

```shell
function burn(address account, uint256 amount) external {
        require(msg.sender == tokenPool || msg.sender ==
owner(), "Not authorized");
        _burn(account, amount);

    }
```

Recommendation

The team should carefully manage the private keys of the owner's account. We strongly recommend a powerful security mechanism that will prevent a single user from accessing the contract admin functions.

Temporary Solutions:

These measurements do not decrease the severity of the finding

- Introduce a time-locker mechanism with a reasonable delay.

- Introduce a multi-signature wallet so that many addresses will confirm the action.
- Introduce a governance model where users will vote about the actions.

Permanent Solution:

- Renouncing the ownership, which will eliminate the threats but it is non-reversible.
- Setting the tokenPool to an immutable value once defined.

BUIBS - Balance Update Initiated Before Swap

Criticality	Critical
Location	Zypto.sol#L210
Status	Unresolved

Description

The contract is designed to perform a token swap after updating the respective balances. This sequence of operations can cause inconsistencies in the balances used for operations involving the router, which may result in the swap being halted. These inconsistencies disrupt the functionality of the swap, causing transactions to fail and affecting the overall liquidity operations of the contract.

```shell
function _trade(address from, address to, uint256
value) internal {
    ...
    _update(from, address(this), totalTax);
    ...
    _update(from, to, value - totalTax);
    ...
    _swapAndLiquify(contractBalance);

}
```

Recommendation

It is recommended to ensure that the swap is triggered only before the balances are updated. This will prevent inconsistencies in the balances used during router operations, ensuring the swap executes successfully and maintaining smooth token sale functionality.

CCR - Contract Centralization Risk

Criticality	Minor / Informative
Location	Zypto.sol#L112,118,123,130,135,140,145,153,161,167,174,181
Status	Unresolved

Description

The contract's functionality and behavior are heavily dependent on external parameters or configurations. While external configuration can offer flexibility, it also poses several centralization risks that warrant attention. Centralization risks arising from the dependence on external configuration include Single Point of Control, Vulnerability to Attacks, Operational Delays, Trust Dependencies, and Decentralization Erosion.

```shell
function setTokenPool(address _tokenPool) external
onlyOwner {...}
function mint(address account, uint256 amount) external
{...}
function burn(address account, uint256 amount) external
{...}
function openTrade() external onlyOwner {...}
function setSwapAmont(uint256 swapTokensAtAmount) public
onlyOwner {...}
function setAutomatedMarketMakerPair(address pair, bool
value) external onlyOwner {...}
function setBuyFee(uint256 liquidityFee, uint256
marketingFee) public onlyOwner {...}
function setSwapAndLiquifyEnabled(bool enabled) external
onlyOwner {...}
function excludeFromFees(address account, bool excluded)
public onlyOwner {...}
function excludeMultipleAccountsFromFees(address[] calldata
accounts, bool excluded) public onlyOwner {...}
function setSellFee(uint256 liquidityFee, uint256
marketingFee) public onlyOwner {...}
```

```
function setMarketingWallet(address account) external
onlyOwner {...}
```

Recommendation

To address this finding and mitigate centralization risks, it is recommended to evaluate the feasibility of migrating critical configurations and functionality into the contract's codebase itself. This approach would reduce external dependencies and enhance the contract's self-sufficiency. It is essential to carefully weigh the trade-offs between external configuration flexibility and the risks associated with centralization.

MAC - Missing Access Control

Criticality	Minor / Informative
Location	ZyptoToken.sol#L187
Status	Unresolved

Description

The `swapAndLiquifyNow` function has no access control, allowing anyone to trigger the swap of the contract's entire accumulated fee token balance at any time. This enables third parties to trigger unauthorized swaps potentially exposing the contact to scenarios of MEV manipulation.

```shell
function swapAndLiquifyNow() public {
    uint256 contractTokenBalance =
balanceOf(address(this));
    if (contractTokenBalance > 0) {
         _swapAndLiquify(contractTokenBalance);
    }

}
```

Recommendation

The team is advised to implement proper access control ensuring only administrative authorities can execute this function.

PZAS - Possible Zero Amount Swap

Criticality	Minor / Informative
Location	ZyptoToken.sol#L235,244
Status	Unresolved

Description

The `_swapAndLiquify` function verifies that `_pendingMarketingValue` is greater than zero before executing a swap; however, it does not validate that the provided `tokenAmount` is also greater than zero. As a result, if `_swapTokensAtAmount` is set to zero and the fees are reduced to zero, the function may attempt to perform swaps with a zero token amount. Most AMM routers reject zero-amount swaps, causing the transaction to revert.

A similar issue exists during the liquidity portion of the swap. When `_pendingMarketingValue` exceeds `tokenAmount`, the function swaps the entire contract balance for marketing purposes. This may leave the contract with a zero token balance, after which the liquidity logic can attempt additional swaps using a zero amount, leading again to a revert.

Finally, if the contract balance is empty and `_pendingMarketingValue == 0`, the function proceeds to calculate and swap half of the contract's balance for liquidity. Since the balance is zero, the contract attempts to execute a zero-value swap, which will revert for the same reasons described above.

```shell
function _swapAndLiquify(uint256 tokenAmount) private
lockTheSwap {
    if (_pendingMarketingValue > 0) {
        uint256 mAmt = _pendingMarketingValue >
tokenAmount ? tokenAmount : _pendingMarketingValue;
        _swapTokensForETH(mAmt, _marketingWallet);
        _pendingMarketingValue -= mAmt;
        tokenAmount = balanceOf(address(this));
    }

    uint256 half = tokenAmount / 2;
    uint256 otherHalf = tokenAmount - half;
    uint256 initialETH = address(this).balance;

    _swapTokensForETH(half, address(this));

    uint256 newETH = address(this).balance - initialETH;
    if (newETH > 0 && otherHalf > 0) {
        _uniswapV2Router.addLiquidityETH{value: newETH}(
            address(this), otherHalf, 0, 0, owner(),
block.timestamp
        );
    }
    emit SwapAndLiquify(half, newETH);

}
```

Recommendation

The team should add explicit validation checks to ensure that swaps are only executed when the token amounts involved are greater than zero. Before calling any swap or liquidity logic, the contract should verify that `tokenAmount`, the marketing swap amount, and any liquidity split amounts are non-zero.

PLPI - Potential Liquidity Provision Inadequacy

Criticality	Minor / Informative
Location	Zypto.sol#L232,255
Status	Unresolved

Description

The contract operates under the assumption that liquidity is consistently provided to the pair between the contract's token and the native currency. However, there is a possibility that liquidity is provided to a different pair. This inadequacy in liquidity provision in the main pair could expose the contract to risks. Specifically, during eligible transactions, where the contract attempts to swap tokens with the main pair, a failure may occur if liquidity has been added to a pair other than the primary one. Consequently, transactions triggering the swap functionality will result in a revert.

Furthermore, the owner has the ability to designate arbitrary addresses as Automated Market Maker pairs. Transfers involving any address flagged as an AMM pair are treated as buy/sell operations and may trigger the internal swap-and-liquify logic. Since these addresses may not be legitimate DEX pairs, triggering a swap during buys from a non-legitimate DEX pair to the actual pair can cause the router interaction to fail and revert.

Shell

```
function _swapTokensForETH(uint256 tokenAmount, address to)
private {
        address[] memory path = new address[](2);
        path[0] = address(this);
        path[1] = _WETH;

_uniswapV2Router.swapExactTokensForETHSupportingFeeOnTransf
erTokens(
            tokenAmount, 0, path, to, block.timestamp
        );
}

function _swapAndLiquify(uint256 tokenAmount) private
lockTheSwap {
    if (_pendingMarketingValue > 0) {
        uint256 mAmt = _pendingMarketingValue > tokenAmount
? tokenAmount : _pendingMarketingValue;
        _swapTokensForETH(mAmt, _marketingWallet);
        _pendingMarketingValue -= mAmt;
        tokenAmount = balanceOf(address(this));
     }

    uint256 half = tokenAmount / 2;
    uint256 otherHalf = tokenAmount - half;
    uint256 initialETH = address(this).balance;

    _swapTokensForETH(half, address(this));

    uint256 newETH = address(this).balance - initialETH;
    if (newETH > 0 && otherHalf > 0) {
        _uniswapV2Router.addLiquidityETH{value: newETH}(
            address(this), otherHalf, 0, 0, owner(),
block.timestamp
        );
     }
     emit SwapAndLiquify(half, newETH);

}
```

Recommendation

The team is advised to implement a runtime mechanism to check if the pair has adequate liquidity provisions. This feature allows the contract to omit token swaps if the pair does not have adequate liquidity provisions, significantly minimizing the risk of potential failures.

Furthermore, the team could ensure the contract has the capability to switch its active pair in case liquidity is added to another pair.

Additionally, the contract could be designed to tolerate potential reverts from the swap functionality, especially when it is a part of the main transfer flow. This can be achieved by executing the contract's token swaps in a non-reversible manner, thereby ensuring a more resilient and predictable operation.

PTRP - Potential Transfer Revert Propagation

Criticality	Minor / Informative
Location	Zypto.sol#L174,259
Status	Unresolved

Description

The contract sends funds to a `marketingWallet` as part of the transfer flow. This address can either be a wallet address or a contract. If the address belongs to a contract then it may revert from incoming payment. As a result, the error will propagate to the token's contract and revert the transfer.

```
Shell
_uniswapV2Router.swapExactTokensForETHSupportingFeeOnTransferTokens(
            tokenAmount, 0, path, to, block.timestamp
        );
```

```
Shell
function setMarketingWallet(address account) public onlyOwner {
        require(_marketingWallet != account, "Already set");
        _marketingWallet = payable(account);
        _isExcludedFromFees[account] = true;
```

```
        emit SetMarketingWallet(account);
    }
```

Recommendation

The contract should tolerate the potential revert from the underlying contracts when the interaction is part of the main transfer flow. This could be achieved by not allowing set contract addresses or by sending the funds in a non-revertable way, including try-catch schemes.

PISV - Potentially Inconsistent State Variable

Criticality	Minor / Informative
Location	Zypto.sol#L266
Status	Unresolved

Description

The contract provides a `rescueERC20` function that allows the owner to withdraw the entire balance of any ERC20 token held by the contract. However, if the rescued token is the contract's own token (address(this)), the `_pendingMarketingValue` state variable is never reset to zero. This creates an accounting inconsistency where the variable continues to track a marketing allocation that no longer exists in the contract's balance.

When fees subsequently accumulate and `_swapAndLiquify` is triggered, the stale `_pendingMarketingValue` will cause a disproportionate amount of tokens to be allocated toward the marketing swap, effectively shortchanging the liquidity provision.

```shell
function rescueERC20(IERC20 _token) external
onlyOwner {
    uint256 balance =
_token.balanceOf(address(this));
    _token.safeTransfer(msg.sender, balance);
    emit EmergencyRescueERC20(address(_token),
balance);

}
```

Recommendation

The contract should reset `_pendingMarketingValue` to zero when the rescued token is the contract's own token. Alternatively, the contract could restrict rescueERC20 from withdrawing its own token entirely, limiting the function to recovering only third-party tokens accidentally sent to the contract.

PVC - Price Volatility Concern

Criticality	Minor / Informative
Location	ZyptoToken.sol#L135
Status	Unresolved

Description

The contract accumulates tokens from the taxes to swap them for ETH. The variable `_swapTokensAtAmount` sets a threshold where the contract will trigger the swap functionality. If the variable is set to a big number, then the contract will swap a huge amount of tokens for ETH.

It is important to note that the price of the token representing it, can be highly volatile. This means that the value of a price volatility swap involving Ether could fluctuate significantly at the triggered point, potentially leading to significant price volatility for the parties involved.

```shell
function setSwapAmont(uint256 swapTokensAtAmount)
public onlyOwner {
        _swapTokensAtAmount = swapTokensAtAmount;
        emit
SetSwapTokensAtAmount(swapTokensAtAmount);

    }
```

Recommendation

The contract could ensure that it will not sell more than a reasonable amount of tokens in a single transaction. A suggested implementation could check that the maximum amount should be less than a fixed percentage of the exchange reserves. Hence, the contract will guarantee that it cannot accumulate a huge amount of tokens in order to sell them.

L04 - Conformance to Solidity Naming Conventions

Criticality	Minor / Informative
Location	ZyptoToken.sol#L40,41,42,46,47,48,49,50,51,52,53,57,59,60,62,63
Status	Unresolved

Description

The Solidity style guide is a set of guidelines for writing clean and consistent Solidity code. Adhering to a style guide can help improve the readability and maintainability of the Solidity code, making it easier for others to understand and work with.

The followings are a few key points from the Solidity style guide:

1. Use camelCase for function and variable names, with the first letter in lowercase (e.g., myVariable, updateCounter).
2. Use PascalCase for contract, struct, and enum names, with the first letter in uppercase (e.g., MyContract, UserStruct, ErrorEnum).
3. Use uppercase for constant variables and enums (e.g., MAX_VALUE, ERROR_CODE).
4. Use indentation to improve readability and structure.
5. Use spaces between operators and after commas.
6. Use comments to explain the purpose and behavior of the code.
7. Keep lines short (around 120 characters) to improve readability.

```shell
IUniswapV2Router02 public immutable
_uniswapV2Router;
address public immutable _WETH;
address public immutable _uniswapV2Pair;
uint256 public _buyFeeLiquidity;
uint256 public _buyFeeMarketing;
uint256 public _buyFeeTotal;
uint256 public _sellFeeLiquidity;
uint256 public _sellFeeMarketing;
uint256 public _sellFeeTotal;
uint256 public _pendingMarketingValue;
address payable public _marketingWallet;
bool public _isOpenForTrading = false;
bool public _swapAndLiquifyEnabled = true;
uint256 public _swapTokensAtAmount = 100_000 *
1e18;
mapping(address => bool) public
_isExcludedFromFees;

mapping(address => bool) public

_isAutomatedMarketMakerPair;
```

Recommendation

By following the Solidity naming convention guidelines, the codebase increased the readability, maintainability, and makes it easier to work with.

Find more information on the Solidity documentation https://docs.soliditylang.org/en/stable/style-guide.html#naming-conventions.

L16 - Validate Variable Setters

Criticality	Minor / Informative
Location	ZyptoToken.sol#L113, 176
Status	Unresolved

Description

The contract performs operations on variables that have been configured on user-supplied input. These variables are missing of proper check for the case where a value is zero. This can lead to problems when the contract is executed, as certain actions may not be properly handled when the value is zero.

```shell
tokenPool = _tokenPool
_marketingWallet = payable(account)
```

Recommendation

By adding the proper check, the contract will not allow the variables to be configured with zero value. This will ensure that the contract can handle all possible input values and avoid unexpected behavior or errors. Hence, it can help to prevent the contract from being exploited or operating unexpectedly.

Functions Analysis

Contract	Type	Bases		
	Function Name	**Visibility**	**Mutability**	**Modifiers**
ZyptoToken	Implementation	ERC20, Ownable		
		Public	✓	ERC20 Ownable
		External	Payable	-
	setTokenPool	External	✓	onlyOwner
	mint	External	✓	-
	burn	External	✓	-
	openTrade	External	✓	onlyOwner
	setSwapAmont	Public	✓	onlyOwner
	setSwapAndLiquifyEnabled	Public	✓	onlyOwner
	setBuyFee	Public	✓	onlyOwner
	setSellFee	Public	✓	onlyOwner
	excludeFromFees	Public	✓	onlyOwner
	excludeMultipleAccountsFromFees	Public	✓	onlyOwner
	setMarketingWallet	Public	✓	onlyOwner
	setAutomatedMarketMakerPair	Public	✓	onlyOwner
	swapAndLiquifyNow	Public	✓	-
	_update	Internal	✓	
	_trade	Internal	✓	
	_swapAndLiquify	Private	✓	lockTheSwap

	_swapTokensForETH	Private	✓	
	rescueERC20	External	✓	onlyOwner
	rescueETH	External	✓	onlyOwner

Inheritance Graph



Flow Graph


Legend
Internal Call
External Call
Custom Error Call
Defined Contract
Undefined Contract
Context
_msgSender
_msgData
_contextSuffixLength
IERC165 (iface)
supportsInterface
IERC20Metadata (iface)
name
symbol
decimals
Ownable
onlyOwner
_checkOwner
Ownable.OwnableUnauthorizedAccount
<Constructor>
Ownable.OwnableInvalidOwner
_msgSender
transferOwnership
address
owner
renounceOwnership
_transferOwnership
IUniswapV2Router02 (iface)
swapExactTokensForETHSupportingFeeOnTransferTokens
WETH
addLiquidityETH
factory
ZyptoToken
lockTheSwap
<Receive Ether>
setTokenPool
openTrade
setSwapAmont
setSwapAndLiquifyEnabled
excludeFromFees
excludeMultipleAccountsFromFees
setAutomatedMarketMakerPair
swapAndLiquifyNow
trade
swapAndLiquify
update
swapTokensForETH
<Constructor>
mint
burn
balanceOf
setMarketingWallet
rescueETH
rescueERC20
transferOwnership
type
_approve
setSellFee
setBuyFee
_mint
_burn
owner
payable
address
IERC20 (iface)
balanceOf
safeTransfer
allowance
totalSupply
transfer
approve
transferFrom
abi
encodeCall
SafeERC20 (lib)
safeDecreaseAllowance
SafeERC20.SafeERC20FailedDecreaseAllowance
trySafeTransferFrom
trySafeTransfer
callOptionalReturnBool
safeIncreaseAllowance
forceApprove
safeTransfer
callOptionalReturn
address
safeTransferFrom
transferAndCallRelaxed
transferFromAndCallRelaxed
approveAndCallRelaxed
SafeERC20.SafeERC20FailedOperation
IUniswapV2Factory (iface)
createPair
IERC1363 (iface)
transferAndCall
transferFromAndCall
approveAndCall
ERC20
<Constructor>
name
symbol
decimals
totalSupply
approve
transferFrom
transfer
_msgSender
_spendAllowance
transfer
_mint
_burn
approve
ERC20.ERC20InvalidSpender
ERC20.ERC20InvalidApprover
ERC20.ERC20InsufficientAllowance
type
ERC20.ERC20InvalidReceiver
address
ERC20.ERC20InvalidSender
_update
ERC20.ERC20InsufficientBalance

Summary

Zypto contract implements a token mechanism. This audit investigates security issues, business logic concerns and potential improvements. There are some functions that can be abused by the owner like stop transactions, mint tokens and burn tokens from any address. If the contract owner abuses the mint functionality, then the contract will be highly inflated. If the contract owner abuses the burn functionality, then the users could lose their tokens. A multi-wallet signing pattern will provide security against potential hacks. Temporarily locking the contract or renouncing ownership will eliminate all the contract threats. There is also a limit of max 4% fees.

Disclaimer

The information provided in this report does not constitute investment, financial or trading advice and you should not treat any of the document's content as such. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes nor may copies be delivered to any other person other than the Company without Cyberscope's prior written consent. This report is not nor should be considered an "endorsement" or "disapproval" of any particular project or team. This report is not nor should be regarded as an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Cyberscope to perform a security assessment. This document does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors' business, business model or legal compliance. This report should not be used in any way to make decisions around investment or involvement with any particular project. This report represents an extensive assessment process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk Cyberscope's position is that each company and individual are responsible for their own due diligence and continuous security Cyberscope's goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies and in no way claims any guarantee of security or functionality of the technology we agree to analyze. The assessment services provided by Cyberscope are subject to dependencies and are under continuing development. You agree that your access and/or use including but not limited to any services reports and materials will be at your sole risk on an as-is where-is and as-available basis Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives false negatives and other unpredictable results. The services may access and depend upon multiple layers of third parties.

About Cyberscope

Cyberscope is a TAC blockchain cybersecurity company that was founded with the vision to make web3.0 a safer place for investors and developers. Since its launch, it has worked with thousands of projects and is estimated to have secured tens of millions of investors' funds.

Cyberscope is one of the leading smart contract audit firms in the crypto space and has built a high-profile network of clients and partners.

A **TAC Security** Company

The Cyberscope team

cyberscope.io