

Strategic Analysis of Cloud Security Incidents and Systemic Supply Chain Vulnerabilities (June 22 – July 3, 2026)

The cybersecurity landscape between late May and early July 2026 experienced an escalation of campaigns targeting perimeter defense systems, cloud-hosted repositories, and trusted business integrations¹. This strategic threat intelligence report provides an in-depth analysis of six material cloud and supply chain incidents reported during this timeframe². The analysis dissects these events using the core intelligence parameters of threat actor identity, operational and data impact, temporal boundaries, target architecture, underlying technical vulnerabilities, and broader tactical motivations². Special emphasis is dedicated to a series of high-severity vulnerabilities identified within IBM WebSphere and WebSphere Liberty application servers, demonstrating the exploitation vectors that threaten complex multi-tenant cloud ecosystems⁹.

Comparative Assessment of Key Cybersecurity Incidents

To establish a consolidated analytical foundation, the matrix below outlines the critical dimensions of each reported incident during the June 22 – July 3, 2026 monitoring window.

Target Entity	Primary Actor (Who)	Operational & Data Impact (What)	Event Timeline (When)	Affected Environment (Where)	Strategic Threat Driver (Why)	Technical Vulnerability Profile
Department of Homeland Security (DHS)	Unattributed threat actor ⁴	Unauthorized access to the unclassified Homeland Security Information Network	Intrusion: Late May – early June 2026; Confirmed: July 3, 2026 ⁴	Unclassified legacy SharePoint and collaboration servers ⁴	Espionage, intelligence harvesting, and event security compromise ⁸	Deserialization of untrusted data leading to remote code execution (RCE) ¹⁴

		(HSIN) ⁴				
Fortinet Integrations	Russian-speaking initial access brokers linked to Lynx and INC Ransomware ¹⁵	Automated sniffing, harvesting, and offline decryption of administrator credentials ⁷	Active since at least Feb 2026; validated mid-June 2026; updated to July 2, 2026 ¹⁶	Publicly exposed Management and SSL VPN ports (443, 4443, 8443, 10443) on FortiGate firewalls ⁷	Access broker monetization and execution of downstream ransomware operations ⁷	Legacy SHA-256 hashing weaknesses, configuration backup file access, and default configurations ¹⁷
AdaptHealth Corp.	Unnamed extortion group ²	Unauthorized exfiltration of cloud application datasets, patient records, and billing credentials ²	Session Compromise: Pre-June 15, 2026; Materiality Declared: June 27, 2026; Disclosed: July 2, 2026 ²	Cloud business applications and external Electronic Health Record (EHR) portals ²	Financial extortion and targeting of Protected Health Information (PHI) ²	Session hijacking and credential theft via targeted social engineering ²
Navient Corp.	Unspecified ransomware syndicate ⁶	Third-party exfiltration of sensitive student loan borrower PII and Social Security	Awareness: June 8, 2026; Materiality Declared: June 29, 2026; Disclosed: July 2, 2026 ⁶	Information systems environment of an external partner law firm ⁶	Extortion of professional service provider to leverage downstream corporate	Supply chain network compromise and lack of isolated data retention controls ⁶

		Numbers (SSNs) ⁶			datasets ⁶	
Database World ROC	Threat actor "Database World ROC" ¹⁶	Multiple large-scale breaches and indexation of cloud-hosted datasets ¹⁶	Discovered and indexed: July 1 – 3, 2026 ¹⁶	Cloud-hosted databases and public archives (LinkedIn, regional datasets from Bolivia and New Zealand) ¹⁶	Data brokering, credentials trading, and identity harvesting on the dark web ⁷	Weak access controls and exposed cloud-storage bucket configurations ⁷
Singapore Land Authority (SLA)	Unattributed / Unauthorized Actor ³	Exposure of un-anonymized real property database, exposing NRIC records and addresses of 70,000 citizens ³	Discovery & Revocation: Prior to July 3, 2026; Public Disclosure: July 3, 2026 ³	IBM-managed cloud development, systems integration, and testing environment ³	Harvesting of government-indexed personal identifiers for downstream targeting ³	Failure in data sanitization/anonymization and insecure staging access controls ³

Detailed Chronological and Technical Incident Analyses

Department of Homeland Security: HSIN SharePoint Compromise

The Homeland Security Information Network (HSIN) serves as the primary unclassified portal for real-time collaboration, threat sharing, and incident management among international, federal, state, local, tribal, and private-sector emergency partners⁴.

The intrusion is estimated to have occurred between late May and early June 2026, remaining undetected for several weeks⁴. DHS isolated the affected unclassified legacy systems and initiated a comprehensive forensic probe, alongside a damage assessment conducted by the Office of Intelligence and Analysis⁴. The platform is actively used to coordinate security preparations for upcoming high-profile national and international events, such as the 2026 FIFA World Cup and America250⁸. Although DHS confirmed that classified networks remained completely unaffected, the exposure of event safety plans, alert lists, and tactical operational methodologies presents a significant risk to physical and national security infrastructure⁸. The compromise was executed via a remote code execution (RCE) vulnerability in Microsoft SharePoint Server, tracked as **CVE-2026-45659**¹⁴. The vulnerability involves a deserialization of untrusted data weakness (CWE-502)¹⁴. The technical mechanism allows a remote attacker to submit a malformed, serialized object to the SharePoint application server¹⁴. Because the system processes these objects without adequate integrity verification, the deserialization routine executes the payload, granting the attacker arbitrary code execution privileges¹⁴.

Attacker Payload → Unvalidated Object Stream → SharePoint Deserializer (CWE-

This vulnerability is highly exploitable due to its low attack complexity (**AC:L**), low privilege requirements (**PR:L**)—requiring only basic Site Member permissions—and lack of required user interaction¹⁴. This zero-day was added to CISA's Known Exploited Vulnerabilities (KEV) catalog on the same day the breach was publicly confirmed, under a strict remediation directive for government systems⁴.

Fortinet FortiGate VPN/Firewall: The "FortiBleed" Campaign

In mid-June 2026, security researchers discovered an active threat infrastructure hosting verified administrator credentials for tens of thousands of Fortinet devices¹.

The campaign, active since at least February 2026, has compromised approximately 74,000 to 86,644 Fortinet FortiGate firewalls and Secure Sockets Layer Virtual Private Network (SSL VPN) gateways globally, representing nearly half of all publicly exposed Fortinet appliances¹. CISA and the UK National Cyber Security Centre (NCSC) issued urgent warnings on June 18, 2026, prompting defensive reviews and credential rotation¹. The infrastructure is operated by Russian-speaking threat groups acting as initial access brokers (IABs)⁷. These brokers construct structured, geographically segmented databases of validated perimeter access points, selling them to ransomware-as-a-service (RaaS) operations like Lynx and INC Ransomware⁷. The FortiBleed campaign utilizes an automated, multi-stage workflow that exploits weak administrator credential configurations, previous vulnerabilities, and legacy cryptographic hashing algorithms⁵.

- **Default Configuration Exploitation:** Roughly 63% of the exposed credentials belonged to generic, built-in, or default administrative accounts (e.g., admin, adminin, fgtsecure) that

organizations failed to rename, disable, or protect with multi-factor authentication (MFA)¹⁷.

- **Legacy Cryptographic Hashing:** FortiGate appliances historically stored administrator password hashes within their configuration backup files¹⁷. Older versions of FortiOS utilized standard salted SHA-256 hashing⁷. This hashing method is highly susceptible to high-speed offline cracking when run through modern GPU clusters¹⁷.
- **Migration Loophole & Hidden Fields:** While Fortinet introduced more secure PBKDF2-based hashing in late 2025 (affecting FortiOS 7.2.11, 7.4.8, and 7.6.1), the cryptographic migration is only applied to an account once an administrator logs in *after* the firmware upgrade¹⁷. Inactive or legacy accounts remained stored in the weaker SHA-256 format¹⁷. Furthermore, a backward-compatibility field named old-password preserved older SHA-256 hashes within configuration files¹⁷. Consequently, an attacker who obtained a configuration backup file from a device could still extract and crack legacy SHA-256 hashes offline, even on fully upgraded appliances¹⁷.
- **Adjacent Zero-Day Vector:** The campaign was also linked to **CVE-2026-24858**, a critical FortiCloud Single Sign-On (SSO) SAML authentication bypass vulnerability (CVSS score 9.8)¹⁶. This flaw allowed external, valid SAML assertions to authenticate unauthorized operators as local administrators, bypassing security boundaries¹⁶.

AdaptHealth Corporation: Social Engineering and Session Hijacking

AdaptHealth Corporation disclosed a material security incident on July 2, 2026, following a SEC Form 8-K filing².

On June 15, 2026, an extortion actor contacted AdaptHealth, claiming to have exfiltrated internal data². Following a forensic assessment by external security teams, the company determined the event to be material on June 27, 2026, due to the volume of sensitive data exposed². While patient care and physical medical services remained uninterrupted, the attacker exfiltrated a plain-text password file dedicated to insurance billing systems and accessed cloud-based patient directories². The compromise exposed Personally Identifiable Information (PII) and Protected Health Information (PHI), though it excluded Social Security numbers and payment card records².

The incident was executed via a targeted social engineering campaign against a third-party contractor². The attacker bypassed active multi-factor authentication (MFA) controls by hijacking an active, authenticated user session². By stealing valid session tokens directly from the contractor's endpoint, the attacker presented a pre-authenticated session to AdaptHealth's SaaS business applications and external Electronic Health Record (EHR) portals². This session hijacking allowed the threat actor to pivot throughout the cloud tenant under the guise of a trusted user, bypassing standard perimeter and MFA challenges².

Navient Corporation: Supply Chain Ransomware Exposure

Navient Corporation disclosed a material third-party cybersecurity incident on July 2, 2026, through an SEC Form 8-K filing⁶.

Navient became aware of the incident on June 8, 2026, after receiving notifications from a

third-party partner law firm that provides legal and administrative services to the corporation⁶. On June 29, 2026, Navient deemed the supply chain breach material because of the volume of compromised Social Security Numbers and financial borrower profiles⁶. Although Navient's internal IT systems and operations remained unaffected, the exfiltrated borrower data included names, dates of birth, mailing addresses, and Social Security numbers⁶.

The incident did not involve a direct vulnerability in Navient's perimeter or cloud systems⁶. Instead, it highlights a supply chain vulnerability, wherein a business partner retained sensitive personal data on its own infrastructure⁶. The external law firm suffered a devastating ransomware attack⁶. Attackers exploited unspecified vulnerabilities within the law firm's hosting environment to execute code, encrypt local databases, and exfiltrate Navient customer profiles⁶. This incident demonstrates the risk of data replication, where secure enterprise networks remain vulnerable to exploitation via downstream vendors that process, transmit, or store sensitive corporate assets without equivalent endpoint or cloud security controls⁶.

Database World ROC (via Breach House Listings)

Between July 1 and July 3, 2026, threat intelligence feeds monitored multiple large-scale data breach listings published under the moniker "Database World ROC"¹⁶.

The campaign involves the public indexation of multiple cloud-hosted datasets¹⁶. The exposed data includes LinkedIn archives, regional directories from Bolivia and New Zealand, and various corporate databases¹⁶. The threat actor utilized Breach House, an open-source OSINT crawler and repository tracking backend, to catalog these leaks¹⁶. The platform provides automated tools to scrape, structure, and categorize ransomware leaks, database exposures, and stealer logs²³. This allows initial access brokers to compile bulk credential dumps and sell targeted corporate profiles on underground marketplaces⁷.

The primary vulnerability vector stems from misconfigured cloud access control lists (ACLs) and exposed cloud storage buckets⁷. Threat actors rely on automated scanning tools to discover exposed S3, Azure Blob, and Elasticsearch endpoints⁷. By failing to enforce strict IAM access policies, default password restrictions, and IP-whitelisting on development and archival cloud instances, organizations allow unauthorized actors to download large datasets with minimal effort⁷.

Singapore Land Authority: Test Environment Exploitation (IBM Cloud)

On July 3, 2026, the Singapore Land Authority (SLA) disclosed a material data breach involving its technology vendor, IBM, which managed the web-based Singapore Titles Automated Registration System (STARS) and the eLodgment System (ELS)³.

The incident involved unauthorized access to an IBM-managed cloud-hosted development and systems-integration testing (SIT) environment³. SLA was notified of the exposure by IBM, prompting immediate access revocation³. The compromise affected a historical testing dataset created in 1998 and updated periodically³. Although the dataset was designated to contain only mock and anonymized records, investigations revealed it contained real personal identifiers—specifically names, NRIC numbers, and historical property addresses—of

approximately 70,000 citizens³.

The incident resulted from a critical breakdown in both cloud tenant segregation and data sanitization policies³.

- **Data Governance and Sanitization Deficit:** A testing dataset originally generated in 1998 and updated periodically over the years was maintained in an IBM-managed cloud-hosted development and systems-integration testing (SIT) environment³. This database was designated for mock tests and was supposed to contain only anonymized structures³. However, real-world data—specifically names, National Registration Identity Card (NRIC) numbers, and historical property addresses of approximately 70,000 individuals—had been copied into the staging DB without undergoing an obfuscation or tokenization process³.
- **IBM Cloud Testing Environment Misconfiguration:** Unauthorized actors discovered an open path into the IBM-managed SIT cloud environment³. Staging and development environments are frequently targeted by threat actors because they often lack the defense-in-depth controls of live production environments, such as continuous log auditing, IP address constraints, and hardened identity boundaries²⁵.

Technical Deep-Dive: IBM WebSphere & Liberty Vulnerability Vectors

The compromise of the IBM-managed SIT environment highlights a broader array of vulnerabilities disclosed across the IBM WebSphere and WebSphere Liberty application server portfolios during the late June to early July 2026 cycle⁹. These flaws represent prime entry vectors for threat actors seeking to target enterprise cloud environments⁹.

CVE-2026-9006: Server-Side Request Forgery via Ajax Proxy

Traditional IBM WebSphere Application Server versions 8.5 and 9.0 are vulnerable to a high-severity Server-Side Request Forgery (SSRF) vulnerability when the administrative or application-level Ajax Proxy component is configured⁹.

Architecture and Attack Path

The WebSphere Ajax Proxy is designed as a server-side forwarding mechanism that allows web-browser clients to bypass browser-enforced Same-Origin Policies by proxying request traffic directly through the application server⁹. The underlying software vulnerability (CWE-918) arises because the proxy fails to validate or restrict destination URLs submitted within user requests⁹.

An unauthenticated attacker can craft an HTTP request containing a target URL query parameter pointing directly to an internal system⁹. Because the WebSphere host sits inside the enterprise cloud network perimeter, it resolves the parameter and issues a request to the restricted resource using its own secure network identity⁹.

Attacker HTTP Request → WebSphere Ajax Proxy Component → Unvalidated Outbound Request

Attackers exploit this behavior to target internal cloud infrastructure endpoints⁹:

```
HTTP
GET /AjaxProxyPath?url=http://169.254.169.254/latest/meta-data/iam/security-credentials/
HTTP/1.1
Host: [REDACTED]
User-Agent: [REDACTED]
```

When WebSphere executes this request, the hosting cloud instance returns its IAM temporary security tokens directly to the attacker, resulting in a complete bypass of the cloud network boundary⁹.

CVE-2026-11546 and CVE-2026-11714: WebSphere Liberty Server-Side Request Forgery

WebSphere Liberty, a lightweight profile of WebSphere widely deployed in cloud-native microservices, containerized environments, and Kubernetes orchestration systems, is impacted by two distinct Server-Side Request Forgery vulnerabilities¹¹.

CVE-2026-11546

This flaw targets WebSphere Liberty versions 17.0.0.3 through 26.0.0.7 when the administrative dashboard management feature (adminCenter-1.0) is enabled¹¹. An attacker with low-level authenticated access within the admin framework can leverage administrative routing functionalities to execute SSRF commands, querying internal endpoints or scanning ports across private subnets¹¹.

CVE-2026-11714

This is a high-severity vulnerability (CVSS score 8.5) affecting WebSphere Liberty versions 17.0.0.3 through 26.0.0.7 when the API auto-discovery service (apiDiscovery-1.0) is enabled³¹. This API discovery feature aggregates OpenAPI definition files across microservices³¹. Due to insecure authorization and input parsing, an authenticated attacker with low-level privileges can force the API discovery daemon to issue automated requests to backend database adapters, REST controllers, or internal web services³¹. This allows attackers to bypass front-end security filters and map out the entire microservice ecosystem³¹.

CVE-2026-8633: Web Server Plug-ins Remote Code Execution

A critical remote code execution flaw affects the IBM Web Server Plug-ins component configured on front-end web proxies (such as IBM HTTP Server or Apache) that interface with backend WebSphere and WebSphere Liberty Application Servers¹⁰.

Architecture and Attack Path

The Web Server Plug-in acts as an intelligent connector, routing incoming HTTP traffic to backend JVM instances based on context paths defined within configuration maps (e.g., plugin-cfg.xml)¹⁰.

The vulnerability (CWE-94) resides in the parsing engine of the plug-in¹⁰. An unauthenticated network attacker can craft a malformed HTTP request with overly long headers, nested parameter configurations, or unexpected content boundaries¹⁰. The plug-in fails to sanitize this input during context verification¹⁰. As a result, the malformed string is written directly into memory segments, causing a buffer overflow or parameter injection that is interpreted as executable code¹⁰.

Because the web server process typically executes under administrative or highly privileged service profiles, the attacker achieves immediate command execution on the host OS¹⁰. This can be used to drop web shells, deploy system monitoring tools, and establish a persistent foothold within the web tier¹⁰.

Second- and Third-Order Cyber Threat Intelligence Analysis

Analyzing these incidents collectively reveals a series of systemic shifts in the current threat landscape, illustrating how modern adversaries bypass security boundaries by exploiting secondary vulnerabilities and trusted connections⁷.

The Illusion of "Mock" Data and Staging Exposures

The compromise of the SLA database hosted by IBM demonstrates the high risk of using realistic data in non-production environments³. Organizations often run tests using staging environments that replicate production architectures, but they frequently fail to enforce production-grade access controls or complete data sanitization²⁵.

When sensitive databases are copied without undergo masking or anonymization, staging environments become a preferred target for attackers³. They offer the same valuable datasets but are much easier to breach because they often lack active monitoring, log analysis, and strict network segmentation²⁵.

The Shift in the Front of the Cyber Kill-Chain

The modern cyber kill-chain has shifted focus³⁵. Rather than relying on custom zero-day exploits to breach perimeters, threat actors are increasingly using automated systems to target the identity layer and exploit common configuration mistakes⁷.

The "FortiBleed" campaign is a prime example of this strategy: attackers used automated

scanning tools to harvest valid VPN and administrative credentials, allowing them to log in to target networks as legitimate administrators⁷. This approach minimizes the attacker's technical footprint and allows them to bypass traditional network defenses, such as Intrusion Detection Systems (IDS) and Web Application Firewalls (WAF)⁵.

Supply Chain Aggregation and Identity Abuse

Threat actors are systematically targeting service providers—such as IT contractors, hosting providers, and law firms—to gain access to their downstream corporate clients².

The incidents at AdaptHealth and Navient highlight the risks of these supply chain connections². When an attacker hijacks a third-party contractor's session (as with AdaptHealth) or compromises a partner law firm's systems (as with Navient), they exploit the inherent trust between these organizations².

This trend is driven by the growing use of automated, AI-assisted tools that scan and map these interconnected systems²⁴. These tools make it easier for attackers to identify and exploit security gaps across supply chain networks²⁴.

Tactical Defensive Recommendations

To defend against these emerging threat methodologies, enterprise cloud and infrastructure engineering teams must adopt proactive, zero-trust security strategies¹².

Implementing Phishing-Resistant Multi-Factor Authentication

Traditional SMS and push-notification based MFA are highly vulnerable to social engineering, session hijacking, and session token theft². Organizations must mandate phishing-resistant FIDO2/WebAuthn hardware tokens for all employees, especially external contractors and third-party partners¹.

Restricting Management Plane Exposure

Critical infrastructure management portals, including FortiGate firewalls, administrative consoles, and IBM WebSphere portals, must never be exposed directly to the public internet¹. Access should be restricted to isolated administrative subnets and protected by zero-trust network access (ZTNA) gateways¹.

Hardening Password Storage and Active Hashing Upgrades

Relying purely on standard salted SHA-256 for credential storage is no longer secure against offline GPU cracking¹⁷. Organizations must enforce computationally hard hashing functions, such as Argon2id or PBKDF2 with high iteration counts, and actively force password rotations after firmware upgrades to ensure credentials are migrated to the new standards¹.

Mandating Rigorous Data Masking and Staging Isolation

Production databases must never be copied directly into testing or staging environments³. Staging data must be generated using synthetic data engines, or completely masked using static data masking (SDM) tools before being loaded into testing systems³.

Testing environments must also be treated with the same security controls as production networks, including centralized logging and network segmentation²⁵.

Mitigating WebSphere and Liberty SSRF Risks

For environments deploying IBM WebSphere or WebSphere Liberty, security teams must immediately apply the latest vendor patches to address CVE-2026-9006, CVE-2026-11546, and CVE-2026-11714⁹. If patches cannot be applied immediately, organizations should disable the Ajax Proxy and administrative features (such as adminCenter-1.0 and apiDiscovery-1.0)⁹. Additionally, egress filtering should be implemented to prevent application servers from communicating with cloud metadata endpoints (e.g., 169.254.169.254) and internal RFC 1918 subnets⁹. Ensure that Web Application Firewalls (WAFs) are updated to detect and block malicious request parameters⁹.

Referências citadas

1. CISA Urges Hardening Fortinet Devices After Reports of Credential Exposure, <https://www.cisa.gov/news-events/alerts/2026/06/18/cisa-urges-hardening-fortinet-devices-after-reports-credential-exposure>
2. Patient data exposed in AdaptHealth (AHCO) material cybersecurity incident - Stock Titan, <https://www.stocktitan.net/sec-filings/AHCO/8-k-adapt-health-corp-reports-material-event-80512081bbc7.html>
3. Personal info of 70000 people compromised in data breach involving SLA's vendor IBM, <https://www.straitstimes.com/singapore/data-of-70000-people-compromised-after-cybersecurity-incident-involving-sla-vendor-and-its-cloud>
4. DHS confirms hackers breached HSIN info-sharing platform, <https://www.bleepingcomputer.com/news/security/dhs-confirms-hackers-breached-hsin-info-sharing-platform/>
5. FortiBleed Credential Exposure and VPN Bruteforce Campaign - Sophos, <https://www.sophos.com/en-us/security-advisories/fortinet-fortibleed-credential-exposure-and-sophos-vpn-bruteforcing-campaign>
6. Third-party cyber incident exposes Navient (JSM) borrower data via law firm - Stock Titan, <https://www.stocktitan.net/sec-filings/JSM/8-k-navient-corp-reports-material-event-40f1052fd741.html>

7. FortiBleed exposes Fortinet credentials at global scale - Field Effect, <https://fieldeffect.com/blog/fortibleed-exposes-fortinet-credentials>
8. DHS Confirms Breach of Information-Sharing Network Platform HSIN - Cyber Security News, <https://cybersecuritynews.com/dhs-confirms-breach-of-hsin/>
9. CVE-2026-9006: IBM WebSphere Application Server SSRF Flaw - SentinelOne, <https://www.sentinelone.com/vulnerability-database/cve-2026-9006/>
10. CVE-2026-8633: IBM WebSphere Application Server RCE Flaw - SentinelOne, <https://www.sentinelone.com/vulnerability-database/cve-2026-8633/>
11. Security Bulletin: IBM WebSphere Application Server Liberty is affected by a server-side request forgery vulnerability (CVE-2026-11546), <https://www.ibm.com/support/pages/node/7278572>
12. Hackers Breach Sensitive Government Network Used for World Cup and Major U.S. Event Security - Inc. Magazine, <https://www.inc.com/georgia-fearn/hackers-breach-sensitive-government-network-used-for-world-cup-event-security/91369238>
13. Hackers Breached A Key Homeland Security Network. The U.S. Government Is Racing To Find Out How. | IBTimes, <https://www.ibtimes.com/hackers-breached-key-homeland-security-network-us-government-racing-find-out-how-3804839>
14. <https://www.bleepingcomputer.com/news/security/cisa-microsoft-sharepoint-rce-flaw-now-actively-exploited/>
15. FortiBleed campaign traced to INC and Lynx ransomware operations, <https://www.cybersecuritydive.com/news/fortibleed-campaign-traced-to-inc-and-lynx-ransomware-operations/824348/>
16. FortiBleed: 86,644 Fortinet Firewalls Compromised — SOCRadar Research, <https://socradar.io/blog/fortibleed-fortinet-firewalls-compromised/>
17. FortiBleed: Default Credential Exploitation and Mass Fortinet Compromise - Lab Space, <https://labs.cloudsecurityalliance.org/research/csa-research-note-fortibleed-default-credentials-20260620-cs/>
18. Active FortiBleed Campaign Impacting Fortinet Devices Across 194 Countries, <https://arcticwolf.com/resources/blog/active-fortibleed-campaign-impacting-fortinet-devices-across-194-countries/>
19. Navient Corporation - Yahoo Finance, https://cdn.yahoofinance.com/prod/sec-filings/0001593538/000114036126027441/ef20077249_8k.htm
20. Personal, property information of 70,000 people compromised in data breach involving SLA vendor IBM, <https://www.asiaone.com/singapore/singapore-land-authority-data-security-incident-sla>
21. DHS Confirms Breach of HSIN Information-Sharing Platform - Particle News, <https://particle.news/story/dhs-confirms-breach-of-hsin-informationsharing-platform>
22. Fortinet "FortiBleed" Global Compromise & Active Exploitation of Fortinet Vulnerabilities - Kudelski Security Research Center,

<https://kudelskisecurity.com/research/fortinet-fortibleed-global-compromise-active-exploitation-of-fortinet-vulnerabilities>

23. GitHub - juanmill4/Breach-House: Yet another Ransomware gang tracker but with Breaches, Stealer Logs and Leads, <https://github.com/juanmill4/Breach-House>
24. Data for 70000 people compromised in Singapore after government test system exposed, <https://www.techgoondu.com/2026/07/03/data-for-70000-people-compromised-in-singapore-after-government-test-system-exposed/>
25. What is cloud patch management? A complete guide - Tanium, <https://www.tanium.com/blog/what-is-cloud-patch-management/>
26. How to Set Effective Vulnerability Remediation SLAs by Severity and Business Impact, <https://www.secure.com/blog/infrastructure-security/vulnerability-remediation-slas>
27. IBM WebSphere Products Multiple Vulnerabilities - HKCert, https://www.hkcert.org/security-bulletin/ibm-websphere-products-multiple-vulnerabilities_20260702
28. IBM WebSphere Products Multiple Vulnerabilities - HKCert, https://www.hkcert.org/security-bulletin/ibm-websphere-products-multiple-vulnerabilities_20260624
29. IBM WebSphere Application Server 8.5.x < 8.5.5.30 / 9.x < 9.0.5.29 (7276600) - Vulners.com, https://vulners.com/nessus/WEBSPPHERE_7276600.NASL
30. CVE-2026-9006 Detail - NVD, <https://nvd.nist.gov/vuln/detail/CVE-2026-9006>
31. CVE-2026-11714: IBM WebSphere Application Server Vulnerability - Sherlock Forensics, <https://www.sherlockforensics.com/blog/2026-06-30-cve-2026-11714.html>
32. CVE-2026-11714: CWE-918 Server-Side Request Forgery (SSRF) in IBM WebSphere Application Server - Liberty - Live Threat Intelligence - Threat Radar | OffSec.com, <https://radar.offsec.com/threat/cve-2026-11714-cwe-918-server-side-request-forgery-f96acf2a29715446>
33. CVE-2026-11546 - CVE Record, <https://www.cve.org/CVERecord?id=CVE-2026-11546>
34. Security Bulletin: IBM WebSphere Application Server Liberty is affected by an authorization bypass vulnerability (CVE-2026-11714), <https://www.ibm.com/support/pages/security-bulletin-ibm-websphere-application-server-liberty-affected-authorization-bypass-vulnerability-cve-2026-11714>
35. The front of the cyber kill chain just moved, <https://www.ibm.com/think/x-force/The-front-of-the-cyber-kill-chain-just-moved>
36. Top AI Security Vulnerabilities to Watch out for in 2026 - Cocode, <https://cocode.com/blog/ai-security-vulnerabilities/>
37. Anthropic's AI Finds Bugs. IBM Bets \$5B It Can Fix Them. - Dark Reading, <https://www.darkreading.com/vulnerabilities-threats/anthropic-s-ai-finds-bugs-ibm-bets-5b-it-can-fix-them->