

1. Create table emp1 and dept1 same as emp and dept. Create a trigger which will delete all records from emp1 table of corresponding department deleted from dept1 table.

```
create table emp1 as select * from emp;
create table dept1 as select * from dept;
delimiter //
create trigger trg_delete_emp
after delete on dept1
for each row
begin
delete from emp1
where deptno=old.deptno;
end;
//
delimiter ; //
select * from emp1 where deptno=10;
delete from dept1 where deptno=10;
```

2. Create table totalsal as select deptno, sum(sal) sal from emp1 group by deptno; Write a trigger which will update total salary in totalsal table whenever there is modification in sal of emp1 table.

```
create table totalsal as select deptno, sum(sal) sal from emp group by deptno;
create table emp1 as select * from emp;
delimiter //
create trigger trg_update_totalsal
after update on emp1
for each row
begin
update totalsal
set sal = sal - old.sal + new.sal
```

```

where deptno = old.deptno;
end;
//
delimiter ; //
select * from totalsal;
update emp1
set sal = 1000
where ename = 'SMITH';

```

3. Create a table emp1 same as emp. Write a plsql block which will insert all the details of employee in given department to a new table emp1.(use cursor)

```

create table emp1 as select * from emp where 1=0;
delimiter //
create procedure insert_dept_emp(in dno int)
begin
declare done int default 0;
declare v_empno int;
declare v_ename varchar(20);
declare v_job varchar(20);
declare v_deptno int;
declare v_mgr int;
declare v_hiredate date;
declare v_sal int;
declare v_comm int;
declare cur cursor for
select * from emp where deptno=dno;
declare continue handler for not found set done=1;
open cur;
read_loop: loop

```

```

fetch cur into v_empno,v_ename,v_job,v_deptno,
v_mgr,v_hiredate,v_sal,v_comm;
if done=1 then
leave read_loop;
end if;
insert into emp1
values(v_empno,v_ename,v_job,v_deptno,
v_mgr,v_hiredate,v_sal,v_comm);
end loop;
close cur;
end;
//
delimiter ; //
call insert_dept_emp(20);
select * from emp1;

```

4.Create a table emp1 same as emp.

I.Write a procedure to update salary of given employee to 3000 if salary is less than 3000 else give 10 percentage increment on emp1 table.

II.Write a plsql procedure which will insert all the details of given employee with empno to a new empty table emp1 which has same structure as emp;

I.

```

create table emp1 as select * from emp;

delimiter //
create procedure update_salary(in eno int)
begin
declare s int;
select sal into s
from emp1
where empno=eno;
if s < 3000 then
update emp1
set sal = 3000

```

```

where empno=eno;
else

update emp1
set sal = sal + sal*0.10
where empno=eno;
end if;
end;
//

delimiter ; //

select empno,ename,sal from emp1 where empno=7369;

call update_salary(7369);

select empno,ename,sal from emp1 where empno=7369;

```

II.

```

create table emp1 as select * from emp where 1=0;

delimiter //
create procedure insert_employee(in eno int)
begin
insert into emp1
select * from emp
where empno=eno;
end;
//
delimiter ; //

select * from emp1;

call insert_employee(7369);

select * from emp1;

```

5. Create a table emp1 same as emp.

I. Write a plsql function which will return total salary paid to given department number in emp1.

I. Write a plsql function which will return total number of employees working in given department number in emp1.

I.

```

create table emp1 as select * from emp;

```

```

delimiter //
create function total_salary(dno int)
returns int
deterministic
begin
declare ts int;
select sum(sal)
into ts
from emp1
where deptno=dno;
return ts;
end;
//
delimiter ; //
select total_salary(20);

```

```

II.
delimiter //
create function total_employee(dno int)
returns int
deterministic
begin
declare c int;
select count(*)
into c
from emp1
where deptno=dno;
return c;
end;
//
delimiter ; //
select total_employee(20);

```

6. Execute DDL/DML statements which demonstrate the use of views.

- I. Create table emp1 same as emp table;
- II. Create view dept20 for employees belonging to department 20 on table emp1.
- III. Update table emp1 increment comm by 100 where comm is not null using view dept20.
- IV. Delete record with empno = 7369 using view dept20
- V. Create view dept30 for employees belonging to department 30 on table emp1 with check option.
- VI. Insert a record in view dept30 for given data (73,'akash','clerk',7902,'1980-12-17',800,null,20) show the error.

VII. Create a view empview which will contain the empno, ename, sal, deptno,dname column. VIII. Delete view empview.
IX.Delete view dept20
X.Delete view dept30

I.

```
create table emp1 as select * from emp;
```

II.

```
create view dept20 as select * from emp1 where deptno=20;  
select * from dept20;
```

III.

```
update dept20 set comm = comm + 100 where comm is not null;
```

IV.

```
delete from dept20 where empno=7369;
```

V.

```
create view dept30 as select * from emp1 where deptno=30 with check option;
```

VI.

```
insert into dept30 values(73,'akash','clerk',30,7902,'1980-12-17',800,null);
```

VII.

```
create view empview as  
select e.empno,e.ename,e.sal,e.deptno,d.dname  
from emp1 e join dept d  
on e.deptno=d.deptno;  
select * from empview;
```

VIII.

```
drop view empview;
```

IX.

```
drop view dept20;
```

X.

```
drop view dept30;
```

7. Perform following SQL queries on the database SEIT

I. List all employees who are managers.

II. List all employees who receives null commission

III. List all employees who receives salary between 1000 and 3000.

IV. List all employees whose name ends with 's'.

V. List all employees order by salary in descending order VI. List minimum salary paid in department 20.

VII. List total salary paid in department 10.

VIII. List the department int and total salary payable to each department

IX. List details of all employees like empno, ename, sal, corresponding deptno, dname, loc from emp and dept table.

X. List details of all employees like empno, ename, sal, corresponding deptno, dname, loc from emp and dept table. Also display department with no employee.

I.

```
select * from emp where job='MANAGER';
```

II.

```
select * from emp where comm is null;
```

III.

```
select * from emp where sal between 1000 and 3000;
```

IV.

```
select * from emp where ename like '%S';
```

V.

```
select * from emp order by sal desc;
```

VI.

```
select min(sal) from emp where deptno=20;
```

VII.

```
select sum(sal) from emp where deptno=10;
```

VIII.

```
select deptno,sum(sal) from emp group by deptno;
```

IX.

```
select e.empno,e.ename,e.sal, d.deptno,d.dname,d.loc from emp e join dept d on e.deptno=d.deptno;
```

X.

```
select e.empno,e.ename,e.sal, d.deptno,d.dname,d.loc from emp e right join dept d on e.deptno=d.deptno;
```

8. Perform following SQL queries on the database SEIT

I. List name of employee and name of manager also list employee with no manager.

II. List employee number, name of employee and his manager name. Also list the employee who does not report to anyone.

- III. List name of employee and name of manager. Also display name of employee who does not have manager.
- IV. List different designations in department 10 and 20 using set operator.
- V. List all employees from department 20 those who are drawing more salary than average salary of department 20;
- VI. List employee details who earn salary greater than average salary of their department.
- VII. List all employees who have joined the company before their manager.
- VIII. List different designations in department 10 but not in department 20 using set operator.
- IX. List all employee whose salary is greater than average salary of his department.
- X. List all employee with name containing two 'a'

- I.
select e.ename employee, m.ename manager from emp e left join emp m on
e.mgr=m.empno;
- II.
select e.empno,e.ename, m.ename manager from emp e left join emp m on
e.mgr=m.empno;
- III.
select e.ename employee, m.ename manager from emp e left join emp m on
e.mgr=m.empno;
- IV.
select job from emp where deptno=10 union select job from emp where deptno=20;
- V.
select * from emp where deptno=20 and sal > (select avg(sal) from emp where deptno=20);
- VI.
select * from emp e where sal > (select avg(sal) from emp where deptno=e.deptno);
- VII.
select e.ename employee, m.ename manager from emp e join emp m on e.mgr=m.empno
where e.hiredate < m.hiredate;
- VIII.
select distinct job from emp where deptno=10 and job not in (select job from emp where
deptno=20);
- IX.
select * from emp e where sal > (select avg(sal) from emp where deptno=e.deptno);
- X.
select * from emp where ename like '%A%A%';

9. Perform following SQL queries on the database SEIT

- I. Create table emp1 same emp.
- II. Add a column to the existing table EMP1 which will hold the grade for each employee.

- III.Delete the column grade from emp table.
- IV.Modify table EMP1 ADD CONSTRAINT EMPNO_P primary key on column empno.
- V.Delete the primary key constraint from emp table;
- VI.Modify table EMP1 ADD CONSTRAINT SAL_C check sal is greater than 100.
- VII.Modify table EMP1 modify data type of sal to int(14,2).
- VIII.Add constraint default on ename column of student table.
- IX.Delete constraint default on name column of student table.
- X.Modify table EMP1 drop column SAL.

- I.
create table emp1 as select * from emp;
- II.
alter table emp1 add grade varchar(10);
- III.
alter table emp1 drop column grade;
- IV.
alter table emp1 add constraint EMPNO_P primary key(empno);
- V.
alter table emp drop primary key;
- VI.
alter table emp1 add constraint SAL_C check(sal>100);
- VII.
alter table emp1 modify sal int(14);
- VIII.
alter table emp1 modify ename varchar(20) default 'unknown';

```
insert into emp1(empno,job,deptno,mgr,hiredate,sal,comm)
values(9003,'CLERK',10,7839,'2024-01-01',1000,NULL);
select * from emp1 where empno=9003;
```

- IX.
alter table emp1 alter ename drop default;

```
insert into emp1(empno,job,deptno,mgr,hiredate,sal,comm)
values(9004,'CLERK',10,7839,'2024-01-01',1000,NULL);
select * from emp1 where empno=9004;
```

- X.
alter table emp1 drop column sal;