
pyart-mch library reference for developers

Release 0.0.1

meteoswiss-mdr

Feb 13, 2020

CONTENTS

Contents:

PYART.CORE.GRID

An class for holding gridded Radar data.

<code>Grid(time, fields, metadata, ...[, ...])</code>	A class for storing rectilinear gridded radar data in Cartesian coordinate.
<code>_point_data_factory(grid, coordinate)</code>	Return a function which returns the locations of all points.
<code>_point_lon_lat_data_factory(grid, coordinate)</code>	Return a function which returns the geographic locations of points.
<code>_point_altitude_data_factory(grid)</code>	Return a function which returns the point altitudes.

```
class pyart.core.grid.Grid(time, fields, metadata, origin_latitude, origin_longitude, origin_altitude, x, y, z, projection=None, radar_latitude=None, radar_longitude=None, radar_altitude=None, radar_time=None, radar_name=None)
```

Bases: `object`

A class for storing rectilinear gridded radar data in Cartesian coordinate.

Refer to the attribute section for information on the parameters.

To create a Grid object using legacy parameters present in Py-ART version 1.5 and before, use `from_legacy_parameters()`, `grid = Grid.from_legacy_parameters(fields, axes, metadata)`.

Attributes

time [dict] Time of the grid.

fields [dict of dicts] Moments from radars or other variables.

metadata [dict] Metadata describing the grid.

origin_longitude, origin_latitude, origin_altitude [dict] Geographic coordinate of the origin of the grid.

x, y, z [dict, 1D] Distance from the grid origin for each Cartesian coordinate axis in a one dimensional array. Defines the spacing along the three grid axes which is repeated throughout the grid, making a rectilinear grid.

nx, ny, nz [int] Number of grid points along the given Cartesian dimension.

projection [dic or str] Projection parameters defining the map projection used to transform from Cartesian to geographic coordinates. None will use the default dictionary with the 'proj' key set to 'pyart_aeqd' indicating that the native Py-ART azimuthal equidistant projection is used. Other values should specify a valid pyproj.Proj projparams dictionary or string.

The special key `'_include_lon_0_lat_0'` is removed when interpreting this dictionary. If this key is present and set to `True`, which is required when `proj='pyart_aeqd'`, then the radar longitude and latitude will be added to the dictionary as `'lon_0'` and `'lat_0'`. Use the `get_projparams()` method to retrieve a copy of this attribute dictionary with this special key evaluated.

radar_longitude, radar_latitude, radar_altitude [dict or None, optional] Geographic location of the radars which make up the grid.

radar_time [dict or None, optional] Start of collection for the radar which make up the grid.

radar_name [dict or None, optional] Names of the radars which make up the grid.

nradar [int] Number of radars whose data was used to make the grid.

projection_proj [Proj] pyproj.Proj instance for the projection specified by the projection attribute. If the `'pyart_aeqd'` projection is specified accessing this attribute will raise a `ValueError`.

point_x, point_y, point_z [LazyLoadDict] The Cartesian locations of all grid points from the origin in the three Cartesian coordinates. The three dimensional data arrays contained these attributes are calculated from the x, y, and z attributes. If these attributes are changed use `py:func: init_point_x_y_z` to reset the attributes.

point_longitude, point_latitude [LazyLoadDict] Geographic location of each grid point. The projection parameter(s) defined in the `projection` attribute are used to perform an inverse map projection from the Cartesian grid point locations relative to the grid origin. If these attributes are changed use `init_point_longitude_latitude()` to reset the attributes.

point_altitude [LazyLoadDict] The altitude of each grid point as calculated from the altitude of the grid origin and the Cartesian z location of each grid point. If this attribute is changed use `init_point_altitude()` to reset the attribute.

Methods

<code>add_field(self, field_name, field_dict[, ...])</code>	Add a field to the object.
<code>get_point_longitude_latitude(self[, level, ...])</code>	Return arrays of longitude and latitude for a given grid height level.
<code>get_projparams(self)</code>	Return a projparam dict from the projection attribute.
<code>init_point_altitude(self)</code>	Initialize the point_altitude attribute.
<code>init_point_longitude_latitude(self)</code>	Initialize or reset the point_{longitude, latitudes} attributes.
<code>init_point_x_y_z(self)</code>	Initialize or reset the point_{x, y, z} attributes.
<code>to_xarray(self)</code>	Convert the Grid object to an xarray format.
<code>write(self, filename[, format, ...])</code>	Write the the Grid object to a NetCDF file.

`__class__`

alias of `builtins.type`

`__delattr__(self, name, /)`

Implement `delattr(self, name)`.

`__dict__ = mappingproxy({'__module__': 'pyart.core.grid', '__doc__': "\n A class for`

`__dir__(self, /)`

Default `dir()` implementation.

`__eq__` (*self, value, /*)
Return self==value.

`__format__` (*self, format_spec, /*)
Default object formatter.

`__ge__` (*self, value, /*)
Return self>=value.

`__getattr__` (*self, name, /*)
Return getattr(self, name).

`__getstate__` (*self*)
Return object's state which can be pickled.

`__gt__` (*self, value, /*)
Return self>value.

`__hash__` (*self, /*)
Return hash(self).

`__init__` (*self, time, fields, metadata, origin_latitude, origin_longitude, origin_altitude, x, y, z, projection=None, radar_latitude=None, radar_longitude=None, radar_altitude=None, radar_time=None, radar_name=None*)
Initialize object.

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self, value, /*)
Return self<=value.

`__lt__` (*self, value, /*)
Return self<value.

`__module__` = 'pyart.core.grid'

`__ne__` (*self, value, /*)
Return self!=value.

`__new__` (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

`__reduce__` (*self, /*)
Helper for pickle.

`__reduce_ex__` (*self, protocol, /*)
Helper for pickle.

`__repr__` (*self, /*)
Return repr(self).

`__setattr__` (*self, name, value, /*)
Implement setattr(self, name, value).

`__setstate__` (*self, state*)
Restore unpicklable entries from pickled object.

`__sizeof__` (*self, /*)
Size of object in memory, in bytes.

`__str__` (*self, /*)
Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

_find_and_check_nradar (*self*)

Return the number of radars which were used to create the grid.

Examine the radar attributes to determine the number of radars which were used to create the grid. If the size of the radar attributes are inconsistent a `ValueError` is raised by this method.

add_field (*self*, *field_name*, *field_dict*, *replace_existing=False*)

Add a field to the object.

Parameters

field_name [str] Name of the field to the fields dictionary.

field_dict [dict] Dictionary containing field data and metadata.

replace_existing [bool, optional] True to replace the existing field with key *field_name* if it exists, overwriting the existing data. If `False`, a `ValueError` is raised if *field_name* already exists.

get_point_longitude_latitude (*self*, *level=0*, *edges=False*)

Return arrays of longitude and latitude for a given grid height level.

Parameters

level [int, optional] Grid height level at which to determine latitudes and longitudes. This is not currently used as all height level have the same layout.

edges [bool, optional] True to calculate the latitude and longitudes of the edges by interpolating between Cartesian coordinates points and extrapolating at the boundaries. `False` to calculate the locations at the centers.

Returns

longitude, latitude [2D array] Arrays containing the latitude and longitudes, in degrees, of the grid points or edges between grid points for the given height.

get_projparams (*self*)

Return a projparam dict from the projection attribute.

init_point_altitude (*self*)

Initialize the *point_altitude* attribute.

init_point_longitude_latitude (*self*)

Initialize or reset the *point_{longitude, latitudes}* attributes.

init_point_x_y_z (*self*)

Initialize or reset the *point_{x, y, z}* attributes.

projection_proj

to_xarray (*self*)

Convert the Grid object to an xarray format.

Attributes

time [dict] Time of the grid.

fields [dict of dicts] Moments from radars or other variables.

longitude, latitude [dict, 2D] Arrays of latitude and longitude for the grid height level.

x, y, z [dict, 1D] Distance from the grid origin for each Cartesian coordinate axis in a one dimensional array.

write (*self*, *filename*, *format*='NETCDF4', *arm_time_variables*=False, *arm_alt_lat_lon_variables*=False)
Write the the Grid object to a NetCDF file.

Parameters

filename [str] Filename to save to.

format [str, optional] NetCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'.

arm_time_variables [bool, optional] True to write the ARM standard time variables base_time and time_offset. False will not write these variables.

arm_alt_lat_lon_variables [bool, optional] True to write the ARM standard alt, lat, lon variables. False will not write these variables.

`pyart.core.grid._point_altitude_data_factory` (*grid*)
Return a function which returns the point altitudes.

`pyart.core.grid._point_data_factory` (*grid*, *coordinate*)
Return a function which returns the locations of all points.

`pyart.core.grid._point_lon_lat_data_factory` (*grid*, *coordinate*)
Return a function which returns the geographic locations of points.

PYART.CORE.RADAR

A general central radial scanning (or dwelling) instrument class.

<code>_rays_per_sweep_data_factory(radar)</code>	Return a function which returns the number of rays per sweep.
<code>_gate_data_factory(radar, coordinate)</code>	Return a function which returns the Cartesian locations of gates.
<code>_gate_lon_lat_data_factory(radar, coordinate)</code>	Return a function which returns the geographic locations of gates.
<code>_gate_altitude_data_factory(radar)</code>	Return a function which returns the gate altitudes.
<code>Radar(time, _range, fields, metadata, ...[, ...])</code>	A class for storing antenna coordinate radar data.

```
class pyart.core.radar.Radar(time, _range, fields, metadata, scan_type, latitude, longitude, altitude, sweep_number, sweep_mode, fixed_angle, sweep_start_ray_index, sweep_end_ray_index, azimuth, elevation, altitude_agl=None, target_scan_rate=None, rays_are_indexed=None, ray_angle_res=None, scan_rate=None, antenna_transition=None, instrument_parameters=None, radar_calibration=None, rotation=None, tilt=None, roll=None, drift=None, heading=None, pitch=None, georefs_applied=None)
```

Bases: `object`

A class for storing antenna coordinate radar data.

The structure of the Radar class is based on the CF/Radial Data file format. Global attributes and variables (section 4.1 and 4.3) are represented as a dictionary in the metadata attribute. Other required and optional variables are represented as dictionaries in a attribute with the same name as the variable in the CF/Radial standard. When a optional attribute not present the attribute has a value of None. The data for a given variable is stored in the dictionary under the 'data' key. Moment field data is stored as a dictionary of dictionaries in the fields attribute. Sub-convention variables are stored as a dictionary of dictionaries under the meta_group attribute.

Refer to the attribute section for information on the parameters.

Attributes

- time** [dict] Time at the center of each ray.
- range** [dict] Range to the center of each gate (bin).
- fields** [dict of dicts] Moment fields.
- metadata** [dict] Metadata describing the instrument and data.

scan_type [str] Type of scan, one of 'ppi', 'rhi', 'sector' or 'other'. If the scan volume contains multiple sweep modes this should be 'other'.

latitude [dict] Latitude of the instrument.

longitude [dict] Longitude of the instrument.

altitude [dict] Altitude of the instrument, above sea level.

altitude_agl [dict or None] Altitude of the instrument above ground level. If not provided this attribute is set to None, indicating this parameter not available.

sweep_number [dict] The number of the sweep in the volume scan, 0-based.

sweep_mode [dict] Sweep mode for each mode in the volume scan.

fixed_angle [dict] Target angle for the sweep. Azimuth angle in RHI modes, elevation angle in all other modes.

sweep_start_ray_index [dict] Index of the first ray in each sweep relative to the start of the volume, 0-based.

sweep_end_ray_index [dict] Index of the last ray in each sweep relative to the start of the volume, 0-based.

rays_per_sweep [LazyLoadDict] Number of rays in each sweep. The data key of this attribute is created upon first access from the data in the `sweep_start_ray_index` and `sweep_end_ray_index` attributes. If the sweep locations need to be modified, do this prior to accessing this attribute or use `init_rays_per_sweep()` to reset the attribute.

target_scan_rate [dict or None] Intended scan rate for each sweep. If not provided this attribute is set to None, indicating this parameter is not available.

rays_are_indexed [dict or None] Indication of whether ray angles are indexed to a regular grid in each sweep. If not provided this attribute is set to None, indicating ray angle spacing is not determined.

ray_angle_res [dict or None] If `rays_are_indexed` is not None, this provides the angular resolution of the grid. If not provided or available this attribute is set to None.

azimuth [dict] Azimuth of antenna, relative to true North. Azimuth angles are recommended to be expressed in the range of [0, 360], but other representations are not forbidden.

elevation [dict] Elevation of antenna, relative to the horizontal plane. Elevation angles are recommended to be expressed in the range of [-180, 180], but other representations are not forbidden.

gate_x, gate_y, gate_z [LazyLoadDict] Location of each gate in a Cartesian coordinate system assuming a standard atmosphere with a 4/3 Earth's radius model. The data keys of these attributes are created upon first access from the data in the `range`, `azimuth` and `elevation` attributes. If these attributes are changed use `init_gate_x_y_z()` to reset.

gate_longitude, gate_latitude [LazyLoadDict] Geographic location of each gate. The projection parameter(s) defined in the `projection` attribute are used to perform an inverse map projection from the Cartesian gate locations relative to the radar location to longitudes and latitudes. If these attributes are changed use `init_gate_longitude_latitude()` to reset the attributes.

projection [dict or str] Projection parameters defining the map projection used to transform from Cartesian to geographic coordinates. The default dictionary sets the 'proj' key to 'pyart_aeqd' indicating that the native Py-ART azimuthal equidistant projection is used. This can be modified to specify a valid pyproj.Proj projparams dictionary or string. The special key '_include_lon_0_lat_0' is removed when interpreting this dictionary. If this

key is present and set to True, which is required when `proj='pyart_aeqd'`, then the radar longitude and latitude will be added to the dictionary as 'lon_0' and 'lat_0'.

gate_altitude [LazyLoadDict] The altitude of each radar gate as calculated from the altitude of the radar and the Cartesian z location of each gate. If this attribute is changed use `init_gate_altitude()` to reset the attribute.

scan_rate [dict or None] Actual antenna scan rate. If not provided this attribute is set to None, indicating this parameter is not available.

antenna_transition [dict or None] Flag indicating if the antenna is in transition, 1 = yes, 0 = no. If not provided this attribute is set to None, indicating this parameter is not available.

rotation [dict or None] The rotation angle of the antenna. The angle about the aircraft longitudinal axis for a vertically scanning radar.

tilt [dict or None] The tilt angle with respect to the plane orthogonal (Z-axis) to aircraft longitudinal axis.

roll [dict or None] The roll angle of platform, for aircraft right wing down is positive.

drift [dict or None] Drift angle of antenna, the angle between heading and track.

heading [dict or None] Heading (compass) angle, clockwise from north.

pitch [dict or None] Pitch angle of antenna, for aircraft nose up is positive.

georefs_applied [dict or None] Indicates whether the variables have had georeference calculation applied. Leading to Earth-centric azimuth and elevation angles.

instrument_parameters [dict of dicts or None] Instrument parameters, if not provided this attribute is set to None, indicating these parameters are not available. This dictionary also includes variables in the radar_parameters CF/Radial subconvention.

radar_calibration [dict of dicts or None] Instrument calibration parameters. If not provided this attribute is set to None, indicating these parameters are not available

ngates [int] Number of gates (bins) in a ray.

nrays [int] Number of rays in the volume.

nsweeps [int] Number of sweep in the volume.

Methods

<code>add_field(self, field_name, dic[, ...])</code>	Add a field to the object.
<code>add_field_like(self, existing_field_name, ...)</code>	Add a field to the object with metadata from a existing field.
<code>check_field_exists(self, field_name)</code>	Check that a field exists in the fields dictionary.
<code>extract_sweeps(self, sweeps)</code>	Create a new radar contains only the data from select sweeps.
<code>get_azimuth(self, sweep[, copy])</code>	Return an array of azimuth angles for a given sweep.
<code>get_elevation(self, sweep[, copy])</code>	Return an array of elevation angles for a given sweep.
<code>get_end(self, sweep)</code>	Return the ending ray for a given sweep.
<code>get_field(self, sweep, field_name[, copy])</code>	Return the field data for a given sweep.
<code>get_gate_lat_lon_alt(self, sweep[, ...])</code>	Return the longitude, latitude and altitude gate locations.
<code>get_gate_x_y_z(self, sweep[, edges, ...])</code>	Return the x, y and z gate locations in meters for a given sweep.

Continued on next page

Table 3 – continued from previous page

<code>get_nyquist_vel(self, sweep[, check_uniform])</code>	Return the Nyquist velocity in meters per second for a given sweep.
<code>get_slice(self, sweep)</code>	Return a slice for selecting rays for a given sweep.
<code>get_start(self, sweep)</code>	Return the starting ray index for a given sweep.
<code>get_start_end(self, sweep)</code>	Return the starting and ending ray for a given sweep.
<code>info(self[, level, out])</code>	Print information on radar.
<code>init_gate_altitude(self)</code>	Initialize the <code>gate_altitude</code> attribute.
<code>init_gate_longitude_latitude(self)</code>	Initialize or reset the <code>gate_longitude</code> and <code>gate_latitude</code> attributes.
<code>init_gate_x_y_z(self)</code>	Initialize or reset the <code>gate_{x, y, z}</code> attributes.
<code>init_rays_per_sweep(self)</code>	Initialize or reset the <code>rays_per_sweep</code> attribute.
<code>iter_azimuth(self)</code>	Return an iterator which returns sweep azimuth data.
<code>iter_elevation(self)</code>	Return an iterator which returns sweep elevation data.
<code>iter_end(self)</code>	Return an iterator over the sweep end indices.
<code>iter_field(self, field_name)</code>	Return an iterator which returns sweep field data.
<code>iter_slice(self)</code>	Return an iterator which returns sweep slice objects.
<code>iter_start(self)</code>	Return an iterator over the sweep start indices.
<code>iter_start_end(self)</code>	Return an iterator over the sweep start and end indices.

`__class__`

alias of `builtins.type`

`__delattr__` (*self, name, /*)

Implement `delattr(self, name)`.

`__dict__` = `mappingproxy({'__module__': 'pyart.core.radar', '__doc__': "\n A class fo`

`__dir__` (*self, /*)

Default `dir()` implementation.

`__eq__` (*self, value, /*)

Return `self==value`.

`__format__` (*self, format_spec, /*)

Default object formatter.

`__ge__` (*self, value, /*)

Return `self>=value`.

`__getattr__` (*self, name, /*)

Return `getattr(self, name)`.

`__getstate__` (*self*)

Return object's state which can be pickled.

`__gt__` (*self, value, /*)

Return `self>value`.

`__hash__` (*self, /*)

Return `hash(self)`.

__init__ (*self, time, _range, fields, metadata, scan_type, latitude, longitude, altitude, sweep_number, sweep_mode, fixed_angle, sweep_start_ray_index, sweep_end_ray_index, azimuth, elevation, altitude_agl=None, target_scan_rate=None, rays_are_indexed=None, ray_angle_res=None, scan_rate=None, antenna_transition=None, instrument_parameters=None, radar_calibration=None, rotation=None, tilt=None, roll=None, drift=None, heading=None, pitch=None, georefs_applied=None*)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)

Return self<=value.

__lt__ (*self, value, /*)

Return self<value.

__module__ = 'pyart.core.radar'

__ne__ (*self, value, /*)

Return self!=value.

__new__ (*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)

Helper for pickle.

__reduce_ex__ (*self, protocol, /*)

Helper for pickle.

__repr__ (*self, /*)

Return repr(self).

__setattr__ (*self, name, value, /*)

Implement setattr(self, name, value).

__setstate__ (*self, state*)

Restore unpicklable entries from pickled object.

__sizeof__ (*self, /*)

Size of object in memory, in bytes.

__str__ (*self, /*)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

_check_sweep_in_range (*self, sweep*)

Check that a sweep number is in range.

_dic_info (*self, attr, level, out, dic=None, ident_level=0*)

Print information on a dictionary attribute.

add_field (*self*, *field_name*, *dic*, *replace_existing=False*)

Add a field to the object.

Parameters

field_name [str] Name of the field to add to the dictionary of fields.

dic [dict] Dictionary contain field data and metadata.

replace_existing [bool, optional] True to replace the existing field with key *field_name* if it exists, losing any existing data. False will raise a `ValueError` when the field already exists.

add_field_like (*self*, *existing_field_name*, *field_name*, *data*, *replace_existing=False*)

Add a field to the object with metadata from an existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the second. To copy NumPy arrays use the `copy()` method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters

existing_field_name [str] Name of an existing field to take metadata from when adding the new field to the object.

field_name [str] Name of the field to add to the dictionary of fields.

data [array] Field data. A copy of this data is not made, see the note above.

replace_existing [bool, optional] True to replace the existing field with key *field_name* if it exists, losing any existing data. False will raise a `ValueError` when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*self*, *field_name*)

Check that a field exists in the fields dictionary.

If the field does not exist raise a `KeyError`.

Parameters

field_name [str] Name of field to check.

extract_sweeps (*self*, *sweeps*)

Create a new radar contains only the data from select sweeps.

Parameters

sweeps [array_like] Sweeps (0-based) to include in new Radar object.

Returns

radar [Radar] Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*self*, *sweep*, *copy=False*)

Return an array of azimuth angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the azimuth angles for a given sweep.

get_elevation (*self*, *sweep*, *copy=False*)

Return an array of elevation angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the elevation angles for a given sweep.

get_end (*self*, *sweep*)

Return the ending ray for a given sweep.

get_field (*self*, *sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with *get_gate_x_y_z* () this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

field_name [str] Name of the field from which data should be retrieved.

copy [bool, optional] True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns

data [array] Array containing data for the requested sweep and field.

get_gate_lat_lon_alt (*self*, *sweep*, *reset_gate_coords=False*, *filter_transitions=False*)

Return the longitude, latitude and altitude gate locations. Longitude and latitude are in degrees and altitude in meters.

With the default parameter this method returns the same data as contained in the *gate_latitude*, *gate_longitude* and *gate_altitude* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute. If coordinates have at all, please use the *reset_gate_coords* parameter.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

reset_gate_coords [bool, optional] Optional to reset the gate latitude, gate longitude and gate altitude attributes before using them in this function. This is useful when the geographic coordinates have changed and gate latitude, gate longitude and gate altitude need to be reset.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns

lat, lon, alt [2D array] Array containing the latitude, longitude and altitude, for all gates in the sweep.

get_gate_x_y_z (*self*, *sweep*, *edges=False*, *filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the `gate_x`, `gate_y` and `gate_z` attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with `get_field()` this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

edges [bool, optional] True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns

x, y, z [2D array] Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*self*, *sweep*, *check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a `LookupError` if the Nyquist velocity is not available, an `Exception` is raised if the velocities are not uniform in the sweep unless `check_uniform` is set to False.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

check_uniform [bool] True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns

nyquist_velocity [float] Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*self*, *sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*self*, *sweep*)

Return the starting ray index for a given sweep.

get_start_end (*self*, *sweep*)

Return the starting and ending ray for a given sweep.

info (*self*, *level*=*'standard'*, *out*=*<io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)
Print information on radar.

Parameters

level [{*'compact'*, *'standard'*, *'full'*, *'c'*, *'s'*, *'f'*}, optional] Level of information on radar object to print, compact is minimal information, standard more and full everything.

out [file-like, optional] Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude (*self*)
Initialize the *gate_altitude* attribute.

init_gate_longitude_latitude (*self*)
Initialize or reset the *gate_longitude* and *gate_latitude* attributes.

init_gate_x_y_z (*self*)
Initialize or reset the *gate_{x, y, z}* attributes.

init_rays_per_sweep (*self*)
Initialize or reset the *rays_per_sweep* attribute.

iter_azimuth (*self*)
Return an iterator which returns sweep azimuth data.

iter_elevation (*self*)
Return an iterator which returns sweep elevation data.

iter_end (*self*)
Return an iterator over the sweep end indices.

iter_field (*self*, *field_name*)
Return an iterator which returns sweep field data.

iter_slice (*self*)
Return an iterator which returns sweep slice objects.

iter_start (*self*)
Return an iterator over the sweep start indices.

iter_start_end (*self*)
Return an iterator over the sweep start and end indices.

pyart.core.radar._gate_altitude_data_factory (*radar*)
Return a function which returns the gate altitudes.

pyart.core.radar._gate_data_factory (*radar*, *coordinate*)
Return a function which returns the Cartesian locations of gates.

pyart.core.radar._gate_lon_lat_data_factory (*radar*, *coordinate*)
Return a function which returns the geographic locations of gates.

pyart.core.radar._rays_per_sweep_data_factory (*radar*)
Return a function which returns the number of rays per sweep.

PYART.CORE.RADAR

A general central radial scanning (or dwelling) spectra instrument class.

RadarSpectra(time, _range, fields, metadata, ...) A class for storing antenna coordinate radar spectra data.

```
class pyart.core.radar_spectra.RadarSpectra(time, _range, fields, metadata,
scan_type, latitude, longitude, altitude, sweep_number, sweep_mode,
fixed_angle, sweep_start_ray_index, sweep_end_ray_index, azimuth, elevation,
npulses, Doppler_velocity=None, Doppler_frequency=None, altitude_agl=None,
target_scan_rate=None, rays_are_indexed=None, ray_angle_res=None, scan_rate=None,
antenna_transition=None, instrument_parameters=None, radar_calibration=None,
rotation=None, tilt=None, roll=None, drift=None, heading=None, pitch=None,
geo_refs_applied=None)
```

Bases: *pyart.core.radar.Radar*

A class for storing antenna coordinate radar spectra data. Based on the radar object class

The structure of the Radar class is based on the CF/Radial Data file format. Global attributes and variables (section 4.1 and 4.3) are represented as a dictionary in the metadata attribute. Other required and optional variables are represented as dictionaries in a attribute with the same name as the variable in the CF/Radial standard. When a optional attribute not present the attribute has a value of None. The data for a given variable is stored in the dictionary under the 'data' key. Moment field data is stored as a dictionary of dictionaries in the fields attribute. Sub-convention variables are stored as a dictionary of dictionaries under the meta_group attribute.

Refer to the attribute section for information on the parameters.

Attributes

time [dict] Time at the center of each ray.

range [dict] Range to the center of each gate (bin).

npulses [dict] number of pulses for each ray

Doppler_velocity [dict or None] The Doppler velocity of each Doppler bin. The data has dimensions nrays x npulses_max

Doppler_frequency [dict or None] The Doppler frequency of each Doppler bin. The data has dimensions `nrays x npulses_max`

fields [dict of dicts] Moment fields. The data has dimensions `nrays x ngates x npulses_max`

metadata [dict] Metadata describing the instrument and data.

scan_type [str] Type of scan, one of 'ppi', 'rhi', 'sector' or 'other'. If the scan volume contains multiple sweep modes this should be 'other'.

latitude [dict] Latitude of the instrument.

longitude [dict] Longitude of the instrument.

altitude [dict] Altitude of the instrument, above sea level.

altitude_agl [dict or None] Altitude of the instrument above ground level. If not provided this attribute is set to None, indicating this parameter not available.

sweep_number [dict] The number of the sweep in the volume scan, 0-based.

sweep_mode [dict] Sweep mode for each mode in the volume scan.

fixed_angle [dict] Target angle for the sweep. Azimuth angle in RHI modes, elevation angle in all other modes.

sweep_start_ray_index [dict] Index of the first ray in each sweep relative to the start of the volume, 0-based.

sweep_end_ray_index [dict] Index of the last ray in each sweep relative to the start of the volume, 0-based.

rays_per_sweep [LazyLoadDict] Number of rays in each sweep. The data key of this attribute is created upon first access from the data in the `sweep_start_ray_index` and `sweep_end_ray_index` attributes. If the sweep locations need to be modified, do this prior to accessing this attribute or use `init_rays_per_sweep()` to reset the attribute.

target_scan_rate [dict or None] Intended scan rate for each sweep. If not provided this attribute is set to None, indicating this parameter is not available.

rays_are_indexed [dict or None] Indication of whether ray angles are indexed to a regular grid in each sweep. If not provided this attribute is set to None, indicating ray angle spacing is not determined.

ray_angle_res [dict or None] If `rays_are_indexed` is not None, this provides the angular resolution of the grid. If not provided or available this attribute is set to None.

azimuth [dict] Azimuth of antenna, relative to true North. Azimuth angles are recommended to be expressed in the range of [0, 360], but other representations are not forbidden.

elevation [dict] Elevation of antenna, relative to the horizontal plane. Elevation angles are recommended to be expressed in the range of [-180, 180], but other representations are not forbidden.

gate_x, gate_y, gate_z [LazyLoadDict] Location of each gate in a Cartesian coordinate system assuming a standard atmosphere with a 4/3 Earth's radius model. The data keys of these attributes are created upon first access from the data in the `azimuth` and `elevation` attributes. If these attributes are changed use `init_gate_x_y_z()` to reset.

gate_longitude, gate_latitude [LazyLoadDict] Geographic location of each gate. The projection parameter(s) defined in the `projection` attribute are used to perform an inverse map projection from the Cartesian gate locations relative to the radar location to longitudes and latitudes. If these attributes are changed use `init_gate_longitude_latitude()` to reset the attributes.

projection [dic or str] Projection parameters defining the map projection used to transform from Cartesian to geographic coordinates. The default dictionary sets the 'proj' key to 'pyart_aeqd' indicating that the native Py-ART azimuthal equidistant projection is used. This can be modified to specify a valid pyproj.Proj projparams dictionary or string. The special key '_include_lon_0_lat_0' is removed when interpreting this dictionary. If this key is present and set to True, which is required when proj='pyart_aeqd', then the radar longitude and latitude will be added to the dictionary as 'lon_0' and 'lat_0'.

gate_altitude [LazyLoadDict] The altitude of each radar gate as calculated from the altitude of the radar and the Cartesian z location of each gate. If this attribute is changed use *init_gate_altitude()* to reset the attribute.

scan_rate [dict or None] Actual antenna scan rate. If not provided this attribute is set to None, indicating this parameter is not available.

antenna_transition [dict or None] Flag indicating if the antenna is in transition, 1 = yes, 0 = no. If not provided this attribute is set to None, indicating this parameter is not available.

rotation [dict or None] The rotation angle of the antenna. The angle about the aircraft longitudinal axis for a vertically scanning radar.

tilt [dict or None] The tilt angle with respect to the plane orthogonal (Z-axis) to aircraft longitudinal axis.

roll [dict or None] The roll angle of platform, for aircraft right wing down is positive.

drift [dict or None] Drift angle of antenna, the angle between heading and track.

heading [dict or None] Heading (compass) angle, clockwise from north.

pitch [dict or None] Pitch angle of antenna, for aircraft nose up is positive.

georefs_applied [dict or None] Indicates whether the variables have had georeference calculation applied. Leading to Earth-centric azimuth and elevation angles.

instrument_parameters [dict of dicts or None] Instrument parameters, if not provided this attribute is set to None, indicating these parameters are not available. This dictionary also includes variables in the radar_parameters CF/Radial subconvention.

radar_calibration [dict of dicts or None] Instrument calibration parameters. If not provided this attribute is set to None, indicating these parameters are not available

ngates [int] Number of gates (bins) in a ray.

nrays [int] Number of rays in the volume.

npulses_max [int] Maximum number of pulses per ray in the volume.

nsweeps [int] Number of sweep in the volume.

Methods

<i>add_field</i> (self, field_name, dic[, ...])	Add a field to the object.
<i>add_field_like</i> (self, existing_field_name, ...)	Add a field to the object with metadata from a existing field.
<i>check_field_exists</i> (self, field_name)	Check that a field exists in the fields dictionary.
<i>extract_sweeps</i> (self, sweeps)	Create a new radar contains only the data from select sweeps.
<i>get_azimuth</i> (self, sweep[, copy])	Return an array of azimuth angles for a given sweep.

Continued on next page

Table 2 – continued from previous page

<i>get_elevation</i> (self, sweep[, copy])	Return an array of elevation angles for a given sweep.
<i>get_end</i> (self, sweep)	Return the ending ray for a given sweep.
<i>get_field</i> (self, sweep, field_name[, copy])	Return the field data for a given sweep.
<i>get_gate_lat_lon_alt</i> (self, sweep[, ...])	Return the longitude, latitude and altitude gate locations.
<i>get_gate_x_y_z</i> (self, sweep[, edges, ...])	Return the x, y and z gate locations in meters for a given sweep.
<i>get_nyquist_vel</i> (self, sweep[, check_uniform])	Return the Nyquist velocity in meters per second for a given sweep.
<i>get_slice</i> (self, sweep)	Return a slice for selecting rays for a given sweep.
<i>get_start</i> (self, sweep)	Return the starting ray index for a given sweep.
<i>get_start_end</i> (self, sweep)	Return the starting and ending ray for a given sweep.
<i>info</i> (self[, level, out])	Print information on radar.
<i>init_gate_altitude</i> (self)	Initialize the gate_altitude attribute.
<i>init_gate_longitude_latitude</i> (self)	Initialize or reset the gate_longitude and gate_latitude attributes.
<i>init_gate_x_y_z</i> (self)	Initialize or reset the gate_{x, y, z} attributes.
<i>init_rays_per_sweep</i> (self)	Initialize or reset the rays_per_sweep attribute.
<i>iter_azimuth</i> (self)	Return an iterator which returns sweep azimuth data.
<i>iter_elevation</i> (self)	Return an iterator which returns sweep elevation data.
<i>iter_end</i> (self)	Return an iterator over the sweep end indices.
<i>iter_field</i> (self, field_name)	Return an iterator which returns sweep field data.
<i>iter_slice</i> (self)	Return an iterator which returns sweep slice objects.
<i>iter_start</i> (self)	Return an iterator over the sweep start indices.
<i>iter_start_end</i> (self)	Return an iterator over the sweep start and end indices.

__class__

alias of builtins.type

__delattr__ (self, name, /)

Implement delattr(self, name).

__dict__ = **mappingproxy**({'__module__': 'pyart.core.radar_spectra', '__doc__': "\n A

__dir__ (self, /)

Default dir() implementation.

__eq__ (self, value, /)

Return self==value.

__format__ (self, format_spec, /)

Default object formatter.

__ge__ (self, value, /)

Return self>=value.

__getattr__ (self, name, /)

Return getattr(self, name).

__getstate__ (self)

Return object's state which can be pickled.

__gt__ (self, value, /)

Return self>value.

__hash__ (*self*, /)
Return hash(*self*).

__init__ (*self*, *time*, *_range*, *fields*, *metadata*, *scan_type*, *latitude*, *longitude*, *altitude*, *sweep_number*, *sweep_mode*, *fixed_angle*, *sweep_start_ray_index*, *sweep_end_ray_index*, *azimuth*, *elevation*, *npulses*, *Doppler_velocity*=None, *Doppler_frequency*=None, *altitude_agl*=None, *target_scan_rate*=None, *rays_are_indexed*=None, *ray_angle_res*=None, *scan_rate*=None, *antenna_transition*=None, *instrument_parameters*=None, *radar_calibration*=None, *rotation*=None, *tilt*=None, *roll*=None, *drift*=None, *heading*=None, *pitch*=None, *geo_refs_applied*=None)
Initialize self. See help(type(*self*)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.core.radar_spectra'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(*self*).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(*self*, *name*, *value*).

__setstate__ (*self*, *state*)
Restore unpicklable entries from pickled object.

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(*self*).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__check_sweep_in_range (*self*, *sweep*)
Check that a sweep number is in range.

_dic_info (*self, attr, level, out, dic=None, ident_level=0*)
Print information on a dictionary attribute.

add_field (*self, field_name, dic, replace_existing=False*)
Add a field to the object.

Parameters

field_name [str] Name of the field to add to the dictionary of fields.

dic [dict] Dictionary contain field data and metadata.

replace_existing [bool] True to replace the existing field with key field_name if it exists, loosing any existing data. False will raise a ValueError when the field already exists.

add_field_like (*self, existing_field_name, field_name, data, replace_existing=False*)
Add a field to the object with metadata from a existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the second. To copy NumPy arrays use the copy() method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters

existing_field_name [str] Name of an existing field to take metadata from when adding the new field to the object.

field_name [str] Name of the field to add to the dictionary of fields.

data [array] Field data. A copy of this data is not made, see the note above.

replace_existing [bool] True to replace the existing field with key field_name if it exists, loosing any existing data. False will raise a ValueError when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',  
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*self, field_name*)
Check that a field exists in the fields dictionary.

If the field does not exist raise a KeyError.

Parameters

field_name [str] Name of field to check.

extract_sweeps (*self, sweeps*)
Create a new radar contains only the data from select sweeps.

Parameters

sweeps [array_like] Sweeps (0-based) to include in new Radar object.

Returns

radar [Radar] Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*self, sweep, copy=False*)
Return an array of azimuth angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the azimuth angles for a given sweep.

get_elevation (*self*, *sweep*, *copy=False*)

Return an array of elevation angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the elevation angles for a given sweep.

get_end (*self*, *sweep*)

Return the ending ray for a given sweep.

get_field (*self*, *sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with *get_gate_x_y_z()* this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

field_name [str] Name of the field from which data should be retrieved.

copy [bool, optional] True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns

data [array] Array containing data for the requested sweep and field.

get_gate_lat_lon_alt (*self*, *sweep*, *reset_gate_coords=False*, *filter_transitions=False*)

Return the longitude, latitude and altitude gate locations. Longitude and latitude are in degrees and altitude in meters.

With the default parameter this method returns the same data as contained in the *gate_latitude*, *gate_longitude* and *gate_altitude* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute. If coordinates have at all, please use the *reset_gate_coords* parameter.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

reset_gate_coords [bool, optional] Optional to reset the gate latitude, gate longitude and gate altitude attributes before using them in this function. This is useful when the geographic coordinates have changed and gate latitude, gate longitude and gate altitude need to be reset.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the antenna_transition attribute is not available (set to None).

Returns

lat, lon, alt [2D array] Array containing the latitude, longitude and altitude, for all gates in the sweep.

get_gate_x_y_z (*self, sweep, edges=False, filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the gate_x, gate_y and gate_z attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with *get_field()* this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

edges [bool, optional] True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the antenna_transition attribute is not available (set to None).

Returns

x, y, z [2D array] Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*self, sweep, check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a LookupError if the Nyquist velocity is not available, an Exception is raised if the velocities are not uniform in the sweep unless check_uniform is set to False.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

check_uniform [bool] True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns

nyquist_velocity [float] Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*self, sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*self, sweep*)

Return the starting ray index for a given sweep.

get_start_end (*self*, *sweep*)

Return the starting and ending ray for a given sweep.

info (*self*, *level*=*'standard'*, *out*=<_io.TextIOWrapper name=*'<stdout>' mode='w' encoding='UTF-8'>*)

Print information on radar.

Parameters

level [{*'compact'*, *'standard'*, *'full'*, *'c'*, *'s'*, *'f'*}] Level of information on radar object to print, compact is minimal information, standard more and full everything.

out [file-like] Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude (*self*)

Initialize the gate_altitude attribute.

init_gate_longitude_latitude (*self*)

Initialize or reset the gate_longitude and gate_latitude attributes.

init_gate_x_y_z (*self*)

Initialize or reset the gate_{x, y, z} attributes.

init_rays_per_sweep (*self*)

Initialize or reset the rays_per_sweep attribute.

iter_azimuth (*self*)

Return an iterator which returns sweep azimuth data.

iter_elevation (*self*)

Return an iterator which returns sweep elevation data.

iter_end (*self*)

Return an iterator over the sweep end indices.

iter_field (*self*, *field_name*)

Return an iterator which returns sweep field data.

iter_slice (*self*)

Return an iterator which returns sweep slice objects.

iter_start (*self*)

Return an iterator over the sweep start indices.

iter_start_end (*self*)

Return an iterator over the sweep start and end indices.

PYART.CORE.WIND_PROFILE

Storage of wind profiles.

HorizontalWindProfile(height, speed, direction) Horizontal wind profile.

class pyart.core.wind_profile.**HorizontalWindProfile**(height, speed, direction, latitude=None, longitude=None)

Bases: `object`

Horizontal wind profile.

Parameters

height [array-like, 1D] Heights in meters above sea level at which horizontal winds were sampled.

speed [array-like, 1D] Horizontal wind speed in meters per second at each height sampled.

direction [array-like, 1D] Horizontal wind direction in degrees at each height sampled.

Other Parameters

latitude [array-like, 1D, optional] Latitude in degrees north at each height sampled.

longitude [array-like, 1D, optional] Longitude in degrees east at each height sampled.

Attributes

height [array, 1D] Heights in meters above sea level at which horizontal winds were sampled.

speed [array, 1D] Horizontal wind speed in meters per second at each height.

direction [array, 1D] Horizontal wind direction in degrees at each height.

u_wind [array, 1D] U component of horizontal wind in meters per second.

v_wind [array, 1D] V component of horizontal wind in meters per second.

Methods

from_u_and_v(height, u_wind, v_wind) Create a HorizontalWindProfile instance from U and V components.

__class__
alias of `builtins.type`

`__delattr__` (*self, name, /*)
Implement `delattr(self, name)`.

`__dict__` = `mappingproxy({'__module__': 'pyart.core.wind_profile', '__doc__': '\n Hor`

`__dir__` (*self, /*)
Default `dir()` implementation.

`__eq__` (*self, value, /*)
Return `self==value`.

`__format__` (*self, format_spec, /*)
Default object formatter.

`__ge__` (*self, value, /*)
Return `self>=value`.

`__getattr__` (*self, name, /*)
Return `getattr(self, name)`.

`__gt__` (*self, value, /*)
Return `self>value`.

`__hash__` (*self, /*)
Return `hash(self)`.

`__init__` (*self, height, speed, direction, latitude=None, longitude=None*)
initialize

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self, value, /*)
Return `self<=value`.

`__lt__` (*self, value, /*)
Return `self<value`.

`__module__` = `'pyart.core.wind_profile'`

`__ne__` (*self, value, /*)
Return `self!=value`.

`__new__` (**args, **kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

`__reduce__` (*self, /*)
Helper for pickle.

`__reduce_ex__` (*self, protocol, /*)
Helper for pickle.

`__repr__` (*self, /*)
Return `repr(self)`.

`__setattr__` (*self, name, value, /*)
Implement `setattr(self, name, value)`.

`__sizeof__` (*self, /*)
Size of object in memory, in bytes.

`__str__` (*self, /*)
Return `str(self)`.

`__subclasshook__()`

Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`_parse_location_data` (*self*, *latitude*, *longitude*)

Parse profile location data.

`classmethod from_u_and_v` (*height*, *u_wind*, *v_wind*)

Create a `HorizontalWindProfile` instance from U and V components.

Parameters

`height` [array-like, 1D] Heights in meters above sea level at which horizontal winds were sampled.

`u_wind` [array-like, 1D] U component of horizontal wind speed in meters per second.

`v_wind` [array-like, 1D] V component of horizontal wind speed in meters per second.

`u_wind`

U component of horizontal wind in meters per second.

`v_wind`

V component of horizontal wind in meters per second.

PYART.IO.ARM_SONDE

Utilities for ARM sonde NetCDF files.

<code>read_arm_sonde(filename)</code>	Read a ARM sonde file returning a wind profile.
<code>read_arm_sonde_vap(filename[, radar, ...])</code>	Read a ARM interpolated or merged sonde returning a wind profile.

`pyart.io.arm_sonde.read_arm_sonde(filename)`

Read a ARM sonde file returning a wind profile.

Parameters

filename [str] Name of ARM sonde NetCDF file to read data from.

`pyart.io.arm_sonde.read_arm_sonde_vap(filename, radar=None, target_datetime=None)`

Read a ARM interpolated or merged sonde returning a wind profile.

Parameters

filename [str] Name of ARM interpolate or merged sonde NetCDF file to read data from.

radar [Radar, optional] If provided the profile returned is that which is closest in time to the first ray collected in this radar. Either radar or target_datetime must be provided.

target_datetime [datetime, optional] If specified the profile returned is that which is closest in time to this datetime.

PYART.IO.AUTO_READ

Automatic reading of radar files by detecting format.

<code>read(filename[, use_rsl])</code>	Read a radar file and return a radar object.
<code>determine_filetype(filename)</code>	Return the filetype of a given file by examining the first few bytes.

`pyart.io.auto_read.determine_filetype(filename)`

Return the filetype of a given file by examining the first few bytes.

The following filetypes are detected:

- 'MDV'
- 'NETCDF3'
- 'NETCDF4'
- 'WSR88D'
- 'NEXRADL3'
- 'UF'
- 'HDF4'
- 'RSL'
- 'DORAD'
- 'SIGMET'
- 'LASSEN'
- 'BZ2'
- 'GZ'
- 'UNKNOWN'

Parameters

filename [str] Name of file to examine.

Returns

filetype [str] Type of file.

`pyart.io.auto_read.read(filename, use_rsl=False, **kwargs)`

Read a radar file and return a radar object.

Additional parameters are passed to the underlying read_* function.

Parameters

filename [str] Name of radar file to read.

use_rsl [bool] True will use the TRMM RSL library to read files which are supported both natively and by RSL. False will choose the native read function. RSL will always be used to read a file if it is not supported natively.

Returns

radar [Radar] Radar object. A TypeError is raised if the format cannot be determined.

Other Parameters

field_names [dict, optional] Dictionary mapping file data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names [bool, optional] True to use the file data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Not all file types support this parameter.

PYART.IO.CFRADIAL

Utilities for reading CF/Radial files.

<code>_NetCDFVariableDataExtractor(ncvar)</code>	Class facilitating on demand extraction of data from a NetCDF variable.
<code>read_cfradial(filename[, field_names, ...])</code>	Read a Cfradial netCDF file.
<code>write_cfradial(filename, radar[, format, ...])</code>	Write a Radar object to a CF/Radial compliant netCDF file.
<code>_find_all_meta_group_vars(ncvars, ...)</code>	Return a list of all variables which are in a given meta_group.
<code>_ncvar_to_dict(ncvar[, lazydict])</code>	Convert a NetCDF Dataset variable to a dictionary.
<code>_unpack_variable_gate_field_dic(dic, shape, ...)</code>	Create a 2D array from a 1D field data, dic update in place.
<code>_create_ncvar(dic, dataset, name, dimensions)</code>	Create and fill a Variable in a netCDF Dataset object.
<code>_calculate_scale_and_offset(dic, dtype[, ...])</code>	Calculate appropriated 'scale_factor' and 'add_offset' for nc variable in dic in order to scaling to fit dtype range.

class `pyart.io.cfradial._NetCDFVariableDataExtractor(ncvar)`

Bases: `object`

Class facilitating on demand extraction of data from a NetCDF variable.

Parameters

ncvar [`netCDF4.Variable`] NetCDF Variable from which data will be extracted.

Methods

<code>__call__(self)</code>	Return an array containing data from the stored variable.
<code>__call__(self)</code>	Return an array containing data from the stored variable.
<code>__class__</code>	alias of <code>builtins.type</code>
<code>__delattr__(self, name, /)</code>	Implement <code>delattr(self, name)</code> .

__dict__ = `mappingproxy({'__module__': 'pyart.io.cfradial', '__doc__': '\n Class fac`
__dir__ (*self*, /)
 Default dir() implementation.

__eq__ (*self*, *value*, /)
 Return self==value.

__format__ (*self*, *format_spec*, /)
 Default object formatter.

__ge__ (*self*, *value*, /)
 Return self>=value.

__getattr__ (*self*, *name*, /)
 Return getattr(self, name).

__gt__ (*self*, *value*, /)
 Return self>value.

__hash__ (*self*, /)
 Return hash(self).

__init__ (*self*, *ncvar*)
 initialize the object.

__init_subclass__ ()
 This method is called when a class is subclassed.

 The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
 Return self<=value.

__lt__ (*self*, *value*, /)
 Return self<value.

__module__ = `'pyart.io.cfradial'`

__ne__ (*self*, *value*, /)
 Return self!=value.

__new__ (**args*, ***kwargs*)
 Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
 Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
 Helper for pickle.

__repr__ (*self*, /)
 Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
 Implement setattr(self, name, value).

__sizeof__ (*self*, /)
 Size of object in memory, in bytes.

__str__ (*self*, /)
 Return str(self).

__subclasshook__()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

`pyart.io.cfradial._calculate_scale_and_offset(dic, dtype, minimum=None, maximum=None)`

Calculate appropriated 'scale_factor' and 'add_offset' for nc variable in dic in order to scaling to fit dtype range.

Parameters

dic [dict] Radar dictionary containing variable data and meta-data.

dtype [Numpy Dtype] Integer numpy dtype to map to.

minimum, maximum [float] Greatest and smallest values in the data, those values will be mapped to the smallest+1 and greatest values that dtype can hold. If equal to None, numpy.amin and numpy.amax will be used on the data contained in dic to determine these values.

`pyart.io.cfradial._create_ncvar(dic, dataset, name, dimensions, physical=False, is_field=False)`

Create and fill a Variable in a netCDF Dataset object.

Parameters

dic [dict] Radar dictionary to containing variable data and meta-data.

dataset [Dataset] NetCDF dataset to create variable in.

name [str] Name of variable to create.

dimension [tuple of str] Dimension of variable.

physical [bool] boolean specifying whether to store the data in physical dimensions or in binary. If true the data will be converted into binary using the gain and offset specified in variables 'scale_factor' and 'add_offset' in the field metadata or a gain and offset computed on the fly

`pyart.io.cfradial._find_all_meta_group_vars(ncvars, meta_group_name)`

Return a list of all variables which are in a given meta_group.

`pyart.io.cfradial._ncvar_to_dict(ncvar, lazydict=False)`

Convert a NetCDF Dataset variable to a dictionary.

`pyart.io.cfradial._unpack_variable_gate_field_dic(dic, shape, ray_n_gates, ray_start_index)`

Create a 2D array from a 1D field data, dic update in place.

`pyart.io.cfradial.read_cfradial(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, delay_field_loading=False, **kwargs)`

Read a Cfradial netCDF file.

Parameters

filename [str] Name of CF/Radial netCDF file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are

still included in the `radar.fields` dictionary, to exclude them use the `exclude_fields` parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the `field_names` parameter is ignored. False will use to `field_names` parameter to re-name fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields specified by `include_fields`.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields not specified by `exclude_fields`.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Delayed field loading will not provide any speedup in file where the number of gates vary between rays (`ngates_vary=True`) and is not recommended.

Returns

radar [Radar] Radar object.

Notes

This function has not been tested on "stream" Cfradial files.

```
pyart.io.cfradial.write_cfradial(filename, radar, format='NETCDF4', time_reference=None,  
                                arm_time_variables=False, physical=True)
```

Write a Radar object to a CF/Radial compliant netCDF file.

The files produced by this routine follow the [CF/Radial standard](#). Attempts are also made to to meet many of the standards outlined in the [ARM Data File Standards](#).

To control how the netCDF variables are created, set any of the following keys in the radar attribute dictionaries.

- `_Zlib`
- `_DeflateLevel`
- `_Shuffle`
- `_Fletcher32`
- `_Contiguous`
- `_ChunkSizes`
- `_Endianness`
- `_Least_significant_digit`
- `_FillValue`

See the netCDF4 documentation for details on these settings.

Parameters

filename [str] Filename to create.

radar [Radar] Radar object.

format [str, optional] NetCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'. See netCDF4 documentation for details.

time_reference [bool] True to include a time_reference variable, False will not include this variable. The default, None, will include the time_reference variable when the first time value is non-zero.

arm_time_variables [bool] True to create the ARM standard time variables base_time and time_offset, False will not create these variables.

physical [bool] True to store the radar fields as physical numbers, False will store the radar fields as binary if the keyword '_Write_as_dtype' is in the field metadata. The gain and offset can be specified in the keyword 'scale_factor' and 'add_offset' or calculated on the fly.

PYART.IO.CFRADIAL2

Utilities for reading CF/Radial2 files.

`read_cfradial2(filename[, field_names, ...])` Read a Cfradial2 netCDF file.

`pyart.io.cfradial2.read_cfradial2(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, delay_field_loading=False, **kwargs)`

Read a Cfradial2 netCDF file.

Parameters

filename [str] Name of CF/Radial netCDF file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the radar.fields dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Delayed field loading will not provide any speedup in file where the number of gates vary between rays (*ngates_vary=True*) and is not recommended.

Returns

radar [Radar] Radar object.

Notes

This function has not been tested on “stream” Cfradial files.

PYART.IO.CHL

Utilities for reading CSU-CHILL CHL files.

<code>ChlFile(filename[, ns_time, debug])</code>	A file object for CHL data.
<code>read_chl(filename[, field_names, ...])</code>	Read a CSU-CHILL CHL file.
<code>_unpack_structure(string, structure)</code>	Unpack a structure.

class `pyart.io.chl.ChlFile` (*filename, ns_time=True, debug=False*)

Bases: `object`

A file object for CHL data.

Parameters

filename [str or file-like.] Name of CHL file to read or a file-like object pointing to the beginning of such a file.

ns_time [bool] True to determine ray collection times to the nano-second, False will only determine times to the second.

debug [bool] True to keep packet data in the `_packets` attribute to aid in debugging.

Attributes

ngates [int] Number of gates per ray.

num_sweeps [int] Number of sweeps in the volume.

gate_spacing [float] Spacing in meters between gates.

first_gate_offset [float] Distance in meters to the first range gate.

time [list of ints] Time in seconds in epoch for each ray in the volume.

azimuth [list of floats] Azimuth angle for each ray in the volume in degrees.

elevation [list of floats] Elevation angle for each ray in the volume in degrees.

fixed_angle [list of floats] Fixed angles for each sweep.

sweep_number [list of ints] Sweep numbers reported in file.

scan_types [list of ints] Chill defined scan type for each sweep.

rays_per_sweep [list of ints] Number of rays in each sweep.

fields [dict] Dictionary of field data index by field number.

radar_info [dict] Radar information recorded in the file.

field_info [dict] Field information (limits, name, etc.) recorded in the file.

processor_info [dict] Processor information recorded in the file.

Methods

close(self)

Close the file.

__class__

alias of `builtins.type`

__delattr__ (self, name, /)

Implement `delattr`(self, name).

__dict__ = `mappingproxy({'__module__': 'pyart.io.ch1', '__doc__': '\n A file object .`

__dir__ (self, /)

Default `dir()` implementation.

__eq__ (self, value, /)

Return `self==value`.

__format__ (self, format_spec, /)

Default object formatter.

__ge__ (self, value, /)

Return `self>=value`.

__getattr__ (self, name, /)

Return `getattr`(self, name).

__gt__ (self, value, /)

Return `self>value`.

__hash__ (self, /)

Return `hash`(self).

__init__ (self, filename, ns_time=True, debug=False)

Initialize self. See `help(type(self))` for accurate signature.

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)

Return `self<=value`.

__lt__ (self, value, /)

Return `self<value`.

__module__ = 'pyart.io.ch1'

__ne__ (self, value, /)

Return `self!=value`.

__new__ (*args, **kwargs)

Create and return a new object. See `help(type)` for accurate signature.

__reduce__ (self, /)

Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_extract_fields (*self*)
Extract field data from _dstring attribute post read.

_parse_field_scale_block (*self, payload*)
Parse a field_scale block. Add scale to field_info attr.

_parse_file_hdr_block (*self, payload*)
Parse a field_hdr block.

_parse_processor_info_block (*self, payload*)
Parse a processor_info block. Set dr attribute.

_parse_radar_info_block (*self, payload*)
Parse a radar_info block. Update metadata attribute.

_parse_ray_hdr_block (*self, payload*)
Parse a ray_hdr block. Update associated attributes.

_parse_scan_seg_block (*self, payload*)
Parse a scan_seg_block. Update sweep attributes.

_parse_sweep_block (*self, payload*)
Parse a sweep block. Set num_sweeps attribute.

_read_block (*self*)
Read a block from an open CHL file.

close (*self*)
Close the file.

pyart.io.chl._unpack_structure (*string, structure*)
Unpack a structure.

pyart.io.chl.read_chl (*filename, field_names=None, additional_metadata=None, file_field_names=None, exclude_fields=None, include_fields=None, use_file_field_attributes=True, **kwargs*)
Read a CSU-CHILL CHL file.

Parameters

filename [str] Name of CHL file.

field_names [dict, optional] Dictionary mapping CHL field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the CHL field names for the field names in the radar object. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not in exclude_fields.

use_file_field_attributes [bool, optional] True to use information provided by in the file to set the field attribute *long_name*, *units*, *valid_max*, and *valid_min*. False will not set these unless they are defined in the configuration file or in *additional_metadata*.

Returns

radar [Radar] Radar object containing data from CHL file.

PYART.IO.COMMON

Input/output routines common to many file formats.

<i>prepare_for_read</i> (filename)	Return a file like object read for reading.
<i>stringarray_to_chararray</i> (arr[, numchars])	Convert an string array to a character array with one extra dimension.
<i>_test_arguments</i> (dic)	Issue a warning if receive non-empty argument dict.
<i>make_time_unit_str</i> (dtobj)	Return a time unit string from a datetime object.

`pyart.io.common._test_arguments(dic)`

Issue a warning if receive non-empty argument dict.

`pyart.io.common.make_time_unit_str(dtobj)`

Return a time unit string from a datetime object.

`pyart.io.common.prepare_for_read(filename)`

Return a file like object read for reading.

Open a file for reading in binary mode with transparent decompression of Gzip and BZip2 files. The resulting file-like object should be closed.

Parameters

filename [str or file-like object] Filename or file-like object which will be opened. File-like objects will not be examined for compressed data.

Returns

file_like [file-like object] File like object from which data can be read.

`pyart.io.common.stringarray_to_chararray(arr, numchars=None)`

Convert an string array to a character array with one extra dimension.

Parameters

arr [array] Array with numpy dtype 'SN', where N is the number of characters in the string.

numchars [int] Number of characters used to represent the string. If numchar > N the results will be padded on the right with blanks. The default, None will use N.

Returns

chararr [array] Array with dtype 'S1' and shape = arr.shape + (numchars,).

PYART.IO.GRID_IO

Reading and writing Grid objects.

<code>read_grid(filename[, exclude_fields, ...])</code>	Read a netCDF grid file produced by Py-ART.
<code>write_grid(filename, grid[, format, ...])</code>	Write a Grid object to a CF-1.5 and ARM standard netCDF file.
<code>_make_coordinatesystem_dict(grid)</code>	Return a dictionary containing parameters for a coordinate transform.

`pyart.io.grid_io._make_coordinatesystem_dict(grid)`
Return a dictionary containing parameters for a coordinate transform.

Examine the grid projection attribute and other grid attributes to return a dictionary containing parameters which can be written to a netCDF variable to specify a horizontal coordinate transform recognized by Unidata's CDM. Return None when the projection defined in the grid cannot be mapped to a CDM coordinate transform.

`pyart.io.grid_io.read_grid(filename, exclude_fields=None, include_fields=None, **kwargs)`
Read a netCDF grid file produced by Py-ART.

Parameters

filename [str] Filename of netCDF grid file to read. This file must have been produced by `write_grid()` or have identical layout.

Returns

grid [Grid] Grid object containing gridded data.

Other Parameters

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields specified by `include_fields`.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields not specified by `exclude_fields`.

`pyart.io.grid_io.write_grid(filename, grid, format='NETCDF4', write_proj_coord_sys=True, proj_coord_sys=None, arm_time_variables=False, arm_alt_lat_lon_variables=False, write_point_x_y_z=False, write_point_lon_lat_alt=False)`

Write a Grid object to a CF-1.5 and ARM standard netCDF file.

To control how the netCDF variables are created, set any of the following keys in the grid attribute dictionaries.

- `_Zlib`

- `_DeflateLevel`
- `_Shuffle`
- `_Fletcher32`
- `_Contiguous`
- `_ChunkSizes`
- `_Endianness`
- `_Least_significant_digit`
- `_FillValue`

See the netCDF4 documentation for details on these settings.

Parameters

filename [str] Filename to save grid to.

grid [Grid] Grid object to write.

format [str, optional] netCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'. See netCDF4 documentation for details.

write_proj_coord_sys bool, optional True to write information on the coordinate transform used in the map projection to the ProjectionCoordinateSystem variable following the CDM Object Model. The resulting file should be interpreted as containing geographic grids by tools which use the Java NetCDF library (THREDDS, toolsUI, etc).

proj_coord_sys [dict or None, optional] Dictionary of parameters which will be written to the ProjectionCoordinateSystem NetCDF variable if write_proj_coord_sys is True. A value of None will attempt to generate an appropriate dictionary by examining the projection attribute of the grid object. If the projection is not understood a warnings will be issued.

arm_time_variables [bool, optional] True to write the ARM standard time variables base_time and time_offset. False will not write these variables.

arm_alt_lat_lon_variables [bool, optional] True to write the ARM standard alt, lat, lon variables. False will not write these variables.

write_point_x_y_z [bool, optional] True to include the point_x, point_y and point_z variables in the written file, False will not write these variables.

write_point_lon_lat_alt [bool, optional] True to include the point_longitude, point_latitude and point_altitude variables in the written file, False will not write these variables.

PYART.IO.MDV_COMMON

Functions and classes common between MDV grid and radar files.

<i>MdvFile</i> (filename[, debug, read_fields])	A file object for MDV data.
<i>_MdvVolumeDataExtractor</i> (mdvfile, field_num, ...)	Class facilitating on demand extraction of data from a MDV file.

class `pyart.io.mdv_common.MdvFile` (filename, debug=False, read_fields=False)

Bases: `object`

A file object for MDV data.

A *MdvFile* object stores metadata and data from a MDV file. Metadata is stored in dictionaries as attributes of the object, field data is stored as NumPy ndarrays as attributes with the field name. By default only metadata is read initially and field data must be read using the *read_a_field* or *read_all_fields* methods. This behavior can be changed by setting the *read_fields* parameter to True.

Parameters

filename [str, file-like or None.] Name of MDV file to read or file-like object pointing to the beginning of such a file. None can be used to initialize an object which can be used for writing mdv files.

debug [bool] True to print out debugging information, False to suppress.

read_fields [bool] True to read all field during initialization, False (default) only reads metadata.

Notes

This class is not stable enough for general purpose MDV reading/writing, nor is that the intention, but with care it can provide sufficient read/write capacity.

Methods

<i>close</i> (self)	Close the MDV file.
<i>read_a_field</i> (self, fnum[, debug])	Read a field from the MDV file.
<i>read_all_fields</i> (self)	Read all fields, storing data to field name attributes.
<i>write</i> (self, filename[, debug])	Write object data to a MDV file.

__class__
alias of `builtins.type`

`__delattr__` (*self, name, /*)
Implement `delattr(self, name)`.

`__dict__` = `mappingproxy({'__module__': 'pyart.io.mdv_common', '__doc__': '\n A file o`

`__dir__` (*self, /*)
Default `dir()` implementation.

`__eq__` (*self, value, /*)
Return `self==value`.

`__format__` (*self, format_spec, /*)
Default object formatter.

`__ge__` (*self, value, /*)
Return `self>=value`.

`__getattr__` (*self, name, /*)
Return `getattr(self, name)`.

`__gt__` (*self, value, /*)
Return `self>value`.

`__hash__` (*self, /*)
Return `hash(self)`.

`__init__` (*self, filename, debug=False, read_fields=False*)
initialize

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self, value, /*)
Return `self<=value`.

`__lt__` (*self, value, /*)
Return `self<value`.

`__module__` = `'pyart.io.mdv_common'`

`__ne__` (*self, value, /*)
Return `self!=value`.

`__new__` (**args, **kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

`__reduce__` (*self, /*)
Helper for pickle.

`__reduce_ex__` (*self, protocol, /*)
Helper for pickle.

`__repr__` (*self, /*)
Return `repr(self)`.

`__setattr__` (*self, name, value, /*)
Implement `setattr(self, name, value)`.

`__sizeof__` (*self, /*)
Size of object in memory, in bytes.

`__str__` (*self, /*)
Return `str(self)`.

`__subclasshook__()`

Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`_calc_file_offsets(self)`

Calculate file offsets.

`_calc_geometry(self)`

Calculate geometry, return `az_deg`, `range_km`, `el_deg`.

`_get_calib(self)`

Get the calibration information, return a dict.

`_get_chunk_header(self)`

Get a single chunk header, return a dict.

`_get_chunk_headers(self, nchunks)`

Get `nchunk` chunk headers, return a list of dicts.

`_get_chunks(self, debug=False)`

Get data in chunks, return `radar_info`, `elevations`, `calib_info`.

`_get_compression_info(self)`

Get compression information, return a dict.

`_get_elevs(self, nbytes)`

Return an array of elevation read from current file position.

`_get_field_header(self)`

Read a single field header, return a dict.

`_get_field_headers(self, nfields)`

Read `nfields` field headers, return a list of dicts.

`_get_levels_info(self, nlevels)`

Get `nlevel` information, return a dict.

`_get_master_header(self)`

Read the MDV master header, return a dict.

`_get_radar_info(self)`

Get the radar information, return dict.

`_get_unknown_chunk(self, cnum)`

Get raw data from chunk.

`_get_vlevel_header(self)`

Read a single vlevel header, return a dict.

`_get_vlevel_headers(self, nfields)`

Read `nfields` vlevel headers, return a list of dicts.

`_make_carts_dict(self)`

Return a carts dictionary, distances in meters.

`_make_fields_list(self)`

Return a list of fields.

`_make_time_dict (self)`
Return a time dictionary.

`_pack_mapped (self, d, mapper, fmt)`
Create a packed string using a mapper and format.

`_secs_since_epoch (self, dt)`
Return the number of seconds since the epoch for a datetime.

`_time_dict_into_header (self)`
Complete time information in master_header from the time dict.

`_unpack_mapped_tuple (self, l, mapper)`
Create a dictionary from a tuple using a mapper.

`_write_a_field (self, fnum)`
write field number 'fnum' to mdv file.

`_write_calib (self, d)`
Write calibration information.

`_write_chunk_header (self, d)`
Write the a single chunk header.

`_write_chunk_headers (self, nchunks)`
Write nchunk chunk headers.

`_write_chunks (self, debug=False)`
write chunks data

`_write_compression_info (self, d)`
Write compression infomation.

`_write_elevs (self, l)`
Write an array of elevation.

`_write_field_header (self, d)`
Write the a single field header.

`_write_field_headers (self, nfields)`
Write nfields field headers.

`_write_levels_info (self, nlevels, d)`
write levels information, return a dict.

`_write_master_header (self)`
Write the MDV master header.

`_write_radar_info (self, d)`
Write radar information.

`_write_unknown_chunk (self, data)`
Write raw data from chunk.

`_write_vlevel_header (self, d)`
Write the a single vfield header.

`_write_vlevel_headers (self, nfields)`
Write nfields vlevel headers.

`calib_fmt = '>16s 6i 51f 14f'`

`calib_mapper = [('radar_name', 0, 1), ('year', 1, 2), ('month', 2, 3), ('day', 3, 4),`

`chunk_header_fmt = '>5i 2i 480s i'`

```
chunk_header_mapper = [('record_len1', 0, 1), ('struct_id', 1, 2), ('chunk_id', 2, 3),
close(self)
    Close the MDV file.

compression_info_fmt = '>I I I I 2I'
compression_info_mapper = [('magic_cookie', 0, 1), ('nbytes_uncompressed', 1, 2), ('nb
field_header_fmt = '>17i 10i 9i 4i f f 8f 12f 4f 5f 64s 16s 16s 16s 16s i'
field_header_mapper = [('record_len1', 0, 1), ('struct_id', 1, 2), ('field_code', 2, 3
master_header_fmt = b'>28i 8i i 5i 6f 3f 12f 512s 128s 128s i'
master_header_mapper = [('record_len1', 0, 1), ('struct_id', 1, 2), ('revision_number'
radar_info_fmt = '>12i 2i 22f 4f 40s 40s'
radar_info_mapper = [('radar_id', 0, 1), ('radar_type', 1, 2), ('nfields', 2, 3), ('ng
read_a_field(self, fnum, debug=False)
    Read a field from the MDV file.
```

Parameters

fnum [int] Field number to read.

debug [bool] True to print debugging information, False to suppress.

Returns

field_data [array] Field data. This data is also stored as a object attribute under the field name.

See also:

read_all_fields Read all fields in the MDV file.

```
read_all_fields(self)
    Read all fields, storing data to field name attributes.

vlevel_header_fmt = '>i i 122i 4i 122f 5f i'
vlevel_header_mapper = [('record_len1', 0, 1), ('struct_id', 1, 2), ('type', 2, 124),
write(self, filename, debug=False)
    Write object data to a MDV file.
```

Note that the file is not explicitly closes, use `x.close()` to close file object when complete.

Parameters

filename [str or file-like] Filename or open file object to which data will be written.

debug [bool, options] True to print out debugging information, False to suppress.

```
class pyart.io.mdv_common._MdvVolumeDataExtractor(mdvfile, field_num, fillvalue,
                                                    two_dims=True)
```

Bases: `object`

Class facilitating on demand extraction of data from a MDV file.

Parameters

mdvfile [MdvFile] Open MdvFile object to extract data from.

field_num [int] Field number of data to be extracted.

fillvalue [int] Value used to fill masked values in the returned array.

two_dims [bool.] True to combine the first and second dimension of the array when returning the data, False will return a three dimensional array.

Methods

<code>__call__(self)</code>	Return an array containing data from the referenced volume.
-----------------------------	---

`__call__(self)`
Return an array containing data from the referenced volume.

`__class__`
alias of `builtins.type`

`__delattr__(self, name, /)`
Implement `delattr(self, name)`.

`__dict__ = mappingproxy({'__module__': 'pyart.io.mdv_common', '__doc__': '\n Class f`

`__dir__(self, /)`
Default `dir()` implementation.

`__eq__(self, value, /)`
Return `self==value`.

`__format__(self, format_spec, /)`
Default object formatter.

`__ge__(self, value, /)`
Return `self>=value`.

`__getattr__(self, name, /)`
Return `getattr(self, name)`.

`__gt__(self, value, /)`
Return `self>value`.

`__hash__(self, /)`
Return `hash(self)`.

`__init__(self, mdvfile, field_num, fillvalue, two_dims=True)`
initialize the object.

`__init_subclass__()`
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__(self, value, /)`
Return `self<=value`.

`__lt__(self, value, /)`
Return `self<value`.

`__module__ = 'pyart.io.mdv_common'`

`__ne__(self, value, /)`
Return `self!=value`.

__new__ (*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)

Helper for pickle.

__reduce_ex__ (self, protocol, /)

Helper for pickle.

__repr__ (self, /)

Return repr(self).

__setattr__ (self, name, value, /)

Implement setattr(self, name, value).

__sizeof__ (self, /)

Size of object in memory, in bytes.

__str__ (self, /)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

pyart.io.mdv_common.**__decode_rle8** (compr_data, key, decompr_size)

Decode 8-bit MDV run length encoding.

PYART.IO.MDV_RADAR

Utilities for reading of MDV radar files.

<code>read_mdv(filename[, field_names, ...])</code>	Read a MDV file.
---	------------------

```
pyart.io.mdv_radar.read_mdv(filename, field_names=None, additional_metadata=None,
                             file_field_names=False, exclude_fields=None, include_fields=None,
                             delay_field_loading=False, **kwargs)
```

Read a MDV file.

Parameters

filename [str] Name of MDV file to read or file-like object pointing to the beginning of such a file.

field_names [dict, optional] Dictionary mapping MDV data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Not all file types support this parameter.

Returns

radar [Radar] Radar object containing data from MDV file.

Notes

Currently this function can only read polar MDV files with fields compressed with gzip or zlib.

PYART.IO.MDV_GRID

Utilities for reading and writing of MDV grid files.

<code>write_grid_mdv(filename, grid[, ...])</code>	Write grid object to MDV file.
<code>read_grid_mdv(filename[, field_names, ...])</code>	Read a MDV file to a Grid Object.
<code>_time_dic_to_datetime(dic)</code>	Return a datetime for the first element in a time dictionary.

`pyart.io.mdv_grid._time_dic_to_datetime(dic)`

Return a datetime for the first element in a time dictionary.

`pyart.io.mdv_grid.read_grid_mdv(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, delay_field_loading=False, **kwargs)`

Read a MDV file to a Grid Object.

Parameters

filename [str] Name of MDV file to read or file-like object pointing to the beginning of such a file.

field_names [dict, optional] Dictionary mapping MDV data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the grid object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

Returns

grid [Grid] Grid object containing data from MDV file.

Notes

This function can only read cartesian MDV files with fields compressed with gzip or zlib. For polar files see `pyart.io.read_mdv()`

MDV files and Grid object are not fully interchangeable. Specific limitation include:

- All fields must have the same shape and dimensions.
- All fields must have the same projection.
- Vlevels types must not vary.
- Projection must not be PROJ_POLAR_RADAR (9) or PROJ_RHI_RADAR (13).
- Correct unit in the Z axis are just available for 'vlevel_type' equal to VERT_TYPE_Z(4), VERT_TYPE_ELEV(9), VERT_TYPE_AZ(17), VERT_TYPE_PRESSURE(3) and VERT_TYPE_THETA(7).
- The behavior in cases of 2D data is unknown but most likely will not fail.

```
pyart.io.mdv_grid.write_grid_mdv(filename, grid, mdv_field_names=None,
                                field_write_order=None)
```

Write grid object to MDV file.

Create a MDV file containing data from the provided grid instance.

The MDV file will contain parameters from the 'source' key if contained in `grid.metadata`. If this key or parameters related to the radar location and name are not present in the grid a default or sentinel value. will be written in the MDV file in the place of the parameter.

Grid fields will be saved in float32 unless the `_Write_as_dtype` key is present.

Parameters

filename [str or file-like object.] Filename of MDV file to create. If a file-like object is specified data will be written using the write method.

grid [Grid] Grid object from which to create MDV file.

mdv_field_names [dict or None, optional] Mapping between grid fields and MDV data type names. Field names mapped to None or with no mapping will be excluded from writing. If None, the same field names will be used.

field_write_order [list or None, optional] Order in which grid fields should be written out in the MDV file. None, the default, will determine a valid order automatically.

Notes

Do to limitations of the MDV format, not all grid objects are writable. To write a grid the following conditions must be satisfied:

- XY grid must be regular (equal spacing), Z can be irregular.
- The number of Z levels must not exceed 122.
- Fields can be encoded in the file using the '`_Write_as_dtype`' key specifying one of 'uint8', 'uint16' or 'float32'. Use the 'scale_factor' and 'add_offset' keys to specify scaling. Field data in the Grid object should be uncompressed, that is to say it has had the scaling applied.

PYART.IO.NEXRADL3_READ

Functions for reading NEXRAD Level 3 products.

```
read_nexrad_level3(filename[, field_names, Read a NEXRAD Level 3 product.  
...])
```

```
pyart.io.nexradl3_read.read_nexrad_level3(filename, field_names=None,  
additional_metadata=None,  
file_field_names=False, exclude_fields=None,  
include_fields=None, **kwargs)
```

Read a NEXRAD Level 3 product.

Parameters

filename [str] Filename of NEXRAD Level 3 product file. The files hosted by at the NOAA National Climate Data Center [?] as well as on the NWS WSR-88D Level III Data Collection and Distribution Network have been tests. Other NEXRAD Level 3 files may or may not work. A file-like object pointing to the beginning of such a file is also supported.

field_names [dict, optional] Dictionary mapping NEXRAD level 3 product number to radar field names. If the product number of the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names [bool, optional] True to use the product number for the field name. In this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

Returns

radar [Radar] Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[?], [?]

PYART.IO.NEXRAD_ARCHIVE

Functions for reading NEXRAD Level II Archive files.

<code>_NEXRADLevel2StagedField(nfile, moment, ...)</code>	A class to facilitate on demand loading of field data from a Level 2 file.
<code>read_nexrad_archive(filename[, field_names, ...])</code>	Read a NEXRAD Level 2 Archive file.
<code>_find_range_params(scan_info, filemetadata)</code>	Return range parameters, first_gate, gate_spacing, last_gate.
<code>_find_scans_to_interp(scan_info, first_gate, ...)</code>	Return a dict indicating what moments/scans need interpolation.
<code>_interpolate_scan(mdata, start, end, ...[, ...])</code>	Interpolate a single NEXRAD moment scan from 1000 m to 250 m.

class `pyart.io.nexrad_archive._NEXRADLevel2StagedField` (*nfile, moment, max_ngates, scans*)

Bases: `object`

A class to facilitate on demand loading of field data from a Level 2 file.

Methods

<code>__call__(self)</code>	Return the array containing the field data.
<code>__call__(self)</code>	Return the array containing the field data.
<code>__class__</code>	alias of <code>builtins.type</code>
<code>__delattr__(self, name, /)</code>	Implement <code>delattr(self, name)</code> .
<code>__dict__ = mappingproxy({'__module__': 'pyart.io.nexrad_archive', '__doc__': '\n A c</code>	
<code>__dir__(self, /)</code>	Default <code>dir()</code> implementation.
<code>__eq__(self, value, /)</code>	Return <code>self==value</code> .

__format__ (*self, format_spec, /*)
Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, nfile, moment, max_ngates, scans*)
initialize.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyart.io.nexrad_archive'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)


```
pyart.io.nexrad_archive._find_range_params(scan_info, filemetadata)
```

Return range parameters, first_gate, gate_spacing, last_gate.

```
pyart.io.nexrad_archive._find_scans_to_interp(scan_info, first_gate, gate_spacing,
                                              filemetadata)
```

Return a dict indicating what moments/scans need interpolation.

```
pyart.io.nexrad_archive._interpolate_scan(mdata, start, end, moment_ngates, linear_interp=True)
```

Interpolate a single NEXRAD moment scan from 1000 m to 250 m.

```
pyart.io.nexrad_archive.read_nexrad_archive(filename, field_names=None,
                                             additional_metadata=None,
                                             file_field_names=False, exclude_fields=None,
                                             include_fields=None, delay_field_loading=False,
                                             station=None, scans=None, linear_interp=True,
                                             **kwargs)
```

Read a NEXRAD Level 2 Archive file.

Parameters

filename [str] Filename of NEXRAD Level 2 Archive file. The files hosted by at the NOAA National Climate Data Center [?] as well as on the UCAR THREDDS Data Server [?] have been tested. Other NEXRAD Level 2 Archive files may or may not work. Message type 1 file and message type 31 files are supported.

field_names [dict, optional] Dictionary mapping NEXRAD moments to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduct any addition metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names [bool, optional] True to use the NEXRAD field names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

delay_field_loading [bool, optional] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

station [str or None, optional] Four letter ICAO name of the NEXRAD station used to determine the location in the returned radar object. This parameter is only used when the location is not contained in the file, which occur in older NEXRAD message 1 files.

scans [list or None, optional] Read only specified scans from the file. None (the default) will read all scans.

linear_interp [bool, optional] True (the default) to perform linear interpolation between valid pairs of gates in low resolution rays in files mixed resolution rays. False will perform a nearest neighbor interpolation. This parameter is not used if the resolution of all rays in the file or requested sweeps is constant.

Returns

radar [Radar] Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[?], [?]

PYART.IO.NEXRAD_CDM

Functions for accessing Common Data Model (CDM) NEXRAD Level 2 files.

<code>read_nexrad_cdm(filename[, field_names, ...])</code>	Read a Common Data Model (CDM) NEXRAD Level 2 file.
<code>__scan_info(dvars)</code>	Return a list of information on the scans in the volume.
<code>__populate_scan_dic(scan_dic, time_var, ...)</code>	Populate a dictionary in the scan_info list.
<code>__get_moment_data(moment_var, index, ngates)</code>	Retrieve moment data for a given scan.

`pyart.io.nexrad_cdm.__get_moment_data(moment_var, index, ngates)`
Retrieve moment data for a given scan.

`pyart.io.nexrad_cdm.__populate_scan_dic(scan_dic, time_var, time_var_i, moment, dvars)`
Populate a dictionary in the scan_info list.

`pyart.io.nexrad_cdm.__scan_info(dvars)`
Return a list of information on the scans in the volume.

`pyart.io.nexrad_cdm.read_nexrad_cdm(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, station=None, **kwargs)`
Read a Common Data Model (CDM) NEXRAD Level 2 file.

Parameters

filename [str] File name or URL of a Common Data Model (CDM) NEXRAD Level 2 file. File of in this format can be created using the NetCDF Java Library tools [?]. A URL of a OPeNDAP file on the UCAR THREDDS Data Server [?] is also accepted the netCDF4 library has been compiled with OPeNDAP support.

field_names [dict, optional] Dictionary mapping NEXRAD moments to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names [bool, optional] True to use the NEXRAD field names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

station [str] Four letter ICAO name of the NEXRAD station used to determine the location in the returned radar object. This parameter is only used when the location is not contained in the file, which occur in older NEXRAD files. If the location is not provided in the file and this parameter is set to None the station name will be determined from the filename.

Returns

radar [Radar] Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[?], [?]

PYART.IO.NEXRAD_COMMON

Data and functions common to all types of NEXRAD files.

<code>get_nexrad_location(station)</code>	Return the latitude, longitude and altitude of a NEXRAD station.
---	--

`pyart.io.nexrad_common.get_nexrad_location(station)`

Return the latitude, longitude and altitude of a NEXRAD station.

Parameters

station [str] Four letter NEXRAD station ICAO name.

Returns

lat, lon, alt [float] Latitude (in degrees), longitude (in degrees), and altitude (in meters above mean sea level) of the NEXRAD station.

PYART.IO.NEXRAD_INTERPOLATE

Interpolation of NEXRAD moments from 1000 meter to 250 meter gate spacing.

`_fast_interpolate_scan()`

Interpolate a single NEXRAD moment scan from 1000 m to 250 m.

`pyart.io.nexrad_interpolate._fast_interpolate_scan()`

Interpolate a single NEXRAD moment scan from 1000 m to 250 m.

PYART.IO.NEXRAD_LEVEL2

<code>NEXRADLevel2File(filename)</code>	Class for accessing data in a NEXRAD (WSR-88D) Level II file.
<code>_decompress_records(file_handler)</code>	Decompressed the records from an BZ2 compressed Archive 2 file.
<code>_get_record_from_buf(buf, pos)</code>	Retrieve and unpack a NEXRAD record from a buffer.
<code>_get_msg31_data_block(buf, ptr)</code>	Unpack a msg_31 data block into a dictionary.
<code>_structure_size(structure)</code>	Find the size of a structure in bytes.
<code>_unpack_from_buf(buf, pos, structure)</code>	Unpack a structure from a buffer.
<code>_unpack_structure(string, structure)</code>	Unpack a structure from a string.

class `pyart.io.nexrad_level2.NEXRADLevel2File` (*filename*)

Bases: `object`

Class for accessing data in a NEXRAD (WSR-88D) Level II file.

NEXRAD Level II files [?], also know as NEXRAD Archive Level II or WSR-88D Archive level 2, are available from the NOAA National Climate Data Center [?] as well as on the UCAR THREDDS Data Server [?]. Files with uncompressed messages and compressed messages are supported. This class supports reading both “message 31” and “message 1” type files.

Parameters

filename [str] Filename of Archive II file to read.

References

[?], [?], [?]

Attributes

radial_records [list] Radial (1 or 31) messages in the file.

nscans [int] Number of scans in the file.

scan_msgs [list of arrays] Each element specifies the indices of the message in the radial_records attribute which belong to a given scan.

volume_header [dict] Volume header.

vcp [dict] VCP information dictionary.

_records [list] A list of all records (message) in the file.

_fh [file-like] File like object from which data is read.

_msg_type ['31' or '1:'] Type of radial messages in file.

Methods

<i>close</i> (self)	Close the file.
<i>get_azimuth_angles</i> (self[, scans])	Retrieve the azimuth angles of all rays in the requested scans.
<i>get_data</i> (self, moment, max_ngates[, scans, ...])	Retrieve moment data for a given set of scans.
<i>get_elevation_angles</i> (self[, scans])	Retrieve the elevation angles of all rays in the requested scans.
<i>get_nrays</i> (self, scan)	Return the number of rays in a given scan.
<i>get_nyquist_vel</i> (self[, scans])	Retrieve the Nyquist velocities of the requested scans.
<i>get_range</i> (self, scan_num, moment)	Return an array of gate ranges for a given scan and moment.
<i>get_target_angles</i> (self[, scans])	Retrieve the target elevation angle of the requested scans.
<i>get_times</i> (self[, scans])	Retrieve the times at which the rays were collected.
<i>get_unambiguous_range</i> (self[, scans])	Retrieve the unambiguous range of the requested scans.
<i>get_vcp_pattern</i> (self)	Return the numerical volume coverage pattern (VCP) or None if unknown.
<i>location</i> (self)	Find the location of the radar.
<i>scan_info</i> (self[, scans])	Return a list of dictionaries with scan information.

__class__

alias of `builtins.type`

__delattr__ (self, name, /)

Implement `delattr`(self, name).

__dict__ = `mappingproxy({'__module__': 'pyart.io.nexrad_level2', '__doc__': '\n Clas`

__dir__ (self, /)

Default `dir()` implementation.

__eq__ (self, value, /)

Return `self==value`.

__format__ (self, format_spec, /)

Default object formatter.

__ge__ (self, value, /)

Return `self>=value`.

__getattr__ (self, name, /)

Return `getattr`(self, name).

__gt__ (self, value, /)

Return `self>value`.

__hash__ (self, /)

Return `hash`(self).

__init__ (*self*, *filename*)
initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.io.nexrad_level2'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_msg_nums (*self*, *scans*)
Find the all message number for a list of scans.

_radial_array (*self*, *scans*, *key*)
Return an array of radial header elements for all rays in scans.

_radial_sub_array (*self*, *scans*, *key*)
Return an array of RAD or msg_header elements for all rays in scans.

close (*self*)
Close the file.

get_azimuth_angles (*self*, *scans*=None)
Retrieve the azimuth angles of all rays in the requested scans.

Parameters

scans [list or None] Scans (0 based) for which ray (radial) azimuth angles will be retrieved. None (the default) will return the angles for all scans in the volume.

Returns

angles [ndarray] Azimuth angles in degrees for all rays in the requested scans.

get_data (*self*, *moment*, *max_ngates*, *scans=None*, *raw_data=False*)

Retrieve moment data for a given set of scans.

Masked points indicate that the data was not collected, below threshold or is range folded.

Parameters

moment ['REF', 'VEL', 'SW', 'ZDR', 'PHI', or 'RHO'] Moment for which to retrieve data.

max_ngates [int] Maximum number of gates (bins) in any ray. requested.

raw_data [bool] True to return the raw data, False to perform masking as well as applying the appropriate scale and offset to the data. When *raw_data* is True values of 1 in the data likely indicate that the gate was not present in the sweep, in some cases it will indicate range folded data.

scans [list or None.] Scans to retrieve data from (0 based). None (the default) will get the data for all scans in the volume.

Returns

data [ndarray]

get_elevation_angles (*self*, *scans=None*)

Retrieve the elevation angles of all rays in the requested scans.

Parameters

scans [list or None] Scans (0 based) for which ray (radial) azimuth angles will be retrieved. None (the default) will return the angles for all scans in the volume.

Returns

angles [ndarray] Elevation angles in degrees for all rays in the requested scans.

get_nrays (*self*, *scan*)

Return the number of rays in a given scan.

Parameters

scan [int] Scan of interest (0 based).

Returns

nrays [int] Number of rays (radials) in the scan.

get_nyquist_vel (*self*, *scans=None*)

Retrieve the Nyquist velocities of the requested scans.

Parameters

scans [list or None] Scans (0 based) for which the Nyquist velocities will be retrieved. None (the default) will return the velocities for all scans in the volume.

Returns

velocities [ndarray] Nyquist velocities (in m/s) for the requested scans.

get_range (*self*, *scan_num*, *moment*)

Return an array of gate ranges for a given scan and moment.

Parameters

scan_num [int] Scan number (0 based).

moment ['REF', 'VEL', 'SW', 'ZDR', 'PHI', or 'RHO'] Moment of interest.

Returns

range [ndarray] Range in meters from the antenna to the center of gate (bin).

get_target_angles (*self*, *scans=None*)

Retrieve the target elevation angle of the requested scans.

Parameters

scans [list or None] Scans (0 based) for which the target elevation angles will be retrieved.
None (the default) will return the angles for all scans in the volume.

Returns

angles [ndarray] Target elevation angles in degrees for the requested scans.

get_times (*self*, *scans=None*)

Retrieve the times at which the rays were collected.

Parameters

scans [list or None] Scans (0-based) to retrieve ray (radial) collection times from. None (the default) will return the times for all scans in the volume.

Returns

time_start [Datetime] Initial time.

time [ndarray] Offset in seconds from the initial time at which the rays in the requested scans were collected.

get_unambiguous_range (*self*, *scans=None*)

Retrieve the unambiguous range of the requested scans.

Parameters

scans [list or None] Scans (0 based) for which the unambiguous range will be retrieved.
None (the default) will return the range for all scans in the volume.

Returns

unambiguous_range [ndarray] Unambiguous range (in meters) for the requested scans.

get_vcp_pattern (*self*)

Return the numerical volume coverage pattern (VCP) or None if unknown.

location (*self*)

Find the location of the radar.

Returns all zeros if location is not available.

Returns

latitude [float] Latitude of the radar in degrees.

longitude [float] Longitude of the radar in degrees.

height [int] Height of radar and feedhorn in meters above mean sea level.

scan_info (*self*, *scans=None*)

Return a list of dictionaries with scan information.

Parameters

scans [list of None] Scans (0 based) for which ray (radial) azimuth angles will be retrieved. None (the default) will return the angles for all scans in the volume.

Returns

scan_info [list, optional] A list of the scan performed with a dictionary with keys 'moments', 'ngates', 'nrays', 'first_gate' and 'gate_spacing' for each scan. The 'moments', 'ngates', 'first_gate', and 'gate_spacing' keys are lists of the NEXRAD moments and gate information for that moment collected during the specific scan. The 'nrays' key provides the number of radials collected in the given scan.

`pyart.io.nexrad_level2._decompress_records` (*file_handler*)

Decompressed the records from an BZ2 compressed Archive 2 file.

`pyart.io.nexrad_level2._get_msg1_from_buf` (*buf*, *pos*, *dic*)

Retrieve and unpack a MSG1 record from a buffer.

`pyart.io.nexrad_level2._get_msg29_from_buf` (*pos*, *dic*)

`pyart.io.nexrad_level2._get_msg31_data_block` (*buf*, *ptr*)

Unpack a msg_31 data block into a dictionary.

`pyart.io.nexrad_level2._get_msg31_from_buf` (*buf*, *pos*, *dic*)

Retrieve and unpack a MSG31 record from a buffer.

`pyart.io.nexrad_level2._get_msg5_from_buf` (*buf*, *pos*, *dic*)

Retrieve and unpack a MSG1 record from a buffer.

`pyart.io.nexrad_level2._get_record_from_buf` (*buf*, *pos*)

Retrieve and unpack a NEXRAD record from a buffer.

`pyart.io.nexrad_level2._structure_size` (*structure*)

Find the size of a structure in bytes.

`pyart.io.nexrad_level2._unpack_from_buf` (*buf*, *pos*, *structure*)

Unpack a structure from a buffer.

`pyart.io.nexrad_level2._unpack_structure` (*string*, *structure*)

Unpack a structure from a string.

PYART.IO.NEXRAD_LEVEL3

Class for reading data from NEXRAD Level 3 files.

<i>NEXRADLevel3File(filename)</i>	A Class for accessing data in NEXRAD Level III (3) files.
-----------------------------------	---

<i>nexrad_level3_message_code(filename)</i>	Return the message (product) code for a NEXRAD Level 3 file.
---	--

<i>_datetime_from_mdate_mtime(mdate, mtime)</i>	Returns a datetime for a given message date and time.
---	---

<i>_structure_size(structure)</i>	Find the size of a structure in bytes.
-----------------------------------	--

<i>_unpack_from_buf(buf, pos, structure)</i>	Unpack a structure from a buffer.
--	-----------------------------------

<i>_unpack_structure(string, structure)</i>	Unpack a structure from a string
---	----------------------------------

<i>_int16_to_float16(val)</i>	Convert a 16 bit interger into a 16 bit float.
-------------------------------	--

class pyart.io.nexrad_level3.NEXRADLevel3File(*filename*)

Bases: `object`

A Class for accessing data in NEXRAD Level III (3) files.

Attributes

text_header [dic] File textual header.

msg_header [dic] Message header.

prod_descr [dic] Product description.

symbology_header [dict] Symbology header.

packet_header [dict] Radial data array packet header.

radial_headers [list of dicts] List of radials headers.

raw_data [array] Raw unscaled, unmasked data.

data [array] Scaled, masked radial data.

_fh [file-like] File like object from which data is read.

Methods

<i>close(self)</i>	Close the file.
--------------------	-----------------

<i>get_azimuth(self)</i>	Return an array of starting azimuth angles in degrees.
--------------------------	--

Continued on next page

Table 3 – continued from previous page

<code>get_data(self)</code>	Return an masked array containing the field data.
<code>get_elevation(self)</code>	Return the sweep elevation angle in degrees.
<code>get_location(self)</code>	Return the latitude, longitude and height of the radar.
<code>get_range(self)</code>	Return an array of gate range spacing in meters.
<code>get_volume_start_datetime(self)</code>	Return a datetime of the start of the radar volume.

```
__class__
    alias of builtins.type

__delattr__ (self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.io.nexrad_level3', '__doc__': '\n A Cl

__dir__ (self, /)
    Default dir() implementation.

__eq__ (self, value, /)
    Return self==value.

__format__ (self, format_spec, /)
    Default object formatter.

__ge__ (self, value, /)
    Return self>=value.

__getattr__ (self, name, /)
    Return getattr(self, name).

__gt__ (self, value, /)
    Return self>value.

__hash__ (self, /)
    Return hash(self).

__init__ (self, filename)
    initialize the object.

__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)
    Return self<=value.

__lt__ (self, value, /)
    Return self<value.

__module__ = 'pyart.io.nexrad_level3'

__ne__ (self, value, /)
    Return self!=value.

__new__ (*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)
    Helper for pickle.

__reduce_ex__ (self, protocol, /)
    Helper for pickle.
```


__repr__ (*self*, /)
Return repr(*self*).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(*self*, *name*, *value*).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(*self*).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_get_data_8_or_16_levels (*self*)
Return a masked array for products with 8 or 16 data levels.

_get_data_msg_134 (*self*)
Return a masked array for product with message code 134.

_read_symbology_block (*self*, *buf2*)
Read symbology block.

close (*self*)
Close the file.

get_azimuth (*self*)
Return an array of starting azimuth angles in degrees.

get_data (*self*)
Return an masked array containing the field data.

get_elevation (*self*)
Return the sweep elevation angle in degrees.

get_location (*self*)
Return the latitude, longitude and height of the radar.

get_range (*self*)
Return an array of gate range spacing in meters.

get_volume_start_datetime (*self*)
Return a datetime of the start of the radar volume.

pyart.io.nexrad_level3.**_datetime_from_mdate_mtime** (*mdate*, *mtime*)
Returns a datetime for a given message date and time.

pyart.io.nexrad_level3.**_int16_to_float16** (*val*)
Convert a 16 bit interger into a 16 bit float.

pyart.io.nexrad_level3.**_structure_size** (*structure*)
Find the size of a structure in bytes.

pyart.io.nexrad_level3.**_unpack_from_buf** (*buf*, *pos*, *structure*)
Unpack a structure from a buffer.

`pyart.io.nexrad_level3._unpack_structure` (*string, structure*)
Unpack a structure from a string

`pyart.io.nexrad_level3.nexrad_level3_message_code` (*filename*)
Return the message (product) code for a NEXRAD Level 3 file.

PYART.IO.RSL

Python wrapper around the RSL library.

<code>_RslVolumeDataExtractor(rslfile, volume_num, ...)</code>	vol-	Class facilitating on demand extraction of data from a RSL file.
--	------	--

<code>read_rsl(filename[, field_names, ...])</code>	Read a file supported by RSL.
<code>VOLUMENUM2RSLNAME</code>	
<code>RSLNAME2VOLUMENUM</code>	

class `pyart.io.rsl._RslVolumeDataExtractor` (*rslfile*, *volume_num*, *fillvalue*)

Bases: `object`

Class facilitating on demand extraction of data from a RSL file.

Parameters

rslfile [`RslFile`] Open `RslFile` object to extract data from.

volume_num [`int`] Volume number of data to be extracted.

fillvalue [`int`] Value used to fill masked values in the returned array.

Methods

<code>__call__(self)</code>	Return an array containing data from the referenced volume.
-----------------------------	---

`__call__(self)`
Return an array containing data from the referenced volume.

`__class__`
alias of `builtins.type`

`__delattr__(self, name, /)`
Implement `delattr(self, name)`.

`__dict__ = mappingproxy({'__module__': 'pyart.io.rsl', '__doc__': '\n Class facilitating on demand extraction of data from a RSL file.'})`

`__dir__(self, /)`
Default `dir()` implementation.

`__eq__(self, value, /)`
Return `self==value`.

`__format__` (*self, format_spec, /*)
Default object formatter.

`__ge__` (*self, value, /*)
Return self>=value.

`__getattr__` (*self, name, /*)
Return getattr(self, name).

`__gt__` (*self, value, /*)
Return self>value.

`__hash__` (*self, /*)
Return hash(self).

`__init__` (*self, rslfile, volume_num, fillvalue*)
initialize the object.

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self, value, /*)
Return self<=value.

`__lt__` (*self, value, /*)
Return self<value.

`__module__` = `'pyart.io.rsl'`

`__ne__` (*self, value, /*)
Return self!=value.

`__new__` (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

`__reduce__` (*self, /*)
Helper for pickle.

`__reduce_ex__` (*self, protocol, /*)
Helper for pickle.

`__repr__` (*self, /*)
Return repr(self).

`__setattr__` (*self, name, value, /*)
Implement setattr(self, name, value).

`__sizeof__` (*self, /*)
Size of object in memory, in bytes.

`__str__` (*self, /*)
Return str(self).

`__subclasshook__` ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`
list of weak references to the object (if defined)

```
pyart.io.rsl._dms_to_d(dms)
```

Degrees, minutes, seconds to degrees

```
pyart.io.rsl.read_rsl(filename, field_names=None, additional_metadata=None,
                     file_field_names=False, exclude_fields=None, delay_field_loading=False,
                     include_fields=None, radar_format=None, callid=None,
                     skip_range_check=False)
```

Read a file supported by RSL.

Parameters

filename [str or RSL_radar] Name of file whose format is supported by RSL.

field_names [dict, optional] Dictionary mapping RSL data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the RSL data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

radar_format [str or None] Format of the radar file. Must be 'wsr88d' or None.

callid [str or None] Four letter NEXRAD radar Call ID, only used when radar_format is 'wsr88d'.

skip_range_check [bool, optional] True to skip check for uniform range bin location, the reported range locations will only be verified true for the first ray. False will perform the check and raise a IOError when the locations of the gates change between rays.

Returns

radar [Radar] Radar object.

PYART.IO.SIGMET

Reading and writing of Sigmet (raw format) files

<code>read_sigmet(filename[, field_names, ...])</code>	Read a Sigmet (IRIS) product file.
<code>ynds_time_to_datetime(ynds)</code>	Return a datetime object from a Sigmet ynds_time dictionary.
<code>_is_time_ordered_by_reversal(data, metadata, ...)</code>	Returns if volume can be time ordered by reversing some or all sweeps.
<code>_is_time_ordered_by_roll(data, metadata, ...)</code>	Returns if volume can be time ordered by rolling some or all sweeps.
<code>_is_time_ordered_by_reverse_roll(data, ...)</code>	Returns if volume can be time ordered by reversing and rolling some or all sweeps.
<code>_time_order_data_and_metadata_roll(data, ...)</code>	Put Sigmet data and metadata in time increasing order using a roll operation.
<code>_time_order_data_and_metadata_reverse(data, ...)</code>	Put Sigmet data and metadata in time increasing order by reverse sweep in time reversed order.
<code>_time_order_data_and_metadata_full(data, ...)</code>	Put Sigmet data and metadata in time increasing order by sorting the times.

`pyart.io.sigmet._is_time_ordered_by_reversal (data, metadata, rays_per_sweep)`
Returns if volume can be time ordered by reversing some or all sweeps. True if the volume can be time ordered, False if not.

`pyart.io.sigmet._is_time_ordered_by_reverse_roll (data, metadata, rays_per_sweep)`
Returns if volume can be time ordered by reversing and rolling some or all sweeps. True if the volume can be time ordered, False if not.

`pyart.io.sigmet._is_time_ordered_by_roll (data, metadata, rays_per_sweep)`
Returns if volume can be time ordered by rolling some or all sweeps. True if the volume can be time ordered, False if not.

`pyart.io.sigmet._time_order_data_and_metadata_full (data, metadata, rays_per_sweep)`
Put Sigmet data and metadata in time increasing order by sorting the times.

`pyart.io.sigmet._time_order_data_and_metadata_reverse (data, metadata, rays_per_sweep)`
Put Sigmet data and metadata in time increasing order by reverse sweep in time reversed order.

`pyart.io.sigmet._time_order_data_and_metadata_roll (data, metadata, rays_per_sweep)`
Put Sigmet data and metadata in time increasing order using a roll operation.

```
pyart.io.sigmet.read_sigmet(filename, field_names=None, additional_metadata=None,
                             file_field_names=False, exclude_fields=None, include_fields=None,
                             time_ordered='none', full_xhdr=None, noaa_hh_hdr=None, debug=False,
                             ignore_xhdr=False, ignore_sweep_start_ms=None,
                             **kwargs)
```

Read a Sigmet (IRIS) product file.

Parameters

filename [str] Name of Sigmet (IRIS) product file to read or file-like object pointing to the beginning of such a file.

field_names [dict, optional] Dictionary mapping Sigmet data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names [bool, optional] True to use the Sigmet data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

time_ordered ['none', 'sequential', 'full', ..., optional] Parameter controlling if and how the rays are re-ordered by time. The default, 'none' keeps the rays ordered in the same manner as they appear in the Sigmet file. 'sequential' will determine and apply an operation which maintains a sequential ray order in elevation or azimuth yet orders the rays according to time. If no operation can be found to accomplish this a warning is issued and the rays are returned in their original order. 'roll', 'reverse', and 'reverse_and_roll' will apply that operation to the rays in order to place them in time order, direct use of these is not recommended. 'full' will order the rays in strictly time increasing order, but the rays will likely become non-sequential, this option is not recommended unless strict time increasing order is required.

full_xhdr [bool or None] Flag to read in all extended headers for possible decoding. None will determine if extended headers should be read in automatically by examining the extended header type.

noaa_hh_hdr [bool or None] Flag indicating if the extended header should be decoded as those used by the NOAA Hurricane Hunters aircraft radars. None will determine if the extended header is of this type automatically by examining the header. The *full_xhdr* parameter is set to True when this parameter is True.

ignore_xhdr [bool, optional] True to ignore all data in the extended headers if they exist. False, the default, extracts milliseconds precision times and other parameters from the extended headers if they exist in the file.

ignore_sweep_start_ms [bool or None, optional] True to ignore the millisecond parameter in the start time for each sweep, False will use this parameter when determining the timing of

each ray. None, the default, will ignore the millisecond sweep start timing only when the file does not contain extended headers or when the extended header has been explicitly ignored using the *ignore_xhdr* parameter. The TRMM RSL library ignores these times so setting this parameter to True is required to match the times determined when reading Sigmet files with `pyart.io.read_rsl()`. When there are not extended headers ignoring the millisecond sweep times provides time data which is always prior to the actual collection time with an error from 0 to 2 seconds.

debug [bool, optional] Print debug information during read.

Returns

radar [Radar] Radar object.

`pyart.io.sigmet.ymds_time_to_datetime(ymds)`

Return a datetime object from a Sigmet ymds_time dictionary.

Reading of Universal format (UF) files.

<code>read_uf(filename[, field_names, ...])</code>	Read a UF File.
<code>_get_scan_type(ufray)</code>	Return the scan type of a UF ray.
<code>_get_instrument_parameters(ufile, filemeta- data)</code>	Return a dictionary containing instrument parameters.

`pyart.io.uf._get_instrument_parameters(ufile, filemetadata)`
Return a dictionary containing instrument parameters.

`pyart.io.uf._get_scan_type(ufray)`
Return the scan type of a UF ray.

`pyart.io.uf.read_uf(filename, field_names=None, additional_metadata=None,
file_field_names=False, exclude_fields=None, include_fields=None, de-
lay_field_loading=False, **kwargs)`
Read a UF File.

Parameters

filename [str or file-like] Name of Universal format file to read data from.

field_names [dict, optional] Dictionary mapping UF data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any addition metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to re-name fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

delay_field_loading [bool] This option is not implemented in the function but included for compatibility.

Returns

radar [Radar] Radar object.

PYART.IO.UFFILE

Low level class for reading Universal Format (UF) files.

<i>UFFile</i> (filename)	A class for reading data from Universal Format (UF) files.
<i>UFRay</i> (record)	A class for reading data from a single ray (record) in a UF file.
<i>_structure_size</i> (structure)	Find the size of a structure in bytes.
<i>_unpack_from_buf</i> (buf, pos, structure)	Unpack a structure from a buffer.
<i>_unpack_structure</i> (string, structure)	Unpack a structure from a string

class pyart.io.uffile.**UFFile** (filename)

Bases: `object`

A class for reading data from Universal Format (UF) files.

Parameters

filename [str or file-like] Filename or file-like object containing data in Universal format (UF).

Attributes

rays [list of UFRay objects] List of rays within the UF file.

nrays, nsweeps [int] Number of rays and sweep in the file.

ray_sweep_numbers [array] Sweep number of each ray in the file.

first_ray_in_sweep, last_ray_in_sweep [array] Indices of the first and last ray in each sweep.

Methods

<i>close</i> (self)	Close the file.
<i>get_azimuths</i> (self)	Return an array of azimuth angles for each ray in degrees.
<i>get_datetimes</i> (self)	Return a list of datetimes for each ray.
<i>get_elevations</i> (self)	Return an array of elevation angles for each ray in degrees.
<i>get_field_data</i> (self, field_number)	Return a 2D array of scale/masked field data for the volume.

Continued on next page

Table 3 – continued from previous page

<code>get_nyquists(self)</code>	Return an array of nyquist velocities for each ray in m/s.
<code>get_prts(self)</code>	Return an array of prts for each ray in microseconds.
<code>get_pulse_widths(self)</code>	Return an array of pulse widths for each ray in meters.
<code>get_sweep_fixed_angles(self)</code>	Return an array of fixed angles for each sweep in degrees.
<code>get_sweep_polarizations(self)</code>	Return an array of polarization modes for each sweep.
<code>get_sweep_rates(self)</code>	Return an array of sweep rates for each ray in degrees/sec.

```
__class__
    alias of builtins.type
__delattr__ (self, name, /)
    Implement delattr(self, name).
__dict__ = mappingproxy({'__module__': 'pyart.io.uffile', '__doc__': '\n A class for
__dir__ (self, /)
    Default dir() implementation.
__eq__ (self, value, /)
    Return self==value.
__format__ (self, format_spec, /)
    Default object formatter.
__ge__ (self, value, /)
    Return self>=value.
__getattr__ (self, name, /)
    Return getattr(self, name).
__gt__ (self, value, /)
    Return self>value.
__hash__ (self, /)
    Return hash(self).
__init__ (self, filename)
    initialize.
__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.
__le__ (self, value, /)
    Return self<=value.
__lt__ (self, value, /)
    Return self<value.
__module__ = 'pyart.io.uffile'
__ne__ (self, value, /)
    Return self!=value.
```

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)
Helper for pickle.

__reduce_ex__ (self, protocol, /)
Helper for pickle.

__repr__ (self, /)
Return repr(self).

__setattr__ (self, name, value, /)
Implement setattr(self, name, value).

__sizeof__ (self, /)
Size of object in memory, in bytes.

__str__ (self, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_get_ray_sweep_numbers (self)
Return an array of the sweep_number stored in each ray.

_get_sweep_limits (self)
Return arrays of indices of first and last ray in each sweep.

close (self)
Close the file.

get_azimuths (self)
Return an array of azimuth angles for each ray in degrees.

get_datetimes (self)
Return a list of datetimes for each ray.

get_elevations (self)
Return an array of elevation angles for each ray in degrees.

get_field_data (self, field_number)
Return a 2D array of scale/masked field data for the volume.

get_nyquists (self)
Return an array of nyquist velocities for each ray in m/s.

Returns None if nyquist velocities cannot be determined for all rays.

get_prts (self)
Return an array of prts for each ray in microseconds.

get_pulse_widths (self)
Return an array of pulse widths for each ray in meters.

get_sweep_fixed_angles (*self*)

Return an array of fixed angles for each sweep in degrees.

get_sweep_polarizations (*self*)

Return an array of polarization modes for each sweep.

get_sweep_rates (*self*)

Return an array of sweep rates for each ray in degrees/sec.

class `pyart.io.uffile.UFRay` (*record*)

Bases: `object`

A class for reading data from a single ray (record) in a UF file.

Parameters

record [str] Byte string containing the binary data for a UF ray.

Attributes

mandatory_header [dic] Mandatory header.

optional_header [dic or None] Optional header or None if no optional header exists in the record.

data_header [dic] Data header.

field_positions [list] List of dictionaries containing the data type and data position.

field_headers [list] List of field header dictionaries for all fields in the ray.

field_raw_data [list] List containing array of raw field data for each field in the ray.

_buf [str] Bytes which make up the record.

Methods

<code>get_datetime(self)</code>	Return a datetime object for the ray.
<code>get_field_data(self, field_number)</code>	Return array of raw data for a particular field in the ray.
<code>get_location(self)</code>	Return the latitude, longitude and height of the ray.

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.io.uffile', '__doc__': '\n A class for`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self*, *value*, /)

Return `self>=value`.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, record*)
Initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyart.io.uffile'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (**args, **kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

get_datetime (*self*)
Return a datetime object for the ray.

get_field_data (*self, field_number*)
Return array of raw data for a particular field in the ray.

Field header is appended to the list in the `field_headers` attribute.

get_location (*self*)

Return the latitude, longitude and height of the ray.

`pyart.io.uffile._structure_size` (*structure*)

Find the size of a structure in bytes.

`pyart.io.uffile._unpack_from_buf` (*buf, pos, structure*)

Unpack a structure from a buffer.

`pyart.io.uffile._unpack_structure` (*string, structure*)

Unpack a structure from a string

PYART.IO.UF_WRITE

Functions for writing UF files.

<i>UFRayCreator</i> (radar, field_mapping, ...[, ...])	A class for generating UF rays for writing UF file.
<i>write_uf</i> (filename, radar[, uf_field_names, ...])	Write a Radar object to a UF file.
<i>_d_to_dms</i> (in_deg)	Degrees to degree, minutes, seconds.
<i>_pack_structure</i> (dic, structure)	Pack a structure from a dictionary.

class pyart.io.uf_write.**UFRayCreator** (radar, field_mapping, field_write_order, volume_start=None, templates_extra=None)

Bases: `object`

A class for generating UF rays for writing UF file.

Parameters

radar [Radar] Radar used to create rays.

field_write_order [list] Order in which radar fields should be written out in the UF file. None, the default, will determine a valid order automatically.

volume_start [datetime, optional] Start of volume used to set UF volume fields.

templates_extra [dict of dict, optional] Advanced usage parameter for setting UF structure templates. Elements defined in dictionaries with keys 'mandatory_header', 'optional_header', and 'field_header' will be added to the appropriate structure template.

Methods

<i>make_data_array</i> (self, field, ray_num[, scale])	Return an array of UF field data.
<i>make_data_header</i> (self)	Return a byte string representing a UF data header.
<i>make_field_header</i> (self, data_offset, ...)	Return a byte string representing a field header.
<i>make_field_position</i> (self)	Return a byte string representing the UF field positions.
<i>make_field_position_list</i> (self)	Return a list of field position dictionaries.
<i>make_fsi_vel</i> (self, ray_num, scale)	Return a byte string representing a UF FSI velocity structure.
<i>make_mandatory_header</i> (self, ray_num)	Return a byte string representing a UF mandatory header.

Continued on next page

Table 3 – continued from previous page

<code>make_optional_header(self)</code>	Return a byte string representing a UF optional header.
<code>make_ray(self, ray_num)</code>	Return a byte string representing a complete UF ray.

```
__class__
    alias of builtins.type

__delattr__(self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.io.uf_write', '__doc__': "\n A class f

__dir__(self, /)
    Default dir() implementation.

__eq__(self, value, /)
    Return self==value.

__format__(self, format_spec, /)
    Default object formatter.

__ge__(self, value, /)
    Return self>=value.

__getattr__(self, name, /)
    Return getattr(self, name).

__gt__(self, value, /)
    Return self>value.

__hash__(self, /)
    Return hash(self).

__init__(self, radar, field_mapping, field_write_order, volume_start=None, templates_extra=None)
    Initialize the object.

__init_subclass__()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__(self, value, /)
    Return self<=value.

__lt__(self, value, /)
    Return self<value.

__module__ = 'pyart.io.uf_write'

__ne__(self, value, /)
    Return self!=value.

__new__(*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.

__reduce__(self, /)
    Helper for pickle.

__reduce_ex__(self, protocol, /)
    Helper for pickle.

__repr__(self, /)
    Return repr(self).
```

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

static _calc_ray_num_to_sweep_num (*radar*)
Return an array mapping ray number to sweep numbers.

static _calc_record_length (*radar, field_mapping, field_write_order*)
Return the record length in 2-byte words.

_parse_custom_templates (*self, templates_extra*)
Set additional template parameter using provided dictionary.

_set_field_header (*self*)
Populate the field header template with radar parameters.

_set_mandatory_header_location (*self*)
Populate the mandatory header template with the location.

_set_optional_header_time (*self, volume_start*)
Populate the optional header template with the volume start.

make_data_array (*self, field, ray_num, scale=100.0*)
Return an array of UF field data.

make_data_header (*self*)
Return a byte string representing a UF data header.

make_field_header (*self, data_offset, ray_num, scale_factor*)
Return a byte string representing a field header.

make_field_position (*self*)
Return a byte string representing the UF field positions.

make_field_position_list (*self*)
Return a list of field position dictionaries.

make_fsi_vel (*self, ray_num, scale*)
Return a byte string representing a UF FSI velocity structure.

make_mandatory_header (*self, ray_num*)
Return a byte string representing a UF mandatory header.

make_optional_header (*self*)
Return a byte string representing a UF optional header.

make_ray (*self, ray_num*)
Return a byte string representing a complete UF ray.

`pyart.io.uf_write._d_to_dms` (*in_deg*)

Degrees to degree, minutes, seconds.

`pyart.io.uf_write._find_field_mapping` (*radar*, *uf_field_names*, *radar_field_names*, *exclude_fields*)

Return a dictionary mapping radar fields to UF data types.

`pyart.io.uf_write._pack_structure` (*dic*, *structure*)

Pack a structure from a dictionary.

`pyart.io.uf_write.write UF` (*filename*, *radar*, *uf_field_names=None*, *radar_field_names=False*, *exclude_fields=None*, *field_write_order=None*, *volume_start=None*, *templates_extra=None*)

Write a Radar object to a UF file.

Create a UF file containing data from the provided radar instance. The UF file will contain instrument parameters from the following dictionaries if they contained in `radar.instrument_parameters`:

- `radar_beam_width_h`
- `radar_beam_width_v`
- `radar_receiver_bandwidth`
- `frequency`
- `pulse_width`
- `prt`
- `polarization_mode`
- `nyquist_velocity`

If any of these parameter are not present a default or sentinel value will be written in the UF file in the place of the parameter. This is also true for the data in the `scan_rate` attribute.

Radar fields will be scaled and rounded to integer values when writing to UF files. The scale factor for each field can be specified in the `_UF_scale_factor` key for each field dictionary. If not specified the default scaling (100) will be used.

Parameters

filename [str or file-like object.] Filename of UF file to create. If a file-like object is specified data will be written using the write method.

radar [Radar] Radar object from which to create UF file.

uf_field_names [dict or None, optional] Mapping between radar fields and two character UF data type names. Field names mapped to None or with no mapping will be excluded from writing. If None, the default mappings for UF files will be used.

radar_field_names [bool, optional] True to use the radar field names as the field names of the UF fields. False to use the `uf_field_names` mapping to generate UF field names. The `exclude_fields` argument can still be used to exclude fields from the UF file when this parameter is True. When reading a UF file using `file_field_names=True` set this parameter to True to write a UF file with the same field names.

exclude_fields [list or None, optional] List of radar fields to exclude from writing.

field_write_order [list or None, optional] Order in which radar fields should be written out in the UF file. None, the default, will determine a valid order automatically.

volume_start [datetime, optional] Start of volume used to set UF volume structure elements.

templates_extra [dict of dict or None] Advanced usage parameter for setting UF structure templates. Elements defined in dictionaries with keys 'mandatory_header', 'optional_header', and 'field_header' will be used to build the structure template.

PYART.IO.WRITE_GRID_GEOTIFF

Write a Py-ART Grid object to a GeoTIFF file.

<code>write_grid_geotiff(grid, filename, field[, ...])</code>	Write a Py-ART Grid object to a GeoTIFF file.
<code>_get_rgb_values(data, vmin, vmax, ...)</code>	Get RGB values for later output to GeoTIFF, given a 2D data field, display min/max and color table info.
<code>_create_sld(cmap, vmin, vmax, filename[, ...])</code>	Develop a Style Layer Descriptor file given a color table and user-specified min/max files.

`pyart.io.output_to_geotiff._create_sld(cmap, vmin, vmax, filename, color_levels=None)`

Develop a Style Layer Descriptor file given a color table and user-specified min/max files. Output color info to that file. Only called if `sld` is `True` in `write_grid_geotiff`.

Parameters

cmap [str or matplotlib.colors.Colormap object, optional] Colormap to use for RGB output or SLD file.

vmin [int or float] Minimum value to color for RGB output or SLD file.

vmax [int or float] Maximum value to color for RGB output or SLD file.

filename [str] Template for SLD filename. The suffix (presumably `.tif` or `.tiff`) is removed and replaced with `.sld`. Thus, if provided a filename `radar_reflectivity.tif`, the output SLD file will be called `radar_reflectivity.sld`.

Other Parameters

color_levels [int or None, optional] Number of color levels in `cmap`. Useful for categorical colormaps with steps < 255 (e.g., hydrometeor ID).

`pyart.io.output_to_geotiff._get_rgb_values(data, vmin, vmax, color_levels, cmap)`

Get RGB values for later output to GeoTIFF, given a 2D data field, display min/max and color table info. Missing data get `numpy.nan`. Only called if `rgb` is `True` in `write_grid_geotiff`.

Parameters

data [numpy.ndarray object, dtype int or float] Two-dimensional data array.

vmin [int or float] Minimum value to color for RGB output or SLD file.

vmax [int or float] Maximum value to color for RGB output or SLD file.

color_levels [int] Number of color levels in `cmap`. Useful for categorical colormaps with steps < 255 (e.g., hydrometeor ID).

cmap [str or matplotlib.colors.Colormap object, optional] Colormap to use for RGB output or SLD file.

Returns

rarr [numpy.ndarray object, dtype int] Red channel indices (range = 0-255).

barr [numpy.ndarray object, dtype int] Blue channel indices (range = 0-255).

garr [numpy.ndarray object, dtype int] Green channel indices (range = 0-255).

```
pyart.io.output_to_geotiff.write_grid_geotiff(grid, filename, field, rgb=False,
                                              level=None, cmap='viridis', vmin=0,
                                              vmax=75, color_levels=None,
                                              warp=False, sld=False,
                                              use_doublequotes=False)
```

Write a Py-ART Grid object to a GeoTIFF file.

The GeoTIFF can be the standard Azimuthal Equidistant projection used in Py-ART, or a lat/lon projection on a WGS84 sphere. The latter is typically more usable in web mapping applications. The GeoTIFF can contain a single float-point raster band, or three RGB byte raster bands. The former will require an SLD file for colorful display using standard GIS or web mapping software, while the latter will show colors “out-of-the-box” but lack actual data values. The function also can output an SLD file based on the user-specified inputs. User can specify the 2D vertical level to be output. If this is not specified, a 2D composite is created. User also can specify the field to output.

This function requires GDAL Python libraries to be installed. These are available via conda; e.g., ‘conda install gdal’

Parameters

grid [pyart.core.Grid object] Grid object to write to file.

filename [str] Filename for the GeoTIFF.

field [str] Field name to output to file.

Other Parameters

rgb [bool, optional] True - Output 3-band RGB GeoTIFF

False - Output single-channel, float-valued GeoTIFF. For display, likely will need an SLD file to provide a color table.

level [int or None, optional] Index for z-axis plane to output. None gives composite values (i.e., max in each vertical column).

cmap [str or matplotlib.colors.Colormap object, optional] Colormap to use for RGB output or SLD file.

vmin [int or float, optional] Minimum value to color for RGB output or SLD file.

vmax [int or float, optional] Maximum value to color for RGB output or SLD file.

color_levels [int or None, optional] Number of color levels in cmap. Useful for categorical colormaps with steps << 255 (e.g., hydrometeor ID).

warp [bool, optional]

True - Use gdalwarp (called from command line using os.system) to warp to a lat/lon WGS84 grid.

False - No warping will be performed. Output will be Az. Equidistant.

sld [bool, optional]

True - Create a Style Layer Descriptor file (SLD) mapped to vmin/vmax and **cmap**. File is named same as output TIFF, except for .sld extension.

False - Don't do this.

use_doublequotes [bool, optional]

True - Use double quotes in the gdalwarp call (requires warp=True), which may help if that command is producing an error like: 'Translating source or target SRS failed'.

False - Use single quotes instead.

PYART.IO._RSL_INTERFACE

Cython wrapper around the NASA TRMM RSL library.

<i>copy_volume</i> (volume)	Return a copy of a <code>_RslVolume</code> object.
<i>create_volume</i> (arr, rays_per_sweep[, vol_num])	Create a <code>_RslVolume</code> object from a 2D float32 array.
<i>_label_volume</i> (volume, radar)	Add labels for dealiasing to a <code>_RslVolume</code> object from a radar object.
<hr/>	
<i>RslFile</i> (filename)	A object for accessing Radar data and parameter using the RSL library.
<i>_RslVolume</i>	A object for accessing RSL Volume data and header information.
<i>_RslSweep</i>	A object for accessing RSL Sweep data and header information.
<i>_RslRay</i>	A object for accessing RSL Ray data and header information

class `pyart.io._rsl_interface.RslFile` (*filename*)

Bases: `object`

A object for accessing Radar data and parameter using the RSL library.

Parameters

filename [str] Radar file to read.

Attributes

month [int] Date, month (1-12).

day [int] Date, day (1-31).

year [int] Date, year (eg. 1993).

hour [int] Time, hour (0-23).

minute [int] Time, minute (0-59).

sec [float] Time, second + fractions of second.

nvolumes [int] Number of volume slots in the file.

number [int] Arbitrary number for this radar site.

latd, latm, lats [int] Latitude degrees, minutes and seconds for the site.

lond, lonm, lons [int] Longitude degrees, minutes and seconds for the site.

height [int] Height of site in meters above sea level.

spulse [int] Length of short pulse in ns.

lpulse [int] Length of long pulse in ns.

scan_mode [int] Scan mode, 0 for PPI, 1 for RHI.

vcp [int] Volume coverage pattern, WSR-88D only.

Methods

<i>available_moments()</i>	Return a list of available volume moments.
<i>get_radar_header()</i>	Return a dictionary of radar header parameters.
<i>get_volume(volume_number)</i>	Return a <code>_RslVolume</code> for a given volume number.
<i>get_volume_array(volume_number)</i>	Return the three-dimensional data contained in a given volume.

```
__class__
    alias of builtins.type

__delattr__ (self, name, /)
    Implement delattr(self, name).

__dir__ (self, /)
    Default dir() implementation.

__eq__ (self, value, /)
    Return self==value.

__format__ (self, format_spec, /)
    Default object formatter.

__ge__ (self, value, /)
    Return self>=value.

__getattr__ (self, name, /)
    Return getattr(self, name).

__gt__ (self, value, /)
    Return self>value.

__hash__ (self, /)
    Return hash(self).

__init__ (self, /, *args, **kwargs)
    Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)
    Return self<=value.

__lt__ (self, value, /)
    Return self<value.

__ne__ (self, value, /)
    Return self!=value.
```

__new__ (*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__reduce__ ()

__reduce_ex__ (self, protocol, /)

Helper for pickle.

__repr__ (self, /)

Return repr(self).

__setattr__ (self, name, value, /)

Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (self, /)

Size of object in memory, in bytes.

__str__ (self, /)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

available_moments ()

Return a list of available volume moments.

day

get_radar_header ()

Return a dictionary of radar header parameters.

get_volume (volume_number)

Return a _RslVolume for a given volume number.

Parameters

volume_number [int] Volume number to retrieve

Returns

volume [_RslVolume] _RslVolume object containing requested volume.

get_volume_array (volume_number)

Return the three-dimensional data contained in a given volume.

Parameters

volume_number [int]

Returns

volume [array (nsweep, nrays, nbins), float32] Array containing data for the given volume.

height

hour

latd

latm

lats
lond
lonm
lons
lpulse
minute
month
number
nvolumes
scan_mode
sec
spulse
vcp
year

class `pyart.io._rsl_interface._RslRay`

Bases: `object`

A object for accessing RSL Ray data and header information

This class should not be initialized from within Python. `_RslRay` object are returned from the `_RslSweep.get_ray()` method.

Attributes

month [int] Date for this ray, month (1-12).
day [int] Date for this ray, day (1-31).
year [int] Date for this ray, year (eg. 1993).
hour [int] Time for this ray, hour (0-23).
minute [int] Time for this ray, minute (0-59).
sec [float] Time for this ray, second + fractor of second.
unam_rng [float] Unambiguous range in km.
azimuth [float] Mean azimuth angle in degrees for the ray, must be positive. 0 for north, 90 for east, 270 for west.
ray_num [int] Ray number within a scan.
elev [float] Elevation angle in degrees.
elev_num [int] Elevation number within the volume scan.
range_bin1 [int] Range to first gate in meters.
gate_size [int] Gate size in meters.
vel_res [float] Doppler velocity resolution.
sweep_rate [float] Sweep rate, full sweeps / minute.
prf [int] Pulse repetition frequency in Hz.

prf2 [int] Second pulse repetition frequency for dual PRF data.

azim_rate [float] Sweep rate in degrees / second.

fix_angle [float] Elevation angle for the sweep in degrees.

pitch [float] Pitch angle.

roll [float] Roll angle.

heading [float] Heading.

pitch_rate [float] Pitch rate in angle / sec.

roll_rate [float] Roll rate in angle / sec.

heading_rate [float] Heading rate in angle / sec.

lat [float] Latitude in degrees.

lon [float] Longitude in degrees.

alt [int] Altitude in meters.

rvc [float] Radial velocity correction in meters / second.

vel_east [float] Platform velocity to the east in meters / second. Negative values for velocity to the west.

vel_north [float] Platform velocity to the north in meters / second. Negative values for velocity to the south.

vel_up [float] Platform velocity upward in meters / second. Negative values for velocity downward.

pulse_count [int] Pulses used in a single dwell time.

pulse_width [float] Pulse width in microseconds.

beam_width [float] Beamwidth in degrees.

frequency [float] Carrier frequency in GHz.

wavelength [float] Wavelength in meters.

nyq_vel [float] Nyquist velocity in meters / second.

nbins [int] Number of array elements in ray data.

Methods

<code>get_data()</code>	Return the one-dimensional data contained in the ray.
<code>get_datetime()</code>	Return a datetime describing the date and time of the ray.

__class__
alias of `builtins.type`

__delattr__ (*self, name, /*)
Implement `delattr(self, name)`.

__dir__ (*self, /*)
Default `dir()` implementation.

__eq__ (*self, value, /*)

Return self==value.

__format__ (*self, format_spec, /*)
Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, /, *args, **kwargs*)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__ne__ (*self, value, /*)
Return self!=value.

__new__ (**args, **kwargs*)
Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`alt`
`azim_rate`
`azimuth`
`beam_width`
`day`
`elev`
`elev_num`
`fix_angle`
`frequency`
`gate_size`
`get_data()`
Return the one-dimensional data contained in the ray.
`get_datetime()`
Return a datetime describing the date and time of the ray.
`heading`
`heading_rate`
`hour`
`lat`
`lon`
`minute`
`month`
`nbins`
`nyq_vel`
`pitch`
`pitch_rate`
`prf`
`prf2`
`pulse_count`
`pulse_width`
`range_bin1`
`ray_num`
`roll`
`roll_rate`
`rvc`
`sec`
`sweep_rate`
`unam_rng`

vel_east
vel_north
vel_res
vel_up
wavelength
year

class pyart.io._rsl_interface._RslSweep

Bases: `object`

A object for accessing RSL Sweep data and header information.

This class should not be initialized from within Python. `_RslSweep` objects are returned from the `_RslVolume.get_sweep()` method.

Attributes

sweep_num [int] Interger sweep number.
elev [float] Mean elevation angle for thr sweep. -999.0 for RHI sweeps.
azimuth [float] Azumuth for the sweep. -999.0 for PPI scans.
beam_width [float] Beam width in degrees. Can also be found in `_RslRay` objects.
vert_half_bw [float] Vertical beam width divided by 2.
horz_half_bw [float] Horizontal beam width divided by 2.
nrays [int] Number of rays in the sweep.

Methods

<code>get_data()</code>	Return the two-dimensional data contained in the sweep.
<code>get_ray(ray_number)</code>	Return a <code>_RslRay</code> for a given ray.

__class__
alias of `builtins.type`
__delattr__ (*self, name, /*)
Implement `delattr(self, name)`.
__dir__ (*self, /*)
Default `dir()` implementation.
__eq__ (*self, value, /*)
Return `self==value`.
__format__ (*self, format_spec, /*)
Default object formatter.
__ge__ (*self, value, /*)
Return `self>=value`.
__getattr__ (*self, name, /*)
Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)
Return self>value.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, /, **args*, ***kwargs*)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

azimuth

beam_width

elev

get_data ()
Return the two-dimensional data contained in the sweep.

If a given ray has few bins than the first ray, the missing bins will be filled with 131072.0

get_ray (*ray_number*)

Return a `_RslRay` for a given ray.

Parameters

ray_number [int] Ray number to retrieve

Returns

ray [`_RslRay`] `_RslRay` object containing the requested ray.

horz_half_bw

nrays

sweep_num

vert_half_bw

class `pyart.io._rsl_interface._RslVolume`

Bases: `object`

A object for accessing RSL Volume data and header information.

This class should not be initialized from within Python. `_RslVolume` objects are returned from the `RslFile.get_volume()` and other functions/methods.

Attributes

nsweeps [int] Sweep number.

calibr_const [float] Calibration constant.

Methods

<code>get_azimuth_and_elev_array()</code>	Return azimuth and elevation array for each sweep and ray.
<code>get_data()</code>	Return the two-dimensional data contained in the volume.
<code>get_instr_params()</code>	Return instrumental parameter for the volume.
<code>get_nray_array()</code>	Return an array of the number of rays for each sweep.
<code>get_sweep(sweep_number)</code>	Return a <code>_RslSweep</code> for a given sweep number.
<code>get_sweep_azimuths()</code>	Return azimuth array for each sweep.
<code>get_sweep_elevs()</code>	Return elevation array for each sweep.
<code>get_sweep_fix_angles()</code>	Return array of fix angle for each sweep.
<code>is_range_bins_uniform()</code>	Return True if the locations of the range bin are identical for all rays, False if locations change in one or more rays.
<code>total_rays()</code>	Return the total number of rays present in all sweeps of the volume.

__class__

alias of `builtins.type`

__delattr__ (*self, name, /*)

Implement `delattr(self, name)`.

__dir__ (*self, /*)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return self==value.

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return self>=value.

__getattr__ (*self*, *name*, /)
Return getattr(self, name).

__gt__ (*self*, *value*, /)
Return self>value.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, /, **args*, ***kwargs*)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

calibr_const

get_azimuth_and_elev_array()

Return azimuth and elevation array for each sweep and ray.

get_data()

Return the two-dimensional data contained in the volume.

If a given ray has few bins than the first ray, the missing bins will be filled with 131072.0

get_instr_params()

Return instrumental parameter for the volume.

Returns

pm_data [array, (nsweeps)] Array of prt modes.

nv_data [array, (total_rays)] Array of nyquist velocities.

pr_data [array, (total_rays)] Array of pulse repetition frequency in Hz.

ur_data [array, (total_rays)] Array of unambiguous ranges, in km.

get_nray_array()

Return an array of the number of rays for each sweep.

get_sweep(sweep_number)

Return a `_RslSweep` for a given sweep number.

Parameters

sweep_number [int] Sweep number to retrieve

Returns

sweep [`_RslSweep`] `_RslSweep` object containing the requested sweep.

get_sweep_azimuths()

Return azimuth array for each sweep.

get_sweep_elevs()

Return elevation array for each sweep.

get_sweep_fix_angles()

Return array of fix angle for each sweep.

Angles determined from the first ray in each sweep.

is_range_bins_uniform()

Return True if the locations of the range bin are identical for all rays, False if locations change in one or more rays.

nsweeps

total_rays()

Return the total number of rays present in all sweeps of the volume.

`pyart.io._rsl_interface._label_volume(volume, radar)`

Add labels for dealiasing to a `_RslVolume` object from a radar object.

This function does not set all parameter in the `_RslVolume` suitable for writing out the volume, rather it set those parameters which must be set prior to using `pyart.correct._fourdd_interface.fourdd_dealias()`.

Parameters

volume [_RslVolume] Volume object to which parameters will be set as needed prior to dealiasing. Object is manipulated in-place.

radar [Radar] Radar object from which parameters are taken.

`pyart.io._rsl_interface.copy_volume(volume)`

Return a copy of a _RslVolume object.

Parameters

volume [_RslVolume] _RslVolume object to create a copy of.

Returns

nvolume [_RslVolume] Copy of volume.

`pyart.io._rsl_interface.create_volume(arr, rays_per_sweep, vol_num=1)`

Create a _RslVolume object from a 2D float32 array.

No headers parameters except nsweeps, nrays and nbins are not set in the resulting _RslVolume object.

Parameters

arr [array, 2D, float32] Two dimensional float32 array.

rays_per_sweep: array, 1D, int32 Array listing number of rays in each sweep.

vol_num [int] Volume number used to set f and invf in the header. The default is for velocity fields. Useful values are 0 for reflectivity and 1 for velocity.

Returns

volumes [_RslVolume] _RslVolume containing array data.

PYART.IO._SIGMET_NOAA_HH

Functions needed for reading Sigmet files from the airborne radar located on NOAA's Hurricane Hunter aircraft.

<code>_decode_noaa_hh_hdr(raw_extended_headers, ...)</code>	Extract data from Sigmet extended headers produced by NOAA Hurricane Hunter airborne radars.
<code>_georeference_yprime(roll, pitch, heading, ...)</code>	Compute georeferenced azimuth and elevation angles for a Y-prime radar.

`pyart.io._sigmet_noaa_hh._decode_noaa_hh_hdr` (*raw_extended_headers*, *filemetadata*, *azimuth*, *elevation*, *position_source='irs'*, *heading_source='irs'*)

Extract data from Sigmet extended headers produced by NOAA Hurricane Hunter airborne radars.

Parameters

raw_extended_headers [ndarray] Raw Sigmet extended headers.

filemetadata [FileMetadata] FileMetadata class from which metadata will be derived.

azimuth [dict] Dictionary of azimuth angles recorded in Sigmet file.

elevation [dict] Dictionary of elevation angles recorded in Sigmet file.

position_source: {'irs', 'gps', 'aamps'}, **optional** Instrument from which to derive position parameters.

heading_source: {'irs', 'aamps'} Instrument from which to derive heading parameters.

Returns

latitude [dict] Dictionary containing latitude data and metadata.

longitude [dict] Dictionary containing longitude data and metadata.

altitude [dict] Dictionary containing altitude data and metadata.

heading_params [dict] Dictionary of dictionary containing aircraft heading data and metadata. Contains 'heading', 'roll', 'pitch', 'drift', 'rotation', 'tilt' and 'georefs_applied' dictionaries.

`pyart.io._sigmet_noaa_hh._georeference_yprime` (*roll*, *pitch*, *heading*, *drift*, *rotation*, *tilt*)

Compute georeferenced azimuth and elevation angles for a Y-prime radar.

This is the georeferencing needed for the tail doppler radar on the NOAA P3 aircraft.

PYART.IO._SIGMETFILE

A class and supporting functions for reading Sigmet (raw format) files.

<i>SigmetFile</i>	A class for accessing data from Sigmet (IRIS) product files.
<i>convert_sigmet_data()</i>	Convert sigmet data.
<i>bin2_to_angle()</i>	Return an angle from Sigmet bin2 encoded value (or array).
<i>bin4_to_angle()</i>	Return an angle from Sigmet bin4 encoded value (or array).
<i>_data_types_from_mask()</i>	Return a list of the data types from the words in the data_type mask.
<i>_is_bit_set()</i>	Return True if bit is set in number.
<i>_parse_ray_headers()</i>	Parse the metadata from Sigmet ray headers.
<i>_unpack_structure()</i>	Unpack a structure
<i>_unpack_key()</i>	Unpack a key.
<i>_unpack_ingest_data_headers()</i>	Unpack one or more ingest_data_header from a record.
<i>_unpack_ingest_data_header()</i>	Unpack a single ingest_data_header from record.
<i>_unpack_raw_prod_bhdr()</i>	Return a dict with the unpacked raw_prod_bhdr from a record.
<i>_unpack_product_hdr()</i>	Return a dict with the unpacked product_hdr from the first record.
<i>_unpack_ingest_header()</i>	Return a dict with the unpacked ingest_header from the second record.

class pyart.io._sigmetfile.**SigmetFile**

Bases: `object`

A class for accessing data from Sigmet (IRIS) product files.

Parameters

filename [str] Filename or file-like object.

Attributes

debug [bool] Set True to print out debugging information, False otherwise.

product_hdr [dict] Product_hdr structure.

ingest_header [dict] Ingest_header structure.

ingest_data_headers [list of dict] Ingest_data_header structures for each data type. Indexed by the data type name (str). None when data has not yet been read.

data_types [list] List of data types (int) in the file.

data_type_names [list] List of data type names (str) in the file.

ndata_types [int] Number of data types in the file.

_fh [file] Open file being read.

_raw_product_bhdrs [list] List of raw_product_bhdr structure dictionaries seperated by sweep. None when data has not yet been read.

Methods

<code>close()</code>	Close the file.
<code>read_data()</code>	Read all data from the file.

__class__
alias of `builtins.type`

__delattr__ (*self*, *name*, /)
Implement `delattr(self, name)`.

__dir__ (*self*, /)
Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return `self==value`.

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return `self>=value`.

__getattr__ (*self*, *name*, /)
Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)
Return `self>value`.

__hash__ (*self*, /)
Return `hash(self)`.

__init__
initalize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return `self<=value`.

__lt__ (*self*, *value*, /)
Return `self<value`.

__ne__ (*self*, *value*, /)
Return `self!=value`.

__new__ (**args*, ***kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)

Helper for pickle.

__repr__ (*self*, /)

Return repr(*self*).

__setattr__ (*self*, *name*, *value*, /)

Implement setattr(*self*, *name*, *value*).

__setstate__ ()

__sizeof__ (*self*, /)

Size of object in memory, in bytes.

__str__ (*self*, /)

Return str(*self*).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__determine_data_types ()

Determine the available data types in the file.

_fh

__get_sweep ()

Get the data and metadata from the next sweep.

If the file ends early None is returned for all values.

Parameters

full_xhdr [bool] True to return the full extended headers if they exist padded with ones. False will return a length 1 extended header converted to int32. This is useful when the file contains a customer specified extended header (for example aircraft radar).

raw_data [bool, optional] True to return the raw_data for the given sweep, False to convert the data to floating point representation.

Returns

ingest_data_headers [list of dict] List of ingest_data_header structures for each data type.

sweep_data [list of arrays] Sweep data for each data types in the order they appear in the file.

sweep_metadata [list of tuples] Sweep metadata for each data type in the same order as sweep_data.

_raw_product_bhdrs

_rbuf_pos

_record_number

close ()

Close the file.

data_type_names

data_types

debug

ingest_data_headers

ingest_header

ndata_types

product_hdr

read_data()

Read all data from the file.

Parameters

full_xhdr [bool] True to return the full extended headers if they exist padded with ones. False will return a length 1 extended header converted to int32. This is useful when the file contains a customer specified extended header (for example aircraft radar).

Returns

data [dict of ndarrays] Data arrays of shape=(nsweeps, nrays, nbins) for each data type. Indexed by data type name (str).

metadata [dict of dicts] Arrays of 'azimuth_0', 'azimuth_1', 'elevation_0', 'elevation_1', 'nbins', and 'time' for each data type. Indexed by data type name (str). Rays which were not collected are marked with a value of -1 in the 'nbins' array.

`pyart.io._sigmetfile._data_types_from_mask()`

Return a list of the data types from the words in the data_type mask.

`pyart.io._sigmetfile._is_bit_set()`

Return True if bit is set in number.

`pyart.io._sigmetfile._parse_ray_headers()`

Parse the metadata from Sigmet ray headers.

Parameters

ray_headers [array, shape=(..., 6)] Ray headers to parse.

Returns

az0 [array] Azimuth angles (in degrees) at beginning of the rays.

el0 [array] Elevation angles at the beginning of the rays.

az1 [array] Azimuth angles at the end of the rays.

el1 [array] Elevation angles at the end of the rays.

nbins [array] Number of bins in the rays.

time [array] Seconds since the start of the sweep for the rays.

prf_flag [array] Numerical indication of what PRF was used, 0 for high, 1 for low. Not applicable if dual-PRF is not used during collection.

`pyart.io._sigmetfile._unpack_ingest_data_header()`

Unpack a single ingest_data_header from record. Return None on error.

`pyart.io._sigmetfile._unpack_ingest_data_headers()`

Unpack one or more ingest_data_header from a record.

Returns a list of dictionaries or None when an error occurs.

`pyart.io._sigmetfile._unpack_ingest_header()`

Return a dict with the unpacked ingest_header from the second record.

`pyart.io._sigmetfile._unpack_key()`

Unpack a key.

`pyart.io._sigmetfile._unpack_product_hdr()`

Return a dict with the unpacked product_hdr from the first record.

`pyart.io._sigmetfile._unpack_raw_prod_bhdr()`

Return a dict with the unpacked raw_prod_bhdr from a record.

`pyart.io._sigmetfile._unpack_structure()`

Unpack a structure

`pyart.io._sigmetfile.bin2_to_angle()`

Return an angle from Sigmet bin2 encoded value (or array).

`pyart.io._sigmetfile.bin4_to_angle()`

Return an angle from Sigmet bin4 encoded value (or array).

`pyart.io._sigmetfile.convert_sigmet_data()`

Convert sigmet data.

PYART.AUX_IO.ARM_VPT

Routines for reading ARM vertically-pointing radar ingest (e.g., a1) files. These files are characterized by being NetCDF files that do not fully conform to the CF/Radial convention. Nonetheless this module borrows heavily from the existing CF/Radial module.

```
pyart.aux_io.arm_vpt.read_kazr(filename, field_names=None, additional_metadata=None,  
                                file_field_names=False, exclude_fields=None, in-  
                                clude_fields=None)
```

Read K-band ARM Zenith Radar (KAZR) NetCDF ingest data.

Parameters

filename [str] Name of NetCDF file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the radar.fields dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to re-name fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

Returns

radar [Radar] Radar object.

PYART.IO.CFRADIAL

Utilities for reading CF/Radial files.

`_NetCDFVariableDataExtractor`

`read_cf1(filename[, field_names, ...])` Read a CF-1 netCDF file.

```
pyart.aux_io.cf1.read_cf1(filename, field_names=None, additional_metadata=None,
                           file_field_names=False, exclude_fields=None, include_fields=None,
                           delay_field_loading=False, **kwargs)
```

Read a CF-1 netCDF file.

Parameters

filename [str] Name of CF/Radial netCDF file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the radar.fields dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

delay_field_loading [bool] True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Delayed field loading will not provide any speedup in file where the number of gates vary between rays (ngates_vary=True) and is not recommended.

Returns

radar [Radar] Radar object.

Notes

This function has not been tested on “stream” Cfradial files.

PYART.AUX_IO.D3R_GCPEX_NC

Routines for reading GCPEX D3R files.

<code>read_d3r_gcpep_nc(filename[, field_names, ...])</code>	Read a D3R GCPEX netCDF file.
<code>_ncvar_to_dict(ncvar)</code>	Convert a NetCDF Dataset variable to a dictionary.

```
pyart.aux_io.d3r_gcpep_nc._ncvar_to_dict(ncvar)
```

Convert a NetCDF Dataset variable to a dictionary.

```
pyart.aux_io.d3r_gcpep_nc.read_d3r_gcpep_nc(filename, field_names=None,
                                             additional_metadata=None,
                                             file_field_names=False, exclude_fields=None, include_fields=None,
                                             read_altitude_from_nc=False, **kwargs)
```

Read a D3R GCPEX netCDF file.

Parameters

filename [str] Name of the ODIM_H5 file to read.

field_names [dict, optional] Dictionary mapping ODIM_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

read_altitude_from_nc [bool, optional] True if you want the altitude value to be read from the provider netCDF file. False will default to the value `np.array([295.], dtype='float64')`

Returns

radar [Radar] Radar object containing data from ODIM_H5 file.

PYART.AUX_IO.EDGE_NECDF

Utilities for reading EDGE NetCDF files.

<code>read_edge_netcdf(filename, **kwargs)</code>	Read a EDGE NetCDF file.
---	--------------------------

`pyart.aux_io.edge_netcdf.read_edge_netcdf(filename, **kwargs)`
Read a EDGE NetCDF file.

Parameters

filename [str] Name of EDGE NetCDF file to read data from.

Returns

radar [Radar] Radar object.

PYART.AUX_IO.READ_GAMIC

Utilities for reading gamic hdf5 files.

<code>read_gamic(filename[, field_names, ...])</code>	Read a GAMIC hdf5 file.
<code>_get_instrument_params(gfile, filemetadata, ...)</code>	Return a dictionary containing instrument parameters.
<code>_avg_radial_angles(angle1, angle2)</code>	Return the average angle between two radial angles.
<code>_prt_mode_from_unfolding(unfolding)</code>	Return 'fixed' or 'staggered' depending on unfolding flag

`pyart.aux_io.gamic_hdf5._avg_radial_angles (angle1, angle2)`

Return the average angle between two radial angles.

`pyart.aux_io.gamic_hdf5._get_instrument_params (gfile, filemetadata, pulse_width)`

Return a dictionary containing instrument parameters.

`pyart.aux_io.gamic_hdf5._prt_mode_from_unfolding (unfolding)`

Return 'fixed' or 'staggered' depending on unfolding flag

`pyart.aux_io.gamic_hdf5.read_gamic (filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, valid_range_from_file=True, units_from_file=True, pulse_width=None, **kwargs)`

Read a GAMIC hdf5 file.

Parameters

filename [str] Name of GAMIC HDF5 file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the radar.fields dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

valid_range_from_file [bool, optional] True to extract valid range (*valid_min* and *valid_max*) for all field from the file when they are present. False will not extract these parameters.

units_from_file [bool, optional] True to extract the units for all fields from the file when available. False will not extract units using the default units for the fields.

pulse_width [list or None,] Mandatory for gamim radar processors which have pulsewidth enums. *pulse_width* should contain the pulsewidth' in us.

Returns

radar [Radar] Radar object.

PYART.AUX_IO.GAMICFILE

GAMICFile class and utility functions.

<i>GAMICFile</i> (filename)	A class to read GAMIC files.
-----------------------------	------------------------------

<i>_get_gamic_sweep_data</i> (group)	Get GAMIC HDF5 sweep data from an HDF5 group.
--------------------------------------	---

class pyart.aux_io.gamicfile.**GAMICFile**(filename)

Bases: `object`

A class to read GAMIC files.

Parameters

filename [str] Filename of GAMIC HDF5 file.

Attributes

nsweeps [int] Number of sweeps (or scans) in the file.

rays_per_sweep [array of int32] Number of rays in each sweep.

total_rays [int] Total number of rays in all sweeps.

start_ray, end_ray [array of int32] Index of the first (start) and last (end) ray in each sweep, 0-based.

_hfile [HDF5 file] Open HDF5 file object from which data is read.

_scans [list] Name of the HDF5 group for each scan.

Methods

<i>close</i> (self)	Close the file.
<i>how_attr</i> (self, attr, dtype)	Return an array containing a attribute from the how group.
<i>how_attrs</i> (self, attr, dtype)	Return an array of an attribute for each scan's how group.
<i>how_ext_attrs</i> (self, attr)	Return a list of an attribute in each scan's how/extended group.
<i>is_attr_in_group</i> (self, group, attr)	True is attribute is present in the group, False otherwise.

Continued on next page

Table 3 – continued from previous page

<i>is_field_in_ray_header</i> (self, field)	True if field is present in ray_header, False otherwise.
<i>is_file_complete</i> (self)	True if all scans in file, False otherwise.
<i>is_file_single_scan_type</i> (self)	True if all scans are the same scan type, False otherwise.
<i>moment_data</i> (self, group, dtype)	Read in moment data from all sweeps.
<i>moment_groups</i> (self)	Return a list of groups under scan0 where moments are stored.
<i>moment_names</i> (self, scan0_groups)	Return a list of moment names for a list of scan0 groups.
<i>raw_group_attr</i> (self, group, attr)	Return an attribute from a group with no reformatting.
<i>raw_scan0_group_attr</i> (self, group, attr)	Return an attribute from the scan0 group with no reformatting.
<i>ray_header</i> (self, field, dtype)	Return an array containing a ray_header field for each sweep.
<i>sweep_expand</i> (self, arr[, dtype])	Expand an sweep indexed array to be ray indexed
<i>what_attrs</i> (self, attr, dtype)	Return a list of an attribute for each scan's what group.
<i>where_attr</i> (self, attr, dtype)	Return an array containing a attribute from the where group.

```
__class__
    alias of builtins.type
__delattr__(self, name, /)
    Implement delattr(self, name).
__dict__ = mappingproxy({'__module__': 'pyart.aux_io.gamicfile', '__doc__': '\n A cl
__dir__(self, /)
    Default dir() implementation.
__eq__(self, value, /)
    Return self==value.
__format__(self, format_spec, /)
    Default object formatter.
__ge__(self, value, /)
    Return self>=value.
__getattr__(self, name, /)
    Return getattr(self, name).
__gt__(self, value, /)
    Return self>value.
__hash__(self, /)
    Return hash(self).
__init__(self, filename)
    initialize object.
__init_subclass__()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.
```

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.aux_io.gamicfile'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

close (*self*)
Close the file.

how_attr (*self*, *attr*, *dtype*)
Return an array containing a attribute from the how group.

how_attrs (*self*, *attr*, *dtype*)
Return an array of an attribute for each scan's how group.

how_ext_attrs (*self*, *attr*)
Return a list of an attribute in each scan's how/extended group.

is_attr_in_group (*self*, *group*, *attr*)
True is attribute is present in the group, False otherwise.

is_field_in_ray_header (*self*, *field*)
True if field is present in ray_header, False otherwise.

is_file_complete (*self*)
True if all scans in file, False otherwise.

is_file_single_scan_type (*self*)

True if all scans are the same scan type, False otherwise.

moment_data (*self, group, dtype*)

Read in moment data from all sweeps.

moment_groups (*self*)

Return a list of groups under scan0 where moments are stored.

moment_names (*self, scan0_groups*)

Return a list of moment names for a list of scan0 groups.

raw_group_attr (*self, group, attr*)

Return an attribute from a group with no reformatting.

raw_scan0_group_attr (*self, group, attr*)

Return an attribute from the scan0 group with no reformatting.

ray_header (*self, field, dtype*)

Return an array containing a ray_header field for each sweep.

sweep_expand (*self, arr, dtype='float32'*)

Expand an sweep indexed array to be ray indexed

what_attrs (*self, attr, dtype*)

Return a list of an attribute for each scan's what group.

where_attr (*self, attr, dtype*)

Return an array containing a attribute from the where group.

`pyart.aux_io.gamicfile._get_gamic_sweep_data` (*group*)

Get GAMIC HDF5 sweep data from an HDF5 group.

METRANET LIBRARY

functions to read METRANET files, require external shared library `srn_idl_py_lib.<ARCH>.so`

<code>get_radar_site_info([verbose])</code>	return dictionary with radar'info
<code>get_library_path()</code>	look for valid library path
<code>get_library([verbose, momentms])</code>	return the link to C-shared library
<code>read_polar(radar_file[, moment, ...])</code>	Reads a METRANET polar data file
<code>read_product(radar_file[, physic_value, ...])</code>	Reads a METRANET cartesian data file
<code>read_file(file[, moment, physic_value, ...])</code>	Reads a METRANET data file
<hr/>	
<code>RadarData([data, dtype, scale, dtype, ...])</code>	A class for storing radar data.
<code>Header_struPM</code>	A class containing the data from the header of the polar PM files
<code>Header_struMS</code>	A class containing the data from the header of the polar MS files
<code>Selex_Angle([angle, radiant])</code>	Class used to convert from digital number to angle

class `pyart.aux_io.metrانet_c.Header_struMS`

Bases: `_ctypes.Structure`

A class containing the data from the header of the polar MS files

Attributes

fields : `dict` A dictionary containing the metadata contained in the MS file

C-Structure of METRANET POLAR data MS format

C-code from METRANET2/share/include/sweep_file.h

struct sweep_header

```
{ int8_t FileId[4]; //4:4 uint8_t Version; //1:5 uint8_t Spare1[3]; //3:8 uint32_t Length;
//4:12 int8_t RadarName[16]; //16:28 int8_t ScanName[16]; //16:44 float RadarLat;
//4:48 float RadarLon; //4:52 float RadarHeight; //4:56 uint8_t SequenceSweep; //1:57
uint8_t CurrentSweep; //1:58 uint8_t TotalSweep; //1:59 uint8_t AntMode; //1:60 uint8_t
Priority; //1:61 uint8_t Quality; //1:62 uint8_t Spare2[2]; //2:64 uint16_t RepeatTime;
//2:66 uint16_t NumMoments; //2:68 float GateWidth; //4:72 float WaveLength; //4:76
float PulseWidth; //4:80 float StartRange; //4:84 uint32_t MetaDataSize; //4:88

};
```

AntMode

Structure/Union member

CurrentSweep
Structure/Union member

FileId
Structure/Union member

GateWidth
Structure/Union member

Length
Structure/Union member

MetaDataSize
Structure/Union member

NumMoments
Structure/Union member

Priority
Structure/Union member

PulseWidth
Structure/Union member

Quality
Structure/Union member

RadarHeight
Structure/Union member

RadarLat
Structure/Union member

RadarLon
Structure/Union member

RadarName
Structure/Union member

RepeatTime
Structure/Union member

ScanName
Structure/Union member

SequenceSweep
Structure/Union member

Spare1
Structure/Union member

Spare2
Structure/Union member

StartRange
Structure/Union member

TotalSweep
Structure/Union member

Version
Structure/Union member

WaveLength

Structure/Union member

__class__alias of `_ctypes.PyCStructType`**__ctypes_from_outparam__**()**__delattr__**(*self*, *name*, /)Implement `delattr(self, name)`.**__dict__** = `mappingproxy({'__module__': 'pyart.aux_io.metranet_c', '__doc__': '\n A c`**__dir__**(*self*, /)Default `dir()` implementation.**__eq__**(*self*, *value*, /)Return `self==value`.**__format__**(*self*, *format_spec*, /)

Default object formatter.

__ge__(*self*, *value*, /)Return `self>=value`.**__getattr__**(*self*, *name*, /)Return `getattr(self, name)`.**__gt__**(*self*, *value*, /)Return `self>value`.**__hash__**(*self*, /)Return `hash(self)`.**__init__**(*self*, /, **args*, ***kwargs*)Initialize `self`. See `help(type(self))` for accurate signature.**__init_subclass__**()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__(*self*, *value*, /)Return `self<=value`.**__lt__**(*self*, *value*, /)Return `self<value`.**__module__** = `'pyart.aux_io.metranet_c'`**__ne__**(*self*, *value*, /)Return `self!=value`.**__new__**(**args*, ***kwargs*)Create and return a new object. See `help(type)` for accurate signature.**__reduce__**()

Helper for pickle.

__reduce_ex__(*self*, *protocol*, /)

Helper for pickle.

__repr__(*self*, /)Return `repr(self)`.

`__setattr__` (*self*, *name*, *value*, /)
Implement setattr(*self*, *name*, *value*).

`__setstate__` ()

`__sizeof__` (*self*, /)
Size of object in memory, in bytes.

`__str__` (*self*, /)
Return str(*self*).

`__subclasshook__` ()
Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`
list of weak references to the object (if defined)

`_b_base_`
the base object

`_b_needsfree_`
whether the object owns the memory or not

`_fields_` = [('FileId', <class 'ctypes.c_int'>), ('Version', <class 'ctypes.c_ubyte'>),

`_objects`
internal objects tree (NEVER CHANGE THIS OBJECT!)

class `pyart.aux_io.metranet_c.Header_struPM`

Bases: `_ctypes.Structure`

A class containing the data from the header of the polar PM files

Attributes

`_fields_`: **dict** A dictionary containing the metadata contained in the PM file

C-Structure of METRANET POLAR data PM format

struct moment_header_struct

{ unsigned int record_type; data format (moment1) + moment mask unsigned int scan_id; unsigned int host_id; unsigned int start_angle; unsigned int end_angle;

unsigned char ant_mode; unsigned char total_sweep; unsigned char current_sweep; 1-any number up to 99 unsigned char end_of_sweep; 0=not end, 1=end sweep, 2=end volume

short sequence; ray sequence number in a sweep short total_record; total ray number in sweep short pulses; short num_gates;

int data_bytes; unsigned short data_flag; short data_time_residue; data time residue in 0.01 sec unsigned int data_time; data time in second short repeat_time; char compressed; flag for compression of data char priority; for file name use

float ny_quest; float gate_width; float w_ny_quest; may be used for other variable float start_range;

};

`__class__`
alias of `_ctypes.PyCStructType`

`__ctypes_from_outparam__()`

`__delattr__(self, name, /)`
Implement `delattr(self, name)`.

`__dict__ = mappingproxy({'__module__': 'pyart.aux_io.metranet_c', '__doc__': '\n A c`

`__dir__(self, /)`
Default `dir()` implementation.

`__eq__(self, value, /)`
Return `self==value`.

`__format__(self, format_spec, /)`
Default object formatter.

`__ge__(self, value, /)`
Return `self>=value`.

`__getattr__(self, name, /)`
Return `getattr(self, name)`.

`__gt__(self, value, /)`
Return `self>value`.

`__hash__(self, /)`
Return `hash(self)`.

`__init__(self, /, *args, **kwargs)`
Initialize self. See `help(type(self))` for accurate signature.

`__init_subclass__()`
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__(self, value, /)`
Return `self<=value`.

`__lt__(self, value, /)`
Return `self<value`.

`__module__ = 'pyart.aux_io.metranet_c'`

`__ne__(self, value, /)`
Return `self!=value`.

`__new__(*args, **kwargs)`
Create and return a new object. See `help(type)` for accurate signature.

`__reduce__()`
Helper for pickle.

`__reduce_ex__(self, protocol, /)`
Helper for pickle.

`__repr__(self, /)`
Return `repr(self)`.

`__setattr__(self, name, value, /)`
Implement `setattr(self, name, value)`.

`__setstate__()`

__sizeof__ (*self*, /)

Size of object in memory, in bytes.

__str__ (*self*, /)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

_b_base_

the base object

_b_needsfree_

whether the object owns the memory or not

fields = [('record_type', <class 'ctypes.c_uint'>), ('scan_id', <class 'ctypes.c_int

_objects

internal objects tree (NEVER CHANGE THIS OBJECT!)

ant_mode

Structure/Union member

compressed

Structure/Union member

current_sweep

Structure/Union member

data_bytes

Structure/Union member

data_flag

Structure/Union member

data_time

Structure/Union member

data_time_residue

Structure/Union member

end_angle

Structure/Union member

end_of_sweep

Structure/Union member

gate_width

Structure/Union member

host_id

Structure/Union member

num_gates

Structure/Union member

ny_quest
Structure/Union member

priority
Structure/Union member

pulses
Structure/Union member

record_type
Structure/Union member

repeat_time
Structure/Union member

scan_id
Structure/Union member

sequence
Structure/Union member

start_angle
Structure/Union member

start_range
Structure/Union member

total_record
Structure/Union member

total_sweep
Structure/Union member

w_ny_quest
Structure/Union member

```
class pyart.aux_io.metranet_c.RadarData (data=array([], dtype=float64), scale=array([ 0, 1,
2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17,
18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30,
31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43,
44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56,
57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69,
70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83,
84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97,
98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108,
109, 110, 111, 112, 113, 114, 115, 116, 117, 118,
119, 120, 121, 122, 123, 124, 125, 126, 127, 128,
129, 130, 131, 132, 133, 134, 135, 136, 137, 138,
139, 140, 141, 142, 143, 144, 145, 146, 147, 148,
149, 150, 151, 152, 153, 154, 155, 156, 157, 158,
159, 160, 161, 162, 163, 164, 165, 166, 167, 168,
169, 170, 171, 172, 173, 174, 175, 176, 177, 178,
179, 180, 181, 182, 183, 184, 185, 186, 187, 188,
189, 190, 191, 192, 193, 194, 195, 196, 197, 198,
199, 200, 201, 202, 203, 204, 205, 206, 207, 208,
209, 210, 211, 212, 213, 214, 215, 216, 217, 218,
219, 220, 221, 222, 223, 224, 225, 226, 227, 228,
229, 230, 231, 232, 233, 234, 235, 236, 237, 238,
239, 240, 241, 242, 243, 244, 245, 246, 247, 248,
249, 250, 251, 252, 253, 254, 255], dtype=uint64),
header=(), pol_header=(), moment='ZH')
```

Bases: `object`

A class for storing radar data.

Attributes

type [str] type of data

data [numpy array or numpy masked array] array containing the data

scale [numpy array] array containing the scale used to transform the data from digital to physical units

header [dict] dictionary containing metadata

pol_header [dict] dictionary containing metadata of the polar files

moment [str] moment name

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.aux_io.metranet_c', '__doc__': '\n A c`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

RadarData.__init__ (*self, data=array([], dtype=float64), scale=array([0, 1, 2, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255], dtype=uint64), header=(), pol_header=()*)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyart.aux_io.metranet_c'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

`__setattr__` (*self, name, value, /*)

Implement setattr(self, name, value).

`__sizeof__` (*self, /*)

Size of object in memory, in bytes.

`__str__` (*self, /*)

Return str(self).

`__subclasshook__` ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`type` = 'RadarData'

`class` pyart.aux_io.metranet_c.Selex_Angle (*angle=0, radiant=False*)

Bases: `object`

Class used to convert from digital number to angle

Attributes

`az` [float] azimuth angle value (degrees or radians)

`el` [float] elevation angle value (degrees or radians)

`__class__`

alias of `builtins.type`

`__delattr__` (*self, name, /*)

Implement delattr(self, name).

`__dict__` = `mappingproxy({'__module__': 'pyart.aux_io.metranet_c', '__doc__': '\n Cla`

`__dir__` (*self, /*)

Default dir() implementation.

`__eq__` (*self, value, /*)

Return self==value.

`__format__` (*self, format_spec, /*)

Default object formatter.

`__ge__` (*self, value, /*)

Return self>=value.

`__getattr__` (*self, name, /*)

Return getattr(self, name).

`__gt__` (*self, value, /*)

Return self>value.

`__hash__` (*self, /*)

Return hash(self).

`__init__` (*self, angle=0, radiant=False*)

Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)

Return self<=value.

__lt__ (self, value, /)

Return self<value.

__module__ = 'pyart.aux_io.metranet_c'

__ne__ (self, value, /)

Return self!=value.

__new__ (*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)

Helper for pickle.

__reduce_ex__ (self, protocol, /)

Helper for pickle.

__repr__ (self, /)

Return repr(self).

__setattr__ (self, name, value, /)

Implement setattr(self, name, value).

__sizeof__ (self, /)

Size of object in memory, in bytes.

__str__ (self, /)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

`pyart.aux_io.metranet_c.get_library(verbose=False, momentms=True)`

return the link to C-shared library

Parameters

verbose [Boolean] If true print out extra information

momentms [Boolean] If true returns the link to the MS library

Returns

metranet_lib [link] loaded METRANET C-library

`pyart.aux_io.metranet_c.get_library_path()`

look for valid library path

Returns

library_metranet_path [str] METRANET library path

`pyart.aux_io.metranet_c.get_radar_site_info(verbose=False)`
return dictionary with radar'info

Returns

radar_def [dict] dictionary containing radar site information

`pyart.aux_io.metranet_c.read_file(file, moment='ZH', physic_value=False, masked_array=False, verbose=False)`

Reads a METRANET data file

Parameters

file [str] file name

moment [str] moment name

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

verbose [boolean] If true prints out extra information

Returns

ret_data [RadarData object] An object containing the information read from the file

`pyart.aux_io.metranet_c.read_polar(radar_file, moment='ZH', physic_value=False, masked_array=False, verbose=False)`

Reads a METRANET polar data file

Parameters

radar_file [str] file name

moment [str] moment name

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

verbose [boolean] If true prints out extra information

Returns

ret_data [RadarData object] An object containing the information read from the file. None if the file has not been properly read

`pyart.aux_io.metranet_c.read_product(radar_file, physic_value=False, masked_array=False, verbose=False)`

Reads a METRANET cartesian data file

Parameters

radar_file [str] file name

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

verbose [boolean] If true prints out extra information

Returns

ret_data [RadarData object] An object containing the information read from the file. None if the file has not been properly read

`pyart.aux_io.metranet_c.xrangle(i)`

METRANET PYTHON LIBRARY

functions to read METRANET files in pure python, no other library required!

<i>read_polar</i> (filename[, moments, ...])	Reads a METRANET polar data file
<i>read_product</i> (radar_file[, physic_value, ...])	Reads a METRANET cartesian data file
<i>read_file</i> (file[, moment, physic_value, ...])	Reads a METRANET data file
<i>_get_radar_site_info</i> ([verbose])	return dictionary with radar'info
<i>_nyquist_vel</i>	
<i>_selex2deg</i> (angle)	Convert angles from SELEX format to degree
<i>_float_mapping</i>	

<i>RadarData</i> ([header, pol_header, data, scale])	A class for storing radar data.
<i>PolarParser</i> (filename)	A class for parsing metranet polar data

class `pyart.aux_io.metranet_python.PolarParser` (*filename*)

Bases: `object`

A class for parsing metranet polar data

Parameters

filename [str] complete file path of the file to read

Attributes

file_format [char] P or M depending on the file format that was used

file_type [char] file type (H, M or L)

bname [str] basename (without path) of the file to read

byttarray: memoryview of a bytearray binary data contained in the file

Methods

<i>parse</i> (self[, moments])	Parses a metranet binary file by calling the appropriate parser depending on the file type (M or P)
--------------------------------	---

```
__class__  
    alias of builtins.type  
__delattr__(self, name, /)  
    Implement delattr(self, name).
```

```
__dict__ = mappingproxy({'__module__': 'pyart.aux_io.metranet_python', '__doc__': '\n\n__dir__ (self, /)\n    Default dir() implementation.\n\n__eq__ (self, value, /)\n    Return self==value.\n\n__format__ (self, format_spec, /)\n    Default object formatter.\n\n__ge__ (self, value, /)\n    Return self>=value.\n\n__getattr__ (self, name, /)\n    Return getattr(self, name).\n\n__gt__ (self, value, /)\n    Return self>value.\n\n__hash__ (self, /)\n    Return hash(self).\n\n__init__ (self, filename)\n    Initialize self. See help(type(self)) for accurate signature.\n\n__init_subclass__ ()\n    This method is called when a class is subclassed.\n\n    The default implementation does nothing. It may be overridden to extend subclasses.\n\n__le__ (self, value, /)\n    Return self<=value.\n\n__lt__ (self, value, /)\n    Return self<value.\n\n__module__ = 'pyart.aux_io.metranet_python'\n\n__ne__ (self, value, /)\n    Return self!=value.\n\n__new__ (*args, **kwargs)\n    Create and return a new object. See help(type) for accurate signature.\n\n__reduce__ (self, /)\n    Helper for pickle.\n\n__reduce_ex__ (self, protocol, /)\n    Helper for pickle.\n\n__repr__ (self, /)\n    Return repr(self).\n\n__setattr__ (self, name, value, /)\n    Implement setattr(self, name, value).\n\n__sizeof__ (self, /)\n    Size of object in memory, in bytes.\n\n__str__ (self, /)\n    Return str(self).
```


__subclasshook__()

Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

__get_chunk(*self*, *file_info*)

Parses part of the bytearray given the info about what data to expect

Parameters

file_info [dict] dictionary with three keys: 'names', 'len', 'type' containing the names, length and types of the variables that should be read from the binary file. These dictionaries are defined in the `pmfile_structure.py` file

Returns

dic_values [dict] dictionary containing all the variables that were read from the file, with keys corresponding to the 'names' key in the `file_info` dict

__parse_m(*self*, *moments*)

Parses a M format metranet binary file

Parameters

moments [list] list of moments to get from the file, possible moments are ZH, ZV, ZDR, ST1, ST2, VEL, WID, PHI, RHO, CLT, ZVC, ZHC, MPH, if none ALL moments available in the file are read

Returns

head [dict] file metadata

pol_header: list list of metadata dictionaries for every ray

moments_data: dictionary dictionary containing the data in DN for every moment

__parse_p(*self*, *moments*)

Parses a P format metranet binary file

Parameters

moments [list] list of moments to get from the file, possible moments are ZH, ZV, ZDR, ST1, ST2, VEL, WID, PHI, RHO, CLT, ZVC, ZHC, MPH, if none ALL moments available in the file are read

Returns

head [dict] file metadata

pol_header: list list of metadata dictionaries for every ray

moments_data: dictionary dictionary containing the data in DN for every moment

parse(*self*, *moments=None*)

Parses a metranet binary file by calling the appropriate parser depending on the file type (M or P)

Parameters

moments [list (optional)] list of moments to get from the file, possible moments are ZH, ZV, ZDR, ST1, ST2, VEL, WID, PHI, RHO, CLT, ZVC, ZHC, MPH, default = ALL moments available in the file are read

Returns

out [RadarClass instance] RadarClass instance containing the file data and metadata

class `pyart.aux_io.metranet_python.RadarData` (*header=None, pol_header=None, data=None, scale=None*)

Bases: `object`

A class for storing radar data.

Attributes

header [dictionary] file header (metadara valid for the whole sweep)

pol_header [list] list of ray metadata dictionaries

data [dictionary] dic of arrays containing data

__class__

alias of `builtins.type`

__delattr__ (*self, name, /*)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.aux_io.metranet_python', '__doc__': '\n`

__dir__ (*self, /*)

Default `dir()` implementation.

__eq__ (*self, value, /*)

Return `self==value`.

__format__ (*self, format_spec, /*)

Default object formatter.

__ge__ (*self, value, /*)

Return `self>=value`.

__getattr__ (*self, name, /*)

Return `getattr(self, name)`.

__gt__ (*self, value, /*)

Return `self>value`.

__hash__ (*self, /*)

Return `hash(self)`.

__init__ (*self, header=None, pol_header=None, data=None, scale=None*)

Initialize self. See `help(type(self))` for accurate signature.

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)

Return `self<=value`.

__lt__ (*self, value, /*)

Return `self<value`.

__module__ = `'pyart.aux_io.metranet_python'`

__ne__ (*self, value, /*)

Return `self!=value`.

__new__ (*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)

Helper for pickle.

__reduce_ex__ (self, protocol, /)

Helper for pickle.

__repr__ (self, /)

Return repr(self).

__setattr__ (self, name, value, /)

Implement setattr(self, name, value).

__sizeof__ (self, /)

Size of object in memory, in bytes.

__str__ (self, /)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

pyart.aux_io.metranet_python.**__get_radar_site_info** (verbose=False)
return dictionary with radar'info

Returns

radar_def [dict] dictionary containing radar site information

pyart.aux_io.metranet_python.**__selex2deg** (angle)
Convert angles from SELEX format to degree

Parameters

angle [float] angle in DN

Returns

conv [float] angle in degrees

pyart.aux_io.metranet_python.**read_file** (file, moment='ZH', physic_value=False,
masked_array=False, reorder_angles=True, ver-
bose=False)

Reads a METRANET data file

Parameters

file [str] file name

moment [str] moment name

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

reorder_angles [boolean] If true angles are reordered

verbose [boolean] If true prints out extra information

Returns

ret_data [RadarData object] An object containing the information read from the file

`pyart.aux_io.metranet_python.read_polar` (*filename*, *moments=None*, *physic_value=True*,
masked_array=True, *reorder_angles=True*)

Reads a METRANET polar data file

Parameters

radar_file [str] file name

moments [list] List of moments to read, by default all are used

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

reorder_angles: boolean If true all recorded rays are sorted by ascending order of their angles
In addition the scan is truncated to a maximum of 360 rays

Returns

ret_data [RadarData object] An object containing the information read from the file.

`pyart.aux_io.metranet_python.read_product` (*radar_file*, *physic_value=False*,
masked_array=False, *verbose=False*)

Reads a METRANET cartesian data file

Parameters

radar_file [str] file name

physic_value [boolean] If true returns the physical value. Otherwise the digital value

masked_array [boolean] If true returns a numpy masked array with NaN values masked. Otherwise returns a regular masked array with NaN values

verbose [boolean] If true prints out extra information

Returns

ret_data [RadarData object] An object containing the information read from the file. None if the file has not been properly read

`pyart.aux_io.metranet_python.xrangle` (*i*)

PYART.AUX_IO.METTRANET_CARTESIAN_READER

Routines for putting METTRANET Cartesian data files into grid object. (Used by ELDES www.eldesradar.it)

`read_cartesian_metranet(filename[, ...])` Read a METTRANET product file.

`pyart.aux_io.metranet_cartesian_reader.read_cartesian_metranet` (*filename*, *additional_metadata=None*,
chy0=255.0,
chx0=-160.0,
reader='C',
***kwargs*)

Read a METTRANET product file.

Parameters

filename [str] Name of the METTRANET file to read.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

chy0, chx0 [float] Swiss coordinates position of the south-western point in the grid

reader [str] The reader library to use. Can be either 'C' or 'python'

Returns

grid [Grid] Grid object containing data from METTRANET file.

PYART.AUX_IO.METRANET_READER

Routines for putting METRANET data files into radar object. (Used by ELDES www.eldesradar.it)

<code>read_metrانet(filename[, field_names, rmax, ...])</code>	Read a METRANET file.
<code>read_metrانet_c(filename[, field_names, ...])</code>	Read a METRANET file.
<code>read_metrانet_python(filename[, ...])</code>	Read a METRANET file.

```
pyart.aux_io.metrانet_reader.read_metrانet(filename, field_names=None,
                                             rmax=0.0, additional_metadata=None,
                                             file_field_names=False, exclude_fields=None,
                                             reader='C', nbytes=4, **kwargs)
```

Read a METRANET file.

Parameters

filename [str] Name of the METRANET file to read.

field_names [dict, optional] Dictionary mapping METRANET field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

rmax [float, optional] Maximum radar range to store in the radar object [m]. If 0 all data will be stored

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any addition metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

reader [str] The reader library to use. Can be either 'C' or 'python'

nbytes [int] The number of bytes used to store the data in numpy arrays, e.g. if nbytes=4 then floats are going to be stored as np.float32

Returns

radar [Radar] Radar object containing data from METRANET file.

```
pyart.aux_io.metranet_reader.read_metranet_c(filename, field_names=None,
                                              rmax=0.0, additional_metadata=None,
                                              file_field_names=False, exclude_fields=None, nbytes=4, **kwargs)
```

Read a METRANET file.

Parameters

filename [str] Name of the METRANET file to read.

field_names [dict, optional] Dictionary mapping METRANET field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

rmax [float, optional] Maximum radar range to store in the radar object [m]. If 0 all data will be stored

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

nbytes [int] The number of bytes used to store the data in numpy arrays, e.g. if *nbytes*=4 then floats are going to be stored as np.float32

Returns

radar [Radar] Radar object containing data from METRANET file.

```
pyart.aux_io.metranet_reader.read_metranet_python(filename, field_names=None,
                                                  rmax=0.0, additional_metadata=None,
                                                  file_field_names=False, exclude_fields=None,
                                                  nbytes=4, **kwargs)
```

Read a METRANET file.

Parameters

filename [str] Name of the METRANET file to read.

field_names [dict, optional] Dictionary mapping METRANET field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

rmax [float, optional] Maximum radar range to store in the radar object [m]. If 0 all data will be stored

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the `field_names` parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

nbytes [int] The number of bytes used to store the data in numpy arrays, e.g. if `nbytes=4` then floats are going to be stored as `np.float32`

Returns

radar [Radar] Radar object containing data from METRANET file.

PYART.AUX_IO.NOXP_IPHEX_NC

Routines for reading IPHEX NOXP files.

```
read_noxp_iphex_nc(filename[, field_names, Read a NOXP IPHEX netCDF file.
...])
```

```
_ncvar_to_dict(ncvar) Convert a NetCDF Dataset variable to a dictionary.
```

```
pyart.aux_io.noxp_iphex_nc._ncvar_to_dict(ncvar)
```

Convert a NetCDF Dataset variable to a dictionary.

```
pyart.aux_io.noxp_iphex_nc.read_noxp_iphex_nc(filename, field_names=None,
additional_metadata=None,
file_field_names=False, exclude_fields=None, **kwargs)
```

Read a NOXP IPHEX netCDF file.

Parameters

filename [str] Name of the netCDF file to read.

field_names [dict, optional] Dictionary mapping netCDF field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the netCDF data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

Returns

radar [Radar] Radar object containing data from netCDF file.

PYART.AUX_IO.ODIM_H5

Routines for reading ODIM_H5 files.

<code>read_odim_h5(filename[, field_names, ...])</code>	Read a ODIM_H5 file.
<code>_to_str(text)</code>	Convert bytes to str if necessary.
<code>_get_odim_h5_sweep_data(group)</code>	Get ODIM_H5 sweep data from an HDF5 group.

```
pyart.aux_io.odim_h5._get_odim_h5_sweep_data(group)
    Get ODIM_H5 sweep data from an HDF5 group.
```

```
pyart.aux_io.odim_h5._to_str(text)
    Convert bytes to str if necessary.
```

```
pyart.aux_io.odim_h5.read_odim_h5(filename, field_names=None, additional_metadata=None,
                                   file_field_names=False, exclude_fields=None, include_fields=None, **kwargs)
```

Read a ODIM_H5 file.

Parameters

filename [str] Name of the ODIM_H5 file to read.

field_names [dict, optional] Dictionary mapping ODIM_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

Returns

radar [Radar] Radar object containing data from ODIM_H5 file.

PYART.IO.ODIM_H5_WRITER.PY

Utilities for writing ODIM hdf5 files.

<code>write_odim_h5(filename, radar[, ...])</code>	Write a Radar object to a EUMETNET OPERA compliant HDF5 file.
<code>_to_str(text)</code>	Converter: From byte arrays to string if necessary.
<code>_get_sec_since_epoch(time_f)</code>	Calculate seconds since 1970-01-01 epoch with microseconds precision
<code>_tree()</code>	Initialize a tree structure for a multidimensional dictionary
<code>_check_file_exists(filename)</code>	Check for ODIM h5 file existence
<code>_create_odim_h5_file(filename[, ...])</code>	Initialize HDF5 file with h5py (https://www.h5py.org/) to write ODIM compliant data structure.
<code>_create_odim_h5_grp(file_id, grp_name)</code>	Create HDF5 group for a specified file ID.
<code>_create_odim_h5_sub_grp(grp_id, sub_grp_name)</code>	Create HDF5 subgroup within a specified group.
<code>_create_odim_h5_attr(grp_id, name, data)</code>	Create and fill group (subgroup) attributes with metadata.
<code>_create_odim_h5_dataset(ID, name, data_arr)</code>	Create and save radar field data array to h5py dataset.
<code>_map_radar_quantity(field_name)</code>	Map radar field quantities to ODIM compliant quantities.
<code>_get_data_from_field(radar, sweep_ind, ...)</code>	Extract data from radar field object with respect to different datasets and datatypes.
<code>_map_radar_to_how_dict(radar_obj)</code>	Tries to map data in a radar sub object (e.g.

`pyart.aux_io.odim_h5_writer._check_file_exists(filename)`
Check for ODIM h5 file existence

`pyart.aux_io.odim_h5_writer._create_odim_h5_attr(grp_id, name, data)`
Create and fill group (subgroup) attributes with metadata.

`pyart.aux_io.odim_h5_writer._create_odim_h5_dataset(ID, name, data_arr, make_legend=False, compression='gzip', compression_opts=6)`
Create and save radar field data array to h5py dataset.

`pyart.aux_io.odim_h5_writer._create_odim_h5_file(filename, access_mode='w', driver=None)`
Initialize HDF5 file with h5py (<https://www.h5py.org/>) to write ODIM compliant data structure.

`pyart.aux_io.odim_h5_writer._create_odim_h5_grp(file_id, grp_name)`
Create HDF5 group for a specified file ID.

```
pyart.aux_io.odim_h5_writer._create_odim_h5_sub_grp(grp_id, sub_grp_name)
```

Create HDF5 subgroup within a specified group.

```
pyart.aux_io.odim_h5_writer._get_data_from_field(radar, sweep_ind, field_name, physical=True)
```

Extract data from radar field object with respect to different datasets and datatypes.

```
pyart.aux_io.odim_h5_writer._get_sec_since_epoch(time_f)
```

Calculate seconds since 1970-01-01 epoch with microseconds precision

```
pyart.aux_io.odim_h5_writer._map_radar_quantity(field_name)
```

Map radar field quantities to ODIM compliant quantities.

```
pyart.aux_io.odim_h5_writer._map_radar_to_how_dict(radar_obj)
```

Tries to map data in a radar sub object (e.g. radar.instrument_parameters) to ODIM how attributes.

```
pyart.aux_io.odim_h5_writer._to_str(text)
```

Converter: From byte arrays to string if necessary.

```
pyart.aux_io.odim_h5_writer._tree()
```

Initialize a tree structure for a multidimensional dictionary

```
pyart.aux_io.odim_h5_writer.write_odim_h5(filename, radar, field_names=None, physical=True, compression='gzip', compression_opts=6)
```

Write a Radar object to a EUMETNET OPERA compliant HDF5 file.

The files produced by this routine follow the EUMETNET OPERA information model: http://eumetnet.eu/wp-content/uploads/2017/01/OPERA_hdf_description_2014.pdf

Supported features:

- Writing PPIs: PVOL and SCAN objects - Different sweeps are saved in different dataset groups
- Writing sectorized PPIs and SCANS: AZIM objects
- Writing RHIs: ELEV objects

Not yet supported:

- Mixed datasets (how group always on top level)
- Single ray data (e.g. from fixed staring mode)
- Profiles

Parameters

filename [str] Filename of file to create.

radar [Radar] Radar object to process.

field_names [list of str] The list of fields from the radar object to save. If none all fields in the radar object will be saved.

physical [Bool] If true the physical values are stored. nodata parameter is equal to the _Fill-Value parameter in the field metadata or the default Py-ART fill value. If false the data is converted into binary values using a linear conversion. The gain and offset are either specified in the metadata of the field with keywords 'scale_factor' and 'add_offset' or calculated on the fly. keyword '_Write_as_dtype' specifies the datatype. It can be either 'uint8' or 'uint16'. The default datatype is uint8. The 'undetected' parameter is not used

compression [str] The type of compression for the datasets. Typical are "gzip" and "lzf".

compression_opts [any] The compression options. In the case of gzip is the level between 0 to 9 (recomended 1 to 6). In the case of lzf there are not options.

PYART.AUX_IO.PATTERN

Routines for reading files from the X-band radar from the [PATTERN](#) project.

<code>read_pattern(filename, **kwargs)</code>	Read a netCDF file from a PATTERN project X-band radar.
---	---

`pyart.aux_io.pattern.read_pattern(filename, **kwargs)`
Read a netCDF file from a PATTERN project X-band radar.

Parameters

filename [str] Name of netCDF file to read data from.

Returns

radar [Radar] Radar object.

PYART.AUX_IO.RAD4ALP_BIN_READER

Routines for putting MeteoSwiss operational radar data contained in binary files into grid object.

`read_bin(filename[, additional_metadata, ...])` Read a MeteoSwiss operational radar data binary file.

```
pyart.aux_io.rad4alp_bin_reader.read_bin(filename, additional_metadata=None,
                                           chy0=255.0, chx0=-160.0, xres=1.0, yres=1.0,
                                           nx=710, ny=640, nz=1, **kwargs)
```

Read a MeteoSwiss operational radar data binary file.

Parameters

filename [str] Name of the file to read.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

chy0, chx0 [float] Swiss coordinates position of the south-western point in the grid

xres, yres [float] resolution of each grid point [km]

nx, ny, nz [int] dimensions of the grid

Returns

grid [Grid] Grid object containing data the data.

PYART.AUX_IO.RAD4ALP_GIF_READER

Routines for putting MeteoSwiss operational radar data contained in gif files into grid object.

<code>read_gif(filename[, additional_metadata, ...])</code>	Read a MeteoSwiss operational radar data gif file.
<code>_get_metadata(raw_metadata)</code>	puts metadata in a dictionary
<code>_get_datatype_from_file(filename)</code>	gets data type from file name
<code>_get_physical_data(rgba_data, datatype, ...)</code>	gets data in physical units

`pyart.aux_io.rad4alp_gif_reader._get_datatype_from_file(filename)`
gets data type from file name

Parameters

filename [str] base name of the file

Returns

datatype [str] Data type contained in the file

`pyart.aux_io.rad4alp_gif_reader._get_metadata(raw_metadata)`
puts metadata in a dictionary

Parameters

raw_metadata [str] dictionary

Returns

datatype [str] Data type contained in the file

`pyart.aux_io.rad4alp_gif_reader._get_physical_data(rgba_data, datatype, prod_time)`
gets data in physical units

Parameters

rgba_data [uint8 ndarray] the data as 4 channel rgba

datatype [str] The data type

prod_time [datetime object] The date at which the product was generated

Returns

data [float ndarray] the data in physical units

`pyart.aux_io.rad4alp_gif_reader.read_gif(filename, additional_metadata=None,
chy0=255.0, chx0=-160.0, xres=1.0, yres=1.0,
nx=710, ny=640, nz=1, **kwargs)`

Read a MeteoSwiss operational radar data gif file.

Parameters

filename [str] Name of the file to read.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

chy0, chx0 [float] Swiss coordinates position of the south-western point in the grid

xres, yres [float] resolution of each grid point [km]

nx, ny, nz [int] dimensions of the grid

Returns

grid [Grid] Grid object containing the data.

PYART.AUX_IO.RAINBOW_PSR

Routines for reading RAINBOW PSR files (Used by SELEX)

<code>read_iq(filename, filenames_iq[, ...])</code>	Read a rad4alp IQ file.
<code>read_iq_data(filename, ngates, npulses[, ...])</code>	Reads the IQ data

`pyart.aux_io.rad4alp_iq_reader.get_valid_rays(filenames_iq, ref_azi, ref_ele, ang_tol=0.4)`
Selects the IQ files corresponding to each ray azimuth and gets the number of pulses corresponding to each ray

Parameters

- filenames_iq** [list of str] List of files containing the IQ information of each ray
- ref_azi** [float array] The radar azimuths (deg)
- ref_ele** [int] The elevation of the current scan (deg)
- ang_tol** [float] The angle tolerance [deg] between the reference azimuth angle of the radar object and that of the IQ file

Returns

- filenames_iq_out** [array of strings] List of files containing IQ information for valid rays
- npulses_vec** [array of ints] Number of pulses for each ray

`pyart.aux_io.rad4alp_iq_reader.read_iq(filename, filenames_iq, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, reader='C', nbytes=4, prf=None, ang_tol=0.4, noise_h=None, noise_v=None, rconst_h=None, rconst_v=None, radconst_h=None, radconst_v=None, mfloss_h=1.0, mfloss_v=1.0, azi_min=None, azi_max=None, ele_min=None, ele_max=None, rng_min=None, rng_max=None, **kwargs)`

Read a rad4alp IQ file.

Parameters

- filename** [str] Name of the METRANET file to be used as reference.
- filenames_iq** [list of str] Name of the IQ files
- field_names** [dict, optional] Dictionary mapping RAINBOW field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it

will not be placed in the `radar.fields` dictionary. A value of `None`, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of `None`, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the `field_names` parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to `None` to include all fields specified by `include_fields`.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to `None` to include all fields not specified by `exclude_fields`.

reader [str] The library used to read the METRANET reference file. Can be either 'C' or 'python'

nbytes [int] The number of bytes used to store the data in numpy arrays, e.g. if `nbytes=4` then floats are going to be stored as `np.float32`

prf [float] The PRF of the read scan

ang_tol [float] Tolerated angle distance between nominal radar angle and angle in PSR files

noise_h, noise_v [float] The estimated H(V) noise power (ADU) of the scan

rconst_h, rconst_v [float] Dynamical factor used in the conversion from dBADU to dBm/dBZ

radconst_h, radconst_v [float] The H(V) radar constant

mfloss_h, mfloss_v [float] The H(V) matched filter losses in the receiver (dB)

azi_min, azi_max, ele_min, ele_max [float or None] The minimum and maximum angles to keep (deg)

rng_min, rng_max [float or None] The minimum and maximum ranges to keep (m)

Returns

radar [Radar] Radar object containing data from PSR file.

`pyart.aux_io.rad4alp_iq_reader.read_iq_data(filename, ngates, npulses, nchannels=2)`
Reads the IQ data

Parameters

filename [str] Name of file containing the IQ data of a ray

ngates [int] Number of gates in ray

npulses [int] Number of pulses in ray

nchannels [int] Number of channels in file

Returns

data_hh, data_vv [2D array] arrays containing the HH and VV channels IQ data

PYART.AUX_IO.RADX

Reading files using Radx to first convert the file to Cf.Radial format

<code>read_radx(filename[, radx_dir])</code>	Read a file by first converting it to Cf/Radial using RadxConvert.
--	--

`pyart.aux_io.radx.read_radx(filename, radx_dir=None, **kwargs)`
Read a file by first converting it to Cf/Radial using RadxConvert.

Parameters

filename [str] Name of file to read using RadxConvert.

radx_dir [str, optional] path to the radx install

Returns

radar [Radar] Radar object.

PYART.AUX_IO.RAINBOW_PSR

Routines for reading RAINBOW PSR files (Used by SELEX)

<i>read_rainbow_psr</i> (filename, filenames_psr[, ...])	Read a PSR file.
<i>read_rainbow_psr_spectra</i> (filename, filenames_psr)	Read a PSR file to get the complex spectra
<i>read_psr_header</i> (filename)	Read a PSR file header.
<i>read_psr_cpi_header</i> (filename)	Reads the CPI data headers contained in a PSR file
<i>read_psr_spectra</i> (filename)	Reads the complex spectral data contained in a PSR file
<i>get_item_numbers</i> (radar, azi_start, azi_stop, ...)	Gets the item numbers to be used and eventually modify the radar object to accomodate more angles
<i>get_field</i> (radar, cpi_header, header, items, ...)	Gets the field corresponding to the reference radar
<i>get_spectra_field</i> (radar, filenames, npulses, ...)	Gets the field corresponding to the reference radar
<i>get_Doppler_info</i> (prfs, npulses, wavelength)	Gets the Doppler information
<i>get_noise_field</i> (radar, field_data, header, ...)	Puts the noise field in the desired units
<i>convert_data</i> (values)	Converts an string of values into the corresponding format
<i>get_library</i> ()	return the link to C-shared library
<i>get_library_path</i> ()	find valid library path

`pyart.aux_io.rainbow_psr.change_rays` (*radar, moving_angle, fixed_angle, rays_per_sweep*)
Modify the radar object to accomodate new rays

Parameters

- radar** [radar object] the radar to modify
- moving_angle** [float array] The moving angles
- fixed_angle** [float array] The fixed angles
- rays_per_sweep** [array of ints] The number of rays per sweep

Returns

- new_radar** [radar object] The modified radar

`pyart.aux_io.rainbow_psr.convert_data` (*values*)
Converts an string of values into the corresponding format

Parameters

- values: str** string containg the values to convert

Returns

values [int, float, str or 1D array of int, float or str] The converted values

`pyart.aux_io.rainbow_psr.get_Doppler_info(prfs, npulses, wavelength, fold=True)`
Gets the Doppler information

Parameters

prfs: float array the PRF at each ray
npulses [float array] the number of pulses per ray
wavelength [float] the radar wavelength [m]
fold [Bool] If True the spectra is folded

Returns

Doppler_velocity, Doppler_frequency [2D float array] The Doppler velocity and Doppler frequency bins for each ray

`pyart.aux_io.rainbow_psr.get_field(radar, cpi_header, header, items, nprfs, field_name, undo_txcorr=True, cpi='low_prf')`
Gets the field corresponding to the reference radar

Parameters

radar: radar object the reference radar
cpi_header, header [dict] dictionaries containing the PSR file header and CPI headers data
items [int array] array containing the items to select
nprfs: float The number of different prfs in the file
field_name [str] The name of the field to filter
undo_txcorr [bool] If True and field is a noise field the correction of the received signal by the transmitted power is undone
cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf', 'all'. If 'all' the mean within the angle step is taken

Returns

field_data [2D float array] The PSR data in the format of the reference radar fields

`pyart.aux_io.rainbow_psr.get_item_numbers(radar, azi_start, azi_stop, ele_start, ele_stop, prf_array, prfs, cpi='low_prf', ang_tol=0.5)`
Gets the item numbers to be used and eventually modify the radar object to accomodate more angles

Parameters

radar: radar object the reference radar
azi_start, azi_stop, ele_start, ele_stop [float array] The start and stop angles of the CPI elements
prf_array: float array The PRF of each CPI element
prfs [float array] The unique PRFs contained in the PSR file
cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf', 'mean', 'all'. If 'mean' the mean within the angle step is taken. If 'all' the data is not filtered by PRF
ang_tol [float] Angle tolerance

Returns

items [int array] the item number selected

`pyart.aux_io.rainbow_psr.get_library()`
return the link to C-shared library

Returns

psr_lib [link] loaded PSR C-library

`pyart.aux_io.rainbow_psr.get_library_path()`
find valid library path

Returns

psr_lib_path [str] library path

`pyart.aux_io.rainbow_psr.get_noise_field(radar, field_data, header, field_name)`
Puts the noise field in the desired units

Parameters

radar: radar object the reference radar

field_data [2D float array] The PSR data in the format of the reference radar fields

header [dict] Dictionary containing the PSR file metadata

field_name [str] The name of the field

Returns

field_data [2D float array] The PSR data in the format of the reference radar fields

`pyart.aux_io.rainbow_psr.get_spectra_field(radar, filenames, npulses, items_per_file,
items, ind_rng, fold=True, positive_away=True)`
Gets the field corresponding to the reference radar

Parameters

radar: radar object the reference radar

filename [str] name of the PSR file

npulses [int array] array containing the number of pulses for each item

items_per_file [int array] array containing the number of items in each PSR file

items [int array] array containing the items to select

ind_rng [int array] array containing the indices to the range gates to select

fold [Bool] If True the spectra is folded

positive_away [Bool] If True positive Doppler velocities are way from the radar

Returns

spectra [3D complex float array] The complex spectra field

`pyart.aux_io.rainbow_psr.get_spectral_noise(radar, cpi_header, header, items,
undo_txcorr=True)`
Gets the field corresponding to the reference radar

Parameters

radar: radar object the reference radar

cpi_header, header [dict] dictionaries containing the PSR file header and CPI headers data

items [int array] array containing the items to select

field_name [str] The name of the field to filter

undo_txcrr [bool] If True and field is a noise field the correction of the received signal by the transmitted power is undone

Returns

field_data [2D float array] The PSR data in the format of the reference radar fields

`pyart.aux_io.rainbow_psr.read_psr_cpi_header(filename)`

Reads the CPI data headers contained in a PSR file

Parameters

filename [str] Name of the PSR file

Returns

cpi_header, header [dict] Dictionary containing the PSR header data and the CPI headers data

`pyart.aux_io.rainbow_psr.read_psr_cpi_headers(filenames)`

Reads the CPI data headers contained in multiple PSR files

Parameters

filenames [list of str] Name of the PSR files

Returns

cpi_header, header [dict] Dictionary containing the PSR header data and the CPI headers data

`pyart.aux_io.rainbow_psr.read_psr_header(filename)`

Read a PSR file header.

Parameters

filename [str] Name of the PSR file

Returns

header [dict] Dictionary containing the PSR header data

`pyart.aux_io.rainbow_psr.read_psr_spectra(filename)`

Reads the complex spectral data contained in a PSR file

Parameters

filename [str] Name of the PSR file

Returns

spectra [3D complex ndarray] The complex spectra

`pyart.aux_io.rainbow_psr.read_rainbow_psr(filename, filenames_psr, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, undo_txcrr=True, cpi='mean', ang_tol=0.5, azi_min=None, azi_max=None, ele_min=None, ele_max=None, rng_min=None, rng_max=None, **kwargs)`

Read a PSR file.

Parameters

filename [str] Name of the rainbow file to be used as reference.

filenames_psr [list of str] Name of the PSR files

field_names [dict, optional] Dictionary mapping RAINBOW field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

undo_txcrr: **Bool** If True the correction of the transmitted power is removed from the noise signal

cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf', 'mean', 'all'. If 'mean' the mean within the angle step is taken

ang_tol [float] Tolerated angle distance between nominal radar angle and angle in PSR files

azi_min, azi_max, ele_min, ele_max [float or None] The minimum and maximum angles to keep (deg)

rng_min, rng_max [float or None] The minimum and maximum ranges to keep (m)

Returns

radar [Radar] Radar object containing data from PSR file.

```
pyart.aux_io.rainbow_psr.read_rainbow_psr_spectra(filename, filenames_psr,
                                                    field_names=None, ad-
                                                    ditional_metadata=None,
                                                    file_field_names=False,
                                                    exclude_fields=None,
                                                    include_fields=None,
                                                    undo_txcrr=True, fold=True, pos-
                                                    itive_away=True, cpi='low_prf',
                                                    ang_tol=0.5, azi_min=None,
                                                    azi_max=None, ele_min=None,
                                                    ele_max=None, rng_min=None,
                                                    rng_max=None, **kwargs)
```

Read a PSR file to get the complex spectra

Parameters

filename [str] Name of the rainbow file to be used as reference.

filenames_psr [list of str] list of PSR file names

field_names [dict, optional] Dictionary mapping RAINBOW field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it

will not be placed in the `radar.fields` dictionary. A value of `None`, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of `None`, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the `field_names` parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to `None` to include all fields specified by `include_fields`.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to `None` to include all fields not specified by `exclude_fields`.

undo_txcrr: **Bool** If True the correction of the transmitted power is removed from the noise signal

fold: **Bool** If True the spectra is folded so that 0-Doppler is in the middle

positive_away: **Bool** If True the spectra is reversed so that positive velocities are away from the radar

cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf' or 'all'

ang_tol [float] Tolerated angle distance between nominal radar angle and angle in PSR files

azi_min, azi_max, ele_min, ele_max [float or None] The minimum and maximum angles to keep (deg)

rng_min, rng_max [float or None] The minimum and maximum ranges to keep (m)

Returns

radar [Radar] Radar object containing data from PSR file.

PYART.AUX_IO.RAINBOW

Routines for reading RAINBOW files (Used by SELEX) using the wradlib library

<code>read_rainbow_wrl(filename[, field_names, ...])</code>	Read a RAINBOW file.
<code>_get_angle(ray_info[, angle_step, ...])</code>	obtains the ray angle start, stop and center
<code>_get_data(rawdata, nrays, nbins[, dtype])</code>	Obtains the raw data
<code>_get_time(date_sweep, time_sweep, ...[, ...])</code>	Computes the time at the center of each ray

`pyart.aux_io.rainbow_wrl._get_angle` (*ray_info*, *angle_step=None*, *scan_type='ppi'*,
dtype=<class 'numpy.float32'>)
obtains the ray angle start, stop and center

Parameters

- ray_info** [dictionary of dictionaries] contains the ray info
- angle_step** [float] Optional. The angle step. Used in case there is no information of angle stop. Otherwise ignored.
- scan_type** [str] Default ppi. scan_type. Either ppi or rhi.
- dtype** [numpy data type object] The data type of the numpy array where the angles are stored

Returns

- moving_angle** [numpy array] the central point of the angle [Deg]
- angle_start** : the starting point of the angle [Deg]
- angle_stop** : the end point of the angle [Deg]

`pyart.aux_io.rainbow_wrl._get_data` (*rawdata*, *nrays*, *nbins*, *dtype=<class 'numpy.float32'>*)
Obtains the raw data

Parameters

- rawdata** [dictionary of dictionaries] contains the raw data information
- nrays** [int] Number of rays in sweep
- nbins** [int] Number of bins in ray
- dtype** [numpy data type object] The data type of the numpy array where the data is stored

Returns

- data** [numpy array] the data

```
pyart.aux_io.rainbow_wrl._get_time(date_sweep,      time_sweep,      first_angle_start,
                                   last_angle_stop,  angle_step,    nrays,    ant_speed,
                                   scan_type='ppi')
```

Computes the time at the center of each ray

Parameters

date_sweep, time_sweep [str] the date and time of the sweep

first_angle_start [float] The starting point of the first angle in the sweep

last_angle_stop [float] The end point of the last angle in the sweep

nrays [int] Number of rays in sweep

ant_speed [float] antenna speed [deg/s]

scan_type [str] Default ppi. scan_type. Either ppi or rhi.

Returns

time_data [numpy array] the time of each ray since sweep start

sweep_start [datetime object] sweep start time

```
pyart.aux_io.rainbow_wrl.read_rainbow_wrl(filename,
                                           field_names=None,
                                           additional_metadata=None,
                                           file_field_names=False, exclude_fields=None,
                                           include_fields=None, nbytes=4, **kwargs)
```

Read a RAINBOW file. This routine has been tested to read rainbow5 files version 5.22.3, 5.34.16 and 5.35.1. Since the rainbow file format is evolving constantly there is no guaranty that it can work with other versions. If necessary, the user should adapt to code according to its own file version and raise an issue upstream.

Data types read by this routine: Reflectivity: dBZ, dBuZ, dBZv, dBuZv Velocity: V, Vu, Vv, Vvu Spectrum width: W, Wu, Wv, Wvu Differential reflectivity: ZDR, ZDRu Co-polar correlation coefficient: RhoHV, Rho-HVu Co-polar differential phase: PhiDP, uPhiDP, uPhiDPu Specific differential phase: KDP, uKDP, uKDPu Signal quality parameters: SQI, SQIu, SQIv, SQIvu Temperature: TEMP Position of the range bin respect to the ISO0: ISO0 radar visibility according to Digital Elevation Model (DEM): VIS

Parameters

filename [str] Name of the RAINBOW file to read.

field_names [dict, optional] Dictionary mapping RAINBOW field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by include_fields.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by exclude_fields.

nbytes [int] The number of bytes used to store the data in numpy arrays, e.g. if nbytes=4 then floats are going to be stored as np.float32

Returns

radar [Radar] Radar object containing data from RAINBOW file.

PYART.AUX_IO.SINARAME_H5

Routines for reading sinarame_H5 files.

<code>read_sinarame_h5(filename[, field_names, ...])</code>	Read a SINARAME_H5 file.
<code>write_sinarame_cfradial(path)</code>	This function takes SINARAME_H5 files (where every file has only one field and one volume) from a folder and writes a CfRadial file for each volume including all fields.
<code>_to_str(text)</code>	Convert bytes to str if necessary.
<code>_get_SINARAME_h5_sweep_data(group)</code>	Get SINARAME_H5 sweep data from an HDF5 group.

`pyart.aux_io.sinarame_h5._get_SINARAME_h5_sweep_data(group)`

Get SINARAME_H5 sweep data from an HDF5 group.

`pyart.aux_io.sinarame_h5._to_str(text)`

Convert bytes to str if necessary.

`pyart.aux_io.sinarame_h5.read_sinarame_h5(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, include_fields=None, **kwargs)`

Read a SINARAME_H5 file.

Parameters

filename [str] Name of the SINARAME_H5 file to read.

field_names [dict, optional] Dictionary mapping SINARAME_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata [dict of dicts, optional] Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names [bool, optional] True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields specified by *include_fields*.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the *file_field_names* and *field_names* parameters. Set to None to include all fields not specified by *exclude_fields*.

Returns

radar [Radar] Radar object containing data from SINARAME_H5 file.

`pyart.aux_io.sinarame_h5.write_sinarame_cfradial` (*path*)

This function takes SINARAME_H5 files (where every file has only one field and one volume) from a folder and writes a CfRadial file for each volume including all fields.

Parameters

path [str] Where the SINARAME_H5 files are.

PYART.IO.SPECTRA

Utilities for reading spectra netcdf files.

<code>read_spectra(filename[, field_names, ...])</code>	Read a spectra netCDF file.
<code>write_spectra(filename, radar[, format, ...])</code>	Write a Radar Spectra object to a netCDF file.

`pyart.aux_io.spectra.read_spectra` (*filename*, *field_names=None*, *additional_metadata=None*,
file_field_names=False, *exclude_fields=None*, *include_fields=None*, *delay_field_loading=False*, ***kwargs*)

Read a spectra netCDF file.

Parameters

filename [str] Name of CF/Radial netCDF file to read data from.

field_names [dict, optional] Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the `radar.fields` dictionary, to exclude them use the `exclude_fields` parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata [dict of dicts, optional] This parameter is not used, it is included for uniformity.

file_field_names [bool, optional] True to force the use of the field names from the file in which case the `field_names` parameter is ignored. False will use to `field_names` parameter to rename fields.

exclude_fields [list or None, optional] List of fields to exclude from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields specified by `include_fields`.

include_fields [list or None, optional] List of fields to include from the radar object. This is applied after the `file_field_names` and `field_names` parameters. Set to None to include all fields not specified by `exclude_fields`.

delay_field_loading [bool] True to delay loading of field data from the file until the ‘data’ key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Delayed field loading will not provide any speedup in file where the number of gates vary between rays (`ngates_vary=True`) and is not recommended.

Returns

radar [Radar] Radar object.

Notes

This function has not been tested on “stream” Cfradial files.

```
pyart.aux_io.spectra.write_spectra(filename, radar, format='NETCDF4',  
                                   time_reference=None, arm_time_variables=False,  
                                   physical=True)
```

Write a Radar Spectra object to a netCDF file.

The files produced by this routine follow the [CF/Radial standard](#). Attempts are also made to to meet many of the standards outlined in the [ARM Data File Standards](#).

To control how the netCDF variables are created, set any of the following keys in the radar attribute dictionaries.

- `_Zlib`
- `_DeflateLevel`
- `_Shuffle`
- `_Fletcher32`
- `_Contiguous`
- `_ChunkSizes`
- `_Endianness`
- `_Least_significant_digit`
- `_FillValue`

See the netCDF4 documentation for details on these settings.

Parameters

filename [str] Filename to create.

radar [Radar] Radar object.

format [str, optional] NetCDF format, one of ‘NETCDF4’, ‘NETCDF4_CLASSIC’, ‘NETCDF3_CLASSIC’ or ‘NETCDF3_64BIT’. See netCDF4 documentation for details.

time_reference [bool] True to include a time_reference variable, False will not include this variable. The default, None, will include the time_reference variable when the first time value is non-zero.

arm_time_variables [bool] True to create the ARM standard time variables base_time and time_offset, False will not create these variables.

physical [bool] True to store the radar fields as physical numbers, False will store the radar fields as binary if the keyword ‘_Write_as_dtype’ is in the field metadata. The gain and offset can be specified in the keyword ‘scale_factor’ and ‘add_offset’ or calculated on the fly.

PYART.CORRECT.ATTENUATION

Attenuation correction from polarimetric radars. Code adapted from method in Gu et al, JAMC 2011, 50, 39. Adapted by Scott Collis and Scott Giangrande, refactored by Jonathan Helmus. New code added by Meteo Swiss and inserted into Py-ART by Robert Jackson.

<code>calculate_attenuation(radar, z_offset[, ...])</code>	Calculate the attenuation from a polarimetric radar using Z-PHI method.
<code>calculate_attenuation_zphi(radar[, doc, ...])</code>	Calculate the attenuation and the differential attenuation from a polarimetric radar using Z-PHI method..
<code>calculate_attenuation_philinear(radar[, ...])</code>	Calculate the attenuation and the differential attenuation from a polarimetric radar using linear dependence with PhiDP.
<code>get_mask_fzl(radar[, fzl, doc, min_temp, ...])</code>	Constructs a mask to mask data placed thickness m below data at min_temp and beyond.
<code>_prepare_phidp(phidp, mask_fzl)</code>	Prepares phidp to be used in attenuation correction by masking values above freezing level setting negative values to 0 and make sure it is monotonously increasing.
<code>_get_param_attzphi(freq)</code>	Get the parameters of Z-Phi attenuation estimation for a particular frequency.
<code>_param_attzphi_table()</code>	Defines the parameters of Z-Phi attenuation estimation at each frequency band.
<code>_get_param_attphilinear(freq)</code>	Get the parameters of attenuation estimation based on phidp for a particular frequency.
<code>_param_attphilinear_table()</code>	Defines the parameters of attenuation estimation based on phidp at each frequency band.

`pyart.correct.attenuation._get_param_attphilinear(freq)`

Get the parameters of attenuation estimation based on phidp for a particular frequency.

Parameters

freq [float] Radar frequency [Hz].

Returns

a_coeff, beta, c, d [floats] The coefficient and exponent of the power law.

`pyart.correct.attenuation._get_param_attzphi(freq)`

Get the parameters of Z-Phi attenuation estimation for a particular frequency.

Parameters

freq [float] Radar frequency [Hz].

Returns

a_coeff, beta, c, d [floats] The coefficient and exponent of the power law.

`pyart.correct.attenuation._param_attphilinear_table()`

Defines the parameters of attenuation estimation based on phidp at each frequency band.

Returns

param_att_dict [dict] A dictionary with the coefficients at each band.

`pyart.correct.attenuation._param_attzphi_table()`

Defines the parameters of Z-Phi attenuation estimation at each frequency band.

Returns

param_att_dict [dict] A dictionary with the coefficients at each band.

`pyart.correct.attenuation._prepare_phidp(phidp, mask_fzl)`

Prepares phidp to be used in attenuation correction by masking values above freezing level setting negative values to 0 and make sure it is monotonously increasing.

Parameters

phidp [ndarray 2D] The phidp field.

mask_fzl [ndarray 2D] A mask of the data above freezing level height.

Returns

corr_phidp: ndarray 2D The corrected PhiDP field.

`pyart.correct.attenuation.calculate_attenuation(radar, z_offset, debug=False, doc=15, fzl=4000.0, rhv_min=0.8, ncp_min=0.5, a_coef=0.06, beta=0.8, refl_field=None, ncp_field=None, rhv_field=None, phidp_field=None, spec_at_field=None, corr_refl_field=None)`

Calculate the attenuation from a polarimetric radar using Z-PHI method. Parameters ——— radar : Radar

Radar object to use for attenuation calculations. Must have copol_coeff, norm_coherent_power, proc_dp_phase_shift, reflectivity_horizontal fields.

z_offset [float] Horizontal reflectivity offset in dBZ.

debug [bool, optional] True to print debugging information, False suppressed this printing.

doc [float, optional] Number of gates at the end of each ray to remove from the calculation.

fzl [float, optional] Freezing layer, gates above this point are not included in the correction.

rhv_min [float, optional] Minimum copol_coeff value to consider valid.

ncp_min [float, optional] Minimum norm_coherent_power to consider valid.

a_coef [float, optional] A coefficient in attenuation calculation.

beta [float, optional] Beta parameter in attenuation calculation.

refl_field [str, optional] Name of the reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

phidp_field [str, optional] Name of the differential phase field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

nco_field [str, optional] Name of the normalized coherent power field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

zdr_field [str, optional] Name of the differential reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. This will only be used if it is available.

spec_at_field [str, optional] Name of the specific attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

corr_refl_field [str, optional] Name of the corrected reflectivity field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

Returns

spec_at [dict] Field dictionary containing the specific attenuation.

cor_z [dict] Field dictionary containing the corrected reflectivity.

References

Gu et al. Polarimetric Attenuation Correction in Heavy Rain at C Band, JAMC, 2011, 50, 39-58.

```
pyart.correct.attenuation.calculate_attenuation_philinear(radar, doc=None,
                                                         fzl=None,
                                                         pia_coef=None,
                                                         gatefilter=None,
                                                         pida_coef=None,
                                                         refl_field=None,
                                                         phidp_field=None,
                                                         zdr_field=None,
                                                         temp_field=None,
                                                         iso0_field=None,
                                                         spec_at_field=None,
                                                         pia_field=None,
                                                         corr_refl_field=None,
                                                         spec_diff_at_field=None,
                                                         pida_field=None,
                                                         corr_zdr_field=None,
                                                         temp_ref='temperature')
```

Calculate the attenuation and the differential attenuation from a polarimetric radar using linear dependence with PhiDP. The attenuation is computed up to a user defined freezing level height, where temperatures in a temperature field are positive or where the height relative to the iso0 is 0. The coefficients are either user-defined or radar frequency dependent.

Parameters

radar [Radar] Radar object to use for attenuation calculations. Must have phidp and refl fields.

doc [float, optional] Number of gates at the end of each ray to remove from the calculation.

fzl [float, optional] Freezing layer, gates above this point are not included in the correction.

gatefilter [GateFilter, optional] The gates to exclude from the calculation. This, combined with the gates above fzl, will be excluded from the correction. Set to None to not use a gatefilter.

pia_coef [float, optional] Coefficient in path integrated attenuation calculation

pida_coeff [float, optional] Coefficient in path integrated differential attenuation calculation

refl_field [str, optional] Name of the reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

phidp_field [str, optional] Name of the differential phase field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

zdr_field [str, optional] Name of the differential reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. This will only be used if it is available.

temp_field [str, optional] Name of the temperature field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

iso0_field [str, optional] Name of the field for the height above the 0C isotherm for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. This will only be used if it is available.

spec_at_field [str, optional] Name of the specific attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

pia_field [str, optional] Name of the path integrated attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

corr_refl_field [str, optional] Name of the corrected reflectivity field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

spec_diff_at_field [str, optional] Name of the specific differential attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. This will only be calculated if ZDR is available.

corr_zdr_field [str, optional] Name of the corrected differential reflectivity field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. This will only be calculated if ZDR is available.

temp_ref [str, optional] The field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl.

Returns

spec_at [dict] Field dictionary containing the specific attenuation.

pia_dict [dict] Field dictionary containing the path integrated attenuation.

cor_z [dict] Field dictionary containing the corrected reflectivity.

spec_diff_at [dict] Field dictionary containing the specific differential attenuation.

pida_dict [dict] Field dictionary containing the path integrated differential attenuation.

cor_zdr [dict] Field dictionary containing the corrected differential reflectivity.

```
pyart.correct.attenuation.calculate_attenuation_zphi (radar, doc=None, fzl=None,
                                                    smooth_window_len=5, gate-
                                                    filter=None, a_coef=None,
                                                    beta=None, c=None,
                                                    d=None, refl_field=None,
                                                    phidp_field=None,
                                                    zdr_field=None,
                                                    temp_field=None,
                                                    iso0_field=None,
                                                    spec_at_field=None,
                                                    pia_field=None,
                                                    corr_refl_field=None,
                                                    spec_diff_at_field=None,
                                                    pida_field=None,
                                                    corr_zdr_field=None,
                                                    temp_ref='temperature')
```

Calculate the attenuation and the differential attenuation from a polarimetric radar using Z-PHI method.. The attenuation is computed up to a user defined freezing level height or up to where temperatures in a temperature field are positive. The coefficients are either user-defined or radar frequency dependent.

Parameters

radar [Radar] Radar object to use for attenuation calculations. Must have phidp and refl fields.

doc [float, optional] Number of gates at the end of each ray to to remove from the calculation.

fzl [float, optional] Freezing layer, gates above this point are not included in the correction.

gatefilter [GateFilter, optional] The gates to exclude from the calculation. This, combined with the gates above fzl, will be excluded from the correction. Set to None to not use a gatefilter.

smooth_window_len [int, optional] Size, in range bins, of the smoothing window

a_coef [float, optional] A coefficient in attenuation calculation.

beta [float, optional] Beta parameter in attenuation calculation.

c, d [float, optional] coefficient and exponent of the power law that relates attenuation with differential attenuation

refl_field [str, optional] Name of the reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

phidp_field [str, optional] Name of the differential phase field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

zdr_field [str, optional] Name of the differential reflectivity field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. This will only be used if it is available.

temp_field [str, optional] Name of the temperature field used for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

iso0_field [str, optional] Name of the field for the height above the 0C isotherm for the attenuation correction. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. This will only be used if it is available.

spec_at_field [str, optional] Name of the specific attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

pia_field [str, optional] Name of the path integrated attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

corr_refl_field [str, optional] Name of the corrected reflectivity field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

spec_diff_at_field [str, optional] Name of the specific differential attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. This will only be calculated if ZDR is available.

pida_field [str, optional] Name of the path integrated differential attenuation field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. This will only be calculated if ZDR is available.

corr_zdr_field [str, optional] Name of the corrected differential reflectivity field that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. This will only be calculated if ZDR is available.

temp_ref [str, optional] the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns

spec_at [dict] Field dictionary containing the specific attenuation.

pia_dict [dict] Field dictionary containing the path integrated attenuation.

cor_z [dict] Field dictionary containing the corrected reflectivity.

spec_diff_at [dict] Field dictionary containing the specific differential attenuation.

pida_dict [dict] Field dictionary containing the path integrated differential attenuation.

cor_zdr [dict] Field dictionary containing the corrected differential reflectivity.

References

Gu et al. Polarimetric Attenuation Correction in Heavy Rain at C Band, JAMC, 2011, 50, 39-58.

Ryzhkov et al. Potential Utilization of Specific Attenuation for Rainfall Estimation, Mitigation of Partial Beam Blockage, and Radar Networking, JAOT, 2014, 31, 599-619.

```
pyart.correct.attenuation.get_mask_fzl(radar, fzl=None, doc=None, min_temp=0.0,
                                     max_h_iso0=0.0, thickness=None,
                                     beamwidth=None, temp_field=None,
                                     iso0_field=None, temp_ref='temperature')
```

Constructs a mask to mask data placed thickness m below data at min_temp and beyond.

Parameters

radar [Radar] The radar object.

fzl [float, optional] Freezing layer, gates above this point are not included in the correction.

doc [float, optional] Number of gates at the end of each ray to to remove from the calculation.

min_temp [float, optional] Minimum temperature below which the data is mask in degrees.

max_h_iso0 [float, optional] Maximum height relative to the iso0 below which the data is mask in meters.

thickness [float, optional] Extent of the layer below the first gate where min_temp is reached that is going to be masked.

beamwidth [float, optional] The radar antenna 3 dB beamwidth.

temp_field: str, optional The temperature field. A value of None will use the default field name as defined in the Py-ART configuration file. It is going to be used only if available.

iso0_field: str, optional The field containing the height over the 0C isotherm. A value of None will use the default field name as defined in the Py-ART configuration file. It is going to be used only if available.

temp_ref [str, optional] The field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl.

Returns

mask_fzl [2D array] The values that should be masked.

end_gate_arr [1D array] The index of the last valid gate in the ray.

PYART.CORRECT.BIAS_AND_NOISE

Corrects polarimetric variables for noise

<i>correct_noise_rhohv</i> (radar[, urhohv_field, ...])	Corrects RhoHV for noise according to eq.
<i>correct_bias</i> (radar[, bias, field_name])	Corrects a radar data bias.
<i>correct_visibility</i> (radar[, vis_field, ...])	Corrects the reflectivity according to visibility.
<i>get_sun_hits</i> (radar[, elev_max, azim_max, ...])	get data from suspected sun hits.
<i>get_sun_hits_ivic</i> (radar[, elev_max, ...])	get data from suspected sun hits.
<i>sun_retrieval</i> (az_rad, az_sun, el_rad, ..., ...)	Estimates sun parameters from sun hits
<i>est_rhohv_rain</i> (radar[, ind_rmin, ind_rmax, ...])	Estimates the quantiles of RhoHV in rain for each sweep
<i>est_zdr_precip</i> (radar[, ind_rmin, ind_rmax, ...])	Filters out all undesired data to be able to estimate ZDR bias, either in moderate rain or from vertically pointing scans
<i>est_zdr_snow</i> (radar[, ind_rmin, ind_rmax, ...])	Filters out all undesired data to be able to estimate ZDR bias in snow
<i>selfconsistency_bias</i> (radar, zdr_kdpzh_dict)	Estimates reflectivity bias at each ray using the self-consistency algorithm by Gourley
<i>selfconsistency_bias2</i> (radar, zdr_kdpzh_dict)	Estimates reflectivity bias at each ray using the self-consistency algorithm by Gourley
<i>selfconsistency_kdp_phidp</i> (radar, zdr_kdpzh_dict)	Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP.
<i>get_kdp_selfcons</i> (zdr, refl, ele_vec, ..., ...)	Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP
<i>_est_sun_hit_pwr_hs</i> (pwr, sun_hit, attg_sun, ...)	estimates sun hit power, standard deviation, and number and position of affected range bins in a ray.
<i>_est_sun_hit_pwr_ivic</i> (pwr, sun_hit, ...)	estimates sun hit power, standard deviation, and number and position of affected range bins in a ray.
<i>_est_sun_hit_zdr</i> (zdr, sun_hit_zdr, ...)	estimates sun hit ZDR, standard deviation, and number and position of affected range bins in a ray
<i>_selfconsistency_kdp_phidp</i> (radar, refl, zdr, ...)	Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP.

`pyart.correct.bias_and_noise._est_sun_hit_pwr_hs` (*pwr*, *sun_hit*, *attg_sun*, *max_std*,
nbins_min, *ind_rmin*)
estimates sun hit power, standard deviation, and number and position of affected range bins in a ray. Uses Hildebrand and Sekhon 1974 to estimate the sun hit power.

Parameters

pwr [1D float array] the power at each range bin in a ray

sun_hit [1D float array] array used to flag sun hit range bins

attg_sun [float] attenuation suffered by the sun signal from the top of the atmosphere to the radar position

max_std [float] maximum standard deviation to consider the sun hit valid

nbins_min [int] minimum number of range gates with valid signal in the ray to consider the ray affected by a noise-like signal

ind_rmin [int] minimum range from which we can look for noise

Returns

sunpwr_dBm [float] the estimated sun power

sunpwr_std [float] the standard deviation of the estimation in dB

sunpwr_npoints [int] the number of range gates affected by the sun hit

nvalid [int] the number of valid range gates

sun_hit [1D array] array with flagged range bins

```
pyart.correct.bias_and_noise._est_sun_hit_pwr_ivic(pwr, sun_hit, attg_sun, pct,  
                                                    flat_reg_wlen, flat_reg_var_max,  
                                                    snr_thr, npulses, ngates_min,  
                                                    iterations)
```

estimates sun hit power, standard deviation, and number and position of affected range bins in a ray. Uses Ivic et al 2013 to estimate the sun hit power.

Parameters

pwr [1D float array] the power at each range bin in a ray

sun_hit [1D float array] array used to flag sun hit range bins

attg_sun [float] attenuation suffered by the sun signal from the top of the atmosphere to the radar position

pct [float] Point Clutter Threshold

flat_reg_wlen [int] Minimum number of gates that should contain a valid region. Default gives a size of 8 km with 83.3 m resolution

flat_reg_var_max [float] Maximum local variance of powers in decibels to consider the region as flat.

snr_thr [float] Threshold applied in steps 3 and 6

npulses [int] Number of pulses used to compute the power of the array

ngates_min: int minimum number of gates with noise to consider the retrieval valid

iterations: int number of iterations in step 7

Returns

sunpwr_dBm [float] the estimated sun power

sunpwr_std [float] the standard deviation of the estimation in dB

sunpwr_npoints [int] the number of range gates affected by the sun hit

nvalid [int] the number of valid range gates

sun_hit [1D array] array with flagged range bins

`pyart.correct.bias_and_noise._est_sun_hit_zdr(zdr, sun_hit_zdr, sun_hit_h, sun_hit_v, max_std, nbins_min, ind_rmin)`
 estimates sun hit ZDR, standard deviation, and number and position of affected range bins in a ray

Parameters

zdr [1D float array] the ZDR at each range bin in a ray
sun_hit_zdr [1D float array] array used to flag sun hit range bins
sun_hit_h, sun_hit_v [1D float array] The position of sun hit range bins in each channel
max_std [float] maximum standard deviation
nbins_min [int] minimum number of range gates with valid signal in the ray to consider the ray affected by a noise-like signal
ind_rmin [int] minimum range from which we can look for noise

Returns

sunzdr [float] the estimated sun power
sunzdr_std [float] the standard deviation of the estimation in dB
sunzdr_npoints [int] the number of range gates affected by the sun hit
sun_hit_zdr [1D array] array with flagged range bins

`pyart.correct.bias_and_noise._selfconsistency_kdp_phidp(radar, refl, zdr, phidp, zdr_kdpzh_dict, max_phidp=20.0, smooth_wind_len=5, rhohv=None, min_rhohv=None, min_zdr=0.0, hydro=None, filter_rain=True, doc=None, fzl=None, thickness=700.0, parametrization='None', temp_field=None, iso0_field=None, temp_ref='temperature')`

Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP. Private method

Parameters

radar [Radar] radar object
refl, zdr, phidp [ndarray 2D] reflectivity field, differential reflectivity field and differential phase field. They must exist
zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations
max_phidp [float] maximum PhiDP value to consider the data valid
smooth_wind_len [int] length of the smoothing window for Zh and ZDR data
rhohv [ndarray 2D] copolar correlation field used for masking data. Optional
min_rhohv [float] minimum RhoHV value to consider the data valid

min_zdr [float] minimum ZDR value to consider the data valid

hydro [ndarray 2D] hydrometer classification field used for masking data. Optional

filter_rain [Bool] If true gates not classified as rain are going to be removed from the data

doc [float] Number of gates at the end of each ray to to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

thickness [float] Assumed thickness of the melting layer [m]

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in `zdr_kdpzh_dict`.

temp_field, iso0_field, hydro_field [str] Field name within the radar object which represent the temperature, the height relative to the iso0 and the hydrometeor classification fields. A value of None will use the default field name as defined in the Py-ART configuration file. It is going to be used only if available.

temp_ref [str] the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns

kdp_sim, phidp_sim [ndarray 2D] the KDP and PhiDP estimated fields

`pyart.correct.bias_and_noise.correct_bias(radar, bias=0.0, field_name=None)`

Corrects a radar data bias. If field name is none the correction is applied to horizontal reflectivity by default.

Parameters

radar [Radar] Radar object.

bias [float, optional] The bias magnitude.

field_name: str, optional Names of the field to be corrected.

Returns

corrected_field [dict] The corrected field

`pyart.correct.bias_and_noise.correct_noise_rhohv(radar, urhohv_field=None, snr_field=None, zdr_field=None, nh_field=None, nv_field=None, rhohv_field=None)`

Corrects RhoHV for noise according to eq. 6 in Gourley et al. 2006. This correction should only be performed if noise has not been subtracted from the signal during the moments computation.

Parameters

radar [Radar] Radar object.

urhohv_field [str, optional] Name of the RhoHV uncorrected for noise field.

snr_field, zdr_field, nh_field, nv_field [str, optional] Names of the SNR, ZDR, horizontal channel noise in dBZ and vertical channel noise in dBZ used to correct RhoHV.

rhohv_field [str, optional] Name of the rhohv field to output.

Returns

rhohv [dict] Noise corrected RhoHV field.

References

Gourley et al. Data Quality of the Meteo-France C-Band Polarimetric Radar, JAOT, 23, 1340-1356

`pyart.correct.bias_and_noise.correct_visibility` (*radar*, *vis_field=None*,
field_name=None)

Corrects the reflectivity according to visibility. Applied to horizontal reflectivity by default

Parameters

radar [Radar] radar object

vis_field [str] the name of the visibility field

field_name: str names of the field to be corrected

Returns

corrected_field [dict] The corrected field

`pyart.correct.bias_and_noise.est_rhohv_rain` (*radar*, *ind_rmin=10*, *ind_rmax=500*,
zmin=20.0, *zmax=40.0*, *thickness=700.0*,
doc=None, *fzl=None*, *rhohv_field=None*,
temp_field=None, *iso0_field=None*,
refl_field=None, *temp_ref='temperature'*)

Estimates the quantiles of RhoHV in rain for each sweep

Parameters

radar [Radar] radar object

ind_rmin, ind_rmax [int] Min and max range index where to look for rain

zmin, zmax [float] The minimum and maximum reflectivity to consider the radar bin suitable rain

thickness [float] Assumed thickness of the melting layer

doc [float] Number of gates at the end of each ray to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

temp_field, iso0_field, rhohv_field, refl_field [str] Field names within the radar object which represent the temperature, the height over the iso0, co-polar correlation and reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature or height_over_iso0

Returns

rhohv_rain_dict [dict] The estimated RhoHV in rain for each sweep and metadata

`pyart.correct.bias_and_noise.est_zdr_precip` (*radar*, *ind_rmin=10*, *ind_rmax=500*,
zmin=20.0, *zmax=22.0*, *rhohvmin=0.97*,
phidpmax=10.0, *elmax=None*, *thickness=700.0*,
doc=None, *fzl=None*,
zdr_field=None, *rhohv_field=None*,
phidp_field=None, *temp_field=None*,
iso0_field=None, *refl_field=None*,
temp_ref='temperature')

Filters out all undesired data to be able to estimate ZDR bias, either in moderate rain or from vertically pointing scans

Parameters

radar [Radar] radar object

ind_rmin, ind_rmax [int] Min and max range index where to look for rain

zmin, zmax [float] The minimum and maximum reflectivity to consider the radar bin suitable rain

rhohvmin [float] Minimum RhoHV to consider the radar bin suitable rain

phidpmax [float] Maximum PhiDP to consider the radar bin suitable rain

elmax [float] Maximum elevation

thickness [float] Assumed thickness of the melting layer

doc [float] Number of gates at the end of each ray to to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

zdr_field, rhohv_field, refl_field, phidp_field, temp_field, iso0_field : str Field names within the radar object which represent the differential reflectivity, co-polar correlation, reflectivity, differential phase, temperature and height relative to the iso0 fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature, height_over_iso0, fixed_fzl or None

Returns

zdr_prec_dict [dict] The ZDR data complying with specifications and metadata

```
pyart.correct.bias_and_noise. est_zdr_snow (radar, ind_rmin=10, ind_rmax=500, zmin=0.0,
                                             zmax=30.0, snrmin=10.0, snrmax=50.0,
                                             rhohvmin=0.97, kept_values=[2], phidp-
                                             max=10.0, kdpmax=None, tempmin=None,
                                             tempmax=None, elmax=None, zdr_field=None,
                                             rhohv_field=None, phidp_field=None,
                                             temp_field=None, snr_field=None,
                                             hydro_field=None, kdp_field=None,
                                             refl_field=None)
```

Filters out all undesired data to be able to estimate ZDR bias in snow

Parameters

radar [Radar] radar object

ind_rmin, ind_rmax [int] Min and max range index where to look for snow

zmin, zmax [float] The minimum and maximum reflectivity to consider the radar bin suitable snow

snrmin, snrmax [float] The minimum and maximum SNR to consider the radar bin suitable snow

rhohvmin [float] Minimum RhoHV to consider the radar bin suitable snow

kept_values [list of int] The hydrometeor classification values to keep

phidpmax [float] Maximum PhiDP to consider the radar bin suitable snow

kdpmax [float or None] Maximum KDP. If not none this is the maximum KDP value to consider the radar bin suitable snow

tempmin, tempmax [float or None] If not None, the minimum and maximum temperature to consider the radar bin suitable snow

elmax [float] Maximum elevation

zdr_field, rhohv_field, refl_field, phidp_field, kdp_field, temp_field,

snr_field, hydro_field [str] Field names within the radar object which represent the differential reflectivity, co-polar correlation, reflectivity, differential phase, specific differential phase, signal to noise ratio, hydrometeor classification and temperature fields. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns

zdr_snow_dict [dict] The ZDR data complying with specifications and metadata

`pyart.correct.bias_and_noise.get_kdp_selfcons(zdr, refl, ele_vec, zdr_kdpzh_dict, parametrization='None')`

Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP

Parameters

zdr, refl [ndarray 2D] reflectivity and differential reflectivity fields

ele_vec [ndarray 1D] vector containing the elevation angles of each ray

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in `zdr_kdpzh_dict`. The parametrized curves are obtained from literature except for Wolfensberger that was derived from disdrometer data obtained by MeteoSwiss and EPFL. All parametrizations are valid for C-band only except that of Gourley.

Returns

kdp_sim [ndarray 2D] the KDP estimated from `zdr` and `refl`

References

E. Gorgucci, G. Scarchilli, V. Chandrasekar, "Calibration of radars using polarimetric techniques", IEEE Transactions on Geoscience and Remote Sensing, 1992, 30

J.J. Gourley, A.J. Illingworth, P. Tabary, "Absolute Calibration of Radar Reflectivity Using Redundancy of the Polarization Observations and Implied Constraints on Drop Shapes", J. of Atmospheric and Oceanic Technology, 2009, 26

V. Louf, A. Protat, R.A. Warren, S.M. Collis, D.B. Wolff, S. Raunyar, C. Jakob, W. A. Petersen, "An Integrated Approach to Weather Radar Calibration and Monitoring Using Ground Clutter and Satellite Comparisons", J. of Atmospheric and Oceanic Technology, 2019, 36

M. Vaccarono, R. Bechini, C. V. Chandrasekar, R. Cremonini, C. Cassardo, "An integrated approach to monitoring the calibration stability of operational dual-polarization radars", Atmos. Meas. Tech., 2016, 9

`pyart.correct.bias_and_noise.get_sun_hits(radar, delev_max=2.0, dazim_max=2.0, elmin=1.0, rmin=50000.0, hmin=10000.0, nbins_min=20, attg=None, max_std_pwr=1.0, max_std_zdr=1.5, sun_position='MF', pwrh_field=None, pwrv_field=None, zdr_field=None)`

get data from suspected sun hits. The sun hits are detected using the Hildebrand and Sekhon noise estimation

Parameters

- radar** [Radar] radar object
- delev_max, dazim_max** [float] maximum difference in elevation and azimuth between sun position and antenna pointing
- elmin** [float] minimum radar elevation angle
- rmin** [float] minimum range from which we can look for noise [m]
- hmin** [float] minimum altitude from which we can look for noise [m]. The actual range min will be the minimum between rmin and the range bin higher than hmin.
- nbins_min** [int] Minimum number of bins with valid data to consider a ray as potentially sun hit
- attg** [float] gas attenuation coefficient (1-way)
- max_std_pwr** [float] Maximum standard deviation of the estimated sun power to consider the sun signal valid [dB]
- max_std_zdr** [float] Maximum standard deviation of the estimated sun ZDR to consider the sun signal valid [dB]
- sun_position** [str] The function to use to compute the sun position. Can be 'MF' or 'pysolar'
- pwrh_field, pwrv_field, zdr_field** [str] names of the signal power in dBm for the H and V polarizations and the differential reflectivity

Returns

- sun_hits** [dict] a dictionary containing information of the sun hits
- new_radar** [radar object] radar object containing sweeps that contain sun hits

```
pyart.correct.bias_and_noise.get_sun_hits_ivic(radar, delev_max=2.0, dazim_max=2.0,  
                                              elmin=1.0, npulses_ray=30,  
                                              flat_reg_wlen=96, nbins_min=800,  
                                              iterations=10, attg=None,  
                                              sun_position='MF', max_std_zdr=1.5,  
                                              pwrh_field=None, pwrv_field=None,  
                                              zdr_field=None)
```

get data from suspected sun hits. The sun hits are detected using the Ivic et al. (2003) noise estimator

Parameters

- radar** [Radar] radar object
- delev_max, dazim_max** [float] maximum difference in elevation and azimuth between sun position and antenna pointing
- elmin** [float] minimum radar elevation angle
- npulses_ray** [int] Default number of pulses used in the computation of the ray. If the number of pulses is not in radar.instrument_parameters this will be used instead
- flat_reg_wlen** [int] number of gates considered to find flat regions. The number represents 8 km length with a 83.3 m resolution
- nbins_min: int** minimum number of gates with noise to consider the retrieval valid
- iterations: int** number of iterations in step 7 of Ivic algorithm
- attg** [float] gas attenuation coefficient (1-way)

sun_position [str] The function to use to compute the sun position. Can be 'MF' or 'pysolar'

max_std_zdr [float] Maximum standard deviation of the estimated sun ZDR to consider the sun signal valid [dB]

pwrh_field, pwrv_field, zdr_field [str] names of the signal power in dBm for the H and V polarizations and the differential reflectivity

Returns

sun_hits [dict] a dictionary containing information of the sun hits

new_radar [radar object] radar object containing sweeps that contain sun hits

```
pyart.correct.bias_and_noise.selfconsistency_bias(radar,                zdr_kdpzh_dict,
                                                    min_rhohv=0.92,                fil-
                                                    ter_rain=True,    max_phidp=20.0,
                                                    smooth_wind_len=5,
                                                    doc=None,    fzl=None,    thick-
                                                    ness=700.0,    min_rcons=20,
                                                    dphidp_min=2,    dphidp_max=16,
                                                    parametrization='None',
                                                    refl_field=None, phidp_field=None,
                                                    zdr_field=None, temp_field=None,
                                                    iso0_field=None,    hy-
                                                    dro_field=None, rhohv_field=None,
                                                    temp_ref='temperature',
                                                    check_wet_radome=True,
                                                    wet_radome_refl=25.0,
                                                    wet_radome_len_min=4,
                                                    wet_radome_len_max=8,
                                                    wet_radome_ngates_min=180,
                                                    valid_gates_only=False,
                                                    keep_points=False,
                                                    kdp_wind_len=12)
```

Estimates reflectivity bias at each ray using the self-consistency algorithm by Gourley

Parameters

radar [Radar] radar object

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

min_rhohv [float] minimum RhoHV value to consider the data valid

filter_rain [bool] If True the hydrometeor classification is going to be used to filter out all gates that are not rain

max_phidp [float] maximum PhiDP value to consider the data valid

smooth_wind_len [int] length of the smoothing window

doc [float] Number of gates at the end of each ray to to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

thickness [float] assumed melting layer thickness [m]

min_rcons [int] minimum number of consecutive gates to consider a valid segment of PhiDP

dphidp_min [float] minimum differential phase shift in a segment

dphidp_max [float] maximum differential phase shift in a segment

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in `zdr_kdpzh_dict`.

refl_field, phidp_field, zdr_field [str] Field names within the radar object which represent the reflectivity, differential phase and differential reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_field, iso0_field, hydro_field, rhohv_field [str] Field names within the radar object which represent the temperature, the height relative to the iso0, the hydrometeor classification and the co-polar correlation fields. A value of None will use the default field name as defined in the Py-ART configuration file. They are going to be used only if available.

kdpsim_field, phidpsim_field [str] Field names which represent the estimated specific differential phase and differential phase. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

check_wet_radome [Bool] if True the average reflectivity of the closest gates to the radar is going to be check to find out whether there is rain over the radome. If there is rain no bias will be computed

wet_radome_refl [Float] Average reflectivity of the gates close to the radar to consider the radome as wet

wet_radome_len_min, wet_radome_len_max [int] Mim and max gate indices of the disk around the radome used to decide whether the radome is wet

wet_radome_ngates_min [int] Minimum number of valid gates to consider that the radome is wet

valid_gates_only [Bool] If True the reflectivity bias obtained for each valid ray is going to be assigned only to gates of the segment used. That will give more weight to longer segments when computing the total bias.

keep_points [Bool] If True the ZDR, ZH and KDP of the gates used in the self-consistency algorithm are going to be stored for further analysis

kdp_wind_len [int] The length of the window used to compute KDP with the single window least square method

Returns

refl_bias_dict [dict] the bias at each ray field and metadata

selfconsistency_dict [dict] If keep_pointst set, a dictionary containing the measured valid values of ZDR, Zh and KDP. None otherwise

```

pyart.correct.bias_and_noise.selfconsistency_bias2(radar,          zdr_kdpzh_dict,
                                                    min_rhohv=0.92,
                                                    min_zdr=0.2,          fil-
                                                    ter_rain=True, max_phidp=20.0,
                                                    smooth_wind_len=5, doc=None,
                                                    fzl=None,          thickness=700.0,
                                                    min_rcons=20,          parametriza-
                                                    tion='None',          refl_field=None,
                                                    phidp_field=None,
                                                    zdr_field=None,
                                                    temp_field=None,
                                                    iso0_field=None,          hy-
                                                    dro_field=None,
                                                    rhohv_field=None,
                                                    kdp_field=None,
                                                    temp_ref='temperature',
                                                    check_wet_radome=True,
                                                    wet_radome_refl=25.0,
                                                    wet_radome_len_min=4,
                                                    wet_radome_len_max=8,
                                                    wet_radome_ngates_min=180,
                                                    keep_points=False,
                                                    bias_per_gate=False)

```

Estimates reflectivity bias at each ray using the self-consistency algorithm by Gourley

Parameters

radar [Radar] radar object

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

min_rhohv [float] minimum RhoHV value to consider the data valid

min_zdr [float] minimum ZDR value to consider the data valid

filter_rain [bool] If True the hydrometeor classification is going to be used to filter out all gates that are not rain

max_phidp [float] maximum PhiDP value to consider the data valid

smooth_wind_len [int] length of the smoothing window

doc [float] Number of gates at the end of each ray to to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

thickness [float] assumed melting layer thickness [m]

min_rcons [int] minimum number of consecutive gates to consider a valid segment of PhiDP

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccaroni'. 'None' will use tables contained in zdr_kdpzh_dict.

refl_field, kdp_field, zdr_field [str] Field names within the radar object which represent the reflectivity, differential phase and differential reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_field, iso0_field, hydro_field, rhohv_field, phidp_field [str] Field names within the radar object which represent the temperature, the height relative to the iso0, the hydrometeor classification and the co-polar correlation fields. A value of None will use the default

field name as defined in the Py-ART configuration file. They are going to be used only if available.

kdp_{sim}_field, phidp_{sim}_field [str] Field names which represent the estimated specific differential phase and differential phase. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

check_wet_radome [Bool] if True the average reflectivity of the closest gates to the radar is going to be check to find out whether there is rain over the radome. If there is rain no bias will be computed

wet_radome_refl [Float] Average reflectivity of the gates close to the radar to consider the radome as wet

wet_radome_len_min, wet_radome_len_max [int] Mim and max gate indices of the disk around the radome used to decide whether the radome is wet

wet_radome_ngates_min [int] Minimum number of valid gates to consider that the radome is wet

keep_points [Bool] If True the ZDR, ZH and KDP of the gates used in the self- consistency algorithm are going to be stored for further analysis

bias_per_gate [Bool] If True the bias per gate will be computed

Returns

kdp_data_dict [dict] A dictionary containing valid observed and estimated using self- consistency values of KDP

refl_bias_dict [dict] If bias_per_gate is set, the bias at each gate field and metadata. None otherwise

selfconsistency_dict [dict] If keep_pointst set, a dictionary containing the measured valid values of ZDR, Zh and KDP. None otherwise

```
pyart.correct.bias_and_noise.selfconsistency_kdp_phidp(radar,          zdr_kdpzh_dict,
                                                         min_rhohv=0.92,
                                                         filter_rain=True,
                                                         max_phidp=20.0,
                                                         smooth_wind_len=5,
                                                         doc=None,          fzl=None,
                                                         thickness=700.0,
                                                         parametrization='None',
                                                         refl_field=None,
                                                         phidp_field=None,
                                                         zdr_field=None,
                                                         temp_field=None,
                                                         iso0_field=None,
                                                         hydro_field=None,
                                                         rhohv_field=None,
                                                         kdpsim_field=None,
                                                         phidpsim_field=None,
                                                         temp_ref='temperature')
```

Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP. Private method

Parameters

radar [Radar] radar object

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

min_rhohv [float] minimum RhoHV value to consider the data valid

filter_rain [bool] If True the hydrometeor classification is going to be used to filter out all gates that are not rain

max_phidp [float] maximum PhiDP value to consider the data valid

smooth_wind_len [int] length of the smoothing window

doc [float] Number of gates at the end of each ray to to remove from the calculation.

fzl [float] Freezing layer, gates above this point are not included in the correction.

thickness [float] assumed melting layer thickness [m]

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in zdr_kdpzh_dict.

refl_field, phidp_field, zdr_field [str] Field names within the radar object which represent the reflectivity, differential phase and differential reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_field, iso0_field, hydro_field, rhohv_field [str] Field names within the radar object which represent the temperature, the height relative to the iso0, the hydrometeor classification and the co-polar correlation fields. A value of None will use the default field name as defined in the Py-ART configuration file. They are going to be used only if available.

kdpssim_field, phidpsim_field [str] Field names which represent the estimated specific differential phase and differential phase. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns

kdp_sim_dict, phidp_sim_dict [dict] the KDP and PhiDP estimated fields and metadata

```
pyart.correct.bias_and_noise.sun_retrieval(az_rad, az_sun, el_rad, el_sun, sun_hit,
                                             sun_hit_std, az_width_co=None,
                                             el_width_co=None, az_width_cross=None,
                                             el_width_cross=None, is_zdr=False)
```

Estimates sun parameters from sun hits

Parameters

az_rad, az_sun, el_rad, el_sun [float array] azimuth and elevation values of the sun and the radar

sun_hit [float array] sun hit value. Either power in dBm or ZDR in dB

sun_hit_std [float array] standard deviation of the sun hit value in dB

az_width_co, el_width_co, az_width_cross, el_width_cross [float] azimuth and elevation antenna width for each channel

is_zdr [boolean] boolean to signal that is ZDR data

Returns

val, val_std [float] retrieved value and its standard deviation

az_bias, el_bias [float] retrieved azimuth and elevation antenna bias respect to the sun position

az_width, el_width [float] retrieved azimuth and elevation antenna widths

nhits [int] number of sun hits used in the retrieval

par [float array] and array with the 5 parameters of the Gaussian fit

PYART.CORRECT.DEALIAS

Front end to the University of Washington 4DD code for Doppler dealiasing.

<code>dealias_fourdd(radar[, last_radar, ...])</code>	Dealias Doppler velocities using the 4DD algorithm.
<code>_create_rsl_volume(radar, field_name, ..., ...)</code>	Create a RSLVolume containing data from a field in radar.

`pyart.correct.dealias._create_rsl_volume(radar, field_name, vol_num, rsl_badval, excluded=None)`
Create a RSLVolume containing data from a field in radar.

`pyart.correct.dealias.dealias_fourdd(radar, last_radar=None, sonde_profile=None, gatefilter=False, filt=1, rsl_badval=131072.0, keep_original=False, set_limits=True, vel_field=None, corr_vel_field=None, last_vel_field=None, debug=False, max_shear=0.05, sign=1, **kwargs)`
Dealias Doppler velocities using the 4DD algorithm.

Dealias the Doppler velocities field using the University of Washington 4DD algorithm utilizing information from a previous volume scan and/or sounding data. Either `last_radar` or `sonde_profile` must be provided. For best results provide both a previous volume scan and sounding data. Radar and `last_radar` must contain the same number of rays per sweep.

Additional arguments are passed to `_fourdd_interface.fourdd_dealias()`. These can be used to fine tune the behavior of the FourDD algorithm. See the documentation of Other Parameters for details. For the default values of these parameters see the documentation of `_fourdd_interface.fourdd_dealias()`.

Parameters

- radar** [Radar] Radar object to use for dealiasing. Must have a `Nyquist` defined in the `instrument_parameters` attribute and have a `reflectivity_horizontal` and `mean_doppler_velocity` fields.
- last_radar** [Radar, optional] The previous radar volume, which has been successfully dealiased. Using a previous volume as an initial condition can greatly improve the dealiasing, and represents the final dimension in the 4DD algorithm.
- sonde_profile** [HorizontalWindProfile, optional] Profile of horizontal winds from a sounding used for the initial condition of the dealiasing.

Returns

- vr_corr** [dict] Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

Other Parameters

- gatefilter** [GateFilter, optional.] A GateFilter instance which specifies which gates should be ignored when performing velocity dealiasing. A value of None will create this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. The default value assumes all gates are valid.
- filt** [int, optional] Flag controlling Bergen and Albers filter, 1 = yes, 0 = no.
- rsl_badval** [float, optional] Value which represents a bad value in RSL.
- keep_original** [bool, optional] True to keep original doppler velocity values when the dealiasing procedure fails, otherwise these gates will be masked. NaN values are still masked.
- set_limits** [bool, optional] True to set `valid_min` and `valid_max` elements in the returned dictionary. False will not set these dictionary elements.
- vel_field** [str, optional] Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.
- corr_vel_field** [str, optional] Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.
- last_vel_field** [str, optional] Name to use for the dealiased Doppler velocity field metadata in `last_radar`. None will use the `corr_vel_field` name.
- maxshear** [float, optional] Maximum vertical shear which will be incorporated into the created volume from the sounding data. Parameter not used when no sounding data is provided.
- sign** [int, optional] Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.
- compthresh** [float, optional] Fraction of the Nyquist velocity to use as a threshold when performing continuity (initial) dealiasing. Velocities differences above this threshold will not be marked as gate from which to begin unfolding during spatial dealiasing.
- compthresh2** [float, optional] The same as `compthresh` but the value used during the second pass of dealiasing. This second pass is only performed in both a sounding and last volume are provided.
- thresh** [float, optional] Fraction of the Nyquist velocity to use as a threshold when performing spatial dealiasing. Horizontally adjacent gates with velocities above this threshold will count against assigning the gate in question the velocity value being tested.
- ckval** [float, optional] When the absolute value of the velocities are below this value they will not be marked as gates from which to begin unfolding during spatial dealiasing.
- stdthresh** [float, optional] Fraction of the Nyquist velocity to use as a standard deviation threshold in the window dealiasing portion of the algorithm.
- epsilon** [float, optional] Difference used when comparing a value to missing value, changing this from the default is not recommended.
- maxcount** [int, optional] Maximum allowed number of fold allowed when unfolding velocities.
- pass2** [int, optional] Controls whether unfolded gates should be removed (a value of 0) or retained for unfolding during the second pass (a value of 1) when both a sounding volume and last volume are provided.
- rm** [int, optional] Determines what should be done with gates that are left unfolded after the first pass of dealiasing. A value of 1 will remove these gates, a value of 0 sets these gates to their initial velocity. If both a sounding volume and last volume are provided this parameter is ignored.

proximity [int, optional] Number of gates and rays to include of either side of the current gate during window dealiasing. This value may be doubled in cases where a standard sized window does not capture a sufficient number of good valued gates.

mingood [int, optional] Number of good valued gates required within the window before the current gate will be unfolded.

ba_mincount [int, optional] Number of neighbors required during Bergen and Albers filter for a given gate to be included, must be between 1 and 8, 5 recommended.

ba_edgecount [int, optional] Same as ba_mincount but used at ray edges, must be between 1 and 5, 3 recommended.

debug [bool, optional] Set True to return RSL Volume objects for debugging: usuccess, radialVelVolume, lastVelVolume, unfoldedVolume, sondVolume

Notes

Due to limitations in the C code do not call with sounding arrays over 999 elements long.

References

C. N. James and R. A. Houze Jr, A Real-Time Four-Dimensional Doppler Dealising Scheme, Journal of Atmospheric and Oceanic Technology, 2001, 18, 1674.

PYART.CORRECT.DESPECKLE

Find contiguous objects in scans and despeckle away ones that are too small.

<code>despeckle_field(radar, field[, label_dict, ...])</code>	Despeckle a radar volume by identifying small objects in each scan and masking them out.
<code>find_objects(radar, field, threshold[, ...])</code>	Find objects (i.e., contiguous gates) in one or more sweeps that match thresholds.
<code>_adjust_for_periodic_boundary(data)</code>	Identify all the contiguous objects in a sweep, accounting for the periodic boundary in a 360-deg PPI.
<code>_append_labels(labels, label_storage)</code>	Appends consecutive sweeps of labels, creating a multi-sweep 2D array.
<code>_check_for_360(az, delta)</code>	Check if an array of azimuths indicates the sweep is a full 360 PPI.
<code>_check_sweeps(sweeps, radar)</code>	Parse the sweeps keyword and convert it to a list of ints.
<code>_check_threshold(threshold)</code>	Parse the threshold keyword and return the lower and upper boundaries for the object search.
<code>_generate_dict(label_storage)</code>	Build the dictionary that includes all the object label information.
<code>_get_data(radar, iswp, field, tlo, thi, window)</code>	Get data for a field from a given sweep in a Radar object.
<code>_get_labels(data)</code>	Identify all the contiguous objects in a sweep.
<code>_smooth_data(data, window)</code>	Perform box filtering along each ray of a sweep, and return the smoothed field.

`pyart.correct.despeckle._adjust_for_periodic_boundary` (*data*)

Identify all the contiguous objects in a sweep, accounting for the periodic boundary in a 360-deg PPI. Contiguous means corners or sides of gates touch. The algorithm appends the sweep to itself, then looks for contiguous objects near the original PPI edges and relabels them. Then, the extra sweep is discarded before returning all the labels.

Parameters

data [2D array of ints] Sweep that will be checked for objects. Sweep has already been converted to binary 0s/1s based on user-supplied thresholds.

Returns

labels [2D array of ints] Numeric object labels, corrected for the periodic boundary. Zero values mean no object at that location.

nobj [int] Number of distinct objects identified in sweep.

`pyart.correct.despeckle._append_labels` (*labels, label_storage*)

Appends consecutive sweeps of labels, creating a multi-sweep 2D array. Typically called iteratively.

Parameters

labels [2D array of ints] Sweep containing object labels.

label_storage [Empty list or 2D array of ints] Array to append new sweep of labels to.

Returns

label_storage [2D array of ints] Updated array of object labels.

`pyart.correct.despeckle._check_for_360` (*az*, *delta*)

Check if an array of azimuths indicates the sweep is a full 360 PPI. This should also spot RHIs (effectively, a narrow azimuth sector sweep).

Parameters

az [array of int or float] Azimuths in the sweep

delta [int or float] Size of allowable gap near PPI edges, in deg, to consider it full 360.

Returns

Flag [bool] True - Sweep is a 360 PPI.

False - Sweep is not a 360 PPI.

`pyart.correct.despeckle._check_sweeps` (*sweeps*, *radar*)

Parse the sweeps keyword and convert it to a list of ints. The output will be iterated over.

Parameters

sweeps [int or list of ints or None] Sweep numbers to put into an iterable list. If None, all sweeps in the radar object will be examined.

radar [pyart.core.Radar object] Radar object to query.

Returns

sweeps [list of ints] Sweep numbers as an iterable list.

`pyart.correct.despeckle._check_threshold` (*threshold*)

Parse the threshold keyword and return the lower and upper boundaries for the object search.

Parameters

threshold [int or float, or 2-element tuple of ints or floats] Threshold values above (if single value) or between (if tuple) for objects to be identified.

Returns

tlo [int or float] Lower bound for the threshold. Values below this will not be included in the hunt for objects.

thi [int or float or None] Upper bound for the threshold. Values above this will not be included in the hunt for objects. None means no upper bound.

`pyart.correct.despeckle._generate_dict` (*label_storage*)

Build the dictionary that includes all the object label information. If the entire Radar object was searched, the dictionary is ready to be added as a new field.

Parameters

label_storage [2D array of ints] Object labels as a 2D array.

Returns

label_dict [dict] Dictionary containing object labels and associated metadata.

`pyart.correct.despeckle._get_data(radar, iswp, field, tlo, thi, window, gatefilter=None)`

Get data for a field from a given sweep in a Radar object. Data are smoothed if desired, then converted to binary 0s/1s based on whether valid values are present.

Parameters

radar [pyart.core.Radar object] Radar object to query.

iswp [int] Sweep number to query.

field [str] Name of field to investigate for speckles.

tlo [int or float] Lower bound for the threshold. Values below this will not be included in the hunt for objects.

thi [int or float or None] Upper bound for the threshold. Values above this will not be included in the hunt for objects. None means no upper bound.

window [int or None] Number of gates included in a smoothing box filter along a ray. If None, no smoothing is done.

Returns

data [2D array of ints] Sweep as array of binary 0s/1s based on whether valid values exist.

Other Parameters

gatefilter [None or pyart.filters.GateFilter object, optional] Py-ART GateFilter object to apply before labeling objects. If None, no filtering will be performed.

`pyart.correct.despeckle._get_labels(data)`

Identify all the contiguous objects in a sweep. Contiguous means corners or sides of gates touch. Uses `scipy.ndimage.label`.

Parameters

data [2D array of ints] Sweep that will be checked for objects. Sweep has already been converted to binary 0s/1s based on user-supplied thresholds.

Returns

labels [2D array of ints] Numeric object labels. Zero values mean no object at that location.

nobj [int] Number of distinct objects identified in sweep.

`pyart.correct.despeckle._smooth_data(data, window)`

Perform box filtering along each ray of a sweep, and return the smoothed field. Uses `scipy.signal.convolve2d` which provides excellent performance.

Parameters

data [2D array of ints or floats] Sweep of data for a specific field. Will be masked.

window [int or None] Number of gates included in a smoothing box filter along a ray. If None, no smoothing is done.

Returns

data [2D array of ints or floats] Smoothed sweep of data.

`pyart.correct.despeckle.despeckle_field(radar, field, label_dict=None, threshold=-100, size=10, gatefilter=None, delta=5.0)`

Despeckle a radar volume by identifying small objects in each scan and masking them out. User can define which field to investigate, as well as various thresholds to use on that field and any objects found within. Requires `scipy` to be installed, and returns a GateFilter object.

Parameters

radar [pyart.core.Radar object] Radar object to query.

field [str] Name of field to investigate for speckles.

Returns

gatefilter [pyart.filters.GateFilter object] Py-ART GateFilter object that includes the despeckling mask

Other Parameters

label_dict [dict or None, optional] Dictionary that is produced by find_objects. If None, find_objects will be called to produce it.

threshold [int or float, or 2-element tuple of ints or floats] Threshold values above (if single value) or between (if tuple) for objects to be identified. Default value assumes reflectivity.

size [int, optional] Number of contiguous gates in an object, below which it is a speckle.

gatefilter [None or pyart.filters.GateFilter object] Py-ART GateFilter object to which to add the despeckling mask. The GateFilter object will be permanently modified with the new filtering. If None, creates a new GateFilter.

delta [int or float, optional] Size of allowable gap near PPI edges, in deg, to consider it full 360. If gap is small, then PPI edges will be checked for matching objects.

`pyart.correct.despeckle.find_objects(radar, field, threshold, sweeps=None, smooth=None, gatefilter=None, delta=5.0)`

Find objects (i.e., contiguous gates) in one or more sweeps that match thresholds. Filtering & smoothing are available prior to labeling objects. In addition, periodic boundaries are accounted for if they exist (e.g., 360-deg PPIs). Requires scipy to be installed.

Parameters

radar [pyart.core.Radar object] Radar object to query.

field [str] Name of field to investigate for objects.

threshold [int or float, or 2-element tuple of ints or floats] Threshold values above (if single value) or between (if tuple) for objects to be identified.

Returns

label_dict [dict] Dictionary that contains all the labeled objects. If this function is performed on the full Radar object, then the dict is ready to be added as a field.

Other Parameters

sweeps [int or array of ints or None, optional] Sweep numbers to examine. If None, all sweeps are examined.

smooth [int or None, optional] Number of gates included in a smoothing box filter along a ray. If None, no smoothing is done prior to labeling objects.

gatefilter [None or pyart.filters.GateFilter object, optional] Py-ART GateFilter object to apply before labeling objects. If None, no filtering will be performed. Note: Filtering always occurs before smoothing.

delta [int or float, optional] Size of allowable gap near PPI edges, in deg, to consider it full 360. If gap is small, then PPI edges will be checked for matching objects along the periodic boundary.

PYART.CORRECT.PHASE_PROC

Utilities for working with phase data.

Code based upon algorithm described in: S. E. Giangrande et al, J. of Atmos. and Ocean. Tech., 2013, 30, 1716.

Adapted by Scott Collis and Scott Giangrande, refactored by Jonathan Helmus.

<i>det_sys_phase</i> (radar[, ncp_lev, rhohv_lev, ...])	Determine the system phase.
<i>det_sys_phase_ray</i> (radar[, ind_rmin, ...])	Public method Alternative determination of the system phase.
<i>correct_sys_phase</i> (radar[, ind_rmin, ...])	correction of the system offset.
<i>smooth_phidp_single_window</i> (radar[, ...])	correction of the system offset and smoothing using one window
<i>smooth_phidp_double_window</i> (radar[, ...])	correction of the system offset and smoothing using two window
<i>smooth_masked_scan</i> (raw_data[, wind_len, ...])	smoothes the data using a rolling window.
<i>smooth_masked</i> (raw_data[, wind_len, ...])	smoothes the data using a rolling window.
<i>fzl_index</i> (fzl, ranges, elevation, radar_height)	Return the index of the last gate below a given altitude.
<i>det_process_range</i> (radar, sweep, fzl[, doc])	Determine the processing range for a given sweep.
<i>snr</i> (line[, wl])	Return the signal to noise ratio after smoothing.
<i>unwrap_masked</i> (lon[, centered, copy])	Unwrap a sequence of longitudes or headings in degrees.
<i>smooth_and_trim</i> (x[, window_len, window])	Smooth data using a window with requested size.
<i>smooth_and_trim_scan</i> (x[, window_len, window])	Smooth data using a window with requested size.
<i>noise</i> (line[, wl])	Return the noise after smoothing.
<i>get_phidp_unf</i> (radar[, ncp_lev, rhohv_lev, ...])	Get Unfolded Phi differential phase
<i>construct_A_matrix</i> (n_gates, filt)	Construct a row-augmented A matrix.
<i>construct_B_vectors</i> (phidp_mod, z_mod, filt)	Construct B vectors.
<i>LP_solver_cvxopt</i> (A_Matrix, B_vectors, weights)	Solve the Linear Programming problem given in Giangrande et al, 2012 using the CVXOPT module.
<i>LP_solver_pyglpk</i> (A_Matrix, B_vectors, weights)	Solve the Linear Programming problem given in Giangrande et al, 2012 using the PyGLPK module.
<i>solve_cylp</i> (model, B_vectors, weights, ray, ...)	Worker process for LP_solver_cylp_mp.
<i>LP_solver_cylp_mp</i> (A_Matrix, B_vectors, weights)	Solve the Linear Programming problem given in Giangrande et al, 2012 using the CyLP module using multiple processes.
<i>LP_solver_cylp</i> (A_Matrix, B_vectors, weights)	Solve the Linear Programming problem given in Giangrande et al, 2012 using the CyLP module.
<i>phase_proc_lp</i> (radar, offset[, debug, ...])	Phase process using a LP method [1].

Continued on next page

Table 1 – continued from previous page

<code>_det_sys_phase(ncp, rhv, phidp, last_ray_idx)</code>	Determine the system phase, see <code>det_sys_phase()</code> .
<code>_det_sys_phase_ray(phidp, refl, nrays, ngates)</code>	Private method Alternative determination of the system phase.
<code>_correct_sys_phase(phidp, refl, nsweeps, ...)</code>	correction of the system offset.
<code>phase_proc_lp_gf(radar[, gatefilter, debug, ...])</code>	Phase process using a LP method [1] using Py-ART's Gatefilter.
<code>get_phidp_unf_gf(radar, gatefilter[, debug, ...])</code>	Get Unfolded Phi differential phase in areas not gate-filtered.
<code>det_sys_phase_gf(radar, gatefilter[, ...])</code>	Determine the system phase.
<code>_det_sys_phase_gf(phidp, last_ray_idx, ...)</code>	Determine the system phase, see <code>det_sys_phase()</code> .

`pyart.correct.phase_proc.LP_solver_cvxopt` (*A_Matrix*, *B_vectors*, *weights*, *solver*='glpk')
Solve the Linear Programming problem given in Giangrande et al, 2012 using the CVXOPT module.

Parameters

A_Matrix [matrix] Row augmented A matrix, see `construct_A_matrix()`

B_vectors [matrix] Matrix containing B vectors, see `construct_B_vectors()`

weights [array] Weights.

solver [str or None] LP solver backend to use, choices are 'glpk', 'mosek' or None to use the conelp function in CVXOPT. 'glpk' and 'mosek' are only available if they are installed and CVXOPT was build with the correct bindings.

Returns

soln [array] Solution to LP problem.

See also:

LP_solver_pyglpk Solve LP problem using the PyGLPK module.

LP_solver_cylp Solve LP problem using the cylp module.

LP_solver_cylp_mp Solve LP problem using the cylp module using multi processes.

`pyart.correct.phase_proc.LP_solver_cylp` (*A_Matrix*, *B_vectors*, *weights*, *really_verbose*=False)
Solve the Linear Programming problem given in Giangrande et al, 2012 using the CyLP module.

Parameters

A_Matrix [matrix] Row augmented A matrix, see `construct_A_matrix()`

B_vectors [matrix] Matrix containing B vectors, see `construct_B_vectors()`

weights [array] Weights.

really_verbose [bool, optional] True to print CLP messaging. False to suppress.

Returns

soln [array] Solution to LP problem.

See also:

LP_solver_cvxopt Solve LP problem using the CVXOPT module.

LP_solver_pyglpk Solve LP problem using the PyGLPK module.

```
pyart.correct.phase_proc.LP_solver_cylp_mp(A_Matrix, B_vectors, weights, really_verbose=False, proc=1)
```

Solve the Linear Programming problem given in Giangrande et al, 2012 using the CyLP module using multiple processes.

Parameters

A_Matrix [matrix] Row augmented A matrix, see *construct_A_matrix()*

B_vectors [matrix] Matrix containing B vectors, see *construct_B_vectors()*

weights [array] Weights.

really_verbose [bool, optional] True to print CLP messaging. False to suppress.

proc [int, optional] Number of worker processes.

Returns

soln [array] Solution to LP problem.

See also:

LP_solver_cvxopt Solve LP problem using the CVXOPT module.

LP_solver_pyglpk Solve LP problem using the PyGLPK module.

LP_solver_cylp Solve LP problem using the CyLP module using single process.

```
pyart.correct.phase_proc.LP_solver_pyglpk(A_Matrix, B_vectors, weights, it_lim=7000, presolve=True, really_verbose=False)
```

Solve the Linear Programming problem given in Giangrande et al, 2012 using the PyGLPK module.

Parameters

A_Matrix [matrix] Row augmented A matrix, see *construct_A_matrix()*

B_vectors [matrix] Matrix containing B vectors, see *construct_B_vectors()*

weights [array] Weights.

it_lim [int, optional] Simplex iteration limit.

presolve [bool, optional] True to use the LP presolver.

really_verbose [bool, optional] True to print LPX messaging. False to suppress.

Returns

soln [array] Solution to LP problem.

See also:

LP_solver_cvxopt Solve LP problem using the CVXOPT module.

LP_solver_cylp Solve LP problem using the cylp module.

LP_solver_cylp_mp Solve LP problem using the cylp module using multi processes.

```
pyart.correct.phase_proc._correct_sys_phase(phidp, refl, nsweeps, nrays, ngates, start_sweep, end_sweep, ind_rmin=10, ind_rmax=500, min_rcons=11, zmin=20.0, zmax=40.0)
```

correction of the system offset. Private method

Parameters

phidp [masked array] the phidp field to correct

refl [masked array] the reflectivity field

nsweeps, nrays, ngates [int] number of sweeps, total rays and gates per ray

start_sweep, end_sweep [int array] index of the starting and ending ray of each sweep

ind_rmin, ind_rmax [int] the minimum and maximum range indexes to use in the estimation

min_rcons [int] the number of consecutive range bins to consider a precipitation cell valid

Returns

corr_phidp [masked array] The corrected phidp field

`pyart.correct.phase_proc._det_sys_phase(ncp, rhv, phidp, last_ray_idx, ncp_lev=0.4, rhv_lev=0.6)`

Determine the system phase, see `det_sys_phase()`.

`pyart.correct.phase_proc._det_sys_phase_gf(phidp, last_ray_idx, radar_meteo)`

Determine the system phase, see `det_sys_phase()`.

`pyart.correct.phase_proc._det_sys_phase_ray(phidp, refl, nrays, ngates, ind_rmin=10, ind_rmax=500, min_rcons=11, zmin=20.0, zmax=40.0)`

Private method Alternative determination of the system phase. Assumes that the valid gates of phidp are only precipitation. A system phase value is found for each ray.

Parameters

phidp [masked array] the phidp data

refl [masked array] the reflectivity data

nrays [int] number of rays in phidp

ngates [int] number of gates per ray

ind_rmin, ind_rmax [int] Min and max range index where to look for continuous precipitation

min_rcons [int] The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax [float]

Returns

phidp0 [array of floats] Estimate of the system phase at each ray

first_gates [array of ints] The first gate where PhiDP is valid

`pyart.correct.phase_proc.construct_A_matrix(n_gates,flt)`

Construct a row-augmented A matrix. Equation 5 in Giangrande et al, 2012.

A is a block matrix given by:

$$\mathbf{A} = \begin{bmatrix} \mathbf{I} & -\mathbf{I} \\ -\mathbf{I} & \mathbf{I} \\ \mathbf{Z} & \mathbf{M} \end{bmatrix}$$

where \mathbf{I} is the identity matrix \mathbf{Z} is a matrix of zeros \mathbf{M} contains our differential constraints.

Each block is of shape `n_gates` by `n_gates` making $\text{shape}(\mathbf{A}) = (3 * n, 2 * n)$.

Note that `M` contains some side padding to deal with edge issues.

Parameters

n_gates [int] Number of gates, determines size of identity matrix.

filt [array] Input filter.

Returns

a [matrix] Row-augmented `A` matrix.

`pyart.correct.phase_proc.construct_B_vectors` (*phidp_mod*, *z_mod*, *filt*, *coef*=0.914,
dweight=60000.0)

Construct `B` vectors. See Giangrande et al, 2012.

Parameters

phidp_mod [2D array] Phi differential phases.

z_mod [2D array.] Reflectivity, modified as needed.

filt [array] Input filter.

coef [float, optional.] Cost coefficients.

dweight [float, optional.] Weights.

Returns

b [matrix] Matrix containing `B` vectors.

`pyart.correct.phase_proc.correct_sys_phase` (*radar*, *ind_rmin*=10, *ind_rmax*=500,
min_rcons=11, *zmin*=20.0, *zmax*=40.0,
psidp_field=None, *refl_field*=None,
phidp_field=None)

correction of the system offset. Public method

Parameters

radar [Radar] Radar object for which to determine the system phase.

ind_rmin, ind_rmax [int] Min and max range index where to look for continuous precipitation

min_rcons [int] The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax [float] Minimum and maximum reflectivity to consider it a rain cell

psidp_field [str] Field name within the radar object which represent the differential phase shift.
A value of `None` will use the default field name as defined in the Py-ART configuration file.

refl_field [str] Field name within the radar object which represent the reflectivity. A value of
`None` will use the default field name as defined in the Py-ART configuration file.

phidp_field [str] Field name within the radar object which represent the corrected differential
phase shift. A value of `None` will use the default field name as defined in the Py-ART
configuration file.

Returns

phidp_dict [dict] The corrected `phidp` field

`pyart.correct.phase_proc.det_process_range` (*radar*, *sweep*, *fzl*, *doc*=10)

Determine the processing range for a given sweep.

Queues the radar and returns the indices which can be used to slice the radar fields and select the desired sweep with gates which are below a given altitude.

Parameters

radar [Radar] Radar object from which ranges will be determined.

sweep [int] Sweep (0 indexed) for which to determine processing ranges.

fzl [float] Maximum altitude in meters. The determined range will not include gates which are above this limit.

doc [int, optional] Minimum number of gates which will be excluded from the determined range.

Returns

gate_end [int] Index of last gate below *fzl* and satisfying the *doc* parameter. -1 if the entire volume is above the freezing level

ray_start [int] Ray index which defines the start of the region.

ray_end [int] Ray index which defined the end of the region.

```
pyart.correct.phase_proc.det_sys_phase(radar,          ncp_lev=0.4,          rhohv_lev=0.6,
                                       ncp_field=None,      rhv_field=None,
                                       phidp_field=None)
```

Determine the system phase.

Parameters

radar [Radar] Radar object for which to determine the system phase.

ncp_lev [float, optional] Minimum normal coherent power level. Regions below this value will not be included in the phase calculation.

rhohv_lev [float, optional] Minimum copolar coefficient level. Regions below this value will not be included in the phase calculation.

ncp_field, rhv_field, phidp_field [str, optional] Field names within the radar object which represent the normal coherent power, the copolar coefficient, and the differential phase shift. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

Returns

sys_phase [float or None] Estimate of the system phase. None is not estimate can be made.

```
pyart.correct.phase_proc.det_sys_phase_gf(radar,      gatefilter,      phidp_field=None,
                                           first_gate=30.0)
```

Determine the system phase.

Parameters

radar [Radar] Radar object for which to determine the system phase.

gatefilter [Gatefilter] Gatefilter object highlighting valid gates.

phidp_field [str, optional] Field name within the radar object which represents differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

first_gate [int, optional] Gate index for where to begin applying the gatefilter.

Returns

sys_phase [float or None] Estimate of the system phase. None is not estimate can be made.

```
pyart.correct.phase_proc.det_sys_phase_ray(radar,      ind_rmin=10,      ind_rmax=500,
                                             min_rcons=11,      zmin=20.0,      zmax=40.0,
                                             phidp_field=None, refl_field=None)
```

Public method Alternative determination of the system phase. Assumes that the valid gates of phidp are only precipitation. A system phase value is found for each ray.

Parameters

- radar** [Radar] Radar object for which to determine the system phase.
- ind_rmin, ind_rmax** [int] Min and max range index where to look for continuous precipitation
- min_rcons** [int] The minimum number of consecutive gates to consider it a rain cell.
- zmin, zmax** [float] The minimum and maximum reflectivity to consider the radar bin suitable precipitation
- phidp_field** [str] Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.
- refl_field** [str] Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns

- phidp0_dict** [dict] Estimate of the system phase at each ray and metadata
- first_gates_dict** [dict] The first gate where PhiDP is valid and metadata

```
pyart.correct.phase_proc.fz1_index(fzl, ranges, elevation, radar_height)
```

Return the index of the last gate below a given altitude.

Parameters

- fzl** [float] Maximum altitude.
- ranges** [array] Range to measurement volume/gate in meters.
- elevation** [float] Elevation of antenna in degrees.
- radar_height** : Altitude of radar in meters.

Returns

- idx** [int] Index of last gate which has an altitude below *fzl*. -1 if all data is above the freezing level

Notes

Standard atmosphere is assumed, $R = 4 / 3 * R_e$

```
pyart.correct.phase_proc.get_phidp_unf(radar,      ncp_lev=0.4,      rhohv_lev=0.6,
                                         debug=False,      ncpts=20,      doc=-10,
                                         override_sys_phase=False,      sys_phase=-135,
                                         nowrap=None,      refl_field=None,      ncp_field=None,
                                         rhv_field=None,      phidp_field=None)
```

Get Unfolded Phi differential phase

Parameters

- radar** [Radar] The input radar.
- ncp_lev** [float, optional] Minimum normal coherent power level. Regions below this value will not be included in the calculation.

rhohv_lev [float, optional] Minimum copolar coefficient level. Regions below this value will not be included in the calculation.

debug [bool, optional] True to print debugging information, False to suppress printing.

ncpts [int, optional] Minimum number of points in a ray. Regions within a ray smaller than this or beginning before this gate number are excluded from calculations.

doc [int or None, optional] Index of first gate not to include in field data, None include all.

override_sys_phase [bool, optional] True to use *sys_phase* as the system phase. False will determine a value automatically.

sys_phase [float, optional] System phase, not used if *override_sys_phase* is False.

nowrap [int or None, optional] Gate number where unwrapping should begin. *None* will unwrap all gates.

refl_field ncp_field, rhv_field, phidp_field [str, optional] Field names within the radar object which represent the horizontal reflectivity, normal coherent power, the copolar coefficient, and the differential phase shift. A value of *None* for any of these parameters will use the default field name as defined in the Py-ART configuration file.

Returns

cordata [array] Unwrapped phi differential phase.

```
pyart.correct.phase_proc.get_phidp_unf_gf(radar, gatefilter, debug=False, ncpts=2,  
                                          sys_phase=None, nowrap=None,  
                                          phidp_field=None, first_gate_sysp=None)
```

Get Unfolded Phi differential phase in areas not gatefiltered.

Parameters

radar [Radar] The input radar.

gatefilter [GateFilter] Only apply on areas included in the gatefilter

debug [bool, optional] True to print debugging information, False to suppress printing.

ncpts [int, optional] Minimum number of points in a ray. Regions within a ray smaller than this or beginning before this gate number are excluded from calculations.

doc [int or None, optional] Index of first gate not to include in field data, None include all.

sys_phase [float, optional] System phase override.

nowrap [int or None, optional] Gate number where unwrapping should begin. *None* will unwrap all gates.

refl_field ncp_field, rhv_field, phidp_field [str, optional] Field names within the radar object which represent the horizontal reflectivity, normal coherent power, the copolar coefficient, and the differential phase shift. A value of *None* for any of these parameters will use the default field name as defined in the Py-ART configuration file.

Returns

cordata [array] Unwrapped phi differential phase.

```
pyart.correct.phase_proc.noise(line, wl=11)
```

Return the noise after smoothing.


```
pyart.correct.phase_proc.phase_proc_lp(radar, offset, debug=False, self_const=60000.0,
                                         low_z=10.0, high_z=53.0, min_phidp=0.01,
                                         min_ncp=0.5, min_rhv=0.8, fzl=4000.0,
                                         sys_phase=0.0, override_sys_phase=False,
                                         nowrap=None, really_verbose=False,
                                         LP_solver='cylp', refl_field=None, ncp_field=None,
                                         rhv_field=None, phidp_field=None,
                                         kdp_field=None, unf_field=None, window_len=35,
                                         proc=1, coef=0.914)
```

Phase process using a LP method [1].

Parameters

- radar** [Radar] Input radar.
- offset** [float] Reflectivity offset in dBz.
- debug** [bool, optional] True to print debugging information.
- self_const** [float, optional] Self consistency factor.
- low_z** [float, optional] Low limit for reflectivity. Reflectivity below this value is set to this limit.
- high_z** [float, optional] High limit for reflectivity. Reflectivity above this value is set to this limit.
- min_phidp** [float, optional] Minimum Phi differential phase.
- min_ncp** [float, optional] Minimum normal coherent power.
- min_rhv** [float, optional] Minimum copolar coefficient.
- fzl** [float, optional] Maximum altitude.
- sys_phase** [float, optional] System phase in degrees.
- override_sys_phase** [bool, optional] True to use *sys_phase* as the system phase. False will calculate a value automatically.
- nowrap** [int or None, optional] Gate number to begin phase unwrapping. None will unwrap all phases.
- really_verbose** [bool, optional] True to print LPX messaging. False to suppress.
- LP_solver** ['pyglpk' or 'cvxopt', 'cylp', or 'cylp_mp', optional] Module to use to solve LP problem. Default is 'cylp'.
- refl_field, ncp_field, rhv_field, phidp_field, kdp_field** [str, optional] Name of field in radar which contains the horizontal reflectivity, normal coherent power, copolar coefficient, differential phase shift, and differential phase. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.
- unf_field** [str, optional] Name of field which will be added to the radar object which will contain the unfolded differential phase. Metadata for this field will be taken from the *phidp_field*. A value of None will use the default field name as defined in the Py-ART configuration file.
- window_len** [int, optional] Length of Sobel window applied to PhiDP field when prior to calculating KDP.
- proc** [int, optional] Number of worker processes, only used when *LP_solver* is 'cylp_mp'.
- coef** [float, optional] Exponent linking Z to KDP in self consistency. $kdp=(10^{**}(0.1z))*coef$

Returns

- reproc_phase** [dict] Field dictionary containing processed differential phase shifts.

sob_kdp [dict] Field dictionary containing recalculated differential phases.

References

[1] Giangrande, S.E., R. McGraw, and L. Lei. An Application of Linear Programming to Polarimetric Radar Differential Phase Processing. J. Atmos. and Oceanic Tech, 2013, 30, 1716.

```
pyart.correct.phase_proc.phase_proc_lp_gf(radar, gatefilter=None, debug=False,
                                           self_const=60000.0, low_z=10.0, high_z=53.0,
                                           min_phidp=0.01, fzl=4000.0, system_phase=None,
                                           nowrap=None, really_verbose=False, LP_solver='cylp',
                                           refl_field=None, phidp_field=None,
                                           kdp_field=None, unf_field=None, window_len=35,
                                           proc=1, coef=0.914, ncpts=None,
                                           first_gate_sysp=None, offset=0.0, doc=0)
```

Phase process using a LP method [1] using Py-ART's Gatefilter.

Parameters

radar [Radar] Input radar.

gatefilter [Gatefilter, optional] Py-ART gatefilter object indicating where processing should be carried out

debug [bool, optional] True to print debugging information.

self_const [float, optional] Self consistency factor.

low_z [float, optional] Low limit for reflectivity. Reflectivity below this value is set to this limit.

high_z [float, optional] High limit for reflectivity. Reflectivity above this value is set to this limit.

fzl [float, optional] Maximum altitude.

system_phase [float, optional] System phase in degrees.

nowrap [int or None, optional] Gate number to begin phase unwrapping. None will unwrap all phases.

really_verbose [bool, optional] True to print LPX messaging. False to suppress.

LP_solver ['pyglpk' or 'cvxopt', 'cylp', or 'cylp_mp', optional] Module to use to solve LP problem. Default is 'cylp'.

refl_field, ncp_field, rhv_field, phidp_field, kdp_field [str, optional] Name of field in radar which contains the horizontal reflectivity, normal coherent power, copolar coefficient, differential phase shift, and differential phase. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

unf_field [str, optional] Name of field which will be added to the radar object which will contain the unfolded differential phase. Metadata for this field will be taken from the phidp_field. A value of None will use the default field name as defined in the Py-ART configuration file.

window_len [int, optional] Length of Sobel window applied to PhiDP field when prior to calculating KDP.

proc [int, optional] Number of worker processes, only used when *LP_solver* is 'cylp_mp'.

coef [float, optional] Exponent linking Z to KDP in self consistency. $kdp=(10^{**}(0.1z))*coef$

ncpts [int, optional] Minimum number of points in a ray. Regions within a ray smaller than this or beginning before this gate number are excluded from unfolding.

offset [float, optional] Reflectivity offset to add in dBz.

doc [int, optional] Number of gates to “doc” off the end of a ray.

Returns

reproc_phase [dict] Field dictionary containing processed differential phase shifts.

sob_kdp [dict] Field dictionary containing recalculated differential phases.

References

[1] Giangrande, S.E., R. McGraw, and L. Lei. An Application of Linear Programming to Polarimetric Radar Differential Phase Processing. J. Atmos. and Oceanic Tech, 2013, 30, 1716.

```
pyart.correct.phase_proc.smooth_and_trim(x, window_len=11, window='hanning')
```

Smooth data using a window with requested size.

This method is based on the convolution of a scaled window with the signal. The signal is prepared by introducing reflected copies of the signal (with the window size) in both ends so that transient parts are minimized in the beginning and end part of the output signal.

Parameters

x [array] The input signal.

window_len [int, optional] The dimension of the smoothing window; should be an odd integer.

window [str] The type of window from ‘flat’, ‘hanning’, ‘hamming’, ‘bartlett’, ‘blackman’, ‘median’ or ‘sg_smooth’. A flat window will produce a moving average smoothing.

Returns

y [array] The smoothed signal with length equal to the input signal.

```
pyart.correct.phase_proc.smooth_and_trim_scan(x, window_len=11, window='hanning')
```

Smooth data using a window with requested size.

This method is based on the convolution of a scaled window with the signal. The signal is prepared by introducing reflected copies of the signal (with the window size) in both ends so that transient parts are minimized in the beginning and end part of the output signal.

Parameters

x [ndarray] The input signal.

window_len [int, optional] The dimension of the smoothing window; should be an odd integer.

window [str, optional] The type of window from ‘flat’, ‘hanning’, ‘hamming’, ‘bartlett’, ‘blackman’, ‘median’ or ‘sg_smooth’. A flat window will produce a moving average smoothing.

Returns

y [ndarray] The smoothed signal with length equal to the input signal.

```
pyart.correct.phase_proc.smooth_masked(raw_data, wind_len=11, min_valid=6,
                                       wind_type='median')
```

smooths the data using a rolling window. data with less than n valid points is masked.

Parameters

raw_data [float masked array] The data to smooth.

window_len [float] Length of the moving window

min_valid [float] Minimum number of valid points for the smoothing to be valid

wind_type [str] type of window. Can be median or mean

Returns

data_smooth [float masked array] smoothed data

```
pyart.correct.phase_proc.smooth_masked_scan(raw_data, wind_len=11, min_valid=6,  
                                             wind_type='median')
```

smooths the data using a rolling window. data with less than n valid points is masked. Processes the entire scan at once

Parameters

raw_data [float masked array] The data to smooth.

window_len [float] Length of the moving window

min_valid [float] Minimum number of valid points for the smoothing to be valid

wind_type [str] type of window. Can be median or mean

Returns

data_smooth [float masked array] smoothed data

```
pyart.correct.phase_proc.smooth_phidp_double_window(radar, ind_rmin=10,  
                                                    ind_rmax=500, min_rcons=11,  
                                                    zmin=20.0, zmax=40,  
                                                    swind_len=11, smin_valid=6,  
                                                    lwind_len=31, lmin_valid=16,  
                                                    zthr=40.0, psidp_field=None,  
                                                    refl_field=None,  
                                                    phidp_field=None)
```

correction of the system offset and smoothing using two window

Parameters

radar [Radar] Radar object for which to determine the system phase.

ind_rmin, ind_rmax [int] Min and max range index where to look for continuous precipitation

min_rcons [int] The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax [float] Minimum and maximum reflectivity to consider it a rain cell

swind_len [int] Length of the short moving window used to smooth

smin_valid [int] Minimum number of valid bins to consider the short window smooth data valid

lwind_len [int] Length of the long moving window used to smooth

lmin_valid [int] Minimum number of valid bins to consider the long window smooth data valid

zthr [float] reflectivity value above which the short window is used

psidp_field [str] Field name within the radar object which represent the differential phase shift.
A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field [str] Field name within the radar object which represent the reflectivity. A value of
None will use the default field name as defined in the Py-ART configuration file.

phidp_field [str] Field name within the radar object which represent the corrected differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns

phidp_dict [dict] The corrected phidp field

```
pyart.correct.phase_proc.smooth_phidp_single_window(radar, ind_rmin=10,
                                                    ind_rmax=500, min_rcons=11,
                                                    zmin=20.0,    zmax=40,
                                                    wind_len=11,   min_valid=6,
                                                    psidp_field=None,
                                                    refl_field=None,
                                                    phidp_field=None)
```

correction of the system offset and smoothing using one window

Parameters

radar [Radar] Radar object for which to determine the system phase.

ind_rmin, ind_rmax [int] Min and max range index where to look for continuous precipitation

min_rcons [int] The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax [float] Minimum and maximum reflectivity to consider it a rain cell

wind_len [int] Length of the moving window used to smooth

min_valid [int] Minimum number of valid bins to consider the smooth data valid

psidp_field [str] Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field [str] Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

phidp_field [str] Field name within the radar object which represent the corrected differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns

phidp_dict [dict] The corrected phidp field

```
pyart.correct.phase_proc.snr(line, wl=11)
```

Return the signal to noise ratio after smoothing.

```
pyart.correct.phase_proc.solve_cylp(model, B_vectors, weights, ray, chunksize)
```

Worker process for LP_solver_cylp_mp.

Parameters

model [CyClpModel] Model of the LP Problem, see *LP_solver_cylp_mp()*

B_vectors [matrix] Matrix containing B vectors, see *construct_B_vectors()*

weights [array] Weights.

ray [int] Starting ray.

chunksize [int] Number of rays to process.

Returns

soln [array] Solution to LP problem.

See also:

LP_solver_cylp_mp Parent function.

LP_solver_cylp Single Process Solver.

`pyart.correct.phase_proc.unwrap_masked(lon, centered=False, copy=True)`

Unwrap a sequence of longitudes or headings in degrees.

Parameters

lon [array] Longitudes or heading in degrees. If masked output will also be masked.

centered [bool, optional] Center the unwrapping as close to zero as possible.

copy [bool, optional.] True to return a copy, False will avoid a copy when possible.

Returns

unwrap [array] Array of unwrapped longitudes or headings, in degrees.

PYART.CORRECT.REGION_DEALIAS

Region based dealiasing using a dynamic network reduction for region joining.

<code>dealias_region_based(radar[, ref_vel_field, ...])</code>	Dealias Doppler velocities using a region based algorithm.
<code>_find_regions(vel, gfilter, limits)</code>	Find regions of similar velocity.
<code>_find_sweep_interval_splits(nyquist, ...)</code>	Return the interval limits for a given sweep.
<code>_combine_regions(region_tracker, edge_tracker)</code>	Returns True when done.
<code>_edge_sum_and_count(labels, ...)</code>	Find all edges between labels regions.
<code>_cost_function(nyq_vector, vels_slice_means, ...)</code>	Cost function for minimization in region based algorithm.
<code>_gradient(nyq_vector, vels_slice_means, ...)</code>	Gradient of cost function for minimization in region based algorithm.
<hr/>	
<code>_RegionTracker(region_sizes)</code>	Tracks the location of radar volume regions contained in each node as the network is reduced.
<code>_EdgeTracker(indices, edge_count, ...)</code>	A class for tracking edges in a dynamic network.

```
class pyart.correct.region_dealias._EdgeTracker(indices, edge_count, velocities,
                                                nyquist_interval, nnodes)
    Bases: object
    A class for tracking edges in a dynamic network.
```

Methods

<code>merge_nodes(self, base_node, merge_node, ...)</code>	Merge nodes.
<code>pop_edge(self)</code>	Pop edge with largest weight.
<code>unwrap_node(self, node, nwrap)</code>	Unwrap a node.

```
__class__
    alias of builtins.type

__delattr__(self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.correct.region_dealias', '__doc__': '
__dir__(self, /)
    Default dir() implementation.
```

`__eq__` (*self*, *value*, /)
Return self==value.

`__format__` (*self*, *format_spec*, /)
Default object formatter.

`__ge__` (*self*, *value*, /)
Return self>=value.

`__getattr__` (*self*, *name*, /)
Return getattr(self, name).

`__gt__` (*self*, *value*, /)
Return self>value.

`__hash__` (*self*, /)
Return hash(self).

`__init__` (*self*, *indices*, *edge_count*, *velocities*, *nyquist_interval*, *nnodes*)
initialize

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self*, *value*, /)
Return self<=value.

`__lt__` (*self*, *value*, /)
Return self<value.

`__module__` = `'pyart.correct.region_dealias'`

`__ne__` (*self*, *value*, /)
Return self!=value.

`__new__` (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

`__reduce__` (*self*, /)
Helper for pickle.

`__reduce_ex__` (*self*, *protocol*, /)
Helper for pickle.

`__repr__` (*self*, /)
Return repr(self).

`__setattr__` (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

`__sizeof__` (*self*, /)
Size of object in memory, in bytes.

`__str__` (*self*, /)
Return str(self).

`__subclasshook__` ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__init_subclass__()`

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__(self, value, /)`

Return self<=value.

`__lt__(self, value, /)`

Return self<value.

`__module__ = 'pyart.correct.region_dealias'`

`__ne__(self, value, /)`

Return self!=value.

`__new__(*args, **kwargs)`

Create and return a new object. See help(type) for accurate signature.

`__reduce__(self, /)`

Helper for pickle.

`__reduce_ex__(self, protocol, /)`

Helper for pickle.

`__repr__(self, /)`

Return repr(self).

`__setattr__(self, name, value, /)`

Implement setattr(self, name, value).

`__sizeof__(self, /)`

Size of object in memory, in bytes.

`__str__(self, /)`

Return str(self).

`__subclasshook__()`

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`get_node_size(self, node)`

Return the number of gates in a node.

`merge_nodes(self, node_a, node_b)`

Merge node b into node a.

`unwrap_node(self, node, nwrap)`

Unwrap all gates contained a node.

`pyart.correct.region_dealias._combine_regions(region_tracker, edge_tracker)`

Returns True when done.

`pyart.correct.region_dealias._cost_function(nyq_vector, vels_slice_means, svels_slice_means, v_nyq_vel, nfeatures)`

Cost function for minimization in region based algorithm.

```
pyart.correct.region_dealias._edge_sum_and_count(labels, num_masked_gates, data,
                                                  rays_wrap_around, max_gap_x,
                                                  max_gap_y)
```

Find all edges between labels regions.

Returns the indices, count and velocities of all edges.

```
pyart.correct.region_dealias._find_regions(vel, gfilter, limits)
```

Find regions of similar velocity.

For each pair of values in the limits array (or list) find all connected velocity regions within these limits.

Parameters

vel [2D ndarray] Array containing velocity data for a single sweep.

gfilter [2D ndarray] Filter indicating if a particular gate should be masked. True indicates the gate should be masked (excluded).

limits [array like] Velocity limits for region finding. For each pair of limits, taken from elements *i* and *i*+1 of the array, all connected regions with velocities within these limits will be found.

Returns

label [ndarray] Integer array with each region labeled by a value. The array ranges from 0 to *nfeatures*, inclusive, where a value of 0 indicates masked gates and non-zero indicates a region of connected gates.

nfeatures [int] Number of regions found.

```
pyart.correct.region_dealias._find_sweep_interval_splits(nyquist, interval_splits,
                                                         velocities, nsweep)
```

Return the interval limits for a given sweep.

```
pyart.correct.region_dealias._gradient(nyq_vector, vels_slice_means, svels_slice_means,
                                       v_nyq_vel, nfeatures)
```

Gradient of cost function for minimization in region based algorithm.

```
pyart.correct.region_dealias.dealias_region_based(radar, ref_vel_field=None, interval_splits=3, interval_limits=None,
                                                  skip_between_rays=100,
                                                  skip_along_ray=100, centered=True, nyquist_vel=None,
                                                  check_nyquist_uniform=True,
                                                  gatefilter=False,
                                                  rays_wrap_around=None,
                                                  keep_original=False,
                                                  set_limits=True, vel_field=None,
                                                  corr_vel_field=None, **kwargs)
```

Dealias Doppler velocities using a region based algorithm.

Performs Doppler velocity dealiasing by finding regions of similar velocities and unfolding and merging pairs of regions until all regions are unfolded. Unfolding and merging regions is accomplished by modeling the problem as a dynamic network reduction.

Parameters

radar [Radar] Radar object containing Doppler velocities to dealias.

ref_vel_field [str or None, optional] Field in radar containing a reference velocity field used to anchor the unfolded velocities once the algorithm completes. Typically this field is created by simulating the radial velocities from wind data from an atmospheric sounding using `pyart.util.simulated_vel_from_profile()`.

interval_splits [int, optional] Number of segments to split the nyquist interval into when finding regions of similar velocity. More splits creates a larger number of initial regions which takes longer to process but may result in better dealiasing. The default value of 3 seems to be a good compromise between performance and artifact free dealiasing. This value is not used if the interval_limits parameter is not None.

interval_limits [array like or None, optional] Velocity limits used for finding regions of similar velocity. Should cover the entire nyquist interval. None, the default value, will split the Nyquist interval into interval_splits equal sized intervals.

skip_between_rays, skip_along_ray [int, optional] Maximum number of filtered gates to skip over when joining regions, gaps between region larger than this will not be connected. Parameters specify the maximum number of filtered gates between and along a ray. Set these parameters to 0 to disable unfolding across filtered gates.

centered [bool, optional] True to apply centering to each sweep after the dealiasing algorithm so that the average number of unfolding is near 0. False does not apply centering which may results in individual sweeps under or over folded by the nyquist interval.

nyquist_velocity [array like or float, optional] Nyquist velocity in unit identical to those stored in the radar's velocity field, either for each sweep or a single value which will be used for all sweeps. None will attempt to determine this value from the Radar object.

check_nyquist_uniform [bool, optional] True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the nyquist_velocity parameter is not None.

gatefilter [GateFilter, None or False, optional.] A GateFilter instance which specified which gates should be ignored when performing de-aliasing. A value of None created this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. False, the default, disables filtering including all gates in the dealiasing.

rays_wrap_around [bool or None, optional] True when the rays at the beginning of the sweep and end of the sweep should be interpreted as connected when de-aliasing (PPI scans). False if they edges should not be interpreted as connected (other scan types). None will determine the correct value from the radar scan type.

keep_original [bool, optional] True to retain the original Doppler velocity values at gates where the dealiasing procedure fails or was not applied. False does not replacement and these gates will be masked in the corrected velocity field.

set_limits [bool, optional] True to set valid_min and valid_max elements in the returned dictionary. False will not set these dictionary elements.

vel_field [str, optional] Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.

corr_vel_field [str, optional] Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.

Returns

corr_vel [dict] Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

PYRAD.CORRECT.SUNLIB

Library to deal with sun measurements

<i>sun_position_pysolar</i> (dt, lat, lon[, elevation])	obtains the sun position in antenna coordinates using the pysolar library.
<i>sun_position_mfr</i> (dt, lat_deg, lon_deg[, ...])	Calculate the sun position for the given time (dt) at the given position (lat, lon).
<i>equation_of_time</i> (dayjul)	Computes the solar hour for a given julian day.
<i>hour_angle</i> (htime, lon, eqt)	Computes the solar angle at a particular time.
<i>solar_declination</i> (dayjul, htime)	Computes the solar declination.
<i>refraction_correction</i> (es_deg)	Computes the correction that has to be applied to the sun elevation angle to account for refraction
<i>gas_att_sun</i> (es_deg, attg)	Computes the attenuation suffered by the sun signal through the atmosphere
<i>gauss_fit</i> (az_data, az_ref, el_data, el_ref, ...)	estimates a gaussian fit of sun hits data
<i>retrieval_result</i> (sunhits, alpha, beta, par, npar)	computes the physical parameters of the sun retrieval from the results of a Gaussian fit.
<i>sun_power</i> (solar_flux, pulse_width, wavelen, ...)	computes the theoretical sun power detected at the antenna [dBm] as it would be without atmospheric attenuation (sun power at top of the atmosphere) for a given solar flux and radar characteristics
<i>ptoa_to_sf</i> (ptoa, pulse_width, wavelen, ...)	Converts the sun power at the top of the atmosphere (in dBm) into solar flux.
<i>solar_flux_lookup</i> (solar_flux, wavelen)	Given the observed solar flux at 10.7 cm wavelength, returns the solar flux at the given radar wavelength
<i>scanning_losses</i> (angle_step, beamwidth)	Given the antenna beam width and the integration angle, compute the losses due to the fact that the sun is not a point target and the antenna is scanning

`pyart.correct.sunlib.equation_of_time` (*dayjul*)

Computes the solar hour for a given julian day.

Parameters

dayjul [double] julian date

Returns

eqt [float] hour

`pyart.correct.sunlib.gas_att_sun` (*es_deg*, *attg*)

Computes the attenuation suffered by the sun signal through the atmosphere

Parameters

es_deg [float] sun elevation in degrees

attg [float] 1-way gas attenuation in dB/km

Returns

gas_att_sun [float] the sun attenuation in dB

`pyart.correct.sunlib.gauss_fit` (*az_data, az_ref, el_data, el_ref, sunhits, npar, degree=True, do_elcorr=True*)
estimates a gaussian fit of sun hits data

Parameters

az_data, el_data [float array] azimuth and elevation radar data

az_ref, el_ref [float array] azimuth and elevation sun data

sunhits [float array] sun hits data

npar [int] number of parameters of the fit

degree [boolean] boolean indicating whether the data is in degree or radians

do_elcorr [boolean] indicates whether azimuth data is corrected so that azimuth differences are invalid with elevation

Returns

par [1D float array] the fit parameters

alpha: 2D float array the matrix used in the fit

beta: 1D float array the vector used in the fit

`pyart.correct.sunlib.hour_angle` (*htime, lon, eqt*)
Computes the solar angle at a particular time.

Parameters

htime [double] time in seconds since midnight

lon [float] longitude in degrees

eqt [float] solar time

Returns

angle [float] the solar angle in radians

`pyart.correct.sunlib.ptoa_to_sf` (*ptoa, pulse_width, wavelen, antenna_gain, coeff_band=1.2*)
Converts the sun power at the top of the atmosphere (in dBm) into solar flux.

Parameters

ptoa [float] sun power at the top of the atmosphere. It already takes into account the correction for antenna polarization

pulse_width [float] pulse width [s]

wavelen [float] radar wavelength [m]

antenna_gain [float] the antenna gain [dB]

coeff_band [float] multiplicative coefficient applied to the inverse of the pulse width to get the effective bandwidth

Returns

s0 [float] solar flux [10e-22 W/(m² Hz)]

References

Altube P., J. Bech, O. Argemi, T. Rigo, 2015: Quality Control of Antenna Alignment and Receiver Calibration Using the Sun: Adaptation to Midrange Weather Radar Observations at Low Elevation Angles

`pyart.correct.sunlib.refraction_correction` (*es_deg*)

Computes the correction that has to be applied to the sun elevation angle to account for refraction

Parameters

es_deg [float] sun elevation in degrees

Returns

refr [float] the correction due to refraction in degrees

References

Holleman & Huuskonen, 2013: analytical formulas for refraction of radiowaves from exoatmospheric sources, radio science, vol. 48, 226-231

`pyart.correct.sunlib.retrieval_result` (*sunhits, alpha, beta, par, npar*)

computes the physical parameters of the sun retrieval from the results of a Gaussian fit.

Parameters

sunhits [float array] sun hits data

alpha: 2D float array the matrix used in the fit

beta: 1D float array the vector used in the fit

par [1D float array] the fit parameters

npar [int] number of parameters of the fit

Returns

val, val_std [float] retrieved value and its standard deviation

az_bias, el_bias [float] retrieved azimuth and elevation antenna bias respect to the sun position

az_width, el_width [float] retrieved azimuth and elevation antenna widths

`pyart.correct.sunlib.scanning_losses` (*angle_step, beamwidth*)

Given the antenna beam width and the integration angle, compute the losses due to the fact that the sun is not a point target and the antenna is scanning

Parameters

angle_step [float] integration angle [deg]

beamwidth [float] 3 dB-beamwidth [deg]

Returns

la [float] The losses due to the scanning of the antenna [dB positive]

References

Altube P., J. Bech, O. Argemi, T. Rigo, 2015: Quality Control of Antenna Alignment and Receiver Calibration Using the Sun: Adaptation to Midrange Weather Radar Observations at Low Elevation Angles

`pyart.correct.sunlib.solar_declination(dayjul, htime)`

Computes the solar declination.

Parameters

dayjul [double] julian date

htime [double] time in seconds since midnight

Returns

angle [float] the solar declination in radians

`pyart.correct.sunlib.solar_flux_lookup(solar_flux, wavelen)`

Given the observed solar flux at 10.7 cm wavelength, returns the solar flux at the given radar wavelength

Parameters

solar_flux [float array] the solar fluxes measured at 10.7 cm wavelength [10e-22 W/(m² Hz)]

wavelen [float] radar wavelength [m]

Returns

s0 [float] the radar flux at the radar wavelength [10e-22 W/(m² Hz)]

References

Altube P., J. Bech, O. Argemi, T. Rigo, 2015: Quality Control of Antenna Alignment and Receiver Calibration Using the Sun: Adaptation to Midrange Weather Radar Observations at Low Elevation Angles

`pyart.correct.sunlib.sun_position_mfr(dt, lat_deg, lon_deg, refraction=True)`

Calculate the sun position for the given time (dt) at the given position (lat, lon).

Parameters

dt [datetime object] the time when to look for the sun

lat_deg, lon_deg: floats latitude and longitude in degrees

refraction [boolean] whether to correct for refraction or not

Returns

elev_sun, azim_sun [floats] elevation and azimuth angles of the sun respect to the sensor in degrees

`pyart.correct.sunlib.sun_position_pysolar(dt, lat, lon, elevation=0.0)`

obtains the sun position in antenna coordinates using the pysolar library.

Parameters

dt [datetime object] the time when to look for the sun

lat, lon [float] latitude and longitude of the sensor in degrees

Returns

el, az [float] elevation and azimuth angles of the sun respect to the sensor in degrees

`pyart.correct.sunlib.sun_power(solar_flux, pulse_width, wavelen, antenna_gain, angle_step, beamwidth, coeff_band=1.2)`

computes the theoretical sun power detected at the antenna [dBm] as it would be without atmospheric attenuation (sun power at top of the atmosphere) for a given solar flux and radar characteristics

Parameters

solar_flux [float array] the solar fluxes measured at 10.7 cm wavelength [10e-22 W/(m² Hz)]

pulse_width [float] pulse width [s]

wavelen [float] radar wavelength [m]

antenna_gain [float] the antenna gain [dB]

angle_step [float] integration angle [deg]

beamwidth [float] 3 dB-beamwidth [deg]

coeff_band [float] multiplicative coefficient applied to the inverse of the pulse width to get the effective bandwidth

Returns

pwr_det [float array] the detected power

References

Altube P., J. Bech, O. Argemi, T. Rigo, 2015: Quality Control of Antenna Alignment and Receiver Calibration Using the Sun: Adaptation to Midrange Weather Radar Observations at Low Elevation Angles

PYART.CORRECT.UNWRAP

Dealias using multidimensional phase unwrapping algorithms.

<code>dealias_unwrap_phase(radar[, unwrap_unit, ...])</code>	Dealias Doppler velocities using multi-dimensional phase unwrapping.
<code>_dealias_unwrap_3d(radar, vdata, ...)</code>	Dealias using 3D phase unwrapping (full volume at once).
<code>_dealias_unwrap_2d(radar, vdata, ...)</code>	Dealias using 2D phase unwrapping (sweep-by-sweep).
<code>_dealias_unwrap_1d(vdata, nyquist_vel)</code>	Dealias using 1D phase unwrapping (ray-by-ray).
<code>_verify_unwrap_unit(radar, unwrap_unit)</code>	Verify that the radar supports the requested unwrap unit
<code>_is_radar_cubic(radar)</code>	Test if a radar is cubic (sweeps have the same number of rays).
<code>_is_radar_sweep_aligned(radar[, diff])</code>	Test that all sweeps in the radar sample nearly the same angles.
<code>_is_radar_sequential(radar)</code>	Test if all sweeps in radar are sequentially ordered.
<code>_is_sweep_sequential(radar, sweep_number)</code>	Test if a specific sweep is sequentially ordered.

`pyart.correct.unwrap._dealias_unwrap_1d(vdata, nyquist_vel)`

Dealias using 1D phase unwrapping (ray-by-ray).

`pyart.correct.unwrap._dealias_unwrap_2d(radar, vdata, nyquist_vel, gfilter, rays_wrap_around)`

Dealias using 2D phase unwrapping (sweep-by-sweep).

`pyart.correct.unwrap._dealias_unwrap_3d(radar, vdata, nyquist_vel, gfilter, rays_wrap_around)`

Dealias using 3D phase unwrapping (full volume at once).

`pyart.correct.unwrap._is_radar_cubic(radar)`

Test if a radar is cubic (sweeps have the same number of rays).

`pyart.correct.unwrap._is_radar_sequential(radar)`

Test if all sweeps in radar are sequentially ordered.

`pyart.correct.unwrap._is_radar_sweep_aligned(radar, diff=0.1)`

Test that all sweeps in the radar sample nearly the same angles.

Test that the maximum difference in sweep sampled angles is below *diff* degrees. The radar should first be tested to verify that is cubic before calling this function using the `_is_radar_cubic` function.

`pyart.correct.unwrap._is_sweep_sequential(radar, sweep_number)`

Test if a specific sweep is sequentially ordered.

`pyart.correct.unwrap._verify_unwrap_unit(radar, unwrap_unit)`

Verify that the radar supports the requested unwrap unit

raises a `ValueError` if the `unwrap_unit` is not supported.

```
pyart.correct.unwrap.dealias_unwrap_phase(radar,                      unwrap_unit='sweep',
                                           nyquist_vel=None,
                                           check_nyquist_uniform=True,      gate-
                                           filter=False,      rays_wrap_around=None,
                                           keep_original=False,      set_limits=True,
                                           vel_field=None,      corr_vel_field=None,
                                           skip_checks=False, **kwargs)
```

Dealias Doppler velocities using multi-dimensional phase unwrapping.

Parameters

radar [Radar] Radar object containing Doppler velocities to dealias.

unwrap_unit [{ 'ray', 'sweep', 'volume' }, optional] Unit to unwrap independently. 'ray' will unwrap each ray individually, 'sweep' each sweep, and 'volume' will unwrap the entire volume in a single pass. 'sweep', the default, often gives superior results when the lower sweeps of the radar volume are contaminated by clutter. 'ray' does not use the `gatefilter` parameter and rays where gates are masked will result in poor dealiasing for that ray.

nyquist_velocity [array like or float, optional] Nyquist velocity in unit identical to those stored in the radar's velocity field, either for each sweep or a single value which will be used for all sweeps. None will attempt to determine this value from the Radar object. The Nyquist velocity of the first sweep is used for all dealiasing unless the `unwrap_unit` is 'sweep' when the velocities of each sweep are used.

check_nyquist_uniform [bool, optional] True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the `nyquist_velocity` parameter is not None.

gatefilter [GateFilter, None or False, optional.] A `GateFilter` instance which specified which gates should be ignored when performing de-aliasing. A value of None created this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. False, the default, disables filtering including all gates in the dealiasing.

rays_wrap_around [bool or None, optional] True when the rays at the beginning of the sweep and end of the sweep should be interpreted as connected when de-aliasing (PPI scans). False if they edges should not be interpreted as connected (other scan types). None will determine the correct value from the radar scan type.

keep_original [bool, optional] True to retain the original Doppler velocity values at gates where the dealiasing procedure fails or was not applied. False does not replacement and these gates will be masked in the corrected velocity field.

set_limits [bool, optional] True to set `valid_min` and `valid_max` elements in the returned dictionary. False will not set these dictionary elements.

vel_field [str, optional] Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.

corr_vel_field [str, optional] Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.

skip_checks [bool] True to skip checks verifying that an appropriate `unwrap_unit` is selected, False retains these checked. Setting this parameter to True is not recommended and is only offered as an option for extreme cases.

Returns

corr_vel [dict] Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

References

[?], [?]

PYART.CORRECT._COMMON_DEALIAS

Routines used by multiple dealiasing functions.

<code>_parse_fields(vel_field, corr_vel_field)</code>	Parse and return the radar fields for dealiasing.
<code>_parse_nyquist_vel(nyquist_vel, radar, ...)</code>	Parse the nyquist_vel parameter, extract from the radar if needed.
<code>_parse_gatefilter(gatefilter, radar, <i>**kwargs</i>)</code>	Parse the gatefilter, return a valid GateFilter object.
<code>_parse_rays_wrap_around(rays_wrap_around, radar)</code>	Parse the rays_wrap_around parameter.
<code>_set_limits(data, nyquist_vel, dic)</code>	Set the valid_min and valid_max keys in dic from dealiased data.

`pyart.correct._common_dealias._parse_fields(vel_field, corr_vel_field)`
Parse and return the radar fields for dealiasing.

`pyart.correct._common_dealias._parse_gatefilter(gatefilter, radar, **kwargs)`
Parse the gatefilter, return a valid GateFilter object.

`pyart.correct._common_dealias._parse_nyquist_vel(nyquist_vel, radar, check_uniform)`
Parse the nyquist_vel parameter, extract from the radar if needed.

`pyart.correct._common_dealias._parse_rays_wrap_around(rays_wrap_around, radar)`
Parse the rays_wrap_around parameter.

`pyart.correct._common_dealias._set_limits(data, nyquist_vel, dic)`
Set the valid_min and valid_max keys in dic from dealiased data.

PYART.CORRECT._FAST_EDGE_FINDER

Cython routine for quickly finding edges between connected regions.

<code>_fast_edge_finder()</code>	Return the gate indices and velocities of all edges between regions.
----------------------------------	--

class `pyart.correct._fast_edge_finder._EdgeCollector`

Bases: `object`

Class for collecting edges, used by `_edge_sum_and_count` function.

Methods

<code>get_indices_and_velocities()</code>	Return the edge indices and velocities.
---	---

```
__class__
    alias of builtins.type

__delattr__ (self, name, /)
    Implement delattr(self, name).

__dir__ (self, /)
    Default dir() implementation.

__eq__ (self, value, /)
    Return self==value.

__format__ (self, format_spec, /)
    Default object formatter.

__ge__ (self, value, /)
    Return self>=value.

__getattr__ (self, name, /)
    Return getattr(self, name).

__gt__ (self, value, /)
    Return self>value.

__hash__ (self, /)
    Return hash(self).

__init__
    initialize.
```

__init_subclass__()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__(*self*, *value*, /)

Return self<=value.

__lt__(*self*, *value*, /)

Return self<value.

__ne__(*self*, *value*, /)

Return self!=value.

__new__(*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__()

__reduce_ex__(*self*, *protocol*, /)

Helper for pickle.

__repr__(*self*, /)

Return repr(self).

__setattr__(*self*, *name*, *value*, /)

Implement setattr(self, name, value).

__setstate__()

__sizeof__(*self*, /)

Size of object in memory, in bytes.

__str__(*self*, /)

Return str(self).

__subclasshook__()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

get_indices_and_velocities()

Return the edge indices and velocities.

pyart.correct._fast_edge_finder.**fast_edge_finder**()

Return the gate indices and velocities of all edges between regions.

PYART.CORRECT._FOURDD_INTERFACE

Cython wrapper around the University of Washington FourDD algorithm.

<i>create_soundvolume()</i>	Create a RSL Volume containing sounding data.
<i>fourdd_dealias(radialVelVolume, ...[, ...])</i>	Dealias using the FourDD algorithm.

`pyart.correct._fourdd_interface.create_soundvolume()`

Create a RSL Volume containing sounding data.

Parameters

radialVelVolume [*_RslVolume*] Radial velocities which will be dealiased, shape used to create soundvolume.

hc [*ndarray*] Sounding heights in meters. Must be a contiguous one-dimensional float32 array.

sc [*ndarray*] Sounding wind speed in m/s. Must be a contiguous one-dimensional float32 array.

dc [*ndarray*] Sounding wind direction in degrees. Must be a contiguous one-dimensional float32 array.

maxshear [*float*] Maximum vertical shear which will be incorporated into the created volume.

sign [*int*] Sign convention which the radial velocities in the created volume will follow. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.

Returns

usuccess [*int*] Flag indicating if loading of data was successful, 1 = yes, 0 = no.

soundvolume [*_RslVolume*] *RslVolume* containing sounding data.

`pyart.correct._fourdd_interface.fourdd_dealias(radialVelVolume, lastVelVolume, sound-`
`Volume, filt, compthresh=0.25,`
`compthresh2=0.49, thresh=0.4,`
`epsilon=0.00001, ckval=1.0,`
`stdthresh=0.8, maxcount=10, pass2=1,`
`rm=0, proximity=5, mingood=5,`
`ba_mincount=5, ba_edgcount=3,`
`debug=False)`

Dealias using the FourDD algorithm.

Parameters

radialVelVolume [*_RslVolume*] Radial velocities which will be dealiased.

lastVelVolume [_RslVolume or None] Radial velocities from a previously dealiased radar volume. For best results, this radar should represent the previous volume scan in time. If the last velocity volume is unavailable, set this to None.

soundVolume [_RslVolume or None] Volume created from sounding data. If unavailable, set this to None. soundVolume and lastVelVolume cannot both be None.

filt [int] Flag controlling Bergen and Albers filter, 1 = yes, 0 = no.

Returns

usuccess [int] Flag indicating if the unfolding was successful, 1 = yes, 0 = no.

data [np.ndarray] Array of unfolded velocities.

Other Parameters

compthresh [float] Fraction of the Nyquist velocity to use as a threshold when performing continuity (initial) dealiasing. Velocities differences above this threshold will not be marked as gate from which to begin unfolding during spatial dealiasing.

compthresh2 [float] The same as compthresh but the value used during the second pass of dealiasing. This second pass is only performed in both a sounding and last volume are provided.

thresh [float] Fraction of the Nyquist velocity to use as a threshold when performing spatial dealiasing. Horizontally adjacent gates with velocities above this threshold will count against assigning the gate in question the velocity value being tested.

ckval [float] When the absolute value of the velocities are below this value they will not be marked as gates from which to begin unfolding during spatial dealiasing.

stdthresh [float] Fraction of the Nyquist velocity to use as a standard deviation threshold in the window dealiasing portion of the algorithm.

epsilon [float] Difference used when comparing a value to missing value, changing this from the default is not recommended.

maxcount [int] Maximum allowed number of fold allowed when unfolding velocities.

pass2 [int] Controls whether unfolded gates should be removed (a value of 0) or retained for unfolding during the second pass (a value of 1) when both a sounding volume and last volume are provided.

rm [int] Determines what should be done with gates that are left unfolded after the first pass of dealiasing. A value of 1 will remove these gates, a value of 0 sets these gates to their initial velocity. If both a sounding volume and last volume are provided this parameter is ignored.

proximity [int] Number of gates and rays to include of either side of the current gate during window dealiasing. This value may be doubled in cases where a standard sized window does not capture a sufficient number of good valued gates.

mingood [int] Number of good valued gates required within the window before the current gate will be unfolded.

ba_mincount [int] Number of neighbors required during Bergen and Albers filter for a given gate to be included, must be between 1 and 8, 5 recommended.

ba_edgecount [int] Same as ba_mincount but used at ray edges, must be between 1 and 5, 3 recommended.

debug [bool] True to return RSL Volume objects for debugging: usuccess, radialVelVolume, lastVelVolume, soundVolume, unfoldedVolume

References

C. N. James and R. A. Houze Jr, A Real-Time Four-Dimensional Doppler Dealising Scheme, *Journal of Atmospheric and Oceanic Technology*, 2001, 18, 1674.

PYART.CORRECT._UNWRAP_1D

unwrap_1d()

Phase unwrapping using the naive approach.

`pyart.correct._unwrap_1d.unwrap_1d()`
Phase unwrapping using the naive approach.

PYART.CORRECT._UNWRAP_2D

unwrap_2d()

2D phase unwrapping.

`pyart.correct._unwrap_2d.unwrap_2d()`
2D phase unwrapping.

PYART.CORRECT._UNWRAP_3D

unwrap_3d()

3D phase unwrapping.

`pyart.correct._unwrap_3d.unwrap_3d()`
3D phase unwrapping.

PYART.RETRIEVE.ADVECTION

Advection calculations.

<i>grid_displacement_pc</i> (grid1, grid2, field, level)	Calculate the grid displacement using phase correlation.
<i>grid_shift</i> (grid, advection[, trim_edges, ...])	Shift a grid by a certain number of pixels.

```
pyart.retrieve.advection.grid_displacement_pc(grid1, grid2, field, level, re-  
turn_value='pixels')
```

Calculate the grid displacement using phase correlation.

See: http://en.wikipedia.org/wiki/Phase_correlation

Implementation inspired by Christoph Gohlke: <http://www.lfd.uci.edu/~gohlke/code/imreg.py.html>

Note that the grid must have the same dimensions in x and y and assumed to have constant spacing in these dimensions.

Parameters

grid1, grid2 [Grid] Py-ART Grid objects separated in time and square in x/y.

field [string] Field to calculate advection from. Field must be in both grid1 and grid2.

level [integer] The vertical (z) level of the grid to use in the calculation.

return_value [str, optional] 'pixels', 'distance' or 'velocity'. Distance in pixels (default) or meters or velocity vector in m/s.

Returns

displacement [two-tuple] Calculated displacement in units of y and x. Value returned in integers if pixels, otherwise floats.

```
pyart.retrieve.advection.grid_shift(grid, advection, trim_edges=0, field_list=None)
```

Shift a grid by a certain number of pixels.

Parameters

grid: Grid Py-ART Grid object.

advection [two-tuple of floats] Number of Pixels to shift the image by.

trim_edges: integer, optional Edges to cut off the grid and axes, both x and y. Defaults to zero.

field_list [list, optional] List of fields to include in new grid. None, the default, includes all fields from the input grid.

Returns

shifted_grid [Grid] Grid with fields shifted and, if requested, subset.

PYART.RETRIEVE.ECHO_CLASS

Functions for echo classification.

<code>steiner_conv_strat(grid[, dx, dy, intense, ...])</code>	Partition reflectivity into convective-stratiform using the Steiner et al.
<code>hydroclass_semisupervised(radar[, ...])</code>	Classifies precipitation echoes following the approach by Besic et al (2016).
<code>get_freq_band(freq)</code>	Returns the frequency band name (S, C, X, ...).
<code>_standardize(data, field_name[, mx, mn])</code>	Stretches the radar data to -1 to 1 interval.
<code>_assign_to_class(zh, zdr, kdp, rhohv, relh, ...)</code>	Assigns an hydrometeor class to a radar range bin computing the distance between the radar variables an a centroid.
<code>_assign_to_class_scan(zh, zdr, kdp, rhohv, ...)</code>	assigns an hydrometeor class to a radar range bin computing the distance between the radar variables an a centroid.
<code>_compute_coeff_transform(mass_centers[, ...])</code>	get the transformation coefficients
<code>_get_mass_centers(freq)</code>	Get mass centers for a particular frequency.
<code>_mass_centers_table()</code>	Defines the mass centers look up table for each frequency band.
<code>_data_limits_table()</code>	Defines the data limits used in the standardization.

`pyart.retrieve.echo_class._assign_to_class(zh, zdr, kdp, rhohv, relh, mass_centers, weights=array([1., 1., 1., 0.75, 0.5]), t_vals=None)`

Assigns an hydrometeor class to a radar range bin computing the distance between the radar variables an a centroid.

Parameters

zh, zdr, kdp, rhohv, relh [radar field] variables used for assignment normalized to [-1, 1] values

mass_centers [matrix] centroids normalized to [-1, 1] values (nclasses, nvariables)

weights [array] optional. The weight given to each variable (nvariables)

t_vals [array] transformation values for the distance to centroids (nclasses)

Returns

hydroclass [int array] the index corresponding to the assigned class

entropy [float array] the entropy

t_dist [float matrix] if entropy is computed, the transformed distances of each class (proxy for proportions of each hydrometeor) (nrays, nbins, nclasses)

```
pyart.retrieve.echo_class._assign_to_class_scan(zh, zdr, kdp, rhohv, relh, mass_centers,
                                                weights=array([1., 1., 1., 0.75, 0.5 ]),
                                                t_vals=None)
```

assigns an hydrometeor class to a radar range bin computing the distance between the radar variables an a centroid. Computes the entire radar volume at once

Parameters

zh, zdr, kdp, rhohv, relh [radar field] variables used for assignment normalized to [-1, 1] values

mass_centers [matrix] centroids normalized to [-1, 1] values

weights [array] optional. The weight given to each variable

t_vals [matrix] transformation values for the distance to centroids (nclasses, nvariables)

Returns

hydroclass [int array] the index corresponding to the assigned class

entropy [float array] the entropy

t_dist [float matrix] if entropy is computed, the transformed distances of each class (proxy for proportions of each hydrometeor) (nrays, nbins, nclasses)

```
pyart.retrieve.echo_class._compute_coeff_transform(mass_centers, weights=array([1.,
                                                                                   1., 1., 0.75, 0.5 ]), value=50.0)
```

get the transformation coefficients

Parameters

mass_centers [ndarray 2D] The centroids for each class and variable (nclasses, nvariables)

weights [array] optional. The weight given to each variable (nvariables)

value [float] parameter controlling the rate of decay of the distance transformation

Returns

t_vals [ndarray 1D] The coefficients used to transform the distances to each centroid for each class (nclasses)

```
pyart.retrieve.echo_class._data_limits_table()
```

Defines the data limits used in the standardization.

Returns

dlimits_dict [dict] A dictionary with the limits for each variable.

```
pyart.retrieve.echo_class._get_mass_centers(freq)
```

Get mass centers for a particular frequency.

Parameters

freq [float] Radar frequency [Hz].

Returns

mass_centers [ndarray 2D] The centroids for each variable and hydrometeor class in (nclasses, nvariables).

```
pyart.retrieve.echo_class._mass_centers_table()
```

Defines the mass centers look up table for each frequency band.

Returns

mass_centers_dict [dict] A dictionary with the mass centers for each frequency band.

`pyart.retrieve.echo_class._standardize(data, field_name, mx=None, mn=None)`

Stretches the radar data to -1 to 1 interval.

Parameters

data [array] Radar field.

field_name [str] Type of field (relH, Zh, ZDR, KDP or RhoHV).

mx, mn [floats or None, optional] Data limits for array values.

Returns

field_std [dict] Standardized radar data.

`pyart.retrieve.echo_class.get_freq_band(freq)`

Returns the frequency band name (S, C, X, ...).

Parameters

freq [float] Radar frequency [Hz].

Returns

freq_band [str] Frequency band name.

`pyart.retrieve.echo_class.hydroclass_semisupervised(radar, mass_centers=None, weights=array([1., 1., 0.75, 0.5]), value=50.0, refl_field=None, zdr_field=None, rhv_field=None, kdp_field=None, temp_field=None, iso0_field=None, dro_field=None, temp_ref='temperature', compute_entropy=False, output_distances=False, vectorize=False)`

Classifies precipitation echoes following the approach by Besic et al (2016).

Parameters

radar [radar] Radar object.

mass_centers [ndarray 2D, optional] The centroids for each variable and hydrometeor class in (nclasses, nvariables).

weights [ndarray 1D, optional] The weight given to each variable.

value [float] The value controlling the rate of decay in the distance transformation

refl_field, zdr_field, rhv_field, kdp_field, temp_field, iso0_field [str] Inputs. Field names within the radar object which represent the horizontal reflectivity, the differential reflectivity, the copolar correlation coefficient, the specific differential phase, the temperature and the height respect to the iso0 fields. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

hydro_field [str] Output. Field name which represents the hydrometeor class field. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be either temperature or height_over_iso0

compute_entropy [bool] If true, the entropy is computed

output_distances [bool] If true, the normalized distances to the centroids for each hydrometeor are provided as output

vectorize [bool] If true, a vectorized version of the class assignment is going to be used

Returns

fields_dict [dict] Dictionary containing the retrieved fields

References

Besic, N., Figueras i Ventura, J., Grazioli, J., Gabella, M., Germann, U., and Berne, A.: Hydrometeor classification through statistical clustering of polarimetric radar measurements: a semi-supervised approach, Atmos. Meas. Tech., 9, 4425-4445, doi:10.5194/amt-9-4425-2016, 2016

```
pyart.retrieve.echo_class.steiner_conv_strat(grid, dx=None, dy=None, intense=42.0, work_level=3000.0,
                                             peak_relation='default',
                                             area_relation='medium',
                                             bkg_rad=11000.0, use_intense=True,
                                             fill_value=None, refl_field=None)
```

Partition reflectivity into convective-stratiform using the Steiner et al. (1995) algorithm.

Parameters

grid [Grid] Grid containing reflectivity field to partition.

dx, dy [float, optional] The x- and y-dimension resolutions in meters, respectively. If None the resolution is determined from the first two axes values.

intense [float, optional] The intensity value in dBZ. Grid points with a reflectivity value greater or equal to the intensity are automatically flagged as convective. See reference for more information.

work_level [float, optional] The working level (separation altitude) in meters. This is the height at which the partitioning will be done, and should minimize bright band contamination. See reference for more information.

peak_relation ['default' or 'sgp', optional] The peakedness relation. See reference for more information.

area_relation ['small', 'medium', 'large', or 'sgp', optional] The convective area relation. See reference for more information.

bkg_rad [float, optional] The background radius in meters. See reference for more information.

use_intense [bool, optional] True to use the intensity criteria.

fill_value [float, optional] Missing value used to signify bad data points. A value of None will use the default fill value as defined in the Py-ART configuration file.

refl_field [str, optional] Field in grid to use as the reflectivity during partitioning. None will use the default reflectivity field name from the Py-ART configuration file.

Returns

eclass [dict] Steiner convective-stratiform classification dictionary.

References

Steiner, M. R., R. A. Houze Jr., and S. E. Yuter, 1995: Climatological Characterization of Three-Dimensional Storm Structure from Operational Radar and Rain Gauge Data. *J. Appl. Meteor.*, 34, 1978-2007.

PYART.RETRIEVE.GATE_ID

<code>map_profile_to_gates(profile, heights, radar)</code>	Given a profile of a variable map it to the gates of radar assuming 4/3Re.
<code>fetch_radar_time_profile(sonde_dset, radar)</code>	Extract the correct profile from a interpolated sonde.

```
pyart.retrieve.gate_id.fetch_radar_time_profile(sonde_dset, radar, time_key='time',  
                                                height_key='height', nvars=None)
```

Extract the correct profile from a interpolated sonde.

This is an ARM specific method which extract the correct profile out of netCDF Variables from a Interpolated Sonde VAP for the volume start time of a radar object.

Parameters

sonde_dset [Dataset] Interpolate sonde Dataset.

radar [Radar] Radar object from which the nearest profile will be found.

time_key [string, optional] Key to find a CF startard time variable.

height_key [string, optional] Key to find profile height data.

nvars [list, optional] NetCDF variable to generated profiles for. If None (the default) all variables with dimension of time, height will be found in nvars.

Returns

return_dic [dict] Profiles at the start time of the radar.

```
pyart.retrieve.gate_id.map_profile_to_gates(profile, heights, radar, toa=None, profile_field=None, height_field=None)
```

Given a profile of a variable map it to the gates of radar assuming 4/3Re.

Parameters

profile [array] Profile array to map.

heights [array] Monotonically increasing heights in meters with same shape as profile.

radar [Radar] Radar to map to.

toa [float, optional] Top of atmosphere, where to use profile up to. If None check for mask and use lowest element, if no mask uses whole profile.

height_field [str, optional] Name to use for height field metadata. None will use the default field name from the Py-ART configuration file.

profile_field [str, optional] Name to use for interpolate profile field metadata. None will use the default field name from the Py-ART configuration file.

Returns

height_dict, profile_dict [dict] Field dictionaries containing the height of the gates and the profile interpolated onto the radar gates.

PYART.RETRIEVE.RADAR

Retrievals from spectral data.

<i>compute_spectra</i> (radar, fields_in_list, ...)	Computes the spectra from IQ data through a Fourier transform
<i>compute_pol_variables_iq</i> (radar, fields_list)	Computes the polarimetric variables from the IQ signals in ADU
<i>compute_reflectivity_iq</i> (radar[, ...])	Computes the reflectivity from the IQ signal data
<i>compute_st1_iq</i> (radar[, signal_field])	Computes the statistical test one lag fluctuation from the horizontal or vertical channel IQ data
<i>compute_st2_iq</i> (radar[, signal_field])	Computes the statistical test two lag fluctuation from the horizontal or vertical channel IQ data
<i>compute_wbn_iq</i> (radar[, signal_field])	Computes the wide band noise from the horizontal or vertical channel IQ data
<i>compute_differential_reflectivity_iq</i> (radar[, ...])	Computes the differential reflectivity from the horizontal and vertical IQ data
<i>compute_mean_phase_iq</i> (radar[, signal_field])	Computes the differential phase from the horizontal or vertical channel IQ data
<i>compute_differential_phase_iq</i> (radar[, ...])	Computes the differential phase from the horizontal and vertical channels IQ data
<i>compute_rhohv_iq</i> (radar[, subtract_noise, ...])	Computes RhoHV from the horizontal and vertical channels IQ data
<i>compute_Doppler_velocity_iq</i> (radar[, ...])	Computes the Doppler velocity from the IQ data
<i>compute_Doppler_width_iq</i> (radar[, ...])	Computes the Doppler width from the IQ data
<i>_compute_power</i> (signal[, noise, subtract_noise])	Compute the signal power in linear units
<i>_compute_autocorrelation</i> (radar, signal_field)	Compute the signal autocorrelation in linear units
<i>_compute_lag_diff</i> (radar, signal_field[, ...])	Compute the signal autocorrelation in linear units
<i>_compute_crosscorrelation</i> (radar, ...[, lag])	Compute the cross-correlation between H and V in linear units

`pyart.retrieve.iq._compute_autocorrelation` (radar, signal_field, lag=1)

Compute the signal autocorrelation in linear units

Parameters

radar [IQ radar object] The radar object containing the fields

signal_field [str] The IQ signal

lag [int] Time lag to compute

Returns

rlag [float array] The computed autocorrelation lag

`pyart.retrieve.iq._compute_crosscorrelation(radar, signal_h_field, signal_v_field, lag=1)`
Compute the cross-correlation between H and V in linear units

Parameters

radar [IQ radar object] The radar object containing the fields
signal_h_field, signal_v_field [str] The IQ H and V signal names
lag [int] Time lag to compute

Returns

rlag [float array] The computed cross-correlation lag

`pyart.retrieve.iq._compute_lag_diff(radar, signal_field, is_log=True, lag=1)`
Compute the signal autocorrelation in linear units

Parameters

radar [IQ radar object] The radar object containing the fields
signal_field [str] The IQ signal
lag [int] Time lag to compute

Returns

rlag [float array] The computed autocorrelation lag

`pyart.retrieve.iq._compute_power(signal, noise=None, subtract_noise=False)`
Compute the signal power in linear units

Parameters

signal [float array] The IQ signal
noise [float array] The noise power per pulse
subtract_noise [Bool] If True and noise not None the noise power will be subtracted from the signal power

Returns

pwr [float array] The computed signal power

`pyart.retrieve.iq.compute_Doppler_velocity_iq(radar, signal_field=None, direction='negative_away')`

Computes the Doppler velocity from the IQ data

Parameters

radar [IQ radar object] Object containing the required fields
signal_field [str] Name of the field in the radar which contains the signal. None will use the default field name in the Py-ART configuration file.
direction [str] The convention used in the Doppler mean field. Can be negative_away or negative_towards

Returns

vel_dict [field dictionary] Field dictionary containing the Doppler velocity

`pyart.retrieve.iq.compute_Doppler_width_iq(radar, subtract_noise=True, signal_field=None, noise_field=None, lag=1)`

Computes the Doppler width from the IQ data

Parameters

radar [Radar radar object] Object containing the required fields

subtract_noise [Bool] If True noise will be subtracted from the signals

lag [int] Time lag used in the denominator of the computation

signal_field, noise_field [str] Name of the field in the radar which contains the signal and noise.
None will use the default field name in the Py-ART configuration file.

Returns

width_dict [field dictionary] Field dictionary containing the Doppler spectrum width

```
pyart.retrieve.iq.compute_differential_phase_iq(radar, phase_offset=0.0,
                                                signal_h_field=None, signal_v_field=None,
                                                noise_h_field=None, noise_v_field=None)
```

Computes the differential phase from the horizontal and vertical channels IQ data

Parameters

radar [IQ radar object] Object containing the required fields

phase_offset [float] system phase offset to add

signal_h_field, signal_v_field [str] Name of the fields that contain the H and V IQ data. None will use the default field name in the Py-ART configuration file.

Returns

phidp_dict [field dictionary] Field dictionary containing the differential phase

```
pyart.retrieve.iq.compute_differential_reflectivity_iq(radar, subtract_noise=False, lag=0,
                                                       signal_h_field=None, signal_v_field=None,
                                                       noise_h_field=None, noise_v_field=None)
```

Computes the differential reflectivity from the horizontal and vertical IQ data

Parameters

radar [IQ radar object] Object containing the required fields

subtract_noise [Bool] If true the noise is subtracted from the power

lag [int] Time lag used to compute the differential reflectivity

signal_h_field, signal_v_field, noise_h_field, noise_v_field [str] Name of the signal and noise fields. None will use the default field name in the Py-ART configuration file.

Returns

zdr_dict [field dictionary] Field dictionary containing the differential reflectivity

```
pyart.retrieve.iq.compute_mean_phase_iq(radar, signal_field=None)
```

Computes the differential phase from the horizontal or vertical channel IQ data

Parameters

radar [IQ radar object] Object containing the required fields

signal_field [str] Name of the field that contain the H or V IQ data. None will use the default field name in the Py-ART configuration file.

Returns

mph_dict [field dictionary] Field dictionary containing the mean phase

```
pyart.retrieve.iq.compute_pol_variables_iq(radar, fields_list, subtract_noise=False,
                                           lag=0, direction='negative_away',
                                           phase_offset=0.0, signal_h_field=None,
                                           signal_v_field=None, noise_h_field=None,
                                           noise_v_field=None)
```

Computes the polarimetric variables from the IQ signals in ADU

Parameters

radar [IQ radar object] Object containing the required fields

fields_list [list of str] list of fields to compute

subtract_noise [Bool] If True noise will be subtracted from the signals

lag [int] The time lag to use in the estimators

direction [str] The convention used in the Doppler mean field. Can be `negative_away` or `negative_towards`

phase_offset [float. Dataset keyword] The system differential phase offset to remove

signal_h_field, signal_v_field, noise_h_field, noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

radar [radar object] Object containing the computed fields

```
pyart.retrieve.iq.compute_reflectivity_iq(radar, subtract_noise=False, sig-
                                          nal_field=None, noise_field=None)
```

Computes the reflectivity from the IQ signal data

Parameters

radar [IQ radar object] Object containing the required fields

subtract_noise [Bool] If true the noise is subtracted from the power

signal_field, noise_field [str] Name of the signal and noise fields. None will use the default field name in the Py-ART configuration file.

Returns

dBZ_dict [field dictionary] Field dictionary containing the reflectivity

```
pyart.retrieve.iq.compute_rhohv_iq(radar, subtract_noise=False, lag=0, signal_h_field=None,
                                   signal_v_field=None, noise_h_field=None,
                                   noise_v_field=None)
```

Computes RhoHV from the horizontal and vertical channels IQ data

Parameters

radar [IQ radar object] Object containing the required fields

subtract_noise [Bool] If True noise will be subtracted from the signals

lag [int] Time lag used in the computation

signal_h_field, signal_v_field, noise_h_field, noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

rhohv_dict [field dictionary] Field dictionary containing the RhoHV

`pyart.retrieve.iq.compute_spectra(radar, fields_in_list, fields_out_list, window=None)`

Computes the spectra from IQ data through a Fourier transform

Parameters

radar [radar object] Object containing the IQ data

fields_in_list [list of str] list of input IQ data fields names

fields_out_list [list of str] list with the output spectra fields names obtained from the input fields

window [string, tuple or None] Parameters of the window used to obtain the spectra. The parameters are the ones corresponding to function `scipy.signal.windows.get_window`. If None no window will be used

Returns

spectra [spectra radar object] radar object containing the spectra fields

`pyart.retrieve.iq.compute_st1_iq(radar, signal_field=None)`

Computes the statistical test one lag fluctuation from the horizontal or vertical channel IQ data

Parameters

radar [IQ radar object] Object containing the required fields

signal_field [str] Name of the field that contain the H or V IQ data. None will use the default field name in the Py-ART configuration file.

Returns

st1_dict [field dictionary] Field dictionary containing the st1

`pyart.retrieve.iq.compute_st2_iq(radar, signal_field=None)`

Computes the statistical test two lag fluctuation from the horizontal or vertical channel IQ data

Parameters

radar [IQ radar object] Object containing the required fields

signal_field [str] Name of the field that contain the H or V IQ data. None will use the default field name in the Py-ART configuration file.

Returns

st2_dict [field dictionary] Field dictionary containing the st2

`pyart.retrieve.iq.compute_wbn_iq(radar, signal_field=None)`

Computes the wide band noise from the horizontal or vertical channel IQ data

Parameters

radar [IQ radar object] Object containing the required fields

signal_field [str] Name of the field that contain the H or V IQ data. None will use the default field name in the Py-ART configuration file.

Returns

wbn_dict [field dictionary] Field dictionary containing the wide band noise

PYART.RETRIEVE.KDP_PROC

Module for retrieving specific differential phase (KDP) from radar total differential phase (PSIDP) measurements. Total differential phase is a function of propagation differential phase (PHIDP), backscatter differential phase (DELTAHV), and the system phase offset.

<i>kdp_schneebeli</i> (radar[, gatefilter, ...])	Estimates Kdp with the Kalman filter method by Schneebeli and al.
<i>kdp_vulpiani</i> (radar[, gatefilter, ...])	Estimates Kdp with the Vulpiani method for a 2D array of psidp measurements with the first dimension being the distance from radar and the second dimension being the angles (azimuths for PPI, elev for RHI).The input psidp is assumed to be pre-filtered (for ex.
<i>kdp_maesaka</i> (radar[, gatefilter, method, ...])	Compute the specific differential phase (KDP) from corrected (e.g., unfolded) total differential phase data based on the variational method outlined in Maesaka et al.
<i>filter_psidp</i> (radar[, psidp_field, ...])	Filter measured psidp to remove spurious data in four steps:
<i>boundary_conditions_maesaka</i> (radar[, ...])	Determine near range gate and far range gate propagation differential phase boundary conditions.
<i>_kdp_estimation_backward_fixed</i> (psidp_in, ...)	Processing one profile of Psidp and estimating Kdp and Phidp with the KFE algorithm described in Schneebeli et al, 2014 IEEE_TGRS.
<i>_kdp_estimation_forward_fixed</i> (psidp_in, ...)	Processing one profile of Psidp and estimating Kdp and Phidp with the KFE algorithm described in Schneebeli et al, 2014 IEEE_TGRS.
<i>_kdp_kalman_profile</i> (psidp_in, dr[, band, ...])	Estimates Kdp with the Kalman filter method by Schneebeli and al.
<i>_kdp_vulpiani_profile</i> (psidp_in, dr[, ...])	Estimates Kdp with the Vulpiani method for a single profile of psidp measurements
<i>_cost_maesaka</i> (x, psidp_o, bcs, dhv, dr, ...)	Compute the value of the cost functional similar to equations (12)-(15) in Maesaka et al.
<i>_jac_maesaka</i> (x, psidp_o, bcs, dhv, dr, Cobs, ...)	Compute the Jacobian (gradient) of the cost functional similar to equations (16)-(18) in Maesaka et al.
<i>_forward_reverse_phidp</i> (k, bcs[, verbose])	Compute the forward and reverse direction propagation differential phases from the control variable k and boundary conditions following equations (1) and (7) in Maesaka et al.
<i>_parse_range_resolution</i> (radar[, ...])	Parse the radar range gate resolution.

Continued on next page

Table 1 – continued from previous page

<code>kdp_leastsquare_single_window(radar[, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.
<code>kdp_leastsquare_double_window(radar[, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.
<code>leastsquare_method(phidp, rng_m[, wind_len, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.
<code>leastsquare_method_scan(phidp, rng_m[, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.

`pyart.retrieve.kdp_proc._cost_maesaka(x, psidp_o, bcs, dhv, dr, Cobs, Clpf, finite_order, fill_value, proc, debug=False, verbose=False)`

Compute the value of the cost functional similar to equations (12)-(15) in Maesaka et al. (2012).

Parameters

- x** [ndarray] Analysis vector containing control variable k .
- psidp_o** [ndarray] Total differential phase measurements.
- bcs** [array_like] The near and far range gate propagation differential phase boundary conditions.
- dhv** [ndarray] Backscatter differential phase.
- dr** [float] Range resolution in meters.
- Cobs** [ndarray] The differential phase measurement constraint weights. The weight should vanish where no differential phase measurements are available.
- Clpf** [float] The low-pass filter (radial smoothness) constraint weight as in equation (15) of Maesaka et al. (2012).
- finite_order** ['low' or 'high'] The finite difference accuracy to use when computing derivatives.
- fill_value** [float] Value indicating missing or bad data in radar field data.
- proc** [int] The number of parallel threads (CPUs) to use.
- debug** [bool, optional] True to print debugging information, False to suppress.
- verbose** [bool, optional] True to print progress information, False to suppress.

Returns

- J** [float] Value of total cost functional.

`pyart.retrieve.kdp_proc._forward_reverse_phidp(k, bcs, verbose=False)`

Compute the forward and reverse direction propagation differential phases from the control variable k and boundary conditions following equations (1) and (7) in Maesaka et al. (2012).

Parameters

- k** [ndarray] Control variable k of the Maesaka et al. (2012) method. The control variable k is proportional to the square root of specific differential phase.
- bcs** [array_like] The near and far range gate boundary conditions.
- verbose** [bool, optional] True to print relevant information, False to suppress.

Returns

phidp_f [ndarray] Forward direction propagation differential phase.

phidp_r [ndarray] Reverse direction propagation differential phase.

`pyart.retrieve.kdp_proc._jac_maesaka(x, psidp_o, bcs, dhv, dr, Cobs, Clpf, finite_order, fill_value, proc, debug=False, verbose=False)`

Compute the Jacobian (gradient) of the cost functional similar to equations (16)-(18) in Maesaka et al. (2012).

Parameters

x [ndarray] Analysis vector containing control variable k .

psidp_o [ndarray] Total differential phase measurements.

bcs [array_like] The near and far range gate propagation differential phase boundary conditions.

dhv [ndarray] Backscatter differential phase.

dr [float] Range resolution in meters.

Cobs [ndarray] The differential phase measurement constraint weights. The weight should vanish where no differential phase measurements are available.

Clpf [float] The low-pass filter (radial smoothness) constraint weight as in equation (15) of Maesaka et al. (2012).

finite_order ['low' or 'high'] The finite difference accuracy to use when computing derivatives.

fill_value [float] Value indicating missing or bad data in radar field data.

proc [int] The number of parallel threads (CPUs) to use.

debug [bool, optional] True to print debugging information, False to suppress.

verbose [bool, optional] True to print progress information, False to suppress.

Returns

jac [ndarray] Jacobian of the cost functional.

`pyart.retrieve.kdp_proc._kdp_estimation_backward_fixed(psidp_in, rcov, pcov_scale, f, f_transposed, h_plus, c1, c2, b1, b2, kdp_th, mpsidp)`

Processing one profile of Psidp and estimating Kdp and Phidp with the KFE algorithm described in Schneebeli et al, 2014 IEEE_TGRS. This routine estimates Kdp in the backward direction given a set of matrices that define the Kalman filter.

Parameters

psidp_in [ndarray] One-dimensional vector of length -nrg- containing the input psidp [degrees].

rcov [3x3 float array] Measurement error covariance matrix.

pcov_scale [4x4 float array] Scaled state transition error covariance matrix.

f [4x4 float array] Forward state prediction matrix [4x4].

f_transposed [4x4 float array] Transpose of F.

h_plus [4x3 float array] Measurement prediction matrix [4x3].

c1, c2, b1, b2 [floats] The values of the intercept of the relation $c = b * Kdp - \delta$. This relation uses b1, c1 IF kdp is lower than a kdp_th and b2, c2 otherwise kdp_th.

kdp_th [float] The kdp threshold which separates the two Kdp - delta regime i.e. the power law relating delta to Kdp will be different if Kdp is larger or smaller than kdp_th.

psidp [float] Final observed value of psidp along the radial (usually also the max value), needed for inverting the psidp vector.

Returns

kdp [ndarray] Filtered Kdp [degrees/km]. Same length as Psidp.

error_kdp [ndarray] Estimated error on Kdp values.

`pyart.retrieve.kdp_proc._kdp_estimation_forward_fixed` (*psidp_in*, *rcov*, *pcov_scale*, *f*, *f_transposed*, *h_plus*, *c1*, *c2*, *b1*, *b2*, *kdp_th*)

Processing one profile of Psidp and estimating Kdp and Phidp with the KFE algorithm described in Schneebeli et al, 2014 IEEE_TGRS. This routine estimates Kdp in the forward direction given a set of matrices that define the Kalman filter.

Parameters

psidp_in [ndarray] One-dimensional vector of length -nrg- containining the input psidp [degrees].

rcov [3x3 float array.] Measurement error covariance matrix.

pcov_scale [4x4 float array] Scaled state transition error covariance matrix.

f [4x4 float array] Forward state prediction matrix [4x4].

f_transposed [4x4 float array] Transpose of F.

h_plus [4x3 float array*np.nan] Measurement prediction matrix [4x3].

c1, c2, b1, b2 [floats] The values of the intercept of the relation $c = b * Kdp - \delta$. This relation uses b1, c1 IF kdp is lower than a kdp_th and b2, c2 otherwise kdp_th.

Returns

kdp [ndarray] Filtered Kdp [degrees/km]. Same length as Psidp.

phidp [ndarray] Estimated phidp (smooth psidp).

error_kdp [ndarray] Estimated error on Kdp values.

`pyart.retrieve.kdp_proc._kdp_kalman_profile` (*psidp_in*, *dr*, *band='X'*, *rcov=0*, *pcov=0*)

Estimates Kdp with the Kalman filter method by Schneebeli and al. (2014) for a set of psidp measurements.

Parameters

psidp_in [ndarray] One-dimensional vector of length -nrg- containining the input psidp [degrees].

dr [float] Range resolution in meters.

band [char, optional] Radar frequency band string. Accepted "X", "C", "S" (capital or not). The band is used to compute intercepts -c and slope b of the $\delta = b * Kdp + c$ relation.

rcov [3x3 float array, optional] Measurement error covariance matrix.

pcov [4x4 float array, optional] Scaled state transition error covariance matrix.

Returns

kdp_dict [ndarray] Retrieved specific differential phase data.

kdp_std_dict [ndarray] Estimated specific differential phase standard dev. data.

phidpr_dict [ndarray] Retrieved differential phase data.

References

Schneebeli, M., Grazioli, J., and Berne, A.: Improved Estimation of the Specific Differential Phase Shift Using a Compilation of Kalman Filter Ensembles, IEEE T. Geosci. Remote Sens., 52, 5137-5149, doi:10.1109/TGRS.2013.2287017, 2014.

```
pyart.retrieve.kdp_proc._kdp_vulpiani_profile(psidp_in, dr, windsize=10, band='X',  
                                              n_iter=10, interp=False)
```

Estimates Kdp with the Vulpiani method for a single profile of psidp measurements

Parameters

psidp_in [ndarray] Total differential phase measurements.

dr [float] Range resolution in meters.

windsize [int, optional] Size in # of gates of the range derivative window.

band [char, optional] Radar frequency band string. Accepted “X”, “C”, “S” (capital or not). It is used to set default boundaries for expected values of Kdp

n_iter [int, optional] Number of iterations of the method. Default is 10.

interp [bool, optional] If set all the nans are interpolated. The advantage is that less data are lost (the iterations in fact are “eating the edges”) but some non-linear errors may be introduced

Returns

kdp_calc [ndarray] Retrieved specific differential profile

phidp_rec,; ndarray Retrieved differential phase profile

```
pyart.retrieve.kdp_proc._parse_range_resolution(radar, check_uniform=True, atol=1.0,  
                                              verbose=False)
```

Parse the radar range gate resolution.

Parameters

radar [Radar] Radar containing range data.

check_uniform [bool, optional] True to check if all range gates are equally spaced, and if so return a scalar value for range resolution. If False, the resolution between each range gate is returned.

atol [float, optional] The absolute tolerance in meters allowed for discrepancies in range gate spacings. Only applicable when check_uniform is True. This parameter may be necessary to catch instances where range gate spacings differ by a few meters or so.

verbose [bool, optional] True to print the range gate resolution. Only valid if check_uniform is True.

Returns

dr [float or ndarray] The radar range gate spacing in meters.

```
pyart.retrieve.kdp_proc.boundary_conditions_maesaka(radar, gatefilter=None, n=20,  
                                                  psidp_field=None, debug=False,  
                                                  verbose=False, **kwargs)
```

Determine near range gate and far range gate propagation differential phase boundary conditions. This follows the method outlined in Maesaka et al. (2012), except instead of using the mean we use the median which is less susceptible to outliers. This function can also be used to estimate the system phase offset.

Parameters

radar [Radar] Radar containing total differential phase measurements.

gatefilter [GateFilter] A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

n [int, optional] The number of range gates necessary to define the near and far range gate boundary conditions. Maesaka et al. (2012) uses a value of 30. If this value is too small then a spurious spike in specific differential phase close to the radar may be retrieved.

check_outliers [bool, optional] True to check for near range gate boundary condition outliers. Outliers near the radar are primarily the result of ground clutter returns.

psidp_field [str, optional] Field name of total differential phase. If None, the default field name must be specified in the Py-ART configuration file.

debug [bool, optional] True to print debugging information, False to suppress.

verbose [bool, optional] True to print relevant information, False to suppress.

Returns

phi_near [ndarray] The near range differential phase boundary condition for each ray.

phi_far [ndarray] The far range differential phase boundary condition for each ray.

range_near [ndarray] The near range gate in meters for each ray.

range_far [ndarray] The far range gate in meters for each ray.

idx_near [ndarray] Index of nearest range gate for each ray.

idx_far [ndarray] Index of furthest range gate for each ray.

```
pyart.retrieve.kdp_proc.filter_psidp(radar, psidp_field=None, rhohv_field=None, min-  
size_seq=5, median_filter_size=7, thresh_rhohv=0.65,  
max_discont=90)
```

Filter measured psidp to remove spurious data in four steps:

1. Censor it where Rhohv is lower than threshold
2. Unravel angles when strong discontinuities are detected
3. Remove very short sequences of valid data
4. Apply a median filter on every profile

Parameters

radar [Radar] Radar containing differential phase field.

psidp_field [str, optional] Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

rhohv_field [str, optional] Cross correlation ratio field. If None, the default field name must be specified in the Py-ART configuration file.

minsize_seq [integer, optional] Minimal len (in radar gates) of sequences of valid data to be accepted

median_filter_size [integer, optional] Size (in radar gates) of the median filter to be applied on psidp

thresh_rhohv [float, optional] Censoring threshold in rhohv (gates with rhohv < thresh_rhohv) will be rejected

max_discont [int, optional] Maximum discontinuity between psidp values, default is 90 deg

Returns

psidp_filt [ndarray] Filtered psidp field

```
pyart.retrieve.kdp_proc.kdp_leastsquare_double_window(radar,          swind_len=11,
                                                         smin_valid=6, lwind_len=31,
                                                         lmin_valid=16,   zthr=40.0,
                                                         phidp_field=None,
                                                         refl_field=None,
                                                         kdp_field=None,      vector-
                                                         ize=False)
```

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out.

Parameters

radar [Radar] Radar object.

swind_len [int] The lenght of the short moving window.

smin_valid [int] Minimum number of valid bins to consider the retrieval valid when using the short moving window

lwind_len [int] The lenght of the long moving window.

lmin_valid [int] Minimum number of valid bins to consider the retrieval valid when using the long moving window

zthr [float] reflectivity value above which the short window is used

phidp_field [str] Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field [str] Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

kdp_field [str] Field name within the radar object which represent the specific differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

vectorize [bool] whether to use a vectorized version of the least square method

Returns

kdp_dict [dict] Retrieved specific differential phase data and metadata.

```
pyart.retrieve.kdp_proc.kdp_leastsquare_single_window(radar,          wind_len=11,
                                                         min_valid=6,
                                                         phidp_field=None,
                                                         kdp_field=None,      vector-
                                                         ize=False)
```

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out.

Parameters

radar [Radar] Radar object.

wind_len [int] The lenght of the moving window.

min_valid [int] Minimum number of valid bins to consider the retrieval valid

phidp_field [str] Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

kdp_field [str] Field name within the radar object which represent the specific differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

vectorize [bool] whether to use a vectorized version of the least square method

Returns

kdp_dict [dict] Retrieved specific differential phase data and metadata.

```
pyart.retrieve.kdp_proc.kdp_maesaka (radar, gatefilter=None, method='cg', backscatter=None,
                                       Clpf=1.0, length_scale=None, first_guess=0.01,
                                       finite_order='low', fill_value=None, proc=1,
                                       psidp_field=None, kdp_field=None, phidp_field=None,
                                       debug=False, verbose=False, **kwargs)
```

Compute the specific differential phase (KDP) from corrected (e.g., unfolded) total differential phase data based on the variational method outlined in Maesaka et al. (2012). This method assumes a monotonically increasing propagation differential phase (PHIDP) with increasing range from the radar, and therefore is limited to rainfall below the melting layer and/or warm clouds at weather radar frequencies (e.g., S-, C-, and X-band). This method currently only supports radar data with constant range resolution.

Following the notation of Maesaka et al. (2012), the primary control variable k is proportional to KDP,

$$k^2 = 2 * KDP * dr$$

which, because of the square, assumes that KDP always takes a positive value.

Parameters

radar [Radar] Radar containing differential phase field.

gatefilter [GateFilter] A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

method [str, optional] Type of scipy.optimize method to use when minimizing the cost functional. The default method uses a nonlinear conjugate gradient algorithm. In Maesaka et al. (2012) they use the Broyden-Fletcher-Goldfarb-Shanno (BFGS) algorithm, however for large functional size (e.g., 100K+ variables) this algorithm is considerably slower than a conjugate gradient algorithm.

backscatter [optional] Define the backscatter differential phase. If None, the backscatter differential phase is set to zero for all range gates. Note that backscatter differential phase can be parameterized using attenuation corrected differential reflectivity.

Clpf [float, optional] The low-pass filter (radial smoothness) constraint weight as in equation (15) of Maesaka et al. (2012).

length_scale [float, optional] Length scale in meters used to bring the dimension and magnitude of the low-pass filter cost functional in line with the observation cost functional. If None, the length scale is set to the range resolution.

first_guess [float, optional] First guess for control variable k . Since k is proportional to the square root of KDP, the first guess should be close to zero to signify a KDP field close to 0 deg/km everywhere. However, the first guess should not be exactly zero in order to avoid convergence criteria after the first iteration. In fact it is recommended to use a value closer to one than zero.

finite_order ['low' or 'high', optional] The finite difference accuracy to use when computing derivatives.

maxiter [int, optional] Maximum number of iterations to perform during cost functional minimization. The maximum number of iterations are only performed if convergence criteria are not met. For variational schemes such as this one, it is generally not recommended to try

and achieve convergence criteria since the values of the cost functional and/or its gradient norm are somewhat arbitrary.

fill_value [float, optional] Value indicating missing or bad data in differential phase field.

proc [int, optional] The number of parallel threads (CPUs) to use. Currently no multiprocessing capability exists.

psidp_field [str, optional] Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field [str, optional] Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field [str, optional] Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

debug [bool, optional] True to print debugging information, False to suppress.

verbose [bool, optional] True to print relevant information, False to suppress.

Returns

kdp_dict [dict] Retrieved specific differential phase data and metadata.

phidpf_dict, phidpr_dict [dict] Retrieved forward and reverse direction propagation differential phase data and metadata.

References

Maesaka, T., Iwanami, K. and Maki, M., 2012: “Non-negative KDP Estimation by Monotone Increasing PHIDP Assumption below Melting Layer”. The Seventh European Conference on Radar in Meteorology and Hydrology.

```
pyart.retrieve.kdp_proc.kdp_schneebeli (radar,          gatefilter=None,          fill_value=None,
                                         psidp_field=None,          kdp_field=None,
                                         phidp_field=None, band='C', rcov=0, pcov=0,
                                         prefilter_psidp=False, filter_opt=None, parallel=True)
```

Estimates Kdp with the Kalman filter method by Schneebeli and al. (2014) for a set of psidp measurements.

Parameters

radar [Radar] Radar containing differential phase field.

gatefilter [GateFilter, optional] A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

fill_value [float, optional] Value indicating missing or bad data in differential phase field, if not specified, the default in the Py-ART configuration file will be used.

psidp_field [str, optional] Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field [str, optional] Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field [str, optional] Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

band [char, optional] Radar frequency band string. Accepted “X”, “C”, “S” (capital or not). The band is used to compute intercepts -c and slope b of the $\delta = b \cdot \text{Kdp} + c$ relation.

rcov [3x3 float array, optional] Measurement error covariance matrix.

pcov [4x4 float array, optional] Scaled state transition error covariance matrix.

prefilter_psidp [bool, optional] If set, the psidp measurements will first be filtered with the `filter_psidp` method, which can improve the quality of the final Kdp.

filter_opt [dict, optional] The arguments for the `prefilter_psidp` method, if empty, the defaults arguments of this method will be used.

parallel [bool, optional] Flag to enable parallel computation (one core for every psidp profile).

Returns

kdp_dict [dict] Retrieved specific differential phase data and metadata.

kdp_std_dict [dict] Estimated specific differential phase standard dev. data and metadata.

phidpr_dict,; dict Retrieved differential phase data and metadata.

References

Schneebeli, M., Grazioli, J., and Berne, A.: Improved Estimation of the Specific Differential Phase SHIFT Using a Compilation of Kalman Filter Ensembles, *IEEE T. Geosci. Remote Sens.*, 52, 5137-5149, doi:10.1109/TGRS.2013.2287017, 2014.

```
pyart.retrieve.kdp_proc.kdp_vulpiani (radar,          gatefilter=None,          fill_value=None,
                                       psidp_field=None, kdp_field=None, phidp_field=None,
                                       band='C', windsize=10, n_iter=10, interp=False, pre-
                                       filter_psidp=False, filter_opt=None, parallel=False)
```

Estimates Kdp with the Vulpiani method for a 2D array of psidp measurements with the first dimension being the distance from radar and the second dimension being the angles (azimuths for PPI, elev for RHI). The input psidp is assumed to be pre-filtered (for ex. with the `filter_psidp` function)

Parameters

radar [Radar] Radar containing differential phase field.

gatefilter [GateFilter, optional] A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

fill_value [float, optional] Value indicating missing or bad data in differential phase field, if not specified, the default in the Py-ART configuration file will be used

psidp_field [str, optional] Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field [str, optional] Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field [str, optional] Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

band [char, optional] Radar frequency band string. Accepted "X", "C", "S" (capital or not). It is used to set default boundaries for expected values of Kdp.

windsize [int, optional] Size in # of gates of the range derivative window. Should be even.

n_iter [int, optional] Number of iterations of the method. Default is 10.

interp [bool, optional] If True, all the nans are interpolated. The advantage is that less data are lost (the iterations in fact are "eating the edges") but some non-linear errors may be introduced.

prefilter_psidp [bool, optional] If set, the psidp measurements will first be filtered with the `filter_psidp` method, which can improve the quality of the final Kdp.

filter_opt [dict, optional] The arguments for the `prefilter_psidp` method, if empty, the defaults arguments of this method will be used.

parallel [bool, optional] Flag to enable parallel computation (one core for every psidp profile).

Returns

kdp_dict [dict] Retrieved specific differential phase data and metadata.

phidpr_dict,; dict Retrieved differential phase data and metadata.

References

Gianfranco Vulpiani, Mario Montopoli, Luca Delli Passeri, Antonio G. Gioia, Pietro Giordano, and Frank S. Marzano, 2012: On the Use of Dual-Polarized C-Band Radar for Operational Rainfall Retrieval in Mountainous Areas. J. Appl. Meteor. Climatol., 51, 405-425, doi: 10.1175/JAMC-D-10-05024.1.

`pyart.retrieve.kdp_proc.leastsquare_method` (*phidp*, *rng_m*, *wind_len=11*, *min_valid=6*)

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out.

Parameters

phidp [masked array] phidp field

rng_m [array] radar range in meters

wind_len [int] the window length

min_valid [int] Minimum number of valid bins to consider the retrieval valid

Returns

kdp [masked array] Retrieved specific differential phase field

`pyart.retrieve.kdp_proc.leastsquare_method_scan` (*phidp*, *rng_m*, *wind_len=11*,
min_valid=6)

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out. This function computes the whole radar volume at once

Parameters

phidp [masked array] phidp field

rng_m [array] radar range in meters

wind_len [int] the window length

min_valid [int] Minimum number of valid bins to consider the retrieval valid

Returns

kdp [masked array] Retrieved specific differential phase field

PYART.RETRIEVE.ML

Routines to detect the ML from polarimetric RHI scans.

<i>detect_ml</i> (radar[, gatefilter, fill_value, ...])	Detects the melting layer (ML) using the reflectivity and copolar correlation coefficient.
<i>melting_layer_giangrande</i> (radar[, nVol, ...])	Detects the melting layer following the approach by Giangrande et al (2008)
<i>melting_layer_hydroclass</i> (radar[, ...])	Using the results of the hydrometeor classification by Besic et al.
<i>get_flag_ml</i> (radar[, hydro_field, ml_field, ...])	Using the results of the hydrometeor classification by Besic et al.
<i>get_pos_ml</i> (radar, ml_data[, ml_pos_field])	Estimates the height of the top and bottom of the melting layer from a field containing the position of each range gate respect to the melting layer.
<i>compute_iso0</i> (radar, ml_top[, iso0_field])	Estimates the distance respect to the freezing level of each range gate using the melting layer top as a proxy
<i>find_ml_field</i> (radar_in, ml_obj[, ...])	Obtains the field of position respect to the melting layer from the top and bottom height of the melting layer
<i>interpol_field</i> (radar_dest, radar_orig, ...)	interpolates field field_name contained in radar_orig to the grid in radar_dest
<i>_create_ml_obj</i> (radar[, ml_pos_field])	Creates a radar-like object that will be used to contain the melting layer top and bottom
<i>_prepare_radar</i> (radar, field_list[, ...])	Select radar fields to use.
<i>_get_ml_global</i> (radar_in[, ml_global, nVol, ...])	Gets global data to be used in melting layer detection
<i>_get_target_azimuths</i> (radar_in)	Gets RHI target azimuths
<i>_find_ml_gates</i> (ml_global[, refl_field, ...])	Find gates suspected to be melting layer contaminated
<i>_insert_ml_points</i> (ml_global, ml_points, ...)	Insert the current suspected melting layer points in the memory array
<i>_find_ml_limits</i> (ml_global[, nml_points_min, ...])	Find melting layer limits
<i>_interpol_ml_limits</i> (radar_in, ml_top, ...[, ...])	Interpolate melting layer limits to obtain a value at each ray of the current radar object
<i>_get_res_vol_sides</i> (radar)	Computes the height of the lower left and upper right points of the range resolution volume.
<i>_detect_ml_sweep</i> (radar_sweep, fill_value, ...)	Detects the melting layer (ML) on an RHI scan of reflectivity and copolar correlation coefficient and returns its properties both in the original polar radar coordinates and in projected Cartesian coordinates
<i>_process_map_ml</i> (gradient_z, rhohv, threshold)	
<i>_process_map_ml_only_zh</i> (gradientZ)	

Continued on next page

Table 1 – continued from previous page

<code>_r_to_h(earth_radius, gate_range, gate_theta)</code>	Computes the height of radar gates knowing the earth radius at the given latitude and the range and elevation angle of the radar gate.
<code>_remap_to_polar(radar_sweep, x, bottom_ml, ...)</code>	This routine converts the ML in Cartesian coordinates back to polar coordinates.
<code>_normalize_image(im, min_val, max_val)</code>	Uniformly normalizes a radar field to the [0-1] range
<code>_gradient_2D(im)</code>	Computes the 2D gradient of a radar image
<code>_convolve_with_nan(input_array, kernel[, ...])</code>	Convolves an image with a kernel while ignoring missing values
<code>_mean_filter(input_array[, shape, boundary])</code>	Local averaging (smoothing) while ignoring missing values
<code>_calc_sub_ind(inputVec)</code>	The code belows finds continuous subsequences of missing values, it fills a vector values containing 1 for values and 0 for missing values starting a new subsequence, a vector idx containing the index of the first value of the subsequence and a vector length containing the length of the subsequence.

`pyart.retrieve.ml._calc_sub_ind(inputVec)`

The code belows finds continuous subsequences of missing values, it fills a vector values containing 1 for values and 0 for missing values starting a new subsequence, a vector idx containing the index of the first value of the subsequence and a vector length containing the length of the subsequence.

Inputs: inputVec : a binary input vector

Outputs:

sub: a dictionary with the keys:

values [an array containing 1 for sequences of valid values] and 0 for sequences of missing values

idx : an array containing the first index of the sequences **length** : an array containing the length of every sequence

`pyart.retrieve.ml._convolve_with_nan(input_array, kernel, boundary='mirror')`

Convolves an image with a kernel while ignoring missing values

Inputs: input_array : the input array can be 1D or 2D

kernel : the kernel (filter) with which to convolve the input array

boundary: how to treat the boundaries, see arguments of scipy's convolve function.

Outputs: conv: the convolved signal

`pyart.retrieve.ml._create_ml_obj(radar, ml_pos_field='melting_layer_height')`

Creates a radar-like object that will be used to contain the melting layer top and bottom

Parameters

radar [Radar] Radar object

ml_pos_field [str] Name of the melting layer height field

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

```
pyart.retrieve.ml._detect_ml_sweep(radar_sweep, fill_value, refl_field, rhohv_field, melting_layer_field, max_range, detect_threshold, interp_holes, max_length_holes, check_min_length)
```

Detects the melting layer (ML) on an RHI scan of reflectivity and copolar correlation coefficient and returns its properties both in the original polar radar coordinates and in projected Cartesian coordinates

Parameters

radar_sweep [Radar]

A Radar class instance of a single sweep

fill_value [float] Value indicating missing or bad data in differential phase

refl_field [str] Reflectivity field. If None, the default field name must be specified in the Py-ART configuration file.

rhohv_field [str] Copolar correlation coefficient field.

melting_layer_field [str] Melting layer field.

max_range [float] the max. range from the radar to be used in the ML determination

detect_threshold [float] the detection threshold (see paper), you can play around and see how it affects the output. Lowering the value makes the algorithm more sensitive but increases the number of erroneous detections.

interp_holes [bool] Flag to allow for interpolation of small holes in the detected ML

max_length_holes [float] The maximum size of holes in the ML for them to be interpolated

check_min_length [bool] If true, the length of the detected ML will be compared with the length of the valid data and the ML will be kept only if sufficiently long

Returns

ml [dict] ml is a dictionary with the following fields:: ml_pol a dict with the following keys:

theta (list of elevation angles) range (list of ranges) data (2D map with 1 where detected ML and 0 otherwise) bottom_ml (the height above the radar of the ML bottom for every angle theta)

top_ml (the height above the radar of the ML top for every angle theta)

ml_cart a dict with the following keys: x : x-coordinates of the Cartesian system (distance at ground) z : z-coordinates of the Cartesian system (height above surface) data (2D map with 1 where detected ML and 0 otherwise) bottom_ml (the height above the radar of the ML bottom for every

distance x)

top_ml (the height above the radar of the ML top for every distance x)

ml_exists a boolean flag = 1 if a ML was detected

```
pyart.retrieve.ml._find_ml_gates (ml_global,                                refl_field='reflectivity',
                                   zdr_field='differential_reflectivity',
                                   rhv_field='cross_correlation_ratio',
                                   iso0_field='height_over_iso0',  rmin=1000.0,  elmin=4.0,
                                   elmax=10.0,    rhomin=0.75,    rhomax=0.94,    zh-
                                   min=20.0,    htol=500.0,    hwindow=500.0,    mlzh-
                                   min=30.0,    mlzhmax=50.0,    mlzdrmin=1.0,    mlzdrmax=5.0,
                                   ml_bottom_diff_max=1000.0)
```

Find gates suspected to be melting layer contaminated

Parameters

ml_global [dict] Dictionary containing global melting layer data

refl_field, zdr_field, rhv_field, iso0_field [str] Name of fields used to find melting layer

rmin [float] Minimum range from radar where to start looking for melting layer gates

elmin, elmax [float] Minimum and maximum elevation angles to use

rhomin, rhomax [float] Minimum and maximum values of RhoHV to consider a range gate potentially melting layer contaminated

zhmin [float] Minimum value of reflectivity to consider a range gate potentially melting layer contaminated

htol [float] Maximum height above the iso-0 where to look for melting layer contaminated gates

hwindow [float] Maximum range above the suspected melting layer contaminated gate to look for a peak

mlzhmin, mlzhmax [float] Minimum and maximum values of the peak reflectivity above the melting layer contaminated range gate to consider it valid

mlzdrmin, mlzdrmax [float] Minimum and maximum values of the peak differential reflectivity above the melting layer contaminated range gate to consider it valid

ml_bottom_diff_max [float] The maximum difference in altitude between the current suspected melting layer gate and the previously retrieved melting layer [m]

Returns

ml_points [2D-array] A 2D-array (nAzimuth, nHeight) with the number of points found

nml_total [int] Number of range gates identified as suspected melting layer contamination

```
pyart.retrieve.ml._find_ml_limits (ml_global,  nml_points_min=None,  wlength=20.0,  per-
                                   centile_bottom=0.3, percentile_top=0.9, interpol=True)
```

Find melting layer limits

Parameters

ml_global [dict] Dictionary containing global melting layer data

nml_points_min [int or None] Minimum number of suspected melting layer contaminated range gates to obtain limits. If none it will be defined as a function of the number of azimuths

wlength [int or None] Size of the window in azimuth to use when identifying melting layer points [degree]

percentile_bottom, percentile_top [float] Percentile of range gates suspected of being melting layer contaminated that has to be reached to estimate the bottom and top of the melting layer

interpol [bool] Whether to interpolate or not across the azimuths

Returns

ml_top, ml_bottom [1D-array] The top and bottom melting layer height at each azimuth

`pyart.retrieve.ml._get_ml_global(radar_in, ml_global=None, nVol=3, maxh=6000.0, hres=50.0)`

Gets global data to be used in melting layer detection

Parameters

radar_in [Radar object] current radar object

nVol [int] Number of consecutive volumes to use to obtain the melting layer

maxh [float] Maximum possible height of the melting layer [m MSL]

hres [float] Resolution of the height vector

Returns

ml_global [dict or None] A dictionary with the data necessary to estimate the melting layer. It has the following keys:

```
iVol: int
    index of current radar volume (Maximum nVol)
time_nodata_start : datetime object
    The date and time where the first radar volume with no data
    was found
ml_points : 3D-array
    an array (nAzimuth, nHeight, nVol) to store the number of
    suspected melting layer points
ml_top, ml_bottom: 1D-array
    an array (nAzimuth) to store the top and bottom height of the
    melting layer
azi_vec : 1D-array
    The azimuth values
alt_vec : 1D-array
    The altitude values
radar_ref : radar object
    The rhi volume radar used as reference
```

is_valid [Bool] Indicates whether the current radar volume can be processed

`pyart.retrieve.ml._get_res_vol_sides(radar)`

Computes the height of the lower left and upper right points of the range resolution volume.

Parameters

radar [radar object] The current radar

Returns

hlowerleft, hupperright [2D-arrays] The matrix (rays, range) with the lower left and upper right height of the resolution volume

`pyart.retrieve.ml._get_target_azimuths(radar_in)`

Gets RHI target azimuths

Parameters

radar_in [Radar object] current radar object

Returns

target_azimuths [1D-array] Azimuth angles

az_tol [float] azimuth tolerance

`pyart.retrieve.ml._gradient_2D(im)`

Computes the 2D gradient of a radar image

Inputs:

im [array] A radar image in Cartesian coordinates

Outputs:

out [a gradient dictionary containing a field 'Gx' for the gradient] in the horizontal and a field 'Gy' for the gradient in the vertical

`pyart.retrieve.ml._insert_ml_points(ml_global, ml_points, time_current, time_accu_max=1800.0)`

Insert the current suspected melting layer points in the memory array

Parameters

ml_global [dict] Dictionary containing global melting layer data

ml_points [2D-array] A 2D-array (nAzimuth, nHeight) with the current number of points found

time_current [datetime object] The current time

time_accu_max [float] Maximum accumulation time [s]

Returns

ml_global [dict] The global melting layer data with the points updated

`pyart.retrieve.ml._interpol_ml_limits(radar_in, ml_top, ml_bottom, ml_azi_angl, ml_pos_field='melting_layer_height')`

Interpolate melting layer limits to obtain a value at each ray of the current radar object

Parameters

radar_in [radar object] The current radar

ml_top, ml_bottom [1D-array] The top and bottom of the melting layer at each reference azimuth angle

ml_azi_angl [1D-array] The reference azimuth angle

ml_pos_field [str] The name of the melting layer height field

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

`pyart.retrieve.ml._mean_filter(input_array, shape=(3, 3), boundary='mirror')`

Local averaging (smoothing) while ignoring missing values

Inputs: `input_array` : the input array can be 1D or 2D

`shape` : the shape of the averaging (smoothing) filter

boundary: how to treat the boundaries, see arguments of `scipy's` `convolve` function.

Outputs: `out`: the smoothed signal

`pyart.retrieve.ml._normalize_image(im, min_val, max_val)`

Uniformly normalizes a radar field to the [0-1] range

Inputs:

im [array] A radar image in native units, ex. dBZ

min_val [float] All values smaller or equal to `min_val` in the original image will be set to zero

max_val : All values larger or equal to min_val in the original image will be set to zero

Outputs: out : the normalized radar image, with all values in [0,1]

```
pyart.retrieve.ml._prepare_radar(radar, field_list, temp_ref='temperature',
                                iso0_field='height_over_iso0', temp_field='temperature',
                                lapse_rate=-6.5)
```

Select radar fields to use. Prepare the field height over the iso0 as according to the temperature reference

Parameters

radar [Radar object] current radar object

field_list [str] List of fields that will be used to get the melting layer

temp_ref [str] the field used as reference for temperature. Can be temperature height_over_iso0, no_field. If None, Outputs a dummy height_over_iso0 field

iso0_field, temp_field [str] Name of the fields height over iso0 and temperature

lapse_rate [float] lapse rate to convert temperature into height with respect to the iso0

Returns

radar_in [Radar object or None] The radar object containing only relevant fields

```
pyart.retrieve.ml._process_map_ml(gradient_z, rhohv, threshold, threshold_min_rhohv=0,
                                threshold_max_rhohv=inf)
```

```
pyart.retrieve.ml._process_map_ml_only_zh(gradientZ)
```

```
pyart.retrieve.ml._r_to_h(earth_radius, gate_range, gate_theta)
```

Computes the height of radar gates knowing the earth radius at the given latitude and the range and elevation angle of the radar gate.

Inputs: earth_radius : the radius of the earth for a given latitude in m.

gate_range : the range of the gate(s) in m.

gate_theta : elevation angle of the gate(s) in degrees.

Outputs: height : the height above ground of all specified radar gates

```
pyart.retrieve.ml._remap_to_polar(radar_sweep, x, bottom_ml, top_ml, tol=1.5, interp=True)
```

This routine converts the ML in Cartesian coordinates back to polar coordinates.

Inputs:

radar_sweep [Radar] A pyart radar instance containing the radar data in polar coordinates for a single sweep

x: array of floats The horizontal distance in Cartesian coordinates.

bottom_ml: array of floats Bottom of the ML detected in Cartesian coordinates.

top_ml: array of floats Top of the ML detected on Cartesian coordinates.

tol [float, optional] Angular tolerance in degrees that is used when mapping elevation angles computed on the Cartesian image to the original angles in the polar data.

interp [bool, optional] Whether or not to interpolate the ML in polar coordinates (fill holes)

Outputs:

(theta, r) [tuple of elevation angle and range corresponding to the] polar coordinates

(bottom_ml, top_ml) [tuple of ml bottom and top ranges for every] elevation angle theta

map_ml_pol : a binary map of the ML in polar coordinates

`pyart.retrieve.ml.compute_iso0 (radar, ml_top, iso0_field='height_over_iso0')`

Estimates the distance respect to the freezing level of each range gate using the melting layer top as a proxy

Parameters

radar [Radar] Radar object

ml_top [1D array] The height of the melting layer at each ray

iso0_field [str] Name of the iso0 field.

Returns

iso0_dict [dict] A dictionary containing the distance respect to the melting layer and metadata

`pyart.retrieve.ml.detect_ml (radar, gatefilter=None, fill_value=None, refl_field=None, rhohv_field=None, ml_field=None, ml_pos_field=None, iso0_field=None, max_range=20000, detect_threshold=0.02, interp_holes=False, max_length_holes=250, check_min_length=True, get_iso0=False)`

Detects the melting layer (ML) using the reflectivity and copolar correlation coefficient. Internally it uses RHIs

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

ml_dict [dict] A dictionary containing the position of the range gate respect to the melting layer and metadata

iso0_dict [dict or None] A dictionary containing the distance respect to the melting layer and metadata

all_ml [dict] Dictionary containing internal parameters in polar and cartesian coordinates

`pyart.retrieve.ml.find_ml_field (radar_in, ml_obj, ml_pos_field='melting_layer_height', ml_field='melting_layer')`

Obtains the field of position respect to the melting layer from the top and bottom height of the melting layer

Parameters

radar_in [radar object] The current radar

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

ml_pos_field [1D-array] The reference azimuth angle

ml_pos_field [str] The name of the melting layer height field

ml_field [str] The name of the melting layer field

Returns

ml_dict [dict] A dictionary containing the position of the range gate respect to the melting layer and metadata

`pyart.retrieve.ml.get_flag_ml (radar, hydro_field='radar_echo_classification', ml_field='melting_layer', force_continuity=False, dist_max=350.0)`

Using the results of the hydrometeor classification by Besic et al. estimates the position of the range gates respect to the melting layer.

Parameters

radar [Radar] Radar object. Must have and hydrometeor classification field

hydro_field [str] Name of the hydrometeor classification field.

ml_field [str] Name of the melting layer field.

force_continuity [Bool] If True, the melting layer is forced to be continuous in range

dist_max [float] The maximum distance between range gates flagged as inside the melting layer to consider them as gates in the melting layer.

Returns

ml_dict [dict] A dictionary containing the position of the range gate respect to the melting layer and metadata

`pyart.retrieve.ml.get_pos_ml(radar, ml_data, ml_pos_field='melting_layer_height')`

Estimates the height of the top and bottom of the melting layer from a field containing the position of each range gate respect to the melting layer.

Parameters

radar [Radar] Radar object

ml_data [2D array] field containing the position of each range gate respect to the melting layer.

ml_pos_field [str] Name of the melting layer height field.

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

`pyart.retrieve.ml.interpolate_field(radar_dest, radar_orig, field_name, fill_value=None)`

interpolates field field_name contained in radar_orig to the grid in radar_dest

Parameters

radar_dest [radar object] the destination radar

radar_orig [radar object] the radar object containing the original field

field_name: str name of the field to interpolate

Returns

field_dest [dict] interpolated field and metadata

`pyart.retrieve.ml.melting_layer_giangrande(radar, nVol=3, maxh=6000.0, hres=50.0, rmin=1000.0, elmin=4.0, elmax=10.0, rhomin=0.75, rhomax=0.94, zhmin=20.0, hwindow=500.0, mlzhmin=30.0, mlzhmax=50.0, mlzdrmin=1.0, mlzdrmax=5.0, htol=500.0, ml_bottom_diff_max=1000.0, time_accu_max=1800.0, nml_points_min=None, wlength=20.0, percentile_bottom=0.3, percentile_top=0.9, interpol=True, time_nodata_allowed=3600.0, refl_field=None, zdr_field=None, rhv_field=None, temp_field=None, iso0_field=None, ml_field=None, ml_pos_field=None, temp_ref=None, get_iso0=False, ml_global=None)`

Detects the melting layer following the approach by Giangrande et al (2008)

Parameters

radar [radar] radar object

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

ml_dict [dict] A dictionary containing the position of the range gate respect to the melting layer and metadata

iso0_dict [dict or None] A dictionary containing the distance respect to the melting layer and metadata

ml_global [dict or None] stack of previous volume data to introduce some time dependency. Its max size is controlled by the nVol parameter. It is always in (pseudo-)RHI mode.

Other Parameters

nVol [int] Number of volume scans to aggregate

maxh [float] Maximum possible height of the melting layer [m MSL]

hres [float] Step of the height of the melting layer [m]

rmin [float] Minimum range from radar where to look for melting layer contaminated range gates [m]

elmin, elmax [float] Minimum and maximum elevation angles where to look for melting layer contaminated range gates [degree]

rhomin, rhomax [float] min and max rhohv to consider pixel potential melting layer pixel

zhmin [float] Minimum reflectivity level of a range gate to consider it a potential melting layer gate [dBZ]

hwindow [float] Maximum distance (in range) from potential melting layer gate where to look for a maximum [m]

mlzhmin, mlzhmax [float] Minimum and maximum values that a peak in reflectivity within the melting layer may have to consider the range gate melting layer contaminated [dBZ]

mlzdrmin, mlzdrmax [float] Minimum and maximum values that a peak in differential reflectivity within the melting layer may have to consider the range gate melting layer contaminated [dB]

htol [float] maximum distance from the iso0 coming from model allowed to consider the range gate melting layer contaminated [m]

ml_bottom_dif_max [float] Maximum distance from the bottom of the melting layer computed in the previous time step to consider a range gate melting layer contaminated [m]

time_accu_max [float] Maximum time allowed to accumulate data from consecutive scans [s]

nml_points_min [int] minimum number of melting layer points to consider valid melting layer detection

wlength [float] length of the window to select the azimuth angles used to compute the melting layer limits at a particular azimuth [degree]

percentile_bottom, percentile_top [float [0,1]] percentile of ml points above which is considered that the bottom of the melting layer starts and the top ends

interpol [bool] Whether to interpolate the obtained results in order to get a value for each azimuth

time_nodata_allowed [float] The maximum time allowed for no data before considering the melting layer not valid [s]

refl_field, zdr_field, rhv_field, temp_field, iso0_field [str] Inputs. Field names within the radar object which represent the horizontal reflectivity, the differential reflectivity, the copolar correlation coefficient, the temperature and the height respect to the iso0 fields. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

ml_field [str] Output. Field name which represents the melting layer field. A value of None will use the default field name as defined in the Py-ART configuration file.

ml_pos_field [str] Output. Field name which represents the melting layer top and bottom height field. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref [str] the field use as reference for temperature. Can be temperature or height_over_iso0. If None, it excludes model data from the algorithm.

get_iso0 [bool] returns height w.r.t. freezing level top for each gate in the radar volume.

ml_global : stack of previous volume data to introduce some time dependency. Its max size is controlled by the nVol parameter. It is always in (pseudo-)RHI mode.

References

Giangrande, S.E., Krause, J.M., Ryzhkov, A.V.: Automatic Designation of the Melting Layer with a Polarimetric Prototype of the WSR-88D Radar, J. of Applied Meteo. and Clim., 47, 1354-1364, doi:10.1175/2007JAMC1634.1, 2008

```
pyart.retrieve.ml.melting_layer_hydroclass (radar, hydro_field=None, ml_field=None,
                                             ml_pos_field=None, iso0_field=None,
                                             force_continuity=True, dist_max=350.0,
                                             get_iso0=False)
```

Using the results of the hydrometeor classification by Besic et al. estimates the position of the range gates respect to the melting layer, the melting layer top and bottom height and the distance of the range gate with respect to the freezing level.

Parameters

radar [Radar] Radar object. Must have and hydrometeor classification field

hydro_field [str] Name of the hydrometeor classification field. A value of None will use the default field name as defined in the Py-ART configuration file.

ml_field, ml_pos_field, iso0_field [str] Name of the melting layer, melting layer height and iso0 field. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

force_continuity [Bool] If True, the melting layer is forced to be continuous in range

dist_max [float] The maximum distance between range gates flagged as inside the melting layer to consider them as gates in the melting layer.

Returns

ml_obj [radar-like object] A radar-like object containing the field melting layer height with the bottom (at range position 0) and top (at range position one) of the melting layer at each ray

ml_dict [dict] A dictionary containing the position of the range gate respect to the melting layer and metadata

iso0_dict [dict or None] A dictionary containing the distance respect to the melting layer and metadata

PYART.RETRIEVE.QPE

Functions for rainfall rate estimation.

<code>est_rain_rate_zpoly(radar[, refl_field, ...])</code>	Estimates rainfall rate from reflectivity using a polynomial Z-R relation developed at McGill University.
<code>est_rain_rate_z(radar[, alpha, beta, ...])</code>	Estimates rainfall rate from reflectivity using a power law.
<code>est_rain_rate_kdp(radar[, alpha, beta, ...])</code>	Estimates rainfall rate from kdp using alpha power law.
<code>est_rain_rate_a(radar[, alpha, beta, ...])</code>	Estimates rainfall rate from specific attenuation using alpha power law.
<code>est_rain_rate_zkdp(radar[, alphaz, betaz, ...])</code>	Estimates rainfall rate from a blending of power law r-kdp and r-z relations.
<code>est_rain_rate_za(radar[, alphaz, betaz, ...])</code>	Estimates rainfall rate from a blending of power law r-alpha and r-z relations.
<code>est_rain_rate_hydro(radar[, alphazr, ...])</code>	Estimates rainfall rate using different relations between R and the polarimetric variables depending on the hydrometeor type.
<code>_get_coeff_rkdp(freq)</code>	Get the R(kdp) power law coefficients for a particular frequency.
<code>_coeff_rkdp_table()</code>	Defines the R(kdp) power law coefficients for each frequency band.
<code>_get_coeff_ra(freq)</code>	Get the R(A) power law coefficients for a particular frequency.
<code>_coeff_ra_table()</code>	Defines the R(A) power law coefficients for each frequency band.

`pyart.retrieve.qpe._coeff_ra_table()`
Defines the R(A) power law coefficients for each frequency band.

Returns

coeff_ra_dict [dict] A dictionary with the coefficients at each band.

`pyart.retrieve.qpe._coeff_rkdp_table()`
Defines the R(kdp) power law coefficients for each frequency band.

Returns

coeff_rkdp_dict [dict] A dictionary with the coefficients at each band.

`pyart.retrieve.qpe._get_coeff_ra(freq)`
Get the R(A) power law coefficients for a particular frequency.

Parameters

freq [float] Radar frequency [Hz].

Returns

alpha, beta [floats] The coefficient and exponent of the power law.

`pyart.retrieve.qpe._get_coeff_rkdp(freq)`

Get the R(kdp) power law coefficients for a particular frequency.

Parameters

freq [float] Radar frequency [Hz].

Returns

alpha, beta [floats] The coefficient and exponent of the power law.

`pyart.retrieve.qpe.est_rain_rate_a(radar, alpha=None, beta=None, a_field=None, rr_field=None)`

Estimates rainfall rate from specific attenuation using alpha power law.

Parameters

radar [Radar] Radar object.

alpha, beta [floats, optional] Factor (alpha) and exponent (beta) of the power law. If not set the factors are going to be determined according to the radar frequency.

a_field [str, optional] Name of the specific attenuation field to use.

rr_field [str, optional] Name of the rainfall rate field.

Returns

rain [dict] Field dictionary containing the rainfall rate.

References

Diederich M., Ryzhkov A., Simmer C., Zhang P. and Tromel S., 2015: Use of Specific Attenuation for Rainfall Measurement at X-Band Radar Wavelengths. Part I: Radar Calibration and Partial Beam Blockage Estimation. Journal of Hydrometeorology, 16, 487-502.

Ryzhkov A., Diederich M., Zhang P. and Simmer C., 2014: Potential Utilization of Specific Attenuation for Rainfall Estimation, Mitigation of Partial Beam Blockage, and Radar Networking. Journal of Atmospheric and Oceanic Technology, 31, 599-619.

`pyart.retrieve.qpe.est_rain_rate_hydro(radar, alphazr=0.0376, betazr=0.6112, alphazs=0.1, betazs=0.5, alphaa=None, betaa=None, mp_factor=0.6, refl_field=None, a_field=None, hydro_field=None, rr_field=None, master_field=None, thresh=None, thresh_max=False)`

Estimates rainfall rate using different relations between R and the polarimetric variables depending on the hydrometeor type.

Parameters

radar [Radar] Radar object.

alphazr, betazr [floats, optional] Factor (alpha) and exponent (beta) of the z-r power law for rain.

alphazs, betazs [floats, optional] Factor (alpha) and exponent (beta) of the z-s power law for snow.

alphaa, betaa [floats, optional] Factor (alpha) and exponent (beta) of the a-r power law. If not set the factors are going to be determined according to the radar frequency.

mp_factor [float, optional] Factor applied to z-r relation in the melting layer.

refl_field [str, optional] Name of the reflectivity field to use.

a_field [str, optional] Name of the specific attenuation field to use.

hydro_field [str, optional] Name of the hydrometeor classification field to use.

rr_field [str, optional] Name of the rainfall rate field.

master_field [str, optional] Name of the field that is going to act as master. Has to be either `refl_field` or `kdp_field`. Default is `refl_field`.

thresh [float, optional] Value of the threshold that determines when to use the slave field.

thresh_max [Bool, optional] If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns

rain [dict] Field dictionary containing the rainfall rate.

```
pyart.retrieve.qpe.est_rain_rate_kdp(radar, alpha=None, beta=None, kdp_field=None,  
                                     rr_field=None)
```

Estimates rainfall rate from kdp using alpha power law.

Parameters

radar [Radar] Radar object.

alpha, beta [floats, optional] Factor (alpha) and exponent (beta) of the power law. If not set the factors are going to be determined according to the radar frequency.

kdp_field [str, optional] Name of the specific differential phase field to use.

rr_field [str, optional] Name of the rainfall rate field.

Returns

rain [dict] Field dictionary containing the rainfall rate.

```
pyart.retrieve.qpe.est_rain_rate_z(radar, alpha=0.0376, beta=0.6112, refl_field=None,  
                                   rr_field=None)
```

Estimates rainfall rate from reflectivity using a power law.

Parameters

radar [Radar] Radar object.

alpha, beta [floats, optional] Factor (alpha) and exponent (beta) of the power law.

refl_field [str, optional] Name of the reflectivity field to use.

rr_field [str, optional] Name of the rainfall rate field.

Returns

rain [dict] Field dictionary containing the rainfall rate.

```
pyart.retrieve.qpe.est_rain_rate_za(radar, alphaz=0.0376, betaz=0.6112, alphaa=None,  
                                   betaa=None, refl_field=None, a_field=None,  
                                   rr_field=None, master_field=None, thresh=None,  
                                   thresh_max=True)
```

Estimates rainfall rate from a blending of power law r-alpha and r-z relations.

Parameters

radar [Radar] Radar object

alphaz, betaz [floats, optional] Factor (alpha) and exponent (beta) of the z-r power law.

alphaa, betaa [floats, optional] Factor (alpha) and exponent (beta) of the a-r power law. If not set the factors are going to be determined according to the radar frequency.

refl_field [str, optional] Name of the reflectivity field to use.

a_field [str, optional] Name of the specific attenuation field to use.

rr_field [str, optional] Name of the rainfall rate field.

master_field [str, optional] Name of the field that is going to act as master. Has to be either `refl_field` or `kdp_field`. Default is `refl_field`.

thresh [float, optional] Value of the threshold that determines when to use the slave field.

thresh_max [Bool, optional] If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns

rain_master [dict] Field dictionary containing the rainfall rate.

```
pyart.retrieve.qpe.estimate_rain_rate_zkdp(radar, alphaz=0.0376, betaz=0.6112, alphakdp=None, betakdp=None, refl_field=None, kdp_field=None, rr_field=None, master_field=None, thresh=None, thresh_max=True)
```

Estimates rainfall rate from a blending of power law r-kdp and r-z relations.

Parameters

radar [Radar] Radar object.

alphaz, betaz [floats, optional] Factor (alpha) and exponent (beta) of the z-r power law.

alphakdp, betakdp [floats, optional] Factor (alpha) and exponent (beta) of the kdp-r power law. If not set the factors are going to be determined according to the radar frequency.

refl_field [str, optional] Name of the reflectivity field to use.

kdp_field [str, optional] Name of the specific differential phase field to use.

rr_field [str, optional] Name of the rainfall rate field.

master_field [str, optional] Name of the field that is going to act as master. Has to be either `refl_field` or `kdp_field`. Default is `refl_field`.

thresh [float, optional] Value of the threshold that determines when to use the slave field [mm/h].

thresh_max [Bool, optional] If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns

rain_master [dict] Field dictionary containing the rainfall rate.

```
pyart.retrieve.qpe.estimate_rain_rate_zpoly(radar, refl_field=None, rr_field=None)
```

Estimates rainfall rate from reflectivity using a polynomial Z-R relation developed at McGill University.

Parameters

radar [Radar] Radar object.

refl_field [str, optional] Name of the reflectivity field to use.

rr_field [str, optional] Name of the rainfall rate field.

Returns

rain [dict] Field dictionary containing the rainfall rate.

PYART.RETRIEVE.QUASI_VERTICAL_PROFILE

Retrieval of QVPs from a radar object

<i>quasi_vertical_profile</i> (radar[,...])	Quasi Vertical Profile.
<i>compute_qvp</i> (radar, field_names[, ref_time, ...])	Computes quasi vertical profiles.
<i>compute_rqvp</i> (radar, field_names[, ref_time, ...])	Computes range-defined quasi vertical profiles.
<i>compute_evp</i> (radar, field_names, lon, lat[,...])	Computes enhanced vertical profiles.
<i>compute_svp</i> (radar, field_names, lon, lat, angle)	Computes slanted vertical profiles.
<i>compute_vp</i> (radar, field_names, lon, lat[,...])	Computes vertical profiles.
<i>compute_ts_along_coord</i> (radar, field_name[,...])	Computes time series along a particular antenna coordinate, i.e.
<i>compute_directional_stats</i> (field[, avg_type, ...])	Computes the mean or the median along one of the axis (ray or range)
<i>project_to_vertical</i> (data_in, data_height, ...)	Projects radar data to a regular vertical grid
<i>find_rng_index</i> (rng_vec, rng[, rng_tol])	Find the range index corresponding to a particular range
<i>get_target_elevations</i> (radar_in)	Gets RHI target elevations
<i>find_nearest_gate</i> (radar, lat, lon[, latlon_tol])	Find the radar gate closest to a lat,lon point
<i>find_neighbour_gates</i> (radar, azi, rng[,...])	Find the neighbouring gates within +-delta_azi and +-delta_rng
<i>_create_qvp_object</i> (radar, field_names[,...])	Creates a QVP object containing fields from a radar object that can be used to plot and produce the quasi vertical profile
<i>_create_along_coord_object</i> (radar, ...[,...])	Creates an along coord object containing fields from a radar object that can be used to plot and produce the time series along a coordinate
<i>_update_qvp_metadata</i> (qvp, ref_time, lon, lat)	updates a QVP object metadata with data from the current radar volume
<i>_update_along_coord_metadata</i> (acoord, ...)	updates an along coordinate object metadata with data from the current radar volume

`pyart.retrieve.qvp._create_along_coord_object` (radar, field_names, rng_values, fixed_angle, mode, start_time=None)
 Creates an along coord object containing fields from a radar object that can be used to plot and produce the time series along a coordinate

Parameters

- radar** [Radar] Radar object used.
- field_names** [list of strings] Radar fields to use for QVP calculation.
- rng_values** [1D-array] The values to put in the range field
- fixed_angle** [float] the fixed angle

mode [str] The along coord mode, can be ALONG_AZI, ALONG_ELE, ALONG_RNG

start_time [datetime object] the acoord start time

Returns

acoord [Radar-like object] An along coordinate object containing fields from a radar object

`pyart.retrieve.qvp._create_qvp_object` (*radar*, *field_names*, *qvp_type='qvp'*,
start_time=None, *hmax=10000.0*, *hres=200.0*)

Creates a QVP object containing fields from a radar object that can be used to plot and produce the quasi vertical profile

Parameters

radar [Radar] Radar object used.

field_names [list of strings] Radar fields to use for QVP calculation.

qvp_type [str] Type of QVP. Can be qvp, rqvp, evp

start_time [datetime object] the QVP start time

hmax [float] The maximum height of the QVP [m]. Default 10000.

hres [float] The QVP range resolution [m]. Default 50

Returns

qvp [Radar-like object] A quasi vertical profile object containing fields from a radar object

`pyart.retrieve.qvp._update_along_coord_metadata` (*acoord*, *ref_time*, *elevation*, *azimuth*)
updates an along coordinate object metadata with data from the current radar volume

Parameters

acoord [along coordinate object] along coordinate object

ref_time [datetime object] the current radar volume reference time

elevation, azimuth [1D-array] the elevation and azimuth value of the data selected

Returns

acoord [along coordinate object] The updated along coordinate object

`pyart.retrieve.qvp._update_qvp_metadata` (*qvp*, *ref_time*, *lon*, *lat*, *elev=90.0*)
updates a QVP object metadata with data from the current radar volume

Parameters

qvp [QVP object] QVP object

ref_time [datetime object] the current radar volume reference time

Returns

qvp [QVP object] The updated QVP object

`pyart.retrieve.qvp.compute_directional_stats` (*field*, *avg_type='mean'*, *nvalid_min=1*,
axis=0)

Computes the mean or the median along one of the axis (ray or range)

Parameters

field [ndarray] the radar field

avg_type :str the type of average: 'mean' or 'median'

nvalid_min [int] the minimum number of points to consider the stats valid. Default 1

axis [int] the axis along which to compute (0=ray, 1=range)

Returns

values [ndarray 1D] The resultant statistics

nvalid [ndarray 1D] The number of valid points used in the computation

```
pyart.retrieve.qvp.compute_evp (radar, field_names, lon, lat, ref_time=None, latlon_tol=0.0005,
                                delta_rng=15000.0, delta_az=10, hmax=10000.0, hres=250.0,
                                avg_type='mean', nvalid_min=1, interp_kind='none',
                                qvp=None)
```

Computes enhanced vertical profiles.

Parameters

radar [Radar] Radar object used.

field_names [list of str] list of field names to add to the QVP

lat, lon [float] latitude and longitude of the point of interest [deg]

ref_time [datetime object] reference time for current radar volume

latlon_tol [float] tolerance in latitude and longitude in deg.

delta_rng, delta_az [float] maximum range distance [m] and azimuth distance [degree] from the central point of the evp containing data to average.

hmax [float] The maximum height to plot [m].

hres [float] The height resolution [m].

avg_type [str] The type of averaging to perform. Can be either “mean” or “median”

nvalid_min [int] Minimum number of valid points to accept average.

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

qvp [QVP object or None] If it is not None this is the QVP object where to store the data from the current time step. Otherwise a new QVP object will be created

Returns

qvp [qvp object] The computed enhanced vertical profile

```
pyart.retrieve.qvp.compute_qvp (radar, field_names, ref_time=None, angle=0.0, ang_tol=1.0,
                                hmax=10000.0, hres=50.0, avg_type='mean', nvalid_min=30,
                                interp_kind='none', qvp=None)
```

Computes quasi vertical profiles.

Parameters

radar [Radar] Radar object used.

field_names [list of str] list of field names to add to the QVP

ref_time [datetime object] reference time for current radar volume

angle [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle.

ang_tol [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI

hmax [float] The maximum height to plot [m].

hres [float] The height resolution [m].

avg_type [str] The type of averaging to perform. Can be either “mean” or “median”

nvalid_min [int] Minimum number of valid points to accept average.

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

qvp [QVP object or None] If it is not None this is the QVP object where to store the data from the current time step. Otherwise a new QVP object will be created

Returns

qvp [qvp object] The computed QVP object

```
pyart.retrieve.qvp.compute_rqvp(radar, field_names, ref_time=None, hmax=10000.0, hres=2.0,
                                avg_type='mean', nvalid_min=30, interp_kind='nearest',
                                rmax=50000.0, weight_power=2.0, qvp=None)
```

Computes range-defined quasi vertical profiles.

Parameters

radar [Radar] Radar object used.

field_names [list of str] list of field names to add to the QVP

ref_time [datetime object] reference time for current radar volume

hmax [float] The maximum height to plot [m].

hres [float] The height resolution [m].

avg_type [str] The type of averaging to perform. Can be either “mean” or “median”

nvalid_min [int] Minimum number of valid points to accept average.

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

rmax [float] ground range up to which the data is intended for use [m].

weight_power [float] Power p of the weighting function $1/abs(grng-(rmax-1))^{*p}$ given to the data outside the desired range. -1 will set the weight to 0.

qvp [QVP object or None] If it is not None this is the QVP object where to store the data from the current time step. Otherwise a new QVP object will be created

Returns

qvp [qvp object] The computed range defined quasi vertical profile

```
pyart.retrieve.qvp.compute_svp (radar, field_names, lon, lat, angle, ref_time=None, ang_tol=1.0,
                                latlon_tol=0.0005, delta_rng=15000.0, delta_az=10,
                                hmax=10000.0, hres=250.0, avg_type='mean', nvalid_min=1,
                                interp_kind='none', qvp=None)
```

Computes slanted vertical profiles.

Parameters

- radar** [Radar] Radar object used.
- field_names** [list of str] list of field names to add to the QVP
- lat, lon** [float] latitude and longitude of the point of interest [deg]
- angle** [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle.
- ref_time** [datetime object] reference time for current radar volume
- ang_tol** [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI
- latlon_tol** [float] tolerance in latitude and longitude in deg.
- delta_rng, delta_az** [float] maximum range distance [m] and azimuth distance [degree] from the central point of the evp containing data to average.
- hmax** [float] The maximum height to plot [m].
- hres** [float] The height resolution [m].
- avg_type** [str] The type of averaging to perform. Can be either “mean” or “median”
- nvalid_min** [int] Minimum number of valid points to accept average.
- interp_kind** [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation
- qvp** [QVP object or None] If it is not None this is the QVP object where to store the data from the current time step. Otherwise a new QVP object will be created

Returns

- qvp** [qvp object] The computed slanted vertical profile

```
pyart.retrieve.qvp.compute_ts_along_coord (radar, field_name, mode='ALONG_AZI',
                                           fixed_range=None, fixed_azimuth=None,
                                           fixed_elevation=None, ang_tol=1.0,
                                           rng_tol=50.0, value_start=None,
                                           value_stop=None, ref_time=None, aco-
                                           ord=None)
```

Computes time series along a particular antenna coordinate, i.e. along azimuth, elevation or range

Parameters

- radar** [Radar] Radar object used.
- field_name** [str] Name of the field
- mode** [str] coordinate to extract data along. Can be ALONG_AZI, ALONG_ELE or ALONG_RNG

fixed_range, fixed_azimuth, fixed_elevation [float] The fixed range [m], azimuth [deg] or elevation [deg] to extract. In each mode two of these parameters have to be defined. If they are not defined they default to 0.

ang_tol, rng_tol [float] The angle tolerance [deg] and range tolerance [m] around the fixed range or azimuth/elevation

value_start, value_stop [float] The minimum and maximum value at which the data along a coordinate start and stop

ref_time [datetime object] reference time for current radar volume

acoord [acoord object or None] If it is not None this is the object where to store the data from the current time step. Otherwise a new acoord object will be created

Returns

acoord [acoord object] The computed data along a coordinate

`pyart.retrieve.qvp.compute_vp(radar, field_names, lon, lat, ref_time=None, latlon_tol=0.0005, hmax=10000.0, hres=50.0, interp_kind='none', qvp=None)`

Computes vertical profiles.

Parameters

radar [Radar] Radar object used.

field_names [list of str] list of field names to add to the QVP

lat, lon [float] latitude and longitude of the point of interest [deg]

ref_time [datetime object] reference time for current radar volume

latlon_tol [float] tolerance in latitude and longitude in deg.

hmax [float] The maximum height to plot [m].

hres [float] The height resolution [m].

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

qvp [QVP object or None] If it is not None this is the QVP object where to store the data from the current time step. Otherwise a new QVP object will be created

Returns

qvp [qvp object] The computed vertical profile

`pyart.retrieve.qvp.find_ang_index(ang_vec, ang, ang_tol=0.0)`

Find the angle index corresponding to a particular fixed angle

Parameters

ang_vec [float array] The angle data array where to look for

ang [float] The angle to search

ang_tol [float] Tolerance [deg]

Returns

ind_ang [int] The angle index

`pyart.retrieve.qvp.find_nearest_gate(radar, lat, lon, latlon_tol=0.0005)`

Find the radar gate closest to a lat,lon point

Parameters

radar [radar object] the radar object
lat, lon [float] The position of the point
latlon_tol [float] The tolerance around this point

Returns

ind_ray, ind_rng [int] The ray and range index
azi, rng [float] the range and azimuth position of the gate

`pyart.retrieve.qvp.find_neighbour_gates(radar, azi, rng, delta_azi=None, delta_rng=None)`

Find the neighbouring gates within +-delta_azi and +-delta_rng

Parameters

radar [radar object] the radar object
azi, rng [float] The azimuth [deg] and range [m] of the central gate
delta_azi, delta_rng [float] The extend where to look for

Returns

inds_ray_aux, ind_rng_aux [int] The indices (ray, rng) of the neighbouring gates

`pyart.retrieve.qvp.find_rng_index(rng_vec, rng, rng_tol=0.0)`

Find the range index corresponding to a particular range

Parameters

rng_vec [float array] The range data array where to look for
rng [float] The range to search
rng_tol [float] Tolerance [m]

Returns

ind_rng [int] The range index

`pyart.retrieve.qvp.get_data_along_azi(radar, field_name, fix_ranges, fix_elevations,
rng_tol=50.0, ang_tol=1.0, azi_start=None,
azi_stop=None)`

Get data at particular (ranges, elevations)

Parameters

radar [radar object] the radar object where the data is
field_name [str] name of the field to filter
fix_ranges, fix_elevations: list of floats List of ranges [m], elevations [deg] couples
rng_tol [float] Tolerance between the nominal range and the radar range [m]
ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]
azi_start, azi_stop: float Start and stop azimuth angle of the data [deg]

Returns

xvals [1D float array] The ranges of each rng, ele pair

yvals [1D float array] The values

valid_rng, valid_ele [float arrays] The rng, ele pairs

```
pyart.retrieve.qvp.get_data_along_ele(radar, field_name, fix_ranges, fix_azimuths,
                                     rng_tol=50.0, ang_tol=1.0, ele_min=None,
                                     ele_max=None)
```

Get data at particular (ranges, azimuths)

Parameters

radar [radar object] the radar object where the data is

field_name [str] name of the field to filter

fix_ranges, fix_azimuths: list of floats List of ranges [m], azimuths [deg] couples

rng_tol [float] Tolerance between the nominal range and the radar range [m]

ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]

ele_min, ele_max: float Min and max elevation angle [deg]

Returns

xvals [1D float array] The ranges of each rng, ele pair

yvals [1D float array] The values

valid_rng, valid_ele [float arrays] The rng, ele pairs

```
pyart.retrieve.qvp.get_data_along_rng(radar, field_name, fix_elevations, fix_azimuths,
                                     ang_tol=1.0, rmin=None, rmax=None)
```

Get data at particular (azimuths, elevations)

Parameters

radar [radar object] the radar object where the data is

field_name [str] name of the field to filter

fix_elevations, fix_azimuths: list of floats List of elevations, azimuths couples [deg]

ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]

rmin, rmax: float Min and Max range of the obtained data [m]

Returns

xvals [1D float array] The ranges of each azi, ele pair

yvals [1D float array] The values

valid_azi, valid_ele [float arrays] The azi, ele pairs

```
pyart.retrieve.qvp.get_target_elevations(radar_in)
```

Gets RHI target elevations

Parameters

radar_in [Radar object] current radar object

Returns

target_elevations [1D-array] Azimuth angles

el_tol [float] azimuth tolerance

```
pyart.retrieve.qvp.project_to_vertical(data_in, data_height, grid_height, in-  
terp_kind='none', fill_value=-9999.0)
```

Projects radar data to a regular vertical grid

Parameters

data_in [ndarray 1D] the radar data to project
data_height [ndarray 1D] the height of each radar point
grid_height [ndarray 1D] the regular vertical grid to project to
interp_kind [str] The type of interpolation to use: 'none' or 'nearest'
fill_value [float] The fill value used for interpolation

Returns

data_out [ndarray 1D] The projected data

```
pyart.retrieve.qvp.quasi_vertical_profile(radar, desired_angle=None, fields=None, gate-  
filter=None)
```

Quasi Vertical Profile.

Creates a QVP object containing fields from a radar object that can be used to plot and produce the quasi vertical profile

Parameters

radar [Radar] Radar object used.
field [string] Radar field to use for QVP calculation.
desired_angle [float] Radar tilt angle to use for indexing radar field data. None will result in wanted_angle = 20.0

Returns

qvp [Dictionary] A quasi vertical profile object containing fields from a radar object

Other Parameters

gatefilter [GateFilter] A GateFilter indicating radar gates that should be excluded from the import qvp calculation

References

- Troemel, S., M. Kumjian, A. Ryzhkov, and C. Simmer, 2013: Backscatter differential phase - estimation and variability. J Appl. Meteor. Clim.. 52, 2529 - 2548.
- Troemel, S., A. Ryzhkov, P. Zhang, and C. Simmer, 2014: Investigations of backscatter differential phase in the melting layer. J. Appl. Meteorol. Clim. 54, 2344 - 2359.
- Ryzhkov, A., P. Zhang, H. Reeves, M. Kumjian, T. Tschallener, S. Tromel, C. Simmer, 2015: Quasi-vertical profiles - a new way to look at polarimetric radar data. Submitted to J. Atmos. Oceanic Technol.

PYART.RETRIEVE.SIMPLE_MOMENT_CALCULATIONS

Simple moment calculations.

<i>compute_ccor</i> (radar[, filt_field, ...])	Computes the clutter correction ratio (CCOR), i.e.
<i>calculate_snr_from_reflectivity</i> (radar[, ...])	Calculate the signal to noise ratio, in dB, from the reflectivity field.
<i>compute_radial_noise_hs</i> (radar[, ind_rmin, ...])	Computes radial noise in dBm from signal power using the algorithm from Hildebrand and Sekhon 1974
<i>compute_radial_noise_ivic</i> (radar[, ...])	Computes radial noise in dBm from signal power using the algorithm described in Ivic et al.
<i>compute_noisedBZ</i> (nrays, noisedBZ_val, ...[, ...])	Computes noise in dBZ from reference noise value.
<i>compute_vol_refl</i> (radar[, kw, freq, ...])	Computes the volumetric reflectivity from the effective reflectivity factor
<i>compute_signal_power</i> (radar[, lmf, attg, ...])	Computes received signal power OUTSIDE THE RADOME in dBm from a reflectivity field.
<i>compute_rcs_from_pr</i> (radar[, lmf, attg, ...])	Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.
<i>compute_rcs</i> (radar[, kw2, pulse_width, ...])	Computes the radar cross-section (assuming a point target) from radar reflectivity.
<i>compute_snr</i> (radar[, refl_field, ...])	Computes SNR from a reflectivity field and the noise in dBZ.
<i>compute_l</i> (radar[, rhohv_field, l_field])	Computes Rhohv in logarithmic scale according to $L = -\log_{10}(1 - \text{RhoHV})$.
<i>compute_cdr</i> (radar[, rhohv_field, zdr_field, ...])	Computes the Circular Depolarization Ratio.
<i>compute_bird_density</i> (radar[, sigma_bird, ...])	Computes the bird density from the volumetric reflectivity
<i>calculate_velocity_texture</i> (radar[, ...])	Derive the texture of the velocity field.
<i>atmospheric_gas_att</i> (freq, elev, rng)	Computes the one-way atmospheric gas attenuation [dB] according to the empirical formula in Doviak and Zrnic (1993) pp 44.
<i>get_coeff_attg</i> (freq)	get the 1-way gas attenuation for a particular frequency
<i>_coeff_attg_table</i> ()	defines the 1-way gas attenuation for each frequency band.

`pyart.retrieve.simple_moment_calculations._coeff_attg_table()`
defines the 1-way gas attenuation for each frequency band.

Returns

coeff_attg_dict [dict] A dictionary with the coefficients at each band

`pyart.retrieve.simple_moment_calculations.atmospheric_gas_att(freq, elev, rng)`

Computes the one-way atmospheric gas attenuation [dB] according to the empirical formula in Doviak and Zrnic (1993) pp 44. This formula is valid for elev < 10 deg and rng < 200 km so values above these will be saturated to 10 deg and 200 km respectively

Parameters

freq [float] radar frequency [Hz]

elev [float or array of floats] elevation angle [deg]

rng [float or array of floats. If array must have the same size as elev] range [km]

Returns

latm [float or array of floats] 1-way gas attenuation [dB]

`pyart.retrieve.simple_moment_calculations.calculate_snr_from_reflectivity(radar, refl_field=None, snr_field=None, toa=25000.0)`

Calculate the signal to noise ratio, in dB, from the reflectivity field.

Parameters

radar [Radar] Radar object from which to retrieve reflectivity field.

refl_field [str, optional] Name of field in radar which contains the reflectivity. None will use the default field name in the Py-ART configuration file.

snr_field [str, optional] Name to use for snr metadata. None will use the default field name in the Py-ART configuration file.

toa [float, optional] Height above which to take noise floor measurements, in meters.

Returns

snr [field dictionary] Field dictionary containing the signal to noise ratio.

`pyart.retrieve.simple_moment_calculations.calculate_velocity_texture(radar, vel_field=None, wind_size=4, nyq=None, check_nyq_uniform=True)`

Derive the texture of the velocity field.

Parameters

radar: Radar Radar object from which velocity texture field will be made.

vel_field [str, optional] Name of the velocity field. A value of None will force Py-ART to automatically determine the name of the velocity field.

wind_size [int, optional] The size of the window to calculate texture from. The window is defined to be a square of size wind_size by wind_size.

nyq [float, optional] The nyquist velocity of the radar. A value of None will force Py-ART to try and determine this automatically.

check_nyquist_uniform [bool, optional] True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the nyq parameter is not None.

Returns

vel_dict: dict A dictionary containing the field entries for the radial velocity texture.

```
pyart.retrieve.simple_moment_calculations.compute_bird_density(radar,
                                                                sigma_bird=11,
                                                                vol_refl_field=None,
                                                                bird_density_field=None)
```

Computes the bird density from the volumetric reflectivity

Parameters

radar [Radar] radar object

sigma_bird [float] Estimated bird radar cross-section

vol_refl_field [str] name of the volumetric reflectivity used for the calculations

bird_density_field [str] name of the bird density field

Returns

bird_density_dict [dict] bird density data and metadata [birds/km³]

```
pyart.retrieve.simple_moment_calculations.compute_ccor(radar,      filt_field=None,
                                                         unfilt_field=None,
                                                         ccor_field=None)
```

Computes the clutter correction ratio (CCOR), i.e. the ratio between the signal without Doppler filtering and the signal with Doppler filtering

Parameters

radar [Radar] Radar object

filt_field, unfilt_field [str] Name of Doppler filtered and unfiltered fields

ccor_field [str] Name of the CCOR field

Returns

ccor_dict [field dictionary] Field dictionary containing the CCOR

```
pyart.retrieve.simple_moment_calculations.compute_cdr(radar,      rhohv_field=None,
                                                         zdr_field=None,
                                                         cdr_field=None)
```

Computes the Circular Depolarization Ratio.

Parameters

radar [Radar] Radar object.

rhohv_field [str, optional] Name of the RhoHV field.

zdr_field [str, optional] Name of the ZDR field.

cdr_field [str, optional] Name of the CDR field.

Returns

cdr [dict] CDR field.

```
pyart.retrieve.simple_moment_calculations.compute_l(radar,      rhohv_field=None,
                                                         l_field=None)
```

Computes Rhohv in logarithmic scale according to $L = -\log_{10}(1 - \text{RhoHV})$.

Parameters

radar [Radar] Radar object.

rhohv_field [str, optional] Name of the RhoHV field to use.

l_field [str, optional] Name of the L field.

Returns

I [dict] L field.

```
pyart.retrieve.simple_moment_calculations.compute_noisedBZ(nrays, noisedBZ_val,  
                                                           _range,      ref_dist,  
                                                           noise_field=None)
```

Computes noise in dBZ from reference noise value.

Parameters

nrays [int] Number of rays in the reflectivity field.

noisedBZ_val [float] Estimated noise value in dBZ at reference distance.

_range [np array of floats] Range vector in m.

ref_dist [float] Reference distance in Km.

noise_field [str, optional] Name of the noise field.

Returns

noisedBZ [dict] The noise field.

```
pyart.retrieve.simple_moment_calculations.compute_radial_noise_hs(radar,  
                                                                    ind_rmin=0,  
                                                                    nbins_min=1,  
                                                                    max_std_pwr=2.0,  
                                                                    pwr_field=None,  
                                                                    noise_field=None,  
                                                                    get_noise_pos=False)
```

Computes radial noise in dBm from signal power using the algorithm from Hildebrand and Sekhon 1974

Parameters

radar: radar object radar object containing the signal power in dBm

ind_rmin: int index of the gate nearest to the radar where start looking for noisy gates

nbins_min: int min number of noisy gates to consider the estimation valid

max_std_pwr: float max standard deviation of the noise power to consider the noise valid

pwr_field: str Name of the input signal power field

noise_field: str name of the noise field to use

get_noise_pos [bool] If true an additional field with gates containing noise according to the algorithm is produced

Returns

noise_dict [dict] the noise field in dBm

noise_pos_dict [dict or None] a dictionary containing a field where the gates with noise are set to 2 and those without are set to 1 (0 reserved)

References

P. H. Hildebrand and R. S. Sekhon, Objective Determination of the Noise Level in Doppler Spectra. Journal of Applied Meteorology, 1974, 13, 808-811.


```
pyart.retrieve.simple_moment_calculations.compute_radial_noise_ivic(radar,
                                                                    npulses_ray=30,
                                                                    flat_reg_wlen=96,
                                                                    ngates_min=800,
                                                                    iterations=10,
                                                                    pwr_field=None,
                                                                    noise_field=None,
                                                                    get_noise_pos=False)
```

Computes radial noise in dBm from signal power using the algorithm described in Ivic et al. 2013

Parameters

radar: radar object radar object containing the signal power in dBm

npulses_ray [int] Default number of pulses used in the computation of the ray. If the number of pulses is not in radar.instrument_parameters this will be used instead

flat_reg_wlen [int] number of gates considered to find flat regions. The number represents 8 km length with a 83.3 m resolution

ngates_min: int minimum number of gates with noise to consider the retrieval valid

iterations: int number of iterations in step 7

pwr_field: str Name of the input signal power field

noise_field: str name of the noise field to use

get_noise_pos [bool] If true an additional field with gates containing noise according to the algorithm is produced

Returns

noise_dict [dict] the noise field in dBm

noise_pos_dict [dict] the position of the noisy gates

get_noise_pos [bool] If true an additional field with gates containing noise according to the algorithm is produced

References

I.R. Ivic, C. Curtis and S.M. Torres, Radial-Based Noise Power Estimation for Weather Radars. Journal of Atmospheric and Oceanic Technology, 2013, 30, 2737-2753.

```
pyart.retrieve.simple_moment_calculations.compute_rcs(radar,
                                                       kw2=0.93,
                                                       pulse_width=None,
                                                       beamwidth=None,
                                                       freq=None, refl_field=None,
                                                       rcs_field=None)
```

Computes the radar cross-section (assuming a point target) from radar reflectivity.

Parameters

radar [Radar] radar object

kw2 [float] water constant

pulse_width [float] pulse width [s]

beamwidth [float] beamwidth [degree]

freq [float] radar frequency [Hz]. If none it will be obtained from the radar metadata

refl_field [str] name of the reflectivity used for the calculations

rsc_field [str] name of the RCS field

Returns

rsc_dict [dict] RCS field and metadata

```
pyart.retrieve.simple_moment_calculations.compute_rsc_from_pr(radar, lmf=None,
                                                             attg=None, rad-
                                                             const=None,
                                                             tx_pwr=None,
                                                             an-
                                                             tenna_gain=None,
                                                             lrx=0.0, ltx=0.0,
                                                             lradome=0.0,
                                                             freq=None,
                                                             refl_field=None,
                                                             rsc_field=None,
                                                             ne-
                                                             glect_gas_att=False)
```

Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.

Parameters

radar [Radar] radar object

lmf [float] matched filter losses. If None it will be obtained from the attribute `radar_calibration` of the radar object

attg [float] 1-way gas attenuation

radconst [float] radar constant

tx_pwr [float] radar transmitted power [dBm]

antenna_gain [float] antenna gain [dB]. If None it will be obtain from the `instrument_parameters` attribute of the radar object

lrx [float] receiver losses from the antenna feed to the reference point (positive value) [dB]

lradome [float] 1-way losses due to the radome (positive value) [dB]

freq [float] radar frequency [Hz]. If none it will be obtained from the radar metadata

refl_field [str] name of the reflectivity used for the calculations

rsc_field [str] name of the RCS field

neglect_gas_att [bool] Whether to neglect or not gas attenuation in the estimation of the RCS

Returns

rsc_dict [dict] RCS field and metadata

```
pyart.retrieve.simple_moment_calculations.compute_signal_power(radar,
                                                                lmf=None,
                                                                attg=None, rad-
                                                                const=None,
                                                                lrx=0.0,
                                                                lradome=0.0,
                                                                refl_field=None,
                                                                pwr_field=None)
```

Computes received signal power OUTSIDE THE RADOME in dBm from a reflectivity field.

Parameters

radar [Radar] radar object
lmf [float] matched filter losses
attg [float] 1-way gas attenuation
radconst [float] radar constant
lrx [float] receiver losses from the antenna feed to the reference point (positive value) [dB]
lradome [float] 1-way losses due to the radome (positive value) [dB]
refl_field [str] name of the reflectivity used for the calculations
pwr_field [str] name of the signal power field

Returns

s_pwr_dict [dict] power field and metadata

```
pyart.retrieve.simple_moment_calculations.compute_snr(radar, refl_field=None,
                                                       noise_field=None,
                                                       snr_field=None)
```

Computes SNR from a reflectivity field and the noise in dBZ.

Parameters

radar [Radar] Radar object
refl_field [str, optional] Name of the reflectivity field to use.
noise_field [str, optional] Name of the noise field to use.
snr_field [str, optional] Name of the SNR field.

Returns

snr [dict] The SNR field.

```
pyart.retrieve.simple_moment_calculations.compute_vol_refl(radar, kw=0.93,
                                                           freq=None,
                                                           refl_field=None,
                                                           vol_refl_field=None)
```

Computes the volumetric reflectivity from the effective reflectivity factor

Parameters

radar [Radar] radar object
kw [float] water constant
freq [None or float] radar frequency
refl_field [str] name of the reflectivity used for the calculations
vol_refl_field [str] name of the volumetric reflectivity

Returns

vol_refl_dict [dict] volumetric reflectivity and metadata in $10\log_{10}(\text{cm}^2 \text{ km}^{-3})$

```
pyart.retrieve.simple_moment_calculations.get_coeff_attg(freq)
```

get the 1-way gas attenuation for a particular frequency

Parameters

freq [float] radar frequency [Hz]

Returns

attg [float] 1-way gas attenuation

PYART.RETRIEVE.SPECTRA

Retrievals from spectral data.

<i>compute_iq</i> (spectra, fields_in_list, ...[, ...])	Computes the IQ data from the spectra through an inverse Fourier transform
<i>compute_spectral_power</i> (spectra[, units, ...])	Computes the spectral power from the complex spectra in ADU.
<i>compute_spectral_noise</i> (spectra[, units, ...])	Computes the spectral noise power from the complex spectra in ADU.
<i>compute_spectral_reflectivity</i> (spectra[, ...])	Computes the spectral reflectivity from the complex spectra in ADU or from the signal power in ADU.
<i>compute_spectral_differential_reflectivity</i> (spectra[, ...])	Computes the spectral differential reflectivity from the complex spectras or the power in ADU
<i>compute_spectral_differential_phase</i> (spectra[, ...])	Computes the spectral differential reflectivity from the complex spectras in ADU or sRhoHV
<i>compute_spectral_rhohv</i> (spectra[, ...])	Computes the spectral RhoHV from the complex spectras in ADU
<i>compute_spectral_phase</i> (spectra[, signal_field])	Computes the spectral phase from the complex spectra in ADU
<i>compute_pol_variables</i> (spectra, fields_list)	Computes the polarimetric variables from the complex spectra in ADU or the spectral powers and spectral RhoHV
<i>compute_noise_power</i> (spectra[, units, navg, ...])	Computes the noise power from the complex spectra in ADU.
<i>compute_reflectivity</i> (spectra[, sdBZ_field])	Computes the reflectivity from the spectral reflectivity
<i>compute_differential_reflectivity</i> (spectra[, ...])	Computes the differential reflectivity from the horizontal and vertical spectral reflectivity
<i>compute_differential_phase</i> (spectra[, ...])	Computes the differential phase from the spectral differential phase and the spectral reflectivity
<i>compute_rhohv</i> (spectra[, use_rhohv, ...])	Computes RhoHV from the horizontal and vertical spectral reflectivity or from sRhoHV and the spectral powers
<i>compute_Doppler_velocity</i> (spectra[, sdBZ_field])	Computes the Doppler velocity from the spectral reflectivity
<i>compute_Doppler_width</i> (spectra[, sdBZ_field])	Computes the Doppler width from the spectral reflectivity
<i>_compute_power</i> (signal[, noise, ...])	Compute the signal power in linear units
<i>_smooth_spectral_power</i> (raw_data[, wind_len])	smoothes the spectral power using a rolling Gaussian window.

`pyart.retrieve.spectra._compute_power` (*signal*, *noise=None*, *subtract_noise=False*,
smooth_window=None)

Compute the signal power in linear units

Parameters

signal [float array] The complex spectra

noise [float array] The noise power per Doppler bin

subtract_noise [Bool] If True and noise not None the noise power will be subtracted from the signal power

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

Returns

pwr [float array] The computed power

`pyart.retrieve.spectra._smooth_spectral_power` (*raw_data*, *wind_len=5*)

smoothes the spectral power using a rolling Gaussian window.

Parameters

raw_data [float masked array] The data to smooth.

wind_len [float] Length of the moving window

Returns

data_smooth [float masked array] smoothed data

`pyart.retrieve.spectra.compute_Doppler_velocity` (*spectra*, *sdBZ_field=None*)

Computes the Doppler velocity from the spectral reflectivity

Parameters

spectra [Radar spectra object] Object containing the required fields

sdBZ_field [str] Name of the field that contains the spectral reflectivity. None will use the default field name in the Py-ART configuration file.

Returns

vel_dict [field dictionary] Field dictionary containing the Doppler velocity

`pyart.retrieve.spectra.compute_Doppler_width` (*spectra*, *sdBZ_field=None*)

Computes the Doppler width from the spectral reflectivity

Parameters

spectra [Radar spectra object] Object containing the required fields

sdBZ_field [str] Name of the field that contains the spectral reflectivity. None will use the default field name in the Py-ART configuration file.

Returns

width_dict [field dictionary] Field dictionary containing the Doppler spectrum width

`pyart.retrieve.spectra.compute_differential_phase` (*spectra*, *sdBZ_field=None*,
sPhiDP_field=None)

Computes the differential phase from the spectral differential phase and the spectral reflectivity

Parameters

spectra [Radar spectra object] Object containing the required fields

sdBZ_field, sPhiDP_field [str] Name of the fields that contain the spectral reflectivity and the spectral differential phase. None will use the default field name in the Py-ART configuration file.

Returns

PhiDP_dict [field dictionary] Field dictionary containing the differential phase

```
pyart.retrieve.spectra.compute_differential_reflectivity(spectra,  
                                                       sdBZ_field=None,  
                                                       sdBZv_field=None)
```

Computes the differential reflectivity from the horizontal and vertical spectral reflectivity

Parameters

spectra [Radar spectra object] Object containing the required fields

sdBZ_field, sdBZv_field [str] Name of the fields that contain the spectral reflectivity. None will use the default field name in the Py-ART configuration file.

Returns

ZDR_dict [field dictionary] Field dictionary containing the differential reflectivity

```
pyart.retrieve.spectra.compute_iq(spectra, fields_in_list, fields_out_list, window=None)
```

Computes the IQ data from the spectra through an inverse Fourier transform

Parameters

spectra [Spectra radar object] Object containing the spectra

fields_in_list [list of str] list of input spectra fields names

fields_out_list [list of str] list with the output IQ fields names obtained from the input fields

window [string, tuple or None] Parameters of the window used to obtain the spectra. The parameters are the ones corresponding to function `scipy.signal.windows.get_window`. If it is not None the inverse will be used to multiply the IQ data obtained by the IFFT

Returns

radar [IQ radar object] radar object containing the IQ fields

```
pyart.retrieve.spectra.compute_noise_power(spectra, units='dBADU', navg=1, rmin=0.0,  
                                           nnoise_min=1, signal_field=None)
```

Computes the noise power from the complex spectra in ADU. Requires key `dBADU_to_dBm_hh` or `dBADU_to_dBm_vv` in `radar_calibration` if the units are to be dBm. The noise is computed using the method described in Hildebrand and Sehkun, 1974.

Parameters

spectra [Radar spectra object] Object containing the required fields

units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'

navg [int] Number of spectra averaged

rmin [int] Range from which the data is used to estimate the noise

nnoise_min [int] Minimum number of samples to consider the estimated noise power valid

signal_field [str, optional] Name of the field in radar which contains the signal. None will use the default field name in the Py-ART configuration file.

Returns

noise_dict [field dictionary] Field dictionary containing the noise power

References

P. H. Hildebrand and R. S. Sekhon, Objective Determination of the Noise Level in Doppler Spectra. Journal of Applied Meteorology, 1974, 13, 808-811.

```
pyart.retrieve.spectra.compute_pol_variables(spectra, fields_list, use_pwr=False, subtract_noise=False, smooth_window=None,  
                                             srhohv_field=None, pwr_h_field=None,  
                                             pwr_v_field=None, signal_h_field=None,  
                                             signal_v_field=None, noise_h_field=None,  
                                             noise_v_field=None)
```

Computes the polarimetric variables from the complex spectra in ADU or the spectral powers and spectral RhoHV

Parameters

spectra [Radar spectra object] Object containing the required fields

fields_list [list of str] list of fields to compute

use_pwr [Bool] If True the polarimetric variables will be computed from the spectral power and the spectral RhoHV. Otherwise from the complex spectra

subtract_noise [Bool] If True noise will be subtracted from the signals

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

srhohv_field, pwr_h_field, pwr_v_field, signal_h_field, signal_v_field,

noise_h_field, noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

radar [radar object] Object containing the computed fields

```
pyart.retrieve.spectra.compute_reflectivity(spectra, sdBZ_field=None)
```

Computes the reflectivity from the spectral reflectivity

Parameters

spectra [Radar spectra object] Object containing the required fields

sdBZ_field [str] Name of the field that contains the spectral reflectivity. None will use the default field name in the Py-ART configuration file.

Returns

dBZ_dict [field dictionary] Field dictionary containing the reflectivity

```
pyart.retrieve.spectra.compute_rhohv(spectra, use_rhohv=False, subtract_noise=False,  
                                     srhohv_field=None, pwr_h_field=None,  
                                     pwr_v_field=None, signal_h_field=None,  
                                     signal_v_field=None, noise_h_field=None,  
                                     noise_v_field=None)
```

Computes RhoHV from the horizontal and vertical spectral reflectivity or from sRhoHV and the spectral powers

Parameters

spectra [Radar spectra object] Object containing the required fields

use_rhohv [Bool] If true the RhoHV will be computed from sRho_hv. Otherwise it will be computed using the complex spectra

subtract_noise [Bool] If True noise will be subtracted from the signals

srhohv_field, pwr_h_field, pwr_v_field, signal_h_field, signal_v_field,

noise_h_field, noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

RhoHV_dict [field dictionary] Field dictionary containing the RhoHV

```
pyart.retrieve.spectra.compute_spectral_differential_phase(spectra,  
                                                         use_rhohv=False,  
                                                         srhohv_field=None,  
                                                         signal_h_field=None,  
                                                         signal_v_field=None)
```

Computes the spectral differential reflectivity from the complex spectras in ADU or sRhoHV

Parameters

spectra [Radar spectra object] Object containing the required fields

use_rhohv [Bool] If true sRhoHV is going to be used to compute the differential phase. Otherwise the complex signals are used

signal_h_field, signal_v_field [str] Name of the fields in radar which contains the signal. None will use the default field name in the Py-ART configuration file.

Returns

sPhiDP_dict [field dictionary] Field dictionary containing the spectral differential phase

```
pyart.retrieve.spectra.compute_spectral_differential_reflectivity(spectra,  
                                                                compute_power=True,  
                                                                subtract_noise=False,  
                                                                smooth_window=None,  
                                                                pwr_h_field=None,  
                                                                pwr_v_field=None,  
                                                                signal_h_field=None,  
                                                                signal_v_field=None,  
                                                                noise_h_field=None,  
                                                                noise_v_field=None)
```

Computes the spectral differential reflectivity from the complex spectras or the power in ADU

Parameters

spectra [Radar spectra object] Object containing the required fields

compute_power [Bool] If True the signal power will be computed. Otherwise the field given by the user will be used

subtract_noise [Bool] If True noise will be subtracted from the signals

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

pwr_h_field, pwr_v_field, signal_h_field, signal_v_field, noise_h_field,

noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

sZDR_dict [field dictionary] Field dictionary containing the spectral differential reflectivity

```
pyart.retrieve.spectra.compute_spectral_noise(spectra, units='dBADU', navg=1,
                                             rmin=0.0, nnoise_min=1, signal_field=None)
```

Computes the spectral noise power from the complex spectra in ADU. Requires key dBADU_to_dBm_hh or dBADU_to_dBm_vv in radar_calibration if the units are to be dBm. The noise is computed using the method described in Hildebrand and Sekhon, 1974.

Parameters

spectra [Radar spectra object] Object containing the required fields

units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'

navg [int] Number of spectra averaged

rmin [int] Range from which the data is used to estimate the noise

nnoise_min [int] Minimum number of samples to consider the estimated noise power valid

signal_field [str, optional] Name of the field in radar which contains the signal. None will use the default field name in the Py-ART configuration file.

Returns

noise_dict [field dictionary] Field dictionary containing the spectral noise power

References

P. H. Hildebrand and R. S. Sekhon, Objective Determination of the Noise Level in Doppler Spectra. Journal of Applied Meteorology, 1974, 13, 808-811.

```
pyart.retrieve.spectra.compute_spectral_phase(spectra, signal_field=None)
```

Computes the spectral phase from the complex spectra in ADU

Parameters

spectra [Radar spectra object] Object containing the required fields

signal_field [str, optional] Name of the field in radar which contains the signal. None will use the default field name in the Py-ART configuration file.

Returns

phase_dict [field dictionary] Field dictionary containing the spectral phase

```
pyart.retrieve.spectra.compute_spectral_power(spectra, units='dBADU',
                                             subtract_noise=False,
                                             smooth_window=None, signal_field=None, noise_field=None)
```

Computes the spectral power from the complex spectra in ADU. Requires key dBADU_to_dBm_hh or dBADU_to_dBm_vv in radar_calibration if the units are to be dBm

Parameters

spectra [Radar spectra object] Object containing the required fields

units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'

subtract_noise [Bool] If True noise will be subtracted from the signal

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

signal_field, noise_field [str, optional] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

pwr_dict [field dictionary] Field dictionary containing the spectral power

```
pyart.retrieve.spectra.compute_spectral_reflectivity(spectra, compute_power=True,  
                                                    subtract_noise=False,  
                                                    smooth_window=None,  
                                                    pwr_field=None,  
                                                    signal_field=None,  
                                                    noise_field=None)
```

Computes the spectral reflectivity from the complex spectra in ADU or from the signal power in ADU. Requires keys dBADU_to_dBm_hh or dBADU_to_dBm_vv in radar_calibration if the to be computed

Parameters

spectra [Radar spectra object] Object containing the required fields

compute_power [Bool] If True the signal power will be computed. Otherwise the field given by the user will be used

subtract_noise [Bool] If True noise will be subtracted from the signal

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

pwr_field, signal_field, noise_field [str, optional] Name of the fields in radar which contains the signal power, complex signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

sdBZ_dict [field dictionary] Field dictionary containing the spectral reflectivity

```
pyart.retrieve.spectra.compute_spectral_rhoHV(spectra, subtract_noise=False,  
                                                signal_h_field=None, sig-  
                                                nal_v_field=None, noise_h_field=None,  
                                                noise_v_field=None)
```

Computes the spectral RhoHV from the complex spectras in ADU

Parameters

spectra [Radar spectra object] Object containing the required fields

subtract_noise [Bool] If True noise will be subtracted from the signals

signal_h_field, signal_v_field, noise_h_field, noise_v_field [str] Name of the fields in radar which contains the signal and noise. None will use the default field name in the Py-ART configuration file.

Returns

sRhoHV_dict [field dictionary] Field dictionary containing the spectral RhoHV

PYART.RETRIEVE.VELOCITY_AZIMUTH_DISPLAY

Retrieval of VADs from a radar object.

<code>velocity_azimuth_display(radar[, vel_field, ...])</code>	Velocity azimuth display.
<code>_vad_calculation(velocity_field, azimuth, ...)</code>	Calculates VAD for a scan, returns speed and angle outdic = vad_algorithm(velocity_field, azimuth, elevation) velocity_field is a 2D array, azimuth is a 1D array, elevation is a number.
<code>_interval_mean(data, current_z, wanted_z)</code>	Find the mean of data indexed by current_z at wanted_z on intervals wanted_z+/- delta wanted_z.
<code>_sd_to_uv(speed, direction)</code>	Takes speed and direction to create u_mean and v_mean.

`pyart.retrieve.vad._interval_mean(data, current_z, wanted_z)`

Find the mean of data indexed by current_z at wanted_z on intervals wanted_z+/- delta wanted_z.

`pyart.retrieve.vad._sd_to_uv(speed, direction)`

Takes speed and direction to create u_mean and v_mean.

`pyart.retrieve.vad._vad_calculation(velocity_field, azimuth, elevation)`

Calculates VAD for a scan, returns speed and angle outdic = vad_algorithm(velocity_field, azimuth, elevation) velocity_field is a 2D array, azimuth is a 1D array, elevation is a number. All in degrees, m outdic contains speed and angle.

`pyart.retrieve.vad.velocity_azimuth_display(radar, vel_field=None, z_want=None, gatefilter=None)`

Velocity azimuth display.

Creates a VAD object containing U Wind, V Wind and height that can then be used to plot and produce the velocity azimuth display.

Parameters

radar [Radar] Radar object used.

vel_field [string, optional] Velocity field to use for VAD calculation.

z_want [array, optional] Heights for where to sample vads from. None will result in np.linspace(0, 10000, 100).

gatefilter [GateFilter, optional] A GateFilter indicating radar gates that should be excluded from the import vad calculation.

Returns

vad: HorizontalWindProfile A velocity azimuth display object containing height, speed, direction, u_wind, v_wind from a radar object.

PYART.RETRIEVE.WIND

Functions for wind estimation

<code>est_wind_vel(radar[, vert_proj, vel_field, ...])</code>	Estimates wind velocity.
<code>est_vertical_windshear(radar[, az_tol, ...])</code>	Estimates wind shear.
<code>est_wind_profile(radar[, npoints_min, ...])</code>	Estimates the vertical wind profile using VAD techniques
<code>_wind_coeff(radar)</code>	Computes the coefficients to transform 3-D wind vectors into radial velocity at each range gate
<code>_vad(radar, u_coeff, v_coeff, w_coeff, vel)</code>	Estimates wind components using VAD techniques
<code>_vel_variance</code>	

```
pyart.retrieve.wind._vad(radar, u_coeff, v_coeff, w_coeff, vel, npoints_min=6,
                        azi_spacing_max=45.0, sign=1)
Estimates wind components using VAD techniques
```

Parameters

- radar** [Radar] Radar object
- u_coeff, v_coeff, w_coeff** [2D float arrays] the coefficients to transform 3D winds into radial velocity
- vel** [2D float array] The measured radial velocity field
- npoints_min** [int] Minimum number of points in the VAD to retrieve wind components. 0 will retrieve them regardless
- azi_spacing_max** [float] Maximum spacing between valid gates in the VAD to retrieve wind components. 0 will retrieve them regardless.
- sign** [int, optional] Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.

Returns

- u_vel, v_vel, w_vel** [2D float arrays] The 3 estimated wind components at each range gate
- vel_est** [2D float array] The estimated radial velocity at each range gate

```
pyart.retrieve.wind._vel_std(radar, vel, vel_est)
Computes the variance of the retrieved wind velocity
```

Parameters

- radar** [Radar] Radar object

vel [2D float array] The measured radial velocity field

vel_est [2D float array] The estimated radial velocity field

Returns

vel_std [2D float arrays] The estimated standard deviation at each range gate (one for VAD)

vel_diff [2D float array] The actual velocity difference between estimated and measured radial velocities

`pyart.retrieve.wind._wind_coeff(radar)`

Computes the coefficients to transform 3-D wind vectors into radial velocity at each range gate

Parameters

radar [Radar] Radar object

Returns

u_coeff, v_coeff, w_coeff [2D float arrays] The coefficients for each wind component

`pyart.retrieve.wind.est_vertical_windshear(radar, az_tol=0.5, wind_field=None, windshear_field=None)`

Estimates wind shear.

Parameters

radar [Radar] Radar object

az_tol [float] azimuth tolerance to consider gate on top of selected one

wind_field [str] name of the horizontal wind velocity field

windshear_field [str] name of the vertical wind shear field

Returns

windshear [dict] Field dictionary containing the wind shear field

`pyart.retrieve.wind.est_wind_profile(radar, npoints_min=6, azi_spacing_max=45.0, vel_diff_max=10.0, sign=1, rad_vel_field=None, u_vel_field=None, v_vel_field=None, w_vel_field=None, vel_est_field=None, vel_std_field=None, vel_diff_field=None)`

Estimates the vertical wind profile using VAD techniques

Parameters

radar [Radar] Radar object

npoints_min [int] Minimum number of points in the VAD to retrieve wind components. 0 will retrieve them regardless

azi_spacing_max [float] Maximum spacing between valid gates in the VAD to retrieve wind components. 0 will retrieve them regardless.

vel_diff_max [float] Maximum velocity difference allowed between retrieved and measured radial velocity at each range gate. Gates exceeding this threshold will be removed and VAD will be recomputed. If -1 there will not be a second pass.

sign [int, optional] Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.

rad_vel_field [str] name of the measured radial velocity field

u_vel_field, v_vel_field, w_vel_field [str] names of the 3 wind components fields
vel_est_field [str] name of the retrieved radial Doppler velocity field
vel_std_field [str] name of the standard deviation of the velocity retrieval field
vel_diff_field [str] name of the difference between retrieved and measured radial velocity field

Returns

wind [dict] Field dictionary containing the estimated wind velocity

`pyart.retrieve.wind.est_wind_vel(radar, vert_proj=False, vel_field=None, wind_field=None)`

Estimates wind velocity. Projects the radial wind component to the horizontal or vertical of the azimuth plane. It assumes that the orthogonal component is negligible.

The horizontal wind component is given by: $v = v_r \cos(\text{el}) - v_{el} \sin(\text{el}) + v_{az}$

where: v_r is the radial wind component (measured by the radar) v_{el} is the perpendicular wind component in the azimuth plane. v_{az} is the horizontal component perpendicular to the radial direction and the azimuth plane el is the elevation

The horizontal wind component in the azimuth plane is given by: $v_h = v_r \cos(\text{el}) - v_{el} \sin(\text{el})$

which since we do not know v_{el} we assume: $v_h \sim v_r \cos(\text{el})$

This assumption holds for small elevation angles

The vertical wind component in the azimuth plane is given by: $v_v = v_r \sin(\text{el}) - v_{el} \cos(\text{el})$

which since we do not know v_{el} we assume: $v_v \sim v_r \sin(\text{el})$

This assumption holds for angles close to 90 deg

Parameters

radar [Radar] Radar object
vert_proj [Boolean] If true estimates the vertical projection, otherwise the horizontal
vel_field [str] name of the velocity field
wind_field [str] name of the velocity field

Returns

wind [dict] Field dictionary containing the estimated wind velocity

PYART.RETRIEVE._KDP_PROC

Cython routines for specific differential phase retrievals.

<code>lowpass_maesaka_term()</code>	Compute the filter term.
<code>lowpass_maesaka_jac()</code>	Compute the Jacobian of the filter cost functional.

`pyart.retrieve._kdp_proc.lowpass_maesaka_jac()`

Compute the Jacobian of the filter cost functional.

Compute the Jacobian of the low-pass filter cost functional similar to equation (18) in Maesaka et al. (2012). This function does not currently support radars with variable range resolution.

Parameters

- d2kdr2** [2D array of float64] Second-order derivative of the control variable k with respect to range. The control variable k is proportional to the square root of specific differential phase.
- dr** [float] The range resolution in meters.
- Clpf** [float] The low-pass filter (radial smoothness) constraint weight.
- finite_order** [str, 'low' or 'high'] The finite difference accuracy used to compute the second-order range derivative of the control variable k .
- dJlpfdk** [2D array of float64] The Jacobian of the low-pass filter cost functional with respect to the control variable k . Updated in place.

`pyart.retrieve._kdp_proc.lowpass_maesaka_term()`

Compute the filter term.

Compute the low-pass filter term found in Maesaka et al. (2012). This term represents the second-order derivative of the control variable k with respect to range. This subroutine does not currently support radars with variable range resolution.

Parameters

- k** [2D array of float64] Control variable k defined in Maesaka et al. (2012). This variable is proportional to the square root of specific differential phase.
- dr** [float] The range resolution in meters.
- finite_order** [str, 'low' or 'high'] The finite difference accuracy to use when computing the second-order range derivative of the control variable k .
- d2kdr2** [2D array of float64] Second-order derivative of k with respect to range. Updated in place.

PYART.GRAPH.CM

Radar related colormaps.

<code>revcmap(data)</code>	Can only handle specification <i>data</i> in dictionary format.
<code>_reverser(f)</code>	perform reversal.
<code>_reverse_cmap_spec(spec)</code>	Reverses cmap specification <i>spec</i> , can handle both dict and tuple type specs.
<code>_generate_cmap(name, lutsizes)</code>	Generates the requested cmap from it's name <i>name</i> .

Available colormaps, reversed versions (`_r`) are also provided, these colormaps are available within matplotlib with names 'pyart_COLORMAP':

- BlueBrown10
- BlueBrown11
- BrBu10
- BrBu12
- Bu10
- Bu7
- BuDOr12
- BuDOr18
- BuDRd12
- BuDRd18
- BuGr14
- BuGy8
- BuOr10
- BuOr12
- BuOr8
- BuOrR14
- Carbone11
- Carbone17
- Carbone42
- Cat12

- EWilson17
- GrMg16
- Gray5
- Gray9
- NWSRef
- NWSVel
- NWS_SPW
- PD17
- RRate11
- RdYlBu11b
- RefDiff
- SCook18
- StepSeq25
- SymGray12
- Theodore16
- Wild25
- LangRainbow12

`pyart.graph.cm.__generate_cmap` (*name*, *lutsize*)

Generates the requested cmap from it's name *name*. The lut size is *lutsize*.

`pyart.graph.cm.__reverse_cmap_spec` (*spec*)

Reverses cmap specification *spec*, can handle both dict and tuple type specs.

`pyart.graph.cm.__reverser` (*f*)

perform reversal.

`pyart.graph.cm.revcmmap` (*data*)

Can only handle specification *data* in dictionary format.

PYART.GRAPH.CM_COLORBLIND

Colorblind friendly radar colormaps

`__generate_cmap(name, lutsizes)` Generates the requested cmap from it's name *name*.

Available colormaps, reversed versions are also provided, these colormaps are available within matplotlib with names `pyart.COLORMAP`:

- HomeyerRainbow

`pyart.graph.cm_colorblind.__generate_cmap(name, lutsizes)`
Generates the requested cmap from it's name *name*. The lut size is *lutsizes*.

PYART.GRAPH.COMMON

Common graphing routines.

<i>parse_ax</i> (ax)	Parse and return ax parameter.
<i>parse_ax_fig</i> (ax, fig)	Parse and return ax and fig parameters.
<i>parse_cmap</i> (cmap[, field])	Parse and return the cmap parameter.
<i>parse_vmin_vmax</i> (container, field, vmin, vmax)	Parse and return vmin and vmax parameters.
<i>parse_lon_lat</i> (grid, lon, lat)	Parse lat and lon parameters
<i>generate_colorbar_label</i> (standard_name, units)	Generate and return a label for a colorbar.
<i>generate_field_name</i> (container, field)	Return a nice field name for a particular field.
<i>generate_radar_name</i> (radar)	Return radar name.
<i>generate_grid_name</i> (grid)	Return grid name.
<i>generate_radar_time_begin</i> (radar)	Return time begin in datetime instance.
<i>generate_radar_time_sweep</i> (radar, sweep)	Return time that a specific sweep began in a datetime instance.
<i>generate_grid_time_begin</i> (grid)	Return time begin in datetime instance.
<i>generate_filename</i> (radar, field, sweep[, ...])	Generate a filename for a plot.
<i>generate_grid_filename</i> (grid, field, level[, ext])	Generate a filename for a plot.
<i>generate_title</i> (radar, field, sweep[, ...])	Generate a title for a plot.
<i>generate_grid_title</i> (grid, field, level)	Generate a title for a plot.
<i>generate_longitudinal_level_title</i> (grid, ...)	Generate a title for a plot.
<i>generate_latitudinal_level_title</i> (grid, ...)	Generate a title for a plot.
<i>generate_latlon_level_title</i> (grid, field)	Generate a title for a plot.
<i>generate_vpt_title</i> (radar, field)	Generate a title for a VPT plot.
<i>generate_ray_title</i> (radar, field, ray)	Generate a title for a ray plot.
<i>set_limits</i> (xlim, ylim, ax)	Set the display limits.

`pyart.graph.common.generate_az_rhi_title` (*radar, field, azimuth*)
Generate a title for a pseudo-RHI from PPI azimuth plot.

Parameters

radar [Radar] Radar structure.
field [str] Field plotted.
azimuth [float] Azimuth plotted.

Returns

title [str] Plot title.

`pyart.graph.common.generate_colorbar_label` (*standard_name, units*)
Generate and return a label for a colorbar.

`pyart.graph.common.generate_field_name` (*container, field*)
Return a nice field name for a particular field.

`pyart.graph.common.generate_filename` (*radar, field, sweep, ext='png', date-
time_format='%Y%m%d%H%M%S',
use_sweep_time=False*)

Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters

radar [Radar] Radar structure.

field [str] Field plotted.

sweep [int] Sweep plotted.

ext [str] Filename extension.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

filename [str] Filename suitable for saving a plot.

`pyart.graph.common.generate_grid_filename` (*grid, field, level, ext='png'*)
Generate a filename for a plot.

Generated filename has form: grid_name_field_level_time.ext

Parameters

grid [Grid] Grid structure.

field [str] Field plotted.

level [int] Level plotted.

ext [str] Filename extension.

Returns

filename [str] Filename suitable for saving a plot.

`pyart.graph.common.generate_grid_name` (*grid*)
Return grid name.

`pyart.graph.common.generate_grid_time_begin` (*grid*)
Return time begin in datetime instance.

`pyart.graph.common.generate_grid_title` (*grid, field, level*)
Generate a title for a plot.

Parameters

grid [Grid] Radar structure.

field [str] Field plotted.

level [int] Verical level plotted.

Returns

title [str] Plot title.

`pyart.graph.common.generate_latitudinal_level_title(grid, field, level)`

Generate a title for a plot.

Parameters

grid [Grid] Radar structure.

field [str] Field plotted.

level [int] Latitudinal level plotted.

Returns

title [str] Plot title.

`pyart.graph.common.generate_latlon_level_title(grid, field)`

Generate a title for a plot.

Parameters

grid [Grid] Radar structure.

field [str] Field plotted.

Returns

title [str] Plot title.

`pyart.graph.common.generate_longitudinal_level_title(grid, field, level)`

Generate a title for a plot.

Parameters

grid [Grid] Radar structure.

field [str] Field plotted.

level [int] Longitudinal level plotted.

Returns

title [str] Plot title.

`pyart.graph.common.generate_radar_name(radar)`

Return radar name.

`pyart.graph.common.generate_radar_time_begin(radar)`

Return time begin in datetime instance.

`pyart.graph.common.generate_radar_time_sweep(radar, sweep)`

Return time that a specific sweep began in a datetime instance.

`pyart.graph.common.generate_ray_title(radar, field, ray)`

Generate a title for a ray plot.

Parameters

radar [Radar] Radar structure.

field [str] Field plotted.

ray [int] Ray plotted.

Returns

title [str] Plot title.

```
pyart.graph.common.generate_title(radar, field, sweep, datetime_format=None,
                                  use_sweep_time=True)
```

Generate a title for a plot.

Parameters

radar [Radar] Radar structure.

field [str] Field plotted.

sweep [int] Sweep plotted.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

title [str] Plot title.

```
pyart.graph.common.generate_vpt_title(radar, field)
```

Generate a title for a VPT plot.

Parameters

radar [Radar] Radar structure.

field [str] Field plotted.

Returns

title [str] Plot title.

```
pyart.graph.common.parse_ax(ax)
```

Parse and return ax parameter.

```
pyart.graph.common.parse_ax_fig(ax, fig)
```

Parse and return ax and fig parameters.

```
pyart.graph.common.parse_cmap(cmap, field=None)
```

Parse and return the cmap parameter.

```
pyart.graph.common.parse_lon_lat(grid, lon, lat)
```

Parse lat and lon parameters

```
pyart.graph.common.parse_vmin_vmax(container, field, vmin, vmax)
```

Parse and return vmin and vmax parameters.

```
pyart.graph.common.set_limits(xlim=None, ylim=None, ax=None)
```

Set the display limits.

Parameters

xlim [tuple, optional] 2-Tuple containing y-axis limits in km. None uses default limits.

ylim [tuple, optional] 2-Tuple containing x-axis limits in km. None uses default limits.

ax [Axis] Axis to adjust. None will adjust the current axis.

PYART.GRAPH.GRIDMAPDISPLAY

A class for plotting grid objects using xarray plotting and cartopy.

GridMapDisplay(grid[, debug])

A class for creating plots from a grid object using xarray with a cartopy projection.

class pyart.graph.gridmapdisplay.**GridMapDisplay**(grid, debug=False)

Bases: *object*

A class for creating plots from a grid object using xarray with a cartopy projection.

Parameters

grid [Grid] Grid with data which will be used to create plots.

debug [bool] True to print debugging messages, False to suppress them.

Attributes

grid [Grid] Grid object.

debug [bool] True to print debugging messages, False to suppress them.

Methods

<i>cartopy_coastlines</i> (self)	Get coastlines using cartopy.
<i>cartopy_political_boundaries</i> (self)	Get political boundaries using cartopy.
<i>cartopy_states</i> (self)	Get state boundaries using cartopy.
<i>generate_filename</i> (self, field, level[, ext])	Generate a filename for a grid plot.
<i>generate_grid_title</i> (self, field, level)	Generate a title for a plot.
<i>generate_latitudinal_level_title</i> (self, ...)	Generate a title for a plot.
<i>generate_longitudinal_level_title</i> (self, ...)	Generate a title for a plot.
<i>get_dataset</i> (self)	Creating an xarray dataset from a radar object.
<i>plot_colorbar</i> (self[, mappable, orientation, ...])	Plot a colorbar.
<i>plot_crosshairs</i> (self[, lon, lat, linestyle, ...])	Plot crosshairs at a given longitude and latitude.
<i>plot_grid</i> (self, field[, level, vmin, vmax, ...])	Plot the grid using xarray and cartopy.
<i>plot_grid_contour</i> (self, field[, level, ...])	Plot the grid contour using xarray and cartopy.
<i>plot_latitude_slice</i> (self, field[, lon, lat])	Plot a slice along a given latitude.

Continued on next page

Table 2 – continued from previous page

<code>plot_latitudinal_level(self, y_index)</code>	<code>field,</code>	Plot a slice along a given latitude.
<code>plot_latlon_level(self, ind_1, ind_2)</code>	<code>field,</code>	Plot a slice along two points given by its lat, lon. Additional arguments are passed to Basemaps's <code>pcolormesh</code> function.
<code>plot_latlon_slice(self, coord1, coord2)</code>	<code>field[,</code>	Plot a slice along a given longitude.
<code>plot_longitude_slice(self, lon, lat)</code>	<code>field[,</code>	Plot a slice along a given longitude.
<code>plot_longitudinal_level(self, x_index)</code>	<code>field,</code>	Plot a slice along a given longitude.

```

__class__
    alias of builtins.type

__delattr__(self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.graph.gridmapdisplay', '__doc__': '\n
__dir__(self, /)
    Default dir() implementation.

__eq__(self, value, /)
    Return self==value.

__format__(self, format_spec, /)
    Default object formatter.

__ge__(self, value, /)
    Return self>=value.

__getattr__(self, name, /)
    Return getattr(self, name).

__gt__(self, value, /)
    Return self>value.

__hash__(self, /)
    Return hash(self).

__init__(self, grid, debug=False)
    initialize the object.

__init_subclass__()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__(self, value, /)
    Return self<=value.

__lt__(self, value, /)
    Return self<value.

__module__ = 'pyart.graph.gridmapdisplay'

__ne__(self, value, /)
    Return self!=value.

__new__(*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.

```

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(*self*).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(*self*, *name*, *value*).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(*self*).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_find_nearest_grid_indices (*self*, *lon*, *lat*)
Find the nearest x, y grid indices for a given latitude and longitude.

_get_label_x (*self*)
Get default label for x units.

_get_label_y (*self*)
Get default label for y units.

_get_label_z (*self*)
Get default label for z units.

_label_axes_grid (*self*, *axis_labels*, *ax*)
Set the x and y axis labels for a grid plot.

_label_axes_latitude (*self*, *axis_labels*, *ax*)
Set the x and y axis labels for a latitude slice.

_label_axes_latlon (*self*, *axis_labels*, *ax*)
Set the x and y axis labels for a lat-lon slice.

_label_axes_longitude (*self*, *axis_labels*, *ax*)
Set the x and y axis labels for a longitude slice.

cartopy_coastlines (*self*)
Get coastlines using cartopy.

cartopy_political_boundaries (*self*)
Get political boundaries using cartopy.

cartopy_states (*self*)
Get state boundaries using cartopy.

generate_filename (*self*, *field*, *level*, *ext*='png')
Generate a filename for a grid plot.

Generated filename has form: grid_name_field_level_time.ext

Parameters

field [str] Field plotted.
level [int] Level plotted.
ext [str] Filename extension.

Returns

filename [str] Filename suitable for saving a plot.

generate_grid_title (*self*, *field*, *level*)

Generate a title for a plot.

Parameters

field [str] Field plotted.
level [int] Vertical level plotted.

Returns

title [str] Plot title.

generate_latitudinal_level_title (*self*, *field*, *level*)

Generate a title for a plot.

Parameters

field [str] Field plotted.
level [int] Latitudinal level plotted.

Returns

title [str] Plot title.

generate_longitudinal_level_title (*self*, *field*, *level*)

Generate a title for a plot.

Parameters

field [str] Field plotted.
level [int] Longitudinal level plotted.

Returns

title [str] Plot title.

get_dataset (*self*)

Creating an xarray dataset from a radar object. This function has been removed from Py-ART ARM-DOE

plot_colorbar (*self*, *mappable*=None, *orientation*='horizontal', *label*=None, *cax*=None, *ax*=None,
fig=None, *field*=None, *ticks*=None, *ticklabs*=None)

Plot a colorbar.

Parameters

mappable [Image, ContourSet, etc.] Image, ContourSet, etc to which the colorbar applied.
If None the last mappable object will be used.
field [str] Field to label colorbar with.
label [str] Colorbar label. None will use a default value from the last field plotted.

orient [str] Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax [Axis] Axis onto which the colorbar will be drawn. None is also valid.

ax [Axes] Axis onto which the colorbar will be drawn. None is also valid.

fig [Figure] Figure to place colorbar on. None will use the current figure.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

plot_crosshairs (*self*, *lon=None*, *lat=None*, *linestyle='-'*, *color='r'*, *linewidth=2*, *ax=None*)

Plot crosshairs at a given longitude and latitude.

Parameters

lon, lat [float] Longitude and latitude (in degrees) where the crosshairs should be placed. If None the center of the grid is used.

linestyle [str] Matplotlib string describing the line style.

color [str] Matplotlib string for color of the line.

linewidth [float] Width of markers in points.

ax [axes or None] Axis to add the crosshairs to, if None the current axis is used.

plot_grid (*self*, *field*, *level=0*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=False*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *ax=None*, *fig=None*, *lat_lines=None*, *lon_lines=None*, *projection=None*, *embellish=True*, *maps_list=['countries', 'coastlines']*, *resolution='110m'*, *alpha=None*, *background_zoom=8*, *ticks=None*, *ticklabs=None*, *imshow=False*, ***kwargs*)

Plot the grid using xarray and cartopy.

Additional arguments are passed to Xarray's pcolormesh function.

Parameters

field [str] Field to be plotted.

level [int] Index corresponding to the height level to be plotted.

Other Parameters

vmin, vmax [float] Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are used for luminance scaling.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None will use the default generated from the field and level parameters. Parameter is ignored if the title_flag is False.

title_flag [bool] True to add title to plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

lat_lines, lon_lines [array or None] Location at which to draw latitude and longitude lines. None will use default values which are reasonable for maps of North America.

projection [cartopy.crs class] Map projection supported by cartopy. Used for all subsequent calls to the GeoAxes object generated. Defaults to PlateCarree.

embelish [bool] True by default. Set to False to supress drawinf of coastlines etc... Use for speedup when specifying shapefiles. Note that lat lon labels only work with certain projections.

maps_list: list of strings if embelish is true the list of maps to use. default countries, coastlines

resolution ['10m', '50m', '110m'.] Resolution of NaturalEarthFeatures to use. See Cartopy documentation for details.

alpha [float or None] Set the alpha tranparency of the grid plot. Useful for overplotting radar over other datasets.

background_zoom [int] Zoom of the background image. A highest number provides more detail at the cost of processing speed

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

imshow [bool] If used, plot uses ax.imshow instead of ax.pcolormesh. Default is False.

plot_grid_contour (*self, field, level=0, vmin=None, vmax=None, mask_outside=False, title=None, title_flag=True, ax=None, fig=None, lat_lines=None, lon_lines=None, projection=None, contour_values=None, linewidths=1.5, embelish=True, maps_list=['countries', 'coastlines'], resolution='110m', background_zoom=8, **kwargs*)

Plot the grid contour using xarray and cartopy.

Additional arguments are passed to Xarray's pcolormesh function.

Parameters

field [str] Field to be plotted.

level [int] Index corresponding to the height level to be plotted.

Other Parameters

vmin, vmax [float] Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are used for luminance scaling.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None will use the default generated from the field and level parameters. Parameter is ignored if the title_flag is False.

title_flag [bool] True to add title to plot, False does not add a title.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

lat_lines, lon_lines [array or None] Location at which to draw latitude and longitude lines. None will use default values which are reasonable for maps of North America.

projection [cartopy.crs class] Map projection supported by cartopy. Used for all subsequent calls to the GeoAxes object generated. Defaults to PlateCarree.

contour_values [float array]

list of contours to plot

linewidths [float] width of the contour lines

embelish [bool] True by default. Set to False to suppress drawing of coastlines etc... Use for speedup when specifying shapefiles. Note that lat lon labels only work with certain projections.

maps_list: list of strings if embelish is true the list of maps to use. default countries, coastlines

resolution ['10m', '50m', '110m'.] Resolution of NaturalEarthFeatures to use. See Cartopy documentation for details.

background_zoom [int] Zoom of the background image. A highest number provides more detail at the cost of processing speed

plot_latitude_slice (*self, field, lon=None, lat=None, **kwargs*)

Plot a slice along a given latitude.

For documentation of additional arguments see *plot_latitudinal_level()*.

Parameters

field [str] Field to be plotted.

lon, lat [float] Longitude and latitude (in degrees) specifying the slice. If None the center of the grid is used.

plot_latitudinal_level (*self, field, y_index, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot a slice along a given latitude.

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters

field [str] Field to be plotted.

y_index [float] Index of the latitudinal level to plot.

vmin, vmax [float] Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

plot_latlon_level (*self, field, ind_1, ind_2, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot a slice along two points given by its lat, lon Additional arguments are passed to Basemaps's pcolormesh function. Parameters ——— field : str

Field to be plotted.

ind_1, ind_2 [float] x,y indices of the two points crossed by the slice.

vmin, vmax [float] Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

plot_latlon_slice (*self*, *field*, *coord1=None*, *coord2=None*, ***kwargs*)

Plot a slice along a given longitude. For documentation of additional arguments see `plot_longitudinal_level()`. Parameters ——— field : str

Field to be plotted.

coord1, coord2 [tuple of floats] tuple of floats containing the longitude and latitude (in degrees) specifying the two points crossed by the slice. If none two extremes of the grid is used

plot_longitude_slice (*self*, *field*, *lon=None*, *lat=None*, ***kwargs*)

Plot a slice along a given longitude.

For documentation of additional arguments see `plot_longitudinal_level()`.

Parameters

field [str] Field to be plotted.

lon, lat [float] Longitude and latitude (in degrees) specifying the slice. If None the center of the grid is used.

plot_longitudinal_level (*self*, *field*, *x_index*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, ***kwargs*)

Plot a slice along a given longitude.

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters

field [str] Field to be plotted.

x_index [float] Index of the longitudinal level to plot.

vmin, vmax [float] Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

```
pyart.graph.gridmapdisplay._lambert_ticks(ax, ticks, tick_location, line_constructor,  
                                           tick_extractor)
```

Get the tick locations and labels for a Lambert Conformal projection.

```
pyart.graph.gridmapdisplay.find_side(ls, side)
```

Given a shapely LineString which is assumed to be rectangular, return the line corresponding to a given side of the rectangle.

```
pyart.graph.gridmapdisplay.lambert_xticks(ax, ticks)
```

Draw ticks on the bottom x-axis of a Lambert Conformal projection.

```
pyart.graph.gridmapdisplay.lambert_yticks(ax, ticks)
```

Draw ticks on the left y-axis of a Lambert Conformal projection.

PYART.GRAPH.RADARDISPLAY

Class for creating plots from Radar objects.

RadarDisplay(radar[, shift])

A display object for creating plots from data in a radar object.

class `pyart.graph.radardisplay.RadarDisplay` (*radar*, *shift*=(0.0, 0.0))

Bases: `object`

A display object for creating plots from data in a radar object.

Parameters

radar [Radar] Radar object to use for creating plots.

shift [(float, float)] Shifts in km to offset the calculated x and y locations.

Attributes

plots [list] List of plots created.

plot_vars [list] List of fields plotted, order matches plot list.

cbs [list] List of colorbars created.

origin [str] 'Origin' or 'Radar'.

shift [(float, float)] Shift in meters.

loc [(float, float)] Latitude and Longitude of radar in degrees.

fields [dict] Radar fields.

scan_type [str] Scan type.

ranges [array] Gate ranges in meters.

azimuths [array] Azimuth angle in degrees.

elevations [array] Elevations in degrees.

fixed_angle [array] Scan angle in degrees.

antenna_transition [array or None] Antenna transition flag (1 in transition, 0 in transition) or None if no antenna transition.

Methods

<code>generate_az_rhi_title(self, field, azimuth)</code>	Generate a title for a ray plot.
<code>generate_filename(self, field, sweep[, ext, ...])</code>	Generate a filename for a plot.
<code>generate_ray_title(self, field, ray)</code>	Generate a title for a ray plot.
<code>generate_title(self, field, sweep[, ...])</code>	Generate a title for a plot.
<code>generate_vpt_title(self, field)</code>	Generate a title for a VPT plot.
<code>label_xaxis_r(self[, ax])</code>	Label the xaxis with the default label for r units.
<code>label_xaxis_rays([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_time([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_x(self[, ax])</code>	Label the xaxis with the default label for x units.
<code>label_yaxis_field(self, field[, ax])</code>	Label the yaxis with the default label for a field units.
<code>label_yaxis_y(self[, ax])</code>	Label the yaxis with the default label for y units.
<code>label_yaxis_z(self[, ax])</code>	Label the yaxis with the default label for z units.
<code>plot(self, field[, sweep])</code>	Create a plot appropriate for the radar.
<code>plot_azimuth_to_rhi(self, field, target_azimuth)</code>	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<code>plot_colorbar(self[, mappable, field, ...])</code>	Plot a colorbar.
<code>plot_cross_hair(size[, npts, ax])</code>	Plot a cross-hair on a ppi plot.
<code>plot_grid_lines([ax, col, ls])</code>	Plot grid lines.
<code>plot_label(self, label, location[, symbol, ...])</code>	Plot a single symbol and label at a given location.
<code>plot_labels(self, labels, locations[, ...])</code>	Plot symbols and labels at given locations.
<code>plot_ppi(self, field[, sweep, mask_tuple, ...])</code>	Plot a PPI.
<code>plot_range_ring(range_ring_location_km[, ...])</code>	Plot a single range ring.
<code>plot_range_rings(self, range_rings[, ax, ...])</code>	Plot a series of range rings.
<code>plot_ray(self, field, ray[, format_str, ...])</code>	Plot a single ray.
<code>plot_rhi(self, field[, sweep, mask_tuple, ...])</code>	Plot a RHI.
<code>plot_vpt(self, field[, mask_tuple, vmin, ...])</code>	Plot a VPT scan.
<code>set_aspect_ratio([aspect_ratio, ax])</code>	Set the aspect ratio for plot area.
<code>set_limits([xlim, ylim, ax])</code>	Set the display limits.

__class__

alias of `builtins.type`

__delattr__ (*self, name, /*)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.graph.radardisplay', '__doc__': '\n A`

__dir__ (*self, /*)

Default `dir()` implementation.

__eq__ (*self, value, /*)

Return `self==value`.

__format__ (*self, format_spec, /*)

Default object formatter.

__ge__ (*self, value, /*)

Return `self>=value`.

__getattr__ (*self, name, /*)

Return `getattr(self, name)`.

__gt__ (*self, value, /*)

Return `self>value`.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, *radar*, *shift*=(0.0, 0.0))
Initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.graph.radardisplay'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__get_azimuth_rhi_data_x_y_z (*self*, *field*, *target_azimuth*, *edges*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return pseudo-RHI data from a plot function.

__get_colorbar_label (*self*, *field*)
Return a colorbar label for a given field.

__get_data (*self*, *field*, *sweep*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return data from a plot function.

__get_ray_data (*self*, *field*, *ray*, *mask_tuple*, *gatefilter*)
Retrieve and return ray data from a plot function.

`_get_vpt_data` (*self, field, mask_tuple, filter_transitions, gatefilter*)
Retrieve and return vpt data from a plot function.

`_get_x_y` (*self, sweep, edges, filter_transitions*)
Retrieve and return x and y coordinate in km.

`_get_x_y_z` (*self, sweep, edges, filter_transitions*)
Retrieve and return x, y, and z coordinate in km.

`_get_x_z` (*self, sweep, edges, filter_transitions*)
Retrieve and return x and z coordinate in km.

`_label_axes_ppi` (*self, axis_labels, ax*)
Set the x and y axis labels for a PPI plot.

`_label_axes_ray` (*self, axis_labels, field, ax*)
Set the x and y axis labels for a ray plot.

`_label_axes_rhi` (*self, axis_labels, ax*)
Set the x and y axis labels for a RHI plot.

`_label_axes_vpt` (*self, axis_labels, time_axis_flag, ax*)
Set the x and y axis labels for a PPI plot.

`_set_az_rhi_title` (*self, field, azimuth, title, ax*)
Set the figure title for a ray plot using a default title.

`_set_ray_title` (*self, field, ray, title, ax*)
Set the figure title for a ray plot using a default title.

`_set_title` (*self, field, sweep, title, ax, datetime_format=None, use_sweep_time=True*)
Set the figure title using a default title.

`static _set_vpt_time_axis` (*ax, date_time_form=None, tz=None*)
Set the x axis as a time formatted axis.

Parameters

ax [Matplotlib axis instance] Axis to plot. None will use the current axis.

date_time_form [str] Format of the time string for x-axis labels.

tz [str] Time zone info to use when creating axis labels (see datetime).

`_set_vpt_title` (*self, field, title, ax*)
Set the figure title using a default title.

`generate_az_rhi_title` (*self, field, azimuth*)
Generate a title for a ray plot.

Parameters

field [str] Field plotted.

azimuth [float] Azimuth plotted.

Returns

title [str] Plot title.

`generate_filename` (*self, field, sweep, ext='png', datetime_format='%Y%m%d%H%M%S', use_sweep_time=False*)
Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

ext [str] Filename extension.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

filename [str] Filename suitable for saving a plot.

generate_ray_title (*self*, *field*, *ray*)

Generate a title for a ray plot.

Parameters

field [str] Field plotted.

ray [int] Ray plotted.

Returns

title [str] Plot title.

generate_title (*self*, *field*, *sweep*, *datetime_format=None*, *use_sweep_time=True*)

Generate a title for a plot.

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

title [str] Plot title.

generate_vpt_title (*self*, *field*)

Generate a title for a VPT plot.

Parameters

field [str] Field plotted.

Returns

title [str] Plot title.

label_xaxis_r (*self*, *ax=None*)

Label the xaxis with the default label for r units.

static label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

static label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*self*, *ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*self*, *field*, *ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*self*, *ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*self*, *ax=None*)

Label the yaxis with the default label for z units.

plot (*self*, *field*, *sweep=0*, ***kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the *scan_type* of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters

field [str] Field to plot.

sweep [int] Sweep number to plot, not used for VPT scans.

See also:

plot_ppi Plot a PPI scan

plot_rhi Plot a RHI scan

plot_vpt Plot a VPT scan

plot_azimuth_to_rhi (*self*, *field*, *target_azimuth*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *reverse_xaxis=None*, *filter_transitions=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's *pcolormesh* function.

Parameters

field [str] Field to plot.

target_azimuth [integer] Azimuthal angle in degrees where cross section will be taken.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the *vmax* and *vmin* parameters are ignored. If None, *vmin* and *vmax* are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to True to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*self*, *mappable=None*, *field=None*, *label=None*, *orient='vertical'*, *cax=None*,
ax=None, *fig=None*, *ticks=None*, *ticklabs=None*)

Plot a colorbar.

Parameters

mappable [Image, ContourSet, etc.] Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field [str] Field to label colorbar with.

label [str] Colorbar label. None will use a default value from the last field plotted.

orient [str] Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax [Axis] Axis onto which the colorbar will be drawn. None is also valid.

ax [Axes] Axis onto which the colorbar will be drawn. None is also valid.

fig [Figure] Figure to place colorbar on. None will use the current figure.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

static plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters

size [float] Size of cross-hair in km.

npts: int Number of points in the cross-hair, higher for better resolution.

ax [Axis] Axis to plot on. None will use the current axis.

static plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for grid lines.

ls [str] Linestyle to use for grid lines.

plot_label (*self, label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters

label [str] Label text to place just above symbol.

location [2-tuples] Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol [str] Matplotlib color+marker strings defining the symbol to place at the given location.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

plot_labels (*self, labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters

labels [list of str] List of labels to place just above symbols.

locations [list of 2-tuples] List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols [list of str or str] List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

```
plot_ppi (self, field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None,
          cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None,
          None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, color-
          bar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None,
          fig=None, ticks=None, ticklabs=None, raster=False, title_datetime_format=None, ti-
          tle_use_sweep_time=True, **kwargs)
```

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int, optional] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static plot_range_ring (*range_ring_location_km*, *npts=100*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)
Plot a single range ring.

Parameters

range_ring_location_km [float] Location of range ring in km.

npts: int Number of points in the ring, higher for better resolution.

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for range rings.

ls [str] Linestyle to use for range rings.

plot_range_rings (*self*, *range_rings*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)
Plot a series of range rings.

Parameters

range_rings [list] List of locations in km to draw range rings.

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for range rings.

ls [str] Linestyle to use for range rings.

plot_ray (*self*, *field*, *ray*, *format_str='k-'*, *mask_tuple=None*, *ray_min=None*, *ray_max=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *gatefilter=None*, *axislabels_flag=True*, *ax=None*, *fig=None*)
Plot a single ray.

Parameters

field [str] Field to plot.

ray [int] Ray number to plot.

Other Parameters

format_str [str] Format string defining the line style and marker.

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min [float] Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max [float] Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

plot_rhi (*self, field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_xaxis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, title_datetime_format=None, title_use_sweep_time=True, **kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int,] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*self*, *field*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *filter_transitions=True*, *time_axis_flag=False*, *date_time_form=None*, *tz=None*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag [bool] True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form [str, optional] Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz [str, optional] Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

static set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters

xlim [tuple, optional] 2-Tuple containing y-axis limits in km. None uses default limits.

ylim [tuple, optional] 2-Tuple containing x-axis limits in km. None uses default limits.

ax [Axis] Axis to adjust. None will adjust the current axis.

`pyart.graph.radardisplay._mask_outside` (*flag, data, v1, v2*)

Return the data masked outside of `v1` and `v2` when `flag` is True.

PYART.GRAPH.RADARDISPLAY_AIRBORNE

Class for creating plots from Airborne Radar objects.

<i>AirborneRadarDisplay</i> (radar[, shift])	A display object for creating plots from data in a airborne radar object.
--	---

```
class pyart.graph.radardisplay_airborne.AirborneRadarDisplay (radar,  shift=(0.0,  
                                                                0.0))
```

Bases: *pyart.graph.radardisplay.RadarDisplay*

A display object for creating plots from data in a airborne radar object.

Parameters

radar [Radar] Radar object to use for creating plots, should be an airborne radar.

shift [(float, float)] Shifts in km to offset the calculated x and y locations.

Attributes

plots [list] List of plots created.

plot_vars [list] List of fields plotted, order matches plot list.

cbs [list] List of colorbars created.

origin [str] 'Origin' or 'Radar'.

shift [(float, float)] Shift in meters.

loc [(float, float)] Latitude and Longitude of radar in degrees.

fields [dict] Radar fields.

scan_type [str] Scan type.

ranges [array] Gate ranges in meters.

azimuths [array] Azimuth angle in degrees.

elevations [array] Elevations in degrees.

fixed_angle [array] Scan angle in degrees.

rotation [array] Rotation angle in degrees.

roll [array] Roll angle in degrees.

drift [array] Drift angle in degrees.

tilt [array] Tilt angle in degrees.

heading [array] Heading angle in degrees.

pitch [array] Pitch angle in degrees.

altitude [array] Altitude angle in meters.

Methods

<i>generate_az_rhi_title</i> (self, field, azimuth)	Generate a title for a ray plot.
<i>generate_filename</i> (self, field, sweep[, ext, ...])	Generate a filename for a plot.
<i>generate_ray_title</i> (self, field, ray)	Generate a title for a ray plot.
<i>generate_title</i> (self, field, sweep[, ...])	Generate a title for a plot.
<i>generate_vpt_title</i> (self, field)	Generate a title for a VPT plot.
<i>label_xaxis_r</i> (self[, ax])	Label the xaxis with the default label for r units.
<i>label_xaxis_rays</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_time</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_x</i> (self[, ax])	Label the xaxis with the default label for x units.
<i>label_yaxis_field</i> (self, field[, ax])	Label the yaxis with the default label for a field units.
<i>label_yaxis_y</i> (self[, ax])	Label the yaxis with the default label for y units.
<i>label_yaxis_z</i> (self[, ax])	Label the yaxis with the default label for z units.
<i>plot</i> (self, field[, sweep])	Create a plot appropriate for the radar.
<i>plot_azimuth_to_rhi</i> (self, field, target_azimuth)	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<i>plot_colorbar</i> (self[, mappable, field, ...])	Plot a colorbar.
<i>plot_cross_hair</i> (size[, npts, ax])	Plot a cross-hair on a ppi plot.
<i>plot_grid_lines</i> ([ax, col, ls])	Plot grid lines.
<i>plot_label</i> (self, label, location[, symbol, ...])	Plot a single symbol and label at a given location.
<i>plot_labels</i> (self, labels, locations[, ...])	Plot symbols and labels at given locations.
<i>plot_ppi</i> (self, field[, sweep, mask_tuple, ...])	Plot a PPI.
<i>plot_range_ring</i> (range_ring_location_km[, ...])	Plot a single range ring.
<i>plot_range_rings</i> (self, range_rings[, ax, ...])	Plot a series of range rings.
<i>plot_ray</i> (self, field, ray[, format_str, ...])	Plot a single ray.
<i>plot_rhi</i> (self, field[, sweep, mask_tuple, ...])	Plot a RHI.
<i>plot_sweep_grid</i> (self, field[, sweep, ...])	Plot a sweep as a grid.
<i>plot_vpt</i> (self, field[, mask_tuple, vmin, ...])	Plot a VPT scan.
<i>set_aspect_ratio</i> ([aspect_ratio, ax])	Set the aspect ratio for plot area.
<i>set_limits</i> ([xlim, ylim, ax])	Set the display limits.

```
__class__
    alias of builtins.type
__delattr__(self, name, /)
    Implement delattr(self, name).
__dict__ = mappingproxy({'__module__': 'pyart.graph.radardisplay_airborne', '__doc__'
__dir__(self, /)
    Default dir() implementation.
__eq__(self, value, /)
    Return self==value.
__format__(self, format_spec, /)
```

Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, radar, shift=(0.0, 0.0)*)
Initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyart.graph.radardisplay_airborne'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

`_get_azimuth_rhi_data_x_y_z` (*self, field, target_azimuth, edges, mask_tuple, filter_transitions, gatefilter*)

Retrieve and return pseudo-RHI data from a plot function.

`_get_colorbar_label` (*self, field*)

Return a colorbar label for a given field.

`_get_data` (*self, field, sweep, mask_tuple, filter_transitions, gatefilter*)

Retrieve and return data from a plot function.

`_get_ray_data` (*self, field, ray, mask_tuple, gatefilter*)

Retrieve and return ray data from a plot function.

`_get_vpt_data` (*self, field, mask_tuple, filter_transitions, gatefilter*)

Retrieve and return vpt data from a plot function.

`_get_x_y` (*self, sweep, edges, filter_transitions*)

Retrieve and return x and y coordinate in km.

`_get_x_y_z` (*self, sweep, edges, filter_transitions, ignoreTilt=False*)

Retrieve and return x, y, and z coordinate in km.

`_get_x_z` (*self, sweep, edges, filter_transitions, ignoreTilt=False*)

Retrieve and return x and z coordinate in km.

`_label_axes_ppi` (*self, axis_labels, ax*)

Set the x and y axis labels for a PPI plot.

`_label_axes_ray` (*self, axis_labels, field, ax*)

Set the x and y axis labels for a ray plot.

`_label_axes_rhi` (*self, axis_labels, ax*)

Set the x and y axis labels for a RHI plot.

`_label_axes_vpt` (*self, axis_labels, time_axis_flag, ax*)

Set the x and y axis labels for a PPI plot.

`_set_az_rhi_title` (*self, field, azimuth, title, ax*)

Set the figure title for a ray plot using a default title.

`_set_ray_title` (*self, field, ray, title, ax*)

Set the figure title for a ray plot using a default title.

`_set_title` (*self, field, sweep, title, ax, datetime_format=None, use_sweep_time=True*)

Set the figure title using a default title.

`static _set_vpt_time_axis` (*ax, date_time_form=None, tz=None*)

Set the x axis as a time formatted axis.

Parameters

`ax` [Matplotlib axis instance] Axis to plot. None will use the current axis.

`date_time_form` [str] Format of the time string for x-axis labels.

`tz` [str] Time zone info to use when creating axis labels (see datetime).

`_set_vpt_title` (*self, field, title, ax*)

Set the figure title using a default title.

`generate_az_rhi_title` (*self, field, azimuth*)

Generate a title for a ray plot.

Parameters

`field` [str] Field plotted.

azimuth [float] Azimuth plotted.

Returns

title [str] Plot title.

generate_filename (*self*, *field*, *sweep*, *ext*='png', *datetime_format*='%Y%m%d%H%M%S',
use_sweep_time=False)

Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

ext [str] Filename extension.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

filename [str] Filename suitable for saving a plot.

generate_ray_title (*self*, *field*, *ray*)

Generate a title for a ray plot.

Parameters

field [str] Field plotted.

ray [int] Ray plotted.

Returns

title [str] Plot title.

generate_title (*self*, *field*, *sweep*, *datetime_format*=None, *use_sweep_time*=True)

Generate a title for a plot.

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

title [str] Plot title.

generate_vpt_title (*self*, *field*)

Generate a title for a VPT plot.

Parameters

field [str] Field plotted.

Returns

title [str] Plot title.

label_xaxis_r (*self*, *ax=None*)

Label the xaxis with the default label for r units.

static label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

static label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*self*, *ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*self*, *field*, *ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*self*, *ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*self*, *ax=None*)

Label the yaxis with the default label for z units.

plot (*self*, *field*, *sweep=0*, ***kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the *scan_type* of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters

field [str] Field to plot.

sweep [int] Sweep number to plot, not used for VPT scans.

See also:

plot_ppi Plot a PPI scan

plot_sweep_grid Plot a RHI or VPT scan

plot_azimuth_to_rhi (*self*, *field*, *target_azimuth*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *reverse_xaxis=None*, *filter_transitions=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's *pcolormesh* function.

Parameters

field [str] Field to plot.

target_azimuth [integer] Azimuthal angle in degrees where cross section will be taken.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to True to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*self*, *mappable=None*, *field=None*, *label=None*, *orient='vertical'*, *cax=None*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*)

Plot a colorbar.

Parameters

mappable [Image, ContourSet, etc.] Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field [str] Field to label colorbar with.

label [str] Colorbar label. None will use a default value from the last field plotted.

orient [str] Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax [Axis] Axis onto which the colorbar will be drawn. None is also valid.

ax [Axes] Axis onto which the colorbar will be drawn. None is also valid.

fig [Figure] Figure to place colorbar on. None will use the current figure.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

static plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters

size [float] Size of cross-hair in km.

npts: int Number of points in the cross-hair, higher for better resolution.

ax [Axis] Axis to plot on. None will use the current axis.

static plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for grid lines.

ls [str] Linestyle to use for grid lines.

plot_label (*self, label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters

label [str] Label text to place just above symbol.

location [2-tuples] Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol [str] Matplotlib color+marker strings defining the symbol to place at the given location.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

plot_labels (*self, labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters

labels [list of str] List of labels to place just above symbols.

locations [list of 2-tuples] List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols [list of str or str] List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

plot_ppi (*self*, *field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=False, *title_datetime_format*=None, *title_use_sweep_time*=True, ***kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int, optional] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static plot_range_ring (*range_ring_location_km*, *npts=100*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a single range ring.

Parameters

range_ring_location_km [float] Location of range ring in km.

npts: int Number of points in the ring, higher for better resolution.

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for range rings.

ls [str] Linestyle to use for range rings.

plot_range_rings (*self*, *range_rings*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a series of range rings.

Parameters

range_rings [list] List of locations in km to draw range rings.

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for range rings.

ls [str] Linestyle to use for range rings.

plot_ray (*self*, *field*, *ray*, *format_str='k-'*, *mask_tuple=None*, *ray_min=None*, *ray_max=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *gatefilter=None*, *axislabels_flag=True*, *ax=None*, *fig=None*)

Plot a single ray.

Parameters

field [str] Field to plot.

ray [int] Ray number to plot.

Other Parameters

format_str [str] Format string defining the line style and marker.

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min [float] Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max [float] Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

plot_rhi (*self, field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_xaxis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, title_datetime_format=None, title_use_sweep_time=True, **kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int,] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

```
plot_sweep_grid(self, field, sweep=0, ignoreTilt=False, mask_tuple=None, vmin=None,
                 vmax=None, cmap=None, norm=None, mask_outside=False, title=None,
                 title_flag=True, axislabels=(None, None), axislabels_flag=True, color-
                 bar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True,
                 filter_transitions=True, ax=None, fig=None, gatefilter=None, raster=False,
                 ticks=None, ticklabs=None, **kwargs)
```

Plot a sweep as a grid.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int, optional] Sweep number to plot.

Other Parameters

ignoreTilt [bool] True to ignore tilt angle when running the antenna_to_cartesian_track_relative coordinate transformation (by setting tilt angle to 0), effectively plotting data relative to slant range (the same plotting method utilized by the NCAR soloii/3 software). False (default) plots relative to the aircraft longitudinal axis.

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

plot_vpt (*self*, *field*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *filter_transitions=True*, *time_axis_flag=False*, *date_time_form=None*, *tz=None*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag [bool] True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form [str, optional] Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz [str, optional] Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

static set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters

xlim [tuple, optional] 2-Tuple containing y-axis limits in km. None uses default limits.

ylim [tuple, optional] 2-Tuple containing x-axis limits in km. None uses default limits.

ax [Axis] Axis to adjust. None will adjust the current axis.

PYART.GRAPH.RADARMAPDISPLAY

Class for creating plots on a geographic map using a Radar object using Cartopy for drawing maps.

<i>RadarMapDisplay</i> (radar[, shift, grid_projection])	A display object for creating plots on a geographic map from data in a Radar object.
--	--

```
class pyart.graph.radarmapdisplay.RadarMapDisplay (radar,          shift=(0.0,      0.0),
                                                    grid_projection=None)
```

Bases: *pyart.graph.radardisplay.RadarDisplay*

A display object for creating plots on a geographic map from data in a Radar object.

This class is still a work in progress. Some functionality may not work correctly. Please report any problems to the Py-ART GitHub Issue Tracker.

Parameters

radar [Radar] Radar object to use for creating plots.

shift [(float, float)] Shifts in km to offset the calculated x and y locations.

Attributes

plots [list] List of plots created.

plot_vars [list] List of fields plotted, order matches plot list.

cbs [list] List of colorbars created.

origin [str] 'Origin' or 'Radar'.

shift [(float, float)] Shift in meters.

loc [(float, float)] Latitude and Longitude of radar in degrees.

fields [dict] Radar fields.

scan_type [str] Scan type.

ranges [array] Gate ranges in meters.

azimuths [array] Azimuth angle in degrees.

elevations [array] Elevations in degrees.

fixed_angle [array] Scan angle in degrees.

grid_projection [cartopy.crs] AzimuthalEquidistant cartopy projection centered on radar. Used to transform points into map projection.

Methods

<i>generate_az_rhi_title</i> (self, field, azimuth)	Generate a title for a ray plot.
<i>generate_filename</i> (self, field, sweep[, ext, ...])	Generate a filename for a plot.
<i>generate_ray_title</i> (self, field, ray)	Generate a title for a ray plot.
<i>generate_title</i> (self, field, sweep[, ...])	Generate a title for a plot.
<i>generate_vpt_title</i> (self, field)	Generate a title for a VPT plot.
<i>label_xaxis_r</i> (self[, ax])	Label the xaxis with the default label for r units.
<i>label_xaxis_rays</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_time</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_x</i> (self[, ax])	Label the xaxis with the default label for x units.
<i>label_yaxis_field</i> (self, field[, ax])	Label the yaxis with the default label for a field units.
<i>label_yaxis_y</i> (self[, ax])	Label the yaxis with the default label for y units.
<i>label_yaxis_z</i> (self[, ax])	Label the yaxis with the default label for z units.
<i>plot</i> (self, field[, sweep])	Create a plot appropriate for the radar.
<i>plot_azimuth_to_rhi</i> (self, field, target_azimuth)	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<i>plot_colorbar</i> (self[, mappable, field, ...])	Plot a colorbar.
<i>plot_cross_hair</i> (size[, npts, ax])	Plot a cross-hair on a ppi plot.
<i>plot_grid_lines</i> ([ax, col, ls])	Plot grid lines.
<i>plot_label</i> (self, label, location[, symbol, ...])	Plot a single symbol and label at a given location.
<i>plot_labels</i> (self, labels, locations[, ...])	Plot symbols and labels at given locations.
<i>plot_line_geo</i> (self, line_lons, line_lats[, ...])	Plot a line segments on the current map given values in lat and lon.
<i>plot_line_xy</i> (self, line_x, line_y[, line_style])	Plot a line segments on the current map given radar x, y values.
<i>plot_point</i> (self, lon, lat[, symbol, ...])	Plot a point on the current map.
<i>plot_ppi</i> (self, field[, sweep, mask_tuple, ...])	Plot a PPI.
<i>plot_ppi_map</i> (self, field[, sweep, ...])	Plot a PPI volume sweep onto a geographic map.
<i>plot_range_ring</i> (self, range_ring_location_km)	Plot a single range ring on the map.
<i>plot_range_rings</i> (self, range_rings[, ax, ...])	Plot a series of range rings.
<i>plot_ray</i> (self, field, ray[, format_str, ...])	Plot a single ray.
<i>plot_rhi</i> (self, field[, sweep, mask_tuple, ...])	Plot a RHI.
<i>plot_vpt</i> (self, field[, mask_tuple, vmin, ...])	Plot a VPT scan.
<i>set_aspect_ratio</i> ([aspect_ratio, ax])	Set the aspect ratio for plot area.
<i>set_limits</i> ([xlim, ylim, ax])	Set the display limits.

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.graph.radarmapdisplay', '__doc__': '\n`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self*, *value*, /)
Return self>=value.

__getattr__ (*self*, *name*, /)
Return getattr(self, name).

__gt__ (*self*, *value*, /)
Return self>value.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, *radar*, *shift*=(0.0, 0.0), *grid_projection*=None)
Initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.graph.radarmapdisplay'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

`_check_ax` (*self*)
Check that a GeoAxes object exists, raise ValueError if not

`_get_azimuth_rhi_data_x_y_z` (*self, field, target_azimuth, edges, mask_tuple, filter_transitions, gatefilter*)
Retrieve and return pseudo-RHI data from a plot function.

`_get_colorbar_label` (*self, field*)
Return a colorbar label for a given field.

`_get_data` (*self, field, sweep, mask_tuple, filter_transitions, gatefilter*)
Retrieve and return data from a plot function.

`_get_ray_data` (*self, field, ray, mask_tuple, gatefilter*)
Retrieve and return ray data from a plot function.

`_get_vpt_data` (*self, field, mask_tuple, filter_transitions, gatefilter*)
Retrieve and return vpt data from a plot function.

`_get_x_y` (*self, sweep, edges, filter_transitions*)
Retrieve and return x and y coordinate in km.

`_get_x_y_z` (*self, sweep, edges, filter_transitions*)
Retrieve and return x, y, and z coordinate in km.

`_get_x_z` (*self, sweep, edges, filter_transitions*)
Retrieve and return x and z coordinate in km.

`_label_axes_ppi` (*self, axis_labels, ax*)
Set the x and y axis labels for a PPI plot.

`_label_axes_ray` (*self, axis_labels, field, ax*)
Set the x and y axis labels for a ray plot.

`_label_axes_rhi` (*self, axis_labels, ax*)
Set the x and y axis labels for a RHI plot.

`_label_axes_vpt` (*self, axis_labels, time_axis_flag, ax*)
Set the x and y axis labels for a PPI plot.

`_set_az_rhi_title` (*self, field, azimuth, title, ax*)
Set the figure title for a ray plot using a default title.

`_set_ray_title` (*self, field, ray, title, ax*)
Set the figure title for a ray plot using a default title.

`_set_title` (*self, field, sweep, title, ax, datetime_format=None, use_sweep_time=True*)
Set the figure title using a default title.

`static _set_vpt_time_axis` (*ax, date_time_form=None, tz=None*)
Set the x axis as a time formatted axis.

Parameters

`ax` [Matplotlib axis instance] Axis to plot. None will use the current axis.

`date_time_form` [str] Format of the time string for x-axis labels.

`tz` [str] Time zone info to use when creating axis labels (see datetime).

`_set_vpt_title` (*self, field, title, ax*)
Set the figure title using a default title.

`generate_az_rhi_title` (*self, field, azimuth*)
Generate a title for a ray plot.

Parameters

field [str] Field plotted.

azimuth [float] Azimuth plotted.

Returns

title [str] Plot title.

generate_filename (*self*, *field*, *sweep*, *ext*='png', *datetime_format*='%Y%m%d%H%M%S',
use_sweep_time=False)

Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

ext [str] Filename extension.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

filename [str] Filename suitable for saving a plot.

generate_ray_title (*self*, *field*, *ray*)

Generate a title for a ray plot.

Parameters

field [str] Field plotted.

ray [int] Ray plotted.

Returns

title [str] Plot title.

generate_title (*self*, *field*, *sweep*, *datetime_format*=None, *use_sweep_time*=True)

Generate a title for a plot.

Parameters

field [str] Field plotted.

sweep [int] Sweep plotted.

datetime_format [str] Format of datetime (using strftime format).

use_sweep_time [bool] If true, the current sweep's beginning time is used.

Returns

title [str] Plot title.

generate_vpt_title (*self*, *field*)

Generate a title for a VPT plot.

Parameters

field [str] Field plotted.

Returns

title [str] Plot title.

label_xaxis_r (*self*, *ax=None*)

Label the xaxis with the default label for r units.

static label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

static label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*self*, *ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*self*, *field*, *ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*self*, *ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*self*, *ax=None*)

Label the yaxis with the default label for z units.

plot (*self*, *field*, *sweep=0*, ***kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the `scan_type` of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters

field [str] Field to plot.

sweep [int] Sweep number to plot, not used for VPT scans.

See also:

plot_ppi Plot a PPI scan

plot_rhi Plot a RHI scan

plot_vpt Plot a VPT scan

plot_azimuth_to_rhi (*self*, *field*, *target_azimuth*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *reverse_xaxis=None*, *filter_transitions=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters

field [str] Field to plot.

target_azimuth [integer] Azimuthal angle in degrees where cross section will be taken.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to True to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*self*, *mappable=None*, *field=None*, *label=None*, *orient='vertical'*, *cax=None*,
ax=None, *fig=None*, *ticks=None*, *ticklabs=None*)

Plot a colorbar.

Parameters

mappable [Image, ContourSet, etc.] Image, ContourSet, etc to which the colorbar applied.
If None the last mappable object will be used.

field [str] Field to label colorbar with.

label [str] Colorbar label. None will use a default value from the last field plotted.

orient [str] Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax [Axis] Axis onto which the colorbar will be drawn. None is also valid.

ax [Axes] Axis onto which the colorbar will be drawn. None is also valid.

fig [Figure] Figure to place colorbar on. None will use the current figure.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

static plot_cross_hair (*size*, *npts=100*, *ax=None*)

Plot a cross-hair on a ppi plot.

Parameters

size [float] Size of cross-hair in km.

npts: **int** Number of points in the cross-hair, higher for better resolution.

ax [Axis] Axis to plot on. None will use the current axis.

static plot_grid_lines (*ax=None*, *col='k'*, *ls=':'*)

Plot grid lines.

Parameters

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for grid lines.

ls [str] Linestyle to use for grid lines.

plot_label (*self*, *label*, *location*, *symbol='r+'*, *text_color='k'*, *ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters

label [str] Label text to place just above symbol.

location [2-tuples] Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol [str] Matplotlib color+marker strings defining the symbol to place at the given location.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

plot_labels (*self*, *labels*, *locations*, *symbols='r+'*, *text_color='k'*, *ax=None*)

Plot symbols and labels at given locations.

Parameters

labels [list of str] List of labels to place just above symbols.

locations [list of 2-tuples] List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols [list of str or str] List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color [str] Matplotlib color defining the color of the label text.

ax [Axis] Axis to plot on. None will use the current axis.

plot_line_geo (*self*, *line_lons*, *line_lats*, *line_style*='r-', ***kwargs*)

Plot a line segments on the current map given values in lat and lon.

Additional arguments are passed to ax.plot.

Parameters

line_lons [array] Longitude of line segment to plot.

line_lats [array] Latitude of line segment to plot.

line_style [str] Matplotlib compatible string which specifies the line style.

plot_line_xy (*self*, *line_x*, *line_y*, *line_style*='r-', ***kwargs*)

Plot a line segments on the current map given radar x, y values.

Additional arguments are passed to ax.plot.

Parameters

line_x [array] X location of points to plot in meters from the radar.

line_y [array] Y location of points to plot in meters from the radar.

line_style [str, optional] Matplotlib compatible string which specifies the line style.

plot_point (*self*, *lon*, *lat*, *symbol*='ro', *label_text*=None, *label_offset*=(None, None), ***kwargs*)

Plot a point on the current map.

Additional arguments are passed to ax.plot.

Parameters

lon [float] Longitude of point to plot.

lat [float] Latitude of point to plot.

symbol [str] Matplotlib compatible string which specified the symbol of the point.

label_text [str, optional.] Text to label symbol with. If None no label will be added.

label_offset [[float, float]] Offset in lon, lat degrees for the bottom left corner of the label text relative to the point. A value of None will use 0.01.

plot_ppi (*self*, *field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=False, *title_datetime_format*=None, *title_use_sweep_time*=True, ***kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int, optional] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

```
plot_ppi_map(self, field, sweep=0, mask_tuple=None, vmin=None, vmax=None, cmap=None,
               norm=None, mask_outside=False, title=None, title_flag=True, colorbar_flag=True,
               colorbar_label=None, ax=None, fig=None, lat_lines=None, lon_lines=None, pro-
               jection=None, min_lon=None, max_lon=None, min_lat=None, max_lat=None,
               width=None, height=None, lon_0=None, lat_0=None, resolution='110m',
               shapefile=None, shapefile_kwargs=None, edges=True, gatefilter=None, fil-
               ter_transitions=True, embellish=True, maps_list=['countries', 'coastlines'],
               raster=False, ticks=None, ticklabs=None, alpha=None, background_zoom=8)
```

Plot a PPI volume sweep onto a geographic map.

Parameters

field [str] Field to plot.

sweep [int, optional] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and tilt parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ax [Cartopy GeoAxes instance] If None, create GeoAxes instance using other keyword info. If provided, ax must have a Cartopy crs projection and projection kwarg below is ignored.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

lat_lines, lon_lines [array or None] Locations at which to draw latitude and longitude lines. None will use default values which are reasonable for maps of North America.

projection [cartopy.crs class] Map projection supported by cartopy. Used for all subsequent calls to the GeoAxes object generated. Defaults to LambertConformal centered on radar.

min_lat, max_lat, min_lon, max_lon [float] Latitude and longitude ranges for the map projection region in degrees.

width, height [float] Width and height of map domain in meters. Only this set of parameters or the previous set of parameters (min_lat, max_lat, min_lon, max_lon) should be specified. If neither set is specified then the map domain will be determined from the extend of the radar gate locations.

shapefile [str] Filename for a shapefile to add to map.

shapefile_kwargs [dict] Key word arguments used to format shapefile. Projection defaults to lat lon (cartopy.crs.PlateCarree())

resolution ['10m', '50m', '110m'.] Resolution of NaturalEarthFeatures to use. See Cartopy documentation for details.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

embelish: bool True by default. Set to False to suppress drawing of coastlines etc.. Use for speedup when specifying shapefiles. Note that lat lon labels only work with certain projections.

maps_list: list of strings if embelish is true the list of maps to use. default countries, coastlines

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

alpha [float or None] Set the alpha transparency of the radar plot. Useful for overplotting radar over other datasets.

background_zoom [int] Zoom of the background image. A highest number provides more detail at the cost of processing speed

plot_range_ring (*self*, *range_ring_location_km*, *npts=360*, *line_style='k'*, ***kwargs*)

Plot a single range ring on the map.

Additional arguments are passed to ax.plot.

Parameters

range_ring_location_km [float] Location of range ring in km.

npts [int] Number of points in the ring, higher for better resolution.

line_style [str] Matplotlib compatible string which specified the line style of the ring.

plot_range_rings (*self, range_rings, ax=None, col='k', ls='-', lw=2*)

Plot a series of range rings.

Parameters

range_rings [list] List of locations in km to draw range rings.

ax [Axis] Axis to plot on. None will use the current axis.

col [str or value] Color to use for range rings.

ls [str] Linestyle to use for range rings.

plot_ray (*self, field, ray, format_str='k-', mask_tuple=None, ray_min=None, ray_max=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), gatefilter=None, axislabels_flag=True, ax=None, fig=None*)

Plot a single ray.

Parameters

field [str] Field to plot.

ray [int] Ray number to plot.

Other Parameters

format_str [str] Format string defining the line style and marker.

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min [float] Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max [float] Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

plot_rhi (*self, field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_xaxis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, title_datetime_format=None, title_use_sweep_time=True, **kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

sweep [int,] Sweep number to plot.

Other Parameters

mask_tuple [(str, float)] 2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_datetime_format [str] Format of datetime in the title (using strftime format).

title_use_sweep_time [bool] True for the current sweep's beginning time to be used for the title. False for the radar's beginning time.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

reverse_xaxis [bool or None] True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*self*, *field*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *filter_transitions=True*, *time_axis_flag=False*, *date_time_form=None*, *tz=None*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=False*, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters

field [str] Field to plot.

Other Parameters

mask_tuple [(str, float)] Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin [float] Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax [float] Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm [Normalize or None, optional] matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap [str or None] Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside [bool] True to mask data outside of vmin, vmax. False performs no masking.

title [str] Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag [bool] True to add a title to the plot, False does not add a title.

axislabels [(str, str)] 2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag [bool] True to add label the axes, False does not label the axes.

colorbar_flag [bool] True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label [str] Colorbar label, None will use a default label generated from the field information.

ticks [array] Colorbar custom tick label locations.

ticklabs [array] Colorbar custom tick labels.

colorbar_orient ['vertical' or 'horizontal'] Colorbar orientation.

edges [bool] True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter [GateFilter] GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions [bool] True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag [bool] True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form [str, optional] Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz [str, optional] Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax [Axis] Axis to plot on. None will use the current axis.

fig [Figure] Figure to add the colorbar to. None will use the current figure.

raster [bool] False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

static set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters

xlim [tuple, optional] 2-Tuple containing y-axis limits in km. None uses default limits.

ylim [tuple, optional] 2-Tuple containing x-axis limits in km. None uses default limits.

ax [Axis] Axis to adjust. None will adjust the current axis.

`pyart.graph.radarmapdisplay._add_populated_places` (*ax, resolution='10m'*)
adds populated places to a figure

Parameters

ax [axes object] The axes where to draw the populated places

resolution [str] the resolution of the natural earth data to use

Returns

ax [axes object] The axes where the data has been written

`pyart.graph.radarmapdisplay._lambert_ticks` (*ax, ticks, tick_location, line_constructor, tick_extractor*)
Get the tick locations and labels for a Lambert Conformal projection.

`pyart.graph.radarmapdisplay.find_side` (*ls*, *side*)

Given a shapely LineString which is assumed to be rectangular, return the line corresponding to a given side of the rectangle.

`pyart.graph.radarmapdisplay.lambert_xticks` (*ax*, *ticks*)

Draw ticks on the bottom x-axis of a Lambert Conformal projection.

`pyart.graph.radarmapdisplay.lambert_yticks` (*ax*, *ticks*)

Draw ticks on the left y-axis of a Lambert Conformal projection.

PYART.GRAPH._CM

Data for radar related colormaps.

PYART.CORRECT.FILTERS

Functions for creating gate filters (masks) which can be used it various corrections routines in Py-ART.

<code>moment_based_gate_filter(radar[, ncp_field, ...])</code>	Create a filter which removes undesired gates based on moments.
<code>moment_and_texture_based_gate_filter(radar[, ncp_field, ...])</code>	Create a filter which removes undesired gates based on texture of moments.
<code>birds_gate_filter(radar[, zdr_field, ...])</code>	Create a filter which removes data not suspected of being birds
<code>snr_based_gate_filter(radar[, snr_field, ...])</code>	Create a filter which removes undesired gates based on SNR.
<code>class_based_gate_filter(radar[, field, ...])</code>	Create a filter which removes undesired gates based on class values
<code>visibility_based_gate_filter(radar[, ...])</code>	Create a filter which removes undesired gates based on visibility.
<code>temp_based_gate_filter(radar[, temp_field, ...])</code>	Create a filter which removes undesired gates based on temperature.
<code>iso0_based_gate_filter(radar[, iso0_field, ...])</code>	Create a filter which removes undesired gates based height over the iso0.
<code>GateFilter(radar[, exclude_based])</code>	A class for building a boolean arrays for filtering gates based on a set of condition typically based on the values in the radar fields.

class `pyart.filters.gatefilter.GateFilter(radar, exclude_based=True)`

Bases: `object`

A class for building a boolean arrays for filtering gates based on a set of condition typically based on the values in the radar fields. These filter can be used in various algorithms and calculations within Py-ART.

See `pyart.correct.GateFilter.exclude_below()` for method parameter details.

Parameters

radar [Radar] Radar object from which gate filter will be build.

exclude_based [bool, optional] True, the default and suggested method, will begin with all gates included and then use the exclude methods to exclude gates based on conditions. False will begin with all gates excluded from which a set of gates to include should be set using the include methods.

Examples

```
>>> import pyart
>>> radar = pyart.io.read('radar_file.nc')
>>> gatefilter = pyart.correct.GateFilter(radar)
>>> gatefilter.exclude_below('reflectivity', 10)
>>> gatefilter.exclude_below('normalized_coherent_power', 0.75)
```

Attributes

gate_excluded [array, dtype=bool] Return a copy of the excluded gates.

gate_included [array, dtype=bool] Return a copy of the included gates.

Methods

<i>copy</i> (self)	Return a copy of the gatefilter.
<i>exclude_above</i> (self, field, value[, ...])	Exclude gates where a given field is above a given value.
<i>exclude_all</i> (self)	Exclude all gates.
<i>exclude_below</i> (self, field, value[, ...])	Exclude gates where a given field is below a given value.
<i>exclude_equal</i> (self, field, value[, ...])	Exclude gates where a given field is equal to a value.
<i>exclude_gates</i> (self, mask[, exclude_masked, op])	Exclude gates where a given mask is equal True.
<i>exclude_inside</i> (self, field, v1, v2[, ...])	Exclude gates where a given field is inside a given interval.
<i>exclude_invalid</i> (self, field[, ...])	Exclude gates where an invalid value occurs in a field (NaNs or infs).
<i>exclude_masked</i> (self, field[, exclude_masked, op])	Exclude gates where a given field is masked.
<i>exclude_none</i> (self)	Exclude no gates, include all gates.
<i>exclude_not_equal</i> (self, field, value[, ...])	Exclude gates where a given field is not equal to a value.
<i>exclude_outside</i> (self, field, v1, v2[, ...])	Exclude gates where a given field is outside a given interval.
<i>exclude_transition</i> (self[, trans_value, ...])	Exclude all gates in rays marked as in transition between sweeps.
<i>include_above</i> (self, field, value[, ...])	Include gates where a given field is above a given value.
<i>include_all</i> (self)	Include all gates.
<i>include_below</i> (self, field, value[, ...])	Include gates where a given field is below a given value.
<i>include_equal</i> (self, field, value[, ...])	Include gates where a given field is equal to a value.
<i>include_gates</i> (self, mask[, exclude_masked, op])	Include gates where a given mask is equal True.
<i>include_inside</i> (self, field, v1, v2[, ...])	Include gates where a given field is inside a given interval.
<i>include_none</i> (self)	Include no gates, exclude all gates.
<i>include_not_equal</i> (self, field, value[, ...])	Include gates where a given field is not equal to a value.

Continued on next page

Table 3 – continued from previous page

<i>include_not_masked</i> (self, field[, ...])	Include gates where a given field is not masked.
<i>include_not_transition</i> (self[, trans_value, ...])	Include all gates in rays not marked as in transition between sweeps.
<i>include_outside</i> (self, field, v1, v2[, ...])	Include gates where a given field is outside a given interval.
<i>include_valid</i> (self, field[, exclude_masked, op])	Include gates where a valid value occurs in a field (not NaN or inf).

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyart.filters.gatefilter', '__doc__': '\n A`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self*, *value*, /)

Return `self>=value`.

__getattr__ (*self*, *name*, /)

Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)

Return `self>value`.

__hash__ (*self*, /)

Return `hash(self)`.

__init__ (*self*, *radar*, *exclude_based=True*)

initialize

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)

Return `self<=value`.

__lt__ (*self*, *value*, /)

Return `self<value`.

__module__ = `'pyart.filters.gatefilter'`

__ne__ (*self*, *value*, /)

Return `self!=value`.

__new__ (*args, **kwargs)

Create and return a new object. See `help(type)` for accurate signature.

__reduce__ (*self*, /)

Helper for pickle.

__reduce_ex__ (*self, protocol, /*)

Helper for pickle.

__repr__ (*self, /*)

Return repr(self).

__setattr__ (*self, name, value, /*)

Implement setattr(self, name, value).

__sizeof__ (*self, /*)

Size of object in memory, in bytes.

__str__ (*self, /*)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

_get_fdata (*self, field*)

Check that the field exists and retrieve field data.

_merge (*self, marked, op, exclude_masked*)

Merge an array of marked gates with the exclude array.

copy (*self*)

Return a copy of the gatefilter.

exclude_above (*self, field, value, exclude_masked=True, op='or', inclusive=False*)

Exclude gates where a given field is above a given value.

exclude_all (*self*)

Exclude all gates.

exclude_below (*self, field, value, exclude_masked=True, op='or', inclusive=False*)

Exclude gates where a given field is below a given value.

Parameters

field [str] Name of field compared against the value.

value [float] Gates with a value below this value in the specified field will be marked for exclusion in the filter.

exclude_masked [bool, optional] True to filter masked values in the specified field if the data is a masked array, False to include any masked values.

op [{ 'and', 'or', 'new' }] Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

inclusive [bool] Indicates whether the specified value should also be excluded.

exclude_equal (*self*, *field*, *value*, *exclude_masked=True*, *op='or'*)
Exclude gates where a given field is equal to a value.

exclude_gates (*self*, *mask*, *exclude_masked=True*, *op='or'*)
Exclude gates where a given mask is equal True.

Parameters

mask [numpy array] Boolean numpy array with same shape as a field array.

exclude_masked [bool, optional] True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op [{ 'and', 'or', 'new' }] Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

exclude_inside (*self*, *field*, *v1*, *v2*, *exclude_masked=True*, *op='or'*, *inclusive=True*)
Exclude gates where a given field is inside a given interval.

exclude_invalid (*self*, *field*, *exclude_masked=True*, *op='or'*)
Exclude gates where an invalid value occurs in a field (NaNs or infs).

exclude_masked (*self*, *field*, *exclude_masked=True*, *op='or'*)
Exclude gates where a given field is masked.

exclude_none (*self*)
Exclude no gates, include all gates.

exclude_not_equal (*self*, *field*, *value*, *exclude_masked=True*, *op='or'*)
Exclude gates where a given field is not equal to a value.

exclude_outside (*self*, *field*, *v1*, *v2*, *exclude_masked=True*, *op='or'*, *inclusive=False*)
Exclude gates where a given field is outside a given interval.

exclude_transition (*self*, *trans_value=1*, *exclude_masked=True*, *op='or'*)
Exclude all gates in rays marked as in transition between sweeps.

Exclude all gates in rays marked as "in transition" by the `antenna_transition` attribute of the radar used to construct the filter. If no antenna transition information is available no gates are excluded.

Parameters

trans_value [int, optional] Value used in the antenna transition data to indicate that the instrument was between sweeps (in transition) during the collection of a specific ray. Typically a value of 1 is used to indicate this transition and the default can be used in these cases.

exclude_masked [bool, optional] True to filter masked values in `antenna_transition` if the data is a masked array, False to include any masked values.

op [{ 'and', 'or', 'new' }] Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when

building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

gate_excluded

Return a copy of the excluded gates.

gate_included

Return a copy of the included gates.

include_above (*self*, *field*, *value*, *exclude_masked=True*, *op='and'*, *inclusive=False*)

Include gates where a given field is above a given value.

include_all (*self*)

Include all gates.

include_below (*self*, *field*, *value*, *exclude_masked=True*, *op='and'*, *inclusive=False*)

Include gates where a given field is below a given value.

include_equal (*self*, *field*, *value*, *exclude_masked=True*, *op='and'*)

Include gates where a given field is equal to a value.

include_gates (*self*, *mask*, *exclude_masked=True*, *op='and'*)

Include gates where a given mask is equal True.

Parameters

mask [numpy array] Boolean numpy array with same shape as a field array.

exclude_masked [bool, optional] True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op [{ 'and', 'or', 'new' }] Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'or' method MAY results in excluding gates which have previously been included.

include_inside (*self*, *field*, *v1*, *v2*, *exclude_masked=True*, *op='and'*, *inclusive=True*)

Include gates where a given field is inside a given interval.

include_none (*self*)

Include no gates, exclude all gates.

include_not_equal (*self*, *field*, *value*, *exclude_masked=True*, *op='and'*)

Include gates where a given field is not equal to a value.

include_not_masked (*self*, *field*, *exclude_masked=True*, *op='and'*)

Include gates where a given field in not masked.

include_not_transition (*self*, *trans_value=0*, *exclude_masked=True*, *op='and'*)

Include all gates in rays not marked as in transition between sweeps.

Include all gates in rays not marked as "in transition" by the antenna_transition attribute of the radar used to construct the filter. If no antenna transition information is available all gates are included.

Parameters

trans_value [int, optional] Value used in the antenna transition data to indicate that the instrument is not between sweeps (in transition) during the collection of a specific ray. Typically a value of 0 is used to indicate no transition and the default can be used in these cases.

exclude_masked [bool, optional] True to filter masked values in antenna_transition if the data is a masked array, False to include any masked values.

op [{‘and’, ‘or’, ‘new’}] Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. ‘and’ will perform a logical AND operation, ‘or’ a logical OR, and ‘new’ will replace the existing excluded gates with the one generated here. ‘or’, the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. ‘and’, the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the ‘or’ method MAY results in excluding gates which have previously been included.

include_outside (*self*, *field*, *v1*, *v2*, *exclude_masked=True*, *op='and'*, *inclusive=False*)

Include gates where a given field is outside a given interval.

include_valid (*self*, *field*, *exclude_masked=True*, *op='and'*)

Include gates where a valid value occurs in a field (not NaN or inf).

```
pyart.filters.gatefilter.birds_gate_filter(radar, zdr_field=None, rhv_field=None,
                                             refl_field=None, vel_field=None,
                                             max_zdr=3.0, max_rhv=0.9, min_refl=0.0,
                                             max_refl=20.0, vel_lim=1.0, rmin=2000.0,
                                             rmax=25000.0, elmin=1.0, elmax=85.0)
```

Create a filter which removes data not suspected of being birds

Creates a gate filter in which the following gates are excluded:

- Gates where the instrument is transitioning between sweeps.
- Gates where the reflectivity is beyond min_refl and max_refl
- Gates where the co-polar correlation coefficient is above max_rhv
- Gates where the differential reflectivity is above max_zdr
- Gates where the Doppler velocity is within the interval given by +-vel_lim
- Gates where any of the above fields are masked or contain invalid values (NaNs or infs).
- Gates outside the range given by range min and range max
- If any of these three fields do not exist in the radar that fields filter criteria is not applied.

Parameters

radar [Radar] Radar object from which the gate filter will be built.

refl_field, zdr_field, rhv_field, vel_field [str] Names of the radar fields which contain the reflectivity, differential reflectivity, co-polar correlation coefficient, and Doppler velocity from which the gate filter will be created using the above criteria. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

max_zdr, max_rhv [float] Maximum values for the differential reflectivity and co-polar correlation coefficient. Gates in these fields above these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the given field including removing masked

or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value above the highest value in the field.

min_refl, max_refl [float] Minimum and maximum values for the reflectivity. Gates outside of this interval as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use this filter. A value or None for one of these parameters will disable the minimum or maximum filtering but retain the other. A value of None for both of these values will disable all filtering based upon the reflectivity including removing masked or gates with an invalid value. To disable the interval filtering but retain the masked and invalid filter set the parameters to values above and below the lowest and greatest values in the reflectivity field.

rmin, rmax [float] Minimum and maximum ranges [m]

elmin, elmax [float] Minimum and maximum elevations [deg]

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in pyart.correct.

```
pyart.filters.gatefilter.class_based_gate_filter(radar, field=None,
                                                  kept_values=None)
```

Create a filter which removes undesired gates based on class values

Parameters

radar [Radar] Radar object from which the gate filter will be built.

field [str] Name of the radar field which contains the classification. A value of None for will use the default field name for the hydrometeor classification as defined in the Py-ART configuration file.

kept_values [list of ints or none] The class values to keep

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in pyart.correct.

```
pyart.filters.gatefilter.iso0_based_gate_filter(radar, iso0_field=None,
                                                  max_h_iso0=0.0, thickness=400.0,
                                                  beamwidth=None)
```

Create a filter which removes undesired gates based height over the iso0. Used primarily to filter out the melting layer and gates above it.

Parameters

radar [Radar] Radar object from which the gate filter will be built.

iso0_field [str] Name of the radar field which contains the height relative to the iso0. A value of None for will use the default field name as defined in the Py-ART configuration file.

max_h_iso0 [float] Maximum height relative to the iso0 in m. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

thickness [float] The estimated thickness of the melting layer in m.

beamwidth [float] The radar antenna 3 dB beamwidth [deg].

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a `gatefilter` parameter to various functions in `pyart.correct`.

```
pyart.filters.gatefilter.moment_and_texture_based_gate_filter(radar,
                                                              zdr_field=None,
                                                              rhv_field=None,
                                                              phi_field=None,
                                                              refl_field=None,
                                                              textzdr_field=None,
                                                              tex-
                                                              trhv_field=None,
                                                              textphi_field=None,
                                                              tex-
                                                              trefl_field=None,
                                                              wind_size=7,
                                                              max_textphi=20.0,
                                                              max_textrhv=0.3,
                                                              max_textzdr=2.85,
                                                              max_textrefl=8.0,
                                                              min_rhv=0.6)
```

Create a filter which removes undesired gates based on texture of moments.

Creates a gate filter in which the following gates are excluded: * Gates where the instrument is transitioning between sweeps. * Gates where RhoHV is below `min_rhv` * Gates where the PhiDP texture is above `max_textphi`. * Gates where the RhoHV texture is above `max_textrhv`. * Gates where the ZDR texture is above `max_textzdr` * Gates where the reflectivity texture is above `max_textrefl` * If any of the thresholds is not set or the field (RhoHV, ZDR, PhiDP, reflectivity) do not exist in the radar the filter is not applied.

Parameters

radar [Radar] Radar object from which the gate filter will be built.

zdr_field, rhv_field, phi_field, refl_field [str] Names of the radar fields which contain the differential reflectivity, cross correlation ratio, differential phase and reflectivity from which the textures will be computed. A value of `None` for any of these parameters will use the default field name as defined in the Py-ART configuration file.

textzdr_field, textrhv_field, textphi_field, textrefl_field [str] Names of the radar fields given to the texture of the differential reflectivity, texture of the cross correlation ratio, texture of differential phase and texture of reflectivity. A value of `None` for any of these parameters will use the default field name as defined in the Py-ART configuration file.

wind_size [int] Size of the moving window used to compute the ray texture.

max_textphi, max_textrhv, max_textzdr, max_textrefl [float] Maximum value for the texture of the differential phase, texture of RhoHV, texture of Zdr and texture of reflectivity. Gates in these fields above these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of `None` will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value above the highest value in the field.

min_rhv [float] Minimum value for the RhoHV. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of `None` will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a **gatefilter** parameter to various functions in `pyart.correct`.

```
pyart.filters.gatefilter.moment_based_gate_filter(radar, ncp_field=None,
                                                    rhv_field=None, refl_field=None,
                                                    min_ncp=0.5, min_rhv=None,
                                                    min_refl=-20.0, max_refl=100.0)
```

Create a filter which removes undesired gates based on moments.

Creates a gate filter in which the following gates are excluded:

- Gates where the instrument is transitioning between sweeps.
- Gates where the reflectivity is outside the interval `min_refl`, `max_refl`.
- Gates where the normalized coherent power is below `min_ncp`.
- Gates where the cross correlation ratio is below `min_rhi`. Using the default parameter this filtering is disabled.
- Gates where any of the above three fields are masked or contain invalid values (NaNs or infs).
- If any of these three fields do not exist in the radar that fields filter criteria is not applied.

Parameters

radar [*Radar*] Radar object from which the gate filter will be built.

refl_field, ncp_field, rhv_field [*str*] Names of the radar fields which contain the reflectivity, normalized coherent power (signal quality index) and cross correlation ratio (RhoHV) from which the gate filter will be created using the above criteria. A value of `None` for any of these parameters will use the default field name as defined in the Py-ART configuration file.

min_ncp, min_rhv [*float*] Minimum values for the normalized coherence power and cross correlation ratio. Gates in these fields below these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of `None` will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

min_refl, max_refl [*float*] Minimum and maximum values for the reflectivity. Gates outside of this interval as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use this filter. A value or `None` for one of these parameters will disable the minimum or maximum filtering but retain the other. A value of `None` for both of these values will disable all filtering based upon the reflectivity including removing masked or gates with an invalid value. To disable the interval filtering but retain the masked and invalid filter set the parameters to values above and below the lowest and greatest values in the reflectivity field.

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a **gatefilter** parameter to various functions in `pyart.correct`.

```
pyart.filters.gatefilter.snr_based_gate_filter(radar, snr_field=None, min_snr=10.0,
                                                max_snr=None)
```

Create a filter which removes undesired gates based on SNR.

Parameters

radar [*Radar*] Radar object from which the gate filter will be built.

snr_field [str] Name of the radar field which contains the signal to noise ratio. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_snr [float] Minimum value for the SNR. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

max_snr [float] Maximum value for the SNR

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in pyart.correct.

```
pyart.filters.gatefilter.temp_based_gate_filter(radar, temp_field=None,
                                                min_temp=0.0, thickness=400.0,
                                                beamwidth=None)
```

Create a filter which removes undesired gates based on temperature. Used primarily to filter out the melting layer and gates above it.

Parameters

radar [Radar] Radar object from which the gate filter will be built.

temp_field [str] Name of the radar field which contains the temperature. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_temp [float] Minimum value for the temperature in degrees. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

thickness [float] The estimated thickness of the melting layer in m.

beamwidth [float] The radar antenna 3 dB beamwidth [deg].

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in pyart.correct.

```
pyart.filters.gatefilter.visibility_based_gate_filter(radar, vis_field=None,
                                                      min_vis=10.0)
```

Create a filter which removes undesired gates based on visibility.

Parameters

radar [Radar] Radar object from which the gate filter will be built.

vis_field [str] Name of the radar field which contains the visibility. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_vis [float] Minimum value for the visibility. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

Returns

gatefilter [*GateFilter*] A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in pyart.correct.

PYART.MAP.GATES_TO_GRID

Generate a Cartesian grid by mapping from radar gates onto the grid.

<code>map_gates_to_grid(radars, grid_shape, ...[, ...])</code>	Map gates from one or more radars to a Cartesian grid.
<code>_determine_cy_weighting_func(weighting_function)</code>	Determine cython weight function value.
<code>_find_projparams(grid_origin, radars, ...)</code>	Determine the projection parameter.
<code>_parse_gatefilters(gatefilters, radars)</code>	Parse the gatefilters parameter.
<code>_determine_fields(fields, radars)</code>	Determine which field should be mapped to the grid.
<code>_find_offsets(radars, projparams, ...)</code>	Find offset between radars and grid origin.
<code>_find_grid_params(grid_shape, grid_limits)</code>	Find the starting points and step size of the grid.
<code>_parse_roi_func(roi_func, constant_roi, ...)</code>	Return the Radius of influence object.

`pyart.map.gates_to_grid._determine_cy_weighting_func` (*weighting_function*)
Determine cython weight function value.

`pyart.map.gates_to_grid._determine_fields` (*fields, radars*)
Determine which field should be mapped to the grid.

`pyart.map.gates_to_grid._find_grid_params` (*grid_shape, grid_limits*)
Find the starting points and step size of the grid.

`pyart.map.gates_to_grid._find_offsets` (*radars, projparams, grid_origin_alt*)
Find offset between radars and grid origin.

`pyart.map.gates_to_grid._find_projparams` (*grid_origin, radars, grid_projection*)
Determine the projection parameter.

`pyart.map.gates_to_grid._parse_gatefilters` (*gatefilters, radars*)
Parse the gatefilters parameter.

`pyart.map.gates_to_grid._parse_roi_func` (*roi_func, constant_roi, z_factor, xy_factor, min_radius, h_factor, nb, bsp, offsets*)
Return the Radius of influence object.

`pyart.map.gates_to_grid.map_gates_to_grid` (*radars, grid_shape, grid_limits, grid_origin=None, grid_origin_alt=None, grid_projection=None, fields=None, gatefilters=False, map_roi=True, weighting_function='Barnes', toa=17000.0, roi_func='dist_beam', constant_roi=None, z_factor=0.05, xy_factor=0.02, min_radius=500.0, h_factor=1.0, nb=1.5, bsp=1.0, **kwargs*)
Map gates from one or more radars to a Cartesian grid.

Generate a Cartesian grid of points for the requested fields from the collected points from one or more radars. For each radar gate that is not filtered a radius of influence is calculated. The weighted field values for that gate are added to all grid points within that radius. This routine scaled linearly with the number of radar gates and the effective grid size.

Parameters not defined below are identical to those in `map_to_grid()`.

Parameters

roi_func [str or RoIFunction] Radius of influence function. A function which takes an z, y, x grid location, in meters, and returns a radius (in meters) within which all collected points will be included in the weighting for that grid points. Examples can be found in the Typically following strings can use to specify a built in radius of influence function:

- constant: constant radius of influence.
- dist: radius grows with the distance from each radar.
- dist_beam: radius grows with the distance from each radar and parameter are based of virtual beam sizes.

A custom RoIFunction can be defined using the RoIFunction class and defining a `get_roi` method which returns the radius. For efficient mapping this class should be implemented in Cython.

Returns

grids [dict] Dictionary of mapped fields. The keys of the dictionary are given by parameter fields. Each elements is a *grid_size* float64 array containing the interpolated grid for that field.

See also:

grid_from_radars Map to a grid and return a Grid object

map_to_grid Create grid by finding the radius of influence around each grid point.

PYART.MAP.GRID_MAPPER

Utilities for mapping radar objects to Cartesian grids.

<code>grid_from_radars(radars, grid_shape, grid_limits)</code>	Map one or more radars to a Cartesian grid returning a Grid object.
<code>map_to_grid(radars, grid_shape, grid_limits)</code>	Map one or more radars to a Cartesian grid.
<code>example_roi_func_constant(zg, yg, xg)</code>	Example RoI function which returns a constant radius.
<code>example_roi_func_dist(zg, yg, xg)</code>	Example RoI function which returns a radius which grows with distance.
<code>_unify_times_for_radars(radars)</code>	Return unified start times and units for a number of radars.
<code>_load_nn_field_data(data, nfields, npoints, ...)</code>	Load the nearest neighbor field data into sdata
<code>_gen_roi_func_constant(constant_roi)</code>	Return a RoI function which returns a constant radius.
<code>_gen_roi_func_dist(z_factor, xy_factor, ...)</code>	Return a RoI function whose radius grows with distance.
<code>_gen_roi_func_dist_beam(h_factor, nb, bsp, ...)</code>	Return a RoI function whose radius which grows with distance and whose parameters are based on virtual beam size.

<code>NNLocator(data[, leafsize, algorithm])</code>	Nearest neighbor locator.
---	---------------------------

class `pyart.map.grid_mapper.NNLocator` (*data*, *leafsize*=10, *algorithm*='kd_tree')

Bases: `object`

Nearest neighbor locator.

Class for finding the neighbors of a points within a given distance.

Parameters

data [array_like, (n_sample, n_dimensions)] Locations of points to be indexed. Note that if data is a C-contiguous array of dtype float64 the data will not be copied. Othersize and internal copy will be made.

leafsize [int] The number of points at which the algorithm switches over to brute-force. This can significantly impact the speed of the contruction and query of the tree.

algorithm ['kd_tree', optional.] Algorithm used to compute the nearest neighbors. 'kd_tree' uses a k-d tree.

Methods

<i>find_neighbors_and_dists</i> (self, q, r)	Find all neighbors and distances within a given distance.
--	---

```
__class__
    alias of builtins.type
__delattr__ (self, name, /)
    Implement delattr(self, name).
__dict__ = mappingproxy({'__module__': 'pyart.map.grid_mapper', '__doc__': "\n Neare
__dir__ (self, /)
    Default dir() implementation.
__eq__ (self, value, /)
    Return self==value.
__format__ (self, format_spec, /)
    Default object formatter.
__ge__ (self, value, /)
    Return self>=value.
__getattr__ (self, name, /)
    Return getattr(self, name).
__gt__ (self, value, /)
    Return self>value.
__hash__ (self, /)
    Return hash(self).
__init__ (self, data, leafsize=10, algorithm='kd_tree')
    initialize.
__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.
__le__ (self, value, /)
    Return self<=value.
__lt__ (self, value, /)
    Return self<value.
__module__ = 'pyart.map.grid_mapper'
__ne__ (self, value, /)
    Return self!=value.
__new__ (*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.
__reduce__ (self, /)
    Helper for pickle.
__reduce_ex__ (self, protocol, /)
    Helper for pickle.
__repr__ (self, /)
    Return repr(self).
```


__setattr__ (*self, name, value, /*)

Implement setattr(self, name, value).

__sizeof__ (*self, /*)

Size of object in memory, in bytes.

__str__ (*self, /*)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

find_neighbors_and_dists (*self, q, r*)

Find all neighbors and distances within a given distance.

Parameters

q [n_dimensional tuple] Point to query

r [float] Distance within which neighbors are returned.

Returns

ind [array of intergers] Indices of the neighbors.

dist [array of floats] Distances to the neighbors.

`pyart.map.grid_mapper._gen_roi_func_constant` (*constant_roi*)

Return a RoI function which returns a constant radius.

See `map_to_grid()` for a description of the parameters.

`pyart.map.grid_mapper._gen_roi_func_dist` (*z_factor, xy_factor, min_radius, offsets*)

Return a RoI function whose radius grows with distance.

See `map_to_grid()` for a description of the parameters.

`pyart.map.grid_mapper._gen_roi_func_dist_beam` (*h_factor, nb, bsp, min_radius, offsets*)

Return a RoI function whose radius which grows with distance and whose parameters are based on virtual beam size.

See `map_to_grid()` for a description of the parameters.

`pyart.map.grid_mapper._unify_times_for_radars` (*radars*)

Return unified start times and units for a number of radars.

`pyart.map.grid_mapper.example_roi_func_constant` (*zg, yg, xg*)

Example RoI function which returns a constant radius.

Parameters

zg, yg, xg [float] Distance from the grid center in meters for the x, y and z axes.

Returns

roi [float] Radius of influence in meters

`pyart.map.grid_mapper.example_roi_func_dist` (*zg, yg, xg*)

Example RoI function which returns a radius which grows with distance.

Parameters

zg, yg, xg [float] Distance from the grid center in meters for the x, y and z axes.

Returns

roi [float]

`pyart.map.grid_mapper.example_roi_func_dist_beam(zg, yg, xg)`

Example RoI function which returns a radius which grows with distance and whose parameters are based on virtual beam size.

Parameters

zg, yg, xg [float] Distance from the grid center in meters for the x, y and z axes.

Returns

roi [float]

`pyart.map.grid_mapper.grid_from_radars(radars, grid_shape, grid_limits, grid-
ding_algo='map_gates_to_grid', **kwargs)`

Map one or more radars to a Cartesian grid returning a Grid object.

Additional arguments are passed to `map_to_grid()` or `map_gates_to_grid()`.

Parameters

radars [Radar or tuple of Radar objects.] Radar objects which will be mapped to the Cartesian grid.

grid_shape [3-tuple of floats] Number of points in the grid (z, y, x).

grid_limits [3-tuple of 2-tuples] Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

gridding_algo ['map_to_grid' or 'map_gates_to_grid'] Algorithm to use for gridding. 'map_to_grid' finds all gates within a radius of influence for each grid point, 'map_gates_to_grid' maps each radar gate onto the grid using a radius of influence and is typically significantly faster.

Returns

grid [Grid] A `pyart.io.Grid` object containing the gridded radar data.

See also:

map_to_grid Map to grid and return a dictionary of radar fields.

map_gates_to_grid Map each gate onto a grid returning a dictionary of radar fields.

References

Barnes S., 1964: A Technique for Maximizing Details in Numerical Weather Map Analysis. Journal of Applied Meteorology and Climatology, 3(4), 396-409.

Cressman G., 1959: An operational objective analysis system. Monthly Weather Review, 87(10), 367-374.

Pauley, P. M. and X. Wu, 1990: The theoretical, discrete, and actual response of the Barnes objective analysis scheme for one- and two-dimensional fields. Monthly Weather Review, 118, 1145-1164

```
pyart.map.grid_mapper.map_to_grid(radars, grid_shape, grid_limits, grid_origin=None,
                                   grid_origin_alt=None, grid_projection=None,
                                   fields=None, gatefilters=False, map_roi=True,
                                   weighting_function='Barnes', toa=17000.0,
                                   copy_field_data=True, algorithm='kd_tree', leafsize=10.0,
                                   roi_func='dist_beam', constant_roi=None, z_factor=0.05,
                                   xy_factor=0.02, min_radius=500.0, h_factor=1.0, nb=1.5,
                                   bsp=1.0, **kwargs)
```

Map one or more radars to a Cartesian grid.

Generate a Cartesian grid of points for the requested fields from the collected points from one or more radars. The field value for a grid point is found by interpolating from the collected points within a given radius of influence and weighting these nearby points according to their distance from the grid points. Collected points are filtered according to a number of criteria so that undesired points are not included in the interpolation.

Parameters

radars [Radar or tuple of Radar objects.] Radar objects which will be mapped to the Cartesian grid.

grid_shape [3-tuple of floats] Number of points in the grid (z, y, x).

grid_limits [3-tuple of 2-tuples] Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

grid_origin [(float, float) or None] Latitude and longitude of grid origin. None sets the origin to the location of the first radar.

grid_origin_alt: float or None Altitude of grid origin, in meters. None sets the origin to the location of the first radar.

grid_projection [dic or str] Projection parameters defining the map projection used to transform the locations of the radar gates in geographic coordinate to Cartesian coordinates. None will use the default dictionary which uses a native azimuthal equidistance projection. See `pyart.core.Grid()` for additional details on this parameter. The geographic coordinates of the radar gates are calculated using the projection defined for each radar. No transformation is used if a `grid_origin` and `grid_origin_alt` are None and a single radar is specified.

fields [list or None] List of fields within the radar objects which will be mapped to the cartesian grid. None, the default, will map the fields which are present in all the radar objects.

gatefilters [GateFilter, tuple of GateFilter objects, optional] Specify what gates from each radar will be included in the interpolation onto the grid. Only gates specified in each `gatefilters` will be included in the mapping to the grid. A single `GateFilter` can be used if a single Radar is being mapped. A value of False for a specific element or the entire parameter will apply no filtering of gates for a specific radar or all radars (the default). Similarly a value of None will create a `GateFilter` from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`.

roi_func [str or function] Radius of influence function. A functions which takes an z, y, x grid location, in meters, and returns a radius (in meters) within which all collected points will be included in the weighting for that grid points. Examples can be found in the `example_roi_func_constant()`, `example_roi_func_dist()`, and `example_roi_func_dist_beam()`. Alternatively the following strings can use to specify a built in radius of influence function:

- constant: constant radius of influence.
- dist: radius grows with the distance from each radar.

- **dist_beam**: radius grows with the distance from each radar and parameter are based of virtual beam sizes.

The parameters which control these functions are listed in the *Other Parameters* section below.

map_roi [bool] True to include a radius of influence field in the returned dictionary under the 'ROI' key. This is the value of *roi_func* at all grid points.

weighting_function ['Barnes' or 'Barnes2' or 'Cressman' or 'Nearest'] Functions used to weight nearby collected points when interpolating a grid point.

toa [float] Top of atmosphere in meters. Collected points above this height are not included in the interpolation.

Returns

grids [dict] Dictionary of mapped fields. The keys of the dictionary are given by parameter fields. Each elements is a *grid_size* float64 array containing the interpolated grid for that field.

Other Parameters

constant_roi [float] Radius of influence parameter for the built in 'constant' function. This parameter is the constant radius in meter for all grid points. This parameter is used when *roi_func* is *constant* or *constant_roi* is not None. If *constant_roi* is not None, the constant *roi_func* is used automatically.

z_factor, xy_factor, min_radius [float] Radius of influence parameters for the built in 'dist' function. The parameter correspond to the radius size increase, in meters, per meter increase in the z-dimension from the nearest radar, the same foreach meteter in the xy-distance from the nearest radar, and the minimum radius of influence in meters. These parameters are only used when *roi_func* is 'dist'.

h_factor, nb, bsp, min_radius [float] Radius of influence parameters for the built in 'dist_beam' function. The parameter correspond to the height scaling, virtual beam width, virtual beam spacing, and minimum radius of influence. These parameters are only used when *roi_func* is 'dist_mean'.

copy_field_data [bool] True to copy the data within the radar fields for faster gridding, the dtype for all fields in the grid will be float64. False will not copy the data which preserves the dtype of the fields in the grid, may use less memory but results in significantly slower gridding times. When False gates which are masked in a particular field but are not masked in the *refl_field* field will still be included in the interpolation. This can be prevented by setting this parameter to True or by gridding each field individually setting the *refl_field* parameter and the *fields* parameter to the field in question. It is recommended to set this parameter to True.

algorithm ['kd_tree'.] Algorithms to use for finding the nearest neighbors. 'kd_tree' is the only valid option.

leafsize [int] Leaf size passed to the neighbor lookup tree. This can affect the speed of the construction and query, as well as the memory required to store the tree. The optimal value depends on the nature of the problem. This value should only effect the speed of the gridding, not the results.

See also:

grid_from_radars Map to grid and return a Grid object.

PYART.MAP.POLAR_TO_CARTESIAN

Routines to project polar radar data to Cartesian coordinates

<code>polar_to_cartesian(radar_sweep, field_name)</code>	Interpolates a PPI or RHI scan in polar coordinates to a regular cartesian grid of South-North and West-East coordinates (for PPI) or distance at ground and altitude coordinates (for RHI)
<code>get_earth_radius(latitude)</code>	Computes the earth radius for a given latitude

`pyart.map.polar_to_cartesian.get_earth_radius(latitude)`
Computes the earth radius for a given latitude

Parameters

latitude: latitude in degrees (WGS84)

Returns

earth_radius [the radius of the earth at the given latitude]

`pyart.map.polar_to_cartesian.polar_to_cartesian(radar_sweep, field_name, cart_res=75, max_range=None, mapping=None)`

Interpolates a PPI or RHI scan in polar coordinates to a regular cartesian grid of South-North and West-East coordinates (for PPI) or distance at ground and altitude coordinates (for RHI)

Parameters

radar [Radar] Radar instance as generated by pyart

sweep [int] Sweep number to project to cartesian coordinates.

field_name [str] Name of the radar field to be interpolated

cart_res [int, optional] Resolution (in m.) of the cartesian grid to which polar data is interpolated

max_range [int, optional] Maximal allowed range (in m.) from radar for gates to be interpolated

mapping [dict, optional] Dictionnary of mapping indexes (from polar to cartesian), gets returned by the function (see below). Can be used as input when interpolating sequentially several variables for the same scan, to save significant time

Returns

coords [tuple of 2 arrays] 2D coordinates of the cartesian grid

cart_data [2D array] Interpolated radar measurements (on the cartesian grid)

mapping,: **dict** Dictionary of mapping indexes (from polar to cartesian), which contains the indexes mapping the polar grid to the cartesian grid as well as some metadata.

PYART.MAP._GATE_TO_GRID_MAP

Cython classes and functions for efficient mapping of radar gates to a uniform grid.

<i>GateToGridMapper</i>	A class for efficient mapping of radar gates to a regular grid by weighting all gates within a specified radius of influence by distance.
<i>RoIFunction</i>	A class for storing radius of interest calculations.
<i>ConstantRoI</i>	Constant radius of influence class.
<i>DistRoI</i>	Radius of influence which expands with distance from the radar.
<i>DistBeamRoI</i>	Radius of influence which expands with distance from multiple radars.

class `pyart.map._gate_to_grid_map.ConstantRoI`
Bases: `pyart.map._gate_to_grid_map.RoIFunction`
Constant radius of influence class.

Methods

<code>get_roi()</code>	Return constant radius of influence.
------------------------	--------------------------------------

```
__class__
    alias of builtins.type
__delattr__ (self, name, /)
    Implement delattr(self, name).
__dir__ (self, /)
    Default dir() implementation.
__eq__ (self, value, /)
    Return self==value.
__format__ (self, format_spec, /)
    Default object formatter.
__ge__ (self, value, /)
    Return self>=value.
__getattr__ (self, name, /)
    Return getattr(self, name).
```

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__
intialize.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__ne__ (*self, value, /*)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

get_roi ()
Return constant radius of influence.

class pyart.map._gate_to_grid_map.**DistBeamRoI**
Bases: *pyart.map._gate_to_grid_map.RoIFunction*

Radius of influence which expands with distance from multiple radars.

Methods

`get_roi()` Return the radius of influence for coordinates in meters.

__class__
alias of `builtins.type`

__delattr__ (*self*, *name*, /)
Implement `delattr(self, name)`.

__dir__ (*self*, /)
Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return `self==value`.

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return `self>=value`.

__getattr__ (*self*, *name*, /)
Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)
Return `self>value`.

__hash__ (*self*, /)
Return `hash(self)`.

__init__
initialize.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return `self<=value`.

__lt__ (*self*, *value*, /)
Return `self<value`.

__ne__ (*self*, *value*, /)
Return `self!=value`.

__new__ (**args*, ***kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return `repr(self)`.

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

get_roi ()
Return the radius of influence for coordinates in meters.

class pyart.map._gate_to_grid_map.**DistRoI**
Bases: *pyart.map._gate_to_grid_map.RoIFunction*

Radius of influence which expands with distance from the radar.

Methods

<i>get_roi</i> ()	Return the radius of influence for coordinates in meters.
-------------------	---

__class__
alias of builtins.type

__delattr__ (*self, name, /*)
Implement delattr(self, name).

__dir__ (*self, /*)
Default dir() implementation.

__eq__ (*self, value, /*)
Return self==value.

__format__ (*self, format_spec, /*)
Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__
italize.

__init_subclass__()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__(self, value, /)

Return self<=value.

__lt__(self, value, /)

Return self<value.

__ne__(self, value, /)

Return self!=value.

__new__(*args, **kwargs)

Create and return a new object. See help(type) for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__()

__reduce_ex__(self, protocol, /)

Helper for pickle.

__repr__(self, /)

Return repr(self).

__setattr__(self, name, value, /)

Implement setattr(self, name, value).

__setstate__()

__sizeof__(self, /)

Size of object in memory, in bytes.

__str__(self, /)

Return str(self).

__subclasshook__()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

get_roi()

Return the radius of influence for coordinates in meters.

class pyart.map._gate_to_grid_map.GateToGridMapper

Bases: `object`

A class for efficient mapping of radar gates to a regular grid by weighting all gates within a specified radius of influence by distance.

Parameters

grid_shape, [tuple of ints] Shape of the grid along the z, y, and x dimensions.

grid_starts, grid_steps [tuple of ints] Starting points and step sizes in meters of the grid along the z, y and x dimensions.

grid_sum, grid_wsum [4D float32 array] Array for collecting grid weighted values and weights for each grid point and field. Dimension are order z, y, x, and fields. These array are modified in place when mapping gates unto the grid.

Methods

<i>find_roi_for_grid()</i>	Fill in the radius of influence for each point in the grid.
<i>map_gates_to_grid()</i>	Map radar gates unto the regular grid.

__class__
alias of `builtins.type`

__delattr__ (*self*, *name*, /)
Implement `delattr(self, name)`.

__dir__ (*self*, /)
Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return `self==value`.

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return `self>=value`.

__getattr__ (*self*, *name*, /)
Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)
Return `self>value`.

__hash__ (*self*, /)
Return `hash(self)`.

__init__
initialize.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return `self<=value`.

__lt__ (*self*, *value*, /)
Return `self<value`.

__ne__ (*self*, *value*, /)
Return `self!=value`.

__new__ (**args*, ***kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return `repr(self)`.

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__setstate__ ()

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

find_roi_for_grid ()
Fill in the radius of influence for each point in the grid.

Parameters

roi_array [3D float32 array] Array which will be filled by the radius of influence for each point in the grid.

roi_func [RoIFunction] Object whose get_roi method returns the radius of influence.

map_gates_to_grid ()
Map radar gates unto the regular grid.

The grid_sum and grid_wsum arrays used to initialize the class are update with the mapped gate data.

Parameters

ngates, nrays [int] Number of gates and rays in the radar volume.

gate_z, gate_y, gate_x [2D float32 array] Cartesian locations of the gates in meters.

field_data [3D float32 array] Array containing field data for the radar, dimension are ordered as nrays, ngates, nfields.

field_mask [3D uint8 array] Array containing masking of the field data for the radar, dimension are ordered as nrays, ngates, nfields.

excluded_gates [2D uint8 array] Array containing gate masking information. Gates with non-zero values will not be included in the mapping.

offset [tuple of floats] Offset of the radar from the grid origin. Dimension are ordered as z, y, x. Top of atmosphere. Gates above this level are considered.

roi_func [RoIFunction] Object whose get_roi method returns the radius of influence.

weighting_function [int] Function to use for weighting gates based upon distance. 0 for Barnes, 1 for Cressman and 2 for Nearest neighbor weighting.

class pyart.map._gate_to_grid_map.**RoIFunction**
Bases: `object`

A class for storing radius of interest calculations.

Methods

<code>get_roi()</code>	Return the radius of influence for coordinates in meters.
------------------------	---

__class__
alias of `builtins.type`

__delattr__ (*self*, *name*, /)
Implement `delattr(self, name)`.

__dir__ (*self*, /)
Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return `self==value`.

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return `self>=value`.

__getattr__ (*self*, *name*, /)
Return `getattr(self, name)`.

__gt__ (*self*, *value*, /)
Return `self>value`.

__hash__ (*self*, /)
Return `hash(self)`.

__init__ (*self*, /, **args*, ***kwargs*)
Initialize self. See `help(type(self))` for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return `self<=value`.

__lt__ (*self*, *value*, /)
Return `self<value`.

__ne__ (*self*, *value*, /)
Return `self!=value`.

__new__ (**args*, ***kwargs*)
Create and return a new object. See `help(type)` for accurate signature.

__pyx_vtable__ = <capsule object NULL>

__reduce__ ()

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return `repr(self)`.

__setattr__ (*self*, *name*, *value*, /)
Implement `setattr(self, name, value)`.

__setstate__()

__sizeof__(self, /)

Size of object in memory, in bytes.

__str__(self, /)

Return str(self).

__subclasshook__()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

get_roi()

Return the radius of influence for coordinates in meters.

pyart.map._gate_to_grid_map.__pyx_unpickle_ConstantRoI()

pyart.map._gate_to_grid_map.__pyx_unpickle_DistBeamRoI()

pyart.map._gate_to_grid_map.__pyx_unpickle_DistRoI()

pyart.map._gate_to_grid_map.__pyx_unpickle_GateToGridMapper()

pyart.map._gate_to_grid_map.__pyx_unpickle_RoIFunction()

PYART.UTIL.CIRCULAR_STATS

Functions for computing statistics on circular (directional) distributions.

<i>angular_mean</i> (angles)	Compute the mean of a distribution of angles in radians.
<i>angular_std</i> (angles)	Compute the standard deviation of a distribution of angles in radians.
<i>angular_mean_deg</i> (angles)	Compute the mean of a distribution of angles in degrees.
<i>angular_std_deg</i> (angles)	Compute the standard deviation of a distribution of angles in degrees.
<i>interval_mean</i> (dist, interval_min, interval_max)	Compute the mean of a distribution within an interval.
<i>interval_std</i> (dist, interval_min, interval_max)	Compute the standard deviation of a distribution within an interval.
<i>mean_of_two_angles</i> (angles1, angles2)	Compute the element by element mean of two sets of angles.
<i>mean_of_two_angles_deg</i> (angle1, angle2)	Compute the element by element mean of two sets of angles in degrees.

`pyart.util.circular_stats.angular_mean (angles)`

Compute the mean of a distribution of angles in radians.

Parameters

angles [array like] Distribution of angles in radians.

Returns

mean [float] The mean angle of the distribution in radians.

`pyart.util.circular_stats.angular_mean_deg (angles)`

Compute the mean of a distribution of angles in degrees.

Parameters

angles [array like] Distribution of angles in degrees.

Returns

mean [float] The mean angle of the distribution in degrees.

`pyart.util.circular_stats.angular_std (angles)`

Compute the standard deviation of a distribution of angles in radians.

Parameters

angles [array like] Distribution of angles in radians.

Returns

std [float] Standard deviation of the distribution.

`pyart.util.circular_stats.angular_std_deg(angles)`

Compute the standard deviation of a distribution of angles in degrees.

Parameters

angles [array like] Distribution of angles in degrees.

Returns

std [float] Standard deviation of the distribution.

`pyart.util.circular_stats.interval_mean(dist, interval_min, interval_max)`

Compute the mean of a distribution within an interval.

Return the average of the array elements which are interpreted as being taken from a circular interval with endpoints given by `interval_min` and `interval_max`.

Parameters

dist [array like] Distribution of values within an interval.

interval_min, interval_max [float] The endpoints of the interval.

Returns

mean [float] The mean value of the distribution.

`pyart.util.circular_stats.interval_std(dist, interval_min, interval_max)`

Compute the standard deviation of a distribution within an interval.

Return the standard deviation of the array elements which are interpreted as being taken from a circular interval with endpoints given by `interval_min` and `interval_max`.

Parameters

dist [array like] Distribution of values within an interval.

interval_min, interval_max [float] The endpoints of the interval.

Returns

std [float] The standard deviation of the distribution.

`pyart.util.circular_stats.mean_of_two_angles(angles1, angles2)`

Compute the element by element mean of two sets of angles.

Parameters

angles1 [array] First set of angles in radians.

angles2 [array] Second set of angles in radians.

Returns

mean [array] Elements by element angular mean of the two sets of angles in radians.

`pyart.util.circular_stats.mean_of_two_angles_deg(angle1, angle2)`

Compute the element by element mean of two sets of angles in degrees.

Parameters

angle1 [array] First set of angles in degrees.

angle2 [array] Second set of angles in degrees.

Returns

mean [array] Elements by element angular mean of the two sets of angles in degrees.

PYART.UTIL.DATETIME_UTILS

Functions for converting date and time between various forms.

`pyart.util.datetime_utils.datetime_from_dataset(dataset, epoch=False, **kwargs)`

Return a datetime for the first time in a netCDF Dataset.

`pyart.util.datetime_utils.datetime_from_grid(grid, epoch=False, **kwargs)`

Return a datetime for the volume start in a Grid.

`pyart.util.datetime_utils.datetime_from_radar(radar, epoch=False, **kwargs)`

Return a datetime for the first ray in a Radar.

`pyart.util.datetime_utils.datetimes_from_dataset(dataset, epoch=False, **kwargs)`

Return an array of datetimes for the times in a netCDF Dataset.

`pyart.util.datetime_utils.datetimes_from_radar(radar, epoch=False, **kwargs)`

Return an array of datetimes for the rays in a Radar.

PYART.UTIL.HILDEBRAND_SEKHON

Estimation of noise in Doppler spectra using the Hildebrand Sekhon method.

```
estimate_noise_hs74(spectrum[,          navg,  Estimate noise parameters of a Doppler spectrum.  
nnoise_min])
```

```
pyart.util.hildebrand_sekhon.estimate_noise_hs74 (spectrum, navg=1, nnoise_min=1)  
Estimate noise parameters of a Doppler spectrum.
```

Use the method of estimating the noise level in Doppler spectra outlined by Hildebrand and Sekhon, 1974.

Parameters

spectrum [array like] Doppler spectrum in linear units.

navg [int, optional] The number of spectral bins over which a moving average has been taken. Corresponds to the **p** variable from equation 9 of the article. The default value of 1 is appropriate when no moving average has been applied to the spectrum.

nnoise_min [int] Minimum number of noise samples to consider the estimation valid

Returns

mean [float-like] Mean of points in the spectrum identified as noise.

threshold [float-like] Threshold separating noise from signal. The point in the spectrum with this value or below should be considered as noise, above this value signal. It is possible that all points in the spectrum are identified as noise. If a peak is required for moment calculation then the point with this value should be considered as signal.

var [float-like] Variance of the points in the spectrum identified as noise.

nnoise [int] Number of noise points in the spectrum.

References

P. H. Hildebrand and R. S. Sekhon, Objective Determination of the Noise Level in Doppler Spectra. Journal of Applied Meteorology, 1974, 13, 808-811.

PYART.UTIL.IVIC

Estimation of noise in a ray using Ivic (2013) method

<code>estimate_noise_ivicl3(pwr_w_ray[, pct, ...])</code>	Estimate noise parameters of a ray
<code>get_ivic_pct(npulses, pct, z[, prob_thr])</code>	Get the point clutter threshold (PCT)
<code>get_ivic_flat_reg_var_max(npulses, y, x, ...)</code>	Get the threshold for maximum local variance of noise [dB]
<code>get_ivic_snr_thr(npulses, snr_thr[, pfa_thr])</code>	Get the threshold for steps 3 and 6 of ivic
<code>ivic_pct_table(npulses)</code>	Get the point clutter threshold (PCT) of Ivic from a look up table.
<code>ivic_flat_reg_var_max_table(npulses, ...)</code>	Get maximum variance of noise of Ivic from a look up table.
<code>ivic_snr_thr_table(npulses)</code>	Get the threshold for steps 3 and 6 of ivic from a look up table The thresholds are computed for between 3 and 200 pulses.

```
pyart.util.ivic.estimate_noise_ivicl3(pwr_w_ray, pct=2.0, delay=1, flat_reg_wlen=96,
                                       flat_reg_var_max=1.5, snr_thr=1.6,
                                       npulses=30, ngates_min=800, iterations=10,
                                       get_noise_pos=False)
```

Estimate noise parameters of a ray

Use the method of estimating the noise level in a ray outlined by Ivic, 2013.

Parameters

- pwr_w_ray** [array like] Doppler spectrum in linear units.
- pct** [float] Point Clutter Threshold
- delay** [int] distance of the gate to which compare for point target threshold
- flat_reg_wlen** [int] Minimum number of gates that should contain a valid region. Default gives a size of 8 km with 83.3 m resolution
- flat_reg_var_max** [float] Maximum local variance of powers in decibels to consider the region as flat.
- snr_thr** [float] Threshold applied in steps 3 and 6
- npulses** [int] Number of pulses used to compute the power of the array
- ngates_min: int** minimum number of gates with noise to consider the retrieval valid
- iterations: int** number of iterations in step 7
- get_noise_pos** [bool] If True the indices of the gates identified as noise will be returned

Returns

mean [float-like] Mean of the gates in the ray identified as noise.
var [float-like] Variance of the gates in the ray identified as noise.
nnoise [int] Number of noise gates in the ray.
inds_ray [1D-array] The indices of the gates containing noise

References

I.R. Ivic, C. Curtis and S.M. Torres, Radial-Based Noise Power Estimation for Weather Radars. Journal of Atmospheric and Oceanic Technology, 2013, 30, 2737-2753.

`pyart.util.ivic.get_ivic_flat_reg_var_max(npulses, y, x, flat_reg_wlen, ndBm=30.0, accuracy=0.001)`

Get the threshold for maximum local variance of noise [dB]

Parameters

npulses [1D array] array with the number of pulses in a ray
y [1D array] array of y values
x [1D array] array of x values. These are the possible values of the threshold
flat_reg_wlen [int] the lenght of the flat region window in bins
ndBm [float] the mean noise power in dBm
accuracy [float] The desired accuracy of the threshold (difference with target probability)

Returns

var_thr [1D array] The thresholds corresponding to each number of pulses

`pyart.util.ivic.get_ivic_pct(npulses, pct, z, prob_thr=0.0001)`

Get the point clutter threshold (PCT)

Parameters

npulses [1D array] array with the number of pulses in a ray
pct [1D array] array with possible values of the PCT
z [1D array] array of z values
prob_thr [float] Desired probability

Returns

pct_out [1D array] The PCT threshold corresponding to each number of pulses

`pyart.util.ivic.get_ivic_snr_thr(npulses, snr_thr, pfa_thr=0.001)`

Get the threshold for steps 3 and 6 of ivic

Parameters

npulses [1D array] array with the number of pulses in a ray
snr_thr [1D array] array with possible values of the snr threshold
pfa_thr [float] the desired probability of false alarm

Returns

snr_thr_out [1D array] The snr threshold corresponding to each number of pulses according to the desired probability of false alarm

`pyart.util.ivic.ivic_flat_reg_var_max_table(npulses, flat_reg_wlen)`

Get maximum variance of noise of Ivic from a look up table.

Parameters

npulses [1D array] array with the number of pulses in a ray

flat_reg_wlen [float] The flat region window length in bins

Returns

flat_reg_var_max [1D array] The maximum variance threshold corresponding to each number of pulses

`pyart.util.ivic.ivic_pct_table(npulses)`

Get the point clutter threshold (PCT) of Ivic from a look up table. The thresholds are computed for between 3 and 78 pulses. If there number of pulses is beyond this range it throws an error

Parameters

npulses [1D array] array with the number of pulses in a ray

Returns

pct_table [1D array] The PCT corresponding to each number of pulses

`pyart.util.ivic.ivic_snr_thr_table(npulses)`

Get the threshold for steps 3 and 6 of ivic from a look up table The thresholds are computed for between 3 and 200 pulses. If there number of pulses is beyond this range it throws an error

Parameters

npulses [1D array] array with the number of pulses in a ray

Returns

snr_thr_out [1D array] The snr threshold corresponding to each number of pulses according to the desired probability of false alarm

General meteorological calculations useful to other modules.

`pyart.util.met.get_best_sounding(target, sdir, minl, maxl)`

`pyart.util.met.nth_smallest(n, iter)`

PYART.UTIL.RADAR_UTILS

Functions for working radar instances.

<code>is_vpt(radar[, offset])</code>	Determine if a Radar appears to be a vertical pointing scan.
<code>to_vpt(radar[, single_scan])</code>	Convert an existing Radar object to represent a vertical pointing scan.
<code>join_radar(radar1, radar2)</code>	Combine two radar instances into one.
<code>join_spectra(spectral1, spectral2)</code>	Combine two spectra instances into one.
<code>cut_radar(radar, field_names[, rng_min, ...])</code>	Cuts the radar object into new dimensions
<code>cut_radar_spectra(radar, field_names[, ...])</code>	Cuts the radar spectra object into new dimensions
<code>radar_from_spectra(psr)</code>	obtain a Radar object from a RadarSpectra object
<code>interpol_spectra(psr[, kind, fill_value])</code>	Interpolates the spectra so that it has a uniform grid

`pyart.util.radar_utils.cut_radar(radar, field_names, rng_min=None, rng_max=None, ele_min=None, ele_max=None, azi_min=None, azi_max=None)`

Cuts the radar object into new dimensions

Parameters

- radar** [radar object] The radar object containing the data
- field_names** [str or None] The fields to keep in the new radar
- rng_min, rng_max** [float] The range limits [m]. If None the entire coverage of the radar is going to be used
- ele_min, ele_max, azi_min, azi_max** [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

Returns

- radar** [radar object] The radar object containing only the desired data

`pyart.util.radar_utils.cut_radar_spectra(radar, field_names, rng_min=None, rng_max=None, ele_min=None, ele_max=None, azi_min=None, azi_max=None)`

Cuts the radar spectra object into new dimensions

Parameters

- radar** [radar object] The radar object containing the data
- field_names** [str or None] The fields to keep in the new radar
- rng_min, rng_max** [float] The range limits [m]. If None the entire coverage of the radar is going to be used

ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

Returns

radar [radar object] The radar object containing only the desired data

`pyart.util.radar_utils.interpolate_spectra (psr, kind='linear', fill_value=0.0)`

Interpolates the spectra so that it has a uniform grid

Parameters

psr [RadarSpectra object] The original spectra

Returns

psr_interp [RadarSpectra object] The interpolated spectra

`pyart.util.radar_utils.is_vpt (radar, offset=0.5)`

Determine if a Radar appears to be a vertical pointing scan.

This function only verifies that the object is a vertical pointing scan, use the `to_vpt ()` function to convert the radar to a vpt scan if this function returns True.

Parameters

radar [Radar] Radar object to determine if.

offset [float, optional] Maximum offset of the elevation from 90 degrees to still consider to be vertically pointing.

Returns

flag [bool] True if the radar appear to be verticle pointing, False if not.

`pyart.util.radar_utils.join_radar (radar1, radar2)`

Combine two radar instances into one.

Parameters

radar1 [Radar] Radar object.

radar2 [Radar] Radar object.

`pyart.util.radar_utils.join_spectra (spectra1, spectra2)`

Combine two spectra instances into one.

Parameters

spectra1 [spectra] spectra object.

spectra2 [spectra] spectra object.

`pyart.util.radar_utils.radar_from_spectra (psr)`

obtain a Radar object from a RadarSpectra object

Parameters

psr [RadarSpectra object] The reference object

Returns

radar [radar object] The new radar object

`pyart.util.radar_utils.to_vpt (radar, single_scan=True)`

Convert an existing Radar object to represent a vertical pointing scan.

This function does not verify that the Radar object contains a vertical pointing scan. To perform such a check use `is_vpt()`.

Parameters

radar [Radar] Mislabeled vertical pointing scan Radar object to convert to be properly labeled. This object is converted in place, no copy of the existing data is made.

single_scan [bool, optional] True to convert the volume to a single scan, any azimuth angle data is lost. False will convert the scan to contain the same number of scans as rays, azimuth angles are retained.

PYART.UTIL.SIGMATH

Function for mathematical, signal processing and numerical routines.

<i>angular_texture_2d</i> (image, N, interval)	Compute the angular texture of an image.
<i>rolling_window</i> (a, window)	create a rolling window object for application of functions eg: result=np.ma.std(array, 11), 1)
<i>texture</i> (radar, var)	Determine a texture field using an 11pt stdev texarray=texture(pyradarobj, field).
<i>texture_along_ray</i> (radar, var[, wind_size])	Compute field texture along ray using a user specified window size.

`pyart.util.sigmath.angular_texture_2d` (*image*, *N*, *interval*)

Compute the angular texture of an image. Uses convolutions in order to speed up texture calculation by a factor of ~50 compared to using `ndimage.generic_filter`.

Parameters

image [2D array of floats] The array containing the velocities in which to calculate texture from.

N [int] This is the window size for calculating texture. The texture will be calculated from an N by N window centered around the gate.

interval [float] The absolute value of the maximum velocity. In conversion to radial coordinates, π will be defined to be interval and $-\pi$ will be -interval. It is recommended that interval be set to the Nyquist velocity.

Returns

std_dev [float array] Texture of the radial velocity field.

`pyart.util.sigmath.rolling_window` (*a*, *window*)

create a rolling window object for application of functions eg: result=np.ma.std(array, 11), 1)

`pyart.util.sigmath.texture` (*radar*, *var*)

Determine a texture field using an 11pt stdev texarray=texture(pyradarobj, field).

`pyart.util.sigmath.texture_along_ray` (*radar*, *var*, *wind_size*=7)

Compute field texture along ray using a user specified window size.

Parameters

radar [radar object] The radar object where the field is.

var [str] Name of the field which texture has to be computed.

wind_size [int, optional] Optional. Size of the rolling window used.

Returns

tex [radar field] The texture of the specified field.

PYART.UTIL.SIMULATED_VEL

Function for creating simulated velocity fields.

simulated_vel_from_profile(*radar*, *profile*[, ...]) Create simulated radial velocities from a profile of horizontal winds.

```
pyart.util.simulated_vel.simulated_vel_from_profile(radar, profile, interp_kind='linear',  
                                                    sim_vel_field=None)
```

Create simulated radial velocities from a profile of horizontal winds.

Parameters

radar [Radar] Radar instance which provides the scanning parameters for the simulated radial velocities.

profile [HorizontalWindProfile] Profile of horizontal winds.

interp_kind [str, optional] Specifies the kind of interpolation used to determine the winds at a given height. Must be one of 'linear', 'nearest', 'zero', 'slinear', 'quadratic', or 'cubic'. The the documentation for the SciPy `scipy.interpolate.interp1d` function for descriptions.

sim_vel_field [str, optional] Name to use for the simulated velocity field metadata. None will use the default field name from the Py-ART configuration file.

Returns

sim_vel [dict] Dictionary containing a radar field of simulated radial velocities.

PYART.UTIL.XSECT

Function for extracting cross sections from radar volumes.

<i>cross_section_ppi</i> (radar, target_azimuths[, ...])	Extract cross sections from a PPI volume along one or more azimuth angles.
<i>cross_section_rhi</i> (radar, target_elevations)	Extract cross sections from an RHI volume along one or more elevation angles.
<i>colocated_gates</i> (radar1, radar2[, h_tol, ...])	Flags radar gates of radar1 colocated with radar2
<i>intersection</i> (radar1, radar2[, h_tol, ...])	Flags region of radar1 that is intersecting with radar2 and complies with criteria regarding visibility, altitude, range, elevation angle and azimuth angle
<i>find_intersection_volume</i> (radar1, radar2[, ...])	Flags region of radar1 that is intersecting with radar2
<i>find_intersection_limits</i> (lat1, lon1, alt1, ...)	Find the limits of the intersection between two volumes
<i>find_equal_vol_region</i> (radar1, radar2[, ...])	Flags regions of radar1 that are equivolumetric (similar pulse volume diameter) with radar2
<i>get_ground_distance</i> (lat_array, lon_array, ...)	Computes the ground distance to a fixed point
<i>get_range</i> (rng_ground, alt_array, alt0)	Computes the range to a fixed point from the ground distance and the altitudes
<i>get_vol_diameter</i> (beamwidth, rng)	Computes the pulse volume diameter from the antenna beamwidth and the range from the radar
<i>_construct_xsect_radar</i> (radar, scan_type, ...)	Constructs a new radar object that contains cross-sections at fixed angles of a PPI or RHI volume scan.
<i>_copy_dic</i> (orig_dic[, excluded_keys])	Return a copy of the original dictionary copying each element.

`pyart.util.xsect._construct_xsect_radar` (*radar*, *scan_type*, *pxsect_rays*,
xsect_sweep_start_ray_index,
xsect_sweep_end_ray_index, *target_angles*)

Constructs a new radar object that contains cross-sections at fixed angles of a PPI or RHI volume scan.

Parameters

radar [Radar] Radar volume containing RHI/PPI sweeps from which a cross sections will be extracted.

scan_type [str] Type of cross section scan (ppi or rhi).

pxsect_rays [list] list of rays from the radar volume to be copied in the cross-sections radar object

xsect_sweep_start_ray_index, xsect_sweep_end_ray_index [array of ints] start and end sweep ray index of each cross-section scan

target_angles [array] the target fixed angles

Returns

radar_xsect [Radar] Radar volume containing sweeps which contain cross sections from the original volume.

`pyart.util.xsect._copy_dic (orig_dic, excluded_keys=None)`

Return a copy of the original dictionary copying each element.

`pyart.util.xsect.colocated_gates (radar1, radar2, h_tol=0.0, latlon_tol=0.0, coloc_gates_field=None)`

Flags radar gates of radar1 colocated with radar2

Parameters

radar1 [Radar] radar object that is going to be flagged

radar2 [Radar] radar object

h_tol [float] tolerance in altitude [m]

latlon_tol [float] tolerance in latitude/longitude [deg]

coloc_gates_field [string] Name of the field to retrieve the data

Returns

coloc_dict [dict] a dictionary containing the colocated positions of radar 1 (ele, azi, rng) and radar 2

coloc_rad1: field with the colocated gates of radar1 flagged, i.e: 1: not colocated gates 2: colocated (0 is reserved)

`pyart.util.xsect.cross_section_ppi (radar, target_azimuths, az_tol=None)`

Extract cross sections from a PPI volume along one or more azimuth angles.

Parameters

radar [Radar] Radar volume containing PPI sweeps from which azimuthal cross sections will be extracted.

target_azimuth [list] Azimuthal angles in degrees where cross sections will be taken.

az_tol [float, optional] Azimuth angle tolerance in degrees. If none the nearest angle is used. If valid only angles within the tolerance distance are considered.

Returns

radar_rhi [Radar] Radar volume containing RHI sweeps which contain azimuthal cross sections from the original PPI volume.

`pyart.util.xsect.cross_section_rhi (radar, target_elevations, el_tol=None)`

Extract cross sections from an RHI volume along one or more elevation angles.

Parameters

radar [Radar] Radar volume containing RHI sweeps from which azimuthal cross sections will be extracted.

target_elevations [list] Elevation angles in degrees where cross sections will be taken.

el_tol [float, optional] Elevation angle tolerance in degrees. If none the nearest angle is used. If valid only angles within the tolerance distance are considered.

Returns

radar_ppi [Radar] Radar volume containing PPI sweeps which contain azimuthal cross sections from the original RHI volume.

`pyart.util.xsect.find_equal_vol_region(radar1, radar2, vol_d_tol=0)`

Flags regions of radar1 that are equivolumetric (similar pulse volume diameter) with radar2

Parameters

radar1 [Radar] radar object that is going to be flagged

radar2 [Radar] radar object

vol_d_tol [float] pulse volume diameter tolerance

Returns

equal_vol [2D boolean array] field with true where both radars have a similar pulse volume diameter

`pyart.util.xsect.find_intersection_limits(lat1, lon1, alt1, lat2, lon2, alt2, h_tol=0.0, latlon_tol=0.0)`

Find the limits of the intersection between two volumes

Parameters

lat1, lon1, alt1 [float array] array with the positions of first volume. lat, lon in decimal degrees, alt in m MSL.

lat2, lon2, alt2 [float array] array with the positions of second volume. lat, lon in decimal degrees, alt in m MSL.

h_tol: float altitude tolerance [m MSL]

latlon_tol: float latitude and longitude tolerance [decimal deg]

Returns

min_lat, max_lat, min_lon, max_lon, min_alt, max_alt [floats] the limits of the intersecting region

`pyart.util.xsect.find_intersection_volume(radar1, radar2, h_tol=0.0, latlon_tol=0.0)`

Flags region of radar1 that is intersecting with radar2

Parameters

radar1 [Radar] radar object that is going to be flagged

radar2 [Radar] radar object checked for intersecting region

h_tol [float] tolerance in altitude [m]

latlon_tol [float] latitude and longitude tolerance [decimal deg]

Returns

intersec [2d array] the field with gates within the common volume flagged, i.e. 1: Not intersecting, 2: intersecting (0 is reserved)

`pyart.util.xsect.get_ground_distance(lat_array, lon_array, lat0, lon0)`

Computes the ground distance to a fixed point

Parameters

lat_array [float array] array of latitudes [decimal deg]

lon_array [float array] array of longitudes [decimal deg]

lat0: float latitude of fix point

lon0: float longitude of fix point

Returns

rng_ground [float array] the ground range [m]

`pyart.util.xsect.get_range(rng_ground, alt_array, alt0)`

Computes the range to a fixed point from the ground distance and the altitudes

Parameters

rng_ground [float array] array of ground distances [m]

alt_array [float array] array of altitudes [m MSL]

alt0: float altitude of fixed point [m MSL]

Returns

rng [float array] the range [m]

`pyart.util.xsect.get_vol_diameter(beamwidth, rng)`

Computes the pulse volume diameter from the antenna beamwidth and the range from the radar

Parameters

beamwidth [float] the radar beamwidth [deg]

rng [float array] the range from the radar [m]

Returns

vol_d [float array] the pulse volume diameter

`pyart.util.xsect.intersection(radar1, radar2, h_tol=0.0, latlon_tol=0.0, vol_d_tol=None, vis-
min=None, hmin=None, hmax=None, rmin=None, rmax=None,
elmin=None, elmax=None, azmin=None, azmax=None,
visib_field=None, intersec_field=None)`

Flags region of radar1 that is intersecting with radar2 and complies with criteria regarding visibility, altitude, range, elevation angle and azimuth angle

Parameters

radar1 [Radar] radar object that is going to be flagged

radar2 [Radar] radar object checked for intersecting region

h_tol [float] tolerance in altitude [m]

latlon_tol [float] latitude and longitude tolerance [decimal deg]

vol_d_tol [float] pulse volume diameter tolerance [m]

vismin [float] minimum visibility [percentage]

hmin, hmax [floats] min and max altitude [m MSL]

rmin, rmax [floats] min and max range from radar [m]

elmin, elmax [floats] min and max elevation angle [deg]

azmin, azmax [floats] min and max azimuth angle [deg]

Returns

intersec_rad1_dict [dict] the field with the gates of radar1 in the same region as radar2 flagged,
i.e.: 1 not intersecting, 2 intersecting, 0 is reserved

PYART.BRIDGE.WRADLIB

Py-ART methods linking to wradlib functions, <http://wradlib.org/>

<code>texture_of_complex_phase(radar[, ...])</code>	Calculate the texture of the differential phase field.
---	--

```
pyart.bridge.wradlib_bridge.texture_of_complex_phase(radar, phidp_field=None,
                                                    phidp_texture_field=None)
```

Calculate the texture of the differential phase field.

Calculate the texture of the real part of the complex differential phase field

Parameters

radar [Radar] Radar object from which to .

phidp_field [str, optional] Name of field in radar which contains the differential phase shift.
None will use the default field name in the Py-ART configuration file.

phidp_texture_field [str, optional] Name to use for the differential phase texture field metadata.
None will use the default field name in the Py-ART configuration file.

Returns

texture_field [dict] Field dictionary containing the texture of the real part of the complex differential phase.

References

Gourley, J. J., P. Tabary, and J. Parent du Chatelet, A fuzzy logic algorithm for the separation of precipitating from nonprecipitating echoes using polarimetric radar observations, Journal of Atmospheric and Oceanic Technology 24 (8), 1439-1451

PYART.TESTING.SAMPLE_FILES

Sample radar files in a number of formats. Many of these files are incomplete, they should only be used for testing, not production.

MDV_PPI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
MDV_RHI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
CFRADIAL_PPI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
CFRADIAL_RHI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
CHL_RHI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
SIGMET_PPI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
SIGMET_RHI_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_ARCHIVE_MSG31_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_ARCHIVE_MSG31_COMPRESSED_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_ARCHIVE_MSG1_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_LEVEL3_MSG19	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_LEVEL3_MSG163	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
NEXRAD_CDM_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
UF_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str
INTERP_SOUNDE_FILE	str(object='') -> str str(bytes_or_buffer[, encoding[, errors]]) -> str

PYART.TESTING.SAMPLE_OBJECTS

Functions for creating sample Radar and Grid objects.

<i>make_empty_ppi_radar</i> (ngates, rays_per_sweep, ...)	Return an Radar object, representing a PPI scan.
<i>make_target_radar</i> ()	Return a PPI radar with a target like reflectivity field.
<i>make_velocity_aliased_radar</i> ([alias])	Return a PPI radar with a target like reflectivity field.
<i>make_single_ray_radar</i> ()	Return a PPI radar with a single ray taken from a ARM C-SAPR Radar.
<i>make_empty_grid</i> (grid_shape, grid_limits)	Make an empty grid object without any fields or meta-data.
<i>make_target_grid</i> ()	Make a sample Grid with a rectangular target.
<i>make_storm_grid</i> ()	Make a sample Grid with a rectangular storm target.
<i>make_normal_storm</i> (sigma, mu)	Make a sample Grid with a gaussian storm target.

`pyart.testing.sample_objects.make_empty_grid(grid_shape, grid_limits)`

Make an empty grid object without any fields or metadata.

Parameters

grid_shape [3-tuple of floats] Number of points in the grid (z, y, x).

grid_limits [3-tuple of 2-tuples] Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

Returns

grid [Grid] Empty Grid object, centered near the ARM SGP site (Oklahoma).

`pyart.testing.sample_objects.make_empty_ppi_radar(ngates, rays_per_sweep, nsweeps)`

Return an Radar object, representing a PPI scan.

Parameters

ngates [int] Number of gates per ray.

rays_per_sweep [int] Number of rays in each PPI sweep.

nsweeps [int] Number of sweeps.

Returns

radar [Radar] Radar object with no fields, other parameters are set to default values.

`pyart.testing.sample_objects.make_empty_rhi_radar(ngates, rays_per_sweep, nsweeps)`

Return an Radar object, representing a RHI scan.

Parameters

ngates [int] Number of gates per ray.

rays_per_sweep [int] Number of rays in each PPI sweep.

nsweeps [int] Number of sweeps.

Returns

radar [Radar] Radar object with no fields, other parameters are set to default values.

`pyart.testing.sample_objects.make_normal_storm(sigma, mu)`

Make a sample Grid with a gaussian storm target.

`pyart.testing.sample_objects.make_single_ray_radar()`

Return a PPI radar with a single ray taken from a ARM C-SAPR Radar.

Radar object returned has 'reflectivity_horizontal', 'norm_coherent_power', 'copol_coeff', 'dp_phase_shift', 'diff_phase', and 'differential_reflectivity' fields with no metadata but a 'data' key. This radar is used for unit tests in correct modules.

`pyart.testing.sample_objects.make_storm_grid()`

Make a sample Grid with a rectangular storm target.

`pyart.testing.sample_objects.make_target_grid()`

Make a sample Grid with a rectangular target.

`pyart.testing.sample_objects.make_target_radar()`

Return a PPI radar with a target like reflectivity field.

`pyart.testing.sample_objects.make_velocity_aliased_radar(alias=True)`

Return a PPI radar with a target like reflectivity field.

Set alias to False to return a de-aliased radar.

`pyart.testing.sample_objects.make_velocity_aliased_rhi_radar(alias=True)`

Return a RHI radar with a target like reflectivity field.

Set alias to False to return a de-aliased radar.

PYART.TESTING.TMPDIRS

Classes for creating and cleaning temporary directories in unit tests.

<code>TemporaryDirectory([suffix, prefix, dir])</code>	Create and return a temporary directory.
<code>InTemporaryDirectory([suffix, prefix, dir])</code>	Create, return, and change directory to a temporary directory.
<code>InGivenDirectory([path])</code>	Change directory to given directory for duration of with block.

This module is taken from the nibable project. The following license applies:

The MIT License

```
Copyright (c) 2009-2014 Matthew Brett <matthew.brett@gmail.com>
Copyright (c) 2010-2013 Stephan Gerhard <git@unidesign.ch>
Copyright (c) 2006-2014 Michael Hanke <michael.hanke@gmail.com>
Copyright (c) 2011 Christian Haselgrove <christian.haselgrove@umassmed.edu>
Copyright (c) 2010-2011 Jarrod Millman <jarrod.millman@gmail.com>
Copyright (c) 2011-2014 Yaroslav Halchenko <debian@onerussian.com>
```

Permission **is** hereby granted, free of charge, to **any** person obtaining a copy of this software **and** associated documentation files (the "**Software**"), to deal **in** the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, **and/or** sell copies of the Software, **and** to permit persons to whom the Software **is** furnished to do so, subject to the following conditions:

The above copyright notice **and** this permission notice shall be included **in** all copies **or** substantial portions of the Software.

THE SOFTWARE IS PROVIDED "**AS IS**", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

```
class pyart.testing.tmpdirs.InGivenDirectory (path=None)
    Bases: object
```

Change directory to given directory for duration of with block. Useful when you want to use *InTemporaryDirectory* for the final test, but you are still debugging. For example, you may want to do this in the end:

```
>>> with InTemporaryDirectory() as tmpdir:
...     # do something complicated which might break
...     pass
```

But indeed the complicated thing does break, and meanwhile the `InTemporaryDirectory` context manager wiped out the directory with the temporary files that you wanted for debugging. So, while debugging, you replace with something like:

```
>>> with InGivenDirectory() as tmpdir: # Use working directory by default
...     # do something complicated which might break
...     pass
```

You can then look at the temporary file outputs to debug what is happening, fix, and finally replace `InGivenDirectory` with `InTemporaryDirectory` again.

```
__class__
    alias of builtins.type

__delattr__ (self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.testing.tmpdirs', '__doc__': '    Change

__dir__ (self, /)
    Default dir() implementation.

__enter__ (self)

__eq__ (self, value, /)
    Return self==value.

__exit__ (self, exc, value, tb)

__format__ (self, format_spec, /)
    Default object formatter.

__ge__ (self, value, /)
    Return self>=value.

__getattr__ (self, name, /)
    Return getattr(self, name).

__gt__ (self, value, /)
    Return self>value.

__hash__ (self, /)
    Return hash(self).

__init__ (self, path=None)
    Initialize directory context manager

    Parameters

        path [None or str, optional] path to change directory to, for duration of with block. De-
            faults to os.getcwd() if None.

__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)
    Return self<=value.
```


__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.testing.tmpdirs'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

class pyart.testing.tmpdirs.**InTemporaryDirectory** (*suffix*='', *prefix*='tmp', *dir*=None)
Bases: *pyart.testing.tmpdirs.TemporaryDirectory*
Create, return, and change directory to a temporary directory.

Examples

```
>>> import os
>>> my_cwd = os.getcwd()
>>> with InTemporaryDirectory() as tmpdir:
...     _ = open('test.txt', 'wt').write('some text')
...     assert os.path.isfile('test.txt')
...     assert os.path.isfile(os.path.join(tmpdir, 'test.txt'))
>>> os.path.exists(tmpdir)
False
>>> os.getcwd() == my_cwd
True
```

Methods

cleanup	
---------	--

```
__class__
    alias of builtins.type

__delattr__ (self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyart.testing.tmpdirs', '__doc__': " Create,
__dir__ (self, /)
    Default dir() implementation.

__enter__ (self)

__eq__ (self, value, /)
    Return self==value.

__exit__ (self, exc, value, tb)

__format__ (self, format_spec, /)
    Default object formatter.

__ge__ (self, value, /)
    Return self>=value.

__getattr__ (self, name, /)
    Return getattr(self, name).

__gt__ (self, value, /)
    Return self>value.

__hash__ (self, /)
    Return hash(self).

__init__ (self, suffix=", prefix='tmp', dir=None)
    Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (self, value, /)
    Return self<=value.

__lt__ (self, value, /)
    Return self<value.

__module__ = 'pyart.testing.tmpdirs'

__ne__ (self, value, /)
    Return self!=value.

__new__ (*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)
    Helper for pickle.
```

`__reduce_ex__(self, protocol, /)`

Helper for pickle.

`__repr__(self, /)`

Return repr(self).

`__setattr__(self, name, value, /)`

Implement setattr(self, name, value).

`__sizeof__(self, /)`

Size of object in memory, in bytes.

`__str__(self, /)`

Return str(self).

`__subclasshook__()`

Abstract classes can override this to customize issubclass().

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`cleanup(self)`

class `pyart.testing.tmpdirs.TemporaryDirectory(suffix="", prefix='tmp', dir=None)`

Bases: `object`

Create and return a temporary directory. This has the same behavior as `mkdtemp` but can be used as a context manager.

Upon exiting the context, the directory and everything contained in it are removed.

Examples

```
>>> import os
>>> with TemporaryDirectory() as tmpdir:
...     fname = os.path.join(tmpdir, 'example_file.txt')
...     with open(fname, 'wt') as fobj:
...         _ = fobj.write('a string\n')
>>> os.path.exists(tmpdir)
False
```

Methods

cleanup	
---------	--

`__class__`

alias of `builtins.type`

`__delattr__(self, name, /)`

Implement delattr(self, name).

`__dict__ = mappingproxy({'__module__': 'pyart.testing.tmpdirs', '__doc__': " Create`

__dir__ (*self*, /)
Default dir() implementation.

__enter__ (*self*)

__eq__ (*self*, *value*, /)
Return self==value.

__exit__ (*self*, *exc*, *value*, *tb*)

__format__ (*self*, *format_spec*, /)
Default object formatter.

__ge__ (*self*, *value*, /)
Return self>=value.

__getattr__ (*self*, *name*, /)
Return getattr(self, name).

__gt__ (*self*, *value*, /)
Return self>value.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, *suffix*=", *prefix*='tmp', *dir*=None)
Initialize self. See help(type(self)) for accurate signature.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyart.testing.tmpdirs'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__()

Abstract classes can override this to customize `issubclass()`.

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

cleanup (*self*)

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

BIBLIOGRAPHY

- [1] <http://www.ncdc.noaa.gov/>
- [2] http://www.roc.noaa.gov/wsr88d/Level_III/Level3Info.asp
- [1] <http://www.ncdc.noaa.gov/>
- [2] <http://thredds.ucar.edu/thredds/catalog.html>
- [1] <http://www.unidata.ucar.edu/software/netcdf-java/documentation.htm>
- [2] <http://thredds.ucar.edu/thredds/catalog.html>
- [Rac8a56e97c0b-1] http://www.roc.noaa.gov/WSR88D/Level_II/Level2Info.aspx
- [Rac8a56e97c0b-2] <http://www.ncdc.noaa.gov/>
- [Rac8a56e97c0b-3] <http://thredds.ucar.edu/thredds/catalog.html>
- [1] Miguel Arevallilo Herraiez, David R. Burton, Michael J. Lalor, and Munther A. Gdeisat, “Fast two-dimensional phase-unwrapping algorithm based on sorting by reliability following a noncontinuous path”, *Journal Applied Optics*, Vol. 41, No. 35 (2002) 7437,
- [2] Abdul-Rahman, H., Gdeisat, M., Burton, D., & Lalor, M., “Fast three-dimensional phase-unwrapping algorithm based on sorting by reliability following a non-continuous path. In W. Osten, C. Gorecki, & E. L. Novak (Eds.), *Optical Metrology* (2005) 32–40, International Society for Optics and Photonics.

PYTHON MODULE INDEX

p

pyart.aux_io.arm_vpt, ??
pyart.aux_io.cfl, ??
pyart.aux_io.d3r_gcpx_nc, ??
pyart.aux_io.edge_netcdf, ??
pyart.aux_io.gamic_hdf5, ??
pyart.aux_io.gamicfile, ??
pyart.aux_io.metranet_c, ??
pyart.aux_io.metranet_cartesian_reader, ??
pyart.aux_io.metranet_python, ??
pyart.aux_io.metranet_reader, ??
pyart.aux_io.noxp_iphex_nc, ??
pyart.aux_io.odim_h5, ??
pyart.aux_io.odim_h5_writer, ??
pyart.aux_io.pattern, ??
pyart.aux_io.rad4alp_bin_reader, ??
pyart.aux_io.rad4alp_gif_reader, ??
pyart.aux_io.rad4alp_iq_reader, ??
pyart.aux_io.radx, ??
pyart.aux_io.rainbow_psr, ??
pyart.aux_io.rainbow_wrl, ??
pyart.aux_io.sinarame_h5, ??
pyart.aux_io.spectra, ??
pyart.bridge.wradlib_bridge, ??
pyart.core.grid, ??
pyart.core.radar, ??
pyart.core.radar_spectra, ??
pyart.core.wind_profile, ??
pyart.correct._common_dealias, ??
pyart.correct._fast_edge_finder, ??
pyart.correct._fourdd_interface, ??
pyart.correct._unwrap_1d, ??
pyart.correct._unwrap_2d, ??
pyart.correct._unwrap_3d, ??
pyart.correct.attenuation, ??
pyart.correct.bias_and_noise, ??
pyart.correct.dealias, ??
pyart.correct.despeckle, ??
pyart.correct.phase_proc, ??
pyart.correct.region_dealias, ??
pyart.correct.sunlib, ??
pyart.correct.unwrap, ??
pyart.filters.gatefilter, ??
pyart.graph._cm, ??
pyart.graph.cm, ??
pyart.graph.cm_colorblind, ??
pyart.graph.common, ??
pyart.graph.gridmapdisplay, ??
pyart.graph.radardisplay, ??
pyart.graph.radardisplay_airborne, ??
pyart.graph.radarmapdisplay, ??
pyart.io._rsl_interface, ??
pyart.io._sigmet_noaa_hh, ??
pyart.io._sigmetfile, ??
pyart.io.arm_sonde, ??
pyart.io.auto_read, ??
pyart.io.cfradial, ??
pyart.io.cfradial2, ??
pyart.io.chl, ??
pyart.io.common, ??
pyart.io.grid_io, ??
pyart.io.mdv_common, ??
pyart.io.mdv_grid, ??
pyart.io.mdv_radar, ??
pyart.io.nexrad_archive, ??
pyart.io.nexrad_cdm, ??
pyart.io.nexrad_common, ??
pyart.io.nexrad_interpolate, ??
pyart.io.nexrad_level2, ??
pyart.io.nexrad_level3, ??
pyart.io.nexradl3_read, ??
pyart.io.output_to_geotiff, ??
pyart.io.rsl, ??
pyart.io.sigmet, ??
pyart.io.uf, ??
pyart.io.uf_write, ??
pyart.io.uffile, ??
pyart.map._gate_to_grid_map, ??
pyart.map.gates_to_grid, ??
pyart.map.grid_mapper, ??
pyart.map.polar_to_cartesian, ??
pyart.retrieve._kdp_proc, ??
pyart.retrieve.advection, ??

```
pyart.retrieve.echo_class, ??
pyart.retrieve.gate_id, ??
pyart.retrieve.iq, ??
pyart.retrieve.kdp_proc, ??
pyart.retrieve.ml, ??
pyart.retrieve.qpe, ??
pyart.retrieve.qvp, ??
pyart.retrieve.simple_moment_calculations,
    ??
pyart.retrieve.spectra, ??
pyart.retrieve.vad, ??
pyart.retrieve.wind, ??
pyart.testing.sample_files, ??
pyart.testing.sample_objects, ??
pyart.testing.tmpdirs, ??
pyart.util.circular_stats, ??
pyart.util.datetime_utils, ??
pyart.util.hildebrand_sekhon, ??
pyart.util.ivic, ??
pyart.util.met, ??
pyart.util.radar_utils, ??
pyart.util.sigmath, ??
pyart.util.simulated_vel, ??
pyart.util.xsect, ??
```