
pyrad library reference for users

Release 0.1.0

meteoswiss-mdr

Feb 07, 2019

CONTENTS

1	processing flow control (<code>pyrad.flow</code>)	3
2	Dataset processing (<code>pyrad.proc</code>)	5
2.1	Auxiliary functions	5
2.2	Echo classification and filtering	5
2.3	Phase processing and attenuation correction	6
2.4	Monitoring, calibration and noise correction	6
2.5	Retrievals	7
2.6	Doppler processing	7
2.7	Time series functions	8
2.8	Trajectory functions	8
2.9	COSMO data	8
3	Products generation (<code>pyrad.prod</code>)	45
3.1	Auxiliary functions	45
3.2	Product generation	45
4	Input and output (<code>pyrad.io</code>)	49
4.1	Reading configuration files	49
4.2	Reading radar data	49
4.3	Reading cosmo data	49
4.4	Reading other data	49
4.5	Writing data	51
4.6	Auxiliary functions	51
4.7	Trajectory	52
4.8	TimeSeries	52
5	Plotting (<code>pyrad.graph</code>)	79
5.1	Plots	79
6	Utilities (<code>pyrad.util</code>)	95
6.1	Radar Utilities	95
7	Indices and tables	105
	Python Module Index	107
	Index	109

Contents:

PROCESSING FLOW CONTROL (PYRAD.FLOW)

Functions to control the Pyrad data processing flow

<code>main(cfgfile[, starttime, endtime, ...])</code>	Main flow control.
<code>main_rt(cfgfile_list[, starttime, endtime, ...])</code>	main flow control.

`pyrad.flow.main` (*cfgfile*, *starttime=None*, *endtime=None*, *trajfile=""*, *trajtype='plane'*, *flashnr=0*, *infostr=""*, *MULTIPROCESSING_DSET=False*, *MULTIPROCESSING_PROD=False*, *PROFILE_MULTIPROCESSING=False*)

Main flow control. Processes radar data off-line over a period of time given either by the user, a trajectory file, or determined by the last volume processed and the current time. Multiple radars can be processed simultaneously

Parameters

cfgfile [str] path of the main config file

starttime, endtime [datetime object] start and end time of the data to be processed

trajfile [str] path to file describing the trajectory

trajtype [str] type of trajectory file. Can be either 'plane' or 'lightning'

flashnr [int] If larger than 0 will select a flash in a lightning trajectory file. If 0 the data corresponding to the trajectory of all flashes will be plotted

infostr [str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

MULTIPROCESSING_DSET [Bool] If true the generation of datasets at the same processing level will be parallelized

MULTIPROCESSING_PROD [Bool] If true the generation of products from each dataset will be parallelized

`pyrad.flow.main_rt` (*cfgfile_list*, *starttime=None*, *endtime=None*, *infostr_list=None*, *proc_period=60*, *proc_finish=None*)

main flow control. Processes radar data in real time. The start and end processing times can be determined by the user. This function is intended for a single radar

Parameters

cfgfile_list [list of str] path of the main config files

starttime, endtime [datetime object] start and end time of the data to be processed

infostr_list [list of str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

proc_period [int] period of time before starting a new processing round (seconds)

cronjob_controlled [Boolean] If True means that the program is started periodically from a cronjob and therefore finishes execution after processing

proc_finish [int or None] if set to a value the program will be forced to shut down after the value (in seconds) from start time has been exceeded

Returns

end_proc [Boolean] If true the program has ended successfully

DATASET PROCESSING (PYRAD . PROC)

Initiate the dataset processing.

2.1 Auxiliary functions

<i>get_process_func</i> (dataset_type, dsname)	Maps the dataset type into its processing function and data set format associated.
<i>process_raw</i> (procstatus, dscfg[, radar_list])	Dummy function that returns the initial input data set
<i>process_save_radar</i> (procstatus, dscfg[, ...])	Dummy function that allows to save the entire radar object
<i>process_roi</i> (procstatus, dscfg[, radar_list])	Obtains the radar data at a region of interest.
<i>process_grid</i> (procstatus, dscfg[, radar_list])	Puts the radar data in a regular grid
<i>process_azimuthal_average</i> (procstatus, dscfg)	Averages radar data in azimuth obtaining and RHI as a result

2.2 Echo classification and filtering

<i>process_echo_id</i> (procstatus, dscfg[, radar_list])	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation
<i>process_birds_id</i> (procstatus, dscfg[, radar_list])	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Birds
<i>process_clt_to_echo_id</i> (procstatus, dscfg[, ...])	Converts clutter exit code from rad4alp into pyrad echo ID
<i>process_echo_filter</i> (procstatus, dscfg[, ...])	Masks all echo types that are not of the class specified in keyword echo_type
<i>process_cdf</i> (procstatus, dscfg[, radar_list])	Collects the fields necessary to compute the Cumulative Distribution Function
<i>process_filter_snr</i> (procstatus, dscfg[, ...])	filters out low SNR echoes
<i>process_filter_visibility</i> (procstatus, dscfg)	filters out rays gates with low visibility and corrects the reflectivity
<i>process_outlier_filter</i> (procstatus, dscfg[, ...])	filters out gates which are outliers respect to the surrounding
<i>process_hydroclass</i> (procstatus, dscfg[, ...])	Classifies precipitation echoes
<i>process_melting_layer</i> (procstatus, dscfg[, ...])	Detects the melting layer

Continued on next page

Table 2 – continued from previous page

<code>process_filter_vel_diff(procstatus, dscfg[, ...])</code>	filters out range gates that could not be used for Doppler velocity estimation
<code>process_zdr_column(procstatus, dscfg[, ...])</code>	Detects ZDR columns

2.3 Phase processing and attenuation correction

<code>process_correct_phidp0(procstatus, dscfg[, ...])</code>	corrects phidp of the system phase
<code>process_smooth_phidp_single_window(...[, ...])</code>	corrects phidp of the system phase and smoothes it using one window
<code>process_smooth_phidp_double_window(...[, ...])</code>	corrects phidp of the system phase and smoothes it using one window
<code>process_kdp_leastsquare_single_window(...[, ...])</code>	Computes specific differential phase using a piecewise least square method
<code>process_kdp_leastsquare_double_window(...[, ...])</code>	Computes specific differential phase using a piecewise least square method
<code>process_phidp_kdp_Vulpiani(procstatus, dscfg)</code>	Computes specific differential phase and differential phase using the method developed by Vulpiani et al.
<code>process_phidp_kdp_Kalman(procstatus, dscfg)</code>	Computes specific differential phase and differential phase using the Kalman filter as proposed by Schneebeli et al.
<code>process_phidp_kdp_Maesaka(procstatus, dscfg)</code>	Estimates PhiDP and KDP using the method by Maesaka.
<code>process_phidp_kdp_lp(procstatus, dscfg[, ...])</code>	Estimates PhiDP and KDP using a linear programming algorithm.
<code>process_attenuation(procstatus, dscfg[, ...])</code>	Computes specific attenuation and specific differential attenuation using the Z-Phi method and corrects reflectivity and differential reflectivity

2.4 Monitoring, calibration and noise correction

<code>process_correct_bias(procstatus, dscfg[, ...])</code>	Corrects a bias on the data
<code>process_correct_noise_rhohv(procstatus, dscfg)</code>	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation
<code>process_rhohv_rain(procstatus, dscfg[, ...])</code>	Keeps only suitable data to evaluate the 80 percentile of RhoHV in rain
<code>process_zdr_precip(procstatus, dscfg[, ...])</code>	Keeps only suitable data to evaluate the differential reflectivity in moderate rain or precipitation (for vertical scans)
<code>process_zdr_snow(procstatus, dscfg[, radar_list])</code>	Keeps only suitable data to evaluate the differential reflectivity in snow
<code>process_estimate_phidp0(procstatus, dscfg[, ...])</code>	estimates the system differential phase offset at each ray
<code>process_sun_hits(procstatus, dscfg[, radar_list])</code>	monitoring of the radar using sun hits
<code>process_selfconsistency_kdp_phidp(...[, ...])</code>	Computes specific differential phase and differential phase in rain using the selfconsistency between Zdr, Zh and KDP

Continued on next page

Table 4 – continued from previous page

<i>process_selfconsistency_bias</i> (procstatus, dscfg)	Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley
<i>process_occurrence</i> (procstatus, dscfg[, ...])	computes the frequency of occurrence of data.
<i>process_occurrence_period</i> (procstatus, dscfg)	computes the frequency of occurrence over a long period of time by adding together shorter periods
<i>process_monitoring</i> (procstatus, dscfg[, ...])	computes monitoring statistics
<i>process_gc_monitoring</i> (procstatus, dscfg[, ...])	computes ground clutter monitoring statistics
<i>process_time_avg</i> (procstatus, dscfg[, radar_list])	computes the temporal mean of a field
<i>process_weighted_time_avg</i> (procstatus, dscfg)	computes the temporal mean of a field weighted by the reflectivity
<i>process_time_avg_flag</i> (procstatus, dscfg[, ...])	computes a flag field describing the conditions of the data used while averaging
<i>process_colocated_gates</i> (procstatus, dscfg[, ...])	Find colocated gates within two radars
<i>process_intercomp</i> (procstatus, dscfg[, ...])	intercomparison between two radars
<i>process_intercomp_time_avg</i> (procstatus, dscfg)	intercomparison between the average reflectivity of two radars

2.5 Retrievals

<i>process_signal_power</i> (procstatus, dscfg[, ...])	Computes the signal power in dBm
<i>process_rcs</i> (procstatus, dscfg[, radar_list])	Computes the radar cross-section (assuming a point target) from radar reflectivity.
<i>process_rcs_pr</i> (procstatus, dscfg[, radar_list])	Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.
<i>process_snr</i> (procstatus, dscfg[, radar_list])	Computes SNR
<i>process_l</i> (procstatus, dscfg[, radar_list])	Computes L parameter
<i>process_cdr</i> (procstatus, dscfg[, radar_list])	Computes Circular Depolarization Ratio
<i>process_rainrate</i> (procstatus, dscfg[, radar_list])	Estimates rainfall rate from polarimetric moments
<i>process_vol_refl</i> (procstatus, dscfg[, radar_list])	Computes the volumetric reflectivity in $10\log_{10}(\text{cm}^2 \text{ km}^{-3})$
<i>process_bird_density</i> (procstatus, dscfg[, ...])	Computes the bird density from the volumetric reflectivity

2.6 Doppler processing

<i>process_dealias_fourdd</i> (procstatus, dscfg[, ...])	Dealiases the Doppler velocity field using the 4DD technique from Curtis and Houze, 2001
<i>process_dealias_region_based</i> (procstatus, dscfg)	Dealiases the Doppler velocity field using a region based algorithm
<i>process_dealias_unwrap_phase</i> (procstatus, dscfg)	Dealiases the Doppler velocity field using multi-dimensional phase unwrapping
<i>process_wind_vel</i> (procstatus, dscfg[, radar_list])	Estimates the horizontal or vertical component of the wind from the radial velocity
<i>process_windshear</i> (procstatus, dscfg[, ...])	Estimates the wind shear from the wind velocity

Continued on next page

Table 6 – continued from previous page

<code>process_vad(procstatus, dscfg[, radar_list])</code>	Estimates vertical wind profile using the VAD (velocity Azimuth Display) technique
-----------------------------------------------------------	------------------------------------------------------------------------------------

2.7 Time series functions

<code>process_point_measurement(procstatus, dscfg)</code>	Obtains the radar data at a point location.
<code>process_qvp(procstatus, dscfg[, radar_list])</code>	Computes quasi vertical profiles, by averaging over height levels PPI data.
<code>process_rqvp(procstatus, dscfg[, radar_list])</code>	Computes range defined quasi vertical profiles, by averaging over height levels PPI data.
<code>process_svp(procstatus, dscfg[, radar_list])</code>	Computes slanted vertical profiles, by averaging over height levels PPI data.
<code>process_evp(procstatus, dscfg[, radar_list])</code>	Computes enhanced vertical profiles, by averaging over height levels PPI data.
<code>process_time_height(procstatus, dscfg[, ...])</code>	Produces time height radar objects at a point of interest defined by latitude and longitude.

2.8 Trajectory functions

<code>process_trajectory(procstatus, dscfg[, ...])</code>	Return trajectory
<code>process_traj_atplane(procstatus, dscfg[, ...])</code>	Return time series according to trajectory
<code>process_traj_antenna_pattern(procstatus, dscfg)</code>	Process a new array of data volumes considering a plane trajectory.
<code>process_traj_lightning(procstatus, dscfg[, ...])</code>	Return time series according to lightning trajectory
<code>process_traj_trt(procstatus, dscfg[, ...])</code>	Processes data according to TRT trajectory

2.9 COSMO data

<code>process_cosmo(procstatus, dscfg[, radar_list])</code>	Gets COSMO data and put it in radar coordinates
<code>process_cosmo_lookup_table(procstatus, dscfg)</code>	Gets COSMO data and put it in radar coordinates using look up tables computed or loaded when initializing
<code>process_cosmo_coord(procstatus, dscfg[, ...])</code>	Gets the COSMO indices corresponding to each cosmo coordinates
<code>process_hzt(procstatus, dscfg[, radar_list])</code>	Gets iso0 degree data in HZT format and put it in radar coordinates
<code>process_hzt_lookup_table(procstatus, dscfg)</code>	Gets HZT data and put it in radar coordinates using look up tables computed or loaded when initializing
<code>process_hzt_coord(procstatus, dscfg[, ...])</code>	Gets the HZT indices corresponding to each HZT coordinates

`pyrad.proc.get_process_func(dataset_type, dsname)`

Maps the dataset type into its processing function and data set format associated.

Parameters

dataset_type [str] data set type, i.e. ‘RAW’, ‘SAN’, etc.

dsname [str] Name of dataset

Returns

func_name [str or processing function] pyrad function used to process the data set type

dsformat [str] data set format, i.e.: ‘VOL’, etc.

`pyrad.proc.process_attenuation` (*procstatus, dscfg, radar_list=None*)

Computes specific attenuation and specific differential attenuation using the Z-Phi method and corrects reflectivity and differential reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

ATT_METHOD [float. Dataset keyword] The attenuation estimation method used. One of the following: ZPhi, Philin

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_azimuthal_average` (*procstatus, dscfg, radar_list=None*)

Averages radar data in azimuth obtaining and RHI as a result

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

gridconfig [dictionary. Dataset keyword] Dictionary containing some or all of this keywords: xmin, xmax, ymin, ymax, zmin, zmax : floats

minimum and maximum horizontal distance from grid origin [km] and minimum and maximum vertical distance from grid origin [m] Defaults -40, 40, -40, 40, 0., 10000.

hres, vres [floats] horizontal and vertical grid resolution [m] Defaults 1000., 500.

latorig, lonorig, altorig [floats] latitude and longitude of grid origin [deg] and altitude of grid origin [m MSL] Defaults the latitude, longitude and altitude of the radar

wfunc [str] the weighting function used to combine the radar gates close to a grid point. Possible values BARNES, CRESSMAN, NEAREST_NEIGHBOUR Default NEAREST_NEIGHBOUR

roif_func [str] the function used to compute the region of interest. Possible values:
dist_beam, constant

roi [float] the (minimum) radius of the region of interest in m. Default half the largest resolution

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the gridded data

ind_rad [int] radar index

`pyrad.proc.process_bird_density` (*procstatus, dscfg, radar_list=None*)

Computes the bird density from the volumetric reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

sigma_bird [float. Dataset keyword] The bird radar cross section

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_birds_id` (*procstatus, dscfg, radar_list=None*)

identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Birds

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cdf` (*procstatus, dscfg, radar_list=None*)

Collects the fields necessary to compute the Cumulative Distribution Function

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cdr` (*procstatus, dscfg, radar_list=None*)

Computes Circular Depolarization Ratio

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_clt_to_echo_id` (*procstatus, dscfg, radar_list=None*)

Converts clutter exit code from rad4alp into pyrad echo ID

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_colocated_gates` (*procstatus, dscfg, radar_list=None*)

Find colocated gates within two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

h_tol [float. Dataset keyword] Tolerance in altitude difference between radar gates [m]. Default 100.

latlon_tol [float. Dataset keyword] Tolerance in latitude and longitude position between radar gates [deg]. Default 0.0005

vol_d_tol [float. Dataset keyword] Tolerance in pulse volume diameter [m]. Default 100.

vismin [float. Dataset keyword] Minimum visibility [percent]. Default None.

hmin [float. Dataset keyword] Minimum altitude [m MSL]. Default None.

hmax [float. Dataset keyword] Maximum altitude [m MSL]. Default None.

rmin [float. Dataset keyword] Minimum range [m]. Default None.

rmax [float. Dataset keyword] Maximum range [m]. Default None.

elmin [float. Dataset keyword] Minimum elevation angle [deg]. Default None.

elmax [float. Dataset keyword] Maximum elevation angle [deg]. Default None.

azrad1min [float. Dataset keyword] Minimum azimuth angle [deg] for radar 1. Default None.

azrad1max [float. Dataset keyword] Maximum azimuth angle [deg] for radar 1. Default None.

azrad2min [float. Dataset keyword] Minimum azimuth angle [deg] for radar 2. Default None.

azrad2max [float. Dataset keyword] Maximum azimuth angle [deg] for radar 2. Default None.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [radar object] radar object containing the flag field

ind_rad [int] radar index

`pyrad.proc.process_correct_bias` (*procstatus*, *dscfg*, *radar_list=None*)
Corrects a bias on the data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type to correct for bias

bias [float. Dataset keyword] The bias to be corrected [dB]. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_correct_noise_rho_hv` (*procstatus*, *dscfg*, *radar_list=None*)
identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The data types used in the correction

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_correct_phidp0` (*procstatus*, *dscfg*, *radar_list=None*)
corrects phidp of the system phase

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]

rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]

Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]

Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo` (*procstatus*, *dscfg*, *radar_list=None*)

Gets COSMO data and put it in radar coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

keep_in_memory [int. Dataset keyword] if set keeps the COSMO data dict, the COSMO coordinates dict and the COSMO field in radar coordinates in memory

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and there is no need to compute a new COSMO field if the COSMO data has not changed

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields. Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo_coord` (*procstatus*, *dscfg*, *radar_list=None*)

Gets the COSMO indices corresponding to each cosmo coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

cosmopath [string. General keyword] path where to store the look up table

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo_lookup_table` (*procstatus, dscfg, radar_list=None*)

Gets COSMO data and put it in radar coordinates using look up tables computed or loaded when initializing

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

lookup_table [int. Dataset keyword] if set a pre-computed look up table for the COSMO coordinates is loaded. Otherwise the look up table is computed taking the first radar object as reference

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and therefore there is no need to interpolate the COSMO field in memory to the current radar grid

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields. Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_dealias_fourdd` (*procstatus, dscfg, radar_list=None*)

Dealiases the Doppler velocity field using the 4DD technique from Curtis and Houze, 2001

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

filt [int. Dataset keyword] Flag controlling Bergen and Albers filter, 1 = yes, 0 = no.

sign [int. Dataset keyword] Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_dealias_region_based` (*procstatus, dscfg, radar_list=None*)

Dealiases the Doppler velocity field using a region based algorithm

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

interval_splits [int, optional] Number of segments to split the nyquist interval into when finding regions of similar velocity. More splits creates a larger number of initial regions which takes longer to process but may result in better dealiasing. The default value of 3 seems to be a good compromise between performance and artifact free dealiasing. This value is not used if the `interval_limits` parameter is not None.

skip_between_rays, skip_along_ray [int, optional] Maximum number of filtered gates to skip over when joining regions, gaps between region larger than this will not be connected. Parameters specify the maximum number of filtered gates between and along a ray. Set these parameters to 0 to disable unfolding across filtered gates.

centered [bool, optional] True to apply centering to each sweep after the dealiasing algorithm so that the average number of unfolding is near 0. False does not apply centering which may results in individual sweeps under or over folded by the nyquist interval.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_dealias_unwrap_phase(procstatus, dscfg, radar_list=None)`

Dealiases the Doppler velocity field using multi-dimensional phase unwrapping

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

unwrap_unit [{‘ray’, ‘sweep’, ‘volume’}, optional] Unit to unwrap independently. ‘ray’ will unwrap each ray individually, ‘sweep’ each sweep, and ‘volume’ will unwrap the entire volume in a single pass. ‘sweep’, the default, often gives superior results when the lower sweeps of the radar volume are contaminated by clutter. ‘ray’ does not use the `gatefilter` parameter and rays where gates are masked will result in poor dealiasing for that ray.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echo_filter(procstatus, dscfg, radar_list=None)`

Masks all echo types that are not of the class specified in keyword `echo_type`

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

echo_type [int] The type of echo to keep: 1 noise, 2 clutter, 3 precipitation. Default 3

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echo_id (procstatus, dscfg, radar_list=None)`
identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_estimate_phidp0 (procstatus, dscfg, radar_list=None)`
estimates the system differential phase offset at each ray

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]

rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]

Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]

Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_evp (procstatus, dscfg, radar_list=None)`
Computes enhanced vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

lat, lon [float] latitude and longitude of the point of interest [deg]

latlon_tol [float] tolerance in latitude and longitude in deg. Default 0.0005

delta_rng, delta_azi [float] maximum range distance [m] and azimuth distance [degree] from the central point of the evp containing data to average. Default 5000. and 10.

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 250.

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to consider the data valid when performing the averaging. Default 1

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. Default ‘none’. ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the EVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_filter_snr (procstatus, dscfg, radar_list=None)`
filters out low SNR echoes

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

SNRmin [float. Dataset keyword] The minimum SNR to keep the data.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_filter_vel_diff (procstatus, dscfg, radar_list=None)`
filters out range gates that could not be used for Doppler velocity estimation

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

SNRmin [float. Dataset keyword] The minimum SNR to keep the data.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_filter_visibility` (*procstatus, dscfg, radar_list=None*)

filters out rays gates with low visibility and corrects the reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

VISmin [float. Dataset keyword] The minimum visibility to keep the data.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_gc_monitoring` (*procstatus, dscfg, radar_list=None*)

computes ground clutter monitoring statistics

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

excessgatespath [str. Config keyword] The path to the gates in excess of quantile location

excessgates_fname [str. Dataset keyword] The name of the gates in excess of quantile file

datatype [list of string. Dataset keyword] The input data types

step [float. Dataset keyword] The width of the histogram bin. Default is None. In that case the default step in function `get_histogram_bins` is used

regular_grid [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not. Default False

val_min [Float. Dataset keyword] Minimum value to consider that the gate has signal. Default None

filter_prec [str. Dataset keyword] Give which type of volume should be filtered. None, no filtering; keep_wet, keep wet volumes; keep_dry, keep dry volumes.

rmax_prec [float. Dataset keyword] Maximum range to consider when looking for wet gates [m]

percent_prec_max [float. Dataset keyword] Maxim percentage of wet gates to consider the volume dry

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object containing histogram data

ind_rad [int] radar index

`pyrad.proc.process_grid` (*procstatus, dscfg, radar_list=None*)

Puts the radar data in a regular grid

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

gridconfig [dictionary. Dataset keyword] Dictionary containing some or all of this keywords: xmin, xmax, ymin, ymax, zmin, zmax : floats

minimum and maximum horizontal distance from grid origin [km] and minimum and maximum vertical distance from grid origin [m] Defaults -40, 40, -40, 40, 0., 10000.

hres, vres [floats] horizontal and vertical grid resolution [m] Defaults 1000., 500.

latorig, lonorig, altorig [floats] latitude and longitude of grid origin [deg] and altitude of grid origin [m MSL] Defaults the latitude, longitude and altitude of the radar

wfunc [str] the weighting function used to combine the radar gates close to a grid point. Possible values BARNES, CRESSMAN, NEAREST_NEIGHBOUR Default NEAREST_NEIGHBOUR

roif_func [str] the function used to compute the region of interest. Possible values: dist_beam, constant

roi [float] the (minimum) radius of the region of interest in m. Default half the largest resolution

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the gridded data

ind_rad [int] radar index

`pyrad.proc.process_hydroclass` (*procstatus, dscfg, radar_list=None*)

Classifies precipitation echoes

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

HYDRO_METHOD [string. Dataset keyword] The hydrometeor classification method. One of the following: SEMISUPERVISED

RADARCENTROIDS [string. Dataset keyword] Used with HYDRO_METHOD SEMISUPERVISED. The name of the radar of which the derived centroids will be used. One of the following: A Albis, L Lema, P Plaine Morte, DX50

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_hzt` (*procstatus, dscfg, radar_list=None*)

Gets iso0 degree data in HZT format and put it in radar coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

keep_in_memory [int. Dataset keyword] if set keeps the COSMO data dict, the COSMO coordinates dict and the COSMO field in radar coordinates in memory

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and there is no need to compute a new COSMO field if the COSMO data has not changed

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields. Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_hzt_coord` (*procstatus, dscfg, radar_list=None*)

Gets the HZT indices corresponding to each HZT coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

cosmopath [string. General keyword] path where to store the look up table

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_hzt_lookup_table` (*procstatus, dscfg, radar_list=None*)

Gets HZT data and put it in radar coordinates using look up tables computed or loaded when initializing

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

lookup_table [int. Dataset keyword] if set a pre-computed look up table for the COSMO coordinates is loaded. Otherwise the look up table is computed taking the first radar object as reference

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and therefore there is no need to interpolate the COSMO field in memory to the current radar grid

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_intercomp` (*procstatus, dscfg, radar_list=None*)
intercomparison between two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

coloc_data_dir [string. Dataset keyword] name of the directory containing the csv file with colocated data

coloc_radars_name [string. Dataset keyword] string identifying the radar names

azi_tol [float. Dataset keyword] azimuth tolerance between the two radars. Default 0.5 deg

ele_tol [float. Dataset keyword] elevation tolerance between the two radars. Default 0.5 deg

rng_tol [float. Dataset keyword] range tolerance between the two radars. Default 50 m

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a dictionary with intercomparison data and the key “final” which contains a boolean that is true when all volumes have been processed

ind_rad [int] radar index

`pyrad.proc.process_intercomp_time_avg` (*procstatus, dscfg, radar_list=None*)
intercomparison between the average reflectivity of two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

coloc_data_dir [string. Dataset keyword] name of the directory containing the csv file with colocated data

coloc_radars_name [string. Dataset keyword] string identifying the radar names

azi_tol [float. Dataset keyword] azimuth tolerance between the two radars. Default 0.5 deg

ele_tol [float. Dataset keyword] elevation tolerance between the two radars. Default 0.5 deg

rng_tol [float. Dataset keyword] range tolerance between the two radars. Default 50 m

clt_max [int. Dataset keyword] maximum number of samples that can be clutter contaminated. Default 100 i.e. all

phi_excess_max [int. Dataset keyword] maximum number of samples that can have excess instantaneous PhiDP. Default 100 i.e. all

non_rain_max [int. Dataset keyword] maximum number of samples that can be no rain. Default 100 i.e. all

phi_avg_max [float. Dataset keyword] maximum average PhiDP allowed. Default 600 deg i.e. any

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a dictionary with intercomparison data and the key “final” which contains a boolean that is true when all volumes have been processed

ind_rad [int] radar index

`pyrad.proc.process_kdp_leastsquare_double_window(procstatus, dscfg, radar_list=None)`

Computes specific differential phase using a piecewise least square method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rwinds [float. Dataset keyword] The length of the short segment for the least square method [m]

rwindl [float. Dataset keyword] The length of the long segment for the least square method [m]

Zthr [float. Dataset keyword] The threshold defining which estimated data to use [dBZ]

vectorize [Bool. Dataset keyword] Whether to vectorize the KDP processing. Default false

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_kdp_leastsquare_single_window(procstatus, dscfg, radar_list=None)`

Computes specific differential phase using a piecewise least square method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rwind [float. Dataset keyword] The length of the segment for the least square method [m]

vectorize [bool. Dataset keyword] Whether to vectorize the KDP processing. Default false

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_1` (*procstatus, dscfg, radar_list=None*)

Computes L parameter

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_melting_layer` (*procstatus, dscfg, radar_list=None*)

Detects the melting layer

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring` (*procstatus, dscfg, radar_list=None*)

computes monitoring statistics

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

step [float. Dataset keyword] The width of the histogram bin. Default is None. In that case the default step in function `get_histogram_bins` is used

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object containing histogram data

ind_rad [int] radar index

`pyrad.proc.process_occurrence` (*procstatus, dscfg, radar_list=None*)

computes the frequency of occurrence of data. It looks only for gates where data is present.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- regular_grid** [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not. Default False
- rmin, rmax** [float. Dataset keyword] minimum and maximum ranges where the computation takes place. If -1 the whole range is considered. Default is -1
- val_min** [Float. Dataset keyword] Minimum value to consider that the gate has signal. Default None
- filter_prec** [str. Dataset keyword] Give which type of volume should be filtered. None, no filtering; keep_wet, keep wet volumes; keep_dry, keep dry volumes.
- rmax_prec** [float. Dataset keyword] Maximum range to consider when looking for wet gates [m]
- percent_prec_max** [float. Dataset keyword] Maxim percentage of wet gates to consider the volume dry

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_occurrence_period(procstatus, dscfg, radar_list=None)`
computes the frequency of occurrence over a long period of time by adding together shorter periods

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- regular_grid** [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not. Default False
- rmin, rmax** [float. Dataset keyword] minimum and maximum ranges where the computation takes place. If -1 the whole range is considered. Default is -1

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_outlier_filter(procstatus, dscfg, radar_list=None)`
filters out gates which are outliers respect to the surrounding

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- threshold** [float. Dataset keyword] The distance between the value of the examined range gate and the median of the surrounding gates to consider the gate an outlier

nb [int. Dataset keyword] The number of neighbours (to one side) to analyse. i.e. 2 would correspond to 24 gates

nb_min [int. Dataset keyword] Minimum number of neighbouring gates to consider the examined gate valid

percentile_min, percentile_max [float. Dataset keyword] gates below (above) these percentiles (computed over the sweep) are considered potential outliers and further examined

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phidp_kdp_Kalman(procstatus, dscfg, radar_list=None)`

Computes specific differential phase and differential phase using the Kalman filter as proposed by Schneebeli et al. The data is assumed to be clutter free and continuous

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

parallel [boolean. Dataset keyword] if set use parallel computing

get_phidp [boolean. Dataset keyword] if set the PhiDP computed by integrating the resultant KDP is added to the radar field

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phidp_kdp_Maesaka(procstatus, dscfg, radar_list=None)`

Estimates PhiDP and KDP using the method by Maesaka. This method only retrieves data in rain (i.e. below the melting layer)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]

rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]

Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]

Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]

fzl [float. Dataset keyword] The freezing level height [m]. Default 2000.

ml_thickness [float. Dataset keyword] The melting layer thickness in meters. Default 700.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phidp_kdp_Vulpiani` (*procstatus, dscfg, radar_list=None*)

Computes specific differential phase and differential phase using the method developed by Vulpiani et al. The data is assumed to be clutter free and monotonous

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- rwind** [float. Dataset keyword] The length of the segment [m]
- n_iter** [int. Dataset keyword] number of iterations
- interp** [boolean. Dataset keyword] if set non valid values are interpolated using neighbouring valid values
- parallel** [boolean. Dataset keyword] if set use parallel computing
- get_phidp** [boolean. Dataset keyword] if set the PhiDP computed by integrating the resultant KDP is added to the radar field

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phidp_kdp_lp` (*procstatus, dscfg, radar_list=None*)

Estimates PhiDP and KDP using a linear programming algorithm. This method only retrieves data in rain (i.e. below the melting layer)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- fzl** [float. Dataset keyword] The freezing level height [m]. Default 2000.
- ml_thickness** [float. Dataset keyword] The melting layer thickness in meters. Default 700.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_point_measurement` (*procstatus, dscfg, radar_list=None*)

Obtains the radar data at a point location.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

latlon [boolean. Dataset keyword] if True position is obtained from latitude, longitude information, otherwise position is obtained from antenna coordinates (range, azimuth, elevation).

truealt [boolean. Dataset keyword] if True the user input altitude is used to determine the point of interest. if False use the altitude at a given radar elevation *ele* over the point of interest.

lon [float. Dataset keyword] the longitude [deg]. Use when *latlon* is True.

lat [float. Dataset keyword] the latitude [deg]. Use when *latlon* is True.

alt [float. Dataset keyword] altitude [m MSL]. Use when *latlon* is True.

ele [float. Dataset keyword] radar elevation [deg]. Use when *latlon* is False or when *latlon* is True and *truealt* is False

azi [float. Dataset keyword] radar azimuth [deg]. Use when *latlon* is False

rng [float. Dataset keyword] range from radar [m]. Use when *latlon* is False

AziTol [float. Dataset keyword] azimuthal tolerance to determine which radar azimuth to use [deg]

EleTol [float. Dataset keyword] elevation tolerance to determine which radar elevation to use [deg]

RngTol [float. Dataset keyword] range tolerance to determine which radar bin to use [m]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_qvp` (*procstatus*, *dscfg*, *radar_list=None*)

Computes quasi vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

angle [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle. Default 0.

ang_tol [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 50

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to accept average. Default 30.

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'none' 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_rainrate(procstatus, dscfg, radar_list=None)`

Estimates rainfall rate from polarimetric moments

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

RR_METHOD [string. Dataset keyword] The rainfall rate estimation method. One of the following: Z, ZPoly, KDP, A, ZKDP, ZA, hydro

alpha, beta [float] factor and exponent of the R-Var power law $R = \alpha * Var^{\beta}$. Default value depending on RR_METHOD. Z (0.0376, 0.6112), KDP (None, None), A (None, None)

alphaz, betaz [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$. Default value (0.0376, 0.6112)

alphazr, betazr [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$ applied to rain in method hydro. Default value (0.0376, 0.6112)

alphazs, betazs [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$ applied to solid precipitation in method hydro. Default value (0.1, 0.5)

alphakdp, betakdp [float] factor and exponent of the R-KDP power law $R = \alpha * KDP^{\beta}$. Default value (None, None)

alphaa, betaa [float] factor and exponent of the R-Ah power law $R = \alpha * Ah^{\beta}$. Default value (None, None)

thresh [float] In hybrid methods, Rainfall rate threshold at which the retrieval method used changes [mm/h]. Default value depending on RR_METHOD. ZKDP 10, ZA 10, hydro 10

mp_factor [float] Factor by which the Z-R relation is multiplied in the melting layer in method hydro. Default 0.6

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_raw (procstatus, dscfg, radar_list=None)`

Dummy function that returns the initial input data set

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_rcs (procstatus, dscfg, radar_list=None)`

Computes the radar cross-section (assuming a point target) from radar reflectivity.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

kw2 [float. Dataset keyowrd] The water constant

pulse_width [float. Dataset keyowrd] The pulse width [s]

beamwidthv [float. Global keyword] The vertical polarization antenna beamwidth [deg].
Used if input is vertical reflectivity

beamwidthh [float. Global keyword] The horizontal polarization antenna beamwidth
[deg]. Used if input is horizontal reflectivity

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_rcs_pr (procstatus, dscfg, radar_list=None)`

Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

antenna_gain [float. Global keyword] The antenna gain [dB]

txpwrv [float. Global keyword] The transmitted power of the vertical channel [dBm]. Used
if input is vertical reflectivity

mflossv [float. Global keyword] The matching filter losses of the vertical channel. Used if
input is vertical reflectivity

radconstv [float. Global keyword] The vertical channel radar constant. Used if input is
vertical reflectivity

lrsv [float. Global keyword] The receiver losses from the antenna feed to the reference point. [dB] positive value Used if input is vertical reflectivity

ltxv [float. Global keyword] The transmitter losses from the output of the high power amplifier to the antenna feed. [dB] positive value Used if input is vertical reflectivity

lradomev [float. Global keyword] The 1-way dry radome losses [dB] positive value. Used if input is vertical reflectivity

txpwrh [float. Global keyword] The transmitted power of the horizontal channel [dBm]. Used if input is horizontal reflectivity

mflossh [float. Global keyword] The matching filter losses of the vertical channel. Used if input is horizontal reflectivity

radconsth [float. Global keyword] The horizontal channel radar constant. Used if input is horizontal reflectivity

lrxh [float. Global keyword] The receiver losses from the antenna feed to the reference point. [dB] positive value Used if input is horizontal reflectivity

ltxh [float. Global keyword] The transmitter losses from the output of the high power amplifier to the antenna feed. [dB] positive value Used if input is horizontal reflectivity

lradomeh [float. Global keyword] The 1-way dry radome losses [dB] positive value. Used if input is horizontal reflectivity

attg [float. Dataset keyword] The gas attenuation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_rhohv_rain(procstatus, dscfg, radar_list=None)`

Keeps only suitable data to evaluate the 80 percentile of RhoHV in rain

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as precipitation [dBZ]. Default 20.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as precipitation [dBZ] Default 40.

ml_thickness [float. Dataset keyword] assumed thickness of the melting layer. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_roi` (*procstatus, dscfg, radar_list=None*)

Obtains the radar data at a region of interest.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_rqvp` (*procstatus, dscfg, radar_list=None*)

Computes range defined quasi vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

anglenr [int] The sweep number to use. It assumes the radar volume consists on PPI scans

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 2.

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to accept average. Default 30.

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. Default ‘nearest’ ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

rmax [float] ground range up to which the data is intended for use [m]. Default 50000.

weight_power [float] Power p of the weighting function $1/(\text{abs}(\text{grng}-(\text{rmax}-1))^{**p}$ given to the data outside the desired range. -1 will set the weight to 0. Default 2.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_save_radar` (*procstatus, dscfg, radar_list=None*)

Dummy function that allows to save the entire radar object

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_selfconsistency_bias` (*procstatus, dscfg, radar_list=None*)

Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

fzl [float. Dataset keyword] Default freezing level height. Default 2000.

rsmooth [float. Dataset keyword] length of the smoothing window [m]. Default 1000.

min_rhohv [float. Dataset keyword] minimum valid RhoHV. Default 0.92

max_phidp [float. Dataset keyword] maximum valid PhiDP [deg]. Default 20.

ml_thickness [float. Dataset keyword] Melting layer thickness [m]. Default 700.

rcell [float. Dataset keyword] length of continuous precipitation to consider the precipitation cell a valid phidp segment [m]. Default 1000.

dphidp_min [float. Dataset keyword] minimum phase shift [deg]. Default 2.

dphidp_max [float. Dataset keyword] maximum phase shift [deg]. Default 16.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_selfconsistency_kdp_phidp` (*procstatus, dscfg, radar_list=None*)

Computes specific differential phase and differential phase in rain using the selfconsistency between Zdr, Zh and KDP

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of strings. Dataset keyword] The input data types

rsmooth [float. Dataset keyword] length of the smoothing window [m]. Default 1000.

min_rhohv [float. Dataset keyword] minimum valid RhoHV. Default 0.92

max_phidp [float. Dataset keyword] maximum valid PhiDP [deg]. Default 20.

ml_thickness [float. Dataset keyword] assumed melting layer thickness [m]. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_signal_power` (*procstatus, dscfg, radar_list=None*)

Computes the signal power in dBm

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

mflossv [float. Global keyword] The matching filter losses of the vertical channel. Used if input is vertical reflectivity

radconstv [float. Global keyword] The vertical channel radar constant. Used if input is vertical reflectivity

lrxv [float. Global keyword] The receiver losses from the antenna feed to the reference point. [dB] positive value Used if input is vertical reflectivity

lradomev [float. Global keyword] The 1-way dry radome losses [dB] positive value. Used if input is vertical reflectivity

mflossh [float. Global keyword] The matching filter losses of the vertical channel. Used if input is horizontal reflectivity

radconsth [float. Global keyword] The horizontal channel radar constant. Used if input is horizontal reflectivity

lrxh [float. Global keyword] The receiver losses from the antenna feed to the reference point. [dB] positive value Used if input is horizontal reflectivity

lradomeh [float. Global keyword] The 1-way dry radome losses [dB] positive value. Used if input is horizontal reflectivity

attg [float. Dataset keyword] The gas attenuation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_smooth_phidp_double_window` (*procstatus, dscfg, radar_list=None*)

corrects phidp of the system phase and smoothes it using one window

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- rmin** [float. Dataset keyword] The minimum range where to look for valid data [m]
- rmax** [float. Dataset keyword] The maximum range where to look for valid data [m]
- rcell** [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]
- rwinds** [float. Dataset keyword] The length of the short smoothing window [m]
- rwindl** [float. Dataset keyword] The length of the long smoothing window [m]
- Zmin** [float. Dataset keyword] The minimum reflectivity [dBZ]
- Zmax** [float. Dataset keyword] The maximum reflectivity [dBZ]
- Zthr** [float. Dataset keyword] The threshold defining wich smoothed data to used [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_smooth_phidp_single_window(procstatus, dscfg, radar_list=None)`
 corrects phidp of the system phase and smoothes it using one window

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- rmin** [float. Dataset keyword] The minimum range where to look for valid data [m]
- rmax** [float. Dataset keyword] The maximum range where to look for valid data [m]
- rcell** [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]
- rwind** [float. Dataset keyword] The length of the smoothing window [m]
- Zmin** [float. Dataset keyword] The minimum reflectivity [dBZ]
- Zmax** [float. Dataset keyword] The maximum reflectivity [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_snr(procstatus, dscfg, radar_list=None)`
 Computes SNR

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [string. Dataset keyword] The input data type
- output_type** [string. Dataset keyword] The output data type. Either SNRh or SNRv

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_sun_hits` (*procstatus, dscfg, radar_list=None*)
monitoring of the radar using sun hits

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] minimum range where to look for a sun hit signal [m]. Default 50000.

hmin [float. Dataset keyword] minimum altitude where to look for a sun hit signal [m MSL]. Default 10000. The actual range from which a sun hit signal will be search will be the minimum between rmin and the range from which the altitude is higher than hmin.

delev_max [float. Dataset keyword] maximum elevation distance from nominal radar elevation where to look for a sun hit signal [deg]. Default 1.5

dazim_max [float. Dataset keyword] maximum azimuth distance from nominal radar elevation where to look for a sun hit signal [deg]. Default 1.5

elmin [float. Dataset keyword] minimum radar elevation where to look for sun hits [deg]. Default 1.

nbins_min [int. Dataset keyword.] minimum number of range bins that have to contain signal to consider the ray a potential sun hit. Default 10.

attg [float. Dataset keyword] gaseous attenuation. Default None

max_std_pwr [float. Dataset keyword] maximum standard deviation of the signal power to consider the data a sun hit [dB]. Default 2.

max_std_zdr [float. Dataset keyword] maximum standard deviation of the ZDR to consider the data a sun hit [dB]. Default 2.

az_width_co [float. Dataset keyword] co-polar antenna azimuth width (convoluted with sun width) [deg]. Default None

el_width_co [float. Dataset keyword] co-polar antenna elevation width (convoluted with sun width) [deg]. Default None

az_width_cross [float. Dataset keyword] cross-polar antenna azimuth width (convoluted with sun width) [deg]. Default None

el_width_cross [float. Dataset keyword] cross-polar antenna elevation width (convoluted with sun width) [deg]. Default None

ndays [int. Dataset keyword] number of days used in sun retrieval. Default 1

coeff_band [float. Dataset keyword] multiply coefficient to transform pulse width into receiver bandwidth

radar_list [list of Radar objects] Optional. list of radar objects

Returns

sun_hits_dict [dict] dictionary containing a radar object, a sun_hits dict and a sun_retrieval dictionary

ind_rad [int] radar index

`pyrad.proc.process_svp` (*procstatus, dscfg, radar_list=None*)

Computes slanted vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

angle [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle. Default 0.

ang_tol [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI

lat, lon [float] latitude and longitude of the point of interest [deg]

latlon_tol [float] tolerance in latitude and longitude in deg. Default 0.0005

delta_rng, delta_azi [float] maximum range distance [m] and azimuth distance [degree] from the central point of the svp containing data to average. Default 5000. and 10.

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 250.

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to consider the data valid when performing the averaging. Default 1

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. Default ‘none’ ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the svp and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_time_avg` (*procstatus, dscfg, radar_list=None*)

computes the temporal mean of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

lin_trans: int. Dataset keyword If 1 apply linear transformation before averaging

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_time_avg_flag` (*procstatus, dscfg, radar_list=None*)
computes a flag field describing the conditions of the data used while averaging

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

phidpmax: float. Dataset keyword maximum PhiDP

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object

ind_rad [int] radar index

`pyrad.proc.process_time_height` (*procstatus, dscfg, radar_list=None*)

Produces time height radar objects at a point of interest defined by latitude and longitude. A time-height contains the evolution of the vertical structure of radar measurements above the location of interest.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

lat, lon [float] latitude and longitude of the point of interest [deg]

latlon_tol [float] tolerance in latitude and longitude in deg. Default 0.0005

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 50

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'none' 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_traj_antenna_pattern` (*procstatus*, *dscfg*, *radar_list=None*, *trajectory=None*)

Process a new array of data volumes considering a plane trajectory. As result a timeseries with the values transposed for a given antenna pattern is created. The result is created when the LAST flag is set.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries]

datatype [list of string. Dataset keyword] The input data types

antennaType [str. Dataset keyword] Type of antenna of the radar we want to get the view from. Can be AZIMUTH, ELEVATION, LOWBEAM, HIGHBEAM

par_azimuth_antenna [dict. Global ekeyword] Dictionary containing the parameters of the PAR azimuth antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

par_elevation_antenna [dict. Global keyword] Dictionary containing the parameters of the PAR elevation antenna, i.e. name of the file with the antenna azimuth pattern and fixed antenna angle

asr_lowbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR low beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

asr_highbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR high beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

target_radar_pos [dict. Global keyword] Dictionary containing the latitude, longitude and altitude of the radar we want to get the view from. If not specifying it will assume the radar is collocated

range_all [Bool. Dataset keyword] If the real radar and the synthetic radar are co-located and this parameter is true the statistics are going to be computed using all the data from range 0 to the position of the plane. Default False

rhi_resolution [Bool. Dataset keyword] Resolution of the synthetic RHI used to compute the data as viewed from the synthetic radar [deg]. Default 0.5

max_altitude [float. Dataset keyword] Max altitude of the data to use when computing the view from the synthetic radar [m MSL]. Default 12000.

latlon_tol [float. Dataset keyword] The tolerance in latitude and longitude to determine which synthetic radar gates are co-located with real radar gates [deg]. Default 0.04

alt_tol [float. Dataset keyword] The tolerance in altitude to determine which synthetic radar gates are co-located with real radar gates [m]. Default 1000.

pattern_thres [float. Dataset keyword] The minimum of the sum of the weights given to each value in order to consider the weighted quantile valid. It is related to the number of valid data points

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

use_nans [dict. Dataset keyword] Dictionary specifying whether the nans have to be used in the computation of the statistics for each field. Default False

nan_value [dict. Dataset keyword] Dictionary with the value to use to substitute the NaN values when computing the statistics of each field. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_traj_atplane` (*procstatus, dscfg, radar_list=None, trajectory=None*)

Return time series according to trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

ang_tol [float. Dataset keyword] Factor that multiplies the angle resolution. Used when determining the neighbouring rays. Default 1.2

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_traj_lightning` (*procstatus, dscfg, radar_list=None, trajectory=None*)

Return time series according to lightning trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

ang_tol [float. Dataset keyword] Factor that multiplies the angle resolution. Used when determining the neighbouring rays. Default 1.2

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_traj_trt` (*procstatus, dscfg, radar_list=None, trajectory=None*)

Processes data according to TRT trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

time_tol [float. Dataset keyword] tolerance between reference time of the radar volume and that of the TRT cell [s]. Default 100.

alt_min, alt_max [float. Dataset keyword] Minimum and maximum altitude of the data inside the TRT cell to retrieve [m MSL]. Default None

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_trajectory` (*procstatus, dscfg, radar_list=None, trajectory=None*)

Return trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

new_dataset [Trajectory object] radar object

ind_rad [int] None

`pyrad.proc.process_vad` (*procstatus, dscfg, radar_list=None*)

Estimates vertical wind profile using the VAD (velocity Azimuth Display) technique

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_vol_refl` (*procstatus, dscfg, radar_list=None*)

Computes the volumetric reflectivity in $10\log_{10}(\text{cm}^2 \text{ km}^{-3})$

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

freq [float. Dataset keyword] The radar frequency

kw [float. Dataset keyword] The water constant

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_weighted_time_avg` (*procstatus, dscfg, radar_list=None*)

computes the temporal mean of a field weighted by the reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object

ind_rad [int] radar index

`pyrad.proc.process_wind_vel` (*procstatus, dscfg, radar_list=None*)

Estimates the horizontal or vertical component of the wind from the radial velocity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

vert_proj [Boolean] If true the vertical projection is computed. Otherwise the horizontal projection is computed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_windshear` (*procstatus, dscfg, radar_list=None*)

Estimates the wind shear from the wind velocity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

az_tol [float] The tolerance in azimuth when looking for gates on top of the gate when computation is performed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_zdr_column` (*procstatus, dscfg, radar_list=None*)

Detects ZDR columns

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_zdr_precip` (*procstatus, dscfg, radar_list=None*)

Keeps only suitable data to evaluate the differential reflectivity in moderate rain or precipitation (for vertical scans)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

ml_filter [boolean. Dataset keyword] indicates if a filter on data in and above the melting layer is applied. Default True.

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as precipitation [dBZ]. Default 20.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as precipitation [dBZ] Default 22.

RhoHVmin [float. Dataset keyword] minimum RhoHV to consider the bin as precipitation Default 0.97

PhiDPmax [float. Dataset keyword] maximum PhiDP to consider the bin as precipitation [deg] Default 10.

elmax [float. Dataset keyword] maximum elevation angle where to look for precipitation [deg] Default None.

ml_thickness [float. Dataset keyword] assumed thickness of the melting layer. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_zdr_snow(procstatus, dscfg, radar_list=None)`

Keeps only suitable data to evaluate the differential reflectivity in snow

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as snow [dBZ]. Default 0.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as snow [dBZ]. Default 30.

SNRmin [float. Dataset keyword] minimum SNR to consider the bin as snow [dB]. Default 10.

SNRmax [float. Dataset keyword] maximum SNR to consider the bin as snow [dB] Default 50.

RhoHVmin [float. Dataset keyword] minimum RhoHV to consider the bin as snow Default 0.97

PhiDPmax [float. Dataset keyword] maximum PhiDP to consider the bin as snow [deg] Default 10.

elmax [float. Dataset keyword] maximum elevation angle where to look for snow [deg] Default None.

KDPmax [float. Dataset keyword] maximum KDP to consider the bin as snow [deg] Default None

TEMPmin [float. Dataset keyword] minimum temperature to consider the bin as snow [deg C]. Default None

TEMPmax [float. Dataset keyword] maximum temperature to consider the bin as snow [deg C] Default None

hydroclass [list of ints. Dataset keyword] list of hydrometeor classes to keep for the analysis Default [1] (dry snow)

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PRODUCTS GENERATION (PYRAD . PROD)

Initiate the products generation.

3.1 Auxiliary functions

`get_dsformat_func`

3.2 Product generation

<code>generate_occurrence_products(dataset, prdcfg)</code>	generates occurrence products
<code>generate_cosmo_coord_products(dataset, prdcfg)</code>	generates COSMO coordinates products
<code>generate_sun_hits_products(dataset, prdcfg)</code>	generates sun hits products
<code>generate_intercomp_products(dataset, prdcfg)</code>	Generates radar intercomparison products.
<code>generate_colocated_gates_products(dataset, ...)</code>	Generates colocated gates products
<code>generate_time_avg_products(dataset, prdcfg)</code>	generates time average products
<code>generate_qvp_products(dataset, prdcfg)</code>	Generates quasi vertical profile products.
<code>generate_vol_products(dataset, prdcfg)</code>	Generates radar volume products.
<code>generate_timeseries_products(dataset, prdcfg)</code>	Generates time series products
<code>generate_monitoring_products(dataset, prdcfg)</code>	generates a monitoring product
<code>generate_grid_products(dataset, prdcfg)</code>	generates grid products
<code>generate_traj_product(traj, prdcfg)</code>	Generates trajectory products
<code>generate_ml_products(dataset, prdcfg)</code>	Generates melting layer products.

`pyrad.prod.generate_colocated_gates_products(dataset, prdcfg)`
Generates colocated gates products

Parameters

dataset [tuple] radar objects and colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_cosmo_coord_products(dataset, prdcfg)`
generates COSMO coordinates products

Parameters

dataset [tuple] radar object containing the COSMO coordinates

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_grid_products(dataset, prdcfg)`
generates grid products

Parameters

dataset [grid] grid object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

no return

`pyrad.prod.generate_intercomp_products(dataset, prdcfg)`
Generates radar intercomparison products.

Parameters

dataset [tuple] values of colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_ml_products(dataset, prdcfg)`
Generates melting layer products.

Parameters

dataset [dict] dictionary containing the radar object and a keyword stating the status of the processing

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_monitoring_products(dataset, prdcfg)`
generates a monitoring product

Parameters

dataset [dictionary] dictionary containing a histogram object and some metadata

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_occurrence_products(dataset, prdcfg)`
generates occurrence products

Parameters

dataset [tuple] radar object and metadata dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_qvp_products(dataset, prdcfg)`
Generates quasi vertical profile products. Quasi vertical profiles come from azimuthal averaging of polarimetric radar data.

Parameters

dataset [dict] dictionary containing the radar object and a keyword stating the status of the processing

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_sun_hits_products(dataset, prdcfg)`
generates sun hits products

Parameters

dataset [tuple] radar object and sun hits dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_time_avg_products(dataset, prdcfg)`
generates time average products

Parameters

dataset [tuple] radar objects and colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.generate_timeseries_products(dataset, prdcfg)`
Generates time series products

Parameters

dataset [dictionary] radar object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

no return

`pyrad.prod.generate_traj_product(traj, prdcfg)`
Generates trajectory products

Parameters

traj [Trajectory object]

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

None

`pyrad.prod.generate_vol_products(dataset, prdcfg)`

Generates radar volume products.

Parameters

dataset [dict] dictionary with key radar_out containing a radar object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

no return

`pyrad.prod.get_prodgen_func(dsformat, dsname, dstype)`

maps the dataset format into its processing function

Parameters

dsformat [str] dataset group, i.e. 'VOL', etc.

Returns

func [function] pyrad function used to generate the products

INPUT AND OUTPUT (PYRAD . IO)

Functions to read and write data and configuration files.

4.1 Reading configuration files

<code>read_config(fname[, cfg])</code>	Read a pyrad config file.
----------------------------------------	---------------------------

4.2 Reading radar data

<code>get_data(voltime, datatypesdescr, cfg)</code>	Reads pyrad input data.
-----------------------------------------------------	-------------------------

4.3 Reading cosmo data

<code>cosmo2radar_data(radar, cosmo_coord, cosmo_data)</code>	get the COSMO value corresponding to each radar gate using nearest neighbour interpolation
<code>cosmo2radar_coord(radar, cosmo_coord[, ...])</code>	Given the radar coordinates find the nearest COSMO model pixel
<code>hzt2radar_data(radar, hzt_coord, hzt_data[, ...])</code>	get the HZT value corresponding to each radar gate using nearest neighbour interpolation
<code>hzt2radar_coord(radar, hzt_coord[, ...])</code>	Given the radar coordinates find the nearest HZT pixel
<code>get_cosmo_fields(cosmo_data, cosmo_ind[, ...])</code>	Get the COSMO data corresponding to each radar gate using a precomputed look up table of the nearest neighbour
<code>get_iso0_field(hzt_data, hzt_ind, z_radar[, ...])</code>	Get the height over iso0 data corresponding to each radar gate using a precomputed look up table of the nearest neighbour
<code>read_cosmo_data(fname[, field_names, celsius])</code>	Reads COSMO data from a netcdf file
<code>read_cosmo_coord(fname[, zmin])</code>	Reads COSMO coordinates from a netcdf file
<code>read_hzt_data(fname[, chy0, chx0])</code>	Reads iso-0 degree data from an HZT file

4.4 Reading other data

<code>read_last_state(fname)</code>	Reads a file containing the date of acquisition of the last volume processed
<code>read_status(voltime, cfg[, ind_rad])</code>	Reads rad4alp xml status file.
<code>read_rad4alp_cosmo(fname, datatype[, ngates])</code>	Reads rad4alp COSMO data binary file.
<code>read_rad4alp_vis(fname, datatype)</code>	Reads rad4alp visibility data binary file.
<code>read_excess_gates(fname)</code>	Reads a csv files containing the position of gates exceeding a given percentile of frequency of occurrence
<code>read_colocated_gates(fname)</code>	Reads a csv files containing the position of colocated gates
<code>read_colocated_data(fname)</code>	Reads a csv files containing colocated data
<code>read_timeseries(fname)</code>	Reads a time series contained in a csv file
<code>read_ts_cum(fname)</code>	Reads a time series of precipitation accumulation contained in a csv file
<code>read_monitoring_ts(fname[, sort_by_date])</code>	Reads a monitoring time series contained in a csv file
<code>read_intercomp_scores_ts(fname[, sort_by_date])</code>	Reads a radar intercomparison scores csv file
<code>get_sensor_data(date, datatype, cfg)</code>	Gets data from a point measurement sensor (rain gauge or disdrometer)
<code>read_smn(fname)</code>	Reads SwissMetNet data contained in a csv file
<code>read_smn2(fname)</code>	Reads SwissMetNet data contained in a csv file with format station,time,value
<code>read_disdro_scattering(fname)</code>	Reads scattering parameters computed from disdrometer data contained in a text file
<code>read_sun_hits(fname)</code>	Reads sun hits data contained in a csv file
<code>read_sun_hits_multiple_days(cfg, time_ref[, ...])</code>	Reads sun hits data from multiple file sources
<code>read_sun_retrieval(fname)</code>	Reads sun retrieval data contained in a csv file
<code>read_solar_flux(fname)</code>	Reads solar flux data from the DRAO observatory in Canada
<code>read_selfconsistency(fname)</code>	Reads a self-consistency table with Zdr, Kdp/Zh columns
<code>read_antenna_pattern(fname[, linear, twoway])</code>	Read antenna pattern from file
<code>read_meteorage(fname)</code>	Reads METEORAGE lightning data contained in a text file.
<code>read_lightning(fname[, filter_data])</code>	Reads lightning data contained in a text file.
<code>read_lightning_traj(fname)</code>	Reads lightning trajectory data contained in a csv file.
<code>read_lightning_all(fname[, labels])</code>	Reads a file containing lightning data and co-located polarimetric data.
<code>read_trt_scores(fname)</code>	Reads the TRT scores contained in a text file.
<code>read_trt_data(fname)</code>	Reads the TRT data contained in a text file.
<code>read_trt_traj_data(fname)</code>	Reads the TRT cell data contained in a text file.
<code>read_trt_cell_lightning(fname)</code>	Reads the lightning data of a TRT cell.
<code>read_rhi_profile(fname[, labels])</code>	Reads a monitoring time series contained in a csv file
<code>read_histogram(fname)</code>	Reads a histogram contained in a csv file
<code>read_quantiles(fname)</code>	Reads quantiles contained in a csv file
<code>read_profile_ts(fname_list, labels[, hres, ...])</code>	Reads a collection of profile data file and creates a time series
<code>read_histogram_ts(fname_list, datatype[, t_res])</code>	Reads a collection of histogram data file and creates a time series
<code>read_quantiles_ts(fname_list[, step, qmin, ...])</code>	Reads a collection of quantiles data file and creates a time series

Continued on next page

Table 4 – continued from previous page

<code>read_ml_ts(fname)</code>	Reads a melting layer time series contained in a csv file
--------------------------------	-----------------------------------------------------------

4.5 Writing data

<code>write_ts_lightning(flashnr, time_data, ...)</code>	writes the LMA sources data and the value of the colocated polarimetric variables
<code>send_msg(sender, receiver_list, subject, fname)</code>	sends the content of a text file by email
<code>write_alarm_msg(radar_name, param_name_unit, ...)</code>	writes an alarm file
<code>write_last_state(datetime_last, fname)</code>	writes SwissMetNet data in format datetime,avg_value, std_value
<code>write_smn(datetime_vec, value_avg_vec, ...)</code>	writes SwissMetNet data in format datetime,avg_value, std_value
<code>write_trt_cell_data(traj_ID, yyyymmddHHMM, ...)</code>	writes TRT cell data
<code>write_trt_cell_scores(traj_ID, ...)</code>	writes TRT cells scores
<code>write_trt_cell_lightning(cell_ID, cell_time, ...)</code>	writes the lightning data for each TRT cell
<code>write_rhi_profile(hvec, data, nvalid_vec, ...)</code>	writes the values of an RHI profile in a text file
<code>write_field_coverage(quantiles, values, ...)</code>	writes the quantiles of the coverage on a particular sector
<code>write_cdf(quantiles, values, ntot, nnan, ...)</code>	writes a cumulative distribution function
<code>write_histogram(bin_edges, values, fname[, ...])</code>	writes a histogram
<code>write_quantiles(quantiles, values, fname[, ...])</code>	writes quantiles
<code>write_ts_polar_data(dataset, fname)</code>	writes time series of data
<code>write_ts_cum(dataset, fname)</code>	writes time series accumulation of data
<code>write_monitoring_ts(start_time, np_t, ..., ...)</code>	writes time series of data
<code>write_excess_gates(excess_dict, fname)</code>	Writes the position and values of gates that have a frequency of occurrence higher than a particular threshold
<code>write_intercomp_scores_ts(start_time, stats, ...)</code>	writes time series of radar intercomparison scores
<code>write_colocated_gates(coloc_gates, fname)</code>	Writes the position of gates colocated with two radars
<code>write_colocated_data(coloc_data, fname)</code>	Writes the data of gates colocated with two radars
<code>write_colocated_data_time_avg(coloc_data, fname)</code>	Writes the time averaged data of gates colocated with two radars
<code>write_sun_hits(sun_hits, fname)</code>	Writes sun hits data.
<code>write_sun_retrieval(sun_retrieval, fname)</code>	Writes sun retrieval data.

4.6 Auxiliary functions

<code>map_hydro(hydro_data_op)</code>	maps the operational hydrometeor classification identifiers to the ones used by Py-ART
<code>map_Doppler(Doppler_data_bin, Nyquist_vel)</code>	maps the binary METRANET Doppler data to actual Doppler velocity
<code>get_save_dir(basepath, procname, dsname, prdname)</code>	obtains the path to a product directory and eventually creates it

Continued on next page

Table 6 – continued from previous page

<code>make_filename(prdtype, dstype, dsname, ext_list)</code>	creates a product file name
<code>generate_field_name_str(datatype)</code>	Generates a field name in a nice to read format.
<code>get_fieldname_pyart(datatype)</code>	maps the config file radar data type name into the corresponding rainbow Py-ART field name
<code>get_fieldname_cosmo(field_name)</code>	maps the Py-ART field name into the corresponding COSMO variable name
<code>get_field_unit(datatype)</code>	Return unit of datatype.
<code>get_file_list(datadescriptor, starttime, ...)</code>	gets the list of files with a time period
<code>get_trtfile_list(datapath, starttime, endtime)</code>	gets the list of TRT files with a time period
<code>get_new_rainbow_file_name(master_fname, ...)</code>	get the rainbow file name containing datatype from a master file name and data type
<code>get_datatype_fields(datadescriptor)</code>	splits the data type descriptor and provides each individual member
<code>get_dataset_fields(datasetdescr)</code>	splits the dataset type descriptor and provides each individual member
<code>get_datetime(fname, datadescriptor)</code>	Given a data descriptor gets date and time from file name
<code>find_raw_cosmo_file(voltime, datatype, cfg)</code>	Search a COSMO file in netcdf format
<code>find_hzt_file(voltime, cfg, ind_rad)</code>	Search an ISO-0 degree file in HZT format
<code>_get_datetime(fname, datagroup[, ftime_format])</code>	Given a data group gets date and time from file name

4.7 Trajectory

<code>Trajectory(filename[, starttime, endtime, ...])</code>	A class for reading and handling trajectory data from a file.
--------------------------------------------------------------	---------------------------------------------------------------

4.8 TimeSeries

<code>TimeSeries(desc[, timevec, timeformat, ...])</code>	Holding timeseries data and metadata.
-----------------------------------------------------------	---------------------------------------

class `pyrad.io.TimeSeries` (*desc, timevec=None, timeformat=None, maxlength=None, datatype=""*)

Bases: `object`

Holding timeseries data and metadata.

Attributes

description [array of str] Description of the data of the time series.

time_vector [array of datetime objects]

timeformat [how to print the time (default:)] 'Date, UTC [seconds since midnight]'

dataseries [List of `_dataSeries` object holding the] data

Methods

<code>add_dataseries(label, unit_name, unit[, ...])</code>	Add a new data series to the timeseries object.
<code>add_timesample(dt, values)</code>	Add a new sample to the time series.

Continued on next page

Table 9 – continued from previous page

<code>plot(fname[, ymin, ymax])</code>	Make a figure of a time series
<code>plot_hist(fname[, step])</code>	Make histograms of time series
<code>write(fname)</code>	Write time series output

```

__class__
    alias of builtins.type

__delattr__ ($self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyrad.io.timeseries', '__doc__': "\n Holding
__dir__ () → list
    default dir() implementation

__eq__ ($self, value, /)
    Return self==value.

__format__ ()
    default object formatter

__ge__ ($self, value, /)
    Return self>=value.

__getattr__ ($self, name, /)
    Return getattr(self, name).

__gt__ ($self, value, /)
    Return self>value.

__hash__ ($self, /)
    Return hash(self).

__init__ (desc, timevec=None, timeformat=None, maxlength=None, datatype="")
    Initialize the object.

```

Parameters

desc [array of str]
timevec [array of datetime]
timeformat [specifies time format]
maxlength [Maximal length of the time series]
num_el [Number of values in the time series]

```

__init_subclass__ ()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__ ($self, value, /)
    Return self<=value.

__lt__ ($self, value, /)
    Return self<value.

__module__ = 'pyrad.io.timeseries'

__ne__ ($self, value, /)
    Return self!=value.

```

__new__ (*\$type, *args, **kwargs*)

Create and return a new object. See help(type) for accurate signature.

__reduce__ ()

helper for pickle

__reduce_ex__ ()

helper for pickle

__repr__ (*\$self, /*)

Return repr(self).

__setattr__ (*\$self, name, value, /*)

Implement setattr(self, name, value).

__sizeof__ () → int

size of object in memory, in bytes

__str__ (*\$self, /*)

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

add_dataseries (*label, unit_name, unit, dataserie=None, plot=True, color=None, linestyle=None*)

Add a new data series to the timeseries object. The length of the data vector must be the same as the length of the time vector.

add_timesample (*dt, values*)

Add a new sample to the time series.

plot (*fname, ymin=None, ymax=None*)

Make a figure of a time series

plot_hist (*fname, step=None*)

Make histograms of time series

write (*fname*)

Write time series output

class pyrad.io.**Trajectory** (*filename, starttime=None, endtime=None, trajtype='plane', flashnr=0*)

Bases: `object`

A class for reading and handling trajectory data from a file.

Attributes

filename [str] Path and name of the trajectory definition file

starttime [datetime] Start time of trajectory processing.

endtime [datetime] End time of trajectory processing.

trajtype [str]

Type of trajectory. Can be 'plane' or 'lightning'

time_vector [Array of datetime objects] Array containing the trajectory time samples

wgs84_lat_deg [Array of floats] WGS84 latitude samples in radian

wgs84_lon_deg [Array of floats] WGS84 longitude samples in radian

wgs84_alt_m [Array of floats] WGS84 altitude samples in m

nsamples [int]

Number of samples in the trajectory

_swiss_grid_done [Bool] Indicates that conversion to Swiss coordinates has been performed

swiss_chy, swiss_chx, swiss_chh [Array of floats] Swiss coordinates in m

radar_list [list] List of radars for which trajectories are going to be computed

flashnr [int] For 'lightning' only. Number of flash for which trajectory data is going to be computed. If 0 all all flashes are going to be considered.

time_in_flash [array of floats] For 'lightning' only. Time within flash (sec)

flashnr_vec [array of ints] For 'lightning' only. Flash number of each data sample

dBm [array of floats] For 'lightning' only. Lightning power (dBm)

Methods

<i>add_radar</i> (radar)	Add the coordinates (WGS84 longitude, latitude and non WGS84 altitude) of a radar to the radar_list.
<i>calculate_velocities</i> (radar)	Calculate velocities.
<i>get_end_time</i> ()	Get time of last trajectory sample.
<i>get_samples_in_period</i> ([start, end])	"
<i>get_start_time</i> ()	Get time of first trajectory sample.

__class__

alias of builtins.type

__delattr__ (\$self, name, /)

Implement delattr(self, name).

__dict__ = **mappingproxy**({'__module__': 'pyrad.io.trajectory', '__doc__': "\n A class

__dir__ () → list

default dir() implementation

__eq__ (\$self, value, /)

Return self==value.

__format__ ()

default object formatter

__ge__ (\$self, value, /)

Return self>=value.

__getattr__ (\$self, name, /)

Return getattr(self, name).

__gt__ (\$self, value, /)

Return self>value.

__hash__ (*\$self*, /)
Return hash(self).

__init__ (*filename*, *starttime=None*, *endtime=None*, *trajtype='plane'*, *flashnr=0*)
Initialize the object.

Parameters

filename [str] Filename containing the trajectory samples.

starttime [datetime] Start time of trajectory processing. If not given, use the time of the first trajectory sample.

endtime [datetime] End time of trajectory processing. If not given, use the time of the last trajectory sample.

trajtype [str] type of trajectory. Can be plane or lightning

flashnr [int] If type of trajectory is lightning, the flash number to check the trajectory. 0 means all flash numbers included

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*\$self*, *value*, /)
Return self<=value.

__lt__ (*\$self*, *value*, /)
Return self<value.

__module__ = 'pyrad.io.trajectory'

__ne__ (*\$self*, *value*, /)
Return self!=value.

__new__ (*\$type*, **args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__ (*\$self*, /)
Return repr(self).

__setattr__ (*\$self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__ (*\$self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`_convert_traj_to_swissgrid()`

Convert trajectory samples from WGS84 to Swiss CH1903 coordinates

`_get_total_seconds(x)`

Return total seconds of timedelta object

`_read_traj()`

Read trajectory from file

`_read_traj_lightning(flashnr=0)`

Read trajectory from lightning file

Parameters

`flashnr` [int] the flash number to keep. If 0 data from all flashes will be kept

`_read_traj_trt()`

Read trajectory from TRT file

`add_radar(radar)`

Add the coordinates (WGS84 longitude, latitude and non WGS84 altitude) of a radar to the radar_list.

Parameters

`radar` [pyart radar object] containing the radar coordinates

`calculate_velocities(radar)`

Calculate velocities.

`get_end_time()`

Get time of last trajectory sample.

`get_samples_in_period(start=None, end=None)`

” Get indices of samples of the trajectory within given time period.

`get_start_time()`

Get time of first trajectory sample.

`pyrad.io.add_field(radar_dest, radar_orig)`

adds the fields from orig radar into dest radar. If they are not in the same grid, interpolates them to dest grid

Parameters

`radar_dest` [radar object] the destination radar

`radar_orig` [radar object] the radar object containing the original field

Returns

`field_dest` [dict] interpolated field and metadata

`pyrad.io.cosmo2radar_coord(radar, cosmo_coord, slice_xy=True, slice_z=False, field_name=None)`

Given the radar coordinates find the nearest COSMO model pixel

Parameters

`radar` [Radar] the radar object containing the information on the position of the radar gates

`cosmo_coord` [dict] dictionary containing the COSMO coordinates

`slice_xy` [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

slice_z [boolean] if true the vertical plane of the COSMO field is cut to the dimensions of the radar field

field_name [str] name of the field

Returns

cosmo_ind_field [dict] dictionary containing a field of COSMO indices and metadata

`pyrad.io.cosmo2radar_data(radar, cosmo_coord, cosmo_data, time_index=0, slice_xy=True, slice_z=False, field_names=['temperature'])`
get the COSMO value corresponding to each radar gate using nearest neighbour interpolation

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

cosmo_coord [dict] dictionary containing the COSMO coordinates

cosmo_data [dict] dictionary containing the COSMO data

time_index [int] index of the forecasted data

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

slice_z [boolean] if true the vertical plane of the COSMO field is cut to the dimensions of the radar field

field_names [str] names of COSMO fields to convert (default temperature)

Returns

cosmo_fields [list of dict] list of dictionary with the COSMO fields and metadata

`pyrad.io.find_hzt_file(voltime, cfg, ind_rad=0)`
Search an ISO-0 degree file in HZT format

Parameters

voltime [datetime object] volume scan time

cfg [dictionary of dictionaries] configuration info to figure out where the data is

ind_rad [int] radar index

Returns

fname [str] Name of HZT file if it exists. None otherwise

`pyrad.io.find_raw_cosmo_file(voltime, datatype, cfg, ind_rad=0)`
Search a COSMO file in netcdf format

Parameters

voltime [datetime object] volume scan time

datatype [str] type of COSMO data to look for

cfg [dictionary of dictionaries] configuration info to figure out where the data is

ind_rad [int] radar index

Returns

fname [str] Name of COSMO file if it exists. None otherwise

`pyrad.io.generate_field_name_str(datatype)`
Generates a field name in a nice to read format.

Parameters**datatype** [str] The data type**Returns****field_str** [str] The field name`pyrad.io.get_cosmo_fields(cosmo_data, cosmo_ind, time_index=0, field_names=['temperature'])`

Get the COSMO data corresponding to each radar gate using a precomputed look up table of the nearest neighbour

Parameters**cosmo_data** [dict] dictionary containing the COSMO data and metadata**cosmo_ind** [dict] dictionary containing a field of COSMO indices and metadata**time_index** [int] index of the forecasted data**field_names** [str] names of COSMO parameters (default temperature)**Returns****cosmo_fields** [list of dict] dictionary with the COSMO fields and metadata`pyrad.io.get_data(volttime, datatypesdescr, cfg)`

Reads pyrad input data.

Parameters**volttime** [datetime object] volume scan time**datatypesdescr** [list] list of radar field types to read. Format : [radar file type]:[datatype]**cfg: dictionary of dictionaries** configuration info to figure out where the data is**Returns****radar** [Radar] radar object`pyrad.io.get_dataset_fields(datasetdescr)`

splits the dataset type descriptor and provides each individual member

Parameters**datasetdescr** [str] dataset type. Format : [processing level]:[dataset type]**Returns****proclevel** [str] dataset processing level**dataset** [str] dataset type, i.e. dBZ, ZDR, ISO0, ...`pyrad.io.get_datatype_fields(datadescriptor)`

splits the data type descriptor and provides each individual member

Parameters**datadescriptor** [str] radar field type. Format : [radar file type]:[datatype]**Returns****radarnr** [str] radar number, i.e. RADAR1, RADAR2, ...**datagroup** [str] data type group, i.e. RAINBOW, RAD4ALP, ODIM, CFRADIAL, COSMO, MXPOL ...**datatype** [str] data type, i.e. dBZ, ZDR, ISO0, ...

dataset [str] dataset type (for saved data only)

product [str] product type (for saved data only)

`pyrad.io.get_datetime` (*fname, datadescriptor*)

Given a data descriptor gets date and time from file name

Parameters

fname [str] file name

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

Returns

fdatetime [datetime object] date and time in file name

`pyrad.io.get_field_unit` (*datatype*)

Return unit of datatype.

Parameters

datatype [str] The data type

Returns

unit [str] The unit

`pyrad.io.get_fieldname_cosmo` (*field_name*)

maps the Py-ART field name into the corresponding COSMO variable name

Parameters

field_name [str] Py-ART field name

Returns

cosmo_name [str] Py-ART variable name

`pyrad.io.get_fieldname_pyart` (*datatype*)

maps the config file radar data type name into the corresponding rainbow Py-ART field name

Parameters

datatype [str] config file radar data type name

Returns

field_name [str] Py-ART field name

`pyrad.io.get_file_list` (*datadescriptor, starttime, endtime, cfg, scan=None*)

gets the list of files with a time period

Parameters

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

starttime [datetime object] start of time period

endtime [datetime object] end of time period

cfg: dictionary of dictionaries configuration info to figure out where the data is

scan [str] scan name

Returns

filelist [list of strings] list of files within the time period

`pyrad.io.get_iso0_field(hzt_data, hzt_ind, z_radar, field_name='height_over_iso0')`

Get the height over iso0 data corresponding to each radar gate using a precomputed look up table of the nearest neighbour

Parameters

hzt_data [dict] dictionary containing the HZT data and metadata

hzt_ind [dict] dictionary containing a field of HZT indices and metadata

z_radar [ndarray] gates altitude [m MSL]

field_name [str] names of HZT parameters (default height_over_iso0)

Returns

iso0_field [list of dict] dictionary with the height over iso0 field and metadata

`pyrad.io.get_new_rainbow_file_name(master_fname, master_datadescriptor, datatype)`

get the rainbow file name containing datatype from a master file name and data type

Parameters

master_fname [str] the master file name

master_datadescriptor [str] the master data type descriptor

datatype [str] the data type of the new file name to be created

Returns

new_fname [str] the new file name

`pyrad.io.get_save_dir(basepath, procname, dsname, prdname, timeinfo=None, timeformat='%Y-%m-%d', create_dir=True)`

obtains the path to a product directory and eventually creates it

Parameters

basepath [str] product base path

procname [str] name of processing space

dsname [str] data set name

prdname [str] product name

timeinfo [datetime] time info to generate the date directory. If None there is no time format in the path

timeformat [str] Optional. The time format.

create_dir [boolean] If True creates the directory

Returns

savedir [str] path to product

`pyrad.io.get_sensor_data(date, datatype, cfg)`

Gets data from a point measurement sensor (rain gauge or disdrometer)

Parameters

date [datetime object] measurement date

datatype [str] name of the data type to read

cfg [dictionary] dictionary containing sensor information

Returns

sensordate, **sensorvalue**, **label**, **period** [tuple] date, value, type of sensor and measurement period

`pyrad.io.get_trtfile_list(datapath, starttime, endtime)`

gets the list of TRT files with a time period

Parameters

datapath [str] directory where to look for data

starttime [datetime object] start of time period

endtime [datetime object] end of time period

Returns

filelist [list of strings] list of files within the time period

`pyrad.io.hzt2radar_coord(radar, hzt_coord, slice_xy=True, field_name=None)`

Given the radar coordinates find the nearest HZT pixel

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

hzt_coord [dict] dictionary containing the HZT coordinates

slice_xy [boolean] if true the horizontal plane of the HZT field is cut to the dimensions of the radar field

field_name [str] name of the field

Returns

hzt_ind_field [dict] dictionary containing a field of HZT indices and metadata

`pyrad.io.hzt2radar_data(radar, hzt_coord, hzt_data, slice_xy=True, field_name='height_over_iso0')`

get the HZT value corresponding to each radar gate using nearest neighbour interpolation

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

hzt_coord [dict] dictionary containing the HZT coordinates

hzt_data [dict] dictionary containing the HZT data

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

field_name [str] name of HZT fields to convert (default height_over_iso0)

Returns

hzt_fields [list of dict] list of dictionary with the HZT fields and metadata

`pyrad.io.interpol_field(radar_dest, radar_orig, field_name, fill_value=None, ang_tol=0.5)`

interpolates field field_name contained in radar_orig to the grid in radar_dest

Parameters

radar_dest [radar object] the destination radar

radar_orig [radar object] the radar object containing the original field

field_name: str name of the field to interpolate

fill_value: float The fill value

ang_tol [float] angle tolerance to determine whether the radar origin sweep is the radar destination sweep

Returns

field_dest [dict] interpolated field and metadata

pyrad.io.make_filename (*prdtype, dstype, dsname, ext_list, prdcfginfo=None, timeinfo=None, timeformat='%Y%m%d%H%M%S', runinfo=None*)
creates a product file name

Parameters

timeinfo [datetime] time info to generate the date directory

prdtype [str] product type, i.e. 'ppi', etc.

dstype [str] data set type, i.e. 'raw', etc.

dsname [str] data set name

ext_list [list of str] file name extensions, i.e. 'png'

prdcfginfo [str] Optional. string to add product configuration information, i.e. 'el0.4'

timeformat [str] Optional. The time format

runinfo [str] Optional. Additional information about the test (e.g. 'RUN01', 'TS011')

Returns

fname_list [list of str] list of file names (as many as extensions)

pyrad.io.map_Doppler (*Doppler_data_bin, Nyquist_vel*)
maps the binary METRANET Doppler data to actual Doppler velocity

Parameters

Doppler_data_bin [numpy array] The binary METRANET data

Returns

Doppler_data [numpy array] The Doppler velocity in [m/s]

pyrad.io.map_hydro (*hydro_data_op*)
maps the operational hydrometeor classification identifiers to the ones used by Py-ART

Parameters

hydro_data_op [numpy array] The operational hydrometeor classification data

Returns

hydro_data_py [numpy array] The pyart hydrometeor classification data

pyrad.io.read_antenna_pattern (*fname, linear=False, twoway=False*)
Read antenna pattern from file

Parameters

fname [str] path of the antenna pattern file

linear [boolean] if true the antenna pattern is given in linear units

twoway [boolean] if true the attenuation is two-way

Returns

pattern [dict] dictionary with the fields angle and attenuation

`pyrad.io.read_colocated_data(fname)`

Reads a csv files containing colocated data

Parameters

fname [str] path of time series file

Returns

rad1_time, rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azimuth, rad1_rng,
rad1_val, rad2_time, rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azimuth,
rad2_rng, rad2_val [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_colocated_gates(fname)`

Reads a csv files containing the position of colocated gates

Parameters

fname [str] path of time series file

Returns

rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azimuth, rad1_rng,
rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azimuth, rad2_rng [tuple] A tuple with the data
read. None otherwise

`pyrad.io.read_config(fname, cfg=None)`

Read a pyrad config file.

Parameters

fname [str] Name of the configuration file to read.

cfg [dict of dicts, optional] dictionary of dictionaries containing configuration parameters where
the new parameters will be placed

Returns

cfg [dict of dicts] dictionary of dictionaries containing the configuration parameters

`pyrad.io.read_cosmo_coord(fname, zmin=None)`

Reads COSMO coordinates from a netcdf file

Parameters

fname [str] name of the file to read

Returns

cosmo_coord [dictionary] dictionary with the data and metadata

`pyrad.io.read_cosmo_data(fname, field_names=['temperature'], celsius=True)`

Reads COSMO data from a netcdf file

Parameters

fname [str] name of the file to read

field_names [str] name of the variable to read

celsius [Boolean] if True and variable temperature converts data from Kelvin to Centigrade

Returns

cosmo_data [dictionary] dictionary with the data and metadata

`pyrad.io.read_disdro_scattering(fname)`

Reads scattering parameters computed from disdrometer data contained in a text file

Parameters

fname [str] path of time series file

Returns

date, precipitype, lwc, rr, zh, zv, zdr, ldr, ah, av, adiff, kdp, deltaco,

rhohv [tuple] The read values

`pyrad.io.read_excess_gates(fname)`

Reads a csv files containing the position of gates exceeding a given percentile of frequency of occurrence

Parameters

fname [str] path of time series file

Returns

rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azi, rad1_rng,

rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azi, rad2_rng [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_histogram(fname)`

Reads a histogram contained in a csv file

Parameters

fname [str] path of time series file

Returns

hist, bin_edges [tuple] The read data. None otherwise

`pyrad.io.read_histogram_ts(fname_list, datatype, t_res=300.0)`

Reads a collection of histogram data file and creates a time series

Parameters

fname_list [str] list of files to read

datatype [str] The data type (dBZ, ZDR, etc.)

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, bin_edges, data_ma, datetime_arr[0] [tuple] The read data. None otherwise

`pyrad.io.read_hzt_data(fname, chy0=255.0, chx0=-160.0)`

Reads iso-0 degree data from an HZT file

Parameters

fname [str] name of the file to read

chy0, chx0: south west point of grid in Swiss coordinates [km]

Returns

hzt_data [dictionary] dictionary with the data and metadata

`pyrad.io.read_intercomp_scores_ts(fname, sort_by_date=False)`

Reads a radar intercomparison scores csv file

Parameters

fname [str] path of time series file

sort_by_date [bool] if True, the read data is sorted by date prior to exit

Returns

date_vec, np_vec, meanbias_vec, medianbias_vec, quant25bias_vec, quant75bias_vec, modebias_vec, corr_vec, slope_vec, intercep_vec, intercep_slope1_vec [tuple] The read data. None otherwise

`pyrad.io.read_last_state(fname)`

Reads a file containing the date of acquisition of the last volume processed

Parameters

fname [str] name of the file to read

Returns

last_state [datetime object] the date

`pyrad.io.read_lightning(fname, filter_data=True)`

Reads lightning data contained in a text file. The file has the following fields:

flashnr: (0 is for noise) UTC seconds of the day Time within flash (in seconds) Latitude (decimal degrees) Longitude (decimal degrees) Altitude (m MSL) Power (dBm)

Parameters

fname [str] path of time series file

filter_data [Boolean] if True filter noise (flashnr = 0)

Returns

flashnr, time_data, time_in_flash, lat, lon, alt, dBm [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_lightning_all(fname, labels=['hydro [-]', 'KDPc [deg/Km]', 'dBZc [dBZ]', 'Rho-HVc [-]', 'TEMP [deg C]', 'ZDRc [dB]'])`

Reads a file containing lightning data and co-located polarimetric data. fields:

flashnr time data Time within flash (in seconds) Latitude (decimal degrees) Longitude (decimal degrees) Altitude (m MSL) Power (dBm) Polarimetric values at flash position

Parameters

fname [str] path of time series file

labels [list of str] The polarimetric variables labels

Returns

flashnr, time_data, time_in_flash, lat, lon, alt, dBm, pol_vals_dict [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_lightning_traj(fname)`

Reads lightning trajectory data contained in a csv file. The file has the following fields:

Date UTC [seconds since midnight] # Flash Flash Power (dBm) Value at flash Mean value in a 3x3x3 polar box Min value in a 3x3x3 polar box Max value in a 3x3x3 polar box # valid values in the polar box

Parameters

fname [str] path of time series file

Returns

time_flash, flashnr, dBm, val_at_flash, val_mean, val_min, val_max,

nval [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_meteorage(fname)`

Reads METEORAGE lightning data contained in a text file. The file has the following fields:

date: date + time + time zone lon: longitude [degree] lat: latitude [degree] intens: amplitude [kilo amperes] ns: number of strokes of the flash mode: kind of localization [0,15] intra: 1 = intra-cloud, 0 = cloud-to-ground ax: length of the semi-major axis of the ellipse [km] ki2: standard deviation on the localization computation (Ki^2) ecc: eccentricity (major-axis / minor-axis) incl: ellipse inclination (angle with respect to the North, +90° is

East) [degrees]

sind: stroke index within the flash

Parameters

fname [str] path of time series file

Returns

stroke_time, lon, lat, intens, ns, mode, intra, ax, ki2, ecc, incl,

sind [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_ml_ts(fname)`

Reads a melting layer time series contained in a csv file

Parameters

fname [str] path of time series file

Returns

dt_ml, ml_top_avg, ml_top_std, thick_avg, thick_std, nrays_valid,

nrays_total [tuple] The read data. None otherwise

`pyrad.io.read_monitoring_ts(fname, sort_by_date=False)`

Reads a monitoring time series contained in a csv file

Parameters

fname [str] path of time series file

sort_by_date [bool] if True, the read data is sorted by date prior to exit

Returns

date, np_t, central_quantile, low_quantile, high_quantile [tuple] The read data. None otherwise

`pyrad.io.read_profile_ts` (*fname_list, labels, hres=None, label_nr=0, t_res=300.0*)

Reads a collection of profile data file and creates a time series

Parameters

fname_list [str] list of files to read

labels [list of str] The data labels

hres [float] Height resolution

label_nr [int] the label nr of the data that will be used in the time series

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, hbin_edges, np_ma, data_ma, datetime_arr[0] [tuple] The read data. None otherwise

`pyrad.io.read_quantiles` (*fname*)

Reads quantiles contained in a csv file

Parameters

fname [str] path of time series file

Returns

quantiles, values [tuple] The read data. None otherwise

`pyrad.io.read_quantiles_ts` (*fname_list, step=5.0, qmin=0.0, qmax=100.0, t_res=300.0*)

Reads a collection of quantiles data file and creates a time series

Parameters

fname_list [str] list of files to read

step, qmin, qmax [float] The minimum, maximum and step quantiles

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, qbin_edges, data_ma, datetime_arr[0] [tuple] The read data. None otherwise

`pyrad.io.read_rad4alp_cosmo` (*fname, datatype, ngates=0*)

Reads rad4alp COSMO data binary file.

Parameters

fname [str] name of the file to read

datatype [str] name of the data type

ngates [int] maximum number of range gates per ray. If larger than 0 the radar field will be cut accordingly.

Returns

field [dictionary] The data field

`pyrad.io.read_rad4alp_vis` (*fname, datatype*)

Reads rad4alp visibility data binary file.

Parameters

fname [str] name of the file to read

datatype [str] name of the data type

Returns

field_list [list of dictionaries] A data field. Each element of the list corresponds to one elevation

`pyrad.io.read_rhi_profile(fname, labels=['50.0-percentile', '25.0-percentile', '75.0-percentile'])`

Reads a monitoring time series contained in a csv file

Parameters

fname [str] path of time series file

labels [list of str] The data labels

Returns

height, np_t, vals [tuple] The read data. None otherwise

`pyrad.io.read_selfconsistency(fname)`

Reads a self-consistency table with Zdr, Kdp/Zh columns

Parameters

fname [str] path of time series file

Returns

zdr, kdpzh [arrays] The read values

`pyrad.io.read_smn(fname)`

Reads SwissMetNet data contained in a csv file

Parameters

fname [str] path of time series file

Returns

smn_id, date , pressure, temp, rh, precip, wspeed, wdir [tuple] The read values

`pyrad.io.read_smn2(fname)`

Reads SwissMetNet data contained in a csv file with format station,time,value

Parameters

fname [str] path of time series file

Returns

smn_id, date , value [tuple] The read values

`pyrad.io.read_solar_flux(fname)`

Reads solar flux data from the DRAO observatory in Canada

Parameters

fname [str] path of time series file

Returns

flux_datetime [datetime array] the date and time of the solar flux retrievals

flux_value [array] the observed solar flux

`pyrad.io.read_status(voltime, cfg, ind_rad=0)`

Reads rad4alp xml status file.

Parameters

volttime [datetime object] volume scan time

cfg: dictionary of dictionaries configuration info to figure out where the data is

ind_rad: int radar index

Returns

root [root element object] The information contained in the status file

`pyrad.io.read_sun_hits` (*fname*)

Reads sun hits data contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, ray, nrng, rad_el, rad_az, sun_el, sun_az, ph, ph_std, npv, nvalh,

pv, pv_std, npv, nvalv, zdr, zdr_std, nzdr, nvalzdr [tuple] Each parameter is an array containing a time series of information on a variable

`pyrad.io.read_sun_hits_multiple_days` (*cfg, time_ref, nfiles=1*)

Reads sun hits data from multiple file sources

Parameters

cfg [dict] dictionary with configuration data to find out the right file

time_ref [datetime object] reference time

nfiles [int] number of files to read

Returns

date, ray, nrng, rad_el, rad_az, sun_el, sun_az, ph, ph_std, npv, nvalh,

pv, pv_std, npv, nvalv, zdr, zdr_std, nzdr, nvalzdr [tuple] Each parameter is an array containing a time series of information on a variable

`pyrad.io.read_sun_retrieval` (*fname*)

Reads sun retrieval data contained in a csv file

Parameters

fname [str] path of time series file

Returns

first_hit_time, last_hit_time, nhits_h, el_width_h, az_width_h, el_bias_h,

az_bias_h, dBm_sun_est, std_dBm_sun_est, sf_h,

nhits_v, el_width_v, az_width_v, el_bias_v, az_bias_v, dBmv_sun_est,

std_dBmv_sun_est, sf_v,

nhits_zdr, zdr_sun_est, std_zdr_sun_est,

sf_ref, ref_time [tuple] Each parameter is an array containing a time series of information on a variable

`pyrad.io.read_timeseries` (*fname*)

Reads a time series contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, value [tuple] A datetime object array containing the time and a numpy masked array containing the value. None otherwise

`pyrad.io.read_trt_cell_lightning(fname)`

Reads the lightning data of a TRT cell. The file has the following fields:

traj_ID yyyyymmddHHMM lon lat area RANKr nflashes flash_dens

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_trt_data(fname)`

Reads the TRT data contained in a text file. The file has the following fields:

traj_ID yyyyymmddHHMM

Description of ellipsis: lon [deg] lat [deg] ell_L [km] long ell_S [km] short ell_or [deg] orientation area [km2]

Cell speed: vel_x [km/h] vel_y [km/h] det [dBZ]: detection threshold RANKr from 0 to 40 (int)

Lightning information: CG- number (int) CG+ number (int) CG number (int) %CG+ [%]

Echo top information: ET45 [km] echotop 45 max ET45m [km] echotop 45 median ET15 [km] echotop 15 max ET15m [km] echotop 15 median

VIL and max echo: VIL [kg/m2] vertical integrated liquid content maxH [km] height of maximum reflectivity (maximum on the cell) maxHm [km] height of maximum reflectivity (median per cell)

POH [%] RANK (deprecated)

standard deviation of the current time step cell velocity respect to the previous time: Dvel_x [km/h] Dvel_y [km/h]

cell_contour_lon-lat

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_trt_scores(fname)`

Reads the TRT scores contained in a text file. The file has the following fields:

traj ID max flash density time max flash density rank max flash density max rank time max rank

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_trt_traj_data(fname)`

Reads the TRT cell data contained in a text file. The file has the following fields:

traj_ID yyyyymmddHHMM

lon [deg] lat [deg] ell_L [km] long ell_S [km] short ell_or [deg] orientation area [km2]

vel_x [km/h] cell speed vel_y [km/h] det [dBZ] detection threshold RANKr from 0 to 40 (int)

CG- number (int) CG+ number (int) CG number (int) %CG+ [%]

ET45 [km] echotop 45 max ET45m [km] echotop 45 median ET15 [km] echotop 15 max ET15m [km] echotop 15 median VIL [kg/m2] vertical integrated liquid content maxH [km] height of maximum reflectivity (maximum on the cell) maxHm [km] height of maximum reflectivity (median per cell) POH [%] RANK (deprecated)

Standard deviation of the current time step cell velocity respect to the previous time: Dvel_x [km/h]
Dvel_y [km/h]

cell_contour_lon-lat

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_ts_cum(fname)`

Reads a time series of precipitation accumulation contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, np_radar, radar_value, np_sensor, sensor_value [tuple] The data read

`pyrad.io.send_msg(sender, receiver_list, subject, fname)`

sends the content of a text file by email

Parameters

sender [str] the email address of the sender

receiver_list [list of string] list with the email addresses of the receiver

subject [str] the subject of the email

fname [str] name of the file containing the content of the email message

Returns

fname [str] the name of the file containing the content

`pyrad.io.write_alarm_msg(radar_name, param_name_unit, date_last, target, tol_abs, np_trend, value_trend, tol_trend, nevents, np_last, value_last, fname)`

writes an alarm file

Parameters

radar_name [str] Name of the radar being controlled

param_name_unit [str] Parameter and units

date_last [datetime object] date of the current event

target, tol_abs [float] Target value and tolerance
np_trend [int] Total number of points in trend
value_trend, tol_trend [float] Trend value and tolerance
nevents: int Number of events in trend
np_last [int] Number of points in the current event
value_last [float] Value of the current event
fname [str] Name of file where to store the alarm information

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_cdf` (*quantiles, values, ntot, nnan, nclut, nblocked, nprec_filter, noutliers, ncdf, fname, use_nans=False, nan_value=0.0, filterprec=[], vismin=None, sector=None, datatype=None, timeinfo=None*)
 writes a cumulative distribution function

Parameters

quantiles [datetime array] array containing the measurement time
values [float array] array containing the average value
fname [float array] array containing the standard deviation
sector [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_colocated_data` (*coloc_data, fname*)
 Writes the data of gates colocated with two radars

Parameters

coloc_data [dict] dictionary containing the colocated data parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_colocated_data_time_avg` (*coloc_data, fname*)
 Writes the time averaged data of gates colocated with two radars

Parameters

coloc_data [dict] dictionary containing the colocated data parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_colocated_gates` (*coloc_gates, fname*)
 Writes the position of gates colocated with two radars

Parameters

coloc_gates [dict] dictionary containing the colocated gates parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_excess_gates` (*excess_dict, fname*)

Writes the position and values of gates that have a frequency of occurrence higher than a particular threshold

Parameters

excess_dict [dict] dictionary containing the gates parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_field_coverage` (*quantiles, values, ele_start, ele_stop, azi_start, azi_stop, threshold, nvalid_min, datatype, timeinfo, fname*)

writes the quantiles of the coverage on a particular sector

Parameters

quantiles [datetime array] array containing the quantiles computed

values [float array] quantile value

ele_start, ele_stop, azi_start, azi_stop [float] The limits of the sector

threshold [float] The minimum value to consider the data valid

nvalid_min [int] the minimum number of points to consider that there are values in a ray

datatype [str] data type and units

timeinfo [datetime object] the time stamp of the data

fname [str] name of the file where to write the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_histogram` (*bin_edges, values, fname, datatype='undefined', step=0*)

writes a histogram

Parameters

bin_edges [float array] array containing the histogram bin edges

values [int array] array containing the number of points in each bin

fname [str] file name

datatype :str The data type

step [str] The bin step

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_intercomp_scores_ts` (*start_time, stats, field_name, fname, rad1_name='RADAR001', rad2_name='RADAR002', rewrite=False*)

writes time series of radar intercomparison scores

Parameters

start_time [datetime object or array of date time objects] the time of the intercomparison
stats [dict] dictionary containing the statistics
field_name [str] The name of the field
fname [str] file name where to store the data
rad1_name, rad2_name [str] Name of the radars intercompared
rewrite [bool] if True a new file is created

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_last_state(datetime_last, fname)`
 writes SwissMetNet data in format datetime, avg_value, std_value

Parameters

datetime_last [datetime object] date and time of the last state
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_monitoring_ts(start_time, np_t, values, quantiles, datatype, fname, rewrite=False)`
 writes time series of data

Parameters

start_time [datetime object or array of date time objects] the time of the monitoring
np_t [int or array of ints] the total number of points
values: float array with 3 elements of array of arrays the values at certain quantiles
quantiles: float array with 3 elements the quantiles computed
datatype [str] The data type
fname [str] file name where to store the data
rewrite [bool] if True a new file is created

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_quantiles(quantiles, values, fname, datatype='undefined')`
 writes quantiles

Parameters

quantiles [float array] array containing the quantiles to write
values [float array] array containing the value of each quantile
fname [str] file name
datatype :str The data type

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_rhi_profile(hvec, data, nvalid_vec, labels, fname, datatype=None, timeinfo=None, sector=None)`
writes the values of an RHI profile in a text file

Parameters

hvec [float array] array containing the altitude in m MSL
data [list of float array] the quantities at each altitude
nvalid_vec [int array] number of valid data points used to compute the quantiles
labels [list of strings] label specifying the quantities in data
fname [str] file name where to store the data
datatype [str] the data type
timeinfo [datetime object] time of the rhi profile
sector [dict] dictionary specifying the sector limits

Returns

fname [str] the name of the file where data has been written

`pyrad.io.write_smn(datetime_vec, value_avg_vec, value_std_vec, fname)`
writes SwissMetNet data in format datetime, avg_value, std_value

Parameters

datetime_vec [datetime array] array containing the measurement time
value_avg_vec [float array] array containing the average value
value_std_vec [float array] array containing the standard deviation
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_sun_hits(sun_hits, fname)`
Writes sun hits data.

Parameters

sun_hits [dict] dictionary containing the sun hits parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_sun_retrieval(sun_retrieval, fname)`
Writes sun retrieval data.

Parameters

sun_retrieval [dict] dictionary containing the sun retrieval parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written


```
pyrad.io.write_trt_cell_data(traj_ID, yyyyymmddHHMM, lon, lat, ell_L, ell_S, ell_or, area,
                             vel_x, vel_y, det, RANKr, CG_n, CG_p, CG, CG_percent_p, ET45,
                             ET45m, ET15, ET15m, VIL, maxH, maxHm, POH, RANK, Dvel_x,
                             Dvel_y, cell_contour, fname)
```

writes TRT cell data

Parameters

traj_ID, **yyyyymmddHHMM**, **lon**, **lat**, **ell_L**, **ell_S**, **ell_or**, **area**,
vel_x, **vel_y**, **det**, **RANKr**, **CG_n**, **CG_p**, **CG**, **CG_percent_p**, **ET45**,
ET45m, **ET15**, **ET15m**, **VIL**, **maxH**, **maxHm**, **POH**, **RANK**, **Dvel_x**,
Dvel_y, **cell_contour**: the cell parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_trt_cell_lightning(cell_ID, cell_time, lon, lat, area, rank, nflash, flash_density,
                                   fname)
```

writes the lightning data for each TRT cell

Parameters

cell_ID [array of ints] the cell ID
cell_time [array of datetime] the time step
lon, **lat** [array of floats] the latitude and longitude of the center of the cell
area [array of floats] the area of the cell
rank [array of floats] the rank of the cell
nflash [array of ints] the number of flashes/sources within the cell
flash_density [array of floats] the flash/source density
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_trt_cell_scores(traj_ID, flash_density_max_time, flash_density_max_rank,
                               nflashes_max_list, area_flash_max_list, flash_density_max,
                               rank_max_time, rank_max, fname)
```

writes TRT cells scores

Parameters

traj_ID [array of ints] The ID of the cells
flash_density_max_time [array of date times] The time at which the maximum flash density
was reached for each cell
flash_density_max_rank [array of floats] The rank when the maximum flash density was
reached for each cell
nflashes_max_list [array of ints] the number of flashes when the max flash density was reached
area_flash_max_list [array of floats] The area when the max flash density was reached
flash_density_max [array of floats] The maximum flash density for each cell

rank_max_time [array of datetime] the time at wich the maximum rank of each cell was reached

rank_max [array of float] the rank when the maximum rank of each cell was reached

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_ts_cum(dataset, fname)`
writes time series accumulation of data

Parameters

dataset [dict] dictionary containing the time series parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_ts_lightning(flashnr, time_data, time_in_flash, lat, lon, alt, dBm, vals_list, fname, pol_vals_labels)`
writes the LMA sources data and the value of the colocated polarimetric variables

Parameters

flashnr [int] flash number

time_data [datetime object] flash source time

time_in_flash [float] seconds since start of flash

lat, lon, alt [float] latitude, longitude [deg] and altitude [m MSL] of the flash source

dBm [float] flash power

vals_list [list of arrays] List containing the data for each polarimetric variable

fname [str] the name of the file containing the content

pol_values_labels [list of strings] List containing strings identifying each polarimetric variable

Returns

fname [str] the name of the file containing the content

`pyrad.io.write_ts_polar_data(dataset, fname)`
writes time series of data

Parameters

dataset [dict] dictionary containing the time series parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

PLOTING (PYRAD . GRAPH)

Functions to plot graphics.

5.1 Plots

<i>plot_surface</i> (grid, field_name, level, ...)	plots a surface from gridded data
<i>plot_latitude_slice</i> (grid, field_name, lon, ...)	plots a latitude slice from gridded data
<i>plot_longitude_slice</i> (grid, field_name, lon, ...)	plots a longitude slice from gridded data
<i>plot_latlon_slice</i> (grid, field_name, coord1, ...)	plots a croos section crossing two points in the grid
<i>plot_ppi</i> (radar, field_name, ind_el, prdcfg, ...)	plots a PPI
<i>plot_ppi_contour</i> (radar, field_name, ind_el, ...)	plots contour data on a PPI
<i>plot_ppi_map</i> (radar, field_name, ind_el, ...)	plots a PPI on a geographic map
<i>plot_rhi</i> (radar, field_name, ind_az, prdcfg, ...)	plots an RHI
<i>plot_rhi_contour</i> (radar, field_name, ind_az, ...)	plots contour data on an RHI
<i>plot_bscope</i> (radar, field_name, ind_sweep, ...)	plots a B-Scope (angle-range representation)
<i>plot_time_range</i> (radar, field_name, ...)	plots a time-range plot
<i>plot_rhi_profile</i> (data_list, hvec, fname_list)	plots an RHI profile
<i>plot_along_coord</i> (xval_list, yval_list, ...)	plots a time series
<i>plot_field_coverage</i> (xval_list, yval_list, ...)	plots a time series
<i>plot_density</i> (hist_obj, hist_type, ...[, ...])	density plot (angle-values representation)
<i>plot_cappi</i> (radar, field_name, altitude, ...)	plots a Constant Altitude Plan Position Indicator CAPPI
<i>plot_traj</i> (rng_traj, azi_traj, ele_traj, ...)	plots a trajectory on a Cartesian surface
<i>plot_pos</i> (lat, lon, alt, fname_list[, ax, ...])	plots a trajectory on a Cartesian surface
<i>plot_quantiles</i> (quant, value, fname_list[, ...])	plots quantiles
<i>plot_histogram</i> (bin_edges, values, fname_list)	computes and plots histogram
<i>plot_histogram2</i> (bin_centers, hist, fname_list)	plots histogram
<i>plot_antenna_pattern</i> (antpattern, fname_list)	plots an antenna pattern
<i>plot_timeseries</i> (tvec, data_list, fname_list)	plots a time series
<i>plot_timeseries_comp</i> (date1, value1, date2, ...)	plots 2 time series in the same graph
<i>plot_monitoring_ts</i> (date, np_t, cquant, ...)	plots a time series of monitoring data
<i>plot_scatter_comp</i> (value1, value2, fname_list)	plots the scatter between two time series
<i>plot_intercomp_scores_ts</i> (date_vec, np_vec, ...)	plots a time series of radar intercomparison scores
<i>plot_ml_ts</i> (dt_ml_arr, ml_top_avg_arr, ...[, ...])	plots a time series of melting layer data
<i>plot_sun_hits</i> (field, field_name, fname_list, ...)	plots the sun hits

Continued on next page

Table 1 – continued from previous page

<code>plot_sun_retrieval_ts</code> (sun_retrieval, ..., plots sun retrieval time series series ...))	
<code>get_colobar_label</code> (field_dict, field_name)	creates the colorbar label using field metadata
<code>get_field_name</code> (field_dict, field)	Return a nice field name for a particular field
<code>_plot_time_range</code> (rad_time, rad_range, ..., plots a time-range plot ...))	

`pyrad.graph.get_colobar_label` (*field_dict*, *field_name*)
creates the colorbar label using field metadata

Parameters

field_dict [dict] dictionary containing field metadata

field_name [str] name of the field

Returns

label [str] colorbar label

`pyrad.graph.get_field_name` (*field_dict*, *field*)
Return a nice field name for a particular field

Parameters

field_dict [dict] dictionary containing field metadata

field [str] name of the field

Returns

field_name [str] the field name

`pyrad.graph.plot_along_coord` (*xval_list*, *yval_list*, *fname_list*, *labelx*='coord', *labely*='Value',
labels=None, *title*='Plot along coordinate', *colors*=None,
linestyles=None, *ymin*=None, *ymax*=None, *dpi*=72)

plots a time series

Parameters

xval_list [list of float arrays] the x values, range, azimuth or elevation

yval_list [list of float arrays] the y values. Parameter to plot

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

labels [array of str] The label of the legend

title [str] The figure title

colors [array of str] Specifies the colors of each line

linestyles [array of str] Specifies the line style of each line

ymin, ymax: float Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_antenna_pattern` (*antpattern*, *fname_list*, *labelx*='Angle [Deg]', *linear*=False, *twoway*=False, *title*='Antenna Pattern', *ymin*=None, *ymax*=None, *dpi*=72)

plots an antenna pattern

Parameters

antpattern [dict] dictionary with the angle and the attenuation
value [float array] values of the time series
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
linear [boolean] if true data is in linear units
linear [boolean] if true data represents the two way attenuation
titl [str] The figure title
ymin, ymax: float Lower/Upper limit of y axis
dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_bscope` (*radar*, *field_name*, *ind_sweep*, *prdcfg*, *fname_list*)
 plots a B-Scope (angle-range representation)

Parameters

radar [Radar object] object containing the radar data to plot
field_name [str] name of the radar field to plot
ind_sweep [int] sweep index to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_cappi` (*radar*, *field_name*, *altitude*, *prdcfg*, *fname_list*, *save_fig*=True)
 plots a Constant Altitude Plan Position Indicator CAPPI

Parameters

radar [Radar object] object containing the radar data to plot
field_name [str] name of the radar field to plot
altitude [float] the altitude [m MSL] to be plotted
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure and axes

`pyrad.graph.plot_density` (*hist_obj*, *hist_type*, *field_name*, *ind_sweep*, *prdcfg*, *fname_list*, *quantiles*=[25.0, 50.0, 75.0], *ref_value*=0.0, *vmin*=None, *vmax*=None)
density plot (angle-values representation)

Parameters

hist_obj [histogram object] object containing the histogram data to plot

hist_type [str] type of histogram (instantaneous data or cumulative)

field_name [str] name of the radar field to plot

ind_sweep [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

quantiles [array] the quantile lines to plot

ref_value [float] the reference value

vmin, vmax [float] Minimum and maximum extend of the vertical axis

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_field_coverage` (*xval_list*, *yval_list*, *fname_list*, *labelx*='Azimuth (deg)', *labely*='Range extension [m]', *labels*=None, *title*='Field coverage', *ymin*=None, *ymax*=None, *xmeanval*=None, *ymeanval*=None, *labelmeanval*=None, *dpi*=72)

plots a time series

Parameters

xval_list [list of float arrays] the x values, azimuth

yval_list [list of float arrays] the y values. Range extension

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

labels [array of str] The label of the legend

title [str] The figure title

ymin, ymax [float] Lower/Upper limit of y axis

xmeanval, ymeanval [float array] the x and y values of a mean along elevation

labelmeanval [str] the label of the mean

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_histogram` (*bin_edges*, *values*, *fname_list*, *labelx*='bins', *labely*='Number of Samples', *title*='histogram', *dpi*=72)

computes and plots histogram

Parameters

bin_edges [array] histogram bin edges
values [array] data values
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
labely [str] The label of the Y axis
titl [str] The figure title
dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_histogram2(bin_centers, hist, fname_list, labelx='bins', labely='Number of Samples', titl='histogram', dpi=72, ax=None, fig=None, save_fig=True, color=None, alpha=None, invert_xaxis=False)`

plots histogram

Parameters

bin_centers [array] histogram bin centers
hist [array] values for each bin
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
labely [str] The label of the Y axis
titl [str] The figure title
dpi [int] dots per inch
fig [Figure] Figure to add the colorbar to. If none a new figure will be created
ax [Axis] Axis to plot on. if fig is None a new axis will be created
save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure
color [str] color of the bars
alpha [float] parameter controlling the transparency
invert_xaxis [bool] If true inverts the x axis

Returns

fname_list or fig, ax: list of str list of names of the created plots

`pyrad.graph.plot_intercomp_scores_ts(date_vec, np_vec, meanbias_vec, medianbias_vec, quant25bias_vec, quant75bias_vec, modebias_vec, corr_vec, slope_vec, intercep_vec, intercep_slope1_vec, fname_list, ref_value=0.0, np_min=0, corr_min=0.0, labelx='Time UTC', titl='RADAR001-RADAR002 intercomparison', dpi=72)`

plots a time series of radar intercomparison scores

Parameters

date_vec [datetime object] time of the time series
np_vec [int array] number of points

meanbias_vec, medianbias_vec, modebias_vec [float array] mean, median and mode bias

quant25bias_vec, quant75bias_vec: 25th and 75th percentile of the bias

corr_vec [float array] correlation

slope_vec, intercep_vec [float array] slope and intercep of a linear regression

intercep_slope1_vec [float] the intercep point of a inear regression of slope 1

ref_value [float] the reference value

np_min [int] The minimum number of points to consider the result valid

corr_min [float] The minimum correlation to consider the results valid

labelx [str] The label of the X axis

titl [str] The figure title

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_latitude_slice` (*grid, field_name, lon, lat, prdcfg, fname_list*)
plots a latitude slice from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot

field_name [str] name of the radar field to plot

lon, lat [float] coordinates of the slice to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_latlon_slice` (*grid, field_name, coord1, coord2, prdcfg, fname_list*)
plots a croos section crossing two points in the grid

Parameters

grid [Grid object] object containing the gridded data to plot

field_name [str] name of the radar field to plot

coord1 [tuple of floats] lat, lon of the first point

coord2 [tuple of floats] lat, lon of the second point

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_longitude_slice` (*grid, field_name, lon, lat, prdcfg, fname_list*)
plots a longitude slice from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot

field_name [str] name of the radar field to plot

lon, lat [float] coordinates of the slice to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_ml_ts(dt_ml_arr, ml_top_avg_arr, ml_top_std_arr, thick_avg_arr, thick_std_arr,
                        nrays_valid_arr, nrays_total_arr, fname_list, labelx='Time UTC',
                        titl='Melting layer time series', dpi=72)
```

plots a time series of melting layer data

Parameters

dt_ml_arr [datetime object] time of the time series

np_vec [int array] number of points

meanbias_vec, medianbias_vec, modebias_vec [float array] mean, median and mode bias

quant25bias_vec, quant75bias_vec: 25th and 75th percentile of the bias

corr_vec [float array] correlation

slope_vec, intercep_vec [float array] slope and intercep of a linear regression

intercep_slope1_vec [float] the intercep point of a inear regression of slope 1

ref_value [float] the reference value

np_min [int] The minimum number of points to consider the result valid

corr_min [float] The minimum correlation to consider the results valid

labelx [str] The label of the X axis

titl [str] The figure title

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_monitoring_ts(date, np_t, cquant, lquant, hquant, field_name, fname_list,
                                ref_value=None, vmin=None, vmax=None, np_min=0, la-
                                belx='Time [UTC]', labely='Value', titl='Time Series', dpi=72)
```

plots a time series of monitoring data

Parameters

date [datetime object] time of the time series

np_t [int array] number of points

cquant, lquant, hquant [float array] values of the central, low and high quantiles

field_name [str] name of the field

fname_list [list of str] list of names of the files where to store the plot

ref_value [float] the reference value

vmin, vmax [float] The limits of the y axis

np_min [int] minimum number of points to consider the sample plotable

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_pos(lat, lon, alt, fname_list, ax=None, fig=None, save_fig=True,
                     sort_altitude='No', dpi=72, alpha=1.0, cb_label='height [m MSL]',
                     titl='Position', xlabel='Lon [Deg]', ylabel='Lat [Deg]', limits=None,
                     vmin=None, vmax=None)
```

plots a trajectory on a Cartesian surface

Parameters

lat, lon, alt [float array] Points coordinates

fname_list [list of str] list of names of the files where to store the plot

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

sort_altitude [str] String indicating whether to sort the altitude data. Can be 'No', 'Lowest_on_top' or 'Highest_on_top'

dpi [int] Pixel density

alpha [float] Transparency

cb_label [str] Color bar label

titl [str] Plot title

limits [tuple or None] The limits of the field to plot

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure and axes

```
pyrad.graph.plot_ppi(radar, field_name, ind_el, prdcfg, fname_list, plot_type='PPI', titl=None,
                    step=None, quantiles=None, save_fig=True)
```

plots a PPI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

plot_type [str] type of plot (PPI, QUANTILES or HISTOGRAM)

titl [str] Plot title

step [float] step for histogram plotting

quantiles [float array] quantiles to plot

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_ppi_contour(radar, field_name, ind_el, prdcfg, fname_list,
                             contour_values=None, linewidths=1.5, ax=None, fig=None,
                             save_fig=True)
```

plots contour data on a PPI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

contour_values [float array] list of contours to plot

linewidths [float] width of the contour lines

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plot_ppi_map(radar, field_name, ind_el, prdcfg, fname_list)
```

plots a PPI on a geographic map

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_quantiles(quant, value, fname_list, labelx='quantile', labely='value',
                           titl='quantile', vmin=None, vmax=None, dpi=72)
```

plots quantiles

Parameters

quant [array] quantiles to be plotted

value [array] values of each quantile
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
labely [str] The label of the Y axis
titl [str] The figure title
vmin, vmax: float Lower/Upper limit of data values
dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_rhi` (*radar, field_name, ind_az, prdcfg, fname_list, plot_type='RHI', titl=None, step=None, quantiles=None, save_fig=True*)
plots an RHI

Parameters

radar [Radar object] object containing the radar data to plot
field_name [str] name of the radar field to plot
ind_az [int] sweep index to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
plot_type [str] type of plot (PPI, QUANTILES or HISTOGRAM)
titl [str] Plot title
step [float] step for histogram plotting
quantiles [float array] quantiles to plot
save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str] list of names of the created plots
fig, ax [tuple] list of names of the saved plots or handle of the figure and axes

`pyrad.graph.plot_rhi_contour` (*radar, field_name, ind_az, prdcfg, fname_list, contour_values=None, linewidths=1.5, ax=None, fig=None, save_fig=True*)

plots contour data on an RHI

Parameters

radar [Radar object] object containing the radar data to plot
field_name [str] name of the radar field to plot
ind_az [int] sweep index to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
contour_values [float array] list of contours to plot

linewidths [float] width of the contour lines

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plot_rhi_profile(data_list, hvec, fname_list, labelx='Value', labely='Height
(m MSL)', labels=['Mean'], title='RHI profile', colors=None,
linestyles=None, vmin=None, vmax=None, hmin=None,
hmax=None, dpi=72)
```

plots an RHI profile

Parameters

data_list [list of float array] values of the profile

hvec [float array] height points of the profile

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

labels [array of str] The label of the legend

title [str] The figure title

colors [array of str] Specifies the colors of each line

linestyles [array of str] Specifies the line style of each line

vmin, vmax: float Lower/Upper limit of data values

hmin, hmax: float Lower/Upper limit of altitude

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_scatter(bin_edges1, bin_edges2, hist_2d, field_name1, field_name2, fname_list,
prdcfg, metadata=None, lin_regr=None, lin_regr_slope1=None,
rad1_name='RADAR001', rad2_name='RADAR002')
```

2D histogram

Parameters

bin_edges1, bin_edges2 [float array2] the bins of each field

hist_2d [ndarray 2D] the 2D histogram

field_name1, field_name2 [str] the names of each field

fname_list [list of str] list of names of the files where to store the plot

prdcfg [dict] product configuration dictionary

metadata [str] a string with metadata to write in the plot

lin_regr [tuple with 2 values] the coefficients for a linear regression

lin_regr_slope1 [float] the intercept point of a linear regression of slope 1

rad1_name, rad2_name [str] name of the radars which data is used

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_scatter_comp` (*value1, value2, fname_list, labelx='Sensor 1', labely='Sensor 2', titl='Scatter', axis=None, metadata=None, dpi=72*)
plots the scatter between two time series

Parameters

value1 [float array] values of the first time series

value2 [float array] values of the second time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

axis [str] type of axis

metadata [string] a string containing metadata

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_sun_hits` (*field, field_name, fname_list, prdcfg*)
plots the sun hits

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

altitude [float] the altitude [m MSL] to be plotted

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_sun_retrieval_ts` (*sun_retrieval, data_type, fname_list, labelx='Date', titl='Sun retrieval Time Series', dpi=72*)
plots sun retrieval time series series

Parameters

sun_retrieval [tuple] tuple containing the retrieved parameters

data_type [str] parameter to be plotted

fname_list [list of str] list of names of the files where to store the plot

labelx [str] the x label

titl [str] the title of the plot

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_surface` (*grid, field_name, level, prdcfg, fname_list*)
plots a surface from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot

field_name [str] name of the radar field to plot

level [int] level index

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_time_range` (*radar, field_name, ind_sweep, prdcfg, fname_list*)
plots a time-range plot

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_sweep [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plot_timeseries` (*tvec, data_list, fname_list, labelx='Time [UTC]', labely='Value', labels=['Sensor'], title='Time Series', period=0, timeformat=None, colors=None, linestyle=None, markers=None, ymin=None, ymax=None, dpi=72*)
plots a time series

Parameters

tvec [datetime object] time of the time series

data_list [list of float array] values of the time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

labels [array of str] The label of the legend

title [str] The figure title

period [float] measurement period in seconds used to compute accumulation. If 0 no accumulation is computed

timeformat [str] Specifies the tvec and time format on the x axis

colors [array of str] Specifies the colors of each line

linestyles [array of str] Specifies the line style of each line

markers: array of str Specify the markers to be used for each line

ymin, ymax: float Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_timeseries_comp(date1, value1, date2, value2, fname_list, labelx='Time
                                [UTC]', labely='Value', label1='Sensor 1', label2='Sensor
                                2', titl='Time Series Comparison', period1=0, period2=0,
                                ymin=None, ymax=None, dpi=72)
```

plots 2 time series in the same graph

Parameters

date1 [datetime object] time of the first time series

value1 [float array] values of the first time series

date2 [datetime object] time of the second time series

value2 [float array] values of the second time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

label1, label2 [str] legend label for each time series

titl [str]

The figure title

period1, period2 [float] measurement period in seconds used to compute accumulation. If
0 no accumulation is computed

dpi [int] dots per inch

ymin, ymax [float] The limits of the Y-axis. None will keep the default limit.

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plot_traj(rng_traj, azi_traj, ele_traj, time_traj, prdcfg, fname_list, rad_alt=None,
                      rad_tstart=None, ax=None, fig=None, save_fig=True)
```

plots a trajectory on a Cartesian surface

Parameters

rng_traj, azi_traj, ele_traj [float array] antenna coordinates of the trajectory [m and deg]

time_traj [datetime array] trajectory time

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

rad_alt [float or None] radar altitude [m MSL]

rad_tstart [datetime object or None] start time of the radar scan

surface_alt [float] surface altitude [m MSL]

color_ref [str] What the color code represents. Can be 'None', 'rel_altitude', 'altitude' or 'time'

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

UTILITIES (PYRAD . UTIL)

Functions to read and write data and configuration files.

6.1 Radar Utilities

<i>get_ROI</i> (radar, fieldname, sector)	filter out any data outside the region of interest defined by sector
<i>rainfall_accumulation</i> (t_in_vec, val_in_vec)	Computes the rainfall accumulation of a time series over a given period
<i>time_series_statistics</i> (t_in_vec, val_in_vec)	Computes statistics over a time-averaged series
<i>join_time_series</i> (t1, val1, t2, val2[, dropnan])	joins time_series
<i>get_range_bins_to_avg</i> (rad1_rng, rad2_rng)	Compares the resolution of two radars and determines if and which radar has to be averaged and the length of the averaging window
<i>find_ray_index</i> (ele_vec, azi_vec, ele, azi[, ...])	Find the ray index corresponding to a particular elevation and azimuth
<i>find_rng_index</i> (rng_vec, rng[, rng_tol])	Find the range index corresponding to a particular range
<i>find_nearest_gate</i>	
<i>find_neighbour_gates</i> (radar, azi, rng[, ...])	Find the neighbouring gates within +-delta_azi and +-delta_rng
<i>find_colocated_indexes</i> (radar1, radar2, ...)	Given the theoretical elevation, azimuth and range of the co-located gates of two radars and a given tolerance returns the indices of the gates for the current radars
<i>get_target_elevations</i> (radar_in)	Gets RHI target elevations
<i>time_avg_range</i> (timeinfo, avg_starttime, ...)	finds the new start and end time of an averaging
<i>get_closest_solar_flux</i> (hit_datetime_list, ...)	finds the solar flux measurement closest to the sun hit
<i>create_sun_hits_field</i> (rad_el, rad_az, ...)	creates a sun hits field from the position and power of the sun hits
<i>create_sun_retrieval_field</i> (par, field_name, ...)	creates a sun retrieval field from the retrieval parameters
<i>compute_quantiles</i> (field[, quantiles])	computes quantiles
<i>compute_quantiles_from_hist</i> (bin_centers, hist)	computes quantiles from histograms
<i>compute_quantiles_sweep</i> (field, ray_start, ...)	computes quantiles of a particular sweep
<i>compute_2d_hist</i> (field1, field2, field_name1, ...)	computes a 2D histogram of the data
<i>compute_1d_stats</i> (field1, field2)	returns statistics of data
<i>compute_2d_stats</i> (field1, field2, ...[, ...])	computes a 2D histogram and statistics of the data

Continued on next page

Table 1 – continued from previous page

<code>compute_histogram(field, field_name[, ...])</code>	computes histogram of the data
<code>compute_histogram_sweep(field, ray_start, ...)</code>	computes histogram of the data in a particular sweep
<code>belongs_roi_indices(lat, lon, roi)</code>	Get the indices of points that belong to roi in a list of points
<code>compute_profile_stats(field, gate_altitude, ...)</code>	Compute statistics of vertical profile
<code>compute_directional_stats(field[, avg_type, ...])</code>	Computes the mean or the median along one of the axis (ray or range)
<code>project_to_vertical(data_in, data_height, ...)</code>	Projects radar data to a regular vertical grid
<code>quantiles_weighted(values[, weight_vector, ...])</code>	Given a set of values and weights, compute the weighted quantile(s).

`pyrad.util.belongs_roi_indices (lat, lon, roi)`

Get the indices of points that belong to roi in a list of points

Parameters

lat, lon [float arrays] latitudes and longitudes to check

roi [dict] Dictionary describing the region of interest

Returns

inds [array of ints] list of indices of points belonging to ROI

is_roi [str] Whether the list of points is within the region of interest. Can be 'All', 'None', 'Some'

`pyrad.util.compute_1d_stats (field1, field2)`

returns statistics of data

Parameters

field1, field2 [ndarray 1D] the two fields to compare

Returns

stats [dict] a dictionary with statistics

`pyrad.util.compute_2d_hist (field1, field2, field_name1, field_name2, step1=None, step2=None)`

computes a 2D histogram of the data

Parameters

field1, field2 [ndarray 2D] the radar fields

field_name1, field_name2 [str] field names

step1, step2 [float] size of the bins

Returns

H [float array 2D] The bi-dimensional histogram of samples x and y

xedges, yedges [float array] the bin edges along each dimension

`pyrad.util.compute_2d_stats (field1, field2, field_name1, field_name2, step1=None, step2=None)`

computes a 2D histogram and statistics of the data

Parameters

field1, field2 [ndarray 2D] the two fields

field_name1, field_name2: str the name of the fields

step1, step2 [float] size of bin

Returns

hist_2d [array] the histogram

bin_edges1, bin_edges2 [float array] The bin edges

stats [dict] a dictionary with statistics

`pyrad.util.compute_directional_stats` (*field*, *avg_type*='mean', *nvalid_min*=1, *axis*=0)

Computes the mean or the median along one of the axis (ray or range)

Parameters

field [ndarray] the radar field

avg_type :str the type of average: 'mean' or 'median'

nvalid_min [int] the minimum number of points to consider the stats valid. Default 1

axis [int] the axis along which to compute (0=ray, 1=range)

Returns

values [ndarray 1D] The resultant statistics

nvalid [ndarray 1D] The number of valid points used in the computation

`pyrad.util.compute_histogram` (*field*, *field_name*, *bin_edges*=None, *step*=None, *vmin*=None, *vmax*=None)

computes histogram of the data

Parameters

field [ndarray 2D] the radar field

field_name: str or none name of the field

bins_edges :ndarray 1D the bin edges

step [float] size of bin

vmin, vmax [float] The minimum and maximum value of the histogram

Returns

bin_edges [float array] interval of each bin

values [float array] values at each bin

`pyrad.util.compute_histogram_sweep` (*field*, *ray_start*, *ray_end*, *field_name*, *step*=None)

computes histogram of the data in a particular sweep

Parameters

field [ndarray 2D] the radar field

ray_start, ray_end [int] starting and ending ray indexes

field_name: str name of the field

step [float] size of bin

Returns

bin_edges [float array] interval of each bin

values [float array] values at each bin

`pyrad.util.compute_profile_stats` (*field, gate_altitude, h_vec, h_res, quantity='quantiles', quantiles=array([0.25, 0.5, 0.75]), nvalid_min=4, std_field=None, np_field=None, make_linear=False, include_nans=False*)

Compute statistics of vertical profile

Parameters

field [ndarray] the radar field

gate_altitude: ndarray the altitude at each radar gate [m MSL]

h_vec [1D ndarray] height vector [m MSL]

h_res [float] height resolution [m]

quantity [str] The quantity to compute. Can be ['quantiles', 'mode', 'regression_mean', 'mean']. If 'mean', the min, max, and average is computed.

quantiles [1D ndarray] the quantiles to compute

nvalid_min [int] the minimum number of points to consider the stats valid

std_field [ndarray] the standard deviation of the regression at each range gate

np_field [ndarray] the number of points used to compute the regression at each range gate

make_linear [Boolean] If true the data is transformed into linear coordinates before taking the mean

include_nans [Boolean] If true NaN will be considered as zeros

Returns

vals [ndarray 2D] The resultant statistics

val_valid [ndarray 1D] The number of points to compute the stats used at each height level

`pyrad.util.compute_quantiles` (*field, quantiles=None*)
computes quantiles

Parameters

field [ndarray 2D] the radar field

ray_start, ray_end [int] starting and ending ray indexes

quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles

values [float array] values at each quantile

`pyrad.util.compute_quantiles_from_hist` (*bin_centers, hist, quantiles=None*)
computes quantiles from histograms

Parameters

bin_centers [ndarray 1D] the bins

hist [ndarray 1D] the histogram

quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles

values [float array] values at each quantile

`pyrad.util.compute_quantiles_sweep` (*field, ray_start, ray_end, quantiles=None*)
 computes quantiles of a particular sweep

Parameters

field [ndarray 2D] the radar field
ray_start, ray_end [int] starting and ending ray indexes
quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles
values [float array] values at each quantile

`pyrad.util.create_sun_hits_field` (*rad_el, rad_az, sun_el, sun_az, data, imgcfg*)
 creates a sun hits field from the position and power of the sun hits

Parameters

rad_el, rad_az, sun_el, sun_az [ndarray 1D] azimuth and elevation of the radar and the sun respectively in degree
data [masked ndarray 1D] the sun hit data
imgcfg: dict a dictionary specifying the ranges and resolution of the field to create

Returns

field [masked ndarray 2D] the sun hit field

`pyrad.util.create_sun_retrieval_field` (*par, field_name, imgcfg, lant=0.0*)
 creates a sun retrieval field from the retrieval parameters

Parameters

par [ndarray 1D] the 5 retrieval parameters
imgcfg: dict a dictionary specifying the ranges and resolution of the field to create

Returns

field [masked ndarray 2D] the sun retrieval field

`pyrad.util.find_colocated_indexes` (*radar1, radar2, rad1_ele, rad1_azi, rad1_rng, rad2_ele, rad2_azi, rad2_rng, ele_tol=0.5, azi_tol=0.5, rng_tol=50.0*)

Given the theoretical elevation, azimuth and range of the co-located gates of two radars and a given tolerance returns the indices of the gates for the current radars

Parameters

radar1, radar2 [radar objects] the two radar objects
rad1_ele, rad1_azi, rad1_rng [array of floats] the radar coordinates of the radar1 gates
rad2_ele, rad2_azi, rad2_rng [array of floats] the radar coordinates of the radar2 gates
ele_tol, azi_tol [floats] azimuth and elevation angle tolerance [deg]
rng_tol [float] range Tolerance [m]

Returns

ind_ray_rad1, ind_rng_rad1, ind_ray_rad2, ind_rng_rad2 [array of ints] the ray and range indexes of each radar gate

`pyrad.util.find_neighbour_gates (radar, azi, rng, delta_azi=None, delta_rng=None)`

Find the neighbouring gates within +/-delta_azi and +/-delta_rng

Parameters

radar [radar object] the radar object

azi, rng [float] The azimuth [deg] and range [m] of the central gate

delta_azi, delta_rng [float] The extend where to look for

Returns

inds_ray_aux, ind_rng_aux [int] The indices (ray, rng) of the neighbouring gates

`pyrad.util.find_ray_index (ele_vec, azi_vec, ele, azi, ele_tol=0.0, azi_tol=0.0, nearest='azi')`

Find the ray index corresponding to a particular elevation and azimuth

Parameters

ele_vec, azi_vec [float arrays] The elevation and azimuth data arrays where to look for

ele, azi [floats] The elevation and azimuth to search

ele_tol, azi_tol [floats] Tolerances [deg]

nearest [str] criteria to define wich ray to keep if multiple rays are within tolerance. azi: nearest azimuth, ele: nearest elevation

Returns

ind_ray [int] The ray index

`pyrad.util.find_rng_index (rng_vec, rng, rng_tol=0.0)`

Find the range index corresponding to a particular range

Parameters

rng_vec [float array] The range data array where to look for

rng [float] The range to search

rng_tol [float] Tolerance [m]

Returns

ind_rng [int] The range index

`pyrad.util.get_ROI (radar, fieldname, sector)`

filter out any data outside the region of interest defined by sector

Parameters

radar [radar object] the radar object where the data is

fieldname [str] name of the field to filter

sector [dict] a dictionary defining the region of interest

Returns

roi_flag [ndarray] a field array with ones in gates that are in the Region of Interest

`pyrad.util.get_closest_solar_flux (hit_datetime_list, flux_datetime_list, flux_value_list)`

finds the solar flux measurement closest to the sun hit

Parameters

hit_datetime_list [datetime array] the date and time of the sun hit

flux_datetime_list [datetime array] the date and time of the solar flux measurement

flux_value_list: ndarray 1D the solar flux values

Returns

flux_datetime_closest_list [datetime array] the date and time of the solar flux measurement closest to sun hit

flux_value_closest_list [ndarray 1D] the solar flux values closest to the sun hit time

`pyrad.util.get_range_bins_to_avg(rad1_rng, rad2_rng)`

Compares the resolution of two radars and determines if and which radar has to be averaged and the length of the averaging window

Parameters

rad1_rng [array] the range of radar 1

rad2_rng [datetime] the range of radar 2

Returns

avg_rad1, avg_rad2 [Boolean] Booleans specifying if the radar data has to be average in range

avg_rad_lim [array with two elements] the limits to the average (centered on each range gate)

`pyrad.util.get_target_elevations(radar_in)`

Gets RHI target elevations

Parameters

radar_in [Radar object] current radar object

Returns

target_elevations [1D-array] Azimuth angles

el_tol [float] azimuth tolerance

`pyrad.util.join_time_series(t1, val1, t2, val2, dropnan=False)`

joins time_series

Parameters

t1 [datetime array] time of first series

val1 [float array] value of first series

t2 [datetime array] time of second series

val2 [float array] value of second series

dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the resultant date time after joining the series

val1_out_vec [float array] value of first series

val2_out_vec [float array] value of second series

`pyrad.util.project_to_vertical(data_in, data_height, grid_height, interp_kind='none', fill_value=-9999.0)`

Projects radar data to a regular vertical grid

Parameters

data_in [ndarray 1D] the radar data to project

data_height [ndarray 1D] the height of each radar point
grid_height [ndarray 1D] the regular vertical grid to project to
interp_kind [str] The type of interpolation to use: 'none' or 'nearest'
fill_value [float] The fill value used for interpolation

Returns

data_out [ndarray 1D] The projected data

`pyrad.util.quantiles_weighted(values, weight_vector=None, quantiles=array([0.5]),
weight_threshold=None, data_is_log=False)`

Given a set of values and weights, compute the weighted quantile(s).

`pyrad.util.rainfall_accumulation(t_in_vec, val_in_vec, cum_time=3600.0, base_time=0.0,
dropnan=False)`

Computes the rainfall accumulation of a time series over a given period

Parameters

t_in_vec [datetime array] the input date and time array
val_in_vec [float array] the input values array [mm/h]
cum_time [int] accumulation time [s]
base_time [int] base time [s]
dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the output date and time array
val_out_vec [float array] the output values array
np_vec [int array] the number of samples at each period

`pyrad.util.time_avg_range(timeinfo, avg_starttime, avg_endtime, period)`

finds the new start and end time of an averaging

Parameters

timeinfo [datetime] the current volume time
avg_starttime [datetime] the current average start time
avg_endtime: datetime the current average end time
period: float the averaging period

Returns

new_starttime [datetime] the new average start time
new_endtime [datetime] the new average end time

`pyrad.util.time_series_statistics(t_in_vec, val_in_vec, avg_time=3600, base_time=1800,
method='mean', dropnan=False)`

Computes statistics over a time-averaged series

Parameters

t_in_vec [datetime array] the input date and time array
val_in_vec [float array] the input values array
avg_time [int] averaging time [s]

base_time [int] base time [s]

method [str] statistical method

dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the output date and time array

val_out_vec [float array] the output values array

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

p

- `pyrad.flow`, [1](#)
- `pyrad.graph`, [78](#)
- `pyrad.io`, [48](#)
- `pyrad.proc`, [4](#)
- `pyrad.prod`, [44](#)
- `pyrad.util`, [93](#)

Symbols

- `__class__` (*pyrad.io.TimeSeries* attribute), 53
- `__class__` (*pyrad.io.Trajectory* attribute), 55
- `__delattr__` (*pyrad.io.TimeSeries* attribute), 53
- `__delattr__` (*pyrad.io.Trajectory* attribute), 55
- `__dict__` (*pyrad.io.TimeSeries* attribute), 53
- `__dict__` (*pyrad.io.Trajectory* attribute), 55
- `__dir__` () (*pyrad.io.TimeSeries* method), 53
- `__dir__` () (*pyrad.io.Trajectory* method), 55
- `__eq__` (*pyrad.io.TimeSeries* attribute), 53
- `__eq__` (*pyrad.io.Trajectory* attribute), 55
- `__format__` () (*pyrad.io.TimeSeries* method), 53
- `__format__` () (*pyrad.io.Trajectory* method), 55
- `__ge__` (*pyrad.io.TimeSeries* attribute), 53
- `__ge__` (*pyrad.io.Trajectory* attribute), 55
- `__getattr__` (*pyrad.io.TimeSeries* attribute), 53
- `__getattr__` (*pyrad.io.Trajectory* attribute), 55
- `__gt__` (*pyrad.io.TimeSeries* attribute), 53
- `__gt__` (*pyrad.io.Trajectory* attribute), 55
- `__hash__` (*pyrad.io.TimeSeries* attribute), 53
- `__hash__` (*pyrad.io.Trajectory* attribute), 55
- `__init__` () (*pyrad.io.TimeSeries* method), 53
- `__init__` () (*pyrad.io.Trajectory* method), 56
- `__init_subclass__` () (*pyrad.io.TimeSeries* method), 53
- `__init_subclass__` () (*pyrad.io.Trajectory* method), 56
- `__le__` (*pyrad.io.TimeSeries* attribute), 53
- `__le__` (*pyrad.io.Trajectory* attribute), 56
- `__lt__` (*pyrad.io.TimeSeries* attribute), 53
- `__lt__` (*pyrad.io.Trajectory* attribute), 56
- `__module__` (*pyrad.io.TimeSeries* attribute), 53
- `__module__` (*pyrad.io.Trajectory* attribute), 56
- `__ne__` (*pyrad.io.TimeSeries* attribute), 53
- `__ne__` (*pyrad.io.Trajectory* attribute), 56
- `__new__` () (*pyrad.io.TimeSeries* method), 53
- `__new__` () (*pyrad.io.Trajectory* method), 56
- `__reduce__` () (*pyrad.io.TimeSeries* method), 54
- `__reduce__` () (*pyrad.io.Trajectory* method), 56
- `__reduce_ex__` () (*pyrad.io.TimeSeries* method), 54
- `__reduce_ex__` () (*pyrad.io.Trajectory* method), 56
- `__repr__` (*pyrad.io.TimeSeries* attribute), 54
- `__repr__` (*pyrad.io.Trajectory* attribute), 56
- `__setattr__` (*pyrad.io.TimeSeries* attribute), 54
- `__setattr__` (*pyrad.io.Trajectory* attribute), 56
- `__sizeof__` () (*pyrad.io.TimeSeries* method), 54
- `__sizeof__` () (*pyrad.io.Trajectory* method), 56
- `__str__` (*pyrad.io.TimeSeries* attribute), 54
- `__str__` (*pyrad.io.Trajectory* attribute), 56
- `__subclasshook__` () (*pyrad.io.TimeSeries* method), 54
- `__subclasshook__` () (*pyrad.io.Trajectory* method), 56
- `__weakref__` (*pyrad.io.TimeSeries* attribute), 54
- `__weakref__` (*pyrad.io.Trajectory* attribute), 56
- `_convert_traj_to_swissgrid` () (*pyrad.io.Trajectory* method), 57
- `_get_total_seconds` () (*pyrad.io.Trajectory* method), 57
- `_read_traj` () (*pyrad.io.Trajectory* method), 57
- `_read_traj_lightning` () (*pyrad.io.Trajectory* method), 57
- `_read_traj_trt` () (*pyrad.io.Trajectory* method), 57

A

- `add_dataserries` () (*pyrad.io.TimeSeries* method), 54
- `add_field` () (in module *pyrad.io*), 57
- `add_radar` () (*pyrad.io.Trajectory* method), 57
- `add_timesample` () (*pyrad.io.TimeSeries* method), 54

B

- `belongs_roi_indices` () (in module *pyrad.util*), 96

C

- `calculate_velocities` () (*pyrad.io.Trajectory* method), 57
- `compute_1d_stats` () (in module *pyrad.util*), 96
- `compute_2d_hist` () (in module *pyrad.util*), 96
- `compute_2d_stats` () (in module *pyrad.util*), 96

`compute_directional_stats()` (in module *pyrad.util*), 97
`compute_histogram()` (in module *pyrad.util*), 97
`compute_histogram_sweep()` (in module *pyrad.util*), 97
`compute_profile_stats()` (in module *pyrad.util*), 97
`compute_quantiles()` (in module *pyrad.util*), 98
`compute_quantiles_from_hist()` (in module *pyrad.util*), 98
`compute_quantiles_sweep()` (in module *pyrad.util*), 99
`cosmo2radar_coord()` (in module *pyrad.io*), 57
`cosmo2radar_data()` (in module *pyrad.io*), 58
`create_sun_hits_field()` (in module *pyrad.util*), 99
`create_sun_retrieval_field()` (in module *pyrad.util*), 99

F

`find_colocated_indexes()` (in module *pyrad.util*), 99
`find_hzt_file()` (in module *pyrad.io*), 58
`find_neighbour_gates()` (in module *pyrad.util*), 99
`find_raw_cosmo_file()` (in module *pyrad.io*), 58
`find_ray_index()` (in module *pyrad.util*), 100
`find_rng_index()` (in module *pyrad.util*), 100

G

`generate_colocated_gates_products()` (in module *pyrad.prod*), 45
`generate_cosmo_coord_products()` (in module *pyrad.prod*), 46
`generate_field_name_str()` (in module *pyrad.io*), 58
`generate_grid_products()` (in module *pyrad.prod*), 46
`generate_intercomp_products()` (in module *pyrad.prod*), 46
`generate_ml_products()` (in module *pyrad.prod*), 46
`generate_monitoring_products()` (in module *pyrad.prod*), 46
`generate_occurrence_products()` (in module *pyrad.prod*), 46
`generate_qvp_products()` (in module *pyrad.prod*), 47
`generate_sun_hits_products()` (in module *pyrad.prod*), 47
`generate_time_avg_products()` (in module *pyrad.prod*), 47
`generate_timeseries_products()` (in module *pyrad.prod*), 47
`generate_traj_product()` (in module *pyrad.prod*), 47
`generate_vol_products()` (in module *pyrad.prod*), 48
`get_closest_solar_flux()` (in module *pyrad.util*), 100
`get_colobar_label()` (in module *pyrad.graph*), 80
`get_cosmo_fields()` (in module *pyrad.io*), 59
`get_data()` (in module *pyrad.io*), 59
`get_dataset_fields()` (in module *pyrad.io*), 59
`get_datatype_fields()` (in module *pyrad.io*), 59
`get_datetime()` (in module *pyrad.io*), 60
`get_end_time()` (*pyrad.io.Trajectory* method), 57
`get_field_name()` (in module *pyrad.graph*), 80
`get_field_unit()` (in module *pyrad.io*), 60
`get_fieldname_cosmo()` (in module *pyrad.io*), 60
`get_fieldname_pyart()` (in module *pyrad.io*), 60
`get_file_list()` (in module *pyrad.io*), 60
`get_iso0_field()` (in module *pyrad.io*), 60
`get_new_rainbow_file_name()` (in module *pyrad.io*), 61
`get_process_func()` (in module *pyrad.proc*), 8
`get_prodcgen_func()` (in module *pyrad.prod*), 48
`get_range_bins_to_avg()` (in module *pyrad.util*), 101
`get_ROI()` (in module *pyrad.util*), 100
`get_samples_in_period()` (*pyrad.io.Trajectory* method), 57
`get_save_dir()` (in module *pyrad.io*), 61
`get_sensor_data()` (in module *pyrad.io*), 61
`get_start_time()` (*pyrad.io.Trajectory* method), 57
`get_target_elevations()` (in module *pyrad.util*), 101
`get_trtfile_list()` (in module *pyrad.io*), 62

H

`hzt2radar_coord()` (in module *pyrad.io*), 62
`hzt2radar_data()` (in module *pyrad.io*), 62

I

`interpol_field()` (in module *pyrad.io*), 62

J

`join_time_series()` (in module *pyrad.util*), 101

M

`main()` (in module *pyrad.flow*), 3
`main_rt()` (in module *pyrad.flow*), 3
`make_filename()` (in module *pyrad.io*), 63
`map_Doppler()` (in module *pyrad.io*), 63
`map_hydro()` (in module *pyrad.io*), 63

P

`plot()` (*pyrad.io.TimeSeries* method), 54

- plot_along_coord() (in module *pyrad.graph*), 80
 plot_antenna_pattern() (in module *pyrad.graph*), 80
 plot_bscope() (in module *pyrad.graph*), 81
 plot_cappi() (in module *pyrad.graph*), 81
 plot_density() (in module *pyrad.graph*), 82
 plot_field_coverage() (in module *pyrad.graph*), 82
 plot_hist() (*pyrad.io.TimeSeries* method), 54
 plot_histogram() (in module *pyrad.graph*), 82
 plot_histogram2() (in module *pyrad.graph*), 83
 plot_intercomp_scores_ts() (in module *pyrad.graph*), 83
 plot_latitude_slice() (in module *pyrad.graph*), 84
 plot_latlon_slice() (in module *pyrad.graph*), 84
 plot_longitude_slice() (in module *pyrad.graph*), 84
 plot_ml_ts() (in module *pyrad.graph*), 85
 plot_monitoring_ts() (in module *pyrad.graph*), 85
 plot_pos() (in module *pyrad.graph*), 86
 plot_ppi() (in module *pyrad.graph*), 86
 plot_ppi_contour() (in module *pyrad.graph*), 87
 plot_ppi_map() (in module *pyrad.graph*), 87
 plot_quantiles() (in module *pyrad.graph*), 87
 plot_rhi() (in module *pyrad.graph*), 88
 plot_rhi_contour() (in module *pyrad.graph*), 88
 plot_rhi_profile() (in module *pyrad.graph*), 89
 plot_scatter() (in module *pyrad.graph*), 89
 plot_scatter_comp() (in module *pyrad.graph*), 90
 plot_sun_hits() (in module *pyrad.graph*), 90
 plot_sun_retrieval_ts() (in module *pyrad.graph*), 90
 plot_surface() (in module *pyrad.graph*), 91
 plot_time_range() (in module *pyrad.graph*), 91
 plot_timeseries() (in module *pyrad.graph*), 91
 plot_timeseries_comp() (in module *pyrad.graph*), 92
 plot_traj() (in module *pyrad.graph*), 92
 process_attenuation() (in module *pyrad.proc*), 9
 process_azimuthal_average() (in module *pyrad.proc*), 9
 process_bird_density() (in module *pyrad.proc*), 10
 process_birds_id() (in module *pyrad.proc*), 10
 process_cdf() (in module *pyrad.proc*), 10
 process_cdr() (in module *pyrad.proc*), 11
 process_clt_to_echo_id() (in module *pyrad.proc*), 11
 process_colocated_gates() (in module *pyrad.proc*), 11
 process_correct_bias() (in module *pyrad.proc*), 12
 process_correct_noise_rho_hv() (in module *pyrad.proc*), 12
 process_correct_phidp0() (in module *pyrad.proc*), 12
 process_cosmo() (in module *pyrad.proc*), 13
 process_cosmo_coord() (in module *pyrad.proc*), 13
 process_cosmo_lookup_table() (in module *pyrad.proc*), 14
 process_dealias_fourdd() (in module *pyrad.proc*), 14
 process_dealias_region_based() (in module *pyrad.proc*), 14
 process_dealias_unwrap_phase() (in module *pyrad.proc*), 15
 process_echo_filter() (in module *pyrad.proc*), 15
 process_echo_id() (in module *pyrad.proc*), 16
 process_estimate_phidp0() (in module *pyrad.proc*), 16
 process_evp() (in module *pyrad.proc*), 16
 process_filter_snr() (in module *pyrad.proc*), 17
 process_filter_vel_diff() (in module *pyrad.proc*), 17
 process_filter_visibility() (in module *pyrad.proc*), 18
 process_gc_monitoring() (in module *pyrad.proc*), 18
 process_grid() (in module *pyrad.proc*), 18
 process_hydroclass() (in module *pyrad.proc*), 19
 process_hzt() (in module *pyrad.proc*), 19
 process_hzt_coord() (in module *pyrad.proc*), 20
 process_hzt_lookup_table() (in module *pyrad.proc*), 20
 process_intercomp() (in module *pyrad.proc*), 21
 process_intercomp_time_avg() (in module *pyrad.proc*), 21
 process_kdp_least_square_double_window() (in module *pyrad.proc*), 22
 process_kdp_least_square_single_window() (in module *pyrad.proc*), 22
 process_l() (in module *pyrad.proc*), 23
 process_melting_layer() (in module *pyrad.proc*), 23
 process_monitoring() (in module *pyrad.proc*), 23
 process_occurrence() (in module *pyrad.proc*), 23
 process_occurrence_period() (in module *pyrad.proc*), 24
 process_outlier_filter() (in module *pyrad.proc*), 24
 process_phidp_kdp_Kalman() (in module *pyrad.proc*), 25
 process_phidp_kdp_lp() (in module *pyrad.proc*), 26

`process_phidp_kdp_Maesaka()` (in module `pyrad.proc`), 25
`process_phidp_kdp_Vulpiani()` (in module `pyrad.proc`), 26
`process_point_measurement()` (in module `pyrad.proc`), 26
`process_qvp()` (in module `pyrad.proc`), 27
`process_rainrate()` (in module `pyrad.proc`), 28
`process_raw()` (in module `pyrad.proc`), 28
`process_rcs()` (in module `pyrad.proc`), 29
`process_rcs_pr()` (in module `pyrad.proc`), 29
`process_rhohv_rain()` (in module `pyrad.proc`), 30
`process_roi()` (in module `pyrad.proc`), 31
`process_rqvp()` (in module `pyrad.proc`), 31
`process_save_radar()` (in module `pyrad.proc`), 32
`process_selfconsistency_bias()` (in module `pyrad.proc`), 32
`process_selfconsistency_kdp_phidp()` (in module `pyrad.proc`), 32
`process_signal_power()` (in module `pyrad.proc`), 33
`process_smooth_phidp_double_window()` (in module `pyrad.proc`), 33
`process_smooth_phidp_single_window()` (in module `pyrad.proc`), 34
`process_snr()` (in module `pyrad.proc`), 34
`process_sun_hits()` (in module `pyrad.proc`), 35
`process_svp()` (in module `pyrad.proc`), 36
`process_time_avg()` (in module `pyrad.proc`), 36
`process_time_avg_flag()` (in module `pyrad.proc`), 37
`process_time_height()` (in module `pyrad.proc`), 37
`process_traj_antenna_pattern()` (in module `pyrad.proc`), 38
`process_traj_atplane()` (in module `pyrad.proc`), 39
`process_traj_lightning()` (in module `pyrad.proc`), 39
`process_traj_trt()` (in module `pyrad.proc`), 40
`process_trajectory()` (in module `pyrad.proc`), 40
`process_vad()` (in module `pyrad.proc`), 40
`process_vol_refl()` (in module `pyrad.proc`), 40
`process_weighted_time_avg()` (in module `pyrad.proc`), 41
`process_wind_vel()` (in module `pyrad.proc`), 41
`process_windshear()` (in module `pyrad.proc`), 41
`process_zdr_column()` (in module `pyrad.proc`), 42
`process_zdr_precip()` (in module `pyrad.proc`), 42
`process_zdr_snow()` (in module `pyrad.proc`), 43
`project_to_vertical()` (in module `pyrad.util`), 101
`pyrad.flow` (module), 1
`pyrad.graph` (module), 78

`pyrad.io` (module), 48
`pyrad.proc` (module), 4
`pyrad.prod` (module), 44
`pyrad.util` (module), 93

Q

`quantiles_weighted()` (in module `pyrad.util`), 102

R

`rainfall_accumulation()` (in module `pyrad.util`), 102
`read_antenna_pattern()` (in module `pyrad.io`), 63
`read_colocated_data()` (in module `pyrad.io`), 63
`read_colocated_gates()` (in module `pyrad.io`), 64
`read_config()` (in module `pyrad.io`), 64
`read_cosmo_coord()` (in module `pyrad.io`), 64
`read_cosmo_data()` (in module `pyrad.io`), 64
`read_disdro_scattering()` (in module `pyrad.io`), 64
`read_excess_gates()` (in module `pyrad.io`), 65
`read_histogram()` (in module `pyrad.io`), 65
`read_histogram_ts()` (in module `pyrad.io`), 65
`read_hzt_data()` (in module `pyrad.io`), 65
`read_intercomp_scores_ts()` (in module `pyrad.io`), 65
`read_last_state()` (in module `pyrad.io`), 66
`read_lightning()` (in module `pyrad.io`), 66
`read_lightning_all()` (in module `pyrad.io`), 66
`read_lightning_traj()` (in module `pyrad.io`), 66
`read_meteorage()` (in module `pyrad.io`), 67
`read_ml_ts()` (in module `pyrad.io`), 67
`read_monitoring_ts()` (in module `pyrad.io`), 67
`read_profile_ts()` (in module `pyrad.io`), 67
`read_quantiles()` (in module `pyrad.io`), 68
`read_quantiles_ts()` (in module `pyrad.io`), 68
`read_rad4alp_cosmo()` (in module `pyrad.io`), 68
`read_rad4alp_vis()` (in module `pyrad.io`), 68
`read_rhi_profile()` (in module `pyrad.io`), 69
`read_selfconsistency()` (in module `pyrad.io`), 69
`read_smn()` (in module `pyrad.io`), 69
`read_smn2()` (in module `pyrad.io`), 69
`read_solar_flux()` (in module `pyrad.io`), 69
`read_status()` (in module `pyrad.io`), 69
`read_sun_hits()` (in module `pyrad.io`), 70
`read_sun_hits_multiple_days()` (in module `pyrad.io`), 70
`read_sun_retrieval()` (in module `pyrad.io`), 70
`read_timeseries()` (in module `pyrad.io`), 70
`read_trt_cell_lightning()` (in module `pyrad.io`), 71
`read_trt_data()` (in module `pyrad.io`), 71
`read_trt_scores()` (in module `pyrad.io`), 71
`read_trt_traj_data()` (in module `pyrad.io`), 71
`read_ts_cum()` (in module `pyrad.io`), 72

S

`send_msg()` (in module *pyrad.io*), 72

T

`time_avg_range()` (in module *pyrad.util*), 102

`time_series_statistics()` (in module *pyrad.util*), 102

`TimeSeries` (class in *pyrad.io*), 52

`Trajectory` (class in *pyrad.io*), 54

W

`write()` (*pyrad.io.TimeSeries* method), 54

`write_alarm_msg()` (in module *pyrad.io*), 72

`write_cdf()` (in module *pyrad.io*), 73

`write_colocated_data()` (in module *pyrad.io*), 73

`write_colocated_data_time_avg()` (in module *pyrad.io*), 73

`write_colocated_gates()` (in module *pyrad.io*), 73

`write_excess_gates()` (in module *pyrad.io*), 74

`write_field_coverage()` (in module *pyrad.io*), 74

`write_histogram()` (in module *pyrad.io*), 74

`write_intercomp_scores_ts()` (in module *pyrad.io*), 74

`write_last_state()` (in module *pyrad.io*), 75

`write_monitoring_ts()` (in module *pyrad.io*), 75

`write_quantiles()` (in module *pyrad.io*), 75

`write_rhi_profile()` (in module *pyrad.io*), 75

`write_smn()` (in module *pyrad.io*), 76

`write_sun_hits()` (in module *pyrad.io*), 76

`write_sun_retrieval()` (in module *pyrad.io*), 76

`write_trt_cell_data()` (in module *pyrad.io*), 76

`write_trt_cell_lightning()` (in module *pyrad.io*), 77

`write_trt_cell_scores()` (in module *pyrad.io*), 77

`write_ts_cum()` (in module *pyrad.io*), 78

`write_ts_lightning()` (in module *pyrad.io*), 78

`write_ts_polar_data()` (in module *pyrad.io*), 78