Title: Decrypting Phantom Wallets and Recovering Seed Phrase

Date: April 20, 2024, rev 1

Author: Cyclone

Github: https://github.com/cyclone-github

Preface: These are the steps I have taken to successfully decrypt and recover the seed phrase from a Phantom crypto wallet. This method has been tested and verified on my own test wallet with a known password and seed phrase. For transparency, I am including the encrypted JSON strings, password, seed phrase, source code I wrote, and the steps taken, as this process can be replicated by following the steps outlined below.

Proof: The steps listed below provide proof that the seed phrase can be successfully recovered from the latest version of Phantom wallets as of this writing.

Phantom Wallet Version: **v24.6.0** Wallet Password: "**password**"

Seed phrase: "car odor pioneer ball treat build load famous develop surface detail art"

1. Extract encrypted JSON strings

To extract the encrypted JSON string from the Phantom test wallet, a custom tool was written to extract the 4x encrypted JSON strings from the LevelDB where Phantom, as several other wallets such as Metamask and Atomic, store their vault data. On my test system running the Chrome browser on ParrotOS (debian based distro), the Phantom LevelDB was located at:

/home/\$USER/.config/google-chrome/Default/Local\ Extension\ Settings/bfnaelmomeimhlpmgjnjophhpkkoljpa/

Example code used to extract first encrypted JSON, "phantom-labs.encryption.encryptionKey", which I'll refer to as "encryptedKey": https://github.com/cyclone-github/phantom_pwn/tree/main/phantom_extractor

Similar code was written to extract the remaining 3x encrypted JSON strings.

Once the encryptedKey JSON was extracted, it somewhat resembled the previous version of Phantom vaults, and turns out, it uses the same encryption implementation.

Extracted encrytpedKey:

{"encryptedKey":

{"digest":"sha256","encrypted":"5pLvA3bCjNGYBbSjjFY3mdPknwFfp3cz9dCBv6izyyrq EhYCBkKwo3zZUzBP44KtY3","iterations":10000,"kdf":"pbkdf2","nonce":"NZT6kw5Cd5 VeZu5yJGJcFcP24tnmg4xsR","salt":"A43vTZnm9c5CiQ6FLTdV9v"},"version":1}

2. Decrypting encrytpedKey

To decrypt encrytpedKey, a tool based of my previous vault decryptors was modified to work with the **nacl/secretbox** encryption implementation. This is the same encryption implementation Phantom used on the previous version of their wallet.

phantom decryptor source code:

https://github.com/cyclone-github/phantom_pwn/tree/main/phantom_decryptor

After successfully decrypting encrytpedKey, the payload was a raw string of bytes and, after testing, it was determined that the payload was used as they key for the remaining encrypted JSON strings. To make it possible to store the raw bytes key in my notes, the payload was encoded as base64 and listed below for reference:

fp+UEdf3RUtAqxtxEMjWQJKStHO9HnaoOoN7Robaj3k=

3. Decrypting the 3x remaining JSON strings

Using the decrypted encrytpedKey payload as the key for the 3 remaining encrypted JSON strings, I was able to decrypt them and was greeted with 3x decoded JSON strings:

phantom-labs.vault.cache.seed:

{"version":1,"identifier":"7aec91735f7e125dde475e982aae316c88f336e361593f70a4e51c2e1c 7c1dd7", "seed":

{"bytes":"NBJYY0wt4wzvDY5qY+STVo78yIdPv5de2aa6yxKTcb69ZaqtKLb450J0ntcZkp1eMMf crTgvlTJl/bRtyyyE0g==","encoding":"base64"}}

phantom-labs.vault.integrityCheck:

{"version":1,"isSafelyOnboarded":true,"lastCheckedTimestamp":1713562315056} phantom-labs.vault.seed:

{"version":1,"identifier":"7aec91735f7e125dde475e982aae316c88f336e361593f70a4e51c2e1c

7c1dd7","name":"Account 1","entropy": {"0":34,"1":83,"2":38,"3":148,"4":136,"5":254,"6":124,"7":59,"8":160,"9":186,"10":149,"11":60,"12 ":155,"13":68,"14":241,"15":6}}

vault.cache.seed was a base64 string which, when decoded, was raw bytes.

vault.integrityCheck gave a version number, boolean of "true", and a timestamp.

vault.seed was a sequence of entropy, which, when used as the entropy for BIP39, produced the original 12 word seed phrase from the test wallet:

car odor pioneer ball treat build load famous develop surface detail art

Phantom's mysterious implementation of encryption and seed phrase obfuscation was finally pwnd.

~Cyclone

All JSON strings from vault:

o .phantom-

labs.vault.cache.seed.7aec91735f7e125dde475e982aae316c88f336e361593f70a4e 51c2e1c7c1dd7 | {"content":

{"digest":"sha256","encrypted":"2T4Q9BZH3i3GbYMEoyhEWpt4H26Sb7TWukwT8ZHSbKJmCMvF1tx8DompQWrhW1YiWdt5z1whnRqfKgDgnzHJxGidRCZRZ3YFHKe8ARXjT21bnxb848UVCsTeERg5AFc3JZir8Kkh2eD2A1in8QUfN9XXLKJNPHpsoNwpxso6rgem47pBQcgxCSvMX4Q8EREu8mHXKLuKajTh8mvbwUrtms6Q4aNcKkRXxZGmvyW7EpEdwDhsuy18A5r5e6H5pQ6UJnkbWZHykcwQ89feGesJrkaU81yE51BYjHgYS1acpQe39mg9uvz43cnYT2DqPqHSbEWP","iterations":10000,"kdf":"pbkdf2","nonce":"5UtP4bwFzH4G9gtvpVyickxfWQMiTEoWc","salt":"A7bjaKUBtRLepfH8MFcV2u"},"version":1}

o .phantom-

labs.vault.seed.7aec91735f7e125dde475e982aae316c88f336e361593f70a4e51c2e 1c7c1dd7 | {"content":

{"digest":"sha256","encrypted":"2z6wicLSo4mXEtkHnhHMZRqHAcRnZXSDnaebAg4tfNQWWP4NBGiywYgZNJGbSMpAJGq5sN1YFCZFuBxuiDLdPy4wckqmsHLipPSC7G8XiAQtH3TPi5THGjCSfciEj9jZ3BFfDCDjSX9x4X2kktxz2QMnQ8Usm5FTQmtw7QvDRt3xVmBRjKD5Q78UGE1d3NcUT64VZSuUHUS6Y5DzWidUKkbj7YGBu51MH6bNRsodqCVbPoSaistgP21f4giUWiMgFpDExAuq7oGkkAVFHB6FoqMebUvgpcaPCJy2BPEGjtU9jg3EwARqkReVWiJGXKCV77i5T84JGhW5qFyknz49L6qdPC9pVwsSMauiK7PRxgYe","iterations":10000,"kdf":"pbkdf2","nonce":"HbeN8rqQdM714DYro4McoxVJxmHnJnu4x","salt":"T83bLpyhG9ASg2atBmVwBN"},"version":1}

• .phantom-labs.vault.integrityCheck

| {"content":

{"digest":"sha256","encrypted":"2BPiigXsTiqxBnj1mqoWvjw7eEbzfZspcUNAq892W NNzEkzNiFeezNth5etVLqJWNjZzqCeBduFGzDh4B12qZ4kdwwF1PPaDUoE7Uau4 ooDzmbYSuRuZn8scknv12","iterations":10000,"kdf":"pbkdf2","nonce":"CSZ5xPChuG7x5W397C3ywdGv4c2VPAPaE","salt":"GNd7PJAMJZ3gUbc3arhvnt"},"version":1}

• Source code for generating mnemonic seed phrase from entropy string:

```
package main
import (
"fmt"
github.com/tyler-smith/go-bip39"
est code for decrypting Phantom vaults
by cyclone
https://github.com/cyclone-github/phantom_pwn
func main() {
// entropy from phantom-labs.vault.seed
entropy := []byte{34, 83, 38, 148, 136, 254, 124, 59, 160, 186, 149, 60, 155, 68, 241, 6}
// convert byte slice to a mnemonic seed phrase using BIP39
mnemonic, err := bip39.NewMnemonic(entropy)
if err != nil {
fmt.Println("Error generating mnemonic:", err)
return
fmt.Println("Mnemonic (Seed Phrase):", mnemonic)
```

• Source code for decrypting JSON strings:

```
package main
import (
'crypto/sha256"
encoding/base64"
'fmt"
github.com/btcsuite/btcutil/base58"
"golang.org/x/crypto/nacl/secretbox"
"golang.org/x/crypto/pbkdf2"
test code for decrypting Phantom vaults
by cyclone
https://github.com/cyclone-github/phantom_pwn
func main() {
base64password := "fp+UEdf3RUtAqxtxEMjWQJKStHO9HnaoOoN7Robaj3k=" |/ decrypted,
base64-encoded password
passwordBytes, err := base64.StdEncoding.DecodeString(base64password)
if err != nil {
fmt.Printf("Failed to decode password from base64: %v\n", err)
return
saltBase58 := "" // salt from vault.cache.seed, vault.seed, vault.integrityCheck
nonceBase58 := "" // nonce from vault.cache.seed, vault.seed, vault.integrityCheck
encryptedBase58 := "" // encrypted from vault.cache.seed, vault.seed, vault.integrityCheck
salt := base58.Decode(saltBase58)
nonce := base58.Decode(nonceBase58)
encryptedData := base58.Decode(encryptedBase58)
if len(nonce) != 24 {
panic("Nonce must be exactly 24 bytes long")
key := pbkdf2.Key(passwordBytes, salt, 10000, 32, sha256.New)
var nonceArray [24]byte
copy(nonceArray[:], nonce)
var keyArray [32]byte
copy(keyArray[:], key)
decrypted, ok := secretbox.Open(nil, encryptedData, &nonceArray, &keyArray)
if !ok {
fmt.Println("Decryption failed")
return
if len(decrypted) < 16 {
fmt.Println("Decrypted data is too short")
return
fmt.Printf("%s\n", decrypted)
```