ATOSL-OT


UPPER VALVE BODY

LOCATION

1. SPRING


HINT:

During reassembly, please refer to the spring specifications below to help you differentiate among the different springs.




Mark	Name (Color)		Free length / Outer diameter mm (in.)	Total No. of coils
Α	Lock-up Relay Valve	(Red)	23.42 (0.922) / 5.86 (0.231)	12.25
B	C-0 Exhaust Valve	(Orange)	24.25 (0.955) / 8.70 (0.343)	7.58
С	4-5 Shift Valve	(Red)	25.50 (1.004) / 9.73 (0.383)	7.75
D	Coast Brake Control Valve	(Green)	26.92 (1.060) / 8.70 (0.343)	10.53
E	Secondary Regulator Valve	(Red)	34.48 (1.357) / 9.22 (0.363)	13.5
F	C-1 Orifice Control Valve	(White)	37.13 (1.461) / 11.14 (0.439)	11.25
G	C-1 Orifice Control Valve	(None)	21.50 (0.846) / 7.76 (0.306)	11.5
Н	C-1 Accumulator Valve	(Yellow)	78.16 (3.077) / 17.50 (0.689)	15.9
1	Solenoid Modulator Valve (L	ght blue)	35.99 (1.417) / 8.30 (0.327)	13.8
J	2-3 Shift Valve	(Red)	25.50 (1.004) / 9.73 (0.383)	7.75
к		: (White) : (Yellow)	30.75 (1.211) / 8.70 (0.343) 26.05 (1.026) / 7.20 (0.283)	9.9 11.83
L		E: (Blue) iE: (Pink)	24.29 (0.956) / 7.70 (0.303) 19.79 (0.779) / 7.70 (0.303)	8.13 8.51

2. RETAINER



		Height / Width / Thickness	
Mark	Retainer	mm (in.)	
A	Lock-up Relay Valve	-1-1-	
В	C-0 Exhaust Valve	8.5 (0.335) / 5.0 (0.197) / 3.2 (0.126)	
С	4-5 Shift Valve	10.0 (0.394) / 5.0 (0.197) / 3.2 (0.126)	
D	Coast Brake Control Valve	15.0 (0.591) / ø 5.0 (ø 0.197) / ø 5.0 (ø 0.197)	
E	Secondary Regulator Valve	10.0 (0.394) / 5.0 (0.197) / 3.2 (0.126)	
F	C-1 Orifice Control Valve	8.5 (0.335) / 5.0 (0.197) / 3.2 (0.126)	
G	C-1 Accumulator Valve	36.5 (1.437) / - / 3.2 (0.126)	
Н	Solenoid Modulator Valve	21.0 (0.827) / - / 3.2 (0.126)	
7	Check Valve	10.0 (0.394) / 5.0 (0.197) / 3.2 (0.126)	
J	2-3 Shift Valve	8.0 (0.315) / 8.0 (0.315) / 3.2 (0.126)	
к	B-3 Control Valve	16.5 (0.650) / 6.0 (0.236) / 3.2 (0.126)	

3. CHECK BALL



AT05K-01

COMPONENTS

