TORQUE SPECIFICATION

SS0C9-06

Part tightened	N·m	kgf⋅cm	ft·lbf
No.1 timing belt idler pulley, No.2 timing belt idler pulley x Oil pump	34.5	350	25
Drive belt tensioner x Cylinder block	15.5	160	11
Camshaft timing pulley x Camshaft timing tube	7.5	80	66
Timing belt tensioner x Oil pump	26	270	19
Crankshaft pulley x Crankshaft	245	2,500	181
No.1 drive belt idler pulley x Cylinder block 12 mm head	16	160	12
14 mm head	32	330	24
No.2 timing belt cover x Cylinder block	16	160	12
No.2 drive belt idler pulley x Fan bracket	39	398	29
Exhaust manifold x Cylinder head	44	450	32
Cylinder head x Cylinder block 1st 2nd	59 Turn 90°	600 Turn 90°	44 Turn 90°
Camshaft drive gear x Camshaft timing tube	7.5	80	66 in.·lbf
Camshaft timing tube x Intake manifold	78	790	58
Screw plug x Camshaft timing tube	15	150	11
Camshaft bearing cap x Cylinder head Bolt C	7.5	80	66 in.·lbf
Others	16	160	12
Cylinder head cover x Cylinder head	6.0	60	53 in.·lbf
Engine hanger x Cylinder head	37	380	27
Front water bypass joint, Rear water bypass joint x Cylinder head	18	185	13
Water bypass pipe x Cylinder Block	18	185	13
Timing belt rear plate x Cylinder head	7.5	80	66 in.·lbf
Intake air control valve x Upper intake manifold	8.5	85	75 in.·lbf
Upper intake manifold, Accelerator cable bracket x Lower intake manifold	18	185	13
Vacuum tank for ACIS x Lower intake manifold	18	185	13
Lower intake manifold x Cylinder head	18	185	13
Drive plate x Crankshaft	49 Turn 90°	500 Turn 90°	36 Turn 90°
Transmission x Cylinder block	72	730	53
Transmission x No.1 oil pan	37	380	27
Drive plate x Torque converter clutch	41	420	30
Flywheel housing under cover x Transmission	18	185	13
Rear engine mounting member x Body	25.5	260	19
Rear engine mounting member x Rear engine mounting insulator	13.5	135	10
Front suspension crossmember x Engine mounting insulator	68	700	50
PS gear housing x Front suspension crossmember	65	660	48
Sliding yoke x Steering intermediate shaft	35	360	26
A/C compressor x Cylinder block, No.1 drive belt idler pulley	49	500	36
A/C compressor stay x Oil filter bracket	29	300	21
PS pump x Cylinder head Bolt Nut	39.2 43.1	400 440	29 32
Center front floor brace x Body	13	130	9
Front suspension member brace x Front suspension crossmember, Strut bar bracket plate	58	590	43

SERVICE SPECIFICATIONS - ENGINE MECHANICAL (3UZ-FE)

Main bearing cap x Cylinder block	2 progressive type 1st 2nd Others	27 Turn 90° 49	275 Turn 90° 500	20 Turn 90° 36
Connecting rod cap x Connecting rod	1st 2nd	25 Turn 90°	250 Turn 90°	18 Turn 90°
Rear oil seal retainer x Cylinder block		8.0	80	71 in.·lbf
Engine coolant drain union x Cylinder block		49	500	36
Water seal plate x Cylinder block		14	145	10
Engine mounting bracket x Cylinder block		36	370	27
TWC x Exhaust manifold		62	630	46
Front exhaust pipe x TWC		44	450	32
Front exhaust pipe support bracket x Transmission	on	44	450	32
Center exhaust pipe x Tailpipe		44	450	32
Heated oxygen sensor x Front exhaust pipe		44	450	32