BODY

TORQUE SPECIFICATION

SS0FF-04

Part tightened	N·m	kgf⋅cm	ft·lbf
HOOD	-	_	_
Hood support x Hood	22	225	16
Hood x Hood hinge	13	130	9
Radiator support upper seal x Door lock	8.0	82	71
Hood lock nut x Hood lock	8.0	82	71
FRONT DOOR	-	_	_
Outside handle x Door panel	5.5	56	49 in.·lbf
Door lock striker x Door panel	23	235	17
Door hinge x Body	32.5	331	24
Door hinge x Door panel	32.5	331	24
Window regulator x Door panel	11	112	8
Door lock x Door panel	5.5	56	49 in.·lbf
REAR DOOR	_	_	-
Outside handle x Door panel	5.5	56	49 in.·lbf
Door hinge x Door panel	32.5	331	24
Door hinge x Body	32.5	331	24
Window regulator x Door panel	8.0	82	71 in.·lbf
Door lock x Door panel	5.5	56	49 in.·lbf
Retractor x Body Upper bolt:	4.9	50	43 in.·lbf
Retractor x Body Lower bolt:	42	430	31
FUEL LID	-	-	-
Lock retainer x Opening lid	5.5	56	49 in.·lbf
Fuel lid lock assembly x Body Luggage side nut:	5.5	56	49 in.·lbf
Fuel lid lock assembly x Body Fuel lid side nut:	8.0	82	71 in.·lbf
WINDSHIELD	_	_	_
Wiper arm x Wiper link	22	220	16
SLIDING ROOF	_	_	_
Sliding roof housing x Body	5.5	56	49 in.·lbf
Bracket x Body	8.0	82	71 in.·lbf
Sliding roof glass x Drive gear	5.5	56	49 in.·lbf
ROOF HEAD LINING	-	-	-
Seatback x Body	18	185	13
Front pillar garnish x Body	9.8	100	7
FRONT SEAT	_	_	-
Seat x Body	37	375	27
Seatback x Seat adjuster	61	622	45
Seat cushion x Seat adjuster	19	194	14
Inner belt x Seat	42	430	31
Vertical seat link sub-assembly x Seat track assembly	26	270	20
Vertical seat link sub-assembly x Bracket	7.8	80	69 in.·lbf
No. 2 vertical seat link sub-assembly x Reclining seat adjuster assembly Nut:	20	200	14

SERVICE SPECIFICATIONS – BODY

No. 2 vertical seat link sub-assembly x Reclining seat adjuster assembly Bolt:	29	300	22
Reclining seat adjuster assembly x Seat track assembly	20	200	14
Belt anchor bracket x Vertical seat link sub-assembly	26	270	20