

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Fuel inlet hose (Rear fuel pipe) x Fuel main tube for use with SST	32	330	24
Fuel tank vent tube set plate x Fuel tank	3.5	36	31 in.·lbf
Delivery pipe x Lower intake manifold	18	185	13
Fuel pressure pulsation damper x Delivery pipe for use with SST	33 39	340 400	24 29
Fuel sender gauge x Fuel tank	1.5	15	13 in.·lbf
Fuel tank x Body	39	400	29
Water bypass pipe x Throttle body	5.4	55	48 in.·lbf
Throttle body x Upper intake manifold, Lower intake manifold	18	185	13
Camshaft oil control valve x Camshaft bearing cap	7.5	80	66 in.·lbf
Intake air control valve x Upper intake manifold	8.5	85	75 in.·lbf
Intake air control valve actuator x Upper intake manifold	8.5	85	75 in.·lbf
Vacuum tank for ACIS x Lower intake manifold	18	185	13
Water temperature sensor x Front water bypass joint	19.6	200	14
Knock sensor x Cylinder block	45	450	33
Heated oxygen sensor x Exhaust manifold, Front exhaust pipe	44	450	32
VVT sensor x Cylinder head	6.5	65	58 in.·lbf