DI2AW-02

## DIAGNOSTIC TROUBLE CODE CHART

If a malfunction code is displayed during the DTC check, check the circuit listed for that code in the table below (Proceed to the page given for that circuit).

DTC No. (See Page)	Detection Item	Trouble Area
B1211/11 (DI-816)	Driver door ECU communication stop	Wireharness     Driver door ECU
B1212/12 (DI-818)	Front passenger door ECU communication stop	Wireharness     Passenger door ECU
B1213/13 (DI-820)	Tilt[and[elescopic[ECU[communication[stop	Wireharness     Tilt and telescopic ECU
B1214/14	Door system communication bus malfunction (+B short)	Wireharness ECU (Door system bus)
B1215/15 (DI-823)	Door system communication bus malfunction (GND short)	
B1216/16 (DI-830)	Rear right door ECU communication stop	Wireharness     Rear right door ECU
B1217/17 (DI-832)	Rear left door ECU communication stop	Wireharness     Rear left door ECU
B1218/18 (DI-834)	Body No.2 ECU communication stop	Wireharness     Body No.2 ECU
B1221/21 (DI-836)	Power window switch circuit on driver door	Power window master switch     Wireharness
B1222/22 (DI-836)	Door lock switch circuit on driver door	Door lock control switch     Door key lock and unlock switch     Wireharness
B1223/23 (DI-836)	Power[window[switch@ircuit[on[passenger@door	Power window switch     Wireharness
B1224/24 (DI-836)	Door lock switch circuit on passenger door	Door lock control switch     Door key lock and unlock switch     Wireharness
B1225/25 (DI-836)	Power window switch circuit on rear right door	Power window switch     Wireharness
B1226/26 (DI-836)	Power window switch circuit on rear left door	Power window switch     Wireharness
B1231/31 (DI-838)	Jam protection limit switch circuit on driver door	Power window motor     Wireharness
B1232/32 (DI-839)	Jam protection pulse switch circuit on driver door	
B1233/33 (DI-838)	Jam protection limit switch circuit on passenger door	Power window motor  Wireharness
B1234/34 (DI-839)	Jam protection pulse switch circuit on passenger door	
B1235/35 (DI-838)	Jam protection limit switch circuit on rear right door	Power window motor     Wireharness
B1236/36 (DI-839)	Jam protection pulse switch circuit on rear right door	
B1237/37 (DI-838)	Jam protection limit switch circuit on rear left door	Power window motor     Wireharness
B1238/38 (DI-839)	Jam protection pulse switch circuit on rear left door	

	_	
B1241/41 (DI-836)	Body No.1 ECU switch circuit diagnosis	Luggage compartment door opener switch     Luggage compartment door key lock and unlock switch     Wireharness
B1242/42 (DI-840)	Wireless door lock tuner circuit malfunction	Wireharness     Wireless door lock tuner
B1243/43 (DI-842)	GSW terminal circuit malfunction	Wireharness     Body No.1 ECU
B1244/44 (DI-845)	Light sensor circuit malfunction	Light sensor     Wireharness
B1252/52 (DI-836)	Body No.2 ECU switch circuit diagnosis	Stop light switch     Wireharness
B1253/53	Body No.2 ECU GSW terminal malfunction (Lo unusual)	Wireharness     Airbag sensor assembly     Body No.2 ECU
B1254/54 (DI-842)	Body No.2 ECU GSW terminal malfunction (Hi unusual)	
B1255/55 (DI-847)	Body No.2 ECU P1 switch malfunction	P1 switch Wireharness
B1261/61 (DI-849)	Engine and ECT ECU communication stop	Wireharness     Engine and ECT ECU
B1262/62 (DI-851)	A/C ECU communication stop	Wireharness     A/C ECU
B1266/66 B1267/67 (DI-853)	Instrument panel system communication bus malfunction (+B short)	Wireharness     ECU (Instrument panel system bus)
	Instrument panel system communication bus malfunction (GND short)	
B1271/71 (DI-861)	Combination meter ECU communication stop	Wireharness     Combination meter ECU
B1272/72 (DI-863)	Power seat ECU communication stop (w/ Seat memory vehicle only)	Wireharness     Power seat ECU
B1273/73 (DI-865)	Sliding roof ECU communication stop (w/ Sliding roof vehicle only)	Wireharness     Sliding roof ECU
B1275/75	Accessory bus buffer communication stop	Wireharness     Accessory

## HINT:

- DTC 66, 67 and 71 are not output through open door warning light on meter because of system itself.
- DTC 21~26, 41 and 52 don't mean switch abnormal but notify how switch works. If DTC is not output when operating switch, it means failure of switch contact.
  - If DTC is output when not opening switch, it means stick of switch.
- When some of the DTC 14, 15, 66, 67 is output, the DTC of other ECU communication stop is also output. In this case, please repair DTC 14, 15, 66, 67 first. The following shows DTCs which are output when +B or GND short occurs on communication bus.

	Door overteen communication has	Instrument penal avetem communication has
	Door system communication bus	Instrument panel system communication bus
GND short	After 10 seconds from detecting fail, Instrument panel system communication bus is able to communicate by bus cut function.	After 10 seconds from detecting fail, Door system communication bus is able to communicate by bus cut function.
Communication possible ECU after bus is cut	Body No.1 ECU, Body No.2 ECU, A/C ECU, Multi display, Tilt and telescopic ECU, Combination Meter ECU, Engine and ECT ECU	Driver door ECU, Passenger door ECU, Rear right door ECU, Rear left door ECU, Power seat ECU, Sliding roof ECU, Accessory bus buffer.
DTC(B12XX) ( ): Option	11, 12, <u>15</u> , 16, 17, (72), (73), (75)	11, 12, 13, 16, 17, 18, 61, 62, <u>67, 71, (72), (73), (75)</u> *
+B short	(Same as GND short)	(Same as GND short)
Communication possible ECU after bus is cut	(Same as GND short)	(Same as GND short)
DTC(B12XX) ( ): Option	11, 12, <u>14</u> , 16, 17, (72), (73), (75)	11, 12, 13, 16, 17, 18, 61, 62, <u>66, 71, (72), (73), (75)</u> *

<sup>\*:</sup> Body No.1 ECU and Door system communication bus are cut off by bus cut relay, so it detects communication stop of ECU connected to Door system communication bus.