

DTC	P1127	ETCS Actuator Power Source Circuit Malfunction
------------	--------------	---

*: ETCS trouble code No. is 23.


CIRCUIT DESCRIPTION

Battery positive voltage is supplied to terminal BM of the engine ECU even once when the ignition switch is OFF for the electric throttle control system.

If this DTC is stored, the engine ECU shuts down the power for the throttle motor, and the throttle valve is fully closed by the return spring.

DTC No.	DTC Detecting Condition	Trouble Area
P1127	Open in ETCS power source circuit	<ul style="list-style-type: none"> • Open in ETCS power source circuit • Engine ECU

WIRING DIAGRAM




INSPECTION PROCEDURE

HINT:

Read freeze frame data using OBD scan tool or hand-held tester. Because freeze frame records the engine conditions when the malfunction is detected. When troubleshooting it is useful for determining whether the vehicle was running or stopped, the engine was warmed up or not, the air-fuel ratio was lean or rich, etc. at the time of the malfunction.

1 Check ETCS fuse.



PREPARATION:

Remove the ETCS fuse from the engine room No.1 R/B.

CHECK:

Check the continuity of the ETCS fuse.

OK:


Continuity

NG

Check for short in all harness and components connected to ETCS fuse.

OK

2 Check voltage between terminal +BM of engine ECU connector and body ground.



PREPARATION:

Remove the engine ECU hood and cover (See page FI-74).

CHECK:

Measure the voltage between terminal +BM of the engine ECU connector and body ground.

OK:

Voltage: 9 - 14 V

OK

Check and replace engine ECU (See page IN-30).

NG

Check and repair harness or connector between battery and ETCS fuse, and ETCS fuse and engine ECU (See page IN-30).