

TORQUE SPECIFICATION

Part tighten	N·m	kgf·cm	ft·lbf
FRONT			
Hub nut	103	1,050	76
Brake caliper x Steering knuckle	118	1,200	87
ABS speed sensor x Steering knuckle	7.8	80	69 in·lbf
Steering knuckle x Upper suspension arm	87	890	64
Lower ball joint x Steering knuckle	113	1,150	83
Brake dust cover x Steering knuckle	8.3	85	74 in·lbf
ABS speed sensor wire harness x Shock absorber	5.0	55	48 in·lbf
Stabilizer bar x Stabilizer bar link	55	560	41
Shock absorber bracket x Shock absorber	157	1,600	116
Piston rod x Suspension support No.2	27	280	20
Suspension support x Body	56	570	41
Upper suspension arm x Body	53	540	39
Stabilizer bar link x No.2 lower suspension arm	113	1,150	83
Height control link x Shock absorber bracket	5.4	55	48 in·lbf
No.2 lower suspension arm x No.1 lower suspension arm	164	1,690	122
No.2 lower suspension arm x Lower ball joint	162	1,650	119
Strut bar bracket x Body	A	58	43
	B	152	112
No.2 lower suspension arm x Body	172	1,755	127
Shock absorber bracket x No.1 lower suspension arm	59	600	44
Tie rod end x Lower ball joint	87	890	64
Stabilizer bar bracket x Body	28	290	21
Tie rod end lock nut	56	570	41
Axle hub lock nut	199	2,030	147
Suspension member brace x Body	58	590	43

SERVICE SPECIFICATIONS – SUSPENSION AND AXLE

Part tighten		N·m	kgf·cm	ft·lbf
REAR				
Hub nut		103	1,050	76
Brake caliper x Axle carrier		104	1,065	77
Axle carrier x Upper suspension arm		108	1,100	80
Backing plate x Axle carrier		59	600	43
Drive shaft x Axle hub		289	2,950	213
No.2 lower suspension arm x Axle carrier		110	1,120	81
No.1 lower suspension arm x Axle carrier		75	765	55
Drive shaft x Differential side gear shaft		83	850	61
Differential drain plug		49	500	39
Differential filler plug		49	500	39
Differential mounting bolt	Front	123	1,250	90
	Rear	142	1,450	105
Ring gear set bolt		See page SA-73		
Companion flange lock nut		See page SA-73		
Differential carrier retainer set bolt		22	225	16
Differential carrier cover set bolt		47	475	34
Breather plug		21	210	15
Suspension support x Body	Upper side	64	650	47
	Lower side	18	185	13
Piston rod x Suspension support		27	280	20
Upper suspension arm x Body		88	900	65
No.1 lower suspension arm x Body		75	765	55
No.2 lower suspension arm x Stabilizer bar link x Height control sensor link		30	305	22
No.2 lower suspension arm x Shock absorber		110	1,120	81
No.2 lower suspension arm x Body		110	1,120	81
ABS speed sensor wire harness x Toe control link		5.4	55	48 in.·lbf
Toe control link x Axle carrier		59	600	44
Toe control link x Body		59	600	44
Stabilizer bar x Stabilizer bar link		65	660	48
Stabilizer bar bracket x Body		18	185	13
ABS speed sensor x Axle carrier		7.8	80	69 in.·lbf
Parking brake cable x Backing plate		7.8	80	69 in.·lbf
Suspension member brace x Body		50	510	37
Differential x Propeller shaft		79	805	58
Oil deflector x Differential carrier cover		7.0	70	62 in.·lbf