

DOCUMENT GSM-AUS-CPL.032

AUS OPERATIONS, FLIGHT PLANNING AND PERFORMANCE

CHAPTER 5 ECHO LOADING DATA

Version 1.0 January 2013

This is a controlled document. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form, or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior permission, in writing, from the Chief Executive Officer of Flight Training Adelaide.

CHAPTER 5 ECHO LOADING DATA



AUS OPERATIONS, FLIGHT PLANNING AND PERFORMANCE

| CONTENTS | PAGE | |
|------------------------------------|------|--|
| | | |
| LOADING DATA - ECHO MK LV AIRCRAFT | 3 | |


LOADING DATA - ECHO MK LV AIRCRAFT


Study the information on these two pages. The moment arms for the various stations are listed in the table on Page 2 of this section.

Look at the picture of the ECHO Mk IV below and compare the distances with those listed on page 2.


Notice that 1 IU = 10000 kgmm as indicated on the graph on Page 2.

The Echo Mark IV aircraft





Echo Mk IV Centre of Gravity envelope



Loading Data

| Location | Maximum permissible load | Loading arm (mm aft of datum) |
|--------------------------------|--------------------------|----------------------------------|
| Seating | | |
| Row 1 (Seats 1 & 2) | Pilot and 1 passenger | 2290 mm |
| Row 2 (Seats 3 & 4) | 2 passengers | 3300 mm |
| Row 3 (Seats 5 & 6) | 2 passengers | 4300 mm |
| Cargo and Baggage Compartments | | |
| Forward compartment | 55 kg | 500 |
| Left wing compartment | 55 kg | 3550 |
| Right wing compartment | 55 kg | 3550 |
| Rear compartment | 155 kg | 5000 |
| Fuel | | |
| Left main tank | 50 gal | 1780 |
| Right main tank | 50 gal | 1780 |
| Left auxiliary tank | 40 gal | 2800 |
| Right auxiliary tank | 40 gal | 2800 |