



DOCUMENT
GSM-AUS-CPL.024

DOCUMENT TITLE
METEOROLOGY FOR AUSTRALIA

CHAPTER 8 – DEW POINT LAPSE RATE

Version 3.0
November 2014

This is a controlled document. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form, or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior permission, in writing, from the Chief Executive Officer of Flight Training Adelaide.


CONTENTS	PAGE
DEW POINT LAPSE RATE	3

DEW POINT LAPSE RATE

As we have seen, dew point is defined as the temperature to which moist air must be cooled to produce saturation. Any further cooling below the dew point will produce condensation.

When a parcel of air rises, it expands. This expansion will cause the pressure in the parcel of air to reduce. The partial pressure of the water vapour will also reduce and this reduces the dew point. The Dew Point Lapse Rate (DPLR) is 0.5°C/1,000 ft. for unsaturated air.

For example, if the surface temperature is 30°C and the Dew Point is 17.5°C, what height is the condensation level?



Answer: 5,000 ft.

$$\frac{\text{Temp} - \text{dew point}}{2.5} \times 1,000\text{s} = \text{cloud base (000's of feet)}$$