Taming Asynchronous .NET Code with Rx

INTRODUCING REACTIVE PROGRAMMING

Edin Kapić

@ekapic www.edinkapic.com

Asynchronous and event-driven programming is difficult

Reactive Extensions (Rx)

Demo



“Show a button if the mouse hovers for more than half a second in the designated active area”

- With event handlers
- With Rx sequences

.NET Reactive Extensions Fundamentals 1.0

by Dan Sullivan

Using the .NET Reactive Extensions to develop asynchronous applications.

▶ Start Course

Table of contents | Description | Transcript | Exercise files | Discussion | Recommended

Expand all

Course author

Dan Sullivan

Dan is an independent consultant, author, and speaker. He likes data; pointy data, rectangular data, even data just lying around on the floor. He is a co-author of the book "A Developers ...

Course info

Level	Advanced
Rating	★★★★½ (304)
My rating	★★★★★
Duration	3h 54m
Released	17 May 2011

“Reactive Programming is a programming paradigm oriented around **data flows** and the **propagation of change**”

Wikipedia

Reactive Excel Spreadsheets



Reactive Extensions (Rx) Library



https://github.com/Reactive-Extensions/Rx.NET

Rx Library Pillars



Flows, Sequences and Events

LINQ and Extensions

Schedulers and Concurrency

Rx Availability

Languages

- Java: RxJava
- JavaScript: RxJS
- C#: Rx.NET
- C#(Unity): UniRx
- Scala: RxScala
- Clojure: RxClojure
- C++: RxCpp
- Ruby: Rx.rb
- Python: RxPY
- Groovy: RxGroovy
- JRuby: RxJRuby
- Kotlin: RxKotlin
- Swift: RxSwift

http://reactivex.io

ReactiveX for platforms and frameworks

- RxNetty
- RxAndroid
- RxCocoa

Events in .NET

Implementation of Observer pattern with delegates

Not a first-class citizen in .NET

- Clumsy syntax (+=)
- Difficult to pass around
- Awkward chaining and error handling
- No history of events

Observables and Observers

Source



Observable Sequence of Mouse Coordinates

Observer

Core Interfaces

IObservable

```
Subscribe(IObserver<T> observer)
```

IObserver

```
void OnNext<T>(T value)
void OnCompleted()
void OnError(Exception ex)
```

Marble Diagrams



Sample Marble Diagram



OnNext()	OnNext()	OnError()	OnCompleted()

Unsubscribing from IObservable



Demo



Fictitious support ticket management UWP app called “Reactive Tickets”

Implement the search-as-you-type feature

- Using events
- Using observable sequences

Summary

Asynchronous and event-driven programming is difficult

- The code is harder to maintain

Reactive programming treats all changes in data as value sequences in time

- “Events on steroids”

Observers can subscribe to changes in those sequences

Rx adds reactive programming to .NET with full Linq support