

# Statically Typed String Sanitation Inside a Python

Nathan Fulton

Cyrus Omar

Jonathan Aldrich

Carnegie Mellon University, Pittsburgh, PA  
{nathanfu, comar, aldrich}@cs.cmu.edu

## ABSTRACT

Web applications must ultimately command systems like web browsers and database engines using strings. Strings derived from improperly sanitized user input can thus be a vector for command injection attacks. In this paper, we introduce *regular string types*, which classify strings known statically to be in a specified regular language. These types come equipped with common operations like concatenation, substitution and coercion, so they can be used to implement, in a conventional manner, the portions of a web application or application framework that must directly construct command strings. Simple type annotations at key interfaces can be used to statically verify that sanitization has been performed correctly without introducing redundant run-time checks. We specify this type system in a minimal typed lambda calculus,  $\lambda_{RS}$ .

To be practical, adopting a specialized type system like this should not require the adoption of a new programming language. Instead, we advocate for extensible type systems: new type system fragments like this should be implemented as libraries atop a mechanism that guarantees that they can be safely composed. We support this with two contributions. First, we specify a translation from  $\lambda_{RS}$  to a language fragment containing only standard strings and regular expressions. Second, taking Python as a language with these constructs, we implement the type system together with the translation as a library using **atlang**, an extensible static type system for Python being developed by the authors.

## 1. INTRODUCTION

Command injection vulnerabilities are among the most common and severe security vulnerabilities in modern web applications [10]. They arise because web applications, at their boundaries, control external systems using commands represented as strings. For example, web browsers are controlled using HTML and Javascript sent from a server as a string, and database engines execute SQL queries also sent as strings. When these commands include data derived from user input, care must be taken to ensure that the user can-

not subvert the intended command by carefully crafting the data they send. For example, a SQL query constructed using string concatenation exposes a SQL injection vulnerability:

```
'SELECT * FROM users WHERE name=' + name + ''
```

If a malicious user enters the name `""; DROP TABLE users --`, the entire database could be erased.

To avoid this problem, the program must *sanitize* user input. For example, in this case, the developer (or, more often, a framework) might define a function **sanitize** that escapes double quotes and existing backslashes with a backslash, which SQL treats safely. Alternatively, it might HTML-encode special characters, which would head off both SQL injection attacks and cross-site scripting attacks. Guaranteeing that user input has already been sanitized before it is used to construct a command is challenging, especially because sanitization and command construction may occur in separately developed and maintained components.

We observe that many such sanitization techniques can be understood using *regular languages* [7]. For example, **name** must be a string in the language described by the regular expression  $([\^"\\]|(\")|(\backslash\backslash))^*$  – a sequence of characters other than quotation marks and backslashes; these can only appear escaped. This syntax for regular expression patterns can be understood to desugar, in a standard way, to the syntax for regular expressions shown in Figure 1, where  $r \cdot r$  is sequencing and  $r + r$  is disjunction. We will work with this “core” for simplicity.

In this paper, we present a static type system that tracks the regular language a string belongs to. For example, the output of **sanitize** will be a string in the regular language described by the regular expression above (we identify regular languages by the notation  $\mathcal{L}\{r\}$ ). By leveraging closure and decidability properties of regular languages, the type system tracks the language of a string through uses of a number of operations, including *replacement* of substrings matching a given pattern. This makes it possible to implement sanitation functions – like the one just described – in a conventional manner. The result is a system where the fact that a string has been correctly sanitized is manifest in its type. Missing calls to sanitization functions are detected statically, and, importantly, so are *incorrectly implemented sanitization functions* (i.e. these functions need not be trusted). These guarantees require run-time checks only when going from less precise to more precise types (e.g. along the interfaces with external systems or components that are not under the control of this type system).

We will begin in Sec. 2 by specifying this type system minimally, as a conservative extension of the simply typed

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

Copyright 20XX ACM X-XXXXX-XX-X/XX/XX ...\$15.00.

lambda calculus called  $\lambda_{RS}$ . This allows us to specify the guarantees that the type system provides precisely. We also formally specify a translation from this calculus to a typed calculus with only standard strings and regular expressions, intending it as a guide to language implementors interested in building this feature into their own languages. This also demonstrates that no additional space overhead is required.

Waiting for a language designer to build this feature in is unsatisfying in practice. Moreover, we also face a “chicken-and-egg problem”: justifying its inclusion into a commonly used language benefits from empirical case studies, but these are difficult to conduct if developers have no way to use the abstraction in real-world code. We take the position that a better path forward for the community is to work within a programming language where such type system fragments can be introduced modularly and orthogonally, as libraries.

In Sec. 3, we show how to implement the type system fragment we have specified using **atlang**, an extensible static type system implemented as a library inside Python. **atlang** leverages local type inference to control the semantics of literal forms, so regular string types can be introduced using string literals without any run-time overhead. Coercions that are known to be safe due to a sublanguage relationship are performed implicitly, also without run-time overhead. This results in a *usably secure* system: working with regular strings differs little from working with standard strings in a language that web developers have already widely adopted.

We conclude after discussing related work in Sec. 4.

## 2. REGULAR STRING TYPES, MINIMALLY

This section is organized as follows:

- Section 2.1 describes  $\lambda_{RS}$ . We also give proof outlines of type safety and correctness theorems and relevant propositions about regular languages.
- Section 2.2 describes a simple target language,  $\lambda_P$ , with a minimal regular expression library. In Section 3, we will take Python to be such a language.
- Section 2.3 describes the translation from  $\lambda_{RS}$  to  $\lambda_P$  and ensures the correctness result for 2.1 is preserved under this translation.

### 2.1 The Language of Regular Strings

In this section, we define a minimal typed lambda calculus with regular string types called  $\lambda_{RS}$ . The syntax of  $\lambda_{RS}$  is specified in Figure 2, its static semantics in Figure 3 and its evaluation semantics in Figure 4.<sup>1</sup>

There are two type constructors in  $\lambda_{RS}$ ,  $\rightarrow$  and **stringin**. Arrow types classify functions, which are introduced via lambda abstraction,  $\lambda x.e$ , and can be applied, written  $e(e)$ , in the usual way [6]. Regular string types are of the form **stringin**[ $r$ ], where  $r$  is a regular expression. Values of such regular string types take the form **rstr**[ $s$ ], where  $s$  is a string (i.e.  $s \in \Sigma^*$ , defined in the usual way). The rule S-T-STRINGIN-I requires that  $s \in \mathcal{L}\{r\}$ .

$\lambda_{RS}$  provides several familiar operations on strings. The type system relates these operations over strings to corresponding operations over the regular languages they belong to. Since these operations over regular languages are known

<sup>1</sup>For convenience, a single sheet containing Figures 2-8 is available in the accompanying technical report [TR](#).

$$r ::= \epsilon \mid \cdot \mid a \mid r \cdot r \mid r + r \mid r^* \quad a \in \Sigma$$

Figure 1: Regular expressions over the alphabet  $\Sigma$ .

$$\begin{aligned} \sigma &::= \sigma \rightarrow \sigma \mid \text{stringin}[r] && \text{source types} \\ e &::= x \mid \lambda x.e \mid e(e) && \text{source terms} \\ &\quad \mid \text{rstr}[s] \mid \text{rconcat}(e; e) \mid \text{rstrcase}(e; e; x, y.e) \quad s \in \Sigma^* \\ &\quad \mid \text{rcoerce}[r](e) \mid \text{rcheck}[r](e; x.e; e) \mid \text{rreplace}[r](e; e) \\ v &::= \lambda x.e \mid \text{rstr}[s] && \text{source values} \end{aligned}$$

Figure 2: Syntax of  $\lambda_{RS}$ .

to be closed and decidable, we can use these operations as a basis for static analysis of sanitation protocols (we will see a complete example in Section 3).

#### 2.1.1 Concatenation and String Decomposition

The S-T-CONCAT rule is the simplest example of our approach. The rule is sound because the result of concatenating two strings, the first in  $\mathcal{L}\{r_1\}$  and the second in  $\mathcal{L}\{r_2\}$ , will always be in the language  $\mathcal{L}\{r_1 \cdot r_2\}$ . The rule therefore relates string concatenation to sequential composition of regular expressions.

Whereas concatenation allows the construction of large strings from smaller strings, **rstrcase**( $e; e_0; x, y.e_1$ ) allows the decomposition, or elimination, of large strings into smaller strings. Intuitively, this operation branches based on whether a string is empty or not, exactly analogous to case analysis on lists in a functional language. The branch for a non-empty string “peels off” the first character, binding it and the remainder of the string to specified variables. The evaluation rules S-E-CASE- $\epsilon$  and S-E-CASE-CONCAT express this semantics. This construct can be used to implement a standard string indexing operation as a function, given a suitable definition of natural numbers (omitted).

The regular expressions describing the first character and remaining characters of a matching string in the language  $\mathcal{L}\{r\}$  must be determined to correctly specify the static semantics. For instance, the first character of a string in the language  $\mathcal{L}\{(A \cdot B \cdot C) + (D \cdot E \cdot F)\}$  is in the language  $\mathcal{L}\{A + D\}$  and the remaining characters are in the language  $\mathcal{L}\{(B \cdot C) + (E \cdot F)\}$ .

The regular expression recognizing any one-character prefix of the strings in  $\mathcal{L}\{r\}$  is easily defined.

**Definition 1** (Definition of **lhead**( $r$ )). The function **lhead**( $r$ ) is defined in terms of the structure of  $r$ :

- **lhead**( $ar'$ ) =  $a$  where  $a \in \Sigma$
- **lhead**( $r_1 r_2$ ) = **lhead**( $r_1$ )
- **lhead**( $\epsilon$ ) =  $\epsilon$
- **lhead**( $r_1 + r_2$ ) = **lhead**( $r_1$ ) + **lhead**( $r_2$ )
- **lhead**( $r^*$ ) = **lhead**( $r$ )
- **lhead**( $\cdot$ ) =  $a_1 + a_2 + \dots + a_n$  for all  $a_i \in \Sigma$  where  $|\Sigma| = n$ .

Given this definition of **lhead**( $r$ ), regular expression derivatives [2] provide a useful tool for defining **ltail**( $r$ ).

**Definition 2** (Brzowski’s Derivative). The *derivative of  $r$  with respect to  $s$*  is denoted by  $\delta_s(r)$  and is  $\delta_s(r) = \{t \mid st \in \mathcal{L}\{r\}\}$ .

Definition 2 is equivalent to the definition given in [2], although we refer the unfamiliar reader to [11]. Definition 2

$$\boxed{\Psi \vdash e : \sigma} \quad \Psi ::= \emptyset \mid \Psi, x : \sigma$$

$$\begin{array}{c}
\text{S-T-VAR} \\
\frac{x : \sigma \in \Psi}{\Psi \vdash x : \sigma}
\end{array}
\quad
\begin{array}{c}
\text{S-T-ABS} \\
\frac{\Psi, x : \sigma_1 \vdash e : \sigma_2}{\Psi \vdash \lambda x. e : \sigma_1 \rightarrow \sigma_2}
\end{array}$$

$$\begin{array}{c}
\text{S-T-APP} \\
\frac{\Psi \vdash e_1 : \sigma_2 \rightarrow \sigma \quad \Psi \vdash e_2 : \sigma_2}{\Psi \vdash e_1(e_2) : \sigma}
\end{array}
\quad
\begin{array}{c}
\text{S-T-STRINGIN-I} \\
\frac{s \in \mathcal{L}\{r\}}{\Psi \vdash \text{rstr}[s] : \text{stringin}[r]}
\end{array}$$

$$\begin{array}{c}
\text{S-T-CONCAT} \\
\frac{\Psi \vdash e_1 : \text{stringin}[r_1] \quad \Psi \vdash e_2 : \text{stringin}[r_2]}{\Psi \vdash \text{rconcat}(e_1; e_2) : \text{stringin}[r_1 \cdot r_2]}
\end{array}$$

$$\begin{array}{c}
\text{S-T-CASE} \\
\frac{\Psi \vdash e_1 : \text{stringin}[r] \quad \Psi \vdash e_2 : \sigma \quad \Psi, x : \text{stringin}[\text{head}(r)], y : \text{stringin}[\text{ltail}(r)] \vdash e_3 : \sigma}{\Psi \vdash \text{rstrcase}(e_1; e_2; x, y, e_3) : \sigma}
\end{array}$$

$$\begin{array}{c}
\text{S-T-SAFECOERCE} \\
\frac{\Psi \vdash e : \text{stringin}[r'] \quad \mathcal{L}\{r'\} \subseteq \mathcal{L}\{r\}}{\Psi \vdash \text{rcoerce}[r](e) : \text{stringin}[r]}
\end{array}$$

$$\begin{array}{c}
\text{S-T-CHECK} \\
\frac{\Psi \vdash e_0 : \text{stringin}[r_0] \quad \Psi, x : \text{stringin}[r] \vdash e_1 : \sigma \quad \Psi \vdash e_2 : \sigma}{\Psi \vdash \text{rcheck}[r](e_0; x, e_1; e_2) : \sigma}
\end{array}$$

$$\begin{array}{c}
\text{S-T-REPLACE} \\
\frac{\Psi \vdash e_1 : \text{stringin}[r_1] \quad \Psi \vdash e_2 : \text{stringin}[r_2] \quad \text{lreplace}(r; r_1; r_2) = r'}{\Psi \vdash \text{rreplace}[r](e_1; e_2) : \text{stringin}[r']}
\end{array}$$

**Figure 3: Typing rules for  $\lambda_{RS}$ . The typing context  $\Psi$  is standard.**

is equivalent to Definition 3.1 in both papers. We now define  $\text{ltail}(r)$  using derivatives with respect to  $\text{lhead}(r)$ .

**Definition 3** (Definition of  $\text{ltail}(r)$ ). The function  $\text{ltail}(r)$  is defined in terms of  $\text{lhead}(r)$ . Note that  $\text{lhead}(r) = a_1 + a_2 + \dots + a_i$ . We define  $\text{ltail}(r) = \delta_{a_1}(r) + \delta_{a_2}(r) + \dots + \delta_{a_i}(r)$ .

The S-T-CASE rule, which is defined in terms of these operations, thus relates the result of “peeling off” the first character of a string to regular expression derivatives.

### 2.1.2 Coercion

The  $\lambda_{RS}$  language supports two forms of coercion. Safe coercions, written  $\text{rcoerce}[r](e)$ , allow passage to a “smaller” regular language. Such coercions will always succeed. Conversely, checked coercions, written  $\text{rcheck}[r](e_0; x, e_1; e_2)$ , allow for passage to regular languages that are not necessarily smaller. Checked coercions branch based on whether the coercion succeeded or not.

The rule S-T-SAFECOERCE checks for language inclusion, which we write  $\mathcal{L}\{r_1\} \subseteq \mathcal{L}\{r_2\}$ . Language inclusion is a decidable relation. As a result, the rule S-E-SAFECOERCE does not need to perform any checks. The rule S-T-CHECK does not perform any static checks on the two languages involved, only checking that the two branches have the same type. The checks are performed dynamically, shown in the rules S-E-CHECK-OK and S-E-CHECK-NOTOK.

In our calculus, both forms of coercion are explicit. For safe coercions, it is often useful for the coercion to be performed implicitly. This can be seen as a form of subtyping for regular string types [cite?](#). In practice, subtyping is crucial to the usability of our system due to the nature of the

$$\boxed{e \Downarrow v}$$

$$\begin{array}{c}
\text{S-E-ABS} \\
\frac{}{\lambda x. e \Downarrow \lambda x. e}
\end{array}
\quad
\begin{array}{c}
\text{S-E-APP} \\
\frac{e_1 \Downarrow \lambda x. e_3 \quad e_2 \Downarrow v_2 \quad [v_2/x]e_3 \Downarrow v}{e_1(e_2) \Downarrow v}
\end{array}$$

$$\begin{array}{c}
\text{S-E-RSTR} \\
\frac{}{\text{rstr}[s] \Downarrow \text{rstr}[s]}
\end{array}
\quad
\begin{array}{c}
\text{S-E-CONCAT} \\
\frac{e_1 \Downarrow \text{rstr}[s_1] \quad e_2 \Downarrow \text{rstr}[s_2]}{\text{rconcat}(e_1; e_2) \Downarrow \text{rstr}[s_1 s_2]}
\end{array}$$

$$\begin{array}{c}
\text{S-E-CASE-}\epsilon \\
\frac{e_1 \Downarrow \text{rstr}[\epsilon] \quad e_2 \Downarrow v_2}{\text{rstrcase}(e_1; e_2; x, y, e_3) \Downarrow v_2}
\end{array}$$

$$\begin{array}{c}
\text{S-E-CASE-CONCAT} \\
\frac{e_1 \Downarrow \text{rstr}[as] \quad [\text{rstr}[a], \text{rstr}[s]/x, y]e_3 \Downarrow v_3}{\text{rstrcase}(e_1; e_2; x, y, e_3) \Downarrow v_3}
\end{array}$$

$$\begin{array}{c}
\text{S-E-SAFECOERCE} \\
\frac{e \Downarrow \text{rstr}[s]}{\text{rcoerce}[r](e) \Downarrow \text{rstr}[s]}
\end{array}$$

$$\begin{array}{c}
\text{S-E-CHECK-OK} \\
\frac{e \Downarrow \text{rstr}[s] \quad s \in \mathcal{L}\{r\} \quad [\text{rstr}[s]/x]e_1 \Downarrow v}{\text{rcheck}[r](e; x, e_1; e_2) \Downarrow v}
\end{array}$$

$$\begin{array}{c}
\text{S-E-CHECK-NOTOK} \\
\frac{e \Downarrow \text{rstr}[s] \quad s \notin \mathcal{L}\{r\} \quad e_2 \Downarrow v}{\text{rcheck}[r](e; x, e_1; e_2) \Downarrow v}
\end{array}$$

$$\begin{array}{c}
\text{S-E-REPLACE} \\
\frac{e_1 \Downarrow \text{rstr}[s_1] \quad e_2 \Downarrow \text{rstr}[s_2] \quad \text{subst}(r; s_1; s_2) = s}{\text{rreplace}[r](e_1; e_2) \Downarrow \text{rstr}[s]}
\end{array}$$

**Figure 4: Big step semantics for  $\lambda_{RS}$**

replacement operator. For simplicity, we do not include this relation; however, subtyping for regular strings is present in previous treatments of our work [4, 5]. The implementation discussed in Section 3 also provides subtyping between regular string types.

### 2.1.3 Replacement

The premier operation for working with regular strings in  $\lambda_{RS}$  is replacement, written  $\text{rreplace}[r](e_1; e_2)$ . It behaves analogously to `str_replace` in PHP and `String.replace` in Java, differing in that the replacement pattern  $r$  must be statically given. The evaluation rule S-E-REPLACE is defined via the relation  $\text{subst}(r; s_1; s_2) = s$ . For simplicity, we do not inductively define this standard relation.

**Definition 4 (subst).** The relation  $\text{subst}(r; s_1; s_2) = s$  produces a string  $s$  in which all substrings of  $s_1$  in  $\mathcal{L}\{r\}$  are replaced with  $s_2$ .

The typing rule S-T-REPLACE requires computing the regular language of the string resulting from this operation given the languages of  $s_1$  and  $s_2$ , written as the relation  $\text{lreplace}(r; r_1; r_2) = r'$ . Given an automata-oriented interpretation of regular languages, it may be helpful to think in terms of replacing sub-automata.

A complete definition of  $\text{lreplace}$  would also give an rewrite system with correctness and termination proofs, which is beyond the scope of this paper. Instead, we provide an abstract definition of the relation and state necessary properties.

**Definition 5** (`lreplace`). The relation  $\text{lreplace}(r; r_1; r_2) = r'$  relates  $r, r_1$ , and  $r_2$  to a language  $r'$  containing all strings of  $r_1$  except that any substring  $s_{\text{pre}} s s_{\text{post}} \in \mathcal{L}\{r_1\}$  where  $s \in \mathcal{L}\{r\}$  is replaced by the set of strings  $s_{\text{pre}} s_2 s_{\text{post}}$  for all  $s_2 \in \mathcal{L}\{r_2\}$  (the prefix and postfix positions may be empty). This procedure saturates the string.

**Proposition 6** (Closure). *If  $\mathcal{L}\{r\}, \mathcal{L}\{r_1\}$  and  $\mathcal{L}\{r_2\}$  are regular languages, then  $\mathcal{L}\{\text{lreplace}(r; r_1; r_2)\}$  is also a regular language.*

*Proof Sketch.* Algorithms for the inclusion problem may be adopted to identify any sublanguage  $x \subseteq r$  of  $r_1$ . The language  $x_{\text{pre}}$  can be computed by taking total derivatives until the remaining language equals  $x$ ;  $x_{\text{post}}$  can be computed in a similar way after reversal. Then  $r'$  is  $x_{\text{pre}} r_2 x_{\text{post}}$ .  $\square$

**Proposition 7** (Substitution Correspondence). *If  $s_1 \in \mathcal{L}\{r_1\}$  and  $s_2 \in \mathcal{L}\{r_2\}$  then  $\text{subst}(r; s_1; s_2) \in \mathcal{L}\{\text{lreplace}(r; r_1; r_2)\}$ .*

*Proof Sketch.* The proposition follows from the definitions of `subst` and `lreplace`; note that language substitutions over-approximate string substitutions. [elaborate on this?](#)  $\square$

### 2.1.4 Safety

In this section, we establish type soundness for  $\lambda_{RS}$ . The theorem relies upon the definitions and propositions given above and some basic properties of regular languages.

**Lemma 8** (Properties of Regular Languages.).

1. *If  $s_1 \in \mathcal{L}\{r_1\}$  and  $s_2 \in \mathcal{L}\{r_2\}$  then  $s_1 s_2 \in \mathcal{L}\{r_1 \cdot r_2\}$ .*
2. *For all strings  $s$  and regular expressions  $r$ , either  $s \in \mathcal{L}\{r\}$  or  $s \notin \mathcal{L}\{r\}$ .*
3. *Regular languages are closed under reversal.*

If any of these properties are unfamiliar, the reader may refer to a standard text on the subject [7].

We also need to establish a well-formedness lemma, which simply expresses the totality of the operations over regular expressions used as premises in the rules in Figure 3.

**Lemma 9.** *If  $\Psi \vdash e : \text{stringin}[r]$  then  $r$  is a well-formed regular expression.*

*Proof Sketch.* The only non-trivial case is S-T-Replace, which follows from Proposition 6. [what about lhead/ltail?](#)  $\square$

Safety for the string fragment of  $\lambda_{RS}$  requires validating that the type system's definition is justified by our theorems about regular languages.

We avoid the most significant issues inherent to proofs related to big-step semantics by avoiding non-termination in our specification. The simply typed lambda calculus terminates, and our conservative extension clearly terminates because new binding structures are not introduced and termination (i.e. decidability) of `subst` and `lreplace` is known. Even in a non-terminating calculus, type safety holds. However, a more careful treatment or treatment for a language with non-termination would need to proceed by either a coinductive argument [1] or with a small-step semantics.

**Theorem 10** (Type Safety.). *If  $\emptyset \vdash e : \sigma$  then  $e \Downarrow v$  and  $\emptyset \vdash v : \sigma$ .*

$\tau ::= \tau \rightarrow \tau \mid \text{string} \mid \text{regex}$	target types
$\iota ::= x \mid \lambda x. \iota \mid \iota(\iota)$ $\quad \mid \text{str}[s] \mid \text{concat}(\iota; \iota) \mid \text{strcase}(\iota; \iota; x, y. \iota)$ $\quad \mid \text{rx}[r] \mid \text{check}(\iota; \iota; \iota) \mid \text{replace}(\iota; \iota; \iota)$	target terms
$\dot{v} ::= \lambda x. \iota \mid \text{str}[s] \mid \text{rx}[r]$	target values

**Figure 5: Syntax for the target language,  $\lambda_P$ , containing strings and statically constructed regular expressions.**

*Proof Sketch.* By induction on the typing relation. The S-T-CONCAT case requires Lemma 8.1, the S-T-CHECK case requires Lemma 8.2 and the S-T-Replace case appeals to Proposition 7.  $\square$

We can also define a canonical forms lemma for regular strings.

**Lemma 11** (Canonical Forms for String Fragment of  $\lambda_{RS}$ ). *If  $\emptyset \vdash e : \text{stringin}[r]$  and  $e \Downarrow v$  then  $v = \text{rstr}[s]$ .*

*Proof Sketch.* The proof is again by induction on the typing relation, following straightforwardly.  $\square$

### 2.1.5 The Security Theorem

The chief benefit of  $\lambda_{RS}$  is its security theorem, which states that any value of a regular string type is recognized by the regular language corresponding to the regular expression the type is indexed by. This is beneficial because this ensure that membership in a regular language known to be secure becomes manifest in the type of the string, rather than being a property that must be established extralinguistically.

**Theorem 12** (Correctness of Input Sanitation for  $\lambda_{RS}$ ). *If  $\emptyset \vdash e : \text{stringin}[r]$  and  $e \Downarrow \text{rstr}[s]$  then  $s \in \mathcal{L}\{r\}$ .*

*Proof Sketch.* The theorem follows directly from type safety, canonical forms for  $\lambda_{RS}$ , and inversion of S-T-STRINGIN-I, the typing rule for terms of the form `rstr[s]`.  $\square$

## 2.2 Target Language

Our next major technical result, stated in Sec. 2.3, establishes that the security property is preserved under translation into  $\lambda_P$ , which we now define.

The system  $\lambda_P$  is another straight-forward extension of a simply typed lambda calculus with a `string` type and a `regex` type, as well as some operations – such as concatenation and replacement – found in the standard libraries of many programming languages. The operations of  $\lambda_P$  correspond to “run-time” versions of the operations performed statically in  $\lambda_{RS}$  in a way made precise by the translation rules described in the next section. The language  $\lambda_P$  is so-called because it is reminiscent of popular web programming languages, such as Python or PHP, albeit statically typed. We will discuss an implementation within the former in the next section.

The grammar of  $\lambda_P$  is defined in Figure 5. The typing rules P-T- are defined in Figure 6 and a big-step semantics is defined by the rules P-E- in Figure 7. The semantics are straightforward given the discussion of the corresponding operations in the previous section.

$\boxed{\Theta \vdash \iota : \tau} \quad \Theta ::= \emptyset \mid \Theta, x : \tau$	
$\frac{\text{P-T-VAR} \quad x : \tau \in \Theta}{\Theta \vdash x : \tau}$	$\frac{\text{P-T-ABS} \quad \Theta, x : \tau_1 \vdash \iota_2 : \tau_2}{\Theta \vdash \lambda x. \iota_2 : \tau_1 \rightarrow \tau_2}$
$\frac{\text{P-T-APP} \quad \Theta \vdash \iota_1 : \tau_2 \rightarrow \tau \quad \Theta \vdash \iota_2 : \tau_2}{\Theta \vdash \iota_1(\iota_2) : \tau}$	$\frac{\text{P-T-STRING}}{\Theta \vdash \text{str}[s] : \text{string}}$
$\frac{\text{P-T-REGEX}}{\Theta \vdash \text{rx}[r] : \text{regex}}$	$\frac{\text{P-T-CONCAT} \quad \Theta \vdash \iota_1 : \text{string} \quad \Theta \vdash \iota_2 : \text{string}}{\Theta \vdash \text{concat}(\iota_1; \iota_2) : \text{string}}$
$\frac{\text{P-T-CASE} \quad \Theta \vdash \iota_1 : \text{string} \quad \Theta \vdash \iota_2 : \tau \quad \Theta, x : \text{string}, y : \text{string} \vdash \iota_3 : \tau}{\Theta \vdash \text{strcase}(\iota_1; \iota_2; x, y. \iota_3) : \tau}$	
$\frac{\text{P-T-REPLACE} \quad \Theta \vdash \iota_1 : \text{regex} \quad \Theta \vdash \iota_2 : \text{string} \quad \Theta \vdash \iota_3 : \text{string}}{\Theta \vdash \text{replace}(\iota_1; \iota_2; \iota_3) : \text{string}}$	
$\frac{\text{P-T-CHECK} \quad \Theta \vdash \iota_r : \text{regex} \quad \Theta \vdash \iota_1 : \text{string} \quad \Theta \vdash \iota_2 : \sigma \quad \Theta \vdash \iota_3 : \sigma}{\Theta \vdash \text{check}(\iota_r; \iota_1; \iota_2; \iota_3) : \sigma}$	

**Figure 6: Typing rules for  $\lambda_P$ . The typing context  $\Theta$  is standard.**

### 2.2.1 Safety

Type safety for  $\lambda_P$  is straight-forward, but is necessary in order to establish the correctness of our translation. Again, we elide a more careful treatment by treating a special case where our language terminates per the discussion above.

**Theorem 13** (Safety for  $\lambda_P$ ). *If  $\emptyset \vdash \iota : \tau$  then  $\iota \Downarrow \dot{v}$  and  $\Theta \vdash \dot{v} : \tau$ .*

We can also define canonical forms for regular expressions and strings in the usual way:

**Lemma 14** (Canonical Forms for Target Language).

1. If  $\emptyset \vdash \iota : \text{regex}$  then  $\iota \Downarrow \text{rx}[r]$  such that  $r$  is a well-formed regular expression.
2. If  $\emptyset \vdash \iota : \text{string}$  then  $\iota \Downarrow \text{str}[s]$ .

## 2.3 Translation from $\lambda_{RS}$ to $\lambda_P$

The translation from  $\lambda_{RS}$  to  $\lambda_P$  is defined in Figure 8. The coercion cases are most interesting. If the safety of coercion is manifest in the types of the expressions, then no runtime check is inserted. If the safety of coercion is not manifest in the types, then a check is inserted. Note that regular strings translate to strings directly; there is no space overhead.

The translation correctness theorem guarantees that the translation is type preserving and that semantics of the original code and translation coincide, following the treatment of compilation pioneered by the TIL compiler for SML [14]. We apply the translation inline in judgements for concision when convenient.

**Theorem 15** (Translation Correctness). *If  $\Theta \vdash e : \sigma$  then there exists an  $\iota$  such that  $\llbracket e \rrbracket = \iota$  and  $\llbracket \Theta \rrbracket \vdash \iota : \llbracket \sigma \rrbracket$ . Furthermore,  $e \Downarrow v$  and  $\iota \Downarrow \dot{v}$  such that  $\llbracket v \rrbracket = \dot{v}$ .*

$\boxed{\iota \Downarrow \dot{v}}$	
$\frac{\text{P-E-ABS}}{\lambda x. e \Downarrow \lambda x. e}$	$\frac{\text{P-E-APP} \quad \iota_1 \Downarrow \lambda x. \iota_3 \quad \iota_2 \Downarrow \dot{v}_2 \quad [\dot{v}_2/x] \iota_3 \Downarrow \dot{v}_3}{\iota_1(\iota_2) \Downarrow \dot{v}_3}$
$\frac{\text{P-E-STR}}{\text{str}[s] \Downarrow \text{str}[s]}$	$\frac{\text{P-E-RX} \quad \text{rx}[r] \Downarrow \text{rx}[r]}{\text{rx}[r] \Downarrow \text{rx}[r]}$
$\frac{\text{P-E-CONCAT} \quad \iota_1 \Downarrow \text{str}[s_1] \quad \iota_2 \Downarrow \text{str}[s_2]}{\text{concat}(\iota_1; \iota_2) \Downarrow \text{str}[s_1 s_2]}$	
$\frac{\text{P-E-CASE-}\epsilon \quad \iota_1 \Downarrow \text{str}[\epsilon] \quad \iota_2 \Downarrow \dot{v}_2}{\text{strcase}(\iota_1; \iota_2; x, y. \iota_3) \Downarrow \dot{v}_2}$	
$\frac{\text{P-E-CASE-CONCAT} \quad \iota_1 \Downarrow \text{str}[a.s] \quad [\text{str}[a], \text{str}[s]/x, y] \iota_3 \Downarrow \dot{v}}{\text{strcase}(\iota_1; \iota_2; x, y. \iota_3) \Downarrow \dot{v}}$	
$\frac{\text{P-E-REPLACE} \quad \iota_1 \Downarrow \text{rx}[r] \quad \iota_2 \Downarrow \text{str}[s_2] \quad \iota_3 \Downarrow \text{str}[s_3] \quad \text{subst}(r; s_2; s_3) = s}{\text{replace}(\iota_1; \iota_2; \iota_3) \Downarrow \text{str}[s]}$	
$\frac{\text{P-E-CHECK-OK} \quad \iota_r \Downarrow \text{rx}[r] \quad \iota \Downarrow \text{str}[s] \quad s \in \mathcal{L}\{r\} \quad \iota_1 \Downarrow \dot{v}_1}{\text{check}(\iota_r; \iota; \iota_1; \iota_2) \Downarrow \dot{v}_1}$	
$\frac{\text{P-E-CHECK-NOTOK} \quad \iota_r \Downarrow \text{rx}[r] \quad \iota \Downarrow \text{str}[s] \quad s \notin \mathcal{L}\{r\} \quad \iota_2 \Downarrow \dot{v}_2}{\text{check}(\iota_r; \iota; \iota_1; \iota_2) \Downarrow \dot{v}_2}$	

**Figure 7: Big step semantics for  $\lambda_P$**

*Proof Sketch.* The proof proceeds by induction on the typing relation for  $e$ . We choose an  $\iota$  based on the syntactic form in  $\lambda_P$  corresponding to the form under consideration (e.g. we choose `replace` when considering `sreplace`). The proof proceeds by our type safety theorems and an appeal to the induction hypothesis.  $\square$

### 2.3.1 Preservation of Security

Finally, our main result establishes that correctness of  $\lambda_{RS}$  is preserved under the translation into  $\lambda_P$ .

**Theorem 16** (Correctness of Input Sanitation for Translated Terms). *If  $\llbracket e \rrbracket = \iota$  and  $\emptyset \vdash e : \text{stringin}[r]$  then  $\iota \Downarrow \text{str}[s]$  for  $s \in \mathcal{L}\{r\}$ .*

*Proof.* By Theorem 15,  $\iota \Downarrow \text{str}[s]$  implies that  $e \Downarrow \text{rstr}[s]$ . By Theorem 12, the above property together with the assumption that  $e$  is well-typed implies that  $s \in \mathcal{L}\{r\}$ .  $\square$

## 3. IMPLEMENTATION IN ATLANG

In the previous section, we specified a type system and a translation semantics to a language containing only strings and regular expressions. In this section, we take Python to be such a target language. Python does not have a static type system, however, so to implement these semantics, we will use `atlang`, an extensible type system for Python (being developed by the authors). By using `atlang`, which leverages Python's quotations and reflection facilities, we can implement these semantics as a library, rather than as a new dialect of the language.



$\llbracket \sigma \rrbracket = \tau$		
$\frac{\text{TR-T-STRING}}{\llbracket \text{stringin}[r] \rrbracket = \text{string}}$	$\frac{\text{TR-T-ARROW} \quad \llbracket \sigma_1 \rrbracket = \tau_1 \quad \llbracket \sigma_2 \rrbracket = \tau_2}{\llbracket \sigma_1 \rightarrow \sigma_2 \rrbracket = \tau_1 \rightarrow \tau_2}$	
$\llbracket \Psi \rrbracket = \Theta$		
$\frac{\text{TR-T-CONTEXT-EMP}}{\llbracket \emptyset \rrbracket = \emptyset}$	$\frac{\text{TR-T-CONTEXT-EXT} \quad \llbracket \Psi \rrbracket = \Theta \quad \llbracket \sigma \rrbracket = \tau}{\llbracket \Psi, x : \sigma \rrbracket = \Theta, x : \tau}$	
$\llbracket e \rrbracket = \iota$		
$\frac{\text{TR-VAR}}{\llbracket x \rrbracket = x}$	$\frac{\text{TR-ABS} \quad \llbracket e \rrbracket = \iota}{\llbracket \lambda x. e \rrbracket = \lambda x. \iota}$	$\frac{\text{TR-APP} \quad \llbracket e_1 \rrbracket = \iota_1 \quad \llbracket e_2 \rrbracket = \iota_2}{\llbracket e_1(e_2) \rrbracket = \iota_1(\iota_2)}$
$\frac{\text{TR-STRING}}{\llbracket \text{rstr}[s] \rrbracket = \text{str}[s]}$	$\frac{\text{TR-CONCAT} \quad \llbracket e_1 \rrbracket = \iota_1 \quad \llbracket e_2 \rrbracket = \iota_2}{\llbracket \text{rconcat}(e_1; e_2) \rrbracket = \text{concat}(\iota_1; \iota_2)}$	
$\frac{\text{TR-CASE} \quad \llbracket e_1 \rrbracket = \iota_1 \quad \llbracket e_2 \rrbracket = \iota_2 \quad \llbracket e_3 \rrbracket = \iota_3}{\llbracket \text{rstrcase}(e_1; e_2; x, y. e_3) \rrbracket = \text{strcase}(\iota_1; \iota_2; x, y. \iota_3)}$		
$\frac{\text{TR-SUBST} \quad \llbracket e_1 \rrbracket = \iota_1 \quad \llbracket e_2 \rrbracket = \iota_2}{\llbracket \text{rreplace}[r](e_1; e_2) \rrbracket = \text{replace}(\text{rx}[r]; \iota_1; \iota_2)}$	$\frac{\text{TR-SAFECOERCE} \quad \llbracket e \rrbracket = \iota}{\llbracket \text{rcoerce}[r'](e) \rrbracket = \iota}$	
$\frac{\text{TR-CHECK} \quad \llbracket e \rrbracket = \iota \quad \llbracket e_1 \rrbracket = \iota_1 \quad \llbracket e_2 \rrbracket = \iota_2}{\llbracket \text{rcheck}[r](e; x. e_1; e_2) \rrbracket = \text{check}(\text{rx}[r]; \iota; (\lambda x. \iota_1)(\iota_2)}$		

Figure 8: Translation from source terms ( $e$ ) to target terms ( $\iota$ ).

### 3.1 Example Usage

Figure 9 demonstrates the use of two type constructors, `fn` and `stringin`, corresponding to the two type constructors of  $\lambda_{RS}$ . We show these as being imported from `atlib`, the standard library for `atlang` (it benefits from no special support from the language itself).

The `fn` type constructor can be used to annotate functions that should be statically checked by `atlang`.<sup>2</sup> The function `sanitize` on lines 3-7, for example, specifies one argument, `s`, of type `stringin[r'.*']`. Here, the index is a regular expression, written using Python’s *raw string notation* as is conventional (in this particular instance, the `r` is not strictly necessary). The `sanitize` function takes an arbitrary string and returns a string without double quotes or left and right brackets. Note that the return type need not be specified: `atlang` uses a form of *local type inference* [12].

In this example, we use an HTML encoding so that the same sanitization function can be used to generate both SQL commands and HTML securely. The sanitized string is generated by invoking the `replace` operator, which has the same semantics as `rreplace` in  $\lambda_{RS}$ . Unlike in the core calculus, it is invoked like a method on `s`. The regular expression determining the substrings to be replaced is given as the first argument (as in  $\lambda_{RS}$ , the only restriction here is that the

<sup>2</sup>Here, we use argument annotation syntax only available in versions 3.0+ of Python. Alternative syntax supporting Python 2.7+ can also be used, but we omit it here.

```

1  from atlib import fn, stringin
2
3  @fn
4  def sanitize(s : stringin[r'.*']):
5      return (s.replace(r'"', '&quot;')
6              .replace(r'<', '&lt;')
7              .replace(r'>', '&gt;'))
8
9  @fn
10 def results_query(s : stringin[r'^.*']):
11     return 'SELECT * FROM users WHERE name=' + s + ''
12
13 @fn
14 def results_div(s : stringin[r'^.*']):
15     return '<div>Results for ' + s + '</div>'
16
17 @fn
18 def main():
19     input = sanitize(user_input())
20     results = db_execute(results_query(input))
21     return results_div(input) + format(results)

```

Figure 9: Regular string types in `atlang`, a library that enables static type checking for Python.

```

1  import re
2
3  def sanitize(s):
4      return re.sub(r'"', re.sub(r'<', re.sub(r'>',
5          s, '&gt;'), '&lt;'), '&quot;')
6
7  def results_query(s):
8      return 'SELECT * FROM users WHERE name=' + s + ''
9
10 def results_div(s):
11     return '<div>Results for ' + s + '</div>'
12
13 def main():
14     input = sanitize(user_input())
15     results = db_execute(results_query(input))
16     return results_div(input) + format(results)

```

Figure 10: The output of compilation of Figure 9 (at the terminal, atc `figure9.py`, or just-in-time).

regular expression must be specified statically.)

The functions `results_query` and `results_div` construct a SQL query and an HTML snippet, respectively, by regular string concatenation. The argument type annotations serve as a check that sanitation was properly performed. In the case of `results_query`, this specification ensures that user input cannot prematurely be terminated. In the case of `results_div`, this specification ensures that user input does not contain any HTML tags, which is a conservative but effective policy for preventing XSS attacks. Note that the type of the surrounding string literals are determined by the type constructor of the function they appear in, `fn` in both cases, which we assume simply chooses `stringin[r'.*']` (an alternative strategy would be to use the most specific type for the literal, rather than the most general, but this choice is immaterial for this example). The addition operator here corresponds to the `rconcat` operator in  $\lambda_{RS}$ .

The `main` function invokes the functions just described. It begins by passing user input to `sanitize`, then executing a database query and returning HTML based on this sanitized input. The helper functions `user_input` and `db_execute` are not shown but can be assumed standard. Importantly, had we mistakenly forgotten to call `sanitize`, the function would not type check (in this case, it is obvious that we did, but lines 19 and 20 would in practice be separated more drastically in the code). Moreover, had `sanitize` itself not been implemented correctly (e.g. we forgot to strip out quotation

```

1 class stringin(atlang.Type):
2     def __init__(self, rx):
3         atlang.Type.__init__(idx=rx)
4
5     def ana_Str(self, ctx, node):
6         if not in_lang(node.s, self.idx):
7             raise atlang.TypeError("...", node)
8
9     def trans_Str(self, ctx, node):
10        return astx.copy(node)
11
12    def syn_BinOp_Add(self, ctx, node):
13        left_t = ctx.syn(node.left)
14        right_t = ctx.syn(node.right)
15        if isinstance(left_t, stringin):
16            left_rx = left_t.idx
17            if isinstance(right_t, stringin):
18                right_rx = right_t.idx
19                return stringin[lconcat(left_rx, right_rx)]
20            raise atlang.TypeError("...", node)
21
22    def trans_BinOp_Add(self, ctx, node):
23        return astx.copy(node)
24
25    def syn_Method_replace(self, ctx, node):
26        [rx, exp] = node.args
27        if not isinstance(rx, ast.Str):
28            raise atlang.TypeError("...", node)
29        rx = rx.s
30        exp_t = ctx.syn(exp)
31        if not isinstance(exp_t, stringin):
32            raise atlang.TypeError("...", node)
33        exp_rx = exp_t.idx
34        return stringin[lreplace(self.idx, rx, exp_rx)]
35
36    def trans_Method_replace(self, ctx, node):
37        return astx.quote(
38            """__import__(re; re.sub(%0, %1, %2)""",
39            astx.Str(s=node.args[0]),
40            astx.copy(node.func.value),
41            astx.copy(node.args[1]))
42
43    # check and strcase omitted
44
45    def check_Coerce(self, ctx, node, other_t):
46        # coercions can only be defined between
47        # types with the same type constructor,
48        if rx_sublang(other_t.idx, self.idx):
49            return other_t
50        else: raise atlang.TypeError("...", node)

```

Figure 11: Implementation of the `stringin` type constructor in `atlang`.

marks), then `main` would also not typecheck either.

One somewhat subtle issue here is that the return type of `sanitize` is equivalent to `stringin[r'[^"<>]*']`, which is a distinct type from the argument types to `results_query` and `results_div`. More specifically, however, it is a “smaller” type, in that it could be coerced to these argument types using an operator like `rcoerce` in  $\lambda_{RS}$ . In our implementation, safe coercions are performed implicitly rather than explicitly. Because all regular strings are implemented as strings, this coercion induces no run-time change in representation.

Figure 10 shows the output of typechecking and translating this code (this can occur either in batch mode at the terminal, generating a new file, or “just-in-time” at the first callsite of each function in the dynamically typed portion of the program, not shown).

### 3.2 Implementation

The primary unit of extension in `atlang` is the *active type constructor*, rather than the abstract syntax as in other work on language extensibility. This allows us to implement the entire system as a library in Python and avoid needing to de-

velop new tooling, and also makes it more difficult to create ambiguities between extensions. Active type constructors are subclasses of `atlang.Type`, and types are instances of these classes. The methods of active type constructors control how typechecking and translation proceed for associated operations. In Figure 11, we show key portions of the implementation of the `stringin` type used in the example above. Although a detailed description of the extension mechanism is beyond the scope of this work, we describe the intuitions behind the various methods below.

The constructor, `__init__` in Python, is called when a type is constructed. It simply stores the provided regular expression as the type index by calling the superclass.

When a string literal is being checked against a regular string type, the method `ana_Str` is called. It checks that the string is in the language of the regular expression provided as the type index, corresponding to rule S-T-STRINGIN-I in Section 2. The method `trans_Str` is called after typechecking to produce a translation. Here, we just copy the original string literal – regular strings are implemented as strings.

The method `syn_BinOp_Add` synthesizes a type for the string concatenation operation if both arguments are regular strings, consistent with rule S-T-CONCAT. The corresponding method `trans_BinOp_Add` again simply translates the operation directly to string concatenation, consistent with our translation semantics.

The method `syn_Method_replace` synthesizes a type for the “method-like” operator `replace`, seen used in our example. It ensures that the first argument is a statically known string, using Python’s built-in `ast` module, and leverages an implementation of `lreplace`, which computes the appropriate regular expression for the string following replacement, again consistent with our description in Section 2. Translation proceeds by using the `re` library built into Python, as can be seen in Figure 10.

Code for checked conversions and string decomposition is omitted, but is again consistent with our specification in the previous section. Safe coercions are controlled by the `check_Coerce` function, which checks for a sublanguage relationship. Here, as in the other methods, failure is indicated by raising an `atlang.TypeError` with an appropriate error message and location.

Taken together, we see that the mechanics of extending `atlang` with a new type constructor are fairly straightforward: we determine which syntactic forms the operators we specified in our core calculus should correspond to, then directly implement a decision procedure for type synthesis (or, in the case of literal forms, type analysis) in Python. The `atlang` compiler invokes this logic when working with regular strings. The result is a library-based embedding of our semantics into Python.

## 4. RELATED WORK

The input sanitation problem is well-understood. There exist a large number of techniques and technologies, proposed by both practitioners and researchers, for preventing injection-style attacks. In this section, we explain how our approach to the input sanitation problem differs from each of these approaches. More important than these differences, however, is our more general assertion that language extensibility is a promising approach toward consideration of security goals in programming language design.

Unlike *frameworks and libraries* provided by languages

such as Haskell and Ruby, our type system provides a *static* guarantee that input is always properly sanitized before use. Doing so requires reasoning about the operations on regular languages corresponding to standard operations on strings; we are unaware of any production system which contains this form of reasoning. Therefore, even where frameworks and libraries provide a viable interface or wrapper around input sanitation, our approach is complementary because it ensures the correctness of the framework or library itself. Furthermore, our approach is more general than database abstraction layers because our mechanism is applicable to all forms of command injection (e.g. shell injection or remote file inclusion).

A number of research languages provide static guarantees that a program is free of input sanitation vulnerabilities [3]. Unlike this work, our solution to the input sanitation problem has a very low barrier to adoption; for instance, our implementation conservatively extends Python – a popular language among web developers. We also believe our general approach is better-positioned for security, where continuously evolving threats might require frequent addition of new analyses; in these cases, the composability and generality of our approach is a substantial advantage.

The Wyvern programming language provides a general framework for composing language extensions [9]. Our work identifies one particular extension, and is therefore complementary to Wyvern and related work on extensible programming languages. We are also unaware of any extensible programming languages which emphasize applications to security concerns.

Incorporating regular expressions into the type system is not novel. The XDuce system [8] checks XML documents against schema using regular expressions. Similarly, XHaskell [13] focuses on XML documents. We differ from this and related work in at least three ways:

- Our system is defined within an extensible type system.
- We demonstrate that regular expression types are applicable to the web security domain, whereas previous work on regular expression types focused on XML schema.
- Although our static replacement operation is definable in some languages with regular expression types, we are the first to expose this operation and connect the semantics of regular language replacement with the semantics of string substitution via a type safety and compilation correctness argument.

In conclusion, our contribution is a type system, implemented within an extensible type system, for checking the correctness of input sanitation algorithms.

## 5. FUTURE WORK

We believe that this type system extension serves as a useful basis for web-oriented static analysis; frameworks and regular expression libraries could be annotated, along with use-sites. We also believe that extensible programming languages are a promising approach toward incorporating other security and privacy analyses into programming languages.

## 6. CONCLUSION

Composable analyses which complement existing approaches constitute a promising approach toward the integration of security concerns into programming languages. In this paper, we presented a system with both of these properties and defined a security-preserving transformation. Unlike other approaches, our solution complements existing, familiar solutions while providing a strong guarantee that traditional library and framework-based approaches are implemented and utilized correctly.

## 7. ACKNOWLEDGEMENTS

[funding sources](#)

## 8. REFERENCES

- [1] D. Ancona. How to prove type soundness of java-like languages without forgoing big-step semantics. In *Proceedings of 16th Workshop on Formal Techniques for Java-like Programs, FTfJP'14*, pages 1:1–1:6, New York, NY, USA, 2014. ACM.
- [2] J. A. Brzozowski. Derivatives of regular expressions. *J. ACM*, 11(4):481–494, Oct. 1964.
- [3] A. Chlipala. Static checking of dynamically-varying security policies in database-backed applications. In *OSDI'10*, Oct. 2010.
- [4] N. Fulton. Security through extensible type systems. *SPLASH '12*, pages 107–108, New York, NY, USA, 2012. ACM.
- [5] N. Fulton. A typed lambda calculus for input sanitation. Undergraduate thesis in mathematics, Carthage College, 2013.
- [6] R. Harper. *Practical Foundations for Programming Languages*. Cambridge University Press, 2012.
- [7] J. E. Hopcroft and J. D. Ullman. *Introduction to Automata Theory, Languages, and Computation*. Addison-Wesley, 1979.
- [8] H. Hosoya, J. Vouillon, and B. C. Pierce. Regular Expression Types for XML. In *ICFP '00*, 2000.
- [9] C. Omar, D. Kurilova, L. Nistor, B. Chung, A. Potanin, and J. Aldrich. Safely composable type-specific languages. In *ECOOP 2014*, volume 8586 of *Lecture Notes in Computer Science*, pages 105–130. Springer Berlin Heidelberg, 2014.
- [10] OWASP. Open web application security project top 10.
- [11] S. Owens, J. Reppy, and A. Turon. Regular-expression derivatives re-examined. *J. Funct. Program.*, Mar. 2009.
- [12] B. C. Pierce and D. N. Turner. Local type inference. *ACM Trans. Program. Lang. Syst.*, 22(1):1–44, Jan. 2000.
- [13] M. Sulzmann and K. Lu. Xhaskell – adding regular expression types to haskell. In *Implementation and Application of Functional Languages*, volume 5083 of *Lecture Notes in Computer Science*, pages 75–92. Springer Berlin Heidelberg, 2008.
- [14] D. Tarditi, G. Morrisett, P. Cheng, C. Stone, R. Harper, and P. Lee. TIL: A type-directed optimizing compiler for ML. In *PLDI '96*, Philadelphia, PA, May 1996.