```
nano test.sh
#!/bin/bash
echo "First argument: $1"
echo "Second argument: $2"
chmod +x test.sh
./test.sh MCA Lab
```

```
name=Mukund
echo $name
a=20
b=30
echo $((a * b))
```

<u>SPECIAL VARIABLES:-</u>

```
nano test.sh
#!/bin/bash
echo "Script name is $0"
chmod +x test.sh
./test.sh
```

(OR)

```
#!/bin/bash
echo "First argument: $1"
echo "Second argument: $2"
./test.sh MCA Lab
```

(OR)

```
#!/bin/bash
echo "Total arguments: $#"
./test.sh A B C
```

(OR)

```
#!/bin/bash
echo "All arguments: $@"
./test.sh MCA Lab 2026
echo "Process ID is $$"(PROCESS ID)

ls
echo $?   (EXIT STATUS 0 OR 1+)
```

OPERATORS:-

```
a=10
b=5
echo $((a + b))
echo $((a - b))
echo $((a * b))
echo $((a / b))
echo $((a % b))
```

(OR)

```
a=10
b=20

if [ $a -lt $b ]
then
```

```
  echo "a is less than b"
fi
```

```
a=10
b=20

if [ $a -lt 15 ] && [ $b -gt 15 ]
then
  echo "Condition True"
fi
```

🔷 3️⃣ Logical Operators

Used to combine conditions.

Operator	Meaning
&&	AND
`	
!	NOT

🔷 2️⃣ Relational Operators (Used in if)

Used to compare numbers.

Operator	Meaning
`-eq`	Equal
`-ne`	Not equal
`-gt`	Greater than
`-lt`	Less than
`-ge`	Greater or equal
`-le`	Less or equal

🔷 4️⃣ String Operators

Used to compare strings.

Operator	Meaning
`=`	Equal
`!=`	Not equal
`-z`	String empty
`-n`	String not empty

✅ **Example:**

```
name="Mukund"

if [ $name = "Mukund" ]
then
  echo "Name matched"
fi
```

🔷 5️⃣ File Test Operators

Used to check file properties.

Operator	Meaning
`-f`	Regular file exists
`-d`	Directory exists
`-r`	Read permission
`-w`	Write permission
`-x`	Execute permission
`-s`	File not empty

```
if [ -f test.txt ]
then
  echo "File exists"
fi
```

💥 Complete Mini Program Example

```bash
#!/bin/bash

echo "Enter two numbers:"
read a b

if [ $a -gt $b ]
then
    echo "$a is greater"
else
    echo "$b is greater"
fi
```

#!/bin/bash

echo "Enter two numbers:"

read a b

if [$a -gt $b]

then

echo "$a is greater"

else

echo "$b is greater"

fi