

[Home](#)[Data Structure](#)[C](#)[C++](#)[C#](#)[Java](#)[SQL](#)[HTML](#)[CSS](#)[JavaScript](#)[Ajax](#)[↑ SCROLL TO TOP](#)

Tree traversal (Inorder, Preorder and Postorder)

In this article, we will discuss the tree traversal in the data structure. The term 'tree traversal' means traversing or visiting each node of a tree. There is a single way to traverse the linear data structure such as linked list, queue, and stack. Whereas, there are multiple ways to traverse a tree that are listed as follows -

- Preorder traversal
- Inorder traversal
- Postorder traversal

So, in this article, we will discuss the above-listed techniques of traversing a tree. Now, let's start discussing the ways of tree traversal.

Preorder traversal

This technique follows the 'root left right' policy. It means that, first root node is visited after that the left subtree is traversed recursively, and finally, right subtree is recursively traversed. As the root node is traversed before (or pre) the left and right subtree, it is called preorder traversal.

So, in a preorder traversal, each node is visited before both of its subtrees.

The applications of preorder traversal include -

- It is used to create a copy of the tree.
- It can also be used to get the prefix expression of an expression tree.

Algorithm

Until all nodes of the tree are not visited

Step 1 - Visit the root node


Step 2 - Traverse the left subtree recursively.

Step 3 - Traverse the right subtree recursively.

Example

↑ SCROLL TO TOP

Example of the preorder traversal technique.



Now, start applying the preorder traversal on the above tree. First, we traverse the root node **A**; after that, move to its left subtree **B**, which will also be traversed in preorder.

So, for left subtree B, first, the root node **B** is traversed itself; after that, its left subtree **D** is traversed. Since node **D** does not have any children, move to right subtree **E**. As node E also does not have any children, the traversal of the left subtree of root node A is completed.

Now, move towards the right subtree of root node A that is C. So, for right subtree C, first the root node **C** has traversed itself; after that, its left subtree **F** is traversed. Since node **F** does not have any children, move to the right subtree **G**. As node G also does not have any children, traversal of the right subtree of root node A is completed.

Therefore, all the nodes of the tree are traversed. So, the output of the preorder traversal of the above tree is -

A → B → D → E → C → F → G

To know more about the preorder traversal in the data structure, you can follow the link [Preorder traversal](#).

Postorder traversal

This technique follows the 'left-right root' policy. It means that the first left subtree of the root node is traversed, after that recursively traverses the right subtree, and finally, the root node is traversed. As the root node is traversed after (or post) the left and right subtree, it is called postorder traversal.

So, in a postorder traversal, each node is visited after both of its subtrees.

↑ SCROLL TO TOP

Postorder traversal include -

- It is used to delete the tree.
- It can also be used to get the postfix expression of an expression tree.

Algorithm

Until all nodes of the tree are not visited


Step 1 - Traverse the left subtree recursively.

Step 2 - Traverse the right subtree recursively.

Step 3 - Visit the root node.

Example

Now, let's see the example of the postorder traversal technique.



Now, start applying the postorder traversal on the above tree. First, we traverse the left subtree B that will be traversed in postorder. After that, we will traverse the right subtree C in postorder. And finally, the root node of the above tree, i.e., A, is traversed.

So, for left subtree B, first, its left subtree D is traversed. Since node D does not have any children, traverse the right subtree E. As node E also does not have any children, move to the root node B. After traversing node B, the traversal of the left subtree of root node A is completed.

Now, move towards the right subtree of root node A that is C. So, for right subtree C, first its left subtree F is traversed. Since node F does not have any children, traverse the right subtree G. As node G also does not have any children, therefore, finally, the root node of the right subtree of root node A is completed.

↑ SCROLL TO TOP

At last, traverse the root node of a given tree, i.e., **A**. After traversing the root node, the postorder traversal of the given tree is completed.

Therefore, all the nodes of the tree are traversed. So, the output of the postorder traversal of the above tree is -

D → E → B → F → G → C → A

To know more about the postorder traversal in the data structure, you can follow the link [Postorder traversal](#).

Inorder traversal

This technique follows the 'left root right' policy. It means that first left subtree is visited after that root node is traversed, and finally, the right subtree is traversed. As the root node is traversed between the left and right subtree, it is named inorder traversal.

So, in the inorder traversal, each node is visited in between of its subtrees.

The applications of Inorder traversal includes -

- It is used to get the BST nodes in increasing order.
- It can also be used to get the prefix expression of an expression tree.

Algorithm

Until all nodes of the tree are not visited


Step 1 - Traverse the left subtree recursively.

Step 2 - Visit the root node.

Step 3 - Traverse the right subtree recursively.

Example

Now, let's see the example of the Inorder traversal technique.



Now, start applying the inorder traversal on the above tree. First, we traverse the left subtree **B** that will be traversed in inorder. After that, we will traverse the root node **A**. And finally, the right subtree **C** is traversed in inorder.

So, for left subtree **B**, first, its left subtree **D** is traversed. Since node **D** does not have any children, so after traversing it, node **B** will be traversed, and at last, right subtree of node B, that is **E**, is traversed. Node E also does not have any children; therefore, the traversal of the left subtree of root node A is completed.

After that, traverse the root node of a given tree, i.e., **A**.

At last, move towards the right subtree of root node A that is C. So, for right subtree C; first, its left subtree **F** is traversed. Since node **F** does not have any children, node **C** will be traversed, and at last, a right subtree of node C, that is, **G**, is traversed. Node G also does not have any children; therefore, the traversal of the right subtree of root node A is completed.

As all the nodes of the tree are traversed, the inorder traversal of the given tree is completed. The output of the inorder traversal of the above tree is -

D → B → E → A → F → C → G

To know more about the inorder traversal in data structure, you can follow the link [Inorder Traversal](#).

Complexity of Tree traversal techniques

The time complexity of tree traversal techniques discussed above is **O(n)**, where '**n**' is the size of binary tree.

↑ SCROLL TO TOP

Whereas the space complexity of tree traversal techniques discussed above is **$O(1)$** if we do not consider the stack size for function calls. Otherwise, the space complexity of these techniques is **$O(h)$** , where 'h' is the tree's height.

Implementation of Tree traversal

Now, let's see the implementation of the above-discussed techniques using different programming languages.

Program: Write a program to implement tree traversal techniques in C.

```
#include <stdio.h>
#include <stdlib.h>

struct node {
    int element;
    struct node* left;
    struct node* right;
};

/*To create a new node*/
struct node* createNode(int val)
{
    struct node* Node = (struct node*)malloc(sizeof(struct node));
    Node->element = val;
    Node->left = NULL;
    Node->right = NULL;

    return (Node);
}

/*function to traverse the nodes of binary tree in preorder*/
void traversePreorder(struct node* root)
{
    if (root == NULL)
        return;

    printf("%d ", root->element);
```

```
    traversePreorder(root->left);
    traversePreorder(root->right);
}

/*function to traverse the nodes of binary tree in Inorder*/
void traverseInorder(struct node* root)
{
    if (root == NULL)
        return;
    traverseInorder(root->left);
    printf(" %d ", root->element);
    traverseInorder(root->right);
}

/*function to traverse the nodes of binary tree in postorder*/
void traversePostorder(struct node* root)
{
    if (root == NULL)
        return;
    traversePostorder(root->left);
    traversePostorder(root->right);
    printf(" %d ", root->element);
}

int main()
{
    struct node* root = createNode(36);
    root->left = createNode(26);
    root->right = createNode(46);
    root->left->left = createNode(21);
    root->left->right = createNode(31);
    root->left->left->left = createNode(11);
    root->right->right = createNode(24);
    root->right->left = createNode(41);
}
```



```
root->right->right = createNode(56);
root->right->right->left = createNode(51);
root->right->right->right = createNode(66);

printf("\n The Preorder traversal of given binary tree is -\n");
traversePreorder(root);

printf("\n The Inorder traversal of given binary tree is -\n");
traverseInorder(root);

printf("\n The Postorder traversal of given binary tree is -\n");
traversePostorder(root);

return 0;
}
```

Output

```
The Preorder traversal of given binary tree is -
36 26 21 11 24 31 46 41 56 51 66
The Inorder traversal of given binary tree is -
11 21 24 26 31 36 41 46 51 56 66
The Postorder traversal of given binary tree is -
11 24 21 31 26 41 51 66 56 46 36
```

Program: Write a program to implement tree traversal techniques in C#.

```
using System;

class Node {
    public int value;
    public Node left, right;

    public Node(int element)
    {
        value = element;
        left = right = null;
    }
}
```

↑ SCROLL TO TOP

```
}
```

```
class BinaryTree {
```

```
    Node root;
```

```
    BinaryTree() { root = null; }
```

```
    void traversePreorder(Node node)
```

```
    {
```

```
        if (node == null)
```

```
            return;
```

```
        Console.Write(node.value + " ");
```

```
        traversePreorder(node.left);
```

```
        traversePreorder(node.right);
```

```
    }
```

```
    void traverseInorder(Node node)
```

```
    {
```

```
        if (node == null)
```

```
            return;
```

```
        traverseInorder(node.left);
```

```
        Console.Write(node.value + " ");
```

```
        traverseInorder(node.right);
```

```
    }
```

```
    void traversePostorder(Node node)
```

```
    {
```

```
        if (node == null)
```

```
            return;
```

```
        traversePostorder(node.left);
```

```
        traversePostorder(node.right);
```

```
        Console.Write(node.value + " ");
```

```
    }
```

```
    void preorder() { traversePreorder(root); }
```

```
    void inorder() { traverseInorder(root); }
```

```
void traversePostorder() { traversePostorder(root); }
```

```
static void Main()
```

```
{  
    BinaryTree bt = new BinaryTree();  
    bt.root = new Node(37);  
    bt.root.left = new Node(27);  
    bt.root.right = new Node(47);  
    bt.root.left.left = new Node(22);  
    bt.root.left.right = new Node(32);  
    bt.root.left.left.left = new Node(12);  
    bt.root.left.left.right = new Node(25);  
    bt.root.right.left = new Node(42);  
    bt.root.right.right = new Node(57);  
    bt.root.right.right.left = new Node(52);  
    bt.root.right.right.right = new Node(67);  
    Console.WriteLine("The Preorder traversal of given binary tree is - ");  
    bt.traversePreorder();  
    Console.WriteLine();  
    Console.WriteLine("The Inorder traversal of given binary tree is - ");  
    bt.traverseInorder();  
    Console.WriteLine();  
    Console.WriteLine("The Postorder traversal of given binary tree is - ");  
    bt.traversePostorder();  
}
```

Output

```
The Preorder traversal of given binary tree is -  
37 27 22 12 25 32 47 42 57 52 67  
The Inorder traversal of given binary tree is -  
12 22 25 27 32 37 42 47 52 57 67  
The Postorder traversal of given binary tree is -  
12 25 22 32 27 42 52 67 57 47 37
```

Program: Write a program to implement tree traversal techniques in C++.

↑ SCROLL TO TOP

```
using namespace std;

struct node {
    int element;
    struct node* left;
    struct node* right;
};

/*To create a new node*/
struct node* createNode(int val)
{
    struct node* Node = (struct node*)malloc(sizeof(struct node));
    Node->element = val;
    Node->left = NULL;
    Node->right = NULL;

    return (Node);
}

/*function to traverse the nodes of binary tree in preorder*/
void traversePreorder(struct node* root)
{
    if (root == NULL)
        return;
    cout<<" "<<root->element<<" ";
    traversePreorder(root->left);
    traversePreorder(root->right);
}

/*function to traverse the nodes of binary tree in Inorder*/
void traverseInorder(struct node* root)
{
    if (root == NULL)
        return;
    traverseInorder(root->left);
    cout<<" "<<root->element<<" ";
    traverseInorder(root->right);
}
```

```

    cout<<" "<<root->element<<" ";
    traverseInorder(root->right);
}

/*function to traverse the nodes of binary tree in postorder*/
void traversePostorder(struct node* root)
{
    if (root == NULL)
        return;
    traversePostorder(root->left);
    traversePostorder(root->right);
    cout<<" "<<root->element<<" ";
}

int main()
{
    struct node* root = createNode(38);
    root->left = createNode(28);
    root->right = createNode(48);
    root->left->left = createNode(23);
    root->left->right = createNode(33);
    root->left->left->left = createNode(13);
    root->left->left->right = createNode(26);
    root->right->left = createNode(43);
    root->right->right = createNode(58);
    root->right->right->left = createNode(53);
    root->right->right->right = createNode(68);
    cout<<"\n The Preorder traversal of given binary tree is -\n";
    traversePreorder(root);

    cout<<"\n The Inorder traversal of given binary tree is -\n";
    traverseInorder(root);

    cout<<"\n The Postorder traversal of given binary tree is -\n";
    traversePostorder(root);
}

```

}

Output

```
The Preorder traversal of given binary tree is -
38 28 23 13 26 33 48 43 58 53 68
The Inorder traversal of given binary tree is -
13 23 26 28 33 38 43 48 53 58 68
The Postorder traversal of given binary tree is -
13 26 23 33 28 43 53 68 58 48 38
```

Program: Write a program to implement tree traversal techniques in Java.

```
class Node {
    public int value;
    public Node left, right;

    public Node(int element)
    {
        value = element;
        left = right = null;
    }
}

class Tree {
    Node root; /* root of the tree */

    Tree() { root = null; }
    /*function to print the nodes of given binary in Preorder*/
    void traversePreorder(Node node)
    {
        if (node == null)
            return;
        System.out.print(node.value + " ");
        traversePreorder(node.left);
        traversePreorder(node.right);
    }
}
```

[↑ SCROLL TO TOP](#)

the nodes of given binary in Inorder*/

```
void traverseInorder(Node node)
{
    if (node == null)
        return;
    traverseInorder(node.left);
    System.out.print(node.value + " ");
    traverseInorder(node.right);
}

/*function to print the nodes of given binary in Postorder*/
void traversePostorder(Node node)
{
    if (node == null)
        return;
    traversePostorder(node.left);
    traversePostorder(node.right);
    System.out.print(node.value + " ");
}

void traversePreorder() { traversePreorder(root); }
void traverseInorder() { traverseInorder(root); }
void traversePostorder() { traversePostorder(root); }

public static void main(String args[])
{
    Tree pt = new Tree();
    pt.root = new Node(36);
    pt.root.left = new Node(26);
    pt.root.right = new Node(46);
    pt.root.left.left = new Node(21);
    pt.root.left.right = new Node(31);
    pt.root.left.left.left = new Node(11);
    pt.root.left.left.right = new Node(24);
    pt.root.right.left = new Node(41);
    pt.root.right.right = new Node(56);
    pt.root.right.right.left = new Node(51);
}
```

```
pt.root.right.right.right = new Node(66);

System.out.println();
System.out.println("The Preorder traversal of given binary tree is - ");
pt.traversePreorder();
System.out.println("\n");
System.out.println("The Inorder traversal of given binary tree is - ");
pt.traverseInorder();
System.out.println("\n");
System.out.println("The Postorder traversal of given binary tree is - ");
pt.traversePostorder();
System.out.println();
}
}
```

Output

After the execution of the above code, the output will be -

```
D:\JTP>javac Tree.java
D:\JTP>java Tree

The Preorder traversal of given binary tree is -
36 26 21 11 24 31 46 41 56 51 66

The Inorder traversal of given binary tree is -
11 21 24 26 31 36 41 46 51 56 66

The Postorder traversal of given binary tree is -
11 24 21 31 26 41 51 66 56 46 36
D:\JTP>_
```

Conclusion

In this article, we have discussed the different types of tree traversal techniques: preorder traversal, inorder traversal, and postorder traversal. We have seen these techniques along with algorithm, example, complexity, and implementation in C, C++, C#, and java.

So, that's all about the article. Hope it will be helpful and informative to you.

 [For Videos Join Our Youtube Channel: Join Now](#)
















Feedback

- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share




Learn Latest Tutorials

 Splunk tutorial Splunk	 SPSS tutorial SPSS	 Swagger tutorial Swagger	 T-SQL tutorial Transact-SQL
 Tumblr tutorial Tumblr	 React tutorial ReactJS	 Regex tutorial Regex	 Reinforcement learning tutorial Reinforcement Learning
 R Programming tutorial R Programming	 RxJS tutorial RxJS	 React Native tutorial React Native	 Python Design Patterns Python Design Patterns
 Python Pillow tutorial Python Pillow	 Python Turtle tutorial Python Turtle	 Keras tutorial Keras	


↑ SCROLL TO TOP



Aptitude
Aptitude



Logical
Reasoning
Reasoning



Verbal Ability
Verbal Ability



Interview
Questions
Interview Questions



Company
Interview
Questions
Company Questions


Trending Technologies



Artificial
Intelligence
Tutorial
Artificial
Intelligence




AWS Tutorial
AWS



Selenium
tutorial
Selenium



Cloud
Computing
tutorial
Cloud Computing



Hadoop tutorial
Hadoop



ReactJS
Tutorial
ReactJS



Data Science
Tutorial
Data Science




Angular 7
Tutorial
Angular 7



Blockchain
Tutorial
Blockchain



Git Tutorial
Git



Machine
Learning Tutorial
Machine Learning




DevOps
Tutorial
DevOps


B.Tech / MCA




DBMS tutorial
DBMS



Data Structures
tutorial
Data Structures



DAA tutorial
DAA



Operating
System tutorial
Operating System

↑ SCROLL TO TOP



Computer
Network tutorial
Computer Network



Compiler
Design tutorial
Compiler Design



Computer
Organization and
Architecture
Computer
Organization



Discrete
Mathematics
Tutorial
Discrete
Mathematics



Ethical Hacking
Tutorial
Ethical Hacking



Computer
Graphics Tutorial
Computer Graphics



Software
Engineering
Tutorial
Software
Engineering



html tutorial
Web Technology



Cyber Security
tutorial
Cyber Security



Automata
Tutorial
Automata



C Language
tutorial
C Programming



C++ tutorial
C++



Java tutorial
Java



.Net
Framework
tutorial
.Net



Python tutorial
Python



List of
Programs
Programs



Control
Systems tutorial
Control System



Data Mining
Tutorial
Data Mining



Data
Warehouse
Tutorial
Data Warehouse