

Home	Data Structure	C	C++	C#	Java	SQL	HTML	CSS	JavaScript	Ajax
------	----------------	---	-----	----	------	-----	------	-----	------------	------

Radix Sort Algorithm

In this article, we will discuss the Radix sort Algorithm. Radix sort is the linear sorting algorithm that is used for integers. In Radix sort, there is digit by digit sorting is performed that is started from the least significant digit to the most significant digit.

The process of radix sort works similar to the sorting of students names, according to the alphabetical order. In this case, there are 26 radix formed due to the 26 alphabets in English. In the first pass, the names of students are grouped according to the ascending order of the first letter of their names. After that, in the second pass, their names are grouped according to the ascending order of the second letter of their name. And the process continues until we find the sorted list.

Now, let's see the algorithm of Radix sort.

Algorithm

```
radixSort(arr)
max = largest element in the given array
d = number of digits in the largest element (or, max)
Now, create d buckets of size 0 - 9
for i -> 0 to d
    sort the array elements using counting sort (or any stable sort) according to the digits at
    the ith place
```

Working of Radix sort Algorithm

Now, let's see the working of Radix sort Algorithm.

The steps used in the sorting of radix sort are listed as follows -

- First, we have to find the largest element (suppose **max**) from the given array. Suppose '**x**' be the number of digits in **max**. The '**x**' is calculated because we need to go through the significant places of all elements.
- After that, go through one by one each significant place. Here, we have to use any stable sorting algorithm to sort the digits of each significant place.

Now let's see the working of radix sort in detail by using an example. To understand it more clearly, let's take an unsorted array and try to sort it using radix sort. It will make the explanation clearer and easier.


181	289	390	121	145	736	514	212
-----	-----	-----	-----	-----	-----	-----	-----

In the given array, the largest element is **736** that have **3** digits in it. So, the loop will run up to three times (i.e., to the **hundreds place**). That means three passes are required to sort the array.

Now, first sort the elements on the basis of unit place digits (i.e., **x = 0**). Here, we are using the counting sort algorithm to sort the elements.

Pass 1:

In the first pass, the list is sorted on the basis of the digits at 0's place.




After the first pass, the array elements are -

390	181	121	212	514	145	736	289
-----	-----	-----	-----	-----	-----	-----	-----

Pass 2:

In this pass, the list is sorted on the basis of the next significant digits (i.e., digits at 10th place).




After the second pass, the array elements are -

212	514	121	736	145	181	289	390
-----	-----	-----	-----	-----	-----	-----	-----

Pass 3:

In this pass, the list is sorted on the basis of the next significant digits (i.e., digits at 100th place).



After the third pass, the array elements are -

121	145	181	212	289	390	514	736
-----	-----	-----	-----	-----	-----	-----	-----

Now, the array is sorted in ascending order.

Radix sort complexity

Now, let's see the time complexity of Radix sort in best case, average case, and worst case. We will also see the space complexity of Radix sort.

1. Time Complexity

Case	Time Complexity
Best Case	$\Omega(n+k)$
Average Case	$\theta(nk)$
Worst Case	$O(nk)$

- **Best Case Complexity** - It occurs when there is no sorting required, i.e. the array is already sorted. The best-case time complexity of Radix sort is **$\Omega(n+k)$** .
- **Average Case Complexity** - It occurs when the array elements are in jumbled order that is not properly ascending and not properly descending. The average case time complexity of Radix sort is **$\theta(nk)$** .
- **Worst Case Complexity** - It occurs when the array elements are required to be sorted in reverse order. That means suppose you have to sort the array elements in ascending order, but its elements are in descending order. The worst-case time complexity of Radix sort is **$O(nk)$** .

Radix sort is a non-comparative sorting algorithm that is better than the comparative sorting algorithms. It has linear time complexity that is better than the comparative algorithms with complexity $O(n \log n)$.

2. Space Complexity

Space Complexity	$O(n + k)$
Stable	YES

- The space complexity of Radix sort is $O(n + k)$.

Implementation of Radix sort

Now, let's see the programs of Radix sort in different programming languages.

Program: Write a program to implement Radix sort in C language.

```
#include <stdio.h>

int getMax(int a[], int n) {
    int max = a[0];
    for(int i = 1; i < n; i++) {
        if(a[i] > max)
            max = a[i];
    }
    return max; //maximum element from the array
}

void countingSort(int a[], int n, int place) // function to implement counting sort
{
    int output[n + 1];
    int count[10] = {0};

    // Calculate count of elements
    for (int i = 0; i < n; i++)
        count[(a[i] / place) % 10]++;

    // Calculate cumulative frequency
    for (int i = 1; i < 10; i++)
        count[i] += count[i - 1];

    // Place the elements in sorted order
    for (int i = n - 1; i >= 0; i--) {
        output[count[(a[i] / place) % 10] - 1] = a[i];
        count[(a[i] / place) % 10]--;
    }
}
```

```
for (int i = 0; i < n; i++)
    a[i] = output[i];
}

// function to implement radix sort
void radixsort(int a[], int n) {

    // get maximum element from array
    int max = getMax(a, n);

    // Apply counting sort to sort elements based on place value
    for (int place = 1; max / place > 0; place *= 10)
        countingSort(a, n, place);
}

// function to print array elements
void printArray(int a[], int n) {
    for (int i = 0; i < n; ++i) {
        printf("%d ", a[i]);
    }
    printf("\n");
}

int main() {
    int a[] = {181, 289, 390, 121, 145, 736, 514, 888, 122};
    int n = sizeof(a) / sizeof(a[0]);
    printf("Before sorting array elements are - \n");
    printArray(a,n);
    radixsort(a, n);
    printf("After applying Radix sort, the array elements are - \n");
    printArray(a, n);
}
```

Output:

After the execution of the above code, the output will be -

```
Before sorting array elements are -  
181 289 390 121 145 736 514 888 122  
After applying Radix sort, the array elements are -  
121 122 145 181 289 390 514 736 888
```

Program: Write a program to implement Radix sort in C++.

```
#include <iostream>  
  
using namespace std;  
  
int getMax(int a[], int n) {  
    int max = a[0];  
    for(int i = 1; i < n; i++) {  
        if(a[i] > max)  
            max = a[i];  
    }  
    return max; //maximum element from the array  
}  
  
void countingSort(int a[], int n, int place) // function to implement counting sort  
{  
    int output[n + 1];  
    int count[10] = {0};  
  
    // Calculate count of elements  
    for (int i = 0; i < n; i++)  
        count[(a[i] / place) % 10]++;  
  
    // Calculate cumulative frequency  
    for (int i = 1; i < 10; i++)  
        count[i] += count[i - 1];  
  
    // Place the elements in sorted order  
    for (int i = n - 1; i >= 0; i--) {
```



```
    output[count[(a[i] / place) % 10] - 1] = a[i];
    count[(a[i] / place) % 10]--;
}

for (int i = 0; i < n; i++)
    a[i] = output[i];
}

// function to implement radix sort
void radixsort(int a[], int n) {

    // get maximum element from array
    int max = getMax(a, n);

    // Apply counting sort to sort elements based on place value
    for (int place = 1; max / place > 0; place *= 10)
        countingSort(a, n, place);
}

// function to print array elements
void printArray(int a[], int n) {
    for (int i = 0; i < n; ++i)
        cout << a[i] << " ";
}

int main() {
    int a[] = {171, 279, 380, 111, 135, 726, 504, 878, 112};
    int n = sizeof(a) / sizeof(a[0]);
    cout << "Before sorting array elements are - \n";
    printArray(a, n);
    radixsort(a, n);
    cout << "\n\nAfter applying Radix sort, the array elements are - \n";
    printArray(a, n);
    return 0;
}
```

Output:

```
Before sorting array elements are -  
171 279 380 111 135 726 504 878 112  
  
After applying Radix sort, the array elements are -  
111 112 135 171 279 380 504 726 878
```

Program: Write a program to implement Radix sort in C#.

```
using System;  
  
class RadixSort {  
  
    static int getMax(int[] a, int n) {  
        int max = a[0];  
        for(int i = 1; i < n; i++) {  
            if(a[i] > max)  
                max = a[i];  
        }  
        return max; //maximum element from the array  
    }  
  
    static void countingSort(int[] a, int n, int place) // function to implement counting sort  
    {  
        int[] output = new int[n+1];  
        int[] count = new int[10];  
  
        // Calculate count of elements  
        for (int i = 0; i < n; i++)  
            count[(a[i] / place) % 10]++;  
  
        // Calculate cumulative frequency  
        for (int i = 1; i < 10; i++)  
            count[i] += count[i - 1];  
  
        // Place the elements in sorted order  
        for (int i = n - 1; i >= 0; i--) {  
            output[count[(a[i] / place) % 10] - 1] = a[i];
```

```
        count[(a[i] / place) % 10]--;
    }

    for (int i = 0; i < n; i++)
        a[i] = output[i];
}

// function to implement radix sort
static void radixsort(int[] a, int n) {

    // get maximum element from array
    int max = getMax(a, n);

    // Apply counting sort to sort elements based on place value
    for (int place = 1; max / place > 0; place *= 10)
        countingSort(a, n, place);
}

// function to print array elements
static void printArray(int[] a, int n) {
    for (int i = 0; i < n; ++i)
        Console.Write(a[i] + " ");
}

static void Main() {
    int[] a = {161, 269, 370, 101, 125, 716, 54, 868, 12};
    int n = a.Length;
    Console.WriteLine("Before sorting array elements are - \n");
    printArray(a,n);
    radixsort(a, n);
    Console.WriteLine("\n\nAfter applying Radix sort, the array elements are - \n");
    printArray(a, n);
}
}
```

Output:

```
Before sorting array elements are -  
161 269 370 101 125 716 54 868 12
```

```
After applying Radix sort, the array elements are -  
12 54 101 125 161 269 370 716 868
```

Program: Write a program to implement Radix sort in Java.

```
class RadixSort {  
  
    int getMax(int a[], int n) {  
        int max = a[0];  
        for(int i = 1; i < n; i++) {  
            if(a[i] > max)  
                max = a[i];  
        }  
        return max; //maximum element from the array  
    }  
  
    void countingSort(int a[], int n, int place) // function to implement counting  
  
    sort  
    {  
        int[] output = new int[n+1];  
        int[] count = new int[10];  
  
        // Calculate count of elements  
        for (int i = 0; i < n; i++)  
            count[(a[i] / place) % 10]++;  
  
        // Calculate cumulative frequency  
        for (int i = 1; i < 10; i++)  
            count[i] += count[i - 1];  
  
        // Place the elements in sorted order  
        for (int i = n - 1; i >= 0; i--) {  
            output[count[(a[i] / place) % 10] - 1] = a[i];  
            count[(a[i] / place) % 10]--;  
        }  
    }  
}
```

```
}

for (int i = 0; i < n; i++)
    a[i] = output[i];
}

// function to implement radix sort
void radixsort(int a[], int n) {

    // get maximum element from array
    int max = getMax(a, n);

    // Apply counting sort to sort elements based on place value
    for (int place = 1; max / place > 0; place *= 10)
        countingSort(a, n, place);
}

// function to print array elements
void printArray(int a[], int n) {
    for (int i = 0; i < n; ++i)
        System.out.print(a[i] + " ");
}

public static void main(String args[]) {
    int a[] = {151, 259, 360, 91, 115, 706, 34, 858, 2};
    int n = a.length;
    RadixSort r1 = new RadixSort();
    System.out.print("Before sorting array elements are - \n");
    r1.printArray(a,n);
    r1.radixsort(a, n);
    System.out.print("\n\nAfter applying Radix sort, the array elements are -

\n");
    r1.printArray(a, n);
}
}
```

Output:

```
D:\JTP>javac RadixSort.java
D:\JTP>java RadixSort
Before sorting array elements are -
151 259 360 91 115 706 34 858 2
After applying Radix sort, the array elements are -
2 34 91 115 151 259 360 706 858
D:\JTP>_
```

So, that's all about the article. Hope the article will be helpful and informative to you.

[← Prev](#)[Next →](#)

 [For Videos Join Our Youtube Channel: Join Now](#)


Feedback


- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share





Learn Latest Tutorials


 [Splunk tutorial](#)
Splunk


 [SPSS tutorial](#)
SPSS

 [Swagger tutorial](#)
Swagger


 [T-SQL tutorial](#)
Transact-SQL

 [Tumblr tutorial](#)
Tumblr


 [React tutorial](#)
ReactJS

 [Regex tutorial](#)
Regex


 [Reinforcement learning tutorial](#)
Reinforcement Learning



R Programming
tutorial
R Programming



RxJS tutorial
RxJS




React Native
tutorial
React Native




Python Design
Patterns
Python Design
Patterns



Python Pillow
tutorial
Python Pillow



Python Turtle
tutorial
Python Turtle




Keras tutorial
Keras


Preparation



Aptitude
Aptitude



Logical
Reasoning
Reasoning



Verbal Ability
Verbal Ability



Interview
Questions
Interview Questions



Company
Interview
Questions
Company Questions


Trending Technologies



Artificial
Intelligence
Tutorial
Artificial
Intelligence




AWS Tutorial
AWS



Selenium
tutorial
Selenium




Cloud
Computing
tutorial
Cloud Computing



Hadoop tutorial
Hadoop



ReactJS
Tutorial
ReactJS



Data Science
Tutorial
Data Science



Angular 7
Tutorial
Angular 7



Blockchain
Tutorial

Blockchain



Git Tutorial
Git



Machine
Learning Tutorial
Machine Learning



DevOps
Tutorial
DevOps

B.Tech / MCA



DBMS tutorial
DBMS



Data Structures
tutorial
Data Structures



DAA tutorial
DAA



Operating
System tutorial
Operating System



Computer
Network tutorial
Computer Network



Compiler
Design tutorial
Compiler Design



Computer
Organization and
Architecture
Computer
Organization



Discrete
Mathematics
Tutorial
Discrete
Mathematics



Ethical Hacking
Tutorial
Ethical Hacking



Computer
Graphics Tutorial
Computer Graphics



Software
Engineering
Tutorial
Software
Engineering



html tutorial
Web Technology



Cyber Security
tutorial
Cyber Security



Automata
Tutorial
Automata



C Language
tutorial
C Programming



C++ tutorial
C++



Java tutorial
Java



.Net
Framework
tutorial
.Net



Python tutorial
Python



List of
Programs
Programs



Control
Systems tutorial
Control System



Data Mining
Tutorial
Data Mining



Data
Warehouse
Tutorial
Data Warehouse

